



GENERAL NOTES:

1. THE FIRST 3' SHOWN AS PAVEMENT SHALL BE PAVED ONLY WHEN ABUTTING A PAVED AREA.
2. ALL RESIDENTIAL OR COMMERCIAL DRIVES 10% AND OVER SHALL BE PAVED.

NOTES ON MAXIMUM DRIVEWAY PROFILES:

1. THESE PROFILES ARE A GUIDE FOR THE MAJORITY OF CASES. BUT SHOULD BE FIELD CHECKED WHEN THE MAIN LINE GRADE IS STEEP (4% TO 6% OR GREATER) OR THE ANGLE OF APPROACH TO THE DRIVE IS UNUSUAL.
2. GENERALLY THE MAJORITY OF DRIVES ON A PROJECT WILL BE BUILT WITH FLATTER PROFILES THAN THESE MAXIMUM CASES.
3. WHEN GRADING DRIVES WHICH ARE FLATTER THAN THE MAXIMUM PROFILES THE FOLLOWING RULE OF THUMB SHOULD BE USED; DO NOT EXCEED A GRADE % CHANGE OF MORE THAN 9% IN A 6 FOOT INCREMENT OF DRIVEWAY LENGTH. THIS APPLIES TO BOTH UP AND DOWN PROFILES.

DRIVES ON NON-SIDEWALK SECTIONS