(10)

E-6

# KNOX MINING CORP.

## DRILL HOLE LOG

Deposit: Area 5
Drill Hole: EDA-6
Logged by: H.M. Parker
Date: 1973
Page 1 of 2

| Deposit | Town | Co. | Lease No. | Hole No = Coordinate | | Collar Elev. | Angle | Azimuth |
|---|---|---|---|---|---|---|---|---|
| | | | | 11618 | 2215 | 2133 | 90 | |

| Depth (1" = 40') | Depth | % Sulfide (visual) | Description | Drill Hole No. | | From | To | Ore Type | % Ni | % Cu | % Co | % Fe | % S | Deposit |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| -8 | 01 | 0 | till | 11618 | 2215 | | | | | | | | | |
| | | 7.6 | | | | | | | | | | | | |
| 8-28 | 021 | | f-mg cumm gab | | | 0 | 13.9 | | 0 | 0 | 0 | 0 | 0 | |
| 28-36 | 022 | 27.5 | m-c eucrite | | | 13.9 | 20.0 | | 0:0.32 | 0:0.44 | 0:0.22 | | | |
| | | 35.5 | mg gab | | | 20 | 21.8 | | 0 | 0 | 0 | 0 | 0 | |
| | | | | | | 21.8 | 24.1 | | 0:0.42 | 0:0.44 | 0:0.14 | | | |
| 36-76 | 023 | | | | | 24.1 | 46 | | 0 | 0 | 0 | 0 | 0 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | 76 | mg hbl gab, peg, sch incls | | | 46.0 | 61.0 | | 0:0.216 | 0:0.115 | 0:0.13 | | 1:018 | |
| 76-111 | 025 | | | | | 61.0 | 76.0 | | 0:0.216 | 0:0.113 | 0:0.13 | | 1:017 | |
| | | 111 | | | | 76 | 115 | | 0 | 0 | 0 | | 0 | |
| | | | m-c g euc gab, peg sch incls | | | | | | | | | | | |
| 111-154 | 025 | | | | | | | | | | | | | |
| | | 154 | | | | | | | | | | | | |
| | | | f,m gab sch incls | | | 115.0 | 126.0 | | 0:0.211 | 0:0.115 | 0:0.08 | | 2:211 | |
| 154-222 | 025 | | | | | 126 | 133 | | 0 | 0 | 0 | | 0 | |
| | | | | | | 133.0 | 141.0 | | 0:0.212 | 0:0.113 | 0:0.11 | | 1:317 | |
| | | | | | | 141 | 199 | | 0 | 0 | 0 | | 0 | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| 222-230 | 09 | 222 | gn incl | | | 199.0 | 207.0 | | 0:0.115 | 0:0.016 | 0:0.10 | | 1:05 | |
| | | 230 | | | | 207.0 | 216.0 | | 0:0.117 | 0:0.018 | 0:0.10 | | 1:18 | |
| | | | f,mg hybrid, sch incls | | | 216 | 222 | | 0 | 0 | 0 | | 0 | |
| 230-283 | 024 | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | 222.0 | 230.0 | | 0:0.117 | 0:0.018 | 0:0.13 | | 1:15 | |
| | | | | | | 230 | 306 | | | | | | | |
| | | | | | | | | | | | | | | |
| | | Footwall 283 | gn | | | | | | | | | | | |
| 283-306 | 09 | | | | | | | | | | | | | |

Depth scale: 20, 40, 60, 80, 100

Drill Hole No. scale: 5, 10, 15, 20, 25, 30, 35, 40, 45, 78, 80

E-6

# KNOX MINING CORP.

## DRILL HOLE LOG

Deposit: Area 5
Drill Hole: EDA-6
Logged by: H.M. Parker
Date: 1973
Page 2 of 2

| Deposit | Town | Co. | Lease No. | Hole No = Coordinate | Collar Elev. | Angle | Azimuth |
|---|---|---|---|---|---|---|---|
| | | | | 116,18 22,15 | 21,33 | 90 | |

Depth (1" = 40') | % Sulfide (visual) 20 40 60 80 100

| Depth | Description | Drill Hole No. | From | To | Ore Type | % Ni | % Cu | % Co | % Fe | % S | Deposit |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 283 | 283-306 plag-bio-graph-gar gn plag-qtz (gar) porphyroblastic seqs, contorted 30-45° fol. | | | | | | | | | | |
| fol. | gn | | | | | | | | | | |
| 306 | bottom | | | | | | | | | | |