

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

After review of the air emissions license renewal application, staff investigation reports and other documents in the applicant's file in the Bureau of Air Quality, pursuant to 38 M.R.S.A., Section 344 and Section 590, the Department finds the following facts:

## **I. REGISTRATION**

### **A. Introduction**

1. Pike Industries, Inc. of Lewiston, Maine has applied to renew their Air Emission License permitting the operation of emission sources associated with their Baldwin, Maine hot mix asphalt (**P705A**), crushed stone and gravel facility.
2. This renewal will also include an amendment to update the facility's equipment inventory to include a previously unlicensed asphalt storage-silo hot oil heater unit.
3. Pike Industries, Inc. has also requested that this license renewal reflect facility fuel limit reductions for the purpose of reducing annual criteria pollutant emissions to below the Department's Chapter 137 applicability thresholds.

### **B. Emission Equipment**

Pike Industries, Inc. is authorized to operate the following equipment:

#### **Asphalt Batch Plant**

<b><u>Equipment</u></b>	<b><u>Production Rate (tons/hr)</u></b>	<b><u>Maximum Capacity (MMBtu/hr)</u></b>	<b><u>Date of Manufacture</u></b>	<b><u>Control Devices</u></b>
Rotary Kiln (P705A)	150	50.0	1984	Baghouse

**Diesel Units**

<b><u>Designation</u></b>	<b><u>Maximum Capacity</u></b>	<b><u>Maximum Firing Rate</u></b>	<b><u>Power Output</u></b>
Diesel #1	7.1 MMBtu/hr	52 gal/hr	680 kW
Diesel #2	3.4 MMBtu/hr	25 gal/hr	320 kW

**Asphalt Storage-silo Hot Oil Heater**

<b><u>Equipment</u></b>	<b><u>Maximum Capacity (MMBtu/hr)</u></b>	<b><u>Fuel Type, % Sulfur</u></b>	<b><u>Maximum Firing Rate (gallon/hour)</u></b>
Silo Heater #1	1.0	#2 Fuel Oil, 0.5%S Spec. Waste Oil, 0.7%S	7.1

**Rock Crushers:**

<b><u>Designation</u></b>	<b><u>Power Source</u></b>	<b><u>Process Rate</u></b>	<b><u>Control Device</u></b>
Primary	Diesel	300 tons/hr	Spray Nozzles
Secondary	Diesel	150 tons/hr	Spray Nozzles
Tertiary	Diesel	140 tons/hr	Spray Nozzles

C. Application Classification

Pike Industries, Inc. is a licensed source with equipment that has not been addressed in the facility's previous air emissions licenses. The license renewal shall include the operation of the previously unlisted equipment. Therefore, the application for Pike Industries, Inc. is considered to be a renewal and an amendment.

**II. BEST PRACTICAL TREATMENT (BPT)**

A. Introduction

In order to receive a license the applicant must control emissions from each unit to a level considered by the Department to represent Best Practical Treatment (BPT), as defined in Chapter 100 of the Department regulations. Separate control requirement categories exist for new and existing equipment as well as for those sources located in designated non-attainment areas.

BPT for existing emissions equipment means that method which controls or reduces emissions to the lowest possible level considering:

- the existing state of technology;
- the effectiveness of available alternatives for reducing emission from the source being considered; and
- the economic feasibility for the type of establishment involved.

#### B. Asphalt Batch Plant

Pike Industries, Inc. operates an asphalt batch plant, designated P705A, for the production of asphalt at their Baldwin, Maine hot mix asphalt, crushed stone and gravel facility. The asphalt batch plant has a maximum designed heat input capacity of 49.6 MMBtu/hr and a maximum design process rate of 150 ton/hr.

The asphalt batch plant was manufactured in 1984 and is therefore subject to EPA New Source Performance Standards (NSPS) Subpart I for Hot Mix Asphalt Facilities. As a requirement of NSPS Subpart I, Pike Industries, Inc. shall perform a performance test in accordance with 40 CFR 60.8 and 40 CFR 60.93.

Pike Industries, Inc. was previously licensed to fire no greater than 300,000 gallons per year (gal/yr) of a combination of #2 fuel oil, with a sulfur content of no greater than 0.5% sulfur by weight, and specification waste oil, with a sulfur content of no greater than 0.7% sulfur by weight, in P705A, based on a twelve-month rolling total. Pike Industries, Inc. has requested a reduction in the fuel restriction, in conjunction with a reduction in the fuel restriction for the diesel units, to reduce the total annual emissions of criteria pollutants for the facility to levels below the Department's Chapter 137 applicability thresholds. Pike Industries, Inc. has requested that the annual fuel restriction for fuel oil fired in asphalt plant P705A be reduced to firing no greater than 250,000 gal/yr of a combination #2 fuel oil with a sulfur content of no greater than 0.5% sulfur by weight, #4 fuel oil with a sulfur content of no greater than 0.7% sulfur by weight and specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight, in P705A, on a calendar year basis.

Pike Industries, Inc. shall maintain a record of fuel use for the asphalt batch plant, which shall include fuel purchase receipts indicating the quantity and sulfur content of the purchased fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis.

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
4

**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

Only waste oil meeting the criteria “specification” waste oil (as defined in the “Waste Oil Management Rules”) may be fired in the asphalt batch plant. Pike Industries, Inc. shall keep the results of a representative waste oil test on site. If the equipment or operations that produce the on-site waste oil change, then a new representative sample shall be tested. The Department may also request additional testing in the future, if deemed necessary.

The asphalt batch plant is subject to both the NSPS and the BPT Particulate matter (PM) emissions standard, however, the BPT standard is more stringent, therefore, only the more stringent PM emission standard of 0.03 gr/dscf shall be included in this license.

To meet requirements of BPT, the asphalt batch plant vents to a baghouse. The performance of the baghouse shall be constantly monitored by either of the following at all times the batch plant is in operation:

1. PM Detector – when the detector signals excessive PM concentrations in the exhaust stream, Pike Industries, Inc. shall take corrective action within 24 hours, or immediately if opacity exceeds 20% based on a 6-minute block average basis.
2. Personnel with an EPA Method 9 visible emissions certification within the past 6 months – when the opacity exceeds 20%, the hot mix asphalt batch plant is operating with insufficient control and Pike Industries, Inc. shall take corrective action immediately.

Pike Industries, Inc. shall establish a system of maintenance, inspection and repair for the asphalt batch plant baghouse, which shall allow for periodic inspection of the system. Pike Industries, Inc. shall document compliance by means of a maintenance, inspection and repair log in which Pike Industries, Inc. shall record the date all bag failures and all routine maintenance as well as all inspection dates and findings.

A summary of the BPT analysis for the Asphalt Plant is as follows.

1. BPT for PM is emissions not to exceed 0.03 gr/dscf. PM<sub>10</sub> emission limits are based on PM limits.
2. For the use of #2, BPT is a sulfur content not to exceed 0.5% sulfur by weight and for the use of #4 fuel oil or specification waste oil, BPT is a sulfur content not to exceed 0.7% sulfur by weight.
3. NO<sub>x</sub>, CO and VOC emission limits are based upon AP-42 data dated 1/95 for #2 fuel.

4. Visible Emissions for the Asphalt Batch Plant baghouse is limited to no greater than 20% opacity on a 6-minute block average, except for no more than two 6-minute block averages in a continuous 3-hour period.

Pike Industries, Inc. may process up to 10,000 cubic yards per year of soil contaminated by gasoline or #2 fuel oil without prior approval from the Department. This limit may be exceeded with written authorization from the Department. The plant owner or operator shall notify the commissioner at least 24 hours prior to processing the contaminated soil and specify the contaminating fuel and quantity, origin of the soil and fuel and the disposition of the contaminated soil.

Pike Industries, Inc. may process up to 5,000 cubic yards per year of soil contaminated with virgin oil as defined by the Bureau of Air Quality without prior approval from the Bureau of Air Quality. Virgin oil processing shall be done at a mixture of no greater than 30% contaminated soil to 70% clean aggregate mix. Processing of virgin oil contaminated soils may require a solid waste processing facility license under MEDEP Chapter 409. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management.

**Virgin Oil Definition:**

Virgin oil means any petroleum derived oil, including petroleum fuels, unused motor oils, hydraulic fluids, lubrication oils and other industrial oils, that are not characterized as waste oil.

Pike Industries, Inc. shall not process soils which are classified as hazardous waste or which have unknown contaminants.

When processing contaminated soils, Pike Industries, Inc. shall maintain records which specify the quantity and type of contaminant in the soil as well as the origin and characterization of the contaminated soil. In addition, when processing contaminated soil, Pike Industries, Inc. shall maintain records of processing temperature, asphalt feed rates and dryer throughput on an hourly basis. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management.

**C. Asphalt Storage-silo Hot Oil Heater**

Pike Industries, Inc. makes use of a 1.0 MMBtu/hr asphalt storage-silo hot oil heater unit, designated Silo Heater #1, to maintain the heat in the asphalt storage silos. The heater heats oil, which in turn is circulated through the silo imparting heat to the asphalt contained in the silo.

Because the Silo Heater #1 is considered new equipment, an application of Best Available Control Technology (BACT) is required. Ordinarily, BACT for new or modified #2 fuel oil burning equipment requires the use of #2 fuel oil with a sulfur content of no greater than 0.35% sulfur by weight. In this case, the Department shall consider BACT satisfied with the currently licensed requirement of the use of #2 fuel oil with a sulfur content of no greater than 0.5% sulfur by weight in the asphalt storage-silo hot oil heater for the following reasons:

- a. If this amendment were to establish a sulfur limit of no greater than 0.35% sulfur by weight for new equipment, Pike Industries, Inc. would be required to either establish a separate contract for fuel delivery for the new equipment, construct a new fuel containment and handling system to service the new equipment or establish a new contract for fuel oil with a lower sulfur fuel for all the facility's fuel burning equipment. This would cause undo time and monetary expense to the facility.
- b. This license already establishes annual SO<sub>2</sub> emissions from the licensed units based on the current total annual fuel oil usage limit of 250,000 gallons per year. Pike Industries, Inc. is requesting that the fuel consumed in the asphalt storage-silo hot oil heater unit be included in the 250,000 gallon per year fuel limit. Therefore, there would be no net change in allowable SO<sub>2</sub> emissions from the facility that would result from requiring Pike Industries, Inc. to fire 0.35% sulfur fuel in the asphalt storage-silo hot oil heater.

Pike Industries, Inc. shall include the fuel consumed in Silo Heater #1 as part of the asphalt batch plant fuel record, also the total fuel consumed in the tank heaters shall be included under the currently licensed asphalt batch plant fuel restriction of 250,000 gallons per year.

A summary of the BPT analysis for Silo Heater #1 is as follows.

1. BPT for PM for the asphalt storage tank heaters is 0.12 lb/MMBtu. PM<sub>10</sub> emission limits are based on PM limits.
2. BPT sulfur content for the #2 fuel oil fired in the asphalt storage tank heater is no greater than 0.5% sulfur by weight.
3. SO<sub>2</sub>, NO<sub>x</sub>, CO and VOC emission rates are based on AP-42 data dated 10/98 for oil fired boilers firing #2 fuel oil (0.5% sulfur).
4. Visible emissions from each of the asphalt storage tank heater shall not exceed 20% on a 6-minute block average.

D. Rock Crushers

Pike Industries, Inc. operate primary, secondary and tertiary rock crushers at their Baldwin pit. The primary rock crusher has a process rate of 300 tons per hour (TPH), the secondary rock crusher has a process rate of 150 TPH and tertiary rock crusher has a process rate of 140 TPH. The rock crushers were manufactured after 1983, therefore, the primary and secondary rock crushers are subject to EPA's NSPS Subpart OOO for Nonmetallic Mineral Processing Plants manufactured after August 31, 1983, with capacities greater than 150 tons/hr for portable plants and greater than 25 tons/hr for non-portable plants.

The regulated pollutant from the rock crushers is particulate emissions. To meet the requirements of Best Practical Treatment (BPT) for control of particulate matter (PM) emissions from the rock crushers, Pike Industries, Inc. shall maintain and operate water sprays on the rock crushers at the Baldwin pit as necessary to control visible emissions to no greater than 10% opacity on a 6-minute block average basis.

E. Diesel Units

Pike Industries, Inc. operates two diesel generator sets, designated Diesel #1 and Diesel #2, primarily as power sources for the primary, secondary and tertiary rock crushers at the Baldwin facility.

The previous air emission license specified that Diesels #1 and #2 have heat input capacities of 7.1 MMBtu/hr and 3.4 MMBtu/hr, respectively. Upon recalculating the heat input capacities, based on an engine efficiency of 35.0% and power outputs of 680 kW and 320 kW, respectively, it was determined that the heat input capacities of the engines are 6.6 MMBtu/hr for Diesel #1 and 3.1 MMBtu/hr for Diesel #2.

Pike Industries, Inc. was previously licensed to fire no greater than 175,000 gallons per year (gal/yr) of diesel fuel oil, with a sulfur content of no greater than 0.05% sulfur by weight based on a twelve-month rolling total. Pike Industries, Inc. has requested a reduction in the fuel restriction, in conjunction with a reduction in the fuel restriction for the asphalt batch plant, to reduce the total annual emissions of criteria pollutants for the facility to levels below the Department's Chapter 137 applicability thresholds. Pike Industries, Inc. has requested that the annual fuel restriction for diesel fuel fired in the diesel units be reduced to firing no greater than 70,000 gal/yr of diesel fuel with a sulfur content of no greater than 0.05% sulfur by weight, on a calendar year basis.

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
8

**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

To demonstrate compliance with the fuel restrictions, Pike Industries, Inc. shall maintain a record of fuel oil purchases, which shall include receipts indicating the amount of fuel delivered and certification from the supplier indicating the sulfur content of the purchased fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis.

A summary of the BPT analysis for the diesel units is as follows

1. BPT is the use of diesel fuel with a sulfur content of 0.05% by weight.
2. BPT for PM is emissions not to exceed 0.12 lb/MMBtu. PM<sub>10</sub> emission limits are based on PM limits.
3. NO<sub>x</sub>, CO and VOC emission limits are based on AP-42 data dated 10/96.
4. Visible emissions from each diesel unit shall not exceed 30% opacity on a 6-minute block average except, for no more than two 6-minute block averages in a 3-hour period.

**F. Fugitive Emissions**

Visible emissions from potential sources of fugitive particulate matter emissions, including material stockpiles and unpaved roadways, shall not exceed an opacity of 20 percent, except for no more than 5-minutes in any 1-hour period. Compliance shall be determined by an aggregate of the individual 15-second opacity observations which exceed 20 percent in any 1-hour.

**G. Annual Emission Restrictions**

- Total fuel use in the asphalt batch plant (P705A) shall not exceed 250,000 gal/year of a combination of #2 fuel oil with a sulfur content of no greater than 0.5% sulfur by weight, #4 fuel oil with a sulfur content of no greater than 0.7% sulfur by weight and specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight, on a calendar year basis.
- Total fuel use in the diesel units (Diesel #1 and Diesel #2) shall not exceed 70,000 gal/year of diesel fuel oil with a sulfur content of no greater than 0.05% sulfur on a calendar year basis.

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
9

**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

Pike Industries, Inc. shall be assessed fees based on the following annual emissions based on a twelve-month rolling total:

<b>Pollutant</b>	<b>Total (tons/yr)</b>		
	Diesel Units	Asphalt Plant (including Silo Heater)	Total
PM	0.6	1.4	2.0
PM <sub>10</sub>	0.6	1.4	2.0
SO <sub>2</sub>	0.2	12.3	12.5
NO <sub>x</sub>	15.3	8.4	23.7
CO	4.1	3.4	7.5
VOC	0.4	2.3	2.7

### **III. AMBIENT AIR QUALITY ANALYSIS**

According to the Maine Regulations Chapter 115, the level of air quality analyses required for a minor source shall be determined on a case-by case basis. Based on the information available in the file, and the similarity to existing sources, Maine Ambient Air Quality Standards (MAAQS) will not be violated by this source. Based on the total facility emissions, Pike Industries, Inc. is below the emissions level required for modeling and monitoring.

### **ORDER**

Based on the above Findings and subject to conditions listed below, the Department concludes that the emissions from this source:

- will receive Best Practical Treatment,
- will not violate applicable emission standards,
- will not violate applicable ambient air quality standards in conjunction with emissions from other sources.

The Department hereby grants Air Emission License A-264-71-H-R/A (SM) subject to the following conditions:

### **STANDARD CONDITIONS**

- (1) Employees and authorized representatives of the Department shall be allowed access to the licensee's premises during business hours, or any time during which any emissions units are in operation, and at such other times as the Department deems necessary for the purpose of performing tests, collecting samples, conducting inspections, or examining and copying records relating to emissions (38 MRSA §347-C).

- (2) The licensee shall acquire a new or amended air emission license prior to commencing construction of a modification, unless specifically provided for in Chapter 115.
- (3) Approval to construct shall become invalid if the source has not commenced construction within eighteen (18) months after receipt of such approval or if construction is discontinued for a period of eighteen (18) months or more. The Department may extend this time period upon a satisfactory showing that an extension is justified, but may condition such extension upon a review of either the control technology analysis or the ambient air quality standards analysis, or both.
- (4) The licensee shall establish and maintain a continuing program of best management practices for suppression of fugitive particulate matter during any period of construction, reconstruction, or operation which may result in fugitive dust, and shall submit a description of the program to the Department upon request.
- (5) The licensee shall pay the annual air emission license fee to the Department, calculated pursuant to 38 M.R.S.A. §353.
- (6) The license does not convey any property rights of any sort, or any exclusive privilege.
- (7) The licensee shall maintain and operate all emission units and air pollution systems required by the air emission license in a manner consistent with good air pollution control practice for minimizing emissions.
- (8) The licensee shall maintain sufficient records to accurately document compliance with emission standards and license conditions and shall maintain such records for a minimum of six (6) years. The records shall be submitted to the Department upon written request.
- (9) The licensee shall comply with all terms and conditions of the air emission license. The filing of an appeal by the licensee, the notification of planned changes or anticipated noncompliance by the licensee, or the filing of an application by the licensee for a renewal of a license or amendment shall not stay any condition of the license.
- (10) The licensee may not use as a defense in an enforcement action that the disruption, cessation, or reduction of licensed operations would have been necessary in order to maintain compliance with the conditions of the air emission license.

- (11) In accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department, the licensee shall:
- (i) perform stack testing to demonstrate compliance with the applicable emission standards under circumstances representative of the facility's normal process and operating conditions:
    - a. within sixty (60) calendar days of receipt of a notification to test from the Department or EPA, if visible emissions, equipment operating parameters, staff inspection, air monitoring or other cause indicate to the Department that equipment may be operating out of compliance with emission standards or license conditions; or
    - b. pursuant to any other requirement of this license to perform stack testing.
  - (ii) install or make provisions to install test ports that meet the criteria of 40 CFR Part 60, Appendix A, and test platforms, if necessary, and other accommodations necessary to allow emission testing; and
  - (iii) submit a written report to the Department within thirty (30) days from date of test completion.
- (12) If the results of a stack test performed under circumstances representative of the facility's normal process and operating conditions indicate emissions in excess of the applicable standards, then:
- (i) within thirty (30) days following receipt of such test results, the licensee shall re-test the non-complying emission source under circumstances representative of the facility's normal process and operating conditions and in accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department; and
  - (ii) the days of violation shall be presumed to include the date of stack test and each and every day of operation thereafter until compliance is demonstrated under normal and representative process and operating conditions, except to the extent that the facility can prove to the satisfaction of the Department that there were intervening days during which no violation occurred or that the violation was not continuing in nature; and

- (iii) the licensee may, upon the approval of the Department following the successful demonstration of compliance at alternative load conditions, operate under such alternative load conditions on an interim basis prior to a demonstration of compliance under normal and representative process and operating conditions.
- (13) Notwithstanding any other provisions in the State Implementation Plan approved by the EPA or Section 114(a) of the CAA, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any statute, regulation, or Part 70 license requirement.
- (14) The licensee shall maintain records of malfunctions, failures, downtime, and any other similar change in operation of air pollution control systems or the emissions unit itself that would affect emission and that is not consistent with the terms and conditions of the air emission license. The licensee shall notify the Department within two (2) days or the next state working day, whichever is later, of such occasions where such changes result in an increase of emissions. The licensee shall report all excess emissions in the units of the applicable emission limitation.
- (15) Upon written request from the Department, the licensee shall establish and maintain such records, make such reports, install, use and maintain such monitoring equipment, sample such emissions (in accordance with such methods, at such locations, at such intervals, and in such a manner as the Department shall prescribe), and provide other information as the Department may reasonably require to determine the licensee's compliance status.

### **SPECIFIC CONDITIONS**

- (16) Asphalt Batch Plant
- A. Total fuel use in the asphalt batch plant, which includes Silo Heater #1, shall not exceed 250,000 gal/year of a combination #2 fuel oil with a sulfur content of no greater than 0.5% sulfur by weight, #4 fuel oil with a sulfur content of no greater than 0.7% sulfur by weight and specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight, on a calendar year basis. [MEDEP Chapter 115, BPT]
- B. Pike Industries, Inc. shall maintain a record of fuel use for the asphalt batch plant, which shall include fuel purchase receipts indicating the quantity and sulfur content of the purchased fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis. [MEDEP Chapter 115, BPT]

- C. Only waste oil meeting the criteria “specification” waste oil (as defined in the “Waste Oil Management Rules”) may be fired in the asphalt plant. [MEDEP Chapter 115, BPT]
- D. As a requirement of NSPS Subpart I, Pike Industries, Inc. shall perform a performance test in accordance with 40 CFR 60.8 and 40 CFR 60.93. This consists of a certified Method 9 observation. The performance test shall be completed within 60 days after achieving the maximum production rate at which the unit will be operated, but no later than 180 days after initial startup of the unit. Pike Industries, Inc. shall submit a test notice to the regional inspector at least 30 days prior to the performance test. Any rescheduled test requires a 7-day notice to the regional inspector. [40 CFR 60, Subpart I]
- E. Emissions from the asphalt batch plant shall vent to a baghouse and all components of the asphalt batch plant shall be maintained so as to prevent particulate matter leaks. [MEDEP Chapter 115, BPT]
- F. Visible Emissions for the Asphalt Batch Plant baghouse are limited to no greater than 20% opacity on a 6-minute block average, except for no more than two 6-minute block averages in a continuous 3-hour period. [MEDEP Chapter 101]
- G. The performance of the baghouse shall be constantly monitored by either of the following at all times the batch plant is in operation:
1. PM Detector – when the detector signals excessive PM concentrations in the exhaust stream, Pike Industries, Inc. shall take corrective action within 24 hours, or immediately if opacity exceeds 20% based on a 6-minute block average basis. [MEDEP Chapter 115, BPT]
  2. Personnel with an EPA Method 9 visible emissions certification within the past 6 months – when the opacity exceeds 20%, the hot mix asphalt batch plant is operating with insufficient control and Pike Industries, Inc. shall take corrective action immediately. [MEDEP Chapter 115, BPT]
- H. Emissions from the asphalt batch plant shall not exceed the following:

<b>Equipment</b>		<b>PM</b>	<b>PM<sub>10</sub></b>	<b>SO<sub>2</sub></b>	<b>NO<sub>x</sub></b>	<b>CO</b>	<b>VOC</b>
Asphalt	Grs/dscf	0.03	-	-	-	-	-
Batch Plant	lb/hr	4.0	4.0	35.0	23.8	9.7	6.4

[MEDEP Chapter 115, BPT]

- I. Fugitive particulate matter emissions from the asphalt batch plant operation shall be controlled so as to prevent visible emissions in excess of 10% opacity except for one 6-minute block average in any continuous 1-hour period. [MEDEP Chapter 101]
- J. Pike Industries, Inc. shall establish a system of maintenance, inspection and repair for the asphalt plant baghouse, which shall allow for periodic inspection of the system. Pike Industries, Inc. shall document compliance by means of a maintenance, inspection and repair log in which Pike Industries, Inc. shall record the date of all bag failures and all routine maintenance as well as all inspection dates, findings and corrective actions. [MEDEP Chapter 115, BPT]
- K. Pike Industries, Inc. may process up to 10,000 cubic yards per year of soil contaminated by gasoline or #2 fuel oil without prior approval from the Department. This limit may be exceeded with written authorization from the Department. The plant owner or operator shall notify the commissioner at least 24 hours prior to processing the contaminated soil and specify the contaminating fuel and quantity, origin of the soil and fuel and the disposition of the contaminated soil. [MEDEP Chapter 115, BPT]
- L. Pike Industries, Inc. may process up to 5,000 cubic yards per year of soil contaminated with virgin oil as defined by the Bureau of Air Quality without prior approval from the Bureau of Air Quality. Virgin oil processing shall be done at a mixture of no greater than 30% contaminated soil to 70% clean aggregate mix. Processing of virgin oil contaminated soils may require a solid waste processing facility license under MEDEP Chapter 409. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management. [MEDEP Chapter 115, BPT]
- M. Pike Industries, Inc. shall not process soils which are classified as hazardous waste or which have unknown contaminants. [MEDEP Chapter 115, BPT]
- N. When processing contaminated soils, Pike Industries, Inc. shall maintain records which specify the quantity and type of contaminant in the soil as well as the origin and characterization of the contaminated soil. In addition, when processing contaminated soil, Pike Industries, Inc. shall maintain records of processing temperature, asphalt feed rates and dryer throughput on an hourly basis. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management. [MEDEP Chapter 115, BPT]

O. Pike Industries, Inc. shall notify the Bureau of Air Quality regional inspector at least 7 days prior to processing soil contaminated with anything other than #2 fuel oil, gasoline or virgin oil. [MEDEP Chapter 115, BPT]

(17) Asphalt Storage-silo Hot Oil Heater (Silo Heater #1)

A. The sulfur content of the fuel oil fired in the Asphalt Storage-silo Hot Oil Heater shall not exceed 0.5% sulfur by weight for #2 fuel oil and 0.7% sulfur by weight for specification waste oil demonstrated by purchase records or certification from the supplier. [MEDEP Chapter 115, BACT]

B. Pike Industries, Inc. shall include the fuel consumed in Silo Heater #1 as part of the asphalt batch plant fuel record, also the total fuel consumed in the tank heaters shall be included under the currently licensed asphalt batch plant fuel restriction of 250,000 gallons per year. [MEDEP Chapter 115, BACT]

C. Emissions from Silo Heater #1 shall not exceed the following:

Equipment		PM	PM <sub>10</sub>	SO <sub>2</sub>	NO <sub>x</sub>	CO	VOC
Hot Oil Heater	lb/hr	0.12	0.12	0.7	0.14	0.04	0.004

[MEDEP Chapter 115, BACT]

D. Visible emissions from the Silo Heater #1 shall not exceed 20% on a 6-minute block average. [MEDEP Chapter 101]

(18) Rock Crushers

A. Pike Industries, Inc. shall maintain spray nozzles on the Primary, Secondary and Tertiary Rock Crushers and operate the spray nozzles as necessary so as not to exceed visible emissions limits. Visible emissions from the crushers shall be limited to no greater than 10% opacity on a 6-minute block average basis. [MEDEP Chapter 101]

B. Pike Industries, Inc. shall maintain a log detailing the maintenance on the water spray nozzles. The maintenance log shall be kept on-site at the rock crushing location. [MEDEP Chapter 115, BPT]

C. Pike Industries, Inc. shall maintain a log detailing and quantifying the hours of operation on a daily basis for the Primary, Secondary and Tertiary Rock Crushers. The operation log shall be kept on-site at the rock crushing location. [MEDEP Chapter 115, BPT]

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
**16**

**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

(19) New Source Performance Standards (NSPS) for rock crushers

- A. The primary and secondary rock crushers are subject to 40 CFR Part 60 Subparts A and OOO and Pike Industries, Inc. shall comply with the notification and record keeping requirements of 40 CFR Part 60.676 and Part 60.7, except for Section (a)(2) of 60.7 per Subpart OOO, §60.676(h).  
[40 CFR 60, Subpart OOO]
- B. Pike Industries, Inc. shall have an initial performance test performed on the primary and secondary crushers per the applicable sections of 40 CFR Part 60, Subpart OOO, §60.675. This consists of a certified Method 9 observation. The performance test shall be completed within 60 days after achieving the maximum production rate at which the unit will be operated, but no later than 180 days after initial startup of the unit. Pike Industries, Inc. shall submit a test notice to the regional inspector at least 30 days prior to the performance test. Any rescheduled test requires a 7-day notice to the regional inspector.  
[40 CFR 60, Subpart OOO]

(20) Fugitive Emissions

Visible emissions from potential sources of fugitive particulate matter emissions, including material stockpiles and unpaved roadways, shall not exceed an opacity of 20%, except for no more than 5-minutes in any 1-hour period. Compliance shall be determined by an aggregate of the individual 15-second opacity observations which exceed 20% in any 1-hour. [MEDEP Chapter 101]

(21) Equipment Relocation [MEDEP Chapter 115, BPT]

- A. Pike Industries, Inc. shall notify the Bureau of Air Quality, by a written notification at least 48 hours prior to relocation of any equipment carried on this license. Written notice may be sent by mail, facsimile (fax), or e-mail. Notification sent by mail shall be sent to the address below or to a Department Regional Office:

Attn: Relocation Notice  
Maine DEP  
Bureau of Air Quality  
17 State House Station  
Augusta, ME 04333-0017

Equipment relocation notification can also be done on-line with e-notice at [www.maine.gov/dep/air/compliance/forms/relocation](http://www.maine.gov/dep/air/compliance/forms/relocation).

**Pike Industries, Inc.**  
**Cumberland County**  
**Baldwin, Maine**  
**A-264-71-H-R/A (SM)**

)  
)  
)  
17

**Departmental**  
**Findings of Fact and Order**  
**Air Emission License**

The notification shall include the address of the equipment's new location, an identification of the equipment and the license number pertaining to the relocated equipment.

- B. Written notification shall also be made to the municipality where the equipment will be relocated, except in the case of an unorganized territory where notification will be made to the respective county commissioners.
- (22) Pike Industries, Inc. shall keep a copy of this Order on site, and have the operator(s) be familiar with the terms of this Order. [MEDEP Chapter 115]
- (23) Pike Industries, Inc. shall notify the Department within 48 hours and submit a report to the Department on a quarterly basis if a malfunction or breakdown in any component causes a violation of any emission standard (38 MRSA §605-C).
- (24) Pike Industries, Inc. shall pay the annual air emission license fee within 30 days of June 30 of each year. Pursuant to 38 MRSA 353-A, failure to pay this annual fee in the stated timeframe is sufficient grounds for the revocation of the license under 38 MRSA 341-D, Subsection 3.

DONE AND DATED IN AUGUSTA, MAINE THIS                      DAY OF                      2005.

DEPARTMENT OF ENVIRONMENTAL PROTECTION

BY: \_\_\_\_\_  
DAWN R. GALLAGHER, COMMISSIONER

PLEASE NOTE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

The term of this Order shall be for five (5) years from the signature above.

Date of initial receipt of application: **October 4, 2004**

Date of application acceptance: **October 8, 2004**

Date filed with the Board of Environmental Protection: \_\_\_\_\_

This Order prepared by, Peter G. Carleton, Bureau of Air Quality