STATE OF MAINE
DEPARTMENT OF ENVIRONMENTAL PROTECTION

JOHN ELIAS BALDACCI
GOVERNOR

BETH NAGUSKY
ACTING COMMISSIONER

L.L. Bean Inc.
Stonewood Data Center
Cumberland County
Freeport, Maine
A-1036-71-A-N (SM)

Departmental
Findings of Fact and Order
Air Emission License
After-the-Fact

After review of the air emissions license application, staff investigation reports and other documents in the applicant's file in the Bureau of Air Quality, pursuant to 38 M.R.S.A., §344 and §590, the Department finds the following facts:

I. REGISTRATION

A. Introduction

L.L. Bean Inc. – Stonewood Data Center (LL Bean) has applied after-the-fact for a new Air Emission License permitting the operation of emission sources associated with their Data Processing Facility.

B. Emission Equipment

The following equipment is addressed in this air emission license:

Electrical Generation Equipment

Equipment	Heat Input Capacity (MMBtu/hr)	Firing Rate (gal/hr)	Fuel Type	Stack #
SDC Gen #1	14.8	108	diesel fuel	1
SDC Gen #2	14.8	108	diesel fuel	2

C. Application Classification

LL Bean is classified as an existing source that is applying for its first air emission license, after the fact. The Department has determined the facility is a minor source and the application has been processed through *Major and Minor Source Air Emission License Regulations*, 06-096 CMR 115 (last amended December 24, 2005). With the operating restrictions on the generators, the facility is licensed below the major source thresholds and is considered a synthetic minor.

II. BEST PRACTICAL TREATMENT (BPT)

A. Introduction

In order to receive a license the applicant must control emissions from each unit to a level considered by the Department to represent Best Practical Treatment (BPT), as defined in *Definitions Regulation*, 06-096 CMR 100 (last amended December 24, 2005). Separate control requirement categories exist for new and existing equipment as well as for those sources located in designated non-attainment areas.

BPT for new sources and modifications requires a demonstration that emissions are receiving Best Available Control Technology (BACT), as defined in *Definitions Regulation*, 06-096 CMR 100 (last amended December 24, 2005). BACT is a top-down approach to selecting air emission controls considering economic, environmental and energy impacts.

B. SDC Gen #1 and SDC Gen #2

LL Bean operates two emergency generators, each rated at 14.8 MMBtu/hr. The generators were ordered after July 11, 2005 and manufactured after April 1, 2006. Therefore, the generators are subject to New Source Performance Standards 40 CFR Part 60, Subpart IIII, *Standards of Performance for Stationary Compression Ignition Internal Combustion Engines*. Because these generators are subject to the requirements of Subpart IIII, they are exempt from the requirements of National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR, Part 63, Subpart ZZZZ.

Due to the potential for tight electricity supplies, ISO New England has taken several precautionary steps to ensure the reliability of the region-wide bulk power system. One of those steps is the implementation of the Demand Response Program. This program offers financial incentives to customers, such as L.L. Bean, to reduce electricity demand during peak periods. This program can significantly improve the reliability of the region-wide bulk power system and hopefully allow ISO New England to avoid drastic measures, such as brown outs.

In order for L.L. Bean to participate in the Demand Response Program, they need to start their generators and run them prior to, or in lieu of, loss of off-site power. L.L. Bean will only operate in this manner if there is a documented request from ISO New England under their emergency OP-4 procedures. ISO New England's OP-4 is a procedure which establishes criteria and guidelines for actions during capacity deficiencies. OP-4 is implemented when there is determined to be a serious threat to the integrity of the bulk power system. Therefore, the Department has agreed to redefine the term "emergency" as it applies to L.L. Bean's generators to include ISO New England OP-4 emergencies.

Therefore "Emergency Generator", as it applies to L.L. Bean, is defined as any stationary internal combustion engine whose operation is limited to emergency situations, required testing and maintenance, and ISO New England OP-4 emergencies. Examples include stationary engines used to produce power for critical networks or equipment (including power supplied to portions of a facility) when electric power from the local utility (or the normal power source, if the facility runs on its own power production) is interrupted, or stationary engines used to pump water in the case of fire or flood.

Additionally, L.L. Bean shall only be permitted to operate their generators in response to an OP-4 emergency for a total of no more than 50 hours each calendar year.

A summary of the BACT analysis for the generators is the following:

1. Each generator shall fire only diesel fuel with a maximum sulfur content not to exceed 500 ppm.
2. Beginning October 1, 2010, each generator shall fire only diesel fuel with a maximum sulfur content not to exceed 15 ppm.
3. Each generator shall be limited to 100 hr/yr of operation for maintenance checks and readiness testing. Each generator shall be limited to 400 hours per year of total operation. Both of these limits are based on a 12 month rolling total. Compliance shall be demonstrated by a written log of all generator operating hours.
4. Each generator shall be equipped with a non-resettable hour meter.
5. 06-096 CMR 103 regulates PM emission limits. The PM_{10} limits are derived from the PM limits.
6. NO_x, CO, and VOC emission limits are based upon AP-42 data dated 10/96.
7. LL Bean shall operate and maintain each generator in accordance with the manufacturer's written instructions. LL Bean shall not change settings that are not approved in writing by the manufacturer.
8. Visible emissions from each generator shall not exceed 20% opacity on a six (6) minute block average, except for no more than two (2), six (6) minute block averages in a continuous 3-hour period.

C. Annual Emissions
LL Bean shall be restricted to the following annual emissions, based on a 12 month rolling total:

Total Licensed Annual Emissions for the Facility
Tons/year
(used to calculate the annual license fee)

	PM	PM_{10}	SO_2	NO_x	CO	VOC
SDC Gen #1	0.36	0.36	0.15	9.47	2.52	0.27
SDC Gen #2	0.36	0.36	0.15	9.47	2.52	0.27
Total TPY	**0.72**	**0.72**	**0.30**	**18.94**	**5.04**	**0.54**

III. AMBIENT AIR QUALITY ANALYSIS

According to 06-096 CMR 115, the level of air quality analyses required for a minor **new** source shall be determined on a case-by case basis. Based on the information available in the file, and the similarity to existing sources, Maine Ambient Air Quality Standards (MAAQS) will not be violated by this source.

ORDER

Based on the above Findings and subject to conditions listed below, the Department concludes that the emissions from this source:

- will receive Best Practical Treatment,
- will not violate applicable emission standards,
- will not violate applicable ambient air quality standards in conjunction with emissions from other sources.

The Department hereby grants Air Emission License A-1036-71-A-N subject to the following conditions.

Severability. The invalidity or unenforceability of any provision, or part thereof, of this License shall not affect the remainder of the provision or any other provisions. This License shall be construed and enforced in all respects as if such invalid or unenforceable provision or part thereof had been omitted.

STANDARD CONDITIONS

(1) Employees and authorized representatives of the Department shall be allowed access to the licensee's premises during business hours, or any time during which any emissions units are in operation, and at such other times as the Department deems necessary for the purpose of performing tests, collecting samples, conducting inspections, or examining and copying records relating to emissions (38 M.R.S.A. §347-C).

(2) The licensee shall acquire a new or amended air emission license prior to commencing construction of a modification, unless specifically provided for in Chapter 115. [06-096 CMR 115]

(3) Approval to construct shall become invalid if the source has not commenced construction within eighteen (18) months after receipt of such approval or if construction is discontinued for a period of eighteen (18) months or more. The Department may extend this time period upon a satisfactory showing that an extension is justified, but may condition such extension upon a review of either the control technology analysis or the ambient air quality standards analysis, or both. [06-096 CMR 115]

(4) The licensee shall establish and maintain a continuing program of best management practices for suppression of fugitive particulate matter during any period of construction, reconstruction, or operation which may result in fugitive dust, and shall submit a description of the program to the Department upon request. [06-096 CMR 115]

(5) The licensee shall pay the annual air emission license fee to the Department, calculated pursuant to Title 38 M.R.S.A. §353. [06-096 CMR 115]

(6) The license does not convey any property rights of any sort, or any exclusive privilege. [06-096 CMR 115]

(7) The licensee shall maintain and operate all emission units and air pollution systems required by the air emission license in a manner consistent with good air pollution control practice for minimizing emissions. [06-096 CMR 115]

(8) The licensee shall maintain sufficient records to accurately document compliance with emission standards and license conditions and shall maintain such records for a minimum of six (6) years. The records shall be submitted to the Department upon written request. [06-096 CMR 115]

(9) The licensee shall comply with all terms and conditions of the air emission license. The filing of an appeal by the licensee, the notification of planned

changes or anticipated noncompliance by the licensee, or the filing of an application by the licensee for a renewal of a license or amendment shall not stay any condition of the license. [06-096 CMR 115]

(10) The licensee may not use as a defense in an enforcement action that the disruption, cessation, or reduction of licensed operations would have been necessary in order to maintain compliance with the conditions of the air emission license. [06-096 CMR 115]

(11) In accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department, the licensee shall:

A. perform stack testing to demonstrate compliance with the applicable emission standards under circumstances representative of the facility's normal process and operating conditions:
   1. within sixty (60) calendar days of receipt of a notification to test from the Department or EPA, if visible emissions, equipment operating parameters, staff inspection, air monitoring or other cause indicate to the Department that equipment may be operating out of compliance with emission standards or license conditions; or
   2. pursuant to any other requirement of this license to perform stack testing.

B. install or make provisions to install test ports that meet the criteria of 40 CFR Part 60, Appendix A, and test platforms, if necessary, and other accommodations necessary to allow emission testing; and

C. submit a written report to the Department within thirty (30) days from date of test completion.

[06-096 CMR 115]

(12) If the results of a stack test performed under circumstances representative of the facility's normal process and operating conditions indicate emissions in excess of the applicable standards, then:

A. within thirty (30) days following receipt of such test results, the licensee shall re-test the non-complying emission source under circumstances representative of the facility's normal process and operating conditions and in accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department; and

B. the days of violation shall be presumed to include the date of stack test and each and every day of operation thereafter until compliance is demonstrated under normal and representative process and operating conditions, except to the extent that the facility can prove to the satisfaction of the Department that there were intervening days during which no violation occurred or that the violation was not continuing in nature; and

C. the licensee may, upon the approval of the Department following the successful demonstration of compliance at alternative load conditions, operate

under such alternative load conditions on an interim basis prior to a demonstration of compliance under normal and representative process and operating conditions.
[06-096 CMR 115]

(13) Notwithstanding any other provisions in the State Implementation Plan approved by the EPA or Section 114(a) of the CAA, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any statute, regulation, or Part 70 license requirement. [06-096 CMR 115]

(14) The licensee shall maintain records of malfunctions, failures, downtime, and any other similar change in operation of air pollution control systems or the emissions unit itself that would affect emission and that is not consistent with the terms and conditions of the air emission license. The licensee shall notify the Department within two (2) days or the next state working day, whichever is later, of such occasions where such changes result in an increase of emissions. The licensee shall report all excess emissions in the units of the applicable emission limitation. [06-096 CMR 115]

(15) Upon written request from the Department, the licensee shall establish and maintain such records, make such reports, install, use and maintain such monitoring equipment, sample such emissions (in accordance with such methods, at such locations, at such intervals, and in such a manner as the Department shall prescribe), and provide other information as the Department may reasonably require to determine the licensee's compliance status. [06-096 CMR 115]

SPECIFIC CONDITIONS

(16) **SDC-Gen #1 and SDC-Gen #2**

A. Each generator shall fire only diesel fuel with a maximum sulfur content not to exceed 500 ppm. [40 CFR 60.4207(a)]
B. Beginning October 1, 2010, each generator shall fire only diesel fuel with a maximum sulfur content not to exceed 15 ppm. [40 CFR 60.4207(b)]
C. Compliance with the sulfur content limits shall be based on fuel records from the supplier showing the type of fuel delivered and the sulfur content of the fuel. [06-096 CMR 115, BACT]
D. Each generator shall be limited to 100 hr/yr of operation for maintenance checks and readiness testing. Each generator shall be limited to 400 hours per year of total operation. Both of these limits are based on a 12 month rolling total. Compliance shall be demonstrated by a written log of all generator operating hours. [40 CFR 60.4211(E) and 06-096 CMR 115, BACT]
E. Each generator shall be equipped with a non-resettable hour meter. [40 CFR 60.4209(a)]

F. Emissions shall not exceed the following for each generator:

Emission Unit	Pollutant	lb/MMBtu	Origin and Authority
Generator	PM	0.12	06-096 CMR 103(2)(B)(1)(a)

G. Emissions shall not exceed the following for each generator [06-096 CMR 115, BACT]:

Emission Unit	PM (lb/hr)	PM_{10} (lb/hr)	SO_2 (lb/hr)	NO_x (lb/hr)	CO (lb/hr)	VOC (lb/hr)
Generator	1.78	1.78	0.76	47.36	12.58	1.33

H. Each generator is subject to PM, CO, and NO_x + VOC emission requirements set forth in 40 CFR 60, Subpart IIII. Compliance with these emission requirements shall be demonstrated by certification from the manufacturer that this engine class meets the appropriate Tier standards. [40 CFR 60, Subpart IIII]

I. LL Bean shall operate and maintain each generator in accordance with the manufacturer's written instructions. LL Bean shall not change settings that are not approved in writing by the manufacturer. [40 CFR 60.4211(a)]

J. Visible emissions from each generator shall not exceed 20% opacity on a six (6) minute block average, except for no more than two (2), six (6) minute block averages in a continuous 3-hour period. [06-096 CMR 101]

(17) **OP-4 Emergencies**

A. *Facility* shall only operate the emergency generators for periods of maintenance and readiness testing, emergencies when off-site power is unavailable, and ISO New England OP-4 emergencies. [06-096 CMR 115, BPT]

B. *Facility* shall keep records for OP-4 emergencies which include the date, which generators were operated, start time and stop time for each generator, and documentation that *Facility* was contacted by ISO New England and asked to reduce consumption as part of an OP-4 event. [06-096 CMR 115, BPT]

C. *Facility* shall not operate the emergency generators for more than 50 hours each per calendar year in response to an OP-4 emergency. [06-096 CMR 115, BPT]

(18) LL Bean shall notify the Department within 48 hours and submit a report to the Department on a quarterly basis if a malfunction or breakdown in any component causes a violation of any emission standard (38 M.R.S.A. §605).

DONE AND DATED IN AUGUSTA, MAINE THIS 22nd DAY OF September, 2010.

DEPARTMENT OF ENVIRONMENTAL PROTECTION

BY: James P. Brooks
BETH NAGUSKY, ACTING COMMISSIONER

The term of this license shall be five (5) years from the signature date above.

PLEASE NOTE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

Date of initial receipt of application: 3/10/2010
Date of application acceptance: 3/15/2010

Date filed with the Board of Environmental Protection:

This Order prepared by Jonathan Voisine, Bureau of Air Quality.

FILED
SEP 27 2010
BOARD OF ENVIRONMENTAL PROT.
STATE OF MAINE