



STATE OF MAINE
DEPARTMENT OF ENVIRONMENTAL PROTECTION

PAUL R. LEPAGE
GOVERNOR

PATRICIA W. AHO
ACTING COMMISSIONER

**Dreamkeepers, Inc. dba
Dyers Bay Crematory
Hancock County
Steuben, Maine
A-1061-71-A-N**

**Departmental
Findings of Fact and Order
Air Emission License**

After review of the air emission license application, staff investigation reports, and other documents in the applicant's file in the Bureau of Air Quality, pursuant to 38 M.R.S.A., Section 344 and Section 590, the Department finds the following facts:

I. REGISTRATION

A. Introduction

1. Dreamkeepers, Inc. dba Dyers Bay Crematory (Dyers Bay) has applied for an Air Emission License, permitting the operation of a Class IV-A crematory.
2. The equipment addressed in this license is located at Stanley Point Road, Steuben, ME.

B. Emission Equipment

The incinerator is a B&L Cremation Systems Inc., N-20AA unit with the following specifications:

Class Incinerator	IV-A
No. of Chambers	2
Type of Waste	Type 4
Max. Design Combustion Rate (lb/hr)	150
Auxiliary Fuel Input:	
Primary Chamber (Btu/hr)	0.5
Secondary Chamber (Btu/hr)	1.5
Emission Control	Afterburner

The incinerator combustion gases vent to a 20 foot AGL (Above Ground Level) stack.

AUGUSTA
17 STATE HOUSE STATION
AUGUSTA, MAINE 04333-0017
(207) 287-7688 FAX: (207) 287-7826
RAY BLDG., HOSPITAL ST.

BANGOR
106 HOGAN ROAD, SUITE 6
BANGOR, MAINE 04401
(207) 941-4570 FAX: (207) 941-4584

PORTLAND
312 CANCO ROAD
PORTLAND, MAINE 04103
(207) 822-6300 FAX: (207) 822-6303

PRESQUE ISLE
1235 CENTRAL DRIVE, SKYWAY PARK
PRESQUE ISLE, MAINE 04679-2094
(207) 764-0477 FAX: (207) 760-3143

C. Application Classification

The new source is considered a major source based on whether or not expected emissions exceed the "Significant Emission Levels" as defined in 06-096 CMR 100 (as amended). The emissions for the new source are determined by the maximum future license allowed emissions, as follows:

<u>Pollutant</u>	<u>Max. Future License</u> <u>(TPY)</u>	<u>Significance Level</u> <u>(TPY)</u>
PM	3.17	100
PM ₁₀	3.17	100
SO ₂	0.71	100
NO _x	2.08	100
CO	1.49	100
VOC	0.17	50

This source is determined to be a minor new source and has been processed as such.

II. **BEST PRACTICAL TREATMENT**

A. Introduction

In order to receive a license, the applicant must control emissions from each unit to a level considered by the Department to represent Best Practical Treatment (BPT), as defined in 06-096 CMR 100 (as amended). Separate control requirement categories exist for new and existing equipment as well as for those sources located in designated areas.

BPT for new sources requires a demonstration that emissions are receiving Best Available Control Technology (BACT), as defined in *Definitions Regulation*, 06-096 CMR 100 (as amended December). BACT is a top-down approach to selecting air emission controls considering economic, environmental and energy impacts.

B. Crematory Incinerator

BACT for the incinerator is the following:

- Emission Limits

Emissions information is based on a licensed allowed particulate matter emission limit of 0.12 gr/dscf corrected to 12% CO₂, the burning of liquefied propane gas as an auxiliary fuel, and the use of AP-42 factors: Table 2.3-1 and 2 for medical waste incinerators (dated 7/93) and Tables 1.5-1 for propane as the auxiliary fuel burning (dated 07/08):

PM - 0.72 lb/hr based on 0.12 gr/dscf corrected to 12 percent CO₂, based on BACT/BPT, for incineration of human remains

SO₂ - 0.16 lb/hr based on the AP-42 factor of 2.17 lb/ton for incineration of human remains

NO_x - 0.27 lb/hr based on the AP-42 factor of 3.56 lb/ton for incineration of human remains, and 0.20 lb/hr based on AP-42 factor of 13.0 lb/1000 gallons of propane fired

CO - 0.22 lb/hr based on the AP-42 factor of 2.95 lb/ton for incineration of human remains, and 0.12 lb/hr based on the AP-42 factor of 7.5 lb/1000 gallons of propane fired

VOC - 0.30 lb/hr based on the AP-42 factor of 0.299 lb/ton for incineration of human remains, and 0.02 lb/hr based on the AP-42 factor of 1.0 lb/1000 gallons of propane fired

Opacity: Visible emissions from the incinerator stack shall not exceed 10 percent opacity based on a six (6) minute block average basis.

- Operating parameters:

- Operating temperature in the secondary chamber shall be maintained at or above 1600°F for the duration of the burn cycle, with a stack gas retention time, at or above 1600°F, of at least 1.0 second.
- To ensure an efficient burn, and to prevent odors and visible emissions, the secondary chamber will be preheated, as specified by the manufacturer, until the pyrometer temperature measures at least 1200°F.
- Once the burn cycle has commenced by introduction of primary chamber combustion, the incinerator shall be operated in an efficient manner, and as specified by the manufacturer, for the period of time between preheat and reaching the set operational temperature to be a minimum of 1600°F in the secondary chamber.
- A pyrometer and 1/4 inch test port shall be installed and maintained at that location of the incinerator or refractory lined stack which provides sufficient volume to insure a flue gas retention time of not less than 1.0 second at a minimum of 1600°F.

- A log will be maintained recording the weight of the charge, preheat time, charging time and the temperature of the secondary chamber every 60 minutes after start-up until, and including, final shutdown time. For facilities operating a chart recorder, the start time, date, and weight charged shall be logged on the chart.
- The incinerator operator(s) shall receive adequate training to operate the incinerator in accordance with the manufacturer's specifications and shall be familiar with the terms of the Air Emission License.

III. AIR QUALITY ANALYSIS

According to 06-096 CMR 115 (as amended), the level of air quality analysis and monitoring are determined on a case-by-case basis. Based on analysis for similar sources, the size of the source, the allowable emissions, the location, and the stack height, ambient air quality standards, including increments, are not expected to be violated. Therefore, an ambient air impact analysis will not be required for this source at this time.

ORDER

Based on the above Findings and subject to conditions listed below the Department concludes that the emissions from this above source:

- will receive Best Practical Treatment,
- will not violate applicable emission standards
- will not violate applicable ambient air quality standards in conjunction with emissions from other sources.

The Department hereby grants Air Emission License A-1061-71-A-N, subject to the following conditions:

Severability. The invalidity or unenforceability of any provision, or part thereof, of this License shall not affect the remainder of the provision or any other provisions. This License shall be construed and enforced in all respects as if such invalid or unenforceable provision or part thereof had been omitted.

STANDARD CONDITIONS

- (1) Employees and authorized representatives of the Department shall be allowed access to the licensee's premises during business hours, or any time which any emission units are in operation, and at such other times as the Department deems necessary for the purpose of performing tests, collecting samples, conducting inspections, or examining and copying records relating to emissions. [06-096 CMR 115]
- (2) The licensee shall acquire a new or amended air emission license prior to commencing construction of a modification, unless specifically provided for in Chapter 115. [06-096 CMR 115]
- (3) Approval to construct shall become invalid if the source has not commenced construction within eighteen (18) months after receipt of such approval or if construction is discontinued for a period of eighteen (18) months or more. The Department may extend this time period upon a satisfactory showing that an extension is justified, but may condition such extension upon a review of either the control technology analysis or the ambient air quality standards analysis, or both. [06-096 CMR 115]
- (4) The licensee shall establish and maintain a continuing program of best management practices for suppression of fugitive particulate matter during any period of construction, reconstruction, or operation which may result in fugitive dust, and shall submit a description of the program to the Department upon request. [06-096 CMR 115]
- (5) The licensee shall pay the annual air emission license fee to the Department, calculated pursuant to Title 38 MRSA §353-A. [06-096 CMR 115]
- (6) The license does not convey any property rights of any sort, or any exclusive privilege. [06-096 CMR 115]
- (7) The licensee shall maintain and operate all emission units and air pollution control systems required by the air emission license in a manner consistent with good air pollution control practices for minimizing emissions. [06-096 CMR 115]
- (8) The licensee shall maintain sufficient records, to accurately document compliance with emission standards and license conditions and shall maintain such records for a minimum of six (6) years. The records shall be submitted to the Department upon written request. [06-096 CMR 115]

- (9) The licensee shall comply with all terms and conditions of the air emission license. The filing of an appeal by the licensee, the notification of planned changes or anticipated noncompliance by the licensee, or the filing of an application by the licensee for the renewal of a license or amendment shall not stay any condition of the license. [06-096 CMR 115]
- (10) The licensee may not use as a defense is an enforcement action that the disruption, cessation, or reduction of licensed operations would have been necessary to maintain compliance with the conditions of the air emission license. [06-096 CMR 115]
- (11) In accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department, the licensee shall:
- A. perform stack testing to demonstrate compliance with the applicable emission standards under circumstances representative of the facility's normal process and operating conditions:
 - 1. within sixty (60) calendar days of receipt of a notification to test from the Department or EPA, if visible emissions, equipment operating parameters, staff inspection, air monitoring or other cause indicate to the Department that equipment may be operating out of compliance with emission standards or license conditions; or
 - 2. pursuant to any other requirement of this license to perform stack testing.
 - B. install or make provisions to install test ports that meet the criteria of 40 CFR part 60, Appendix A, and test platforms, if necessary, and other accommodations necessary to allow emission testing; and
 - C. submit a written report to the Department within thirty (30) days from the date of test completion.
- [06-096 CMR 115]
- (12) If the results of a stack test performed under circumstances representative of the facility's normal process and operating conditions indicate emissions in excess and operating conditions indicate emissions in excess of the applicable standards, then:
- A. within thirty (30) days following receipt of such test results, the licensee shall re-test the non-complying emission source under circumstances representative of the facility's normal process and operating conditions and in accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department; and

- B. The days of violation shall be presumed to include the date of stack test and each and every day of operation thereafter until compliance is demonstrated under normal and representative process and operating conditions, except to the extent that the facility can prove to the satisfaction that there were intervening days during which no violation occurred or that the violation was not continuing in nature; and
- C. The licensee may, upon the approval of the Department following the successful demonstration of compliance at alternative load conditions, operate under such alternative load conditions on an interim basis prior to a demonstration of compliance under normal and representative process and operating conditions.

[06-096 CMR 115]

- (13) Notwithstanding any other provision in the State Implementation Plan approved by the EPA or Section 114(a) of the CAA, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any statute, regulation, or Part 70 license requirement. [06-096 CMR 115]
- (14) The licensee shall maintain records of malfunctions, failures, downtime, and any other similar change in operation of air pollution control systems or the emissions unit itself that would affect emissions and that is not consistent with the terms and conditions of the air emission license. The licensee shall notify the Department within two (2) days or the next state working day, whichever is later, of such occasions when such changes result in an increase of emissions. The licensee shall report all excess emissions in the units of the applicable emission limitations. [06-096 CMR 115]
- (15) Upon the written request of the Department, the licensee shall establish and maintain such records, make such reports, install, use, and maintain such monitoring equipment, sample such emissions (in accordance with such methods, at such locations, at such intervals, and in such a manner as the Department shall prescribe), and provide other information as the Department may reasonably require to determine the licensee's compliance data. [06-096 CMR 115]

SPECIFIC CONDITIONS

(16) Crematory Incinerator

- A. The Crematory Incinerator shall be used for the disposal of Type 4 waste and shall not be used for the disposal of plastics, cytotoxic (antineoplastic) drugs or any radioactive wastes and shall not be used to dispose of any medical waste classified as Type 7 waste, as defined in 06-096 CMR 100 (as amended). [06-096 CMR 115, BACT]

- B. The Crematory Incinerator shall not exceed the unit's maximum design combustion rates. Auxiliary fuel inputs to the primary and secondary chambers shall be liquefied propane gas. Compliance shall be demonstrated through fuel receipts. [06-096 CMR 115, BACT]
- C. The Crematory Incinerator shall not exceed a particulate matter emission limit of 0.12 gr/dscf corrected to 12% CO₂. Licensed allowed emissions for the incinerators shall not exceed the following:

Incinerator Emission Limits
Pounds per hour

	Crem. Incinerator
PM	0.72
PM ₁₀	0.72
SO ₂	0.16
NO _x	0.48
CO	0.34
VOC	0.04

Compliance shall be demonstrated through stack testing by request of the Department, in accordance with the appropriate method found in 40 CFR Part 60, Appendix A.
[06-096 CMR 115, BACT]

- D. Visible emissions from the stack of the Crematory Incinerator shall not exceed 10% on a 6-minute block average basis. [06-096 CMR 115, BACT]
- E. Operating temperature in the secondary chamber shall be maintained at or above 1600°F, with a stack gas retention time, at or above 1600°F, of at least 1.0 second. [06-096 CMR 115, BACT]
- F. To insure an efficient burn, and to prevent odors and visible emissions, the secondary chamber will be preheated, as specified by the manufacturer, until the pyrometer temperature measures at least 1600°F. [06-096 CMR 115, BACT]

- G. Once the burn cycle has commenced by introduction of primary chamber combustion, the Crematory Incinerator shall be operated in an efficient manner, and as specified by the manufacturer, for the period of time between preheat and reaching the set operational temperature to be a minimum of 1600°F in the secondary chamber. The temperature in the secondary chamber shall be maintained at a minimum of 1600°F for the duration of the burn cycle. [06-096 CMR 115, BACT]
- H. A pyrometer and 1/4 inch test port shall be installed and maintained at that location of the incinerator or refractory lined stack which provides sufficient volume to insure a flue gas retention time of not less than 1.0 second at a minimum of 1600°F. [06-096 CMR 115, BACT]
- I. A log will be maintained recording the weight of the charge, preheat time, charging time and the temperature of the secondary chamber every 60 minutes after start-up until, and including, final shutdown time. For facilities operating a chart recorder, the start time, date, and weight charged shall be logged on the chart. [06-096 CMR 115, BACT]
- J. The incinerator operator(s) shall receive adequate training to operate the incinerator in accordance with the manufacturer's specifications and shall be familiar with the terms of the Air Emission License. [06-096 CMR 115, BACT]

DONE AND DATED IN AUGUSTA, MAINE THIS 21st DAY OF September, 2011.

DEPARTMENT OF ENVIRONMENTAL PROTECTION

BY: Melanie [Signature]
PATRICIA W. AHO, ACTING COMMISSIONER

The term of this license shall be five (5) years from the signature date above.

PLEASE NOTE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

Date of initial receipt of application: 07/21/2011

Date of application acceptance: 08/01/2011

Date filed with the Board of Environmental Protection:

This Order prepared by N. Lynn Cornfield, Bureau of Air Quality.

