

CONST. 1975
STA 1304+00 TO 1316+00 LT. SB.
INSTALL 6" X 1200' U.D. TYPE B,
INV. TO BE 3'-3" BELOW SUBGRADE

STA 1316+00 21' LT TO 1316+50 65' LT SB
INSTALL 6" X 1200' U.D. OUTLET

STA 1317+00 TO 1319+50' SB
PLACE EROSION CONTROL
MESH (STANDARD) IN DITCH RT.

STA 1318+00.16 SB 12' LT. =
STA 1318+00.16 RAMP "A"

CONST. 1975
STA 1319+76, SKD AND LT. 30' SB
INSTALL 42" 160' RCP CL III

STA 1317+00 TO 1319+75 SB
PLACE EROSION CONTROL
MESH (STANDARD) IN DITCH LT.

CONST. 1975
STA 1331+00 TO 1335+00 LT. SB
INSTALL 450' TYPE "B" U.D.
STA 1335+50 TO 1336+75 LT. SB
INSTALL 6" X 125' U.D. OUTLET

STA 1320+50 TO 1324+00 SB LT.
PLACE EROSION CONTROL MESH
(STANDARD) IN DITCH LT.
RAMP "A"
PI STA. 33+57.43
A = 3'-01'-01.4
D = 3'-00'-00"
T = 130.60'
L = 300.57'
R = 1905.86'
E = 5.93'

