



MAINE FOREST SERVICE TEMPORARY BRIDGE COST-SHARE PROGRAM BRIDGE SPECIFICATIONS

To be eligible for reimbursement through the Maine Forest Service Temporary Bridge Cost Share program, bridges must meet the minimum specifications in the table below:

Minimum Bridge Specs	
	Hardwood or hemlock (no popple);
Species	no rot or seams
# of panels per bridge	3
Panel length	16-20 ft.
Panel width	4 ft.
Timber beams	Minimum dimensions of 6 x 8in.
Steel rods	Minimum gauge of 1 in.

Suggested: Below is a materials list and specifications for a <u>suggested</u> wooden bridge design:

Three-Panel, 20' Wood Portable Skidder Bridge (Standard Design):

Materials and Specifications for (One) Three-Panel Bridge

- ► Hardwood or softwood beams
 - \Box (18) 6" x 8" x 20'
 - \Box (6) 6" x 8" x 16'
- ► (18) Threaded Rod 1" 8 (coarse thread) x 4', cut and thread checked. (A-307 Rod)
- ▶ (36) USS Flat Washers, 1½"
- ▶ (36) USS Flat Washers, 1"
- \blacktriangleright (36) Hex Nuts, 1" 8 GR 5
- ▶ (123) Flat-Head Log Cabin Screws
- ▶ (12) Steel Sleeves: Extra Strong Steel Pipe w/nominal diameter of $1\frac{1}{2}$ "; outside diameter = 1.9"; inside diameter = 1.5"; wall thickness = .200"; length = 6"

A 'heavy duty' design consisting of larger timbers is also available from MFS.

