

CONNOR CONSOLIDATED SCHOOL

1581 VAN BUREN RD.
CONNOR, MAINE 04736

SHEET INDEX


G0	COVER
C001	GENERAL NOTES & ABBREVIATIONS
C101	PROPOSED SITE PLAN
C501	SITE DETAILS
C502	SITE DETAILS
C503	SITE DETAILS
C504	SITE DETAILS
S001	STRUCTURAL NOTES
S002	STRUCTURAL NOTES
S101	FOUNDATION AND ROOF FRAMING PLANS
S200	STRUCTURAL FRONT ELEVATION
S300	STRUCTURAL SECTION
S301	STRUCTURAL SECTION
S302	STRUCTURAL SECTION
S303	STRUCTURAL SECTION
A001	ABBREVIATIONS, SYMBOLS & NOTES
A002	ACCESSIBILITY REQUIREMENTS
A003	PARTITION TYPES / WALL SECTIONS
AD101	FIRST FLOOR DEMOLITION PLAN
A101	FIRST FLOOR PLAN
A102	ROOF PLAN AND REFLECTED CEILING PLAN
A201	EXTERIOR ELEVATION
A301	BUILDING SECTIONS
A401	ENLARGED PLANS
A501	MILLWORK DETAILS
A601	SCHEDULES
P-001	PLUMBING NOTES, SYMBOLS & ABBREVIATIONS
PD101	PLUMBING DOMESTIC FIRST FLOOR PLAN DEMOLITION PLAN
P-101	DOMESTIC AND DWV PLUMBING PLANS
P-501	PLUMBING DETAILS & SCHEDULES
M-001	MECHANICAL NOTES, SYMBOLS & ABBREVIATIONS
MD101	MECHANICAL HVAC FIRST FLOOR DEMOLITION PLAN
MD102	MECHANICAL PIPING FIRST FLOOR DEMOLITION PLAN
MH101	MECHANICAL HVAC FIRST FLOOR PLAN
MP101	MECHANICAL PIPING FIRST FLOOR PLAN
M-301	MECHANICAL SECTION
M-501	MECHANICAL DETAILS
M-502	MECHANICAL DETAILS
M-503	MECHANICAL DETAILS
M-504	MECHANICAL DETAILS
M-601	MECHANICAL SCHEDULES
M-602	MECHANICAL SCHEDULES
M-701	MECHANICAL SEQUENCES OF OPERATION
E-001	ELECTRICAL ABBREVIATIONS, NOTES & SYMBOLS
E-101	ELECTRICAL SITE PLAN
ED101	ELECTRICAL LIGHTING DEMOLITION PLAN
ED102	ELECTRICAL POWER & SYSTEMS DEMOLITION
EL101	ELECTRICAL LIGHTING FIRST FLOOR PLAN
EP101	ELECTRICAL POWER FIRST FLOOR PLAN
E-501	ELECTRICAL DETAILS
E-601	ELECTRICAL SCHEDULES

ISSUED FOR BID

2025.04.22



HALEY WARD
ENGINEERING | ENVIRONMENTAL | SURVEYING



FILE LOCATION: P:\MET\0377\BUREAU OF GENERAL SERVICES\0365\CONNER SCHOOL RENOVATIONS\MG0302.CAD - FILESCAL\10377.0365.COT DWG, 2025.04.18, 3:24 PM

EROSION AND SEDIMENTATION CONTROL NOTES

- EROSION AND SEDIMENT CONTROL, BEST MANAGEMENT PRACTICES (BMP) SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OR SOIL DISTURBANCE ACTIVITIES. BMPs SHALL COMPLY WITH THE MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION RULES AND REGULATIONS AND MAINE EROSION AND SEDIMENT CONTROL PRACTICES FIELD GUIDE FOR CONTRACTORS: [HTTPS://WWW.MAINE.GOV/DEP/LAND/EROSION/VSCBAMPS/ESC_BMP_FIELD.PDF](https://www.maine.gov/dep/land/erosion/vscbamps/esc_bmp_field.pdf)
- EROSION CONTROL MEASURES WITHIN 50 FEET OF PROTECTED NATURAL RESOURCES SHALL HAVE A DOUBLE PERIMETER EROSION CONTROL AND DISTURBED AREAS MUST BE TEMPORARILY OR PERMANENTLY STABILIZED WITHIN 7 DAYS.
- OPEN AREAS THAT ARE STRIPPED OR GRADED SHALL BE LIMITED TO ONE ACRE OR NO LARGER THAN CAN BE MULCHED IN ONE DAY.
- SEDIMENT BARRIERS SHALL BE PLACED DOWNGRADIENT OF ALL STOCKPILES. STORMWATER RUNOFF SHOULD BE PREVENTED FROM RUNNING INTO STOCKPILES.
- MINIMUM EROSION CONTROL MEASURES WILL NEED TO BE IMPLEMENTED AND THE CONTRACTOR WILL BE RESPONSIBLE TO MAINTAIN ALL COMPONENTS OF THE EROSION CONTROL PLAN UNTIL THE SITE IS FULLY STABILIZED. HOWEVER, BASED ON SITE AND WEATHER CONDITIONS DURING CONSTRUCTION, ADDITIONAL EROSION CONTROL MEASURES MAY NEED TO BE IMPLEMENTED. ALL AREAS OF INSTABILITY AND EROSION MUST BE REPAIRED IMMEDIATELY DURING CONSTRUCTION AND NEED TO BE MAINTAINED UNTIL THE SITE IS FULLY STABILIZED OR VEGETATION IS ESTABLISHED. A CONSTRUCTION LOG MUST BE MAINTAINED FOR THE EROSION AND SEDIMENTATION CONTROL INSPECTIONS AND MAINTENANCE.
- MINIMIZE DISTURBED AREA AND PROTECT NATURAL DOWNGRAIENT BUFFER AREAS TO THE EXTENT PRACTICABLE. CONTROL STORMWATER VOLUME AND VELOCITY WITHIN THE SITE TO MINIMIZE SOIL EROSION.
- WHENEVER PRACTICABLE, NO DISTURBANCE ACTIVITIES SHOULD TAKE PLACE WITHIN 50 FEET OF ANY PROTECTED NATURAL RESOURCE. IF DISTURBANCE ACTIVITIES TAKE PLACE BETWEEN 30 FEET AND 50 FEET OF ANY PROTECTED NATURAL RESOURCE, AND STORMWATER DISCHARGES THROUGH THE DISTURBED AREAS TOWARD THE PROTECTED NATURAL RESOURCE, PERIMETER EROSION CONTROLS MUST BE DOUBLED. IF DISTURBANCE ACTIVITIES TAKE PLACE LESS THAN 30 FEET FROM ANY PROTECTED NATURAL RESOURCE, AND STORMWATER DISCHARGES THROUGH THE DISTURBED AREAS TOWARD THE PROTECTED NATURAL RESOURCE, PERIMETER EROSION CONTROLS MUST BE DOUBLED, AND DISTURBED AREAS MUST BE TEMPORARILY OR PERMANENTLY STABILIZED WITHIN 7 DAYS.
- PRIOR TO CONSTRUCTION, PROPERLY INSTALL SEDIMENT BARRIERS AT THE DOWN GRADIENT EDGE OF ANY AREA TO BE DISTURBED AND ADJACENT TO ANY DRAINAGE CHANNELS WITHIN THE DISTURBED AREA. SEDIMENT BARRIERS SHOULD BE INSTALLED DOWNGRADIENT OF SOIL OR SEDIMENT STOCKPILES AND STORMWATER PREVENTED FROM RUNNING ONTO THE STOCKPILE. MAINTAIN THE SEDIMENT BARRIERS BY REMOVING ACCUMULATED SEDIMENT, OR REMOVING AND REPLACING THE BARRIER, UNTIL THE DISTURBED AREA IS PERMANENTLY STABILIZED. WHERE A DISTURBED AREA TO A STORM DRAIN INLET OCCURS, IF THE STORM DRAIN CARRIES WATER DIRECTLY TO A SURFACE WATER AND YOU HAVE AUTHORITY TO ACCESS THE STORM DRAIN INLET, YOU MUST INSTALL AND MAINTAIN PROTECTION MEASURES THAT REMOVE SEDIMENT FROM THE DISCHARGE.
- PRIOR TO CONSTRUCTION, PROPERLY INSTALL A STABILIZED CONSTRUCTION ENTRANCE (SCE) AT ALL POINTS OF EGRESS FROM THE SITE. THE SCE IS A STABILIZED PAD OF AGGREGATE, UNDERLAIN BY A GEOTEXTILE FILTER FABRIC, USED TO PREVENT TRAFFIC FROM TRACKING MATERIAL AWAY FROM THE SITE ONTO PUBLIC ROWS. MAINTAIN THE SCE UNTIL ALL DISTURBED AREAS ARE STABILIZED.
- INSTALL SILT FENCES OR SEDIMENT BARRIERS ALONG CONTOUR DIVIDING FLAT AND STEEP SLOPES, AREAS WITH DIFFERENT DISTURBANCE SCHEDULES, AROUND TEMPORARY STOCKPILES OR IN OTHER UNSPECIFIED POSSIBLE CIRCUMSTANCES SHOULD BE CONSIDERED BY THE CONTRACTOR. THE INTENT OF SUCH INTERIOR SILT FENCES IS TO LIMIT SEDIMENT TRANSPORT WITHIN THE SITE TOWARD THE PROTECTED RESOURCES.
- SILT FENCE AND SEDIMENT BARRIERS WILL BE INSPECTED, REPLACED AND/OR REPAIRED IMMEDIATELY FOLLOWING ANY SIGNIFICANT RAINFALL (0.5 INCH OR GREATER) OR SNOW MELT OR LOSS OF SERVICEABILITY DUE TO SEDIMENT ACCUMULATION. AT A MINIMUM, ALL EROSION CONTROL DEVICES WILL BE OBSERVED WEEKLY.
- EROSION CONTROL MIX BERMS SHALL CONSIST OF A MIX OF SHREDDED WOOD FRAGMENTS AND GRIT THAT MUST BE WELL GRADED WITH AN ORGANIC CONTENT THAT IS BETWEEN 50 AND 100% OF WEIGHT. MINERAL PORTION OF THE MIX SHOULD BE NATURALLY INCLUDED IN THE PRODUCT WITH NO ROCKS GRATER THAN 4-INCHES OR LARGE AMOUNTS OF FINES (SILTS AND CLAYS). MIX SHOULD BE FREE OF REFUSE OR MATERIAL TOXIC TO PLANT GROWTH.
- EROSION CONTROL MIX SHALL BE USED ON SLOPES 3:1 OR SHALLOWER. SLOPES BETWEEN 3:1 AND 2:1 SHALL HAVE EROSION CONTROL BLANKET. SLOPES BETWEEN 2:1 AND 1.5:1 SHALL HAVE RIP RAP. SLOPES GREATER THAN 1.5:1 ARE PROHIBITED.
- HAYBALES MAY BE INSTALLED IN ADDITION TO SILT FENCE OR USED AROUND INLETS TO PROVIDE ADDITIONAL SEDIMENT CAPTURE AND CONTROL.
- EROSION CONTROL BLANKETS INTENDED FOR TEMPORARY SLOPE OR CHANNEL STABILIZATION SIMILAR TO NORTH AMERICAN GREEN ERONET BIODEGRADABLE EROSION CONTROL BLANKET OR SIMILAR.
- DURING THE CONSTRUCTION PHASE, INTERCEPTED SEDIMENT WILL BE RETURNED TO CONSTRUCTION SITE.
- A SUITABLE BINDER SUCH AS TERRACK WILL BE USED ON THE HAY MULCH FOR WIND CONTROL.
- IF FINAL SEEDING OF DISTURBED AREAS IS NOT COMPLETED BY SEPTEMBER 15TH OF THE YEAR OF CONSTRUCTION, THEN ON THAT DATE THESE AREAS WILL BE GRADED AND SEEDED WITH WINTER RYE AT THE RATE OF 112 POUNDS PER ACRE OR 3 POUNDS PER 1000 SQUARE FEET. THE RYE SEEDING WILL BE PRECEDED BY AN APPLICATION OF 3 TONS OF LIME AND 800 LBS. OF 10-20-20 FERTILIZER OR ITS EQUIVALENT. MULCH WILL BE APPLIED AT A RATE OF 90 POUNDS PER 1000 SQUARE FEET.
- IF THE RYE SEEDING CANNOT BE COMPLETED BY OCTOBER 1ST OR IF THE RYE DOES NOT MAKE ADEQUATE GROWTH BY DECEMBER 1ST, THEN ON THOSE DATES, HAY MULCH WILL BE APPLIED AT 150 POUNDS PER 1000 SQUARE FEET.
- WITHIN 7 DAYS OF THE CESSATION OF CONSTRUCTION ACTIVITIES IN AN AREA THAT WILL NOT BE WORKED FOR MORE THAN 7 DAYS, STABILIZE ANY EXPOSED SOIL WITH MULCH, OR OTHER NON-ERODIBLE COVER. STABILIZE AREAS WITHIN 75 FEET OF A WETLAND OR WATER BODY WITHIN 48 HOURS OF THE INITIAL DISTURBANCE OF THE SOIL OR PRIOR TO ANY STORM EVENT, WHICHEVER COMES FIRST.
- REMOVE ANY TEMPORARY CONTROL MEASURES, SUCH AS SILT FENCE, WITHIN 30 DAYS AFTER PERMANENT STABILIZATION IS ATTAINED. REMOVE ANY ACCUMULATED SEDIMENTS AND STABILIZE.
- PERMANENT STABILIZATION: IF THE AREA WILL NOT BE WORKED FOR MORE THAN ONE YEAR OR HAS BEEN BROUGHT TO FINAL GRADE, THEN PERMANENTLY STABILIZE THE AREA WITHIN 7 DAYS BY PLANTING VEGETATION, SEEDING, SOD, OR THROUGH THE USE OF PERMANENT MULCH, OR RIP-RAP, OR ROAD SUB-BASE. IF USING VEGETATION FOR STABILIZATION, SELECT THE PROPER VEGETATION FOR THE LIGHT, MOISTURE, AND SOIL CONDITIONS, AMEND AREAS OF DISTURBED SUBSOILS WITH TOPSOIL, COMPOST, OR FERTILIZERS; PROTECT SEEDED AREAS WITH MULCH OR, IF NECESSARY, EROSION CONTROL BLANKETS; AND SCHEDULE SODDING, PLANTING, AND SEEDING SO TO AVOID DIE-OFF FROM SUMMER DROUGHT AND FALL FROSTS. NEWLY SEEDD OR SODDED AREAS MUST BE PROTECTED FROM VEHICLE TRAFFIC, EXCESSIVE PEDESTRIAN TRAFFIC, AND CONCENTRATED RUNOFF UNTIL THE VEGETATION IS WELL-ESTABLISHED WITH 90% COVER BY HEALTHY VEGETATION. IF NECESSARY, AREAS MUST BE REWORKED AND RE-STABILIZED IF GERMINATION IS SPARSE, PLANT COVERAGE IS SPOTTY, OR TOPSOIL EROSION IS EVIDENT. ONE OR MORE OF THE FOLLOWING MAY APPLY TO A PARTICULAR SITE.
 - SEEDD AREAS: FOR SEEDD AREAS, PERMANENT STABILIZATION MEANS A 90% COVER OF THE DISTURBED AREA WITH MATURE, HEALTHY PLANTS WITH NO EVIDENCE OF WASHING OR RILLING OF THE TOPSOIL.
 - SODDED AREAS: FOR SODDED AREAS, PERMANENT STABILIZATION MEANS THE COMPLETE BINDING OF THE SOD ROOTS INTO THE UNDERLYING SOIL WITH NO SLUMPING OF THE SOD OR DIE-OFF.
 - PERMANENT MULCH: FOR MULCHED AREAS, PERMANENT MULCHING MEANS TOTAL COVERAGE OF THE EXPOSED AREA WITH AN APPROVED MULCH MATERIAL. EROSION CONTROL MIX MAY BE USED AS MULCH FOR PERMANENT STABILIZATION ACCORDING TO THE APPROVED APPLICATION RATES AND LIMITATIONS.
 - RIP-RAP: FOR AREAS STABILIZED WITH RIP-RAP, PERMANENT STABILIZATION MEANS THAT SLOPES STABILIZED WITH RIP-RAP HAVE AN APPROPRIATE BACKING OF A WELL-GRADED GRAVEL OR APPROVED GEOTEXTILE TO PREVENT SOIL MOVEMENT FROM BEHIND THE RIP-RAP. STONE MUST BE SIZED APPROPRIATELY. IT IS RECOMMENDED THAT ANGULAR STONE BE USED.
 - PAVED AREAS: FOR PAVED AREAS, PERMANENT STABILIZATION MEANS THE PLACEMENT OF THE COMPACTED GRAVEL SUBBASE IS COMPLETED, PROVIDED IT IS FREE OF FINE MATERIALS THAT MAY RUNOFF WITH A RAIN EVENT.
 - DITCHES, CHANNELS, AND SWALES: FOR OPEN CHANNELS, PERMANENT STABILIZATION MEANS THE CHANNEL IS STABILIZED WITH A 90% COVER OF HEALTHY VEGETATION, WITH A WELL-GRADED RIP-RAP LINING, TURF REINFORCEMENT MAT, OR WITH ANOTHER NON-EROSIVE LINING SUCH AS CONCRETE OR ASPHALT PAVEMENT. THERE MUST BE NO EVIDENCE OF SLUMPING OF THE CHANNEL LINING, UNDERCUTTING OF THE CHANNEL BANKS, OR DOWN-CUTTING OF THE CHANNEL.
- ALL DISTURBED AREAS WILL BE SEEDD WITH 2.5 LBS. RED PESQUE AND 0.5 LBS. RYE GRASS PER 1,000 SQUARE FEET AND MULCHED AT A RATE OF 90 LBS. PER 1,000 SQUARE FEET OR EQUIVALENT APPLICATION OF SEED AND MULCH.
- IF PERMANENT BMP LOCATIONS ARE TO BE USED AS SEDIMENT TRAPS THEN THE AREAS OF THE AREAS OF THE BMPs SHALL BE RESTORED AS NEEDED TO PREPARE FOR LONG TERM USE, SUCH AS BY REMOVAL OF SEDIMENT, REGRADEING ELEVATIONS, INSTALLING UNDERDRAINS (WHERE APPROPRIATE) AND STABILIZING THE AREA.
- WINTER CONSTRUCTION IS CONSTRUCTION ACTIVITY PERFORMED DURING THE PERIOD FROM NOVEMBER 1 THROUGH APRIL 15. IF DISTURBED AREAS ARE NOT STABILIZED WITH PERMANENT MEASURES BY NOVEMBER 1 OR NEW SOIL DISTURBANCE OCCURS AFTER NOVEMBER 1, BUT BEFORE APRIL 15, THEN THESE AREAS MUST BE PROTECTED AND RUNOFF FROM THEM MUST BE CONTROLLED BY ADDITIONAL MEASURES AND RESTRICTIONS.
 - SITE STABILIZATION: FOR WINTER STABILIZATION, HAY MULCH IS APPLIED AT TWICE THE STANDARD TEMPORARY STABILIZATION RATE. AT THE END OF EACH CONSTRUCTION DAY, AREAS THAT HAVE BEEN BROUGHT TO FINAL GRADE MUST BE STABILIZED. MULCH MAY NOT BE SPREAD ON TOP OF SNOW.
 - SEDIMENT BARRIERS: ALL AREAS WITHIN 75 FEET OF A PROTECTED NATURAL RESOURCE MUST BE PROTECTED WITH A DOUBLE ROW OF SEDIMENT BARRIERS.
 - DITCH: ALL VEGETATED DITCH LINES THAT HAVE NOT BEEN STABILIZED BY NOVEMBER 1, OR WILL BE WORKED DURING THE WINTER CONSTRUCTION PERIOD, MUST BE STABILIZED WITH AN APPROPRIATE STONE LINING BACKED BY AN APPROPRIATE GRAVEL BED OR GEOTEXTILE UNLESS SPECIFICALLY RELEASED FROM THIS STANDARD BY THE DEPARTMENT.
 - SLOPES: MULCH NETTING MUST BE USED TO ANCHOR MULCH ON ALL SLOPES GREATER THAN 8% UNLESS EROSION CONTROL BLANKETS OR EROSION CONTROL MIX IS BEING USED ON THESE SLOPES.
- STORMWATER CHANNELS: DITCHES, SWALES, AND OTHER OPEN STORMWATER CHANNELS MUST BE DESIGNED, CONSTRUCTED, AND STABILIZED USING MEASURES THAT ACHIEVE LONG-TERM EROSION CONTROL. DITCHES, SWALES AND OTHER OPEN STORMWATER CHANNELS MUST BE SIZED TO HANDLE, AT A MINIMUM, THE EXPECTED VOLUME RUN-OFF. EACH CHANNEL SHOULD BE CONSTRUCTED IN SECTIONS SO THAT THE SECTIONS GRADING, SHAPING, AND INSTALLATION OF THE PERMANENT LINING CAN BE COMPLETED THE SAME DAY. IF A CHANNEL'S FINAL GRADING OR LINING INSTALLATION MUST BE DELAYED, THEN DIVERSION BERMS MUST BE USED TO DIVERT STORMWATER AWAY FROM THE CHANNEL. PROPERLY-SPACED CHECK DAMS MUST BE INSTALLED IN THE CHANNEL, TO SLOW THE WATER VELOCITY, AND A TEMPORARY LINING INSTALLED ALONG THE CHANNEL TO PREVENT SCOURING.
 - THE CHANNEL SHOULD RECEIVE ADEQUATE ROUTINE MAINTENANCE TO MAINTAIN CAPACITY AND PREVENT OR CORRECT ANY EROSION OF THE CHANNEL'S BOTTOM OR SIDE SLOPES.
 - WHEN THE WATERSHED DRAINING TO A DITCH OR SWALE IS LESS THAN 1 ACRE OF TOTAL DRAINAGE AND LESS THAN 1/4 ACRE OF IMPERVIOUS AREA, DIVERSION OF RUNOFF TO ADJACENT WOODED OR OTHERWISE VEGETATED BUFFER AREAS IS ENCOURAGED WHERE THE OPPORTUNITY EXISTS.
- CULVERTS: CULVERTS MUST BE SIZED TO AVOID UNINTENDED FLOODING OF UPSTREAM AREAS OR FREQUENT OVERTOPPING OF ROADWAYS. CULVERT INLETS MUST BE PROTECTED WITH APPROPRIATE MATERIALS FOR THE EXPECTED ENTRANCE VELOCITY, AND PROTECTION MUST EXTEND AT LEAST AS HIGH AS THE EXPECTED MAXIMUM ELEVATION OF STORAGE BEHIND THE CULVERT. CULVERT OUTLET DESIGN MUST INCORPORATE MEASURES, SUCH AS APRONS, TO PREVENT SCOUR OF THE STREAM CHANNEL. OUTLET PROTECTION MEASURES MUST BE DESIGNED TO STAY WITHIN THE CHANNEL LIMITS. THE DESIGN MUST TAKE ACCOUNT OF TAILWATER DEPTH.
- ADDITIONAL REQUIREMENTS MAY BE APPLIED ON A SITE-SPECIFIC BASIS.

INSPECTION AND MAINTENANCE

THE FOLLOWING STANDARDS MUST BE MET DURING CONSTRUCTION:

- INSPECT DISTURBED AND IMPERVIOUS AREAS, EROSION CONTROL MEASURES, MATERIALS STORAGE AREAS THAT ARE EXPOSED TO PRECIPITATION, AND LOCATIONS WHERE VEHICLES ENTER OR EXIT THE SITE. INSPECT THESE AREAS AT LEAST ONCE A WEEK AS WELL AS BEFORE AND WITHIN 24 HOURS AFTER A STORM EVENT (0.5" OR MORE IN A CONSECUTIVE 24-HOUR PERIOD), AND PRIOR TO COMPLETING PERMANENT STABILIZATION MEASURES. A PERSON WITH KNOWLEDGE OF EROSION AND STORMWATER CONTROL, INCLUDING THE STANDARDS AND CONDITIONS IN THE PERMIT, SHALL CONDUCT THE INSPECTIONS.
- IF BEST MANAGEMENT PRACTICES (BMPs) NEED TO BE REPAIRED, THE REPAIR WORK SHOULD BE INITIATED UPON DISCOVERY OF THE PROBLEM BUT NO LATER THAN THE END OF THE NEXT WORKDAY. IF ADDITIONAL BMPs OR SIGNIFICANT REPAIR OF BMPs ARE NECESSARY, IMPLEMENTATION MUST BE COMPLETED WITHIN 7 CALENDAR DAYS AND PRIOR TO ANY STORM EVENT (0.5" OR MORE IN A CONSECUTIVE 24-HOUR PERIOD). ALL MEASURES MUST BE MAINTAINED IN EFFECTIVE OPERATING CONDITION UNTIL AREAS ARE PERMANENTLY STABILIZED.
- KEEP A LOG (REPORT) SUMMARIZING THE INSPECTIONS AND ANY CORRECTIVE ACTION TAKEN. THE LOG MUST INCLUDE THE NAME(S) AND QUALIFICATIONS OF THE PERSON MAKING THE INSPECTIONS, THE DATE(S) OF THE INSPECTIONS, AND MAJOR OBSERVATIONS ABOUT THE OPERATION AND MAINTENANCE OF EROSION AND SEDIMENTATION CONTROLS, MATERIALS STORAGE AREAS, AND VEHICLES ACCESS POINTS TO THE PARCEL. MAJOR OBSERVATIONS MUST INCLUDE BMPs THAT NEED MAINTENANCE, BMPs THAT FAILED TO OPERATE AS DESIGNED OR PROVIDED INADEQUATE FOR A PARTICULAR LOCATION, AND LOCATION(S) WHERE ADDITIONAL BMPs ARE NEEDED. FOR EACH BMP REQUIRING MAINTENANCE, BMP NEEDING REPLACEMENT, AND LOCATION NEEDING ADDITIONAL BMPs, NOTE IN THE LOG THE CORRECTIVE ACTION TAKEN AND WHEN IT WAS TAKEN.

HOUSEKEEPING

- SPILL PREVENTION: CONTROLS MUST BE USED TO PREVENT POLLUTANTS FROM CONSTRUCTION AND WASTE MATERIALS STORED ON SITE TO ENTER STORMWATER, WHICH INCLUDES STORAGE PRACTICES TO MINIMIZE EXPOSURE OF THE MATERIALS TO STORMWATER. THE SITE CONTRACTOR OR OPERATOR MUST DEVELOP, AND IMPLEMENT AS NECESSARY, APPROPRIATE SPILL PREVENTION, CONTAINMENT, AND RESPONSE PLANNING MEASURES.
- GROUNDWATER PROTECTION: DURING CONSTRUCTION, LIQUID PETROLEUM PRODUCTS AND OTHER HAZARDOUS MATERIALS WITH THE POTENTIAL TO CONTAMINATE GROUNDWATER MAY NOT BE STORED OR HANDLED IN AREAS OF THE SITE DRAINING TO AN INFILTRATION AREA. AN "INFILTRATION AREA" IS ANY AREA OF THE SITE THAT BY DESIGN OR AS A RESULT OF SOILS, TOPOGRAPHY AND OTHER RELEVANT FACTORS ACCUMULATES RUNOFF THAT INFILTRATES INTO THE SOIL. DIKES, BERMS, SUMPS, AND OTHER FORMS OF SECONDARY CONTAMINANT THAT PREVENT DISCHARGE TO GROUNDWATER MAY BE USED TO ISOLATE PORTIONS OF THE SITE FOR THE PURPOSES OF STORAGE AND HANDLING OF THESE MATERIALS. ANY PROJECT PROPOSING INFILTRATION OF STORMWATER MUST PROVIDE ADEQUATE PRE-TREATMENT OF STORMWATER PRIOR TO DISCHARGE OF STORMWATER TO THE INFILTRATION AREA, OR PROVIDE FOR TREATMENT WITHIN THE INFILTRATION AREA, IN ORDER TO PREVENT THE ACCUMULATION OF FINES, REDUCTION IN INFILTRATION RATE, AND CONSEQUENT FLOODING AND DESTABILIZATION.
- FUGITIVE SEDIMENT AND DUST: ACTIONS MUST BE TAKEN TO ENSURE THAT ACTIVITIES DO NOT RESULT IN NOTICEABLE EROSION OF SOILS OR FUGITIVE DUST EMISSIONS DURING OR AFTER CONSTRUCTION. OIL MAY NOT BE USED FOR DUST CONTROL, BUT OTHER WATER ADITIVES MAY BE CONSIDERED AS NEEDED. A STABILIZED CONSTRUCTION ENTRANCE (SCE) SHOULD BE INCLUDED TO MINIMIZE TRACKING OF MUD AND SEDIMENT. IF OFF-SITE TRACKING OCCURS, PUBLIC ROADS SHOULD BE SWEEP IMMEDIATELY AND NO LESS THAN ONCE A WEEK AND PRIOR TO SIGNIFICANT STORM EVENTS. OPERATIONS DURING DRY MONTHS, THAT EXPERIENCE FUGITIVE DUST PROBLEMS, SHOULD WET DOWN UNPAVED ACCESS ROADS ONCE A WEEK OR MORE FREQUENTLY AS NEEDED WITH A WATER ADITIVE TO SUPPRESS FUGITIVE SEDIMENT AND DUST.

- DEBRIS AND OTHER MATERIALS: MINIMIZE THE EXPOSURE OF CONSTRUCTION DEBRIS, BUILDING AND LANDSCAPING MATERIALS, TRASH, FERTILIZERS, PESTICIDES, HERBICIDES, DETERGENTS, SANITARY WASTE AND OTHER MATERIALS TO PRECIPITATION AND STORMWATER RUNOFF. THESE MATERIALS MUST BE PREVENTED FROM BECOMING A POLLUTANT SOURCE.
- EXCAVATION DE-WATERING: EXCAVATION DE-WATERING IS THE REMOVAL OF WATER FROM TRENCHES, FOUNDATIONS, COFFER DAMS, PONDS, AND OTHER AREAS WITHIN THE CONSTRUCTION AREA THAT RETAIN WATER AFTER EXCAVATION. IN MOST CASES THE COLLECTED WATER IS HEAVILY SILTED AND HINDERS CORRECT AND SAFE CONSTRUCTION PRACTICES. THE COLLECTED WATER REMOVED FROM THE PONDED AREA, EITHER THROUGH GRAVITY OR PUMPING, MUST BE SPREAD THROUGH NATURAL WOODED BUFFERS OR REMOVED TO AREAS THAT ARE SPECIFICALLY DESIGNED TO COLLECT THE MAXIMUM AMOUNT OF SEDIMENT POSSIBLE, LIKE A COFFERDAM SEDIMENTATION BASIN. AVOID ALLOWING THE WATER TO FLOW OVER DISTURBED AREAS OF THE SITE. EQUIVALENT MEASURES MAY BE TAKEN IF APPROVED BY THE DEPARTMENT.
- AUTHORIZED NON-STORMWATER DISCHARGES: IDENTIFY AND PREVENT CONTAMINATION BY NON-STORMWATER DISCHARGES. WHERE ALLOWED NON-STORMWATER DISCHARGES EXIST, THEY MUST BE IDENTIFIED AND STEPS SHOULD BE TAKEN TO ENSURE THE IMPLEMENTATION OF APPROPRIATE POLLUTION PREVENTION MEASURES FOR THE NON-STORMWATER COMPONENT(S) OF THE DISCHARGE. AUTHORIZED NON-STORMWATER DISCHARGES ARE:
 - DISCHARGES FROM FIREFIGHTING ACTIVITY;
 - FIRE HYDRANT FLUSHINGS;
 - VEHICLE WASHWATER IF DETERGENTS ARE NOT USED AND WASHING IS LIMITED TO THE EXTERIOR OF VEHICLES (ENGINE, UNDERCARRIAGE AND TRANSMISSION WASHING IS PROHIBITED);
 - DUST CONTROL RUNOFF IN ACCORDANCE WITH PERMIT CONDITIONS AND APPENDIX C (I/3);
 - ROUTINE EXTERNAL BUILDING WASHDOWN, NOT INCLUDING SURFACE PAINT REMOVAL, THAT DOES NOT INVOLVE DETERGENTS;
 - PAVEMENT WASHWATER (WHERE SPILLS/LEAKS OF TOXIC OR HAZARDOUS MATERIALS HAVE NOT OCCURRED, UNLESS ALL SPILLED MATERIAL HAD BEEN REMOVED) IF DETERGENTS ARE NOT USED;
 - UNCONTAMINATED AIR CONDITIONING OR COMPRESSOR CONDENSATE;
 - UNCONTAMINATED GROUNDWATER OR SPRING WATER;
 - FOUNDATION OR FOOTER DRAIN-WATER WHERE FLOWS ARE NOT CONTAMINATED;
 - UNCONTAMINATED EXCAVATION DEWATERING (SEE REQUIREMENTS IN APPENDIX C (5));
 - POTABLE WATER SOURCES INCLUDING WATERLINE FLUSHINGS; AND
 - LANDSCAPE IRRIGATION.
- UNAUTHORIZED NON-STORMWATER DISCHARGES: THE DEPARTMENT'S APPROVAL UNDER THIS CHAPTER DOES NOT AUTHORIZE A DISCHARGE THAT IS MIXED WITH A SOURCE OF NON STORMWATER, OTHER THAN THOSE DISCHARGES IN COMPLIANCE WITH APPENDIX C (6). SPECIFICALLY, THE DEPARTMENT'S APPROVAL DOES NOT AUTHORIZE DISCHARGES OF THE FOLLOWING:
 - WASTEWATER FROM THE WASHOUT OR CLEANOUT OF CONCRETE, STUCCO, PAINT, FORM RELEASE OILS, CURING COMPOUNDS OR OTHER CONSTRUCTION MATERIALS;
 - FUELS, OILS OR OTHER POLLUTANTS USED IN VEHICLE AND EQUIPMENT OPERATION AND MAINTENANCE;
 - SOAPS, SOLVENTS, OR DETERGENTS USED IN VEHICLE AND EQUIPMENT WASHING; AND
 - TOXIC OR HAZARDOUS SUBSTANCES FROM A SPILL OR OTHER RELEASE.

GENERAL CONSTRUCTION NOTES

- CONTRACTOR TO PROVIDE OWNER AND ENGINEER WITH A WORK PLAN OUTLINING THE WORK SCHEDULE, TRAFFIC CONTROL PLAN, AND WORK AREA BARRICADING PLAN TO BE APPROVED BY THE OWNER AND ENGINEER PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL COORDINATE ALL CONSTRUCTION WITH THE TOWN, UTILITY COMPANIES, DIG SAFE, AND EMERGENCY SERVICES WHERE APPLICABLE. CONTRACTOR SHALL NOTIFY ALL UTILITIES PRIOR TO COMMENCING WORK TO ALLOW SUFFICIENT TIME TO LOCATE AND MARK THE LOCATION OF ALL BURIED UTILITIES. CONTRACTOR SHALL ALSO CONTACT "DIG SAFE", TELEPHONE NO 811 OR 888-DIG-SAFE. REPAIR OF ANY DAMAGED UTILITY WILL BE INCIDENTAL TO THIS PROJECT.
- THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER IN WRITING OF ANY CONDITION OR OCCURRENCE THAT REPRESENTS A CHANGE IN PROJECT SCOPE. VERBAL NOTIFICATION IS REQUIRED PRIOR TO PROCEEDING WITH THE WORK OF THE PROJECT AND WRITTEN NOTIFICATION MUST BE PROVIDED. REQUESTS FOR FEE ADJUSTMENTS WILL NOT BE CONSIDERED UNLESS PROPER NOTICE IS GIVEN.
- THE CONTRACTOR SHALL PROVIDE ALL LABOR, EQUIPMENT, AND MATERIALS AS REQUIRED TO PERFORM THE WORK AS INDICATED ON THE DRAWINGS AND IN THE SPECIFICATIONS. ALL WORK SHALL BE COMPLETED IN ACCORDANCE WITH THE APPLICABLE FEDERAL, STATE AND LOCAL CODES.
- CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL NECESSARY CONSTRUCTION PERMITS. PERMIT APPLICATIONS SHALL BE SUBMITTED WITH ADEQUATE TIME SO AS NOT TO DELAY CONSTRUCTION.
- THE CONTRACTOR SHALL SUPERVISE AND INSPECT THE WORK OF THIS PROJECT IN AN EFFICIENT AND COMPETENT MANNER. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES USED TO COMPLETE THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THE WORK IS IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. A REPRESENTATIVE OF THE GENERAL CONTRACTOR SHALL BE PRESENT DURING ALL PHASES OF THE WORK.
- SAFETY IS THE RESPONSIBILITY OF THE CONTRACTOR. PERFORM ALL WORK IN ACCORDANCE WITH SAFETY STANDARDS OF APPLICABLE LAWS, BUILDING AND CONSTRUCTION CODES, THE "MANUAL OF ACCIDENT PREVENTION IN CONSTRUCTION" PUBLISHED BY THE ASSOCIATED GENERAL CONTRACTORS OF AMERICA, THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ACT OF 1970, AND THE REQUIREMENTS OF TITLE 9 OF THE CODE OF FEDERAL REGULATIONS, PART 1926, "SAFETY AND HEALTH REGULATIONS FOR CONSTRUCTION".
- THE LOCATIONS OF ALL PROPERTY LINES AND RIGHT OF WAYS ARE APPROXIMATE (SHOWN FOR REFERENCE ONLY), UNLESS NOTED OTHERWISE. PROPERTY LINES AND RIGHT OF WAYS SHOWN ARE NOT INTENDED TO REPRESENT LEGAL BOUNDARIES.
- THE LOCATION, TYPE AND SIZE OF EXISTING PIPES, DUCTS, CONDUITS AND OTHER UNDERGROUND STRUCTURES SHOWN ON THE DRAWINGS ARE NOT WARRANTED TO BE EXACT NOR IS IT WARRANTED THAT ALL UNDERGROUND STRUCTURES ARE SHOWN. CONTRACTOR SHALL FIELD VERIFY ALL UTILITY LOCATIONS PRIOR TO COMMENCEMENT OF CONSTRUCTION. DEPTH OF SERVICES ARE UNKNOWN AND SHALL BE FIELD VERIFIED BY THE CONTRACTOR. EXCAVATING TEST PITS AS NECESSARY TO VERIFY UTILITY LOCATIONS AND DEPTHS SHALL BE INCIDENTAL TO THIS PROJECT.
- THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING TOPOGRAPHY AND EXISTING CONDITIONS PRIOR TO CONSTRUCTION.
- CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING PIPE SIZES, INVERTS, AND LOCATIONS, AND SHALL INCLUDE IN SUBMITTAL PRIOR TO ORDERING.
- LAYOUT OF THE PROJECT IS THE RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE APPROVED BY THE ENGINEER. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL GRADE AND LAYOUT CONTROL. LAYOUT SHOULD BE PERFORMED WITH SURVEY EQUIPMENT AND OVERSEEN BY A LICENSED SURVEYOR. A CAD FILE WILL BE AVAILABLE TO THE CONTRACTOR.
- CONTRACTOR SHALL BE REQUIRED TO PROVIDE DUST CONTROL FOR PROJECT WHICH CAN INCLUDE, BUT IS NOT LIMITED TO, WATER AND CALCIUM CHLORIDE. COST IS INCIDENTAL TO THE PROJECT.
- RESTRICT ACCESS TO SITE THROUGH THE USE OF APPROPRIATE SIGNAGE, GATES, BARRIERS, FENCES, ETC. SITE SHALL BE LEFT WITH APPROPRIATE SAFETY MEASURES IN PLACE DURING NON-WORKING HOURS. NO TRENCH SHALL BE LEFT OPEN DURING NON-WORKING HOURS. SITE SAFETY IS THE RESPONSIBILITY OF CONTRACTOR, DURING BOTH WORKING AND NON-WORKING HOURS.
- CONTRACTOR SHALL PERFORM ALL CONSTRUCTION ACTIVITIES RELATED TO THE PROJECT WITHIN THE CONFINES OF THE SITE. ANY ACTIVITY, MATERIAL STORAGE ETC., TAKING PLACE ON PRIVATE PROPERTY SHALL BE WITH THE EXPRESS WRITTEN PERMISSION OF THE OWNER AND PROPERTY OWNER AND COORDINATED WITH THE OWNER. WORK OUTSIDE OF THESE LIMITS MAY BE REQUIRED.
- THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO PREVENT EQUIPMENT FLUIDS FROM REACHING ANY WATER COURSE. ANY INADVERTENT FLUID DISCHARGES SHALL BE IMMEDIATELY CLEANED FROM THE WATERS USING WHATEVER MEANS NECESSARY, AS DETERMINED BY THE ENGINEER.
- CONTRACTOR SHALL BACKFILL TRENCH FOLLOWING EACH DAY'S CONSTRUCTION. NO OPEN TRENCHES WILL BE ALLOWED OVERNIGHT UNLESS APPROVED BY ENGINEER AND PROPERLY BARRICADED (IE. SNOW FENCING, CHAIN LINK FENCING, JERSEY BARRIER OR APPROVED EQUAL. CAUTION RIBBON AND EQUIPMENT PLACEMENT WILL NOT BE APPROVED AS BARRICADING. CONTRACTOR IS RESPONSIBLE TO MAINTAIN TRENCH AS DIRECTED BY THE ENGINEER.
- ALL FINISH SURFACES SHALL BE INSTALLED TO PROMOTE POSITIVE DRAINAGE. IN NO WAY SHALL THE NEW FINISH SURFACES CREATE DRAINAGE PROBLEMS THAT DID NOT EXIST PRIOR TO CONSTRUCTION.
- ALL MATERIALS SCHEDULED FOR REMOVAL SHALL BE DISPOSED OF IN A LEGAL MANNER BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER. THE OWNER HAS THE FIRST RIGHT AND REFUSAL FOR ANY DEMOLITION MATERIALS DISPOSAL OF SURPLUS SOIL MATERIAL SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. SURPLUS MATERIAL SHALL NOT BE DISPOSED OF ON THE PROJECT SITE. DISPOSAL SHALL BE MADE ONLY AT WASTE AREAS WHICH ARE LICENSED TO ACCEPT SUCH MATERIALS, UNLESS THE MATERIAL IS ACCEPTABLE FOR USE AS FILL IN OTHER AREAS OF THE PROJECT. THE OWNER HAS THE FIRST RIGHT AND REFUSAL FOR ANY SURPLUS SOIL MATERIALS.
- PROPERLY PROTECT AND DO NOT DISTURB PROPERTY IRONS AND MONUMENTS. IF DISTURBED, THE PROPERTY MONUMENT WILL BE RESET AT THE CONTRACTOR'S EXPENSE, BY A REGISTERED LAND SURVEYOR APPROVED BY THE ENGINEER.

REMOVAL NOTES:

- CONTRACTOR TO VERIFY THE LOCATION OF ALL UTILITIES PRIOR TO STARTING WORK. NOTIFY THE ARCHITECT OF ANY DISCREPANCY FROM THE PLANS.
- CONTRACTOR TO COORDINATE AND MEET THE REQUIREMENT OF THE MUNICIPAL UTILITY COMPANY WHEN DOING WORK ON THEIR SYSTEM.
- ALL DEMOLITION DEBRIS SHALL BE REMOVED AND DISPOSED OF OFFSITE IN ACCORDANCE WITH ALL APPLICABLE LAWS.

LAYOUT NOTES:

- CONTRACTOR IS RESPONSIBLE FOR LAYOUT OF SITE ELEMENTS. CONTRACTOR SHALL EMPLOY A REGISTERED LAND SURVEYOR FOR THE PROPER LAYOUT.
- CONTRACTOR SHALL LOCATE AND CLEARLY MARK ALL PROPERTY LINES, NATURAL RESOURCES, CLEARING LIMITS AND/OR EXISTING TO REMAIN ELEMENTS, PRIOR TO COMMENCING WORK.
- ALL RADII ARE 5' UNLESS OTHERWISE NOTED ON THE PLANS.

GRADING NOTES:

- ALL ELEVATIONS EXISTING AND PROPOSED ARE BASED ON THE TOPOGRAPHIC SURVEY COMPLETED. ALL RADII ARE 5' UNLESS OTHERWISE NOTED ON THE PLANS.
- ALL TOPSOILS AND ORGANICS SHALL BE REMOVED FROM PAVEMENT AND BUILDING AREAS PRIOR TO CONSTRUCTION. THIS MATERIAL SHALL NOT BE USED AS GENERAL SITE FILL.
- GRADES ADJACENT TO THE BUILDING SHALL BE 6"-8" BELOW FINISH FLOOR UNLESS OTHERWISE NOTED.
- GRADES OF SIDEWALK AT BUILDING ENTRANCES SHALL BE FLUSH WITH FINISH FLOOR, SLOPING AWAY FROM THE THRESHOLD, ON A FROST PROTECTED SLAB, UNLESS OTHERWISE NOTED.
- ALL DISTURBED AREAS SHALL RECEIVE 4" OF LOAM UNLESS OTHERWISE NOTED.
- TREES AND TREE CANOPIES SHOWN ON THE PLANS ARE APPROXIMATE AND HAVE NOT BEEN FIELD VERIFIED.

UTILITY NOTES:

- ALL UNDERGROUND SECONDARY POWER SHALL BE RUN IN SCHEDULE 40 PVC CONDUIT UNLESS OTHERWISE SPECIFIED.
- ALL UNDERGROUND ELECTRIC FOR SITE LIGHTING SHALL BE RUN IN SCHEDULE 40 PVC CONDUIT.
- PROVIDE A PULL WIRE IN ALL UNDERGROUND CONDUIT.
- CONDUIT TRENCHING AND BACKFILLING BY THE SITE CONTRACTOR. CONDUITS AND CONDUCTORS ARE SUPPLIED AND INSTALLED BY THE ELECTRICAL CONTRACTOR.
- NO UTILITY TRENCH BACKFILLING SHALL OCCUR UNTIL THE WORK HAS BEEN INSPECTED BY THE AUTHORITY HAVING JURISDICTION.
- WHERE NEW WATER AND SEWER RUN SIDE BY SIDE, MAINTAIN A TEN FOOT (10') HORIZONTAL SEPARATION IF POSSIBLE. WHERE THEY CROSS MAINTAIN AN 18" SEPARATION WITH THE WATERLINE GOING OVER THE SEWER LINE. PROVIDE 2" RIGID INSULATION BARRIER, IN A 8" DIAMETER FROM THE POINT OF WHERE THEY CROSS. IF WATER MUST PASS UNDER SEWER, ENCASE THE WATERLINE IN CONCRETE 4' EITHER SIDE OF THE CROSSING.
- WATER, SEWER AND STORM DRAIN LINES SHALL BE INSTALLED BELOW APPLICABLE FROST DEPTH. PENETRATIONS INTO BUILDING CAN OCCUR OVER THE FOUNDATION AND THROUGH THE FROST WALL.


MATERIAL SPECIFICATIONS


- SAND BEDDING SHALL MEET MDOT STANDARD SPECIFICATION 703.05.
- AGGREGATE BASE GRAVEL SHALL MEET MDOT STANDARD SPECIFICATION 703.06 TYPE A.
- AGGREGATE SUBBASE GRAVEL SHALL MEET MDOT STANDARD SPECIFICATION 703.06 TYPE D.
- STRUCTURAL FILL TO MEET MDOT STANDARD SPECIFICATION 703.06 TYPE A.
- SEEDING SHALL MEET MDOT STANDARD SPECIFICATION 717.03 METHOD ONE.
- BACKFILL MATERIAL SHALL MEET THE FOLLOWING FOR COMPACTION:

FILL AND BACKFILL LOCATION	MODIFIED PROCTOR DENSITY %
ROADWAY	95
UNDER OR WITHIN FIVE FEET OF STRUCTURES	95
FILL FOR EROSION REPAIR AREAS	92
TRENCHES THROUGH NON-ROADWAY AREAS	92
IN EMBANKMENT (INCLUDING TEMPORARY)	92
PIPE BEDDING AND TRENCHING	92


ABBREVIATIONS

@ AFG ANSI APPROX:±	AT ABOVE FINISHED GRADE AMERICAN NATIONAL STANDARDS INSTITUTE APPROXIMATELY	MAX. MDOT MH MIN	MAXIMUM MAINE DEPT. OF TRANSPORTATION MANHOLE MINIMUM
BLDG	BUILDING	N	NORTHING
CL	CENTERLINE	NE	NORTHEAST
CB	CATCH BASIN	N.T.S.	NOT TO SCALE
CLR	CLEAR	OD	OUTSIDE DIAMETER
CMP	CORRUGATED METAL PIPE	O.C.	ON CENTER
CO	CLEANOUT	OH	OVERHEAD
CPE	CORRUGATED POLYETHYLENE	OZ	OUNCES
DI	DUCTILE IRON	PERF	PERFORATED
DIA.	DIAMETER	PSF	POUNDS PER SQUARE FOOT
E	EASTING	PSI	POUNDS PER SQUARE INCH
EL	ELEVATION	PVC	POLYVINYL CHLORIDE
EFM	EXISTING FORCE MAIN	PL	PROPERTY LINE
EPS	EXTRUDED POLYSTYRENE	POH	PROPOSED OVERHEAD ELECTRIC
		PUGE	PROPOSED UNDERGROUND ELECTRIC
FM	FORCEMAIN	R	RADIUS
GAL	GALLON	SCL	SLOPE
GALV	GALVANIZED	SCS	STORMWATER COLLECTION LINE
GPH	GALLONS PER HOUR	SDR	STANDARD DIMENSION RATIO
GPM	GALLONS PER MINUTE	SE	SOUTHEAST
HP	HIGH DENSITY POLYETHYLENE	SH	SHEET
HDPE	HORSEPOWER	SS	STAINLESS STEEL
HP		SY	SQUARE YARD
ID	INSIDE DIAMETER		
IN.	INCHES	TBM	TEMPORARY BENCH MARK
INT.	INTERSECTION	TOC	TOP OF CONCRETE
INV.	INVERT	TYP	TYPICAL

REV	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUE FOR BID				
<div><div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div>				
PROJECT				
CONNER SCHOOL RENOVATIONS CONNER, MAINE				
TITLE				
GENERAL NOTES & ABBREVIATIONS				
DATE 2025.04.22		SCALE NTS		
DRAWN BY PAM	DESIGNED BY PAM	CHECKED BY --		
PROJECT No. 10377.028				
DRAWING No.		REV		
C001		1		



FILE LOCATION: P:\MET10377\BUREAU OF GENERAL SERVICES\CONNER SCHOOL RENOVATIONS\AG0302.CAD / FILESCIVIL10377.022-C-SR.DWG, 2025.04.18, 3:19 PM




LOCATION MAP: USGS QUADRANGLE: QUAD
SCALE: 1"=2000'
MAPTECH® USGS TOPOGRAPHIC SERIES™,
©MAPTECH®, INC. 978-933-3000
WWW.MAPTECH.COM/TOPO


DESCRIPTION	EXISTING	PROPOSED
PROPERTY LINE		
BENCHMARK		
SURVEY STATION		
MANHOLE		
UTILITY POLE		
WELL		
WATER VALVE		
SIGN		
CATCH BASIN		
HYDRANT		
EDGE OF GRAVEL		
EDGE OF PAVEMENT		
MAJOR FOOT CONTOUR	100	100
MINOR FOOT CONTOUR	98	98
WATERLINE	W	W
STORM DRAIN	SD	SD
SANITARY SEWER	SS	SS
OVERHEAD UTILITIES	OHU	OHU
UNDERGROUND UTILITIES	UGU	UGU
CHAIN LINK FENCE	X	X
SILT FENCE		SF
TREE LINE		
GRAVEL SURFACE		
PAVED SURFACE		

PLAN REFERENCE:
INFORMATION BASED ON A SITE PLAN DEVELOPED BY J.
GORDON ARCHITECTURE DATED MARCH 28, 2000. ADDITIONAL
SITE FEATURES SUPPLEMENTED FROM AERIAL PHOTOGRAPHS
AND SITE OBSERVATIONS.
TOPOGRAPHIC BASED ON LIDAR DATA PROVIDED ONLINE
SERVICES PROVIDED BY NOAA, AND SET TO NAD 83, 2011
MAINE STATE PLANE EAST


NOTES:
CONTRACTOR SHALL VERIFY ALL EXISTING INFORMATION IN
THE FIELD AND REPORT ANY DISCREPANCIES PRIOR TO
STARTING WORK.




1	2025.04.22	ISSUE FOR BID	PAM	MGC
REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUE FOR BID				
 www.haleyward.com One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824				
PROJECT CONNER SCHOOL RENOVATIONS CONNER, MAINE				
TITLE PROPOSED SITE PLAN				
DATE 2025.04.22		SCALE 1" = 30'		
DRAWN BY PAM		DESIGNED BY PAM		CHECKED BY ---
PROJECT No. 10377.028				
DRAWING No. C101		REV. 1		



FILE LOCATION: P:\MET10377\BUREAU OF GENERAL SERVICES\CONNER SCHOOL RENOVATIONS\AG0302.CAD / P:\SIC\CVL10377.025.CAD DWG: 2025.04.18, 3:25 PM




NOTE: CONTRACTOR SHALL ADD STONE TO ENTRANCE AS MUD/SILT MATERIAL ACCUMULATES



SECTION


STABILIZED CONSTRUCTION ENTRANCE DETAIL

N.T.S.



BANK STABILIZATION DETAIL

N.T.S.




INSTALLATION NOTES:

1. AREA CHOSEN FOR STOCKPILING OPERATIONS SHALL BE DRY AND STABLE.
2. MAXIMUM SLOPE OF STOCKPILE SHALL BE 2:1.
3. UPON COMPLETION OF SOIL STOCKPILING, EACH PILE SHALL BE SURROUNDED W/ EITHER SILT FENCING, THEN STABILIZED WITH VEGETATION OR COVERED.
4. SEE SILT FENCE DETAIL ON THIS SHEET
5. TEMPORARILY STABILIZE AS NOTED IN SPECIFICATIONS

TEMPORARY STOCKPILE AREA


N.T.S.



NOTE:
THE EROSION CONTROL MIX MUST BE WELL-GRADED WITH AN ORGANIC COMPONENT THAT IS BETWEEN 50 AND 100% OF DRY WEIGHT, AND THAT IS COMPOSED OF FIBROUS AND ELONGATED FRAGMENTS. THE MINERAL PORTION OF THE MIX SHOULD BE NATURALLY INCLUDED IN THE PRODUCT WITH NO LARGER ROCKS (>4") OR LARGE AMOUNTS OF FINES (SILTS AND CLAYS). IN STUMP GRINDING, THE MINERAL SOIL ORIGINATES FROM THE ROOT BALL AND SHOULD NOT BE REMOVED BEFORE GRINDING. THE MIX SHOULD BE FREE OF REFUSE, MATERIAL TOXIC TO PLANT GROWTH OR UNSUITABLE MATERIAL (BARK CHIPS, GROUND CONSTRUCTION DEBRIS OR REPROCESSED WOOD PRODUCTS).


EROSION CONTROL MIX BERM DETAIL

N.T.S. (MAY BE USED AS AN ALTERNATE TO SILT FENCE)




DUMPSTER PAD AND ENCLOSURE DETAIL

N.T.S.




PLAN VIEW




STEEL PIPE HANDRAIL DETAIL

N.T.S.




CHAIN LINK FENCE DETAIL


N.T.S.




4' MAN GATE DETAIL

N.T.S.


REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUE FOR BID				
 ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824				
PROJECT CONNER SCHOOL RENOVATIONS CONNER, MAINE				
TITLE SITE DETAILS				
DATE	2025.04.22	SCALE	NTS	
DRAWN BY	PAM	DESIGNED BY	PAM	CHECKED BY
PROJECT No.	10377.028			
DRAWING No.	C501			
REV	1			




STONE MAINTENANCE EDGE DETAIL
N.T.S.



FULL DEPTH FROST PROTECTED ENTRY PAD DETAIL
N.T.S.




CONCRETE ISOLATION JOINT DETAIL
N.T.S.




NOTE:
1. MATCH EXISTING SURFACE FINISH, EXCEPT WHERE NOTED. IN LAWN AREAS INSTALL 4" OF LOAM AND SEED AND MULCH.


TYPICAL CONCRETE PAD DETAIL
N.T.S.




TYPICAL ROADWAY/SIDEWALK BUILDUP DETAIL
NTS




TYPICAL CONCRETE SIDEWALK DETAIL
N.T.S.



TYPICAL CONCRETE SIDEWALK DETAIL
N.T.S.



EXPANSION JOINT



CONTROL JOINT


NOTES:
1. TOOLED JOINT SURFACES SHALL BE SMOOTH AND AT A CONSTANT DEPTH.
2. CONCRETE REINFORCEMENT NOT SHOWN FOR CLARITY.

TYPICAL CONCRETE SIDEWALK JOINT DETAILS
N.T.S.


CONCRETE NOTES

1. ALL CONCRETE MATERIALS AND WORKMANSHIPS SHALL CONFIRM TO THE LATEST EDITIONS OF ACI 318 AND ACI 301.
2. CONCRETE EXPOSED TO FREEZING AND THAWING SHALL BE AS FOLLOWS UNLESS NOTED OTHERWISE:
 - A. MINIMUM COMPRESSIVE STRENGTH: 5000 PSI @ 28 DAYS
 - B. CEMENT: ASTM C150 TYPE II
 - C. AGGREGATE: ASTM C33 OR C330
 - D. MAXIMUM AGGREGATE SIZE: 1"
 - E. MAXIMUM WATER-CEMENT RATIO: 0.45
 - F. SLUMP: 2 TO 4 INCHES
 - G. AIR ENTRAINMENT: ASTM C260, 4 TO 6 PERCENT
 - H. WATER REDUCING ADMIXTURE: ASTM C494
 - I. ADMIXTURES SHALL BE USED IN ACCORDANCE WITH ACI AND THE MANUFACTURERS RECOMMENDATIONS.
 - J. USE OF CALCIUM CHLORIDE, CHLORIDE IONS OR OTHER SALTS IS NOT PERMITTED.
3. REINFORCING BARS SHALL CONFORM TO ASTM A615, GRADE 60, DEFORMED BARS. REINFORCING BARS TO BE WELDED SHALL BE ASTM A706, GRADE 60, DEFORMED BARS.
4. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A1064.
5. PROVIDE ALL NECESSARY CHAIRS, SHAIR BARS, SPACER, ETC WIRED SECURELY TO HOLD REINFORCEMENT IN POSITION. THESE ACCESSORIES SHALL BE PLASTIC BOOTED WHERE CONCRETE IS TO BE EXPOSED TO WEATHER OR MOISTURE.
6. REINFORCING BARS SHALL BE PLACED IN ACCORDANCE WITH THE LATEST EDITION OF THE CRSI "RECOMMENDED PRACTICE FOR PLACING REINFORCING BARS".
7. CONCRETE COVER TO REINFORCING STEEL SHALL CONFORM TO ACI 318.
8. PROVIDE A 3/4" CHAMFER TO ALL EXPOSED CONCRETE EDGES.
9. WET CURE CONCRETE SLABS FOR A MINIMUM OF 3 DAYS.
10. SAW CUT CONTROL JOINTS SHALL BE 1/8" X 1/4 SLAB DEPTH CUT WITH AN EARLY ENTRY DRY-CUT SAW AS SOON AS THE CONCRETE IS SUFFICIENTLY HARD TO RESIST TEARING AND RAVELING (1 TO 4 HOURS AFTER FINISHING).


FROST DEPTH: 5 FEET




TYPICAL HANDICAP PARKING STALL SYMBOL
NTS



TYPICAL HANDICAP PARKING SIGN DETAIL
NTS





- NOTES:
1. SIGNS AND ASSOCIATED MOUNTING HARDWARE TO BE PROVIDED BY SITE CONTRACTOR.
 2. VAN ACCESSIBLE SIGN ONLY REQUIRED WHERE INDICATED ON PLANS.
 3. EQUIVALENT SIGNAGE OF DIFFERENT STYLES MAY BE SUBSTITUTED IF APPROVED BY ENGINEER.



- NOTES:
1. SLOPES ACROSS PARKING SPACES IN EACH DIRECTION SHALL BE 2% MAX.

ACCESSIBLE PARKING SPACE LAYOUT
N.T.S.


REV.	DATE	DESCRIPTION	BY	CHK.	
DRAWING ISSUE STATUS					
ISSUE FOR BID					
 ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824					
PROJECT					
CONNER SCHOOL RENOVATIONS CONNER, MAINE					
TITLE					
SITE DETAILS					
DATE		2025.04.22	SCALE	NTS	
DRAWN BY		PAM	DESIGNED BY	PAM	
PROJECT No.		10377.028		CHECKED BY	--
DRAWING No.		C502		REV.	



NOTE:
1. MATCH EXISTING SURFACE FINISH, EXCEPT WHERE NOTED. IN LAWN AREAS INSTALL 4" OF LOAM AND SEED AND MULCH.

TYPICAL TRENCH DETAIL - PE WATER SERVICE


N.T.S.



- NOTE:
1. 2" RIGID INSULATION BLUE BOARD BY DOW CO. SM. EXTRUDED POLYSTYRENE, (OR APPROVED EQUAL) TO BE USED IF EARTHEN COVER IS LESS THAN 5'-0" OVER PROPOSED STORM DRAIN CULVERT.
 2. CONTRACTOR MAY HAVE TO SUPPLY MORE THAN ONE LAYER OF BLUE BOARD INSULATION, IN AREAS THAT HAVE MINIMAL EARTHEN COVER TO MAINTAIN THE INSULATION VALUE OF 5'-0" COVER. 2" BLUE BOARD INSULATION HAS THE INSULATION VALUE OF APPROXIMATELY 1'-4" OF EARTHEN COVER. INSULATE PIPE TO EQUAL 5'-0" OF COVER.
 3. MAINTAIN A MINIMUM OF 12" OF EARTHEN COVER OVER INSULATION AS A MECHANICAL PROTECTION. LOAM AND SEED AS NECESSARY TO PREVENT EROSION.
 4. IF PIPE IS INSTALLED OVER BEDROCK, PLACE 6" OF CLEAN BEDDING UNDER PIPING.


TYPICAL PIPE TRENCH INSULATION DETAIL

N.T.S.




STEEL BOLLARD DETAIL

N.T.S.



CLEANOUT DETAIL


N.T.S.



- NOTE:
1. CULVERTS MUST HAVE A MINIMUM OF 1' OF AGGREGATE COVER FOR PROPER SUPPORT. INSULATION PLACED BELOW PIPE TRENCH ASSEMBLY TO COUNTERACT FROST.


TYPICAL CULVERT TRENCH DETAIL

N.T.S.




TYPICAL HANDHOLE DETAIL

N.T.S.




FOUNDATION DRAIN DETAIL

N.T.S.




TYPICAL POLE MOUNTED LIGHT DETAIL

N.T.S.




TYPICAL UNDERGROUND STREET LIGHTING TRENCH DETAIL

N.T.S.



TYPICAL LIGHT POLE BASE DETAIL

N.T.S.

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUE FOR BID				
<div><div><div>HALEY WARD</div><div>ENGINEERING ENVIRONMENTAL SURVEYING</div><div>www.haleyward.com</div></div><div><div>One Merchants Plaza, Suite 701</div><div>Bangor, Maine 04401</div><div>207.989.4824</div></div></div>				
PROJECT				
CONNER SCHOOL RENOVATIONS CONNER, MAINE				
TITLE				
SITE DETAILS				
DATE				
2025.04.22				
SCALE				
N.T.S.				
DRAWN BY				
PAM				
DESIGNED BY				
PAM				
CHECKED BY				
--				
PROJECT No.				
10377.028				
DRAWING No.				
REV				
C503				

SAWN LUMBER NOTES:

1. ALL WOOD FRAMING MEMBERS INCLUDING BUT NOT LIMITED TO WALL STUDS AND JOISTS, ARE INTENDED TO ACT AS A SYSTEM AS DETAILED IN THE STRUCTURAL DRAWINGS AND ONCE CONSTRUCTION IS COMPLETE, IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE SAFETY AND STABILITY OF WOOD FRAMING SYSTEMS (I.E. TEMPORARY BRACING IF REQUIRED) DURING CONSTRUCTION AS A RESULT OF CONSTRUCTION METHODS AND SEQUENCES. REFERENCE ARCHITECTURAL DRAWINGS FOR ALL SAWN LUMBER FINISH REQUIREMENTS.
2. ALL SAWN LUMBER SHALL CONFORM TO THE WESTERN WOOD PRODUCTS ASSOCIATION OR THE WEST COAST LUMBER INSPECTION BUREAU GRADING RULES. LUMBER SHALL BE OF THE SPECIES AND GRADE SHOWN BELOW:
- | MEMBER | GRADE |
|----------------------|-------------------------|
| 2x AND 4x FRAMING | DOUGLAS FIR-LARCH NO. 2 |
| 5x AND GREATER BEAMS | DOUGLAS FIR-LARCH NO. 1 |
| POSTS/COLUMNS | DOUGLAS FIR-LARCH NO. 1 |
- WOOD STUDS IN BEARING WALLS SHALL BE OF THE SIZE, GRADE, AND SPACING NOTED BELOW UNLESS NOTED OTHERWISE ON THE DRAWINGS. ALL STUD BEARING WALLS REQUIRE SHEATHING ON A MINIMUM OF ONE SIDE OF THE WALL, WHERE PLYWOOD SHEATHING DOES NOT EXIST AS NOTED IN THE DRAWINGS, THE SHEATHING MAY CONSIST OF 3/4" GYPSUM SHEATHING ATTACHED WITH #8 SCREWS AT 8" ON CENTER AT ALL PANEL EDGES AND AT 12" O.C. IN THE FIELD. WHERE ARCHITECTURAL FINISHES ARE APPLIED TO FLOORS ABOVE PRIOR TO THE MINIMUM SHEATHING REQUIREMENTS BEING INSTALLED ON THE STUD BEARING WALLS, IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE ADEQUACY OF THE UNSHEATHED BEARING WALL AND TO PROVIDE BRACING AS REQUIRED.
- | MEMBER AND SPACING | GRADE | FLOOR LOCATION |
|--------------------|-------------------------|-------------------------------------|
| REF. PLANS | DOUGLAS FIR-LARCH NO. 2 | EXTERIOR AND INTERIOR BEARING WALLS |
3. STORAGE OF ALL LUMBER AND TIMBER ON SITE SHALL BE KEPT OFF GROUND, UNDER COVER AND PROTECTED FROM DAMAGE
4. ALL DIMENSIONAL LUMBER SHALL BE CERTIFIED BY THE SUPPLIER IN WRITING TO BE KILN DRIED
5. STRUCTURE SHALL NOT BE ENCLOSED UNLESS LUMBER MOISTURE CONTENT HAS BEEN VERIFIED TO BE AT OR BELOW 15%. ANY SIGNS OF MOLD SHALL BE REMOVED AND TREATED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS OR INDUSTRY STANDARDS.
6. ALL LUMBER IN CONTACT WITH THE GROUND, CONCRETE SHALL BE PRESSURE TREATED. CONTRACTOR MAY SUBMIT FOR APPROVAL, A MOISTURE BARRIER IN-LIEU OF THE PRESSURE TREATED WOOD
7. FASTENERS FOR PRESERVATIVE-TREATED AND FIRE-RETARDANT-TREATED WOOD SHALL BE OF HOT-DIPPED ZINC-COATED GALVANIZED STEEL, OR STAINLESS STEEL AND SHALL FOLLOW CURRENT SIMPSON GUIDELINES BASED ON WEATHER EXPOSURE. WHERE STAINLESS STEEL CONNECTORS OR HOT DIPPED GALVANIZED CONNECTORS ARE SPECIFIED IN THE DRAWINGS, STAINLESS STEEL OR HOT DIPPED GALVANIZED FASTENERS SHALL BE USED TO MATCH THE CONNECTOR TYPE
8. ALL PLATES AND LEDGERS SHALL BE FASTENED WITH A MINIMUM (3) ANCHORS PER PIECE.
9. ALL METAL HARDWARE AND FRAMING ACCESSORIES SHALL BE MANUFACTURED BY SIMPSON STRONG-TIE COMPANY. SUBSTITUTIONS SHALL NOT BE MADE. ALL ITEMS SHALL BE INSTALLED PER THE SIMPSON'S INSTALLATION REQUIREMENTS. ALL NAIL HOLES SHALL BE FILLED WITH THE RECOMMENDED FASTENER UNLESS NOTED OTHERWISE ON THE DRAWINGS
10. WHERE FRAMING HANGERS OR WOOD CONNECTIONS ARE REQUIRED BUT HAVE NOT BEEN SPECIFIED ON THE STRUCTURAL DRAWINGS, PLEASE CONTACT EOR FOR APPROPRIATE WOOD CONNECTOR OR CONNECTION TO UTILIZE
11. ALL WALLS SHALL HAVE DOUBLE TOP PLATES AND SHALL BE SPLICED PER THE TYPICAL TOP PLATE SPLICE DETAIL, UNLESS NOTED OTHERWISE. TOP PLATES AT WALL INTERSECTIONS SHALL BE LAPPED AND NAILED WITH (3) 16d NAILS
12. WHERE ROOF MEMBERS OR ROOF TRUSSES ARE CONNECTED TO EXTERIOR WALLS OR WALLS w/ PLYWOOD SHEATHING, THE SPECIFIED HURRICANE CLIP SPECIFIED SHALL BE PLACED ON THE SIDE OF THE WALL DOUBLE TOP PLATE WHICH ATTACHES TO THE PLYWOOD.
13. HOLES FOR BOLTS SHALL BE DRILLED WITH A BIT OF THE SAME NOMINAL DIAMETER AS THE BOLT + 1/16". LEAD HOLES FOR LAG SCREWS SHALL BE BORED PER NDS 11.1.3
14. ALL BOLTS, CARRIAGE BOLTS, LAG SCREWS, EXPANSION BOLTS AND EPOXY BOLTS SHALL BE INSTALLED WITH STANDARD CUT WASHERS UNDER THE BOLT HEADS AND NUTS THAT BEAR DIRECTLY ON THE WOOD. ALL NUTS SHALL BE TIGHTENED AT THE TIME OF INSTALLATION AND RE-TIGHTENED IF NECESSARY, DUE TO WOOD SHRINKAGE, PRIOR TO CLOSE-IN OR AT THE COMPLETION OF THE PROJECT. BOLTS AND LAG SCREWS SHALL CONFORM TO ANSI/ASME STANDARD B18.2.1. WOOD SCREWS SHALL CONFORM TO B18.6.1. ALL BOLTS SHALL CONFORM TO ASTM A307 GRADE A UNLESS NOTED OTHERWISE. THE MINIMUM STRENGTHS FOR LAG SCREWS AND WOOD SCREWS SHALL BE AS FOLLOWS:
- | WOOD SCREW DIAMETER - INCHES | MIN. BENDING YIELD STRENGTH (PSI) |
|------------------------------|-----------------------------------|
| 0.138 (#6) | 100,000 |
| 0.151 (#7) | 90,000 |
| 0.164 (#8) | 90,000 |
| 0.177 (#9) | 90,000 |
| 0.190 (#10) | 90,000 |
| 0.216 (#12) | 80,000 |
| 0.246 (#14) | 70,000 |
- | LAG SCREW DIAMETER - INCHES | MIN. BENDING YIELD STRENGTH (PSI) |
|-----------------------------|-----------------------------------|
| 1/4 | 70,000 |
| 5/16 | 60,000 |
| 3/8 AND GREATER | 45,000 |
15. CUTTING AND NOTCHING OF SAWN LUMBER JOISTS, SAWN LUMBER RAFTERS AND STUDS SHALL BE IN CONFORMANCE WITH THE FOLLOWING CRITERIA:
- A. JOISTS
- NOTCHES AT THE ENDS OF JOISTS SHALL NOT EXCEED 1/5 THE JOIST DEPTH. HOLES BORED IN JOISTS SHALL NOT BE WITHIN 2-1/2 INCHES OF THE TOP OR BOTTOM OF THE JOIST, AND THE DIAMETER OF ANY SUCH HOLE SHALL NOT EXCEED 1/4 THE DEPTH OF THE JOIST. NOTCHES IN THE TOP OR BOTTOM OF THE JOISTS SHALL NOT EXCEED 1/6 THE DEPTH AND SHALL NOT BE LOCATED IN THE MIDDLE THIRD OF THE SPAN
- B. RAFTERS
- NOTCHING AT THE ENDS OF RAFTERS OR CEILING JOISTS SHALL NOT EXCEED 1/5 THE DEPTH. NOTCHES IN THE TOP OR BOTTOM OF THE RAFTER OR CEILING JOIST SHALL NOT EXCEED 1/6 THE DEPTH AND SHALL NOT BE LOCATED IN THE MIDDLE 1/3 OF THE SPAN, EXCEPT THAT A NOTCH NOT EXCEEDING 1/3 OF THE DEPTH IS PERMITTED IN THE TOP OF THE RAFTER OR CEILING JOIST NOT FURTHER FROM THE FACE OF THE SUPPORT THAN THE DEPTH OF THE MEMBER. HOLES BORED IN RAFTERS OR CEILING JOISTS SHALL NOT BE WITHIN 2-1/2 INCHES OF THE TOP AND BOTTOM AND THEIR DIAMETER SHALL NOT EXCEED 1/4 THE DEPTH OF THE MEMBER.
- C. WALLS
- MAXIMUM OF 2 1/4" DIAMETER NEATLY BORED HOLE MAY BE PLACED IN THE CENTER OF ALL BEARING 2x6 STUDS WITH NO ADDITIONAL REINFORCEMENT REQUIRED. REF. SHEET SXXX FOR ADDITIONAL INFORMATION ON STUDS AND POSTS
16. ALL NAILS FOR STRUCTURAL WORK SHALL BE COMMON WIRE NAILS UNLESS NOTED OR DETAILED OTHERWISE MEETING ASTM F1667. HOLES SHALL BE PRE-DRILLED WHERE NECESSARY TO PREVENT SPLITTING. NAILS SHALL HAVE THE MINIMUM PROPERTIES SPECIFIED IN THE TABLE BELOW:
- | NAIL TYPE | SHANK DIA. - INCHES | MIN. PENETRATION - INCHES | MIN. BENDING YIELD STRENGTH (PSI) |
|-----------|---------------------|---------------------------|-----------------------------------|
| 6d | 0.113 | 1.13 | 100,000 |
| 8d | 0.131 | 1.31 | 100,000 |
| 10d | 0.148 | 1.48 | 90,000 |
| 12d | 0.148 | 1.48 | 90,000 |
| 16d | 0.162 | 1.63 | 90,000 |
| 20d | 0.192 | 1.92 | 80,000 |
17. NAILING NOT SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE PER THE APPLICABLE VERSION OF THE IRC NAILING SCHEDULE.

NAILING SCHEDULE NOTES:

1. ALL OTHER NAILING REQUIREMENTS NOT SHOWN ON DRAWINGS OR IN SCHEDULE ABOVE SHALL BE IN ACCORDANCE WITH 2021 INTERNATIONAL BUILDING CODE.
2. POWER DRIVEN OR PNEUMATIC NAILS OTHER THAN COMMON NAILS MAY BE USED IF DATA IS SUBMITTED TO THE ARCHITECT/ENGINEER FOR APPROVAL PRIOR TO USE.
3. MINIMUM NAIL LENGTHS SHALL BE SUFFICIENT TO ACHIEVE MINIMUM PENETRATION INTO MAIN MEMBER AS NOTED IN SCHEDULE ON NOTE #16.

STRUCTURAL STEEL NOTES:

1. ALL STRUCTURAL STEEL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION'S "SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS" AND THE "AISC CODE OF STANDARD PRACTICE."
2. ALL STRUCTURAL STEEL SHAPES AND PLATES SHALL CONFORM TO THE FOLLOWING:
- | W AND WT SHAPES | ASTM A992 |
|----------------------------------|--------------------|
| S SHAPES, CHANNEL, ANGLE & PLATE | ASTM A36 |
| HSS | ASTM A500, GRADE B |
| PIPES | ASTM A53, GRADE B |
3. THE STRUCTURAL STEEL FABRICATOR SHALL BE AN AISC CERTIFIED FABRICATOR, MINIMUM CATEGORY "SBD" CERTIFICATION. (SUBMIT FABRICATOR CERTIFICATION FOR APPROVAL).
4. ALL SHOP INSPECTION SHALL BE COMPLETED BY THE FABRICATOR'S INSPECTOR. SHOP INSPECTION SHALL BE IN ACCORDANCE WITH AISC, AWS, AND AS OUTLINED IN THE CONTRACT DRAWINGS.
5. FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL CONFORM TO THE AISC "MANUAL OF STEEL CONSTRUCTION" (14TH EDITION) AND THE AISC "SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS (2005 EDITION).
6. ALL STEEL DETAILS AND CONNECTIONS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE AISC "MANUAL OF STEEL CONSTRUCTION" (14TH EDITION)
7. THE CONTRACTOR SHALL PROVIDE TEMPORARY BRACING OR GUYS TO PROVIDE LATERAL SUPPORT UNTIL THE PERMANENT LATERAL FORCE RESISTING SYSTEM IS INSTALLED.
8. THE CONTRACTOR SHALL COORDINATE BOTTOM OF BASE PLATE ELEVATION WITH THE TOP OF CONCRETE ELEVATION PLUS ALLOWANCE FOR GROUT BED. IN CASE OF CONFLICT THE CONTRACTOR SHALL MAKE ALLOWANCE IN THE BID FOR THE MORE STRINGENT REQUIREMENT.
9. CUTS OR BURNING OF HOLES IN STRUCTURAL STEEL MEMBERS IN THE FIELD WILL NOT BE PERMITTED.
10. ALL NUTS INDICATED "FINGER TIGHT" SHALL BE HAND TIGHTENED AS REQUIRED TO INSTALL ELEMENTS. DO NOT TIGHTEN NUTS INDICATED AS "FINGER TIGHT" BY MECHANICAL MEANS. TACK WELD "FINGER TIGHT" NUTS IN PLACE OR PROVIDE JAM NUT TO PREVENT BACK OFF.
11. ALL STEEL TO STEEL CONNECTIONS SHALL BE SIMPLE SHEAR CONNECTIONS UNLESS NOTED OTHERWISE.
12. ALL SIMPLE SHEAR CONNECTIONS SHALL BE BEARING TYPE CONNECTIONS UNLESS NOTED AS SLIP CRITICAL.
13. MINIMUM NUMBER OF BOLTS FOR ANY CONNECTION SHALL BE TWO.
14. ALL STEEL TO STEEL CONNECTIONS SHALL EXTEND AT LEAST 2/3 THE DEPTH OF THE SHALLOWEST MEMBER BEING CONNECTED.
15. SHOP CONNECTIONS NOT SPECIFICALLY INDICATED ON THE DRAWINGS MAY BE WELDED OR BOLTED. FIELD CONNECTIONS NOT SPECIFICALLY SHOWN ON THE DRAWINGS SHALL BE BOLTED.
16. ALL WELDING ELECTRODES SHALL BE E70 WITH A MINIMUM YIELD STRENGTH OF 58KSI, MINIMUM TENSILE STRENGTH OF 70 KSI, AND MINIMUM ELONGATION OF 22% IN ACCORDANCE WITH AWS A5.
17. ALL WELD MATERIAL SHALL HAVE A MINIMUM CVN TOUGHNESS OF 20 FT-LBS AT MINUS 10 DEGREES FAHRENHEIT AND 40 FT-LB AT 70° FAHRENHEIT.
18. 100% OF ALL SHOP FULL PENETRATION WELDS SHALL BE ULTRASONICALLY TESTED AND ALL DEFECTS REPAIRED.
19. ALL STRUCTURAL STEEL SHALL BE SHOP PRIMED WITH FABRICATOR'S STANDARD LEAD AND CHROMATE FREE PRIMER UNO OR UNLESS STEEL IS TO BE FIREPROOFED OR IS INDICATED TO RECEIVE HIGH PERFORMANCE PRIMER AND TOP COAT. FABRICATOR SHALL COORDINATE PRIMER REQUIREMENTS WITH SLIP CRITICAL BOLTS
20. FABRICATOR SHALL SUBMIT METHOD FOR INSTALLING SLIP CRITICAL BOLTS FOR APPROVAL. ERECTOR SHALL SET UP PREINSTALLATION TESTING WITH THE OWNER'S SPECIAL INSPECTOR.
21. STEEL FABRICATOR SHALL SUBMIT SHOP DRAWINGS FABRICATION OF ALL STRUCTURAL STEEL ELEMENTS. SHOP DRAWINGS SHALL INDICATE:
- A. INCLUDE DETAILS OF CUTS, CONNECTIONS, SPLICES, CAMBER, HOLES AND OTHER PERTINENT DATA.
- B. INCLUDED EMBEDMENT DRAWINGS.
- C. INDICATE WELDS BY STANDARD AWS SYMBOLS, DISTINGUISHING BETWEEN SHOP AND FIELD WELDS, AND SHOW SIZE, LENGTH AND TYPE OF EACH WELD.
- D. INDICATE TYPE, SIZE, AND LENGTH OF BOLTS, DISTINGUISHING BETWEEN SHOP AND FIELD BOLTS.
- E. IDENTIFY PRETENSIONED AND SLIP CRITICAL HIGH STRENGTH BOLTS.
22. FIELD TESTING AND INSPECTION OF STRUCTURAL STEEL MATERIALS, AND STRUCTURAL STEEL INSTALLATION SHALL BE COMPLETED BY AN INDEPENDENT TESTING AGENCY (COMMISSIONED BY THE OWNER), AND SHALL BE IN ACCORDANCE WITH THE SCHEDULE OF SPECIAL INSPECTIONS.

FOUNDATION NOTES:

1. DESIGN OF FOUNDATIONS IS BASED ON AN ALLOWABLE SOIL BEARING PRESSURE OF 2000 POUNDS PER SQUARE FOOT.
2. ALL DELETERIOUS MATERIALS FOUND WITHIN THE LIMITS OF THE STRUCTURE, AS DETERMINED BY THE TESTING AGENCY, SHALL BE REMOVED AND REPLACED WITH COMPACTED SELECT FILL.
3. NO FOUNDATIONS SHALL BE PLACED ON FROZEN GROUND OR IN WATER. ALL TRENCHES SHALL BE DEWATERED PRIOR TO PLACING CONCRETE.
4. FROST WALLS SHALL BE CURED FOR A MINIMUM OF 7 DAYS PRIOR TO GRADEFILLING. THE BACKFILL MATERIAL SHALL BE BROUGHT UP TO GRADE EQUALLY ON BOTH SIDES OF FROST WALLS.
5. RETAINING WALLS AND FOUNDATION WALLS SHALL BE CURED TO MEET SPECIFIED STRENGTH PRIOR TO BACKFILLING.
6. SELECT FILL AND BACKFILL MATERIAL SHALL BE PLACED IN MAXIMUM 8" LIFTS. EACH LIFT SHALL BE COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY PER ASTM D-1557, MODIFIED PROCTOR TEST.
7. SELECT FILL AND BACKFILL MATERIAL SHALL BE SCREENED OR CRUSHED GRAVEL OF HARD DURABLE PARTICLES FREE FROM VEGETABLE MATTER, LUMPS, BALLS OF CLAY AND OTHER DELETERIOUS SUBSTANCES. SELECT FILL SHALL CONFORM TO THE FOLLOWING GRADATION REQUIREMENTS:
- | SELECT FILL - GRADATION REQUIREMENTS | |
|--------------------------------------|-------------------------|
| SIEVE SIZE | PERCENT FINER BY WEIGHT |
| 4 INCH | 100 |
| 3 INCH | 90 - 100 |
| 1 1/4 INCH | 25 - 90 |
| No. 40 | 0 - 30 |
| No. 200 | 0 - 5 |
8. ON SITE MATERIALS GENERATED DURING EXCAVATION MAY BE USED AS BACKFILL MATERIAL PLACED ADJACENT TO FOUNDATION WALLS PROVIDED IT MEETS THE GRADATION REQUIREMENTS FOR SELECT FILL.
9. FIELD QUALITY CONTROL FOR SUBGRADE PREPARATION AND ALL OTHER ASSOCIATED FOUNDATION WORK SHALL BE COMPLETED BY AN INDEPENDENT TESTING AGENCY (COMMISSIONED BY THE OWNER), AND SHALL BE IN ACCORDANCE WITH THE SCHEDULE OF SPECIAL INSPECTIONS.
10. CONCRETE FOR FOUNDATIONS SHALL COMPLY WITH THE CONCRETE NOTES
11. COORDINATE PLUMBING AND FOUNDATION ELEVATIONS TO MINIMIZE INTERFERENCES. STEP FOOTINGS PER TYPICAL DETAILS WHERE INTERFERENCES OCCUR.
12. THE CONTRACTOR SHALL SUBMIT THE FOLLOWING INFORMATION TO THE STRUCTURAL ENGINEER OF RECORD FOR REVIEW:
- A. GRADATION OF MATERIAL TO BE USED AS SELECT FILL.
- B. COMPACTION TEST RESULTS UNDER PAVEMENTS, SLABS ON GRADE AND FOUNDATIONS.

POST INSTALLED ANCHOR NOTES:

1. NOTED EMBEDMENT DEPTHS ARE FROM FACE OF CMU OR FACE OF CONCRETE
2. ALL INSTALLATION SHALL BE IN STRICT ACCORDANCE WITH THE MANUFACTURER'S DATA AND THE ASSOCIATED ICC REPORT.
3. ALL PERSONNEL INSTALLING ANCHORS SHALL HAVE ATTENDED INSTALLER TRAINING PER THE SPECIFICATIONS.
4. FIELD TESTING AND INSPECTION OF POST INSTALLED ANCHOR MATERIALS AND POST INSTALLED ANCHOR INSTALLATION SHALL BE COMPLETED BY AN INDEPENDENT TESTING AGENCY COMMISSIONED BY THE OWNER, AND SHALL BE IN ACCORDANCE WITH THE SCHEDULE OF SPECIAL INSPECTIONS.

CONCRETE AND REINFORCEMENT NOTES:

1. ALL CONCRETE SHALL CONFORM TO LATEST EDITIONS OF ACI 318 AND ACI 301.
2. CONCRETE SHALL BE AS FOLLOWS UNLESS NOTED OTHERWISE
- | | 4000 PSI @28 DAYS |
|----------------------------------|------------------------|
| A. MINIMUM COMPRESSIVE STRENGTH: | ASTM C150 TYPE II |
| B. CEMENT | ASTM C33 OR C330 |
| C. AGGREGATE | 1 1/2 INCH |
| D. MAXIMUM AGGREGATE SIZE | 0.45 |
| E. MAXIMUM WATER-CEMENT RATIO: | 2 TO 4 INCHES |
| F. SLUMP | ASTM C260, 6.5% (± 1%) |
| G. AIR ENTRAINMENT: | ASTM C494 |
| H. WATER REDUCING ADMIXTURE: | |
1. ADMIXTURES SHALL BE USED IN ACCORDANCE WITH ACI AND THE MANUFACTURERS RECOMMENDATIONS
2. USE OF CALCIUM CHLORIDE, CHLORIDE IONS OR OTHER SALTS IS NOT PERMITTED.
3. REINFORCING STEEL SHALL CONFORM TO ASTM A615 GRADE 60
4. REINFORCING STEEL SHALL BE SUPPORTED ON CHAIRS OR BOLSTERS.
5. ALL LAP SPLICES SHALL BE IN ACCORDANCE WITH THE TABLES BELOW (TYPE 2 MECHANICAL SPLICES MAY BE USED IN LIEU OF LAP SPLICES AT CONTRACTOR'S OPTION)
- | 4000 PSI CONCRETE | GRADE 60 REINFORCING STEEL | | | | | | | | | | fy = 60,000 PSI |
|-----------------------|----------------------------|----|----|----|----|----|----|-----|-----|--|-----------------|
| BAR SIZE | #3 | #4 | #5 | #6 | #7 | #8 | #9 | #10 | #11 | | |
| LAP (IN) - TOP BARS | 15 | 20 | 24 | 29 | 48 | 60 | 74 | 91 | 109 | | |
| LAP (IN) - OTHER BARS | 12 | 15 | 19 | 22 | 37 | 47 | 57 | 70 | 84 | | |
6. ALL LAP SPLICES SHALL BE ACI CLASS B SPLICES. THE FOLLOWING TABLES ARE BASED ON NORMAL WEIGHT CONCRETE WITH BARS 4 BAR DIAMETERS OR MORE APART AND CONCRETE COVER EQUAL TO 2 BAR DIAMETERS OR MORE. TOP BARS ARE DEFINED AS HORIZONTAL BARS WITH MORE THAN 12 INCHES OF CONCRETE PLACED BELOW THE REINFORCEMENT.
7. REINFORCEMENT SHALL BE SECURELY ANCHORED IN POSITION WHILE PLACING CONCRETE. THE CONTRACTOR SHALL PROVIDE ADDITIONAL BARS OR STIRRUPS AS REQUIRED TO ANCHOR BARS IN THE PROPER POSITION
8. THE DESIGN AND CONSTRUCTION OF FORMS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. FORMS SHALL BE CONSTRUCTED TO SHAPE, FORMS, AND LINES INDICATED ON DRAWINGS. BRACING SHALL BE DESIGNED TO RESIST FORCES EXERTED BY FRESH CONCRETE.
9. QUALIFIED WORKMEN SHALL CONSTANTLY OBSERVE AND ADJUST FORMS AND SHORES AS REQUIRED DURING CONCRETE PLACEMENT.
10. ALL SHORING SHALL REMAIN IN PLACE UNTIL THE SUPPORTED CONCRETE HAS ATTAINED 75% OF THE REQUIRED 28 DAY COMPRESSIVE STRENGTH.
11. CONTRACTOR SHALL VERIFY DIMENSIONS AND LOCATIONS OF ALL SLOTS, PIPE SLEEVES, ANCHOR BOLTS, ETC. AS REQUIRED FOR ALL OTHER TRADES BEFORE CONCRETE IS POURED. THESE ITEMS SHALL BE INSTALLED AND VERIFIED BY THE CONTRACTOR.
12. CONCRETE COVER TO REINFORCING STEEL SHALL CONFORM TO ACI 318 AS FOLLOWS:
- | | #3 THRU #5: | 1 1/2" |
|----------------------------------------------------------------------|----------------|--------|
| A. CONCRETE AGAINST EARTH: | 1 1/2" | |
| B. CONCRETE EXPOSED TO EARTH OR WEATHER: | #6 THRU #11: | 2" |
| C. CONCRETE NOT EXPOSED TO WEATHER OR PLACED IN CONTACT WITH GROUND: | SLABS/WALLS: | 3/4" |
| | BEAMS/COLUMNS: | 1 1/2" |
13. FOOTING AND GRADE BEAM SIZES SHOWN ARE FOR FOOTINGS CONSTRUCTED WITH SIDE FORMS. IF EARTH FORMING IS USED FOUNDATION SIZES SHALL INCREASED IN WIDTH 1" IN EACH DIRECTION.
14. SHOP DRAWINGS FOR PLACEMENT SHALL BE SUBMITTED FOR REVIEW PRIOR TO REBAR FABRICATION.
15. ALL INSIDE CONCRETE WEARING SURFACES SHALL RECEIVE A SMOOTH STEEL TROWEL FINISH.
16. ALL OUTSIDE CONCRETE WEARING SURFACES SHALL RECEIVE A STEEL TROWEL AND A MEDIUM BROOM FINISH PERPENDICULAR TO THE TRAFFIC FLOW.
17. ALL CONCRETE SLABS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE FOLLOWING FLATNESS/LEVELNESS REQUIREMENTS:
- | SLAB CATEGORY | FLATNESS, Ff | LEVELNESS, Fl | DEVIATION |
|---------------|--------------|---------------|--------------|
| BULLFLOATED | 15 | 13 | 1/2" IN 10' |
| STRAIGHTEDGED | 20 | 15 | 3/4" IN 10' |
| FLAT | 30 | 20 | 7/8" IN 10' |
| VERY FLAT | 50 | 30 | 1" IN 10' |
| SUPERFLAT | 100 | 50 | <1/4" IN 10' |
- FLOOR FLATNESS / LEVELNESS TESTS SHALL BE CONDUCTED ACCORDING TO ASTM E1155
18. PROVIDE A 3/4" CHAMFER TO ALL EXPOSED CONCRETE EDGES
19. WET CURE ALL CONCRETE SLABS FOR A MINIMUM OF 3 DAYS.
20. SAW CUT CONTROL JOINTS SHALL BE 1/8"x1 1/2" DEEP CUT WITH AN EARLY ENTRY DRY-CUT SAW AS SOON AS THE CONCRETE IS SUFFICIENTLY HARD TO RESIST TEARING AND RAVELING (1 TO 4 HOURS AFTER FINISHING).
21. HORIZONTAL JOINTS IN FOOTINGS, GRADE BEAMS, AND TIE BEAMS WILL NOT BE PERMITTED.
22. DO NOT INSTALL PLUMBING SLEEVES IN GRADE BEAMS OR TIE BEAMS WITHOUT ENGINEER APPROVAL.
23. REINFORCING BARS SHALL NOT BE CUT TO ACCOMMODATE THE INSTALLATION OF ANCHORS, EMBEDS, OR OTHER ITEMS.
24. AT CHANGES IN DIRECTION OF CONTINUOUS CONCRETE ELEMENTS PROVIDE CORNER BARS OF SAME SIZE AND SPACING OF HORIZONTAL REINFORCEMENT.
25. PLACE CONCRETE PER ACI 304. USE INTERNAL MECHANICAL VIBRATION FOR ALL CONCRETE. LIMIT MAXIMUM FREE FALL DROP OF CONCRETE TO 6'-0". PRECAUTIONS SHALL BE TAKEN TO AVOID SEGREGATION DURING CONCRETE PLACEMENT.
26. FIELD TESTING AND INSPECTION OF ALL CONCRETE MATERIALS AND CONCRETE INSTALLATION SHALL BE CONDUCTED BY AN INDEPENDENT TESTING AGENCY (COMMISSIONED BY THE OWNER), AND SHALL BE IN ACCORDANCE WITH THE SCHEDULE OF SPECIAL INSPECTIONS.

GENERAL NOTES:

1. STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH ARCHITECTURAL, CIVIL, MECHANICAL, PLUMBING, AND ELECTRICAL CONTRACT DRAWINGS, AND ASSOCIATED SHOP DRAWING SUBMITTALS. CONTRACTOR SHALL BE RESPONSIBLE FOR CHECKING AND COORDINATING DIMENSIONS, CLEARANCES, ETC. WITH WORK OF OTHER TRADES.
2. IN CASE OF CONFLICT BETWEEN VARIOUS STRUCTURAL DRAWINGS, OR STRUCTURAL PLANS AND DETAILS, THE MORE STRINGENT REQUIREMENT SHALL GOVERN
3. IN CASE OF CONFLICT BETWEEN DRAWINGS, NOTES, AND SPECIFICATIONS THE MORE STRINGENT REQUIREMENT SHALL GOVERN.
4. WORK NOT INDICATED ON A PART OF THE DRAWINGS BUT REASONABLY IMPLIED TO BE SIMILAR TO THAT SHOWN AT CORRESPONDING PLACES SHALL BE REPEATED.
5. ALL DETAILS AND SECTIONS ARE INTENDED TO BE TYPICAL FOR THE GENERAL CONDITIONS INDICATED. ALL DETAILS SHALL BE CONSTRUED TO APPLY TO ANY SIMILAR SITUATION THROUGHOUT THE PROJECT EXCEPT WHERE A SEPARATE DETAIL IS INDICATED
6. REVIEW ALL PROJECT DOCUMENTS PRIOR TO FABRICATION AND START OF CONSTRUCTION. REPORT ANY DISCREPANCIES TO CONTRACTING OFFICER OR A/E PRIOR TO PROCEEDING WITH WORK.
7. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROTECT EXISTING FACILITIES, STRUCTURES, UTILITY LINES, ETC. FROM DAMAGE DURING CONSTRUCTION.
8. COORDINATE STRUCTURAL DRAWINGS WITH OTHER CONTRACT DRAWINGS FOR ANCHORED, EMBEDDED OR SUPPORTED ITEMS THAT MAY AFFECT THE STRUCTURAL DRAWINGS.
9. USE OF CONTRACT DRAWINGS REPRODUCED IN WHOLE OR IN ANY PART FOR SHOP DRAWINGS PRODUCTION SHALL NOT RELIEVE THE CONTRACTOR OR SUBCONTRACTOR FROM THE REQUIREMENT TO ACCURATELY LAYOUT, COORDINATE, DETAIL, FABRICATE AND INSTALL A COMPLETE STRUCTURE.
10. ALL SHOP DRAWINGS SHALL BE REVIEWED BY THE SUBCONTRACTOR AND CONTRACTOR FOR CONFORMANCE WITH CONTRACT DOCUMENTS, COMPLETENESS, AND TO RESPOND TO QUESTIONS RELATED TO CONTRACTOR INFORMATION PRIOR TO SUBMITTING FOR APPROVAL. ALL SHEETS SHALL BE STAMPED AND INITIALED BY CONTRACTOR INDICATING SUCH REVIEW IS COMPLETE PRIOR TO SUBMITTING SHOP DRAWINGS FOR APPROVAL.
11. CONTRACTOR SHALL MAKE NO DEVIATIONS FROM THE CONTRACT DRAWINGS WITHOUT WRITTEN APPROVAL OF THE CONTRACTING OFFICER.
12. ALL ELEVATIONS INDICATED IN STRUCTURAL DRAWINGS ARE IN REFERENCE TO A GROUND FLOOR FINISHED SLAB ELEVATION OF 0'-0". SEE CIVIL FOR FINISHED FLOOR MSL ELEVATION

BUILDING - DESIGN CRITERIA:

CODES:

INTERNATIONAL BUILDING CODE (IBC) 2021
ASCE -7-16 MINIMUM DESIGN LOADS FOR BUILDING AND OTHER STRUCTURES

BUILDING AND SITE DATA:

ROOF PITCH: 1 1/2:12
CATEGORY: II
EXPOSURE: B
PARTIALLY ENCLOSED
WARM ROOF
SEISMIC SITE CLASS D (N-VALUE METHOD)

LOADS:



GROUND SNOW LOAD: 100 PSF
ROOF DEAD LOAD: 20 PSF
BASIC WIND SPEED: 102 MPH

DEFLECTION:

LIVE LOAD: L/240
TOTAL LOAD: L/180

FOUNDATION DESIGN:

FOUNDATION DESIGN IS BASED ON AN ASSUMED NET ALLOWABLE BEARING CAPACITY OF 2000 PSF.

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div><div>HALEY WARD ENGINEERING & ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div><div>WWW.HALEYWARD.COM</div></div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS				
1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
STRUCTURAL NOTES				
<div></div>		DATE 2025.04.22	SCALE 12" = 1'-0"	
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028				
DRAWING NO. S001		REV		

Autodesk Draw110377.028 - R28 - Connor School10377.028 - Connor School - Structural.rvt

MASONRY NOTES:

1. ALL MASONRY WORK SHALL BE IN COMPLIANCE WITH ACI 530, "BUILDING CODE REQUIREMENTS FOR MASONRY CONSTRUCTION" AND ACI 530.1 "SPECIFICATIONS FOR MASONRY CONSTRUCTION."
2. HOLLOW LOAD BEARING CONCRETE BLOCK SHALL CONFORM TO ASTM C90, TYPE 1, NORMAL WEIGHT. BLOCK UNITS SHALL BE TWO CELL, 50% SOLID WITH A MINIMUM NET AREA COMPRESSIVE STRENGTH OF 1900 PSI.
3. SPECIFIED MASONRY DESIGN COMPRESSIVE STRENGTH, f_m = 1500 PSI.
4. MORTAR SHALL CONFORM TO ASTM C270, TYPE S. MINIMUM COMPRESSIVE STRENGTH SHALL BE 1800 PSI AT 28 DAYS.
5. GROUT SHALL CONFORM TO ASTM C476 WITH A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT 28 DAYS.
6. REINFORCING STEEL SHALL CONFORM TO ASTM A615, GRADE 60, DEFORMED BARS.
7. HORIZONTAL JOINT REINFORCEMENT SHALL BE LADDER TYPE, STANDARD CLASS, MILL GALVANIZED WITH 9 GAGE SIDE RODS AND 9 GAGE CROSS RODS. HORIZONTAL JOINT REINFORCEMENT SHALL BE PROVIDED AT EVERY OTHER HORIZONTAL JOINT UNLESS NOTED OTHERWISE. WHERE JOINT REINFORCEMENT IS SPLICED PROVIDE 12" MINIMUM LAP, INCLUDING CORNERS AND TEES. PREFABRICATED CORNERS AND TEES SHALL BE USED AT ALL WALL INTERSECTIONS.
8. PROVIDE CONTROL JOINTS IN CONCRETE MASONRY WALLS AS INDICATED OR, IF NOT INDICATED, AT A MAXIMUM SPACING OF 25' ON CENTER.
9. HOLLOW CONCRETE UNITS SHALL BE LAID IN RUNNING BOND UNLESS NOTED OTHERWISE. PROVIDE FULL MORTAR COVERAGE ON HORIZONTAL AND VERTICAL FACES. EXPOSED JOINTS SHALL BE TOOLED CONCAVE, UNEXPOSED JOINTS SHALL BE STRUCK FLUSH.
10. CORNER BLOCKS AND END BLOCKS SHALL BE USED TO FINISH ALL 90 DEGREE CORNERS SAND WALL OPENINGS.
11. ALL BOND BEAM BLOCKS SHALL BE KNOCK-OUT TYPE BLOCKS. 41/2" MINIMUM GROUT MESH SHALL BE USED UNDER BOND BEAMS TO CONFINE GROUT FROM HOLLOW CORES.
12. GROUTING:

A. CELLS THAT ARE TO BE GROUTED SOLID SHALL BE ALIGNED TO MAINTAIN A CLEAR, UNOBSTRUCTED, CONTINUOUS VERTICAL CELL. PROVIDE CLEANOUTS IN THE BOTTOM COURSE OF MASONRY FOR EACH GROUT POUR, AT EACH VERTICAL BAR.

B. GROUT SOLID ALL CELLS CONTAINING REINFORCING BARS OR OTHER ATTACHMENTS.

C. GROUT SOLID (3) CELLS MINIMUM BELOW LINTELS AND STEEL BEAMS BEARING ON MASONRY.

D. LOW LIFT GROUTS SHALL NOT EXCEED 5 FEET. GROUT POUR HEIGHT SHALL NOT EXCEED 10 FEET. PROVIDE CLEANOUTS IN THE BOTTOM COURSE OF MASONRY FOR EACH GROUT POUR, WHEN GROUT POUR EXCEEDS 5 FEET.

E. HIGH LIFT GROUTS SHALL NOT EXCEED 12'-8" AND THE FOLLOWING CONDITIONS MUST BE MET:

a. THE MASONRY MUST CURE FOR AT LEAST FOUR HOURS.

b. THE GROUT SLUMP MUST BE MAINTAINED BETWEEN 10 AND 11 INCHES.

c. THE WALL CANNOT CONTAIN INTERMEDIATE BOND BEAMS BETWEEN THE TOP AND BOTTOM OF THE POUR HEIGHT.

F. GROUTING SHALL BE STOPPED 11/2" BELOW THE TOP OF A COURSE TO FORM A KEY AT THE JOINT.

G. GROUTING OF MASONRY BEAMS OR LINTELS SHALL BE DONE IN ONE CONTINUOUS OPERATION.
13. MASONRY LINTELS:

A. PROVIDE A MINIMUM OF 8" BEARING AT EACH END OF EACH LINTEL. KNOCK-OUT SHALL BE PROVIDED. USE LINTEL-TYPE BLOCKS ONLY AT OPENINGS.

B. EXTEND BOTTOM BARS 24" BEYOND THE OPENING FOR #4 & #5 BARS AND 30" BEYOND THE OPENING FOR #6.
14. REINFORCING:

A. VERTICAL REINFORCING SHALL BE PLACED AT EACH JAMB OF EACH WALL OPENING, AT EACH WALL END, AT EACH SIDE OF WALL CONTROL JOINT, AT EACH WALL INTERSECTION.

B. SPLICED REINFORCING SHALL BE LAPPED 48 BAR DIAMETERS OR AS SHOWN ON DRAWINGS, WHICHEVER IS GREATER.

C. VERTICAL REINFORCING BARS SHALL HAVE A MINIMUM CLEARANCE OF 3/4" FROM MASONRY AND SHALL BE HELD IN POSITION TOP AND BOTTOM AND AT INTERVALS NOT EXCEEDING FOUR (4) FEET.

D. FOUNDATION DOWELS MAY BE SLOPED NO MORE THAN 1h:6v TO ALIGN WITH WALL CAVITIES OR VERTICAL CMU CORES. PROVIDE DOWELS TO MATCH WALL REINFORCEMENT SIZE AND SPACING, UNLESS OTHERWISE NOTED ON THE DRAWINGS.

E. LOCATE ALL VERTICAL REINFORCEMENT CENTERED IN THE WALL UNLESS OTHERWISE DETAILED.

F. WHERE BOND BEAMS ARE DISCONTINUOUS, EXTEND REINFORCEMENT 48 BAR DIAMETERS BEYOND THE SPECIFIED TERMINATION.

G. WHERE BOND BEAMS ARE REQUIRED TO STEP BY 4"-12" VERTICALLY, REMOVE MASONRY AS REQUIRED TO MAINTAIN CONTINUITY OF REINFORCEMENT @ A SLOPE = 6 UNITS HORIZONTAL TO 1 UNIT VERTICAL.
15. FIELD PENETRATIONS THROUGH BLOCK WALLS SHALL NOT BE MADE THROUGH BOND BEAMS, LINTELS OR GROUTED CELLS.
16. DRAWINGS INDICATE DOWELS FOR SECURING REINFORCEMENT IN STRUCTURAL WALLS TO BE CAST IN CONCRETE. POST-INSTALLED DOWELS ARE ACCEPTABLE AS A SUBSTITUTION WHEN APPROVED BY THE STRUCTURAL ENGINEER OF RECORD, SUBJECT TO THE FOLLOWING REQUIREMENTS:

A. REQUIRED HOLE SIZE FOR "UNIFORM VERTICAL REINFORCEMENT" SHALL BE AS FOLLOWS:

a. #4 5/8"Øx4 1/4"



b. #5 3/4"Øx5 1/4"


B. REQUIRED HOLE SIZE FOR "JAMB REINFORCEMENT" SHALL BE AS FOLLOWS:

a. #4 5/8"Øx6 1/4"

b. #5 3/4"Øx8"

C. SET BARS IN EPOXY INJECTION ADHESIVE HILTI HIT-RE 500 OR AN APPROVED EQUAL. COMPLY WITH MANUFACTURER'S SPECIFICATIONS FOR PREPARATION & PLACEMENT REQUIREMENTS.

REV.	1	DATE	DESCRIPTION		BY	CHK.				
DRAWING ISSUE STATUS										
ISSUED FOR BID										
<div><div><div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div></div></div>										
PROJECT										
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736										
TITLE										
STRUCTURAL NOTES										
		DATE		2025.04.22	SCALE 12" = 1'-0"					
		DRAWN BY		WCT	DESIGNED BY		WCT	CHECKED BY		CDL
		PROJECT No.		10377.028						
		DRAWING NO.		S002				REV.		



1
S101


SLAB PLAN


SCALE: 1/4" = 1'-0"


2
S102

ROOF FRAMING PLAN

SCALE: 1/4" = 1'-0"


REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
FOUNDATION AND ROOF FRAMING PLANS				
DATE 2025.04.22		SCALE 1/4" = 1'-0"		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028		DRAWING NO. S101		






1
S200
STRUCTURAL FRONT ELEVATION
SCALE: 3/4" = 1'-0"


TYPICAL BP





TYPICAL BASEPLATE
SCALE: 1 1/2" = 1'-0"


TYPICAL STEEL COLUMN BASEPLATE CONNECTION
SCALE: 1 1/2" = 1'-0"





REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824				
PROJECT CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE STRUCTURAL FRONT ELEVATION				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028		REV.		
DRAWING NO. S200				






REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
STRUCTURAL SECTION				
DATE 2025.04.22		SCALE 3/4" = 1'-0"		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028		REV.		
DRAWING NO. S300				








1
S301
STRUCTURAL SECTION 2
SCALE: 3/4" = 1'-0"





2
S301
(N) CMU WALL TO (E) FOUNDATION
SCALE: 3/4" = 1'-0"


REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
STRUCTURAL SECTION				
DATE 2025.04.22		SCALE 3/4" = 1'-0"		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028		REV.		
DRAWING NO. S301				





REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
STRUCTURAL SECTION				
DATE 2025.04.22		SCALE 3/4" = 1'-0"		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT NO. 10377.028		REV.		
DRAWING NO. S302		REV.		







1
S303

STRUCTURAL SECTION 4

SCALE: 3/4" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS 1581 VAN BUREN RD, CONNOR, ME 04736				
TITLE				
STRUCTURAL SECTION				
DATE 2025.04.22		SCALE 3/4" = 1'-0"		
DRAWN BY WCT	DESIGNED BY WCT	CHECKED BY CDL		
PROJECT No. 10377.028		DRAWING NO. S303		



PROJECT GENERAL NOTES

1. THESE GENERAL NOTES ARE INTENDED TO COMPLIMENT CONTRACT DOCUMENTS. REFER TO CONTRACT DOCUMENTS FOR DETAILED INFORMATION AND ADDITIONAL REQUIREMENTS.
2. WORK INCLUDED IN THIS CONTRACT SHALL CONFORM TO FEDERAL, STATE, AND LOCAL LAWS, STATUTES, ORDINANCES, CODES, RULES AND REGULATIONS, OR LAWFUL ORDERS OF PUBLIC AUTHORITY. PROMPTLY REPORT NONCONFORMITY DISCOVERED TO ARCHITECT/ENGINEER.
3. INTENT OF CONTRACT DOCUMENTS IS TO INCLUDE ITEMS NECESSARY FOR PROPER EXECUTION AND COMPLETION OF WORK BY CONTRACTOR AND PROVIDE A COMPLETE, FULLY OPERATIONAL BUILDING, PROVIDE ALL LABOR, MATERIALS, AND INCIDENTALS NECESSARY TO ACHIEVE THIS INTENT.
4. FAILURE OF DRAWINGS OR SPECIFICATIONS TO INDICATE EACH INCIDENTAL SHALL NOT RELIEVE CONTRACTOR FROM PROVIDING NECESSARY ITEMS AS PART OF THIS CONTRACT. DRAWINGS SHOW DESIGN, LOCATION, DESCRIBE QUALITY LEVEL AND CONSTRUCTION TECHNIQUES IN A GENERAL SENSE ONLY.
5. DETAILS ARE TYPICAL, WHAT IS SHOWN IN ONE CONDITION APPLIES TO OTHER SIMILAR CONDITIONS, UNLESS NOTED OTHERWISE.
6. VERIFY FOLLOWING ITEMS AND REPORT DISCREPANCIES TO ARCHITECT PRIOR TO PROCEEDING WITH WORK, AND PROCEED WITH WORK AFTER SUCH DISCREPANCIES ARE RESOLVED.
- EXISTING CONDITIONS
 - WALLS, FLOORS, AND SUBSTRATES WHERE PRODUCTS AND SYSTEMS ARE TO BE INSTALLED.
 - SIZE AND CONDITIONS OF WINDOW, DOOR, AND OTHER OPENINGS WHERE PRODUCTS AND SYSTEMS ARE TO BE INSTALLED.
 - THE EXISTENCE, SIZE, AND LOCATION OF EXISTING UTILITIES, MECHANICAL, AND ELECTRICAL SYSTEMS.
 - DISCREPANCIES BETWEEN OR WITHIN CONTRACT DOCUMENTS.
 - UNSUITABLE SOILS: REPORT LOCATION OF UNSUITABLE SOIL MATERIALS BELOW ANTICIPATED LEVELS OF FOOTINGS OR SLABS PRIOR TO SETTING FORMS.
 - DIMENSIONAL DISCREPANCIES.
7. COORDINATE THE WORK OF SUBCONTRACTORS.
8. COORDINATE WORK TO ACHIEVE GIVEN VISUAL AND PERFORMANCE REQUIREMENTS OF MECHANICAL, ELECTRICAL, AND PLUMBING SYSTEMS WITHIN INDICATED SPACE.
9. DEFINITIONS
- NEW: INDICATES ITEMS THAT SHALL BE FURNISHED AND INSTALLED BY THIS CONTRACT. TYPICALLY USED TO ENSURE CLARITY BETWEEN VARIOUS COMPONENTS OF THE DRAWINGS. NOT ALL ITEMS ARE LABELED AS "NEW" WHEN IT IS OBVIOUS BY OTHER INDICATION.
 - EXISTING: EXISTING BUILDING OR SITE COMPONENTS WHICH ARE IN PLACE AT START OF CONSTRUCTION. NOT ALL ITEMS ARE LABELED AS "EXISTING" WHEN IT IS OBVIOUS BY OTHER INDICATION.
 - REPAIR: RESTORE TO SUITABLE OR APPROPRIATE OPERATING AND AESTHETIC CONDITION.
 - RESTORE: BRING BACK TO FORMER CONDITION, BY REPAIRING OR PATCHING AS REQUIRED.
 - PATCH: RESTORE TO CONDITION MATCHING EXISTING ADJACENT CONSTRUCTION, SURFACE TEXTURE, AND FINISH.
 - N.I.C. (NOT IN CONTRACT): WORK WHICH IS NOT INCLUDED IN THIS CONTRACT BUT WHICH MAY REQUIRE CONTRACTOR COORDINATION.
 - REMOVE: DISMANTLE AND/OR EXTRACT FROM PREMISES ENTIRELY, DISPOSE OF OFF SITE UNLESS NOTED OTHERWISE. PROVIDE NEW MATERIAL AS INDICATED.
 - DAMAGES: EXISTING BUILDING OR SITE COMPONENTS, NOT SCHEDULED FOR WORK WHICH ARE DAMAGED. SUCH ELEMENTS AND COMPONENTS SHALL BE REPLACED OR RESTORED TO ORIGINAL CONDITION BY METHODS APPROVED BY ARCHITECT.
 - DEMOLISH: DISMANTLE AND/OR EXTRACT FROM PREMISES ENTIRELY, DISPOSE OF OFF SITE UNLESS NOTED OTHERWISE.
 - SALVAGE: REMOVE AND REINSTALL OR REMOVE AND DELIVER TO OWNER AS INDICATED. SALVAGED COMPONENTS MAY BE FOR LIMITED REUSE, TO MATCH EXISTING CONDITIONS OR TO PATCH AND REPAIR AS INDICATED.

DOOR AND WINDOW NOTES

1. PROVIDE DOOR STOPS TO PROTECT WALLS AT LOCATIONS WHERE A DOOR SWING WILL STRIKE WALL.
2. EXTERIOR DOORS SHALL HAVE WEATHER STRIPPING, THRESHOLDS, AND SHALL BE INSTALLED WEATHERTIGHT.
3. REFER TO SPECIFICATION FOR DOOR & FRAME GAUGES, ANCHORS, AND REINFORCEMENT.

GENERAL ARCHITECTURAL NOTES

1. DRAWINGS USE A SYSTEM OF KEYED NOTES ON PLANS, ELEVATIONS AND DETAILS. INSTRUCTIONS FOR SPECIFIC COMPONENTS OF WORK ARE KEYED TO DRAWINGS. BUILDING SYSTEMS ARE KEYED TO FLOOR PLANS, WALL SECTIONS, ROOF PLAN, AND OTHER DETAILS AS APPROPRIATE.
2. MAINTAIN MINIMUM MANEUVERING CLEARANCES AT DOORS IN COMPLIANCE WITH ADA ACCESSIBILITY GUIDELINES (ADAAG AND ANSI A117.1).
3. MOUNTING HEIGHTS AND CLEARANCES AT TOILET ROOMS AND ELSEWHERE SHALL COMPLY WITH THE LATEST VERSION OF ADA ACCESSIBILITY GUIDELINES (ADAAG AND ANSI A117.1 ACCESSIBILITY STANDARD).
- BARRIER-FREE CLEARANCES ARE GIVEN. THESE CLEAR DIMENSIONS SHALL BE MAINTAINED IN CASES OF DISCREPANCY.
 - DIMENSIONS GIVEN FOR FIXTURE AND ACCESSORY LOCATIONS ARE CLEAR DIMENSIONS FROM FINISHED SURFACES UNLESS NOTED OTHERWISE.
4. MAINTAIN CLEAR DIMENSIONS IN ACCORDANCE WITH LATEST VERSION OF ADA ACCESSIBILITY GUIDELINES (ADAAG).
5. GRAB BAR COMPONENTS SHALL BE ABLE TO WITHSTAND A LOAD OF 250 LBS AT ANY POINT.
6. INSTALL BLOCKING BEHIND SURFACE-APPLIED FIXTURE, TRIM, GRAB BARS, SHELVES, CHAIR RAILS, PICTURE RAILS, BASE MOLDINGS, TACK OR MARKER BOARDS, WINDOW TREATMENTS, WALL OR BASE CABINETS OR COUNTERS, AND MISCELLANEOUS ACCESSORIES MOUNTED ON STUD WALLS.
7. EXPOSED WOOD NOT INDICATED SHALL BE STAINED NATURAL FINISH (CLEAR).
8. PROVIDE TRANSITION STRIPS OR THRESHOLDS (1/2" MAXIMUM) OF SAME MATERIAL AS FLOORING AND/OR AS NOTED ON DRAWINGS BETWEEN DISSIMILAR FLOORING MATERIALS.
9. PATCH AND LEVEL EXISTING SUBFLOORS TO RECEIVE NEW FLOOR FINISHES AS INDICATED IN ROOM FINISH SCHEDULE.
10. EXPOSED PIPES UNDER LAVATORIES AND SINKS SHALL BE INSULATED OR OTHERWISE CONFIGURED TO PROTECT AGAINST CONTACT.

WALL SYSTEM NOTES

1. ALL PARTITIONS SHALL EXTEND FROM SUB-FLOOR TO SLAB TO UNDERSIDE OF FLOOR OR ROOF DECK ABOVE, UNLESS NOTED OTHERWISE.
2. GYPSUM BOARD APPLIED TO WALLS SHALL BE APPLIED WITH THE BOTTOM EDGE SPACED NOT LESS THAN 1/2" ABOVE THE FLOOR. INSTALL A CONTINUOUS BEAD OF ACOUSTICAL SEALANT UNDER EACH LAYER OF GWB AT THE INTERSECTION WITH FLOOR, ON EACH SIDE OF THE WALL.
3. ALL TOP OF WALL CONDITIONS SHALL BE SEALED TO THE DECK ABOVE, UNLESS NOTED OTHERWISE. MAINTAIN THE REQUIRED FIRE RATINGS, SMOKE RATINGS, AND ACOUSTICAL RATINGS. COORDINATE THE TOP OF WALL CONSTRUCTION WITH THE STRUCTURAL FRAMING.
4. FOR EXISTING WALLS SUPPORTING NEW ITEMS, VERIFY THE WALL TYPE PRIOR TO PERFORMING THE WORK TO DETERMINE APPROPRIATE TYPE OF ANCHOR UNLESS INDICATED OTHERWISE. CONSULT ARCHITECT FOR CLARIFICATION IF NEEDED.
5. ALL EXTERIOR WOOD FRAMING IN CONTACT WITH CONCRETE, WITHIN 18" OF THE GROUND, OR EXPOSED TO THE WEATHER SHALL BE WOOD-PRESERVATIVE TREATED LUMBER (PRESSURE TREATED).

SITE MAP

NOT TO SCALE

ABBREVIATIONS

AB	ANCHOR BOLT
AB	AIR BARRIER
AC	AIR CONDITIONING
ADDL	ADDITIONAL
ADJ	ADJUSTABLE
ADO	AUTOMATIC DOOR OPERATOR
AED	AUTOMATIC ELECTRONIC DEFIBRILLATOR
AFF	ABOVE FINISHED FLOOR
AH	AIR HANDWEIGHT (CMU)
AIB	AIR INFILTRATION BARRIER
ALT	ALTERNATE
ALUM	ALUMINUM
AOR	AREA OF REFUGE
APPROX	APPROXIMATE
ARCH	ARCHITECT (URAL)
AROUND	AROUND
AVB	AIR/VAPOR BARRIER
AWP	ACOUSTICAL WALL PANEL
BD	BOARD
BF	BARRIER FREE
BIT	BITUMINOUS
BLDG	BUILDING
BLKG	BLOCKING
BM	BENCHMARK
BOT	BOTTOM
BO	BOTTOM OF
BRCK	BRICK
BRG	BEARING
B/S	BRICK SHELF
BSMT	BASEMENT
C, CRS	COURSE
CB	CABINET
CC	CATCH BASIN
CC	CENTER TO CENTER
CF	CUBIC FOOT
CFMF	COLD FORMED METAL FRAMING
CJ	CONTROL JOINT
CL	CENTERLINE
CLG	CEILING
CLR	CLEAR
CMT	CERAMIC MOSAIC TILE
CMU	CONCRETE MASONRY UNIT
CO	CLEANOUT
COL	COLUMN
CONC	CONCRETE
CONC/C	COLORLED CONCRETE
CONT	CONTINUOUS OR CONTINUE
CONTR	CONTRACTOR
CPT	CARPET
CS	COUNTERSINK
CSMT	CASEMENT
CT	CERAMIC TILE
CW	CURTAIN WALL
CERAMT	CERAMIC WALL TILE
CUH	CABINET UNIT HEATER
CY	CUBIC YARD
DBL	DOUBLE
DC	DISPLAY CASE
DEMO	DEMOLISH, DEMOLITION
DF	DRINKING FOUNTAIN
DIA, DIAM	DIAMETER
DIM	DIMENSION
DIV	DIVISION
DMP	DEMOUNTABLE PARTITION
DN	DOWN
DR	DOOR
DTL	DETAIL
DWG	DRAWING
DWR	DRAWER
E	EAST
EA	EXHAUST FAN
EF	ELECTRO MAGNETIC HOLD OPEN
EMHO	EXTERIOR INSULATION FINISH SYSTEM
EFS	EXPANSION JOINT
EJ	ELEVATION
EL	ELEVATION
EPOXY	EPOXY PAINT
ELEC	ELECTRICAL
ELEV	ELEVATOR
EMER	EMERGENCY
ENCL	ENCLOSED/ENCLOSURE
EQ	EQUAL
EQUIP	EQUIPMENT
EXH	EXHAUST
EXIST	EXISTING
EXT	EXTERIOR
EYEWASH	EYEWASH
EW	ELECTRIC WATER COOLER
EWC	ELECTRIC WATER COOLER
FB	FIRE BLANKET
FBO	FURNISHED BY OWNER
FCS	FLOOR COATING SYSTEM
FD	FLOOR DRAIN
FE	FIRE EXTINGUISHER
FEC	FIRE EXTINGUISHER AND CABINET
FFE	FINISHED FLOOR ELEVATION
FG	FIBERGLASS
FHVC	FIRE HOUSE AND VALVE CABINET
FIN	FINISH
FIN GR	FINISH GRADE
FLR	FLOOR(ING)
FLN	FOUNDATION
FP	FIREPROOFING
FPD	FLAT PANEL DISPLAY
FO	FACE OF
FRMG	FRAMING
FRP	FIBER REINFORCED PLASTIC
FRTG	FIRE RATED TEMPERED GLASS
FR	FIRE RETARDANT TREATED
FSR	FLEXIBLE SHEET ROOFING
FT	FOOT (FEET)
FTG	FOOT
FTR	FIN TUBE RADIATION
FUR	FURRED(ING)
FV	FIELD VERIFY
FWC	FABRIC WALL COVERING
GA	GAUGE
GALV	GALVANIZED
GB	GRAB BAR
GFB	GROUND FACE CMU
GL	GLASS, GLAZING
GWB	GYPSUM WALLBOARD
GMGB	GLASS MATT GYPSUM BOARD
HARD	HARDENER
HB	HOSE BIB
HC	HOLLOW CORE
HD	HEAD
HDD	HIGH DENSITY OVERLAY
HDWD	HARDWOOD
HDWR	HARDWARE
HM	HOLLOW METAL
HORIZ	HORIZONTAL
HR	HANDRAIL
HS	HIGH SCHOOL
HT	HEIGHT
HTG	HEATING
HVAC	HEATING/VENTILATION/AIR CONDITIONING
IBC	INSTALLED BY CONTRACTOR
ID	INSIDE DIAMETER
IN	INCH(ES)
INCL	INCLUDE(D),(ING)
INFO	INFORMATION
INSUL	INSULATED
ITWP	INSULATED TRANSLUCENT WALL PANELS
INT	INTERIOR
INV	INVERT
JT	JOINT
KIT	KITCHEN

SYMBOLS

	SECTION
	DETAIL
	EXTERIOR ELEVATION
	INTERIOR ELEVATION
	DOOR INDICATION
	WINDOW OR GLAZED OPENING INDICATION
	ROOM NUMBER
	WALL TYPE
	CENTERLINE
	LEVEL LINE CONTROL POINT
	MATCHLINE
	BREAKLINE
	COLUMN CENTERLINE

MATERIALS LEGEND

	CONCRETE
	EARTH
	GRAVEL
	SAND
	BRICK
	CONCRETE MASONRY UNIT
	STEEL
	WOOD
	WOOD FRAMING
	WOOD BLOCKING
	GYPSUM BOARD
	PLYWOOD
	RIGID INSULATION
	BATT INSULATION

REV | DATE | DESCRIPTION | BY | CHK

DRAWING ISSUE STATUS

ISSUED FOR BID

HALEY WARD
ENGINEERING | ENVIRONMENTAL | SURVEYING
One Merchants Plaza, Suite 701
Bangor, Maine 04401
207.989.4824

PROJECT

CONNOR SCHOOL
1581 VAN BUREN RD.
CONNOR, MAINE 04736

TITLE

ABBREVIATIONS, SYMBOLS & NOTES

DATE
2025.04.22

SCALE

DRAWN BY
Author

DESIGNED BY
Designer

CHECKED BY
Checker

PROJECT No.
10377.028

DRAWING No.
A001

REV

SEAL
REGISTERED ARCHITECT
MATTHEW G. CARTER
NO. 2887
STATE OF MAINE
2025

DATE
2025.04.22

SCALE

DRAWN BY
Author

DESIGNED BY
Designer


CHECKED BY
Checker

PROJECT No.
10377.028

DRAWING No.
A001


REV

NOTE:
MOUNTING HEIGHTS SHOWN ARE CLEARANCES REQUIRED FROM
FINISHED FLOOR AND WALL MATERIALS.




- NOTE:
1. REFER TO MANUFACTURER'S INSTRUCTIONS FOR SPECIFIC ADA REQUIRED MOUNTING HEIGHTS AS APPLICABLE.
 2. ALL CONTROLS ON ACCESSIBLE ACCESSORIES REQUIRE 5LBS MAXIMUM FORCE TO OPERATE OR ACTIVATE; ARE OPERABLE WITH ONE HAND WITHOUT REQUIRING TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST; AND ARE WITHIN COMPLIANT REACH RANGES. OPERABLE PARTS ON ACCESSIBLE ACCESSORIES TO BE 15" AFF MINIMUM AND NOT TO EXCEED 48" MAXIMUM.
 3. 35" MAX AFF TO BOTTOM OF REFLECTIVE SURFACE ON FULL LENGTH MIRRORS.

WATER CLOSET
ADA 213, 305, 308, 309, 604




- NOTE:
1. PROVIDE BLOCKING AT ALL GRAB BAR LOCATIONS.
 2. FLUSH VALVE REQUIRED TO BE ON OPEN (WIDE) SIDE.
 3. FLUSH CONTROLS ARE OPERABLE WITH ONE HAND AND DO NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST.
 4. SPACE BETWEEN THE GRAB BAR AND ANY PROJECTING OBJECT BELOW OR AT EACH END IS 1 1/2" MIN.
 5. THE SPACE BETWEEN THE GRAB BAR AND ANY PROJECTING OBJECT ABOVE IS 12" MIN, EXCEPT FOR SHOWER CONTROLS AND FITTINGS, AND OTHER GRAB BARS WHICH HAVE 1 1/2" MIN CLEAR.

URINAL
ADA 213, 305, 308, 309, 605




- NOTE:
1. FLUSH CONTROLS ARE OPERABLE WITH ONE HAND AND DO NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST.
 2. PROVIDE A 30"x48" LEVEL CLEAR SPACE IN FRONT OF THE URINAL FOR FORWARD APPROACH; IF THE WALL OR SHIELD PROJECTS MORE THAN 24" FROM THE PLUMBING WALL ON BOTH SIDES, PROVIDE A 36"x48" CLEAR FLOOR SPACE.

LAVATORY
ADA 213, 305, 308, 309, 606




- NOTE:
1. 34" AFF MAX TO RIM OF SINK.
 2. 40" MAX TO BOTTOM OF REFLECTIVE SURFACE OF MIRROR.
 3. FAUCET CONTROLS CAN NOT BE FURTHER BACK THAN THE TOE SPACE BELOW.

DRINKING FOUNTAIN CLEARANCES
ADA 211, 602




- NOTE:
1. 34" MIN HEIGHT WATER FLOW FROM CENTERLINE OF SPIGOT TYPICAL.
 2. LOW SPOUT OUTLETS ARE 36" MAXIMUM AFF WITH AN ADDITIONAL 4" MINIMUM HEIGHT WATER FLOW.

BABY CHANGING STATION
ADA 305, 306, 308



- NOTE:
1. WHERE A HIGH FORWARD REACH IS OVER AN OBSTRUCTION, THE CLEAR FLOOR SPACE SHALL EXTEND BENEATH THE ELEMENT FOR A DISTANCE NOT LESS THAN THE REQUIRED REACH DEPTH OVER THE OBSTRUCTION. THE HIGH FORWARD REACH SHALL BE 48" MAXIMUM WHERE THE REACH DEPTH IS 20" MAXIMUM. WHERE THE REACH DEPTH EXCEEDS 20", THE HIGH FORWARD REACH SHALL BE 44" MAXIMUM AND THE REACH DEPTH SHALL BE 25" MAXIMUM.

TOILET COMPARTMENT SIDE OPENING - IN-SWINGING
ADA 213.3.1, 604.8




- NOTE:
1. TOILETS HAVE A 60" MINIMUM WIDE CLEAR SPACE ALONG THE PLUMBING WALL.
 2. TOILETS HAVE 59" DEEP CLEAR SPACE FROM THE BACK WALL IF FLOOR MOUNTED AND 56" IF WALL MOUNTED.
 3. NO OTHER FIXTURES OR DOORS CAN OVERLAP THE TOILET CLEAR FLOOR SPACE EXCEPT FOR GRAB BARS, DISPENSERS, SANITARY NAPKIN DISPOSAL UNITS, COAT HOOKS, SHELVES, CLEAR FLOOR SPACE OF OTHER FIXTURES, AND TURNING SPACES.
 4. AN IN-SWINGING DOOR CAN SWING INTO THE SPACE IN FRONT OF THE TOILET CLEAR FLOOR SPACE, BUT IT CANNOT ENCROACH INTO THE MINIMUM OF 56" OR 59" DEPTH REQUIRED FOR THE TOILET CLEAR SPACE.
 5. TOE CLEARANCE OF 9" HEIGHT AND 6" DEEP MINIMUM BEYOND ONE SIDE PARTITION IS PROVIDED IF THE COMPARTMENT IS 66" OR LESS WIDE EXCLUSIVE OF PARTITION SUPPORT.
 6. TOE CLEARANCE OF 9" HEIGHT AND 6" DEEP BEYOND THE FRONT PARTITION IS PROVIDED IF THE COMPARTMENT IS 62" OR LESS DEEP FOR WALL HUNG TOILETS OR 65" OR LESS DEEP FOR FLOOR MOUNTED EXCLUSIVE OF PARTITION SUPPORT.
 7. ACCESSIBLE STALL DOOR TO HAVE SELF-CLOSING HINGES WITH ACCESSIBLE HARDWARE ON BOTH SIDES. IF COAT HOOK PROVIDED MUST NOT EXCEED 48" MAX AFF.

3. FIXTURE AND ACCESSORY MOUNTING HEIGHTS


4. TOILET COMPARTMENTS

FRONT APPROACH
FULL SIDE




PUSH SIDE WITH BOTH CLOSER & LATCH

FRONT APPROACH
PUSH SIDE




PUSH SIDE

HINGE APPROACH
FULL SIDE




PUSH SIDE WITH BOTH CLOSER & LATCH

HINGE APPROACH
FULL SIDE




PUSH SIDE

LATCH APPROACH
FULL SIDE




PUSH SIDE WITH CLOSER

LATCH APPROACH
FULL SIDE




PUSH SIDE

POCKET DOOR




BARN DOOR


FRONT APPROACH
BI-FOLD & SLIDING/POCKET



HINGE/POCKET SIDE APPROACH
BI-FOLD & SLIDING/POCKET




LATCH SIDE APPROACH
BI-FOLD & SLIDING/POCKET




- NOTE:
1. REFERENCE ADA 404.2

T-SHAPED TURN
ADA 304.3




- NOTE:
1. ONLY ONE OF THE 3 ARMS OF THE T CAN GO UNDERNEATH AN OBJECT WITH KNEE/TOE CLEARANCE BELOW

CIRCULAR TURN
ADA 304.3




- NOTE:
1. TURNING SPACE CAN GO UNDERNEATH AN OBJECT WITH KNEE/TOE CLEARANCE BELOW

T-SHAPED PASSING SPACE
ADA 403.5



- NOTE:
1. * = AS REQUIRED FOR ACCESSIBLE ROUTE



ACCESSIBLE ROUTE CLEAR WIDTH
ADA 403.5




- NOTE:
1. * = CLEAR BETWEEN PROTRUSIONS

2. MANEUVERING CLEARANCES AT DOORS

1. ACCESSIBLE ROUTES


REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
ACCESSIBILITY REQUIREMENTS				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY KEK	DESIGNED BY KEK	CHECKED BY MGC		
PROJECT No. 10377.028				
DRAWING No.				REV
				A002



A 3-3/4" (2X4 WOOD STUDS)

*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED


A - PARTITION TYPE
B.O. TRUSS



A2 6-3/4" (2X6 WOOD STUDS)

*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED


A2 - PARTITION TYPE
B.O. TRUSS



A3 2-1/8" (2X4 WOOD STUDS)

*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED


A3 - PARTITION TYPE
B.O. TRUSS



B 6" CMU BLOCK WALL

*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED


B - PARTITION TYPE
6" CMU BLOCK WALL



B2 6" CMU BLOCK WALL
WITH BRICK EXTERIOR

*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED


B2 - PARTITION TYPE
6" CMU WALL WITH BRICK



C SINGLE WYTHE BRICK WALL


*CONFIRM AGAINST EXISTING WALL SIZES
WHERE ALIGNING WITH EXISTING WALL &
AGAINST EXISTING DOORS BEING REUSED

C - PARTITION TYPE
SINGLE WYTHE BRICK WALL





1 ENTRY DESK WALL SECTION
A003 SCALE: 1/2" = 1'-0"


1 PARTITION TYPES
A003 SCALE: 1 1/2" = 1'-0"

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
PARTITION TYPES / WALL SECTIONS				
DATE		2025.04.22		SCALE
DRAWN BY		DESIGNED BY		As indicated
Author		AM		JM
PROJECT No.		10377.028		
DRAWING NO.		A003		REV


DEMOLITION NOTES		
Number	Description	
1	REMOVE WINDOW.	
2	DOOR AND ASSEMBLY.	
3	REMOVE MILLWORK AND SINK. NEW SINK LOCATION PER PLAN	
4	REMOVE SIDEWALK	
5	REMOVE FLOORING.	




REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
		HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824		
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
FIRST FLOOR DEMOLITION PLAN				
DATE 2025.04.22		SCALE 1/8" = 1'-0"		
DRAWN BY JAM	DESIGNED BY Designer	CHECKED BY Checker		
PROJECT No. 10377.028				
DRAWING NO. AD101		REV		





Autodesk Civil 3D 11/03/27 02:11:42 - R23 - Connor School 10377 028 1/3 16/26/24.rvt




1 FIRST FLOOR
SCALE: 1/8" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div><div>WWW.HALEYWARD.COM</div></div>				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
FIRST FLOOR PLAN				
DATE		SCALE		
2025.04.22		1/8" = 1'-0"		
DRAWN BY	DESIGNED BY	CHECKED BY		
AM	Designer	JM		
PROJECT No.		10377.028		
DRAWING NO.				REV.
A101				





REV.	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
<div><div></div><div>ISSUED FOR BID</div></div>				
<div><div><div>HALEY WARD</div><div>ENGINEERING ENVIRONMENTAL SURVEYING</div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div><div>WWW.HALEYWARD.COM</div></div></div>				
PROJECT				
<div><div>CONNOR SCHOOL</div><div>1581 VAN BUREN RD. CONNOR, MAINE 04736</div></div>				
TITLE				
<div>ROOF PLAN AND REFLECTED CEILING PLAN</div>				
		DATE		SCALE
		2025.04.22		1/4" = 1'-0"
		DRAWN BY	DESIGNED BY	CHECKED BY
JAM		Designer	Checker	
PROJECT No.				
10377 028				
DRAWING NO.				REV.
A102				


A:\000\Draw\10377\028 - R023 - Connor School\10377 CONNOR SCHOOL_ARCH V3 16-26-24.rvt




1 FURNITURE PLAN
SCALE: 1/4" = 1'-0"




REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
FURNITURE PLAN				
DATE 2025.04.22		SCALE 1/4" = 1'-0"		
DRAWN BY AM	DESIGNED BY AM	CHECKED BY MGC		
PROJECT No. 10377.028				
DRAWING NO. A103				REV







1
A201
FRONT ENTRY VIEW
SCALE:




3
A201
PROPOSED WEST ELEVATION WITH ENTRY ADDITION
SCALE: 1/8" = 1'-0"




2
A201
WEST ELEVATION - ENLARGED
SCALE: 1/4" = 1'-0"


REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
EXTERIOR ELEVATION				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY JAM	DESIGNED BY Designer	CHECKED BY Checker		
PROJECT No. 10377.028				
DRAWING NO. A201		REV.		




2 SECTION AT ENTRY VESTIBULE DOORS
SCALE: 3/8" = 1'-0"




3 ROOF CONNECTION DETAIL
SCALE: 1 1/2" = 1'-0"




4 SECTION AT FRONT OFFICE MASONRY WALL
SCALE: 3/8" = 1'-0"

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
BUILDING SECTIONS				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY AM	DESIGNED BY JAM	CHECKED BY JM		
PROJECT No. 10377.028		REV		
DRAWING NO. A301		REV		






Autodesk Draw #10377.028 - R23 - Connor School#10377.028 CONNOR SCHOOL_ARCH V3 16-26-24.rvt




1 ENLARGED ENTRY AREA
A401 SCALE: 1/4" = 1'-0"

KEY NOTES	
Number	Description
1	INFILL WALL. MATCH ADJACENT FINISHES.
2	BUILT-IN WORK SURFACE. FINISH PER OWNER.
3	NEW CONC. SLAB. FINISH PER OWNER
4	NEW CASEWORK AND PLUMBING FIXTURES.
5	NEW CASEWORK. THERMOFOIL FINISH. COLOR PER OWNER

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
ENLARGED PLANS				
DATE		2025.04.22		SCALE
DRAWN BY		DESIGNED BY		CHECKED BY
JAM		Designer		Checker
PROJECT No.		10377.028		
DRAWING NO.		REV		
		A401		



- MILLWORK GENERAL NOTES:**
1. THERMOFOIL SLAB DOORS ON 3/4" PLYWOOD FRAMELESS CABINETS. FINISH COLOR/STYLE PER OWNER.
 2. INTERIOR FINISH: MELAMINE.
 3. PROVIDE ADJUSTABLE, 1/2" MELAMINE SHELVES, BORED PIN & HOLE METHOD.
 4. PROVIDE SMOOTH CLOSE HINGES AND DRAWER GLIDES.
 5. PULLS: 4" BAR PULL. STYLE PER OWNER.
 6. PROVIDE INTEGRAL TOE KICK AT SINK BASE. FLOOR FINISH TO CONTINUE UNDER SINK BASE.
 7. PLASTIC LAMINATE COUNTERTOP: 1 1/2" W/ EASED EDGE AND 4" MATCHING BACKSPLASH UNLESS NOTED OTHERWISE.

REV.	DATE	DESCRIPTION	BY	CHK.																																								
DRAWING ISSUE STATUS																																												
ISSUED FOR BID																																												
<div><div><div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div><div>WWW.HALEYWARD.COM</div></div></div>																																												
PROJECT																																												
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736																																												
TITLE																																												
MILLWORK DETAILS																																												
<table><tr><td colspan="2">DATE</td><td colspan="3">SCALE</td></tr><tr><td colspan="2">2025.04.22</td><td colspan="3">As Indicated</td></tr><tr><td>DRAWN BY</td><td>DESIGNED BY</td><td colspan="2">CHECKED BY</td><td></td></tr><tr><td>AM</td><td>AM</td><td colspan="2">MGC</td><td></td></tr><tr><td colspan="5">PROJECT NO.</td></tr><tr><td colspan="5">10377 028</td></tr><tr><td colspan="4">DRAWING NO.</td><td>REV.</td></tr><tr><td colspan="4">A501</td><td></td></tr></table>					DATE		SCALE			2025.04.22		As Indicated			DRAWN BY	DESIGNED BY	CHECKED BY			AM	AM	MGC			PROJECT NO.					10377 028					DRAWING NO.				REV.	A501				
DATE		SCALE																																										
2025.04.22		As Indicated																																										
DRAWN BY	DESIGNED BY	CHECKED BY																																										
AM	AM	MGC																																										
PROJECT NO.																																												
10377 028																																												
DRAWING NO.				REV.																																								
A501																																												


Autodesk Draw110377.028 - R23 - Connor School110377.028 CONNOR SCHOOL.ARCN V3 16-26-24.rvt

- GENERAL NOTES:
1. CONTRACTOR TO PROVIDE DOOR AND DOOR HARDWARE SPECIFICATIONS.
 2. INTERIOR DOOR HARDWARE FINISHES AND TYPES TO BE SATIN CHROME OR BRUSHED STAINLESS STEEL.
 3. REPLACE EXISTING DOORS WITH SOLID CORE FLUSH DOOR TYPE 'A'. DOOR TRIM TO MATCH EXISTING STYLES.
 4. EXISTING DOOR HEIGHTS AND WIDTHS ARE SHOWN FOR REFERENCE ONLY.
 5. REPLACE ALL EXISTING KNOBS WITH LEVER HARDWARE.
 6. REPLACE ALL EXISTING KNOBS, DOOR HINGES, AND FLOOR STOPS WITH SATIN CHROME OR BRUSHED STAINLESS STEEL.
 7. CONFIRM ALL LOCKING AND ACCESS CONTROL REQUIREMENTS WITH OWNER & ARCHITECT.
 8. MAGLOCK, PUSH BUTTON DOOR RELEASE, CARD READER, CLOSER, AND ANY OTHER ASSOCIATED EGRESS HARDWARE TO REMAIN ON EXISTING DOORS UNLESS OTHERWISE NOTED. CONFIRM ALL HARDWARE IS FUNCTIONAL AND SUITABLE FOR REUSE.
 9. REUSE SALVAGED DOORS AND FRAMES REMOVED DURING DEMOLITION WHERE APPLICABLE. OWNER AND ARCHITECT SHALL REVIEW ALL SALVAGED DOORS WITH CONTRACTOR PRIOR TO DEMOLITION AND INSTALLATION.
 10. CONFIRM DOORS AGAINST DRAWINGS. NOTIFY ARCHITECT OF ANY DISCREPENCIES.
 11. PROVIDE FRAME ROUGH OPENINGS AS RECOMMENDED BY FRAME MANUFACTURER.
 12. INSTALLATION OF ALL DOORS AND HARDWARE SHALL MEET 521 CMR REQUIREMENTS. NOTIFY ARCHITECT IF ANY CLEARANCES CANNOT BE MET PRIOR TO CONSTRUCTION.
 13. ALL DOORS SHALL COMPLY WITH MINIMUM 521 CMR REQUIRED APPROACH CLEARANCES. NOTIFY ARCHITECT IF MINIMUM CANNOT BE ACHIEVED.

DOOR SCHEDULE												
DOOR NUMBER	DOOR							FRAME		FIRE RATING	HARDWARE SETS	COMMENTS
	LOCATION	WIDTH	HEIGHT	THICKNESS	TYPE	MATERIAL	FINISH	TYPE	MATERIAL	FINISH		
125	LOBBY	2' - 11 1/2"	6' - 5 1/2"		B	GLASS	ANODIZED ALUM		STOREFRONT	ANNODIZED ALUM	PANIC	BULLET RESISTENT GLASS. ELECTRIC STRIKE LATCH
125A	LOBBY	2' - 11 1/2"	6' - 5 1/2"		B	GLASS	ANODIZED ALUM		STOREFRONT	ANNODIZED ALUM	PANIC	BULLET RESISTENT
126	VESTIBULE	2' - 11 1/2"	6' - 5 1/2"		B	GLASS	ANODIZED ALUM		STOREFRONT	ANNODIZED ALUM	PANIC	PROVIDE ACCESSIBLE AUTO ENTRANCE PAD AND OPENER
126A	VESTIBULE	2' - 11 1/2"	6' - 5 1/2"		B	GLASS	ANODIZED ALUM		STOREFRONT	ANNODIZED ALUM	PANIC	BULLET RESISTENT- DOORWAY TO HAVE ELECT. STRIKE AND REMOTE RELEASE
128	FRONT OFFICE	3' - 0"	7' - 0"	0' - 1 3/4"	A	WOOD	STAIN / POLY		HM	PAINT	LEVER; OFFICE	
129	ADMIN OFFICE	3' - 0"	7' - 0"	0' - 1 3/4"	A	WOOD	STAIN / POLY		HM	PAINT	LEVER; OFFICE	



WINDOW SCHEDULE							
Type Mark	Count	Description	Height	Width	Head Height	Sill Height	Comments
A	2	FIXED; VINYL; DOUBLE PANE	4' - 0"	3' - 0"	6' - 4 1/2"	2' - 4 1/2"	
A1	2	FIXED; VINYL; DOUBLE PANE	4' - 0"	2' - 0"	6' - 4 1/2"	2' - 4 1/2"	MULL TOGETHER WITH A
A11	1	SECURE TICKET/TELLER WINDOW	3' - 0"	3' - 0"	5' - 7 3/4"	2' - 7 3/4"	BULLET RESISTANT
Grand total: 5							

FINISH SCHEDULE						
NUMBER	NAME	Area	FLOOR FIELD	BASE FINISH	WALL FINISH	CEILING FINISH
119	BREAK ROOM	235 SF	VCT	VINYL BASE	PAINT	EXISTING TO REMAIN
126	VESTIBULE	184 SF	SEALED CONCRETE	VINYL BASE	PAINT	ACT
128	FRONT OFFICE	169 SF	CARPET TILE	VINYL BASE	PAINT	ACT
129	ADMIN OFFICE	167 SF	CARPET TILE	VINYL BASE	PAINT	ACT




DOOR TYPES

SCALE: 1/4" = 1'-0"



FRAME TYPES



SCALE: 1/4" = 1'-0"



CW1 - ENTRY STOREFRONT


SCALE: 1/4" = 1'-0"

**BULLET RESISTENT GLASS. THREAT LEVEL TO BE DETERMINED



WINDOW TYPES

SCALE: 1/4" = 1'-0"

REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD ENGINEERING ENVIRONMENTAL SURVEYING One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div>				
PROJECT				
CONNOR SCHOOL 1581 VAN BUREN RD. CONNOR, MAINE 04736				
TITLE				
SCHEDULES				
DATE		SCALE		
2025.04.22		1/4" = 1'-0"		
DRAWN BY		DESIGNED BY		CHECKED BY
AM		AM		MGC
PROJECT No.				
10377.028				
DRAWING NO.				REV.
A601				

Autodesk Docs/10377.028 - R23 - Connor School/10377 - CONNOR SCHOOL - MEP.rvt

ABBREVIATIONS

AC	ABOVE CEILING
AD	ACCESS DOOR
AD	AREA DRAIN
ADA	AMERICANS WITH DISABILITIES ACT
AFF	ABOVE FINISHED FLOOR
AP	ACCESS PANEL
ATC	AUTOMATIC TEMPERATURE CONTROL
AV	AIR VENT
BFP	BACK FLOW PREVENTER
BOP	BOTTOM OF PIPE
CD	CONDENSATE
CFCI	CONTRACTOR FURNISHED CONTRACTOR INSTALLED
CFF	CAPPED FOR FUTURE
CFH	CUBIC FEET PER HOUR
CO	CLEAN OUT
COND	CONDENSATE
CONT	CONTINUATION
COORD	COORDINATION
CSS	CLINIC SERVICE SINK
CTE	CONNECT TO EXISTING
CU	COPPER
CW	COLD WATER
DC	DOUBLE CONTAINED
DCO	DANDY CLEANOUT
DOV	DOUBLE CHECK VAVLE
DDC	DIRECT DIGITAL CONTROL
DF	DRINKING FOUNTAIN
DFU	DRINKING FIXTURE UNIT
DIA	DIAMETER
DIC	DOWN IN CHASE
DIW	DOWN IN WALL
DN	DOWN
DS	DOWNSPOUT
DT	DROP AND TRANSITION
DWH	DOMESTIC WATER HEATER
ERV	ENERGY RECOVERY VENTILATORS
ELEV	ELEVATOR
ETR	EXISTING TO REMAIN
EWC	ELECTRIC WATER COOLER
EX	EXAMPLE
F	FURNACE
FBO	FURNISHED BY OWNER
FC	FIELD CONNECT
FCO	FLOOR CLEAN OUT
FLR	FLOOR
FD	FLOOR DRAIN
FD	FUNNEL FLOOR DRAIN
FG	FIBERGLASS
FRHB	FREEZE RESISTANT HOSE BIB
FS	FLOW SWITCH
FU	FIXTURE UNIT
G	GALLON
GAL	GENERAL CONTRACTOR
G.C.	GALLONS PER FLUSH
GPF	GALLONS PER FLUSH
GPM	GALLONS PER MINUTE
CVTR	GREASE VENT THROUGH ROOF
GW	GREASE WASTE
HB	HOSE BIB
HC	HANDICAPPED ACCESSIBLE
HRU	HEAT RECOVERY UNIT
HTR	HEATER
HW	HOT WATER
HX	HEAT EXCHANGER
IN	INCHES
INV	INVERT
IAW	IN ACCORDANCE WITH IN WG INCHES WATER GAUGE
IWFD	INDIRECT WASTE FUNNEL DRAIN
IW, ID	INDIRECT WASTE
LP	LIQUEFIED PROPANE
L, LAV	LAVATORY
LS	JANITOR'S SINK
MAU	MAKEUP AIR UNIT
MAX.	MAXIMUM
MBH	1000 BTU/HR
MC	MECHANICAL CONTRACTOR
MIN.	MINIMUM
MPV	MULTI-PURPOSE VALVE
MSB	MOP SERVICE SINK
MTD	MOUNTED
MV	MIXING VALVE
NC	NORMALLY CLOSED
NG	NATURAL GAS
NO	NORMALLY OPEN
NIC	NOT IN CONTRACT
NPW	NON-POTABLE WATER
NTS	NOT TO SCALE
OFCI	OWNER FURNISHED CONTRACTOR INSTALLED
PC	PLUMBING CONTRACTOR
PDI	PUMBING & DRAINAGE INSTITUTE
PLUMB	PLUMBING
PP	POLYPROPYLENE
PPE	PREPURCHASED EQUIPMENT
PRS	PRESSURE REDUCING STATION
PRV	PRESSURE REDUCING VAVLE
PSI	POUNDS PER SQUARE INCH
RD	ROOF DRAIN
RDOF	ROOF DRAIN OVERFLOW
RHW	RECIRCULATION HOT WATER
RPZ	REDUCE PRESSURE ZONE BFP
RV	RELIEF VALVE
S	SANITARY
SAN	SANITARY
SCV	SELF CONTAINED VALVE
SD	STORM DRAIN
SH	SHOWER
SK	SINK
SQ. FT.	CALCULATED SURFACE AREA OF ROOF, ADJACENT WALLS, ETC.
SS	STAINLESS STEEL
ST	STORM
T&P	TEMPERATURE & PRESSURE RELIEF VALVE
TE	TEMPERATURE ELEMENT
TMV	THERMOSTATIC MIXING VALVE
TOP	TOP OF PIPE
TP	TRAP PRIMER
TYP.	TYPICAL
UIC	UP IN CHASE
UIW	UP IN WALL
U.O.N.	UNLESS OTHERWISE NOTED
UR	URINAL
UV	UNIT VENTILATOR
V	VENT
VB	VACUUM BREAKER
VCFE	VALVED AND CAPPED FOR FUTURE
VFD	VARIABLE FEQUENCY DRIVE
VIF	VERIFY IN FIELD
VOL	VOLUME
VTR	VENT THRU ROOF
W	WASTE
W/	WITH
WC	WATER CLOSET
W&V	WASTE AND VENT
WCO	WALL CLEAN OUT
WFU	WATER FIXTURE UNITS
WH	WALL HYDRANT
WHA	WATER HAMMER ARRESTOR
W&T	WASTE AND TRAP
ZVB	ZONE VALVE BOX

PIPING SYMBOLS

	PIPE ELBOW TURNED DOWN
	PIPE ELBOW TURNED UP
	P-TRAP (W&T)
	PIPE TEE DOWN
	PIPE TEE UP
	PIPE BREAK
	DIRECTION OF FLOW
	PIPE PITCHES DOWN
	UNION
	PIPE ANCHOR
	PIPE GUIDE OR SLEEVES
	GENERIC VALVE, SEE SPECIFICATIONS FOR TYPE
	GATE VALVE
	BALL VALVE
	BUTTERFLY VALVE (MANUAL)
	2-WAY CONTROL VALVE
	3-WAY CONTROL VALVE
	CALIBRATED BALANCING VALVE (CIRCUIT SETTER)
	AUTOMATIC FLOW CONTROL VALVE
	CHECK VALVE
	BACK FLOW PREVENTER
	GLOBE VALVE
	NEEDLE VALVE
	PLUG VALVE
	SOLENOID VALVE
	OS&Y VALVE
	PRESSURE REDUCING OR REGULATING VALVE
	MANUAL AIR VENT
	AUTOMATIC AIR VENT
	VACUUM BREAKER
	CONCENTRIC REDUCER/INCREASER
	ECCENTRIC REDUCER/INCREASER
	FLEXIBLE PIPE CONNECTOR
	EXPANSION JOINT
	PUMP
	TEMPERATURE & PRESSURE TAP (PETE'S PLUG)
	PRESSURE GAUGE AND COOK
	THERMOMETER AND WELL
	PRESSURE RELIEF VALVE
	HOSE END DRAIN VALVE WITH CAP
	HOSE BIBB
	PIPE CAP
	CLEAN OUT
	WATER HAMMER ARRESTOR
	WATER METER
	STRAINER
	STRAINER WITH BLOWDOWN

PIPING SYMBOLS

	EXISTING PIPING TO REMAIN
	EXISTING PIPING TO BE REMOVED
	DOMESTIC COLD WATER
	DOMESTIC HOT WATER
	DOMESTIC RECIRCULATION HOT WATER
	DOMESTIC COLD WATER (BELOW SLAB)
	DOMESTIC HOT WATER (BELOW SLAB)
	TRAP PRIMER
	TRAP PRIMER (BELOW SLAB)
	CONDENSATE DRAIN
	GAS PIPING
	KITCHEN SANITARY TO GREASE INTERCEPTOR
	KITCHEN SANITARY TO GREASE INTERCEPTOR (UNDER SLAB)
	SANITARY
	SANITARY (BELOW SLAB)
	SANITARY VENT
	SANITARY VENT (BELOW SLAB)
	STORM WATER
	STORM WATER (BELOW SLAB)
	STORM WATER OVERFLOW
	STORM WATER OVERFLOW (BELOW SLAB)
	PUMPED DISCHARGE

MISCELLANEOUS SYMBOLS

	DETAIL NUMBER
	SHEET NUMBER WHERE DETAIL IS LOCATED
	CONNECT NEW TO EXISTING
	LIMITS OF DEMOLITION
	REVISION NUMBER

PLUMBING EQUIPMENT ABBREVIATIONS

(REFER TO PLUMBING SCHEDULE SHEET FOR INFORMATION)

PET	EXPANSION TANK
DWH	DOMESTIC WATER HEATER
RP	RECIRCULATION PUMP
MV	THERMOSTATIC MIXING VALVE

PLUMBING FIXTURES ABBREVIATIONS

(REFER TO PLUMBING FIXTURE SCHEDULE SHEET FOR INFORMATION)

BF	BOTTLE FILLER
FD	FLOOR DRAIN
FCO	FLOOR CLEANOUT
FPBH	FREEZEPROOF HOSE BIBB
LV	LAVATORY
MB	MOP BASIN
SH	SHOWER
SK	SINK
TP	TRAP PRIMER
UR	URINAL
WB	WALL BOX
WC	WATER CLOSET

EXISTING EQUIPMENT LEGEND

(E)	EXISTING TO REMAIN
(R)	EXISTING TO BE DISCONNECTED AND REMOVED
(RL)	EXISTING TO BE DISCONNECTED AND RELOCATED
(ER)	EXISTING IN NEW LOCATION
(RP)	EXISTING TO BE REPLACED



PLUMBING NOTES


- ALL PLUMBING GENERAL NOTES, SYMBOLS, LISTS AND DETAILS ARE TO BE CONSIDERED AS APPLICABLE TO ALL PLUMBING DRAWINGS FOR THIS PROJECT.
- OBTAIN ALL PERMITS AND APPROVALS TO PERFORM THE WORK.
- PLUMBING CONTRACTOR SHALL REPORT ASBESTOS TO GENERAL CONTRACTOR.
- SAFETY CONFINED SPACE WORK: THE CONTRACTOR IS RESPONSIBLE TO PROVIDE TEMPORARY LIGHTING, VENTILATION, EMERGENCY EXTRACTION EQUIPMENT, ETC. FOR ALL WORK WITHIN CONFINED SPACE (IF APPLICABLE).
- THE DRAWINGS ARE DIAGRAMMATIC IN NATURE AND EXACT LOCATIONS AND ARRANGEMENTS OF EXISTING AND NEW EQUIPMENT, DUCTWORK, PIPING AND OTHER COMPONENTS SHALL BE DETERMINED IN THE FIELD WITH DUE CONSIDERATION OF STRUCTURAL, ELECTRICAL AND ARCHITECTURAL SYSTEM. EXISTING STRUCTURAL SYSTEMS SHALL NOT BE MODIFIED WITHOUT THE EXPRESS PERMISSION OF THE ENGINEER.
- THE CONTRACTOR SHALL VISIT THE SITE, BECOME FAMILIAR WITH THE EXISTING FIELD CONDITIONS, AND MAKE THEIR OWN ESTIMATE OF THE DIFFICULTIES IN EXECUTING THE WORK PRIOR TO SUBMITTING ITS BID. NO COMPENSATION WILL BE AWARDED TO THE CONTRACTOR BASED ON A CLAIM OF LACK OF KNOWLEDGE OF EXISTING FIELD CONDITIONS.
- REVIEW PROTOCOL AND PROCEDURES WITH FACILITY OWNERS AND OPERATORS PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING BUILDING OWNER'S PROTOCOL AND PROCEDURES BY ITS EMPLOYEES AND SUB-CONTRACTORS.
- ALL WORK SHALL BE IN ACCORDANCE WITH THE INTERNATIONAL BUILDING CODE, THE ACCEPTED PLUMBING CODE WITH STATE AMENDMENTS, THE AHJ AND THE LOCAL PLUMBING INSPECTOR.
- IF REQUIRED THE PROJECT SHALL BE PHASED IN ACCORDANCE WITH THE APPROVED PHASING PLAN. THE CONTRACTOR SHALL OBTAIN APPROVAL FOR THE SEQUENCING AND TIMING OF OPERATIONS PRIOR TO COMMENCING WORK. SEE SPECIFICATIONS.
- CONTRACTOR IS TO MAINTAIN SERVICE TO ROOMS OUTSIDE THE PROJECT SCOPE OF WORK AND PHASING SCHEDULE. IF INTERRUPTION OF SERVICE IS REQUIRED COORDINATE SHUTDOWN WITH PROJECT ENGINEER AND OWNER.
- THE CONTRACTOR SHALL VERIFY SHUTDOWN AND ISOLATION VALVE LOCATIONS. THE CONTRACTOR SHALL COORDINATE ALL SHUTDOWN WORK WITH THE FACILITY OWNER AND OPERATOR.
- CARE SHALL BE TAKEN BY THE CONTRACTOR TO PROTECT EXISTING SYSTEMS AND SURFACES TO REMAIN. RESTORE DAMAGED AREAS THAT ARE BEYOND THE SCOPE OF THIS CONTRACT TO THEIR ORIGINAL CONDITION.
- WHERE INDICATED ON THE DRAWINGS, REMOVE OR RELOCATE EXISTING COMPONENTS AS REQUIRED TO ACCOMMODATE THE NEW WORK. REMOVALS SHALL INCLUDE ALL ASSOCIATED OFF-SITE DISPOSAL COSTS.
- PIPING AND EQUIPMENT ARE NOT COMPLETELY DETAILED ON THE DIAGRAMS AND ELEVATIONS PROVIDED ON THE DRAWINGS ARE APPROXIMATE. THE DISTRIBUTION IS INTENDED AS A GENERAL ROUTING ONLY, BUT DOES ILLUSTRATE THE DESIRED LOCATION. THE CONTRACTOR SHALL AVOID INTERFERENCES WITH OTHER EQUIPMENT AND THE WORK OF OTHER DISCIPLINES.
- NOT ALL VALVES, INSTRUMENTS AND CONTROLS ARE SHOWN IN THE PLAN VIEWS. INSTALL PIPING AND VALVES AS SHOWN ON PIPING DIAGRAMS AND DETAILS. SEE DETAILS, PIPING DIAGRAMS AND MANUFACTURER'S RECOMMENDATIONS FOR ADDITIONAL VALVES & FITTINGS NECESSARY FOR COMPLETE PIPING SYSTEM.
- DRAWINGS OF REVISED PIPING ARRANGEMENTS SHALL BE SUBMITTED IF ITEMS ARE NOT SHOWN ON THE DRAWINGS. REVISIONS SHALL BE SUBJECT TO REVIEW AND APPROVAL BY THE ENGINEER PRIOR TO COMMENCEMENT OF THE CHANGES.
- COORDINATE REMOVALS AND RELOCATION'S INCLUDING SELECTIVE CUTTING AND PENETRATIONS WITH ARCHITECTURAL, MECHANICAL STRUCTURAL AND ELECTRICAL CONTRACTORS.
- FIELD VERIFY EXISTING EQUIPMENT AND PIPING PRIOR TO REMOVAL OR REUSE. CONFIRM WITH PROJECT ENGINEER THAT ALL EQUIPMENT AND PIPING DESIGNATED TO BE REMOVED IS NO LONGER IN SERVICE PRIOR TO ITS REMOVAL. PROJECT ENGINEER SHALL HAVE FIRST RIGHT OF REFUSAL ON ALL DEMOD EQUIPMENT.
- EXISTING EQUIPMENT AND PIPING TO REMAIN IN SERVICE SHALL BE INSPECTED. REPORT INOPERABLE EQUIPMENT TO PROJECT ENGINEER.
- ALL UNUSED (ABANDONED), PIPING AND EQUIPMENT INDICATED TO BE REMOVED SHALL BE REMOVED AND CAPPED.
- TIE-IN POINT LOCATIONS ARE APPROXIMATE. CONTRACTOR SHALL DETERMINE EXACT LOCATIONS IN THE FIELD BASED ON EXISTING CONDITIONS.
- COORDINATE THE LOCATIONS OF ALL WALL MOUNTED EQUIPMENT WITH FINAL EQUIPMENT/FURNITURE LAYOUT.
- INTENT OF PROJECT IS FOR NEW MATERIALS AND COMPONENTS TO MATCH EXISTING. ALL MATERIALS SHALL BE APPROVED BY THE FACILITY OWNERS AND OPERATORS.
- EQUIPMENT SCHEDULED IS THE BASIS OF DESIGN, OR APPROVED EQUAL.
- COORDINATE ELECTRICAL POWER REQUIREMENTS FOR ALL MOTORS.
- COORDINATE WITH OWNER FURNISHED EQUIPMENT AND SYSTEMS.
- PLUMBING CONTRACTOR SHALL PROVIDE ALL SUPPLEMENTARY STRUCTURAL SUPPORTS, ANGLE IRON, PLATES, ROD, ETC. AS NECESSARY FOR PROPER INSTALLATION OF PIPING, EQUIPMENT, AND ACCESSORIES.
- CONTRACTOR SHALL BE RESPONSIBLE FOR SIZING SUPPORTS, STRUT RACKS, TRAPZEE STEEL, PIPE SUPPORT COMPONENTS, ETC AT THE END OF EACH WORKING DAY. THE CONSTRUCTION SITE SHALL BE LEFT IN A CLEAN AND NEAT CONDITION.
- INSTALL EQUIPMENT IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND GOOD PRACTICE NORMAL TO THE TRADE. INSTALLATION SHALL INCLUDE PROVISIONS FOR ACCESS TO NORMAL MAINTENANCE ITEMS. PROVIDE ADEQUATE STRUCTURAL SUPPORTS AND SECURE MOUNTING METHODS WITH PROVISIONS FOR VIBRATION ISOLATION AND EXPANSION WHERE REQUIRED.
- COORDINATE ALL PENETRATIONS WITH GENERAL CONTRACTOR. SEE ARCHITECTURAL DRAWINGS FOR PENETRATION DETAILS. PLUMBING CONTRACTOR SHALL PROVIDE FLASHING AND COUNTER FLASHING FOR ROOF PENETRATIONS AS REQUIRED.
- CONTRACTOR TO COORDINATE ALL WORK WITH OTHER BUILDING TRADES, RELOCATION OF EXISTING UTILITIES MAY BE NECESSARY TO ACCOMMODATE INSTALLATION OF NEW EQUIPMENT OR DUCTWORK.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL DAMAGE MADE BY ITS FIRM ON NEW OR EXISTING EQUIPMENT INSTALLED OR RELOCATED BY THEM UNDER THIS CONTRACT. THIS SHALL INCLUDE ALL TOUCH-UP PAINTING.

SHEET LIST - PLUMBING


P-001	PLUMBING NOTES, SYMBOLS & ABBREVIATIONS
PD101	PLUMBING DOMESTIC FIRST FLOOR PLAN DEMOLITION PLAN
P-101	DOMESTIC AND DWV PLUMBING PLANS
P-501	PLUMBING DETAILS & SCHEDULES

- CONTRACTOR SHALL FIELD VERIFY ALL CLEARANCES AND DIMENSIONS.
- PROVIDE ACCESS PANELS FOR ALL CONCEALED SHUT-OFF VALVES EXCEPT THOSE ABOVE SUSPENDED CEILING.
- INFILL ALL NEW OR EXISTING ABANDONED FLOOR SLAB PENETRATIONS WITH GROUT, FULL THICKNESS OF SLAB. MAINTAIN FIRE RATING. ALL EXISTING CONCRETE FLOORS AND CHASES ARE 2-HR FIRE RATED.
- ALL DOMESTIC WATER SUPPLY AND DWV PIPING SHALL BE RUN ABOVE CEILINGS OR WITHIN PARTITIONS UNLESS OTHERWISE NOTED.
- PLUMBING RISERS SHALL BE RUN CONCEALED WITHIN WALLS OR CHASES. COORDINATE WITH ARCHITECTURAL DRAWINGS.
- SANITARY LINES SHALL SLOPE 1/4" PER FOOT UNLESS NOTED OTHERWISE.
- COORDINATE WITH BUILDING OWNER PRIOR TO CUTTING OR GRINDING FLOORS.
- INSTALLATION SHALL PERMIT ACCESSIBILITY FOR SERVICE AND/OR REPLACEMENT OF EQUIPMENT PROVIDED. PROVIDE ACCESS PANELS TO ALLOW ACCESS TO SYSTEMS COMPONENTS THAT REQUIRE INSPECTION AND MAINTENANCE ACCORDING TO MANUFACTURER'S LITERATURE.
- NEW PIPING LOCATIONS ON THE PLANS ARE DIAGRAMMATICAL. TO THE EXTENT POSSIBLE THE CONTRACTOR SHALL INSTALL PIPING SYSTEMS TO MINIMIZE RUN LENGTHS TO FIXTURES.
- CONTRACTOR TO PROVIDE ALL MATERIALS NEEDED FOR CONSTRUCTION UNLESS OTHERWISE NOTED OR DIRECTED.
- DIELECTRIC UNIONS SHALL BE INSTALLED BETWEEN DISSIMILAR METALS IN SOLDERED AND THREADED PIPING SYSTEMS AND INSULATED FLANGES FOR WELDING SYSTEMS.
- OPERATIONS AND MAINTENANCE MANUALS: SUBMIT ALL TESTING DATA AND COPIES OF APPROVED PRODUCT DATA, INCLUDING MAINTENANCE INFORMATION IN A TABBED, NEATLY ORGANIZED THREE RING BINDER. INCLUDE VALVE IDENTIFICATION CHARTS PROVIDE 3 COPIES TO THE OWNER.
- PIPE IDENTIFICATION: LABELING SHALL APPEAR AT INTERVALS OF NOT MORE THAN 20 FEET AND AT LEAST ONCE IN EACH ROOM AND EACH STORY TRAVERSED BY THE PIPING SYSTEM. ALL PIPING SHALL BE CLEARLY IDENTIFIED SPECIFICALLY FOR TYPE OF SERVICE WITH COILED PLASTIC PIPE MARKERS AND FLOW DIRECTION ARROWS. LABELING COLOR AND SIZE SHALL BE PER OSHA SPECIFICATIONS.
- VALVE IDENTIFICATION: PROVIDE A CIRCULAR BRASS TAG AND CHAIN ON EACH VALVE. TAG TO INCLUDE A DISCRETE NUMBER AND SHALL BE COORDINATED WITH ANY CURRENT FACILITY NUMBERING SCHEME OR STANDARD.
- IF CONTRACT INCLUDES RENOVATION WORK WHICH TAKES PLACE IN AN OCCUPIED SPACE. INSTALLATIONS SHALL NOT AFFECT ONGOING OPERATIONS. COORDINATE HOURS AVAILABLE TO PERFORM WORK WITH THE OWNER AND GENERAL CONTRACTOR.
- PRIOR TO CONNECTING TO ANY EXISTING PIPING, CONFIRM TIE-IN LOCATIONS WITH THE FACILITY OWNERS AND OPERATORS.
- INSTALL ALL NEW AND RELOCATED EXISTING COMPONENTS IN ACCORDANCE WITH MANUFACTURER RECOMMENDATIONS, APPLICABLE CODES AND STANDARDS.
- SEAL INTERIOR PIPE PENETRATIONS WITH FIRE SEALANT. SEAL EXTERIOR WALL PIPE PENETRATIONS WATER TIGHT.
- CUT AND PATCH SURFACES, RESTORING ORIGINAL FINISHES.
- ASTM E84 COMPLIANCE: INSULATION AND OTHER MATERIALS SHALL COMPLY WITH THE FLAME AND SMOKE SPREAD RATINGS.
- SUBMITTALS, PRE-CONSTRUCTION: SUBMIT CATALOG CUT SHEETS OF PROPOSED EQUIPMENT FOR ENGINEER REVIEW AND APPROVAL PRIOR TO PURCHASE AND INSTALLATION.
- SUBMITTALS, DURING CONSTRUCTIONS: SUBMIT COPIES OF PIPE ROUGH-IN PRESSURE TESTS AS COMPLETED.
- SUBMITTALS, POST CONSTRUCTION: SUBMIT COPIES OF FINAL PRESSURE TEST, FLUSHING AND PLUMBING DISINFECTION REPORTS. SUBMIT COPIES OF COMPLETED MANUFACTURER START UP REPORTS FOR EQUIPMENT.
- RECORD DRAWINGS: MAINTAIN A CURRENT SET OF MARKED UP CONSTRUCTION DRAWINGS ON SITE AT ALL TIMES. PROVIDE A COMPLETE SET OF THESE RECORD MARK-UPS, OR AS-BUILT. DRAWINGS TO THE ARCHITECT AT THE END OF THE PROJECT.
- USE OF PIPE DOPE IS NOT ALLOWED.
- SEE SPECIFICATIONS FOR OTHER REQUIREMENTS.


REV	DATE	DESCRIPTION	BY	CHK		
DRAWING ISSUE STATUS						
ISSUED FOR BID						
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM						
PROJECT						
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE						
TITLE						
PLUMBING NOTES, SYMBOLS & ABBREVIATIONS						
		DATE	2025.04.22	SCALE	1/2" = 1'-0"	
DRAWN BY		JNB	DESIGNED BY	JNB	CHECKED BY	JMM
PROJECT No.		10377.028				
DRAWING No.		P-001				
REV						




1 BASEMENT DOMESTIC PLUMBING DEMO PLAN
PD101 SCALE: 1/4" = 1'-0"



2 BASEMENT DWV PLUMBING DEMO PLAN
PD101 SCALE: 1/4" = 1'-0"


REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div><div>HALEY WARD</div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div><div>WWW.HALEYWARD.COM</div></div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
PLUMBING DOMESTIC FIRST FLOOR PLAN DEMOLITION PLAN				
DATE 2025.04.22		SCALE 1/4" = 1'-0"		
DRAWN BY JNB	DESIGNED BY JNB	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. PD101				



7 6 5 4 3 2 1


SHEET PW101 GENERAL NOTES

- SEE PLUMBING FIXTURE SCHEDULE FOR ALL FIXTURE CONNECTION SIZES.
- PITCH SANITARY PIPING 1/4" PER FT UNLESS NOTED OTHERWISE.
- TRAP PRIMER PIPING TO BE 1/2".




2 BASEMENT DWV PLUMBING PLAN

P-101 SCALE: 1/4" = 1'-0"




3 FIRST FLOOR PLUMBING PLAN


P-101 SCALE: 1/4" = 1'-0"



1 BASEMENT DOMESTIC PLUMBING PLAN

P-101 SCALE: 1/4" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div><div>HALEY WARD</div><div>www.haleyward.com</div></div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
DOMESTIC AND DWV PLUMBING PLANS				
DATE		SCALE		
2025.04.22		As indicated		
DRAWN BY		DESIGNED BY		CHECKED BY
JNB		JNB		JMM
PROJECT No.		10377.028		
DRAWING No.		P-101		
REV.				



Autodesk Docs/110377/028-1623 - Connor School/10377 - CONNOR SCHOOLS - MEP-14

ABBREVIATIONS

@	AT	I/O	INPUT / OUTPUT
A	AMP	ID	INSIDE DIAMETER
ABS	ACRYLONITRILE BUTADIENE STYRENE PLASTIC	IN	INCHES
ABV	ABOVE	KW	KILOWATT
AD	ACCESS DOOR	L	LENGTH
ADA	AMERICANS WITH DISABILITIES ACT	LAT	LEAVING AIR TEMPERATURE
AF	AIR FILTER	LD	LIQUEFIED PETROLEUM
AFF	ABOVE FINISHED FLOOR	LDB	LEAVING DRY BULB
AFM	AIR FLOW MEASURING STATION	LF	LINEAR FEET
AL	ACOUSTICAL LINER	LG	LONG
AMB	AMBIENT	LOC	LOCATION, LOCATED
AP	ACCESS PANEL	LP	LIQUEFIED PROPANE
APD	AIR PRESSURE DROP	LPC	LOW PRESSURE CONDENSATE
APPROX	APPROXIMATELY	LPS	LOW PRESSURE STEAM
ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS	LRA	LOCKED ROTOR AMPS
ASSY	ASSEMBLY	LS	LINE SET (REFRIG)
ATC	AUTOMATIC TEMPERATURE CONTROL	LVG	LEAVING
ATT	ACOUSTICAL ATTENUATOR	LWB	LEAVING WET BULB
AV	AUTOMATIC VENT	LWT	LEAVING WATER TEMPERATURE
BDD	BACKDRAFT DAMPER	MAX	MAXIMUM
BHP	BRAKE HORSEPOWER	MAX PD	MAXIMUM PRESSURE DROP
BLDG	BUILDING	MBH	1000 BTU PER HOUR
BOT	BOTTOM	MBU	1000 BTU
BOD	BOTTOM OF DUCT	MC	MECHANICAL CONTRACTOR
BTUH	BTU PER HOUR	MCA	MAXIMUM CIRCUIT AMPS
C	CENTERLINE	MCC	MOTOR CONTROL CENTER
CA	COMPRESSED AIR	MECH	MECHANICAL
CAP	CAPACITY	MEZZ	MEZZANINE
CC	COOLING COIL	MFG	MANUFACTURER
CFM	CUBIC FEET PER MINUTE	MIN	MINIMUM, MINUTES
CLG	CEILING	MLS	MAIN LINE SET (REFRIG)
CO	CLEAN OUT, CARBON MONOXIDE	mm	MILLIMETERS
COL	COLUMN	MNTD	MOUNTED
CONC	CONCRETE	MOCP	MAXIMUM OVERCURRENT PROTECTION
CHWR	CHILLED WATER RETURN	MUW	MAKE-UP WATER
CHWS	CHILLED WATER SUPPLY	N/A	NOT APPLICABLE
COND	CONDENSATE	NATL	NATURAL
CONN	CONNECTION	NC	NORMALLY CLOSED, NOISE CRITERIA
CONT	CONTINUATION	NEC	NATIONAL ELECTRIC CODE NFPA 70
CP	CONTROL PANEL, CONDENSATE PUMP	NG	NATURAL GAS
CPT	CONDENSATE PUMP TRAP	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
CV	CONTROL VALVE	NIC	NOT IN CONTRACT
Cv	CONTROL VALVE RATING	NO	NORMALLY OPEN, NUMBER
CVT	CONSTANT VOLUME AIR TERMINAL	N02	NITROGEN DIOXIDE
CW	DOMESTIC COLD WATER	NTS	NOT TO SCALE
CWS	COLD WATER SUPPLY	OA	OUTSIDE AIR
D	DRAIN, DEPTH	OAF	OUTSIDE AIR FILTER, OUTSIDE AIR FAN
dB	DECIBELS	OAI	OUTSIDE AIR INTAKE
DB	DRY BULB	OAT	OUTSIDE AIR TEMPERATURE
DDC	DIRECT DIGITAL CONTROL	OBVD	OPPOSED BLADE VOLUME DAMPER
Ø, DIA	DIAMETER	OD	OUTSIDE DIAMETER
DIFF	DIFFERENTIAL, DIFFUSER	OED	OPEN ENDED DUCT
DISCH	DISCHARGE	OS&Y	OUTSIDE STEM AND YOKE
DN	DOWN	P	PUMP, PITCH
DOM	DOMESTIC	PC	PUMPED CONDENSATE
DP	DIFFERENTIAL PRESSURE	PD	PRESSURE DROP
DWG	DRAWING	PH	PHASE
DWGS	DRAWINGS	PLMB	PLUMBING
EA	EXHAUST AIR	PRESS	PRESSURE
EAT	ENTERING AIR TEMPERATURE	PRV	PRESSURE REDUCING VALVE
EAC	ELECTRICAL CONTRACTOR	PSI	POUNDS PER SQUARE INCH
EDR	EQUIVALENT DIRECT RADIATION	PSIG	POUNDS PER SQUARE INCH GAUGE
EER	ENERGY EFFICIENT RATIO	PT	PRESSURE TREATED
EFF	EFFICIENCY	PVC	POLYVINYL CHLORIDE
ELEC	ELECTRIC, ELECTRICAL	QTY	QUANTITY
ELEV	ELEVATION	R	RADIUS, RETURN
ENT	ENTERING	RA	RETURN AIR
EPDM	ETHYLENE PROPYLENE DIENE MEMBRANE	RAD	RADIATOR
EQUIP	EQUIPMENT	RAF	RETURN AIR FAN
ESP	EXTERNAL STATIC PRESSURE	RAT	RETURN AIR TEMPERATURE
EXP	EXPANSION	REL	RELIEF
F	FAN, DEGREES FAHRENHEIT	REQD	REQUIRED
FA	FRESH AIR	RET	RETURN
FAI	FRESH AIR INTAKE	RH	RELATIVE HUMIDITY
FBG	FURNISHED BY GOVERNMENT	RLA	RATED LOAD AMPS
FC	FLEX CONNECTION	RL	REFRIGERANT LIQUID
FCO	FLOOR CLEANOUT	RM	ROOM
FD	FIRE DAMPER	RPM	REVOLUTIONS PER MINUTE
FF	FINISH FLOOR	RS	REFRIGERANT SUCTION
FIX	FIXTURE	SA	SUPPLY AIR
FLA	FULL LOAD AMPS	SCH	SCHEDULE
FLR	FLOOR	SCR	SCREEN
FOB	FLAT ON BOTTOM	SD	SMOKE DAMPER
FOT	FLAT ON TOP	SF	SQUARE FOOT
FS	FLOAT SWITCH	SIM	SIMILAR
FSD	FIRE SMOKE DAMPER	SIM	SIMILAR
FTR	FIN TUBE RADIATION	SMA	SHEET METAL AND AIR CONDITIONING
FZ	FREEZE/STAT	SOV	SHUT OFF VALVE
G	GAS	SP	STATIC PRESSURE
GAL	GALLONS	SPH	STATIC PRESSURE HIGH LIMIT
GALV	GALVANIZED	SPL	STATIC PRESSURE LOW LIMIT
GC	GENERAL CONTRACTOR	SPS	STATIC PRESSURE SENSOR
GP	GENERAL PURPOSE	SQ	SQUARE
GPH	GALLONS PER HOUR	SS	STAINLESS STEEL
GPM	GALLONS PER MINUTE	STL	STEEL
GRH	GRAVITY RELIEF HOOD	SUP	SUPPLY
GV	GATE VALVE	TC	TEMPERATURE SENSOR, THERMOSTAT
GSM	GALVANIZED SHEET METAL	T	TEMPERATURE
GYP	GYPSUM WALLBOARD	THK	THICK, THICKNESS
H	HEIGHT	TG	TRANSFER GRILLE
HOA	HANDS-OFF-AUTOMATIC	TRANS	TRANSITION
HOR	HORIZONTAL	TSP	TOTAL STATIC PRESSURE
HP	HORSEPOWER, HIGH PRESSURE	TSTAT	THERMOSTAT
HPC	HIGH PRESSURE CONDENSATE	TYP	TYPICAL
HPS	HIGH PRESSURE STEAM	UNO	UNLESS NOTED OTHERWISE
HR	HOUR	V	VENT, VOLT
HT	HEIGHT	VD	VOLUME DAMPER
HUMID	HUMIDIFIER, HUMIDITY	VEL	VELOCITY
HVAC	HEATING, VENTILATING AND AIR CONDITIONING	VFD	VARIABLE FREQUENCY DRIVE
HW	DOMESTIC HOT WATER	VIF	VERIFY IN FIELD
HWR	HOT WATER RETURN	VRF	VARIABLE REFRIGERANT FLOW
HWS	HOT WATER SUPPLY	VTR	VENT THROUGH ROOF
HZ	HERTZ	W	WIDTH, WATT
		W/	WITH
		WB	WET BULB
		WC	WATER COLUMN
		WCO	WALL CLEANOUT
		WG	WATER GAUGE
		WMS	WIRE MESH SCREEN
		WPD	WATER PRESSURE DROP

AIR DISTRIBUTION SYMBOLS

	RECTANGULAR DUCT, (FIRST NUMBER IS SIDE SHOWN) DIMENSION IN INCHES.
	ROUND DUCT
	MOTORIZED DAMPER
	FLEXIBLE DUCT
	FLEXIBLE DUCT CONNECTOR (FC)
	DUCT DROPS AND RISES IN DIRECTION OF AIR FLOW
	RETURN DUCT TURNED UP OR DOWN (DASHED)
	SUPPLY DUCT TURNED UP OR DOWN (DASHED)
	EXHAUST DUCT TURNED UP OR DOWN (DASHED)
	ACOUSTICAL LINING (DUCT DIM. FOR NET FREE AREA)
	ROUND DUCT ELBOW DOWN
	ROUND DUCT ELBOW UP
	SQUARE TO ROUND TRANSITION
	POINT OF CHANGE IN DUCT CONSTRUCTION BY STATIC PRESSURE CLASS, THE NUMBER ASSIGNS PRESSURE CLASS (IN. OF WATER) WHICH WILL ACCOMMODATE MAXIMUM OPERATING PRESSURE THE ASSIGNMENT UNTIL THE DUCT TERMINATES OR ANOTHER SYMBOL APPEARS. A "N" SUPERScript INDICATES NEGATIVE PRESSURE.
	CAP (DUCT AND/OR PIPE)
	INDICATES DUCT, PIPING, EQUIPMENT TO BE REMOVED.
	EXHAUST AIR
	RETURN AIR
	SUPPLY AIR
	OUTSIDE AIR
	VOLUME DAMPER
	FIRE DAMPER
	SMOKE DAMPER
	COMBINATION FIRE/SMOKE DAMPER
	VANED ELBOW (PROVIDE FOR ALL SQUARE OR RECTANGULAR ELBOWS EVEN IF SYMBOL MISSING.)
	VANED ELBOW (SHORT RADIUS) NOTE: ADJUSTABLE ELBOWS ARE NOT ALLOWED.
	DIRECTION OF AIR FLOW (IN)
	DIRECTION OF AIR FLOW (OUT)
	HUMIDISTAT OR HUMIDITY SENSOR
	THERMOSTAT (TSTAT) OR TEMP. SENSOR
	BACS SENSOR (COMBINATION TEMP, CO2 & OCC)
	SMOKE DETECTOR
	CEILING RETURN GRILLE
	CEILING SUPPLY DIFFUSER
	CEILING EXHAUST DIFFUSER
	DYNAMIC PRESSURE SENSOR
	DIFFERENTIAL PRESSURE MONITOR
	OCCUPANCY SENSOR

MISCELLANEOUS SYMBOLS

	DIFFUSER, REGISTER OR GRILLE TAG
	CFM AIR FLOW
	FINNED TUBE TAG
	LENGTH OF FINNED ELEMENT
	DETAIL NUMBER
	SHEET NUMBER WHERE DETAIL IS LOCATED
	CONNECT NEW TO EXISTING
	LIMITS OF DEMOLITION
	REVISION NUMBER

MECHANICAL EQUIPMENT ABBREVIATIONS

(REFER TO MECHANICAL SCHEDULE SHEET FOR INFORMATION)

AHU	AIR HANDLING UNIT
EF	EXHAUST FAN
ERV	ENERGY RECOVER VENTILATOR
EBH	ELECTRIC BASEBOARD HEATER
HP	HEAT PUMP
DHC	DUCT HEATING COIL
DBE	DRYER BOOSTER FAN
IU	HEAT PUMP INDOOR UNIT
OU	HEAT PUMP OUTDOOR UNIT
UH	UNIT HEATER
ET	EXPANSION TANK
VAV	VARIABLE AIR VOLUME

EXISTING EQUIPMENT LEGEND

(E)	EXISTING TO REMAIN
(R)	EXISTING TO BE DISCONNECTED AND REMOVED
(RL)	EXISTING TO BE DISCONNECTED AND RELOCATED
(ER)	EXISTING IN NEW LOCATION
(RP)	EXISTING TO BE REPLACED

PIPING SYMBOLS

	PIPE ELBOW TURNED DOWN
	PIPE ELBOW TURNED UP
	P-TRAP (W&T)
	PIPE TEE DOWN
	PIPE TEE UP
	PIPE BREAK
	DIRECTION OF FLOW
	PIPE PITCHES DOWN
	UNION
	PIPE ANCHOR
	PIPE GUIDE OR SLEEVES
	GENERIC VALVE, SEE SPECIFICATIONS FOR TYPE
	GATE VALVE
	BALL VALVE
	BUTTERFLY VALVE (MANUAL)
	2-WAY CONTROL VALVE
	3-WAY CONTROL VALVE
	CALIBRATED BALANCING VALVE (CIRCUIT SETTER)
	AUTOMATIC FLOW CONTROL VALVE
	CHECK VALVE
	BACK FLOW PREVENTER
	GLOBE VALVE
	NEEDLE VALVE
	PLUG VALVE
	SOLENOID VALVE
	OS&Y VALVE
	PRESSURE REDUCING OR REGULATING VALVE
	MANUAL AIR VENT
	AUTOMATIC AIR VENT
	VACUUM BREAKER
	CONCENTRIC REDUCER/INCREASER
	ECCENTRIC REDUCER/INCREASER
	FLEXIBLE PIPE CONNECTOR
	EXPANSION JOINT
	PUMP
	TEMPERATURE & PRESSURE TAP (PETE'S PLUG)
	PRESSURE GAUGE AND COCK
	THERMOMETER AND WELL
	PRESSURE RELIEF VALVE
	HOSE END DRAIN VALVE WITH CAP
	HOSE BIBB
	PIPE CAP
	WATER METER
	STRAINER
	STRAINER WITH BLOWDOWN

PIPING SYSTEMS



	EXISTING PIPING TO REMAIN
	EXISTING PIPING TO BE REMOVED
	HOT WATER RETURN
	HOT WATER SUPPLY
	REFRIGERANT LIQUID / REFRIGERANT SUCTION
	REFRIGERANT LIQUID
	REFRIGERANT SUCTION
	REFRIGERANT HOT GAS
	CHILLED WATER RETURN
	CHILLED WATER SUPPLY
	CONDENSATE DRAIN
	COMPRESSED AIR
	ACID DRAIN
	ACID DRAIN (BELOW SLAB)
	ACID VENT
	CONDENSER WATER SUPPLY
	CONDENSER WATER RETURN
	FUEL OIL RETURN
	FUEL OIL SUPPLY
	FUEL OIL VENT
	GLYCOL
	GLYCOL SUPPLY
	GLYCOL RETURN
	HIGH PRESSURE CONDENSATE RETURN
	HIGH PRESSURE LIQUID PROPANE
	HIGH PRESSURE NATURAL GAS
	HIGH PRESSURE STEAM
	LOW PRESSURE STEAM
	LOW PRESSURE RETURN
	MEDIUM PRESSURE STEAM
	MEDIUM PRESSURE RETURN
	NON POTABLE COLD WATER
	PROCESS COOLING WATER SUPPLY
	PROCESS COOLING WATER RETURN
	PUMP STEAM CONDENSATE
	PUMP DISCHARGE
	POTABLE WATER
	RELIEF LINE

GENERAL MECHANICAL NOTES

- IT IS THE INTENT OF THESE DRAWINGS TO SHOW COMPLETE AND FUNCTIONAL SYSTEMS THAT ARE IN COMPLIANCE WITH ALL INDUSTRY STANDARDS AND APPLICABLE CODES. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ENGINEER'S ATTENTION.
- ALL MECHANICAL SYSTEMS WORK SHALL BE IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL AUTHORITIES HAVING JURISDICTION AND ALL APPLICABLE CODES. ALL WORK SHALL CONFORM TO EQUIPMENT MANUFACTURER'S INSTRUCTIONS AND INDUSTRY STANDARDS.
- ALL WORKMANSHIP SHALL BE OF THE HIGHEST STANDARDS. INSTALL ALL WORK IN A NEAT, SYSTEMATIC AND ORDERLY ARRANGEMENT. ALL MATERIAL SHALL BE NEW AND OF THE BEST QUALITY AVAILABLE, FREE FROM DEFECTS. THE CONTRACTOR SHALL GUARANTEE THE MATERIALS AND INSTALLATION FOR ONE YEAR FROM THE PROJECT ACCEPTANCE DATE AGAINST ANY DEFECTS DUE TO FAULTY MATERIALS, EQUIPMENT, WORKMANSHIP, OR INSTALLATION. UPON NOTICE OF THE DEFECT, THE CONTRACTOR SHALL REPLACE OR REPAIR THE DEFECTIVE ITEM AT NO ADDITIONAL COST.
- THE CONTRACTOR SHALL VISIT THE JOB SITE TO VERIFY ALL EXISTING FIELD CONDITIONS, DIMENSIONS AND OBSTRUCTIONS.
- ALL PIPING AND DUCTWORK IS SHOWN DIAGRAMMATICALLY. PIPING AND SYSTEMS SHALL FOLLOW ARRANGEMENT AS MUCH AS POSSIBLE, HOWEVER, ACTUAL FIELD CONDITIONS SHALL DICTATE. CAREFULLY COORDINATE THE SPACE REQUIREMENTS AND LOCATIONS OF ALL DUCTWORK WITH ALL OTHER TRADES. GIVE PRIORITY TO GRAVITY DRAINAGE PIPING.
- DO NOT SCALE DRAWINGS. SEE ARCHITECTURAL DRAWINGS AND REFLECTED CEILING PLAN FOR EXACT LOCATION OF WALLS, DOORS, WINDOWS, CEILING DIFFUSERS, ETC.
- THE CONTRACTOR SHALL COORDINATE ALL WORK WITH THE WORK OF ALL OTHER TRADES. SHOULD ANY DISCREPANCIES BE DISCOVERED IN ANY OF THE BID DOCUMENTS, (INCLUDING ALL OTHER DIVISIONS) THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER BEFORE PROCEEDING ANY FURTHER WITH THE WORK, OTHERWISE THE CONTRACTOR SHALL BE HELD RESPONSIBLE FOR ALL COST INVOLVED WITH THE CORRECTION OF THE CONSTRUCTION INSTALLATION.
- ALL EQUIPMENT, DUCTWORK, PIPING, ETC. SHALL BE SUPPORTED FROM THE BUILDING'S STRUCTURAL FRAME AND MEMBERS. ALL DUCT SIZES ARE NET DIMENSIONS AND DO NOT INCLUDE AND INSULATION, SUPPORT OR REINFORCEMENT DIMENSIONS. ALL WORK SHALL BE NEW UNLESS OTHERWISE NOTED AS EXISTING.
- THE CONTRACTOR SHALL PERFORM TESTS ON ALL MECHANICAL SYSTEMS AS REQUIRED BY FEDERAL, STATE, AND LOCAL CODES AND REGULATIONS. ALL TESTS SHALL BE WITNESSED AND ACCEPTED BY THE AUTHORITY HAVING JURISDICTION. THE CONTRACTOR SHALL PROVIDE ALL SERVICES AND MATERIALS REQUIRED BY THE TEST AND CERTIFY IN WRITING THAT ALL WORK HAS PASSED ALL REQUIRED TESTS.
- THE MECHANICAL SYSTEMS SHALL BE BALANCED, COMPLETE WITH A WRITTEN REPORT BY AN INDEPENDENT AIR BALANCE FIRM WITH A MINIMUM OF 3 YEARS EXPERIENCE.
- WHERE PIPES AND DUCTS PENETRATE WALLS OR FLOOR, THE SPACE BETWEEN THE STRUCTURE AND THE DUCT OR PIPE SHALL BE SEALED AIRTIGHT WITH AN APPROVED MATERIAL. PROVIDE FIRE STOPS AND/OR SEALANT AROUND ALL PENETRATIONS THAT HAVE A FIRE RATING GREATER THAN OR EQUAL TO THE FIRE RATING OF THE WALL, FLOOR OR ENCLOSURE.
- PROVIDE ACCESS PANELS FOR ALL VALVES, DAMPERS, CLEANOUTS, ETC. THAT REQUIRE ACCESS.


SHEET LIST - MECHANICAL

M-001	MECHANICAL NOTES, SYMBOLS & ABBREVIATIONS
MD101	MECHANICAL HVAC FIRST FLOOR DEMOLITION PLAN
MD102	MECHANICAL PIPING FIRST FLOOR DEMOLITION PLAN
MH101	MECHANICAL HVAC FIRST FLOOR PLAN
MP101	MECHANICAL PIPING FIRST FLOOR PLAN
M-301	MECHANICAL SECTION
M-501	MECHANICAL DETAILS
M-502	MECHANICAL DETAILS
M-503	MECHANICAL DETAILS
M-504	MECHANICAL DETAILS
M-601	MECHANICAL SCHEDULES
M-602	MECHANICAL SCHEDULES
M-701	MECHANICAL SEQUENCES OF OPERATION


REV.	DATE	DESCRIPTION	BY	CHK.	
DRAWING ISSUE STATUS					
ISSUED FOR BID					
<div><div><div>HALEY WARD</div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div><div>WWW.HALEYWARD.COM</div></div>					
PROJECT					
CONNOR SCHOOL RENOVATIONS					
CONNOR, MAINE					
TITLE					
MECHANICAL NOTES, SYMBOLS & ABBREVIATIONS					
<div></div>		DATE 2025.04.22	SCALE 1/2" = 1'-0"		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM			
PROJECT No.		10377.028			
DRAWING NO.		M-001			
		REV.			

SHEET MD101 GENERAL NOTES


1. DUCTWORK TO REMAIN SHALL BE CEANED AND TESTED FOR LEAKS; REPAIRED IF NECESSARY.




1 MECHANICAL DUCTWORK FIRST FLOOR DEMOLITION PLAN - CLASSROOMS
MD101/ SCALE: 1/4" = 1'-0"




2 MECHANICAL DUCTWORK FIRST FLOOR DEMOLITION PLAN - LIBRARY
MD101/ SCALE: 1/4" = 1'-0"




3 MECHANICAL DUCTWORK FIRST FLOOR DEMOLITION PLAN - GYM/STAGE/STORAGE
MD101/ SCALE: 1/4" = 1'-0"



4 DEMOLITION KEY PLAN
MD101/ SCALE: 1/16" = 1'-0"


REV.	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 www.haleyward.com				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL HVAC FIRST FLOOR DEMOLITION PLAN				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. MD101				


D
C
B
A



1 MECHANICAL PIPING FIRST FLOOR DEMOLITION PLAN
MD102 / SCALE: 1/8" = 1'-0"

- SHEET MD102 NUMBERED NOTES** #
- 1 ZONE VALVE TO BE DEMOLISHED AND REPLACED WITH NEW.
 - 2 THERMOSTAT TO BE DEMOLISHED AND REPLACED WITH THERMOSTAT FROM TRANE/MITSUBISHI.


REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL PIPING FIRST FLOOR DEMOLITION PLAN				
DATE 2025.04.22		SCALE 1/8" = 1'-0"		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028				
DRAWING NO. MD102		REV.		




7 6 5 4 3 2 1


SHEET MH101 GENERAL NOTES

1. EXISTING DUCTWORK TO BE USED TO THE MAXIMUM EXTENT POSSIBLE.




1 MECHANICAL DUCTWORK FIRST FLOOR PLAN
MH101 SCALE: 1/8" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL HVAC FIRST FLOOR PLAN				
DATE		2025.04.22		SCALE
DRAWN BY		ITB		As indicated
DESIGNED BY		JMM		CHECKED BY
PROJECT No.		10377.028		JMM
DRAWING NO.		MH101		REV.





MECHANICAL PIPING GENERAL NOTES:


1. THE CONTRACTOR SHALL CONNECT HYDRONIC ZONE VALVES TO THE ZONE'S NEW INDOOR UNIT CN-24 RELAY UNIT CONNECTIONS TO OPERATE AS AUXILIARY HEAT.




1 MECHANICAL PIPING FIRST FLOOR PLAN
MP101 SCALE: 1/8" = 1'-0"


REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE MECHANICAL PIPING FIRST FLOOR PLAN				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. MP101				









1 CLASSROOM EXISTING DUCTWORK CONNECTION
SCALE: 1" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL SECTION				
DATE 2025.04.22		SCALE 1" = 1'-0"		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028				
DRAWING NO. M-301		REV.		







REV.	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 www.haleyward.com				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE MECHANICAL DETAILS				
 JARED MERRY No. 11679 LICENSED PROFESSIONAL ENGINEER		DATE 2025.04.22	SCALE 1/4" = 1'-0"	
DRAWN BY ITB		DESIGNED BY JMM	CHECKED BY JMM	
PROJECT No. 10377.028				
DRAWING No.		REV.		
M-501				





REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div><div></div><div></div><div></div></div><div>HALEY WARD</div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div> <div>WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL DETAILS				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. M-502				





1 MECHANICAL PIPING DIAGRAM - OU-1
M-503 NTS

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL DETAILS				
DATE 2025.04.22		SCALE 1/2" = 1'-0"		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. M-503				






REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE MECHANICAL DETAILS				
<div></div>		DATE 2025.04.22	SCALE 1/2" = 1'-0"	
DRAWN BY ITB		DESIGNED BY JMM	CHECKED BY JMM	
PROJECT No.		10377.028		
DRAWING No.		M-504		

Autodesk Docs/10377.028 - R23 - Connor School/10377 - CONNOR SCHOOL - MEP.rvt

VRF/SPLIT SYSTEM INDOOR UNIT SCHEDULE																									
TAG	ROOM SERVING	OUTDOOR UNIT	MODEL	TYPE	NOMINAL COOLING CAPACITY(BTU/h)	NOMINAL HEATING CAPACITY (BTU/h)	COOLING DESIGN ENTERING AIR TEMP DB/WB (°F)	HEATING DESIGN ENTERING AIR TEMP DB/WB (°F)	CORRECTED CAPACITY				COOLING COIL LAT (°F)	HEATING COIL LAT (°F)	REFR. PIPE SIZE LIQUID/SUCTION (IN.)	FAN SPEED SETTING	PEAK FAN AIRFLOW (CFM)	SOUND PRESSURE PER FAN SPEED (dBA)	VOLTAGE/PHASE	POWER COOLING 208V (kW)	POWER HEATING 208V (kW)	MCA/MFS	CONDENSATE REMOVAL (GAL/HR)	NOTES	
									COOLING DIVERSITY (FULL/PARTIAL) SEE NOTES 5&6	COOLING TOTAL CAPACITY (BTU/h)	COOLING SENSIBLE CAPACITY (BTU/h)	HEATING DIVERSITY (FULL/PARTIAL) SEE NOTES 5&6													HEATING CAPACITY (BTU/h)
IU-1	120 Principal	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-2	119 Breakroom	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-3	102 Hall	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8, 10
IU-4	128 Front Office	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-5	129 Admin	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-6	108 Library	OU-1	TPKFYP015HM142A	WALL-MOUNTED	15,000	17,000	80.0/67.0	70	FULL DEMAND	14,659.6	10,405.9	FULL DEMAND	16,569.3	55.3	108.6	1/4 / 1/2	HIGH	413	34-39-43	208/230V/1	0.03	0.03	0.38(208V)/0.38(230V)/15	0.56	1-8
IU-7	108 Library	OU-1	TPKFYP015HM142A	WALL-MOUNTED	15,000	17,000	80.0/67.0	70	FULL DEMAND	14,659.6	10,405.9	FULL DEMAND	16,569.3	55.3	108.6	1/4 / 1/2	HIGH	413	34-39-43	208/230V/1	0.03	0.03	0.38(208V)/0.38(230V)/15	0.56	1-8
IU-8	104 Spec Ed	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8, 10
IU-9	105 Reading	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-10	102 Hall	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8, 10
IU-11	107 Girls	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8, 10
IU-12	110 Boys	OU-1	TPKFYP006LM140A	WALL-MOUNTED	6,000	6,700	80.0/67.0	70	FULL DEMAND	5,863.9	4,198.3	FULL DEMAND	6,530.2	58.5	102.9	1/4 / 1/2	HIGH	191	22-26-29-31	208/230V/1	0.02	0.01	0.24/0.24/15	0.26	1-8
IU-13	109 Classroom	OU-1	TPKFYP018LM140A	WALL-MOUNTED	18,000	20,000	80.0/67.0	70	FULL DEMAND	17,591.6	11,940.4	FULL DEMAND	19,493.3	53.3	112.8	1/4 / 1/2	HIGH	438	31-36-41-46	208/230V/1	0.05	0.04	0.24/0.24/15	0.78	1-8
IU-14	121 Classroom	OU-2	TPKFYP015LM140A	WALL-MOUNTED	15,000	17,000	80.0/67.0	70	FULL DEMAND	14,656.9	9,744.1	FULL DEMAND	16,568.3	53.0	115.1	1/4 / 1/2	HIGH	353	29-34-37-40	208/230V/1	0.04	0.03	0.24/0.24/15	0.61	1-8
IU-15	122 Classroom	OU-2	TPKFYP024KM142A	WALL-MOUNTED	24,000	27,000	80.0/67.0	70	FULL DEMAND	23,451.1	19,400.1	FULL DEMAND	26,314.4	59.3	97.5	3/8 / 5/8	HIGH	918	39-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.53	1-8
IU-16	118 Classroom	OU-2	TPKFYP015LM140A	WALL-MOUNTED	15,000	17,000	80.0/67.0	70	FULL DEMAND	14,656.9	9,744.1	FULL DEMAND	16,568.3	53.0	115.1	1/4 / 1/2	HIGH	353	29-34-37-40	208/230V/1	0.04	0.03	0.24/0.24/15	0.61	1-8
IU-17	123 Classroom	OU-2	TPKFYP024KM142A	WALL-MOUNTED	24,000	27,000	80.0/67.0	70	FULL DEMAND	23,451.1	19,400.1	FULL DEMAND	26,314.4	59.3	97.5	3/8 / 5/8	HIGH	918	39-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.53	1-8
IU-18	116 PE Office	OU-3	TPKFYP012HM142A	WALL-MOUNTED	12,000	13,500	80.0/67.0	70	FULL DEMAND	11,727.7	8,721.0	FULL DEMAND	10,977.3	59.3	95.5	1/4 / 1/2	HIGH	413	34-39-43	208/230V/1	0.03	0.03	0.38(208V)/0.38(230V)/15	0.4	1-8
IU-19	111 MPR	OU-3	TPKFYP030KM142A	WALL-MOUNTED	30,000	34,000	80.0/67.0	70	FULL DEMAND	29,319.3	21,810.1	FULL DEMAND	27,646.6	56.7	98.9	3/8 / 5/8	HIGH	918	43-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.97	1-9
IU-20	111 MPR	OU-3	TPKFYP030KM142A	WALL-MOUNTED	30,000	34,000	80.0/67.0	70	FULL DEMAND	29,319.3	21,810.1	FULL DEMAND	27,646.6	56.7	98.9	3/8 / 5/8	HIGH	918	43-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.97	1-9
IU-21	111 MPR	OU-3	TPKFYP030KM142A	WALL-MOUNTED	30,000	34,000	80.0/67.0	70	FULL DEMAND	29,319.3	21,810.1	FULL DEMAND	27,646.6	56.7	98.9	3/8 / 5/8	HIGH	918	43-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.97	1-9
IU-22	111 MPR	OU-3	TPKFYP030KM142A	WALL-MOUNTED	30,000	34,000	80.0/67.0	70	FULL DEMAND	29,319.3	21,810.1	FULL DEMAND	27,646.6	56.7	98.9	3/8 / 5/8	HIGH	918	43-49	208/230V/1	0.07	0.07	0.63(208V)/0.63(230V)/15	0.97	1-9
IU-23	112 MP Storage	OU-3	TPKFYP012LM140A	WALL-MOUNTED	12,000	13,500	80.0/67.0	70	FULL DEMAND	11,727.7	7,976.1	FULL DEMAND	10,977.3	53.7	105.5	1/4 / 1/2	HIGH	297	24-31-37-41	208/230V/1	0.04	0.03	0.24/0.24/15	0.59	1-8
NOTES: 1 NOMINAL COOLING CAPACITIES ARE BASED ON INDOOR COIL EAT OF 80/67°F (DB/WB), OUTDOOR OF 95°F (DB) 2 NOMINAL HEATING CAPACITIES ARE BASED ON INDOOR COIL EAT OF 70°F (DB), OUTDOOR OF 43°F (WB) 3 SEE OUTDOOR UNIT SCHEDULE FOR OUTDOOR AMBIENT CONDITIONS, CONNECTED CAPACITY, AND OTHER FACTORS ASSOCIATED WITH CORRECTED CAPACITIES 4 NOT USED 5 FULL DEMAND CORRECTED CAPACITY INCLUDES DE-RATE ASSOCIATED WITH INDOOR VS. OUTDOOR CONNECTED CAPACITY INDICATED ON OUTDOOR UNIT SCHEDULE FOR ASSOCIATED SYSTEM. PARTIAL CORRECTED CAPACITY ASSUMES SUFFICIENT DIVERSITY EXISTS SUCH THAT THE CONNECTED CAPACITY DE-RATE DOES NOT APPLY.IT IS THE DESIGNER'S RESPONSIBILITY TO ENSURE "DIAMOND SYSTEM BUILDER" IS SET IN THE APPROPRIATE OUTPUT CAPACITY SETTING (FULL DEMAND/PARTIAL DEMAND) PRIOR TO GENERATING THIS SCHEDULE. 6 IT IS RECOMMENDED TO ALWAYS BASE HEATING CORRECTED CAPACITY ON FULL DEMAND. 7 PROVIDE WITH CN 24 RELAY KIT. 8 PROVIDE WITH MANUFACTURER'S TAR-U01MEDU-K WIRELESS CONTROLLER. 9 PROVIDE WITH SAFTEY TECHNOLOGY WIRE GUARD PROTECTIVE CAGE OR EQUIVALENT. 10 PROVIDE WITH CONDENSATE LIFT PUMP.																									

VRF/SPLIT SYSTEM OUTDOOR UNIT SCHEDULE																							
TAG	SERVES	MANUFACTURER	MODEL	MODULES	NOM. COOLIGN CAPACITY (BTU/h)	NOM. HEATING CAPACITY (BTU/h)	COOLIGN EFF. IEER/EER	HEATING COP @ 47°F	CONNECTED CAPACITY (% OF NOM)	DESIGN COOLING OUDOOR DB (°F)	DESIGN HEATING OUTDOOR WB (°F)	MAX PIPE LENGTH FROM BC OR FIRST PIPE JOINT (FT)	REF. PIPING SIZES LIQUID/SUCTION	CORRECTED COOLING CAPACITY (BTU/h)	CORRECTED HEATING CAPACITY (BTU/h)	SOUND PRESSURE (dBA)	COMPRESSOR TYPE / QUANTITY	PRELIM. FIELD ADDED CHARGE (SEE NOTE 5)	ELECTRICAL - PER MODULE				NOTES
																			VOLTAGE / PHASE	MCA	RFS	MOCP	
OU-1	OFFICES / LIB	TRANE/MITSUBISHI	TURYH1443BN40AN	HP72, HP72	144,000	160,000	21.6 / 11.15	3.635	75.0 %	82.0	-10.4	86.4	7/8 / 1-1/8	148,203.9	131,536.1	59.5/61	SCROLL/2	27.7	208/230V / 3Ø	55/49, 55/49	60/50, 60/50	90/80, 90/80	1-12
OU-2	CLASSROOMS	TRANE/MITSUBISHI	TUHYH0963AN40AN	HP96	96,000	108,000	22.15 / 12.4	4.175	81.3 %	82.0	-10.4	61.1	3/8 / 7/8	100,017.4	90,258.4	56/58.5	SCROLL/1	9.6	208/230V / 3Ø	63/57	70/60	100/90	1-12
OU-3	GYNASSIUM	TRANE/MITSUBISHI	TUHYH1443BN41AN	HP72, HP72	144,000	160,000	21.25 / 11.2	3.895	100.0 %	82.0	-10.4	93.9	1/2 / 1-1/8	142,082.3	132,541.0	77.5/79.5	SCROLL/2	13.7	208/230V / 3Ø	55/49, 55/49	55/49, 55/49	90/80, 90/80	1-12
NOTES: 1 NOMINAL COOLING CAPACITIES ARE BASED ON INDOOR COIL EAT OF 80/67°F (DB/WB), OUTDOOR OF 95°F (DB). 2 NOMINAL HEATING CAPACITIES ARE BASED ON INDOOR COIL EAT OF 70°F (DB), OUTDOOR OF 43°F (WB). 3 EFFICIENCY VALUES FOR EER, IEER, COP ARE BASED ON AHRI 1230 TEST METHOD FOR MIXTURE OF DUCTED & NON-DUCTED INDOOR UNITS. 4 FOR SYSTEMS WITH MULTIPLE MODULES, REFRIGERANT PIPE DIMENSIONS INDICATE TOTAL SYSTEM COMBINED PIPING DOWNSTREAM OF MODULE TWINNING. 5 ADDED FIELD CHARGE LISTED IS IN ADDITION TO FACTORY CHARGE, THIS MUST BE UPDATED BASED UPON FINAL AS-BUILT PIPING LAYOUT. 6 FACTORY REPRESENTATIVES SHALL REVIEW THE PROJECT PRIOR TO AND THROUGHOUT THE INSTALLATION OF CITY MULTI EQUIPMENT. 7 FACTORY REPRESENTATIVES SHALL STARTUP AND COMMISSION CITY MULTI EQUIPMENT UPON COMPLETION OF EQUIPMENT INSTALLATIONS. 8 FACTORY REPRESENTATIVES SHALL PROVIDE ON-SITE ASSISTANCE FOR THE BMS INTEGRATION OF THE CITY MULTI EQUIPMENT. 9 FACTORY REPRESENTATIVES SHALL PROVIDE END-USER TRAINING ON THE CITY MULTI EQUIPMENT UPON COMPLETION OF THE INSTALLATION OF EQUIPMENT. 10 PROVIDE 24" SUPER STAND KIT. 11 PROVIDE WITH SNOW AND HAILE GUARD. 12 PROVIDE WITH APPROPRIATELY SIZED CONCRETE PAD FOR OU. REINFORCED WITH #4 REBAR, 12" OC, EACH WAY. 6" DEPTH, MINIMUM.																							

REV.	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div><div><div>HALEY WARD</div><div>www.haleyward.com</div></div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
MECHANICAL SCHEDULES				
DATE 2025.04.22		SCALE 1/2" = 1'-0"		
DRAWN BY ITB	DESIGNED BY JMM	CHECKED BY JMM		
PROJECT No. 10377.028				
DRAWING NO. M-601				REV.

ERV SCHEDULE

ERV SCHEDULE																								
TAG	LOCATION	AREA SERVED	TOTAL AIRFLOW (CFM)	RETURN AIRFLOW (CFM)	FAN SECTIONS								ELECTRICAL DATA						ENERGY RECOVERY WHEEL (Y/N)	OPERATING WEIGHT (LBS)	PRE FILTERS (MERV)	FINAL FILTERS (MERV)	TYPICAL UNIT MFG & MODEL NO.	NOTES:
					SUPPLY FAN				EXHAUST FAN				ELECTRICAL CONNECTION # 1 - MAIN UNIT											
					SUPPLY AIRFLOW (CFM)	FAN QTY	TSP/ESP (IN WC)	HP (EACH)	EXHAUST AIRFLOW (CFM)	FAN QTY	TSP/ESP (IN WC)	HP (EACH)	VOLTS/Ø	FLA	MCA	MOCP	DISCONNECT BY DIV 26 (Y/N)	STANDBY POWER (Y/N)						
ERV-1	112 MP STORAGE	GYMNASIUM	625	625	632	1	.5	0.50	625	1	.4	0.50	208/1	3.1	3.5	15	Y	Y	N	196	8	8	RENEWAIRE HE07-JINH-S15AA--1GNT--L	ALL
ERV-2	109 CLASSROOM	CLASSROOM	230	230	230	1	.5	0.11	230	1	.4	0.11	120/1	2.5	15	15	Y	Y	N	52	8	8	RENEWAIRE EV PREMIUM LH	ALL
ERV-3	121 CLASSROOM	CLASSROOM	230	230	230	1	.5	0.11	230	1	.4	0.11	120/1	2.5	15	15	Y	Y	N	52	8	8	RENEWAIRE EV PREMIUM LH	ALL
ERV-4	122 CLASSROOM	CLASSROOM	230	230	230	1	.5	0.11	230	1	.4	0.11	120/1	2.5	15	15	Y	Y	N	52	8	8	RENEWAIRE EV PREMIUM LH	ALL
ERV-5	118 CLASSROOM	CLASSROOM	230	230	230	1	.5	0.11	230	1	.4	0.11	120/1	2.5	15	15	Y	Y	N	52	8	8	RENEWAIRE EV PREMIUM LH	ALL
ERV-6	123 CLASSROOM	CLASSROOM	230	230	230	1	.5	0.11	230	1	.4	0.11	120/1	2.5	15	15	Y	Y	N	52	8	8	RENEWAIRE EV PREMIUM LH	ALL
ERV-7	108 LIBRARY	LIBRARY/OFFICES	380	380	380	1	.5	0.5	380	1	.4	0.5	208/1	2.32	2.6	15	Y	Y	N	148	8	8	RENEWAIRE HE07-JINH-S15EE--GNT--L	ALL
NOTES: 1. REFER TO NOTES, DETAILS, SEQUENCE OF OPERATIONS, AND SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS. 2. PROVIDE SINGLE POINT POWER CONNECTION FOR ALL COMPONENTS AND ADDITIONAL SINGLE POINT POWER CONNECTION FOR LIGHTING CIRCUIT. 3. PROVIDE DOUBLE-WALL INSULATED (R-13 MIN.) CONSTRUCTION AND HINGED ACCESS DOORS. 4. PROVIDE WITH MANUFACTURER'S STANDARD CONTROLLER AND DUCT MOUNTED CO2 SENSOR.																								

VRF HEAT RECOVERY BRANCH CIRCUIT CONTROLLER

TAG	SERVES	MANUFACTURER	MODEL NUMBER	TYPE (DOUBLE / MAIN / SUB)	# OF PORTS	CONNECTED CAPACITY	VOTAGE/PHASE	POWER COOLING 208V (kW)	POWER HEATING 208V (kW)	MCA 208	NOTES
BC-1	OFFICE / LIBRARY	TRANE/MITSUBISHI	TCMBM1012JA11N4	MAIN	12	108,000.0	208/230V/1Ø	0.198	0.106	1.19	ALL
NOTES: 1. INCLUDE DIAMONDBACK BALL VALVES BV-SERIES, 700PSIG WORKING PRESSURE, FULL PORT, 410A RATED. 2. FOR SUB BC CONTROLLER CMB-P-NU-GB1 OR -.GB, THE TOTAL CONNECTABLE INDOOR UNIT CAPACITY CAN BE 126,000 BTUS OR LESS. IF TWO SUB BC CONTROLLERS ARE USED, THE TOTAL INDOOR UNIT CAPACITY CONNECTED TO BOTH SUB BC CONTROLLERS ALSO CANNOT EXCEED 126,000 BTUS. FOR SUB BC CONTROLLER CMB-P1016NU-HB1 THE TOTAL CONNECTABLE INDOOR UNIT CAPACITY CAN BE 126,000 BTUS OR LESS. HOWEVER, IF TWO SUB CONTROLLERS ARE USED, AND ONE OF THEM IS CMB-1016NU-HB1, THE TOTAL INDOOR UNIT CAPACITY CONNECTED TO BOTH SUB CONTROLLERS MUST NOT EXCEED 168,000 BTUS. 3. PROVIDE WITH ACCESSORY BALL VALVES TO ALL PORTS ON BRANCH CONTROLLER.											

ELECTRIC DUCT COIL SCHEDULE

ELECTRIC DUCT COIL SCHEDULE												
TAG	LOCATION	ROWS	AIR DATA					ELECTRICAL DATA	MFG SIZE HxL (IN.)	TYPICAL UNIT MFG & MODEL NO.	NOTES:	
			CFM	MBH	KW	EAT/LAT (°F)	MAX FACE VELOCITY (FPM)	MAX APD (IN WC)				VOLTS/Ø
EDC-1	GYM	1	625	17.06	5	40/65	700	0.01	208/1	8x18	INDEECO QUA	1
EDC-2	CLASSROOMS	1	270	10.25	3	40/75	773.5	0.01	208/1	8"Ø	RENEWAIRE RH RH03240-8	1
EDC-3	LIBRARY	1	380	10.25	3	40/65	420	<0.01	208/1	12x12	INDEECO QUA	1
NOTES: 1. PROVIDE WITH INTEGRAL CONTROLLER WITH SCR CONTROLS.												

ELECTRIC UNIT HEATER SCHEDULE

TAG	MANUFACTURER	MODEL	TYPE	CFM	BTUH	ELECTRICAL						DIMENSIONS H X W X D	NOTES:
						VOLTAGE	PHASE	FLA	KW	MCA	MOCP		
EUH-1	QMARK	CUS93505483FFW	CEILING RECESSEED	250	17060	480	3	6	5	10	15	26 3/8" x 35" x 9 7/8"	1,2,3
NOTES: 1. COLOR/FINISH TO BE DETERMINED BY THE CLIENT. 2. DISCONNECT BY ELECTRICAL CONTRACTOR. 3. PROVIDE WITH WALL RECESS TRIM KIT. 4. UNIT HEATERS TO BE MOUNTED AT A MAXIMUM OF 10' AFF.													

HYDRONIC KICKSPACE HEATER SCHEDULE

HYDRONIC KICKSPACE HEATER SCHEDULE														
TAG	LOCATION	HOT WATER UNIT					ELECTRICAL					TYPICAL UNIT MFG & MODEL NO.	NOTES:	
		CFM	MBH	GPM	EWTLWT ("F)	MAX WPD (FT. HD)	PIPING RUNOUT SIZE (IN.)	VOLTAGE	PHASE	FLA	MCA			MOCP
KH-1	119 BREAKROOM	103	8460	1	180/160	0.22	3/4	120	1	0.5	0.75	15	BEACON MORRIS K-84	ALL
NOTES: 1. INFORMATION GIVEN FOR WHEN HEATER IS OPERATING IN "HIGH" MODE. 2. GRILL COLOR TO BE DETERMINED BY OWNER 3. PROVIDE WITH MANUFACTURER'S AQUASTAT.														

REGISTER, DIFFUSER & GRILL SCHEDULE

TAG	MAX CFM	NECK SIZE	TYPE	DELTA - P	MAX NC	THROW (FT)	MFG AND MODEL NO.	NOTES
S-1	625	18"x12"	SIDEWALL	0.016	-	10-15-23	PRICE 600	2, 4, 5
S-2	230	8"Ø	CEILING (SUSPENDED)	<0.007	<20	4-10-17	METALAIRES 9000	4, 5, 6, 7
S-3	50	6"Ø	CEILING	0.001	<20	1-2-6	METALAIRES 9000	2, 4, 6, 8
S-4	150	24"x4"	SIDEWALL	0.006	-	7-12-24	PRICE 600	2, 4, 5
R-1	80	6"Ø	CEILING	0.029	-	-	METALAIRES 5700	2, 4, 5, 6
GH-1	460	14"x14"	ROOFTOP	<0.024	-	-	GREENHECK FGR	4, 5, 9
W-1	230	8"Ø	EXTERNAL WALL	0.010	-	-	GREENHECK WC-8	4, 5
KEYED NOTES: 1. PROVIDE WITH OPTIONAL SDFA FRAMES, COORDINATE SPIRAL DUCT DIAMETER WITH PLANS. 2. PROVIDE WITH OPTIONAL VCS3 OPPOSED BLADE DAMPERS. 3. PROVIDE WITH OPTIONAL POB. 4. ALUMINUM CONSTRUCTION. 5. COLOR/FINISH TO BE DETERMINED BY OWNER. 6. PROVIDE WITH MELTALAIRES TR DUCT TRANSITIONS 7. 14x14 INCH FACE 8. 8x8 INCH FACE 9. FIELD VERIFY EXISTING CURB DIMENSIONS BEFORE ORDERING								


LOUVER SCHEDULE

TAG	LOCATION	SERVICE	FREE AREA (FT^2)	CFM	SP (IN WG)	SIZE WxH (IN)	TYPICAL UNIT MFG. & MODEL	NOTES
L-1	MP STORAGE	INTAKE	1.11	625	0.047	20x20	GREENHECK ESD-635	1
L-2	LIBRARY	INTAKE	0.57	380	0.066	16x16	GREENHECK ESD-635	1
NOTES 1. PROVIDE ALUMINUM BIRD SCREEN								

REV. DATE DESCRIPTION BY CHK

DRAWING ISSUE STATUS

ISSUED FOR BID



HALEY WARD

One Merchants Plaza, Suite 701
Bangor, Maine 04401
207.989.4824

www.haleyward.com

PROJECT

CONNOR SCHOOL RENOVATIONS
CONNOR, MAINE

TITLE

MECHANICAL SCHEDULES

STATE OF MAINE

JARED MERRY

No. 11679

PROFESSIONAL ENGINEER

DATE 2025.04.22

SCALE 1/2" = 1'-0"

DRAWN BY ITB

DESIGNED BY JMM

CHECKED BY JMM

PROJECT No. 10377.028


DRAWING NO. M-602

REV.

Autodesk Docs/10377.028 - R23 - Connor School/10377 - CONNOR SCHOOL - MEP.rvt

3 TYPICAL ERV AND DUCT HEATER SEQUENCE OF OPERATIONS

M-701 NTS



INSTRUMENTATION LEGEND	
	MOTOR
	ELEC. COMMUTATED MOTOR
SA	SUPPLY AIR
RA	RETURN AIR
OA	OUTSIDE AIR
EA	EXHAUST AIR
	TEMPERATURE SENSOR
	CO2 SENSOR

A. GENERAL:

1. THE ERV AND ELECTRIC DUCT HEATER SHALL BE CONTROLLED VIA THEIR OWN INTEGRAL CONTROLLERS.
2. ALL SETPOINTS SHALL BE ADJUSTABLE.
3. OPERATION SHALL BE BASED ON THE OCCUPANCY SCHEDULE AS SET BY THE FACILITY'S MANAGEMENT AND PROGRAMMED INTO THE INTEGRAL CONTROLLER.
4. ALL SENSORS SHOWN SHALL BE SUPPLIED WITH THE UNIT.

B. ERV CONTROL:


1. UNOCCUPIED: THE ERV FANS SHALL BE OFF AND THE OUTSIDE AIR AND EXHAUST AIR DAMPERS SHALL BE CLOSED.
2. OCCUPIED: THE ERV EXHAUST AIR AND OUTSIDE AIR DAMPERS SHALL BE OPEN. THE ERV SUPPLY FAN SHALL START AND RUN AT THE MINIMUM VENTILATION RATE SETPOINT, INDICATED ON THE SCHEDULE.
3. WHEN CO2 LEVELS RISE ABOVE 600 PPM, ADJ. THE ERV SUPPLY AND EXHAUST FANS SHALL RAMP THEIR SPEED TO MAINTAIN CO2 LEVELS OF 6000 PPM OR LESS, ADJ.

C. ELECTRIC DUCT HEATER CONTROL:

1. THE ELECTRIC DUCT HEATER SHALL ENERGIZE WHEN THE ASSOCIATED ERV SUPPLY FAN IS OPERATIONAL AND MODULATE TO MAINTAIN A SUPPLY AIR TEMPERATURE OF 68°F (ADJ.).

5 ERV-1 (MULTIPURPOSE ROOM) SEQUENCE OF OPERATIONS

M-701 NTS



INSTRUMENTATION LEGEND	
	MOTORIZED DAMPER ACTUATOR
	ELEC. COMMUTATED MOTOR
SA	SUPPLY AIR
RA	RETURN AIR
OA	OUTSIDE AIR
EA	EXHAUST AIR
	THERMOSTAT
	DIFFERENTIAL PRESSURE SWITCH
	STATIC PRESSURE SENSOR

A. GENERAL:


1. THE ERV AND ELECTRIC DUCT HEATER SHALL BE CONTROLLED VIA THE MANUFACTURER'S INTEGRAL CONTROLLERS.
2. ALL SETPOINTS SHALL BE ADJUSTABLE.
3. OPERATION SHALL BE BASED ON THE OCCUPANCY SCHEDULE AS SET BY THE FACILITY'S MANAGEMENT.
4. THE BUILDING'S FIRE ALARM SYSTEM SHALL INITIATE SHUTDOWN OF THE ERV SYSTEM.

B. ERV CONTROL:

1. THE POSSIBLE CYCLES/MODES SHALL BE OCCUPIED, UNOCCUPIED, ECONOMIZING & UNOCCUPIED BYPASS.
2. UNOCCUPIED CYCLE: THE ERV EXHAUST AIR AND OUTSIDE AIR DAMPERS SHALL BE CLOSED AND THE ERV SHALL BE OFF.
3. OCCUPIED CYCLE:
 - A. THE ERV EXHAUST AND OUTSIDE AIR DAMPERS SHALL BE OPEN.
 - B. THE ERV SHALL START AND RUN CONTINUOUSLY AT THE MINIMUM CFM INDICATED ON SCHEDULE.
 - C. THE ERV FANS SHALL MODULATE BETWEEN THE MINIMUM VENTILATION RATE AND MAXIMUM UNIT FLOW TO MAINTAIN CO2 LEVELS BELOW 600 PPM (ADJ.).
 - D. ECONOMIZING - PROVIDE WITH MANUFACTURER'S SENSORS AND BYPASS CONTROLLER. WHEN THE OUTDOOR AIR ENTHALPY IS LESS THAN THE RETURN AIR ENTHALPHY, AND THE OUTDOOR AIR TEMPERATURE IS GREATER THAN THE LOW LIMIT SETPOINT (50°F ADJ.).
 - a. THE RA FACE DAMPER SHALL CLOSE AND THE BYPASS DAMPER SHALL OPEN.
 - b. THE ERV SHALL RUN AT FULL CFM UNTIL SIGNAL IS SENT TO STOP ECONOMIZING MODE.

C. ELECTRIC DUCT HEATER CONTROL

1. DURING SPACE HEATING OPERATION AND WHEN THE SUPPLY AIR TEMPERATURE FROM THE ERV FALLS BELOW 68°F, THE DUCT HEATER SHALL ENERGIZE AND MODULATE TO MAINTAIN A SUPPLY AIR TEMPERATURE OF 68°F, ADJ.
2. DURING SPACE COOLING OPERATION THE DUCT HEATING COIL SHALL BE OFF.
3. WHEN THE ERV IS OFF THE DUCT HEATING COIL SHALL BE OFF.




VRF CHANGEOVER HEAT PUMP SYSTEM

1. GENERAL:
 - A. THE SYSTEM SHALL OPERATE AS A CHANGEOVER VRF HEAT PUMP SYSTEM.
 - B. EACH INDOOR UNIT SHALL CONDITION A SINGLE ZONE THROUGH A SINGLE WALL MOUNTED CONTROLLER.
 - C. INDOOR AND OUTDOOR UNITS SHALL BE CONTROLLED BY THE MANUFACTURER'S CONTROLLERS:
 - a. PROVIDE AND CONNECT ALL INDOOR AND OUTDOOR UNITS TO A SINGLE CENTRAL CONTROLLER.
 - b. PROVIDE WALL MOUNTED ZONE CONTROLLERS AS INDICATED ON THE MECHANICAL PLANS.
2. CYCLES/MODES:
 - A. THE CYCLE/MODE OF THE ZONE EQUIPMENT AND OUTDOOR EQUIPMENT SHALL BE DETERMINED AND SET BY THE MANUFACTURER'S HEAT PUMP CONTROLS.
 - B. ALL SETPOINTS SHALL BE FIELD ADJUSTABLE FROM THE UNIT ZONE CONTROLLERS AND CENTRAL CONTROLLER.
3. AUXILIARY HEAT: EXISTING HYDRONIC HEAT SHALL ACT AS AUXILIARY HEAT TO THE EACH VRF ZONE. PROVIDE MANUFACTURER CN 24 RELAY KIT WITH EACH INDOOR UNIT. IF SPACE TEMPERATURE FALLS BELOW PRESET TEMPERATURE DIFFERENCE FROM SETPOINT, THE NEW CN 24 RELAY KIT SHALL OPEN THE EXISTING HYDRONIC ZONE VALVE FOR THAT ZONE. WHEN MANUFACTURER'S CONTROLS ARE SATISFIED, HYDRONIC ZONE VALVE SHALL CLOSE AND THE VRF SYSTEM SHALL CONTINUE TO OPERATE.

4 VRF CHANGEOVER HEAT PUMP SYSTEM SEQUENCE OF OPERATIONS

M-701 SCALE: 1/4" = 1'-0"



HEAT RECOVERY VRF HEAT PUMP SYSTEM

1. GENERAL:
 - A. THE SYSTEM SHALL OPERATE AS HEAT RECOVERY VRF HEAT PUMP SYSTEM TO SIMULTANEOUSLY HEAT AND COOL EACH ZONE.
 - B. ALL INDOOR UNITS SHALL BE CONTROLLED BY A WALL MOUNTED CONTROLLER. IN SPACES SERVED BY MULTIPLE INDOOR UNITS A SINGLE CONTROLLER SHALL CONTROL THEM AS A SINGLE ZONE. SEE PLANS FOR CONTROLLER/THERMOSTAT LOCATIONS AND EQUIPMENT SERVED.
 - C. INDOOR AND OUTDOOR UNITS SHALL BE CONTROLLED BY THE MANUFACTURER'S CONTROLLERS:
 - a. PROVIDE AND CONNECT ALL INDOOR AND OUTDOOR UNITS TO A SINGLE CENTRAL CONTROLLER.
 - b. PROVIDE WALL MOUNTED ZONE CONTROLLERS AS INDICATED ON THE MECHANICAL PLANS.
 - D. EXISTING HYDRONIC HEAT SHALL ACT AS AUXILIARY HEAT TO THE EACH VRF ZONE. PROVIDE MANUFACTURER CN 24 RELAY KIT WITH EACH INDOOR UNIT. IF SPACE TEMPERATURE FALLS BELOW PRESET TEMPERATURE DIFFERENCE FROM SETPOINT, THE NEW CN 24 RELAY KIT SHALL OPEN THE EXISTING HYDRONIC ZONE VALVE FOR THAT ZONE. WHEN MANUFACTURER'S CONTROLS ARE SATISFIED, HYDRONIC ZONE VALVE SHALL CLOSE AND THE VRF SYSTEM SHALL CONTINUE TO OPERATE.
1. CYCLES/MODES:
 - A. THE CYCLE/MODE OF THE ZONE EQUIPMENT AND OUTDOOR EQUIPMENT SHALL BE DETERMINED AND SET BY THE MANUFACTURER'S HEAT PUMP CONTROLS.
 - B. ALL SETPOINTS SHALL BE FIELD ADJUSTABLE FROM THE UNIT ZONE CONTROLLERS, CENTRAL CONTROLLER AND BAS INTERFACE.

2 VRF HEAT RECOVERY SYSTEM SEQUENCE OF OPERATIONS

M-701 SCALE: 1/4" = 1'-0"

GENERAL CONTROLS NOTES:

1. ALL VRF INDOOR UNITS SHALL BE PROVIDED WITH AND CONTROLLED BY A SINGLE DELUXE MA THERMOSTAT. EACH THERMOSTAT MA NET COMMUNICATION WIRE SHALL DAISY CHAIN BETWEEN ALL INDOOR UNITS AND BRANCH CONTROLLER(S) THROUGHOUT THE BUILDING AND CONNECT BACK TO THE CENTRAL CONTROLLER.

GLOBAL PROJECT SETPOINTS:

OCCUPIED SETPOINTS:		
HEATING:	68°F	(ADJ.)
COOLING:	75°F	(ADJ.)
CO2:	600 PPM	(ADJ.)

UNOCCUPIED SETPOINTS:		
HEATING:	55°F	(ADJ.)
COOLING:	85°F	(ADJ.)

OTHER SEQUENCES OF CONTROL

1. VESTIBULE CABINET UNIT HEATER:

- A. THE VESTIBULE CABINET UNIT HEATER (CUH) SHALL RESPOND TO A SINGLE THERMOSTAT LOCATED ON THE VESTIBULE WALL.
- B. WHEN THE TEMPERATURE FALLS BELOW THE HEATING SETPOINT (60°F, ADJUSTABLE) THE UNIT HEATER SHALL ENERGIZE AND THE BLOWER SHALL START. WHEN THE THERMOSTAT IS SATISFIED THE HEATER SHALL DE-ENERGIZE AND BLOWER SHALL TURN OFF.

2. BREAK ROOM KICKSPACE HEATER:


- A. THE KICKSPACE HEATER (KH) SHALL RESPOND TO AN EXISTING THERMOSTAT LOCATED ON THE BREAKROOM WALL.
- B. WHEN THE TEMPERATURE FALLS BELOW THE HEATING SETPOINT (68°F, ADJUSTABLE) THE EXISTING CONTROL VALVE SHALL OPEN AND THE BLOWER SHALL START. WHEN THE THERMOSTAT IS SATISFIED THE BLOWER SHALL BE OFF AND HEATING CONTROL VALVE SHALL BE CLOSED.

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				



PROJECT	
CONNOR SCHOOL RENOVATIONS	
CONNOR, MAINE	

TITLE	
MECHANICAL SEQUENCES OF OPERATION	

	DATE		SCALE	
	2025.04.22		1/4" = 1'-0"	
	DRAWN BY	DESIGNED BY	CHECKED BY	
	JNB	JNB	JMM	
	PROJECT No.			
	10377.028			
	DRAWING NO.			REV.
	M-701			

ABBREVIATIONS

A	AMPERES
ADA	AMERICANS WITH DISABILITIES ACT
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AHJ	AUTHORITY HAVING JURISDICTION
AHU	AIR HANDLING UNIT
AIC	AMPERE INTERRUPTING CAPACITY
AL	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ARCH	ARCHITECT
ATS	AUTOMATIC TRANSFER SWITCH
ATC	AUTOMATIC TEMPERATURE CONTROL
AWG	AMERICAN WIRE GAUGE
BFG	BELOW FINISH GRADE
BLOG	BUILDING
C	CONDUIT
CAT	CATALOG
CB	CIRCUIT BREAKER
CBM	CERTIFIED BALLAST MANUFACTURERS
CKT	CIRCUIT
CL	CENTERLINE
CLF	CURRENT LIMITING FUSE
COL	COLUMN
CPT	CONTROL POWER TRANSFORMER
CT	CURRENT TRANSFORMER
CU	COPPER
DWG	DRAWING
EF	EXHAUST FAN
EM	EMERGENCY
ELEV.	ELEVATOR
EMT	ELECTRICAL METALLIC TUBING
EPO	EMERGENCY POWER OFF
EW	ELECTRIC WATER COOLER
FW	FUSE
FA	FIRE ALARM
FLA	FULL LOAD AMPERES
FMC	FLEXIBLE METAL CONDUIT
FT	FEET
GFI	GROUND FAULT CIRCUIT INTERRUPTER
GND, G	GROUND OR GROUNDING
GRMC	GALVANIZED RIGID METALLIC CONDUIT
HOA	HAND, OFF, AUTOMATIC SWITCH
IEEE	INSTITUTE OF ELECTRICAL AND ELECTRONIC ENGINEERS
IMC	INTERMEDIATE METAL CONDUIT
INT	INTERLOCK
IG	ISOLATED GROUND
KCMIL	THOUSAND CIRCULAR MILS
KVA	KILOVOLT AMPERES
KW	KILOWATTS
LGT	LIGHTING
LFMC	LIQUIDTIGHT FLEXIBLE METAL CONDUIT
MC	METAL CLAD CABLE
MCB	MAIN CIRCUIT BREAKER
MCC	MOTOR CONTROL CENTER
MCP	MOTOR CIRCUIT PROTECTOR
MISC	MISCELLANEOUS
MLO	MAIN LUGS ONLY
NC	NORMALLY CLOSED
NEC	NATIONAL ELECTRIC CODE
NEMA	NATIONAL ELECTRICAL MANUFACTURES ASSOCIATION
NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
NO	NORMALLY OPEN OR NUMBER
NTS	NOT TO SCALE
P	POLE
PB	PUSHBUTTON
PNL	PANEL
POS	PROVIDED UNDER OTHER SECTIONS
PVC	POLYVINYL CHLORIDE
PWR	POWER
QTY	QUANTITY
REQ'D	REQUIRED
RMC	RIGID METAL CONDUIT
RMS	ROOT MEAN SQUARED
RNMC	RIGID NON-METALLIC CONDUIT
RTU	ROOF TOP UNIT
SP	SPARE
SW	SWITCH
SYM	SYMMETRICAL
TEL	TELEPHONE
TMCB	THERMAL MAGNETIC CIRCUIT BREAKER
TP	TAMPER PROOF
TYP	TYPICAL
UG	UNDERGROUND OR UNDERGRADE
UL	UNDERWRITERS LABORATORIES
V	VOLT
VT	VOLTAGE TRANSFORMER
W	WIRE
WH	WATER HEATER
WP	WEATHER PROOF
XFMR	TRANSFORMER
UON	UNLESS OTHERWISE NOTED
Δ	DELTA
Y	WYE
Ø	PHASE
G.C.	GENERAL CONTRACTOR
M.C.	MECHANICAL CONTRACTOR
E.C.	ELECTRICAL CONTRACTOR
NL	INDICATES NIGHT LIGHT FIXTURE TO BE CONNECTED TO UNSWITCHED SOURCE, ENERGIZED 24 HOURS A DAY

LIGHTING FIXTURES LEGEND

(REFER TO LIGHTING FIXTURE SCHEDULE FOR ADDITIONAL INFORMATION)

CEILING OUTLET AND LED FIXTURE

	2x2' LED FIXTURE TYPE "A" (REFER TO LIGHTING SCHEDULE)
	"a" INDICATES CONTROLLED BY SWITCH "a"
	"P-2" INDICATES CONNECTED TO PANEL P CIRCUIT NUMBER 2
	2x4'
	1x4'
	SURFACE MOUNTED DOWNLIGHT
	PENDANT MOUNTED DOWNLIGHT
	STRIP LIGHT (SURFACE, SUSPENDED, CHAIN-HUNG)
	LINEAR (SURFACE, SUSPENDED, CHAIN-HUNG)
	WRAP AROUND (SURFACE, SUSPENDED, CHAIN-HUNG)
	HIGH BAY (SURFACE, SUSPENDED, CHAIN-HUNG)

WALL OUTLET AND LED FIXTURE

	WALLPACK
	WALL SCONCE
	WALL SCONCE
	VANITY
	UNDERCABINET

WALL OUTLET AND LED EMERGENCY FIXTURE

	BATTERY BACKUP UNIT
	SINGLE HEADED REMOTE HEAD
	DOUBLE HEADED REMOTE HEAD
	EXIT SIGN (SHADING INDICATES DIRECTION OF FACE(S))
	DIRECTIONAL ARROWS AS INDICATED)

CEILING OUTLET AND LED EMERGENCY FIXTURE

	BATTERY UNIT
	EXIT SIGN (SHADING INDICATES DIRECTION OF FACE(S))
	EMERGENCY (LIFE SAFETY) LIGHTING FIXTURES
	"NL" DENOTES NIGHT LIGHT, "EM" DENOTES BATTERY PACK

CRITICAL BRANCH FIXTURES

	CRITICAL BRANCH FIXTURES
--	--------------------------

LIGHTING DEVICES LEGEND

a	LOWER CASE LETTER DESIGNATION SUCH AS "a" INDICATES CONTROL OF SWITCH LEG "a"
v	"V" INDICATES OCCUPANCY SENSOR VACANCY OPERATION
S	SINGLE POLE SWITCH
S3	THREE WAY SWITCH
S4	FOUR WAY SWITCH
S ^D	DIMMER SWITCH
S ^T	TIMER SWITCH
	DUAL TECHNOLOGY WALL MOUNTED OCCUPANCY SENSOR
	DIMMABLE DUAL TECHNOLOGY WALL MOUNTED OCCUPANCY SENSOR
	DUAL TECHNOLOGY CEILING MOUNTED OCCUPANCY SENSOR

FIRE ALARM SYSTEM LEGEND

	FIRE ALARM SYSTEM COMBINATION HORN/ADA APPROVED STROBE LIGHT SIGNAL UNIT (75CD UNLESS NOTED OTHERWISE) "LF" INDICATES LOW FREQUENCY DEVICE
	FIRE ALARM SYSTEM COMBINATION HORN/ADA APPROVED CEILING MOUNTED STROBE LIGHT SIGNAL UNIT (75CD UNLESS NOTED OTHERWISE) "LF" INDICATES LOW FREQUENCY DEVICE
	FIRE ALARM SYSTEM ADA APPROVED STROBE LIGHT SIGNAL UNIT (75cd UNLESS NOTED OTHERWISE)
	FIRE ALARM SYSTEM ADA APPROVED CEILING MOUNTED STROBE LIGHT SIGNAL UNIT (75CD UNLESS NOTED OTHERWISE)
	FIRE ALARM SYSTEM HORN
	FIRE ALARM SYSTEM DUAL ACTION MANUAL PULL STATION
	DUCT SMOKE DETECTOR
	FIRE ALARM SYSTEM SMOKE DETECTOR
	"XX" DENOTES THE TYPE OF SMOKE DETECTOR
	ELEVATOR COMBINATION SMOKE DETECTOR AND CARBONMONOXIDE DETECTION
	PHOTOELECTRIC SMOKE DETECTOR
	STANDALONE 120V SMOKE DETECTOR NOT CONNECTED TO THE BUILDING SYSTEM
	FIRE ALARM SYSTEM SMOKE DETECTOR MULTI-CRITERIA TYPE UNLESS OTHERWISE NOTED
	FIRE ALARM SYSTEM SMOKE DETECTOR MULTI-CRITERIA TYPE UNLESS OTHERWISE NOTED, WITH SOUNDER BASE.
	FIRE ALARM SYSTEM COMBINATION 135°F FIXED TEMPERATURE/RATE OF RISE HEAT DETECTOR. "F" INDICATES 190°F FIXED TEMPERATURE.
	GAS DETECTOR
	FIRE ALARM SYSTEM BELL
	SPRINKLER SYSTEM WATER FLOW SWITCH
	SPRINKLER SYSTEM VALVE TAMPER SWITCH
	MAGNETIC DOOR HOLDER/CLOSER
	FIRE ALARM ADDRESSABLE INPUT MODULE
	FIRE ALARM ADDRESSABLE OUTPUT MODULE
	REMOTE TEST INDICATOR
	FIRE ALARM CONTROL PANEL
	FIRE ALARM SYSTEM REMOTE ANNUNCIATOR PANEL
	FIRE ALARM KEY BOX
	KITCHEN CHEMICAL PULL STATION
	PLACE OF REFUGE CALL FOR HELP
	AUDIO AND VISUAL ALARM DEVICES SHALL BE MOUNTED 80" ABOVE

ELECTRICAL FIXTURES & EQUIPMENT LEGEND

#	INDICATES CIRCUIT NUMBER CONNECTED TO
	20A, 125V RECEPTACLES ALL TAMPERPROOF
	DUPLEX RECEPTACLE
	DUPLEX RECEPTACLE, HALF-SWITCHED
	DUPLEX RECEPTACLE MOUNTED AT COUNTER HEIGHT
	QUADRUPLEX RECEPTACLE, HALF-SWITCHED
	DUPLEX RECEPTACLE WITH TWO USB CHARGING PORTS
	DUPLEX RECEPTACLE CONNECTED TO 120V EMERGENCY CIRCUIT. EMERGENCY SYSTEM RECEPTACLES SHALL HAVE INDICATION OF PANELBOARD AND CIRCUIT NUMBER SUPPLYING THEM.
	QUADRUPLEX RECEPTACLE CONNECTED TO 120V EMERGENCY CIRCUIT. EMERGENCY SYSTEM RECEPTACLES SHALL HAVE INDICATION OF PANELBOARD AND CIRCUIT NUMBER SUPPLYING THEM.
	FLUSH CEILING MOUNTED DUPLEX RECEPTACLE
	FLUSH CEILING MOUNTED QUAD RECEPTACLE
	OVERHEAD CORD REEL WITH GFI QUAD RECEPTACLE HUBBELL CATALOG #ACA12335-DR20 OR APPROVED EQUAL
	FLUSH POKE-THRU FLOOR WITH DUPLEX RECEPTACLE
	FLUSH POKE-THRU FLOOR WITH QUAD RECEPTACLE

OTHER RECEPTACLES (AS NOTED)

	SPECIAL RECEPTACLE, SEE SPECIAL RECEPTACLE SCHEDULE
	METAL RACEWAY WITH FULL SIZE DEVICES AS INDICATED. PROVIDE WITH AMOUNT OF CHANNELS NECESSARY TO INCORPORATE DEVICES SHOWN.

CONTROL DEVICES (AS NOTED)

	EMERGENCY SHUT-OFF SWITCH
	MANUAL MOTOR STARTER (THERMAL OVERLOAD SWITCH)
	TOGGLE SWITCH WITH PILOT LIGHT (20 AMP)
	KEYED TOGGLE SWITCH (20 AMP)
	AUTOMATIC DOOR PUSH BUTTON FURNISHED AND INSTALLED BY OTHERS, WIRED BY THE ELECTRICAL CONTRACTOR. VERIFY EXACT REQUIREMENTS WITH ARCHITECT PRIOR TO ROUGHING-IN
	THERMAL CUTOFF, TEMPERATURE
	EMERGENCY POWER OFF PUSHBUTTON
	START STOP STATION

EQUIPMENT

	MOTOR - NUMERAL DENOTES HORSEPOWER
	JUNCTION BOX - CEILING AND WALL MOUNTED RESPECTIVELY
	PULL BOX - SIZE PER ELECTRIC CODE

DISCONNECTING EQUIPMENT

	HEAVY DUTY UNFUSED DISCONNECT
	HEAVY DUTY FUSED DISCONNECT
	NEMA RATING (NEMA 1 UNLESS OTHERWISE NOTED)
	TIME DELAY FUSE TRIP RATING
	VOLTAGE (SEE CIRCUITING FOR # OF POLES)
	ENCLOSED BREAKER (AS NOTED)

CONTROLS EQUIPMENT

	CONTROL PANEL
	LIGHTING CONTACTOR
	TIME CLOCK
	TIMER
	CONTACTOR
	VARIABLE FREQUENCY DRIVE

FIXTURE & EQUIPMENT DESIGNATIONS

GFI	GROUND FAULT CIRCUIT INTERRUPTER
WP	WEATHERPROOF

BUILDING GROUNDING GRID LEGEND

—G—	GROUNDING CABLE EXPOSED
—G—	GROUNDING CABLE BURIED
	LIGHTNING PROTECTION ROD
	GROUND ROD
	EXOTHERMIC BONDING CONNECTION
	BOLTED BORDING CONNECTION
	IT ROOM SECONDARY BUS BAR

CIRCUITRY, AND FEEDERS LEGEND

	HOMERUN TO PANEL "LP2A", CIRCUIT #1,3,5
	FEEDER SIZE TAG SYMBOL. REFER TO "LEGEND OF FEEDER SIZES".
	CIRCUITRY TURNING UP
	CIRCUITRY TURNING DOWN

POWER ONE-LINE LEGEND

	POWER TRANSFORMER
	KILOWATT HOUR METER
	KILOWATT HOUR METER WITH BREAKER
	ENCLOSED BREAKER WITH FRAME AND TRIP RATING
	TRANSFER SWITCH WITH RATING AND TYPE (MANUAL OR AUTOMATIC) "ATS" FOR AUTOMATIC "MTS" FOR MANUAL
	UNFUSED DISCONNECT WITH FRAME RATING
	FUSED DISCONNECT FRAME & FUSE TRIP RATING
	INLINE FUSE WITH TRIP RATING
	SYSTEM GROUND OR EQUIPMENT GROUND
	SPECIAL OUTLET
	MOTOR WITH HORSEPOWER RATING
	GENERATOR WITH VOLTAGE, PHASES, RATING BUILT IN MAIN BREAKER WITH RATING, AND #OF POLES

AUDIO / VISUAL LEGEND

	SOUND SYSTEM SUB-AMPLIFIER
	VOLUME CONTROL SWITCH - WALL MOUNTED
	SPEAKER-CEILING MOUNTED, "V" INDICATES WITH VOLUME CONTROL
	RECESSED AV MONITOR UTILITY BOX WITH DUPLEX RECEPTACLE AND DATA OUTLET. PROVIDE 1 1/4" CONDUIT TO WITH PULL STRING TO ABOVE DROP CEILING. 6" AFF CHIEF MODEL #PAC526F
	SEMI-FLUSH WALL MOUNTED, 120 VOLT, 3 WIRE SYNCHRONOUS, 12/24 HOUR ANALOG FACED CLOCK - INTERCONNECT TO THE EAREST RECEPTACLE CIRCUIT
	CARD READER
	KEY PAD
	DOOR CONTACTS
	MOTION SENSOR
	GLASS BREAK SENSOR
	ELECTRIC DOOR LOCK, EITHER STRIKE OR LATCH, CONTRACTOR SHALL VERIFY WITH THE DOOR AND SECURITY VENDOR.
	REQUEST TO EXIT DEVICE
	VIDEO CAMERA
	PUSH/PANIC BUTTON
	SECURITY PANEL
	DOOR RELEASE BUTTON
	WALL MOUNTED TWO WAY INTERCOM
	"V" INDICATES VIDEO CAPABILITY

EXISTING EQUIPMENT LEGEND

	EXISTING EQUIPMENT TO REMAIN (INDICATED BY LIGHT COLOR)
	EXISTING EQUIPMENT TO BE MODIFIED OR REMOVED (INDICATED AS BOLD AND DASHED.)
	EXISTING TO REMAIN
	EXISTING TO BE DISCONNECTED AND REMOVED
	EXISTING TO BE DISCONNECTED AND RELOCATED
	EXISTING TO BE REPLACED
	EXISTING IN NEW LOCATION
	EXISTING LOCATION WITH NEW DEVICE

COMMUNICATION DEVICES LEGEND

	TELEPHONE OUTLET: 4"x4" JUNCTION BOX WITH SINGLE GANG FACEPLATE AND 1" CONDUIT STUBBED 6" ABOVE AN ACCESSIBLE CEILING. "W" INDICATES MOUNTING AT 48" AFF.
	COAXIAL OUTLET: 4"x4" JUNCTION BOX WITH SINGLE GANG FACEPLATE AND 1" CONDUIT STUBBED 6" ABOVE AN ACCESSIBLE CEILING.
	DATA OUTLET: 4"x4" JUNCTION BOX WITH SINGLE GANG FACEPLATE AND 1" CONDUIT STUBBED 6" ABOVE AN ACCESSIBLE CEILING.
	CEILING MOUNTED OUTLET
	FLOOR MOUNTED OUTLET
	WIRELESS ACCESS POINT

GENERAL ELECTRICAL NOTES


- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST EDITION OF THE NFPA 70, NATIONAL ELECTRICAL CODE (NEC), OSHA REGULATIONS, AS WELL AS APPLICABLE REGULATIONS OF THE PERTINENT FEDERAL, STATE, COUNTY, AND CITY AGENCIES. PROVIDE MATERIALS AND EQUIPMENT THAT COMPLY WITH ANSI, IEEE, IES AND NEMA STANDARDS. WHERE APPLICABLE, PROVIDE ONLY MATERIALS THAT ARE U.L. LISTED AND LABELED.
- PROVIDE ALL NECESSARY ACCESSORIES REQUIRED TO MEET THE INTENT OF THE CONTRACT DRAWINGS.
- ALL GENERAL NOTES, SYMBOL LISTS, ABBREVIATIONS AND DETAILS ARE TO BE CONSIDERED APPLICABLE TO ALL ELECTRICAL DRAWINGS FOR THIS PROJECT.
- WHERE A DISCREPANCY OCCURS BETWEEN THE DRAWINGS AND THE SPECIFICATIONS, THE SPECIFICATIONS SHALL PREVAIL. CONTACT THE ENGINEER FOR CLARIFICATION WHEN SUCH A SITUATION OCCURS.
- WHERE MATERIAL IS CALLED OUT IN THE LEGEND BY MANUFACTURER TYPE OR CATALOG NUMBER, SUCH DESIGNATIONS ARE TO ESTABLISH STANDARDS OR DESIRED QUALITY. ACCEPTANCE OR REJECTION OF PROPOSED SUBSTITUTIONS SHALL BE SUBJECT TO THE APPROVAL OF THE OWNER.
- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL IN NATURE AND SHALL NOT BE SCALED. REFER TO ARCHITECTURAL/CIVIL DRAWINGS FOR EXACT LOCATION OF EQUIPMENT AND DEVICES, AND FURNITURE REQUIREMENTS, PRIOR TO ROUGHING IN FOR SAME.
- GIVE ALL NECESSARY NOTICES, OBTAIN ALL PERMITS; PAY ALL GOVERNMENT AND STATE SALES TAXES AND FEES WHERE APPLICABLE, AND OTHER COSTS, INCLUDING UTILITY CONNECTIONS OR EXTENSIONS IN CONNECTION WITH THE PROJECT SCOPE OF WORK. FILE ALL NECESSARY DRAWINGS, PREPARE AND OBTAIN ALL NECESSARY APPROVALS OF ALL GOVERNMENTAL AND STATE DEPARTMENTS HAVING JURISDICTION, OBTAIN ALL REQUIRED CERTIFICATES OF INSPECTIONS FOR PROJECT SCOPE OF WORK AND DELIVER A COPY TO THE ENGINEER BEFORE REQUEST FOR ACCEPTANCE AND FINAL PAYMENT FOR THE PROJECT SCOPE OF WORK.
- COOPERATE FULLY WITH SEPARATE CONTRACTORS SO WORK ON THOSE CONTRACTS MAY BE CARRIED OUT SMOOTHLY, WITHOUT INTERFERING WITH OR DELAYING WORK UNDER THIS CONTRACT. COORDINATE THE WORK OF THIS CONTRACT WITH WORK PERFORMED UNDER SEPARATE CONTRACTS.
- EACH CONTRACTOR SHALL COORDINATE ITS CONSTRUCTION OPERATIONS WITH THOSE OF OTHER CONTRACTORS AND ENTITIES TO ENSURE EFFICIENT AND ORDERLY INSTALLATION OF EACH PART OF THE WORK. EACH CONTRACTOR SHALL COORDINATE ITS OPERATIONS WITH OPERATIONS, INCLUDING IN DIFFERENT SECTIONS, THAT DEPEND ON EACH OTHER FOR PROPER INSTALLATION, CONNECTION, AND OPERATION. SCHEDULE CONSTRUCTION OPERATIONS IN SEQUENCE REQUIRED TO OBTAIN THE BEST RESULTS WHERE INSTALLATION OF ONE PART OF THE WORK DEPENDS ON INSTALLATION OF OTHER COMPONENTS, BEFORE OR AFTER ITS OWN INSTALLATION. COORDINATE INSTALLATION OF DIFFERENT COMPONENTS WITH OTHER CONTRACTORS TO ENSURE MAXIMUM PERFORMANCE AND ACCESSIBILITY FOR REQUIRED MAINTENANCE, SERVICE, AND REPAIR. MAKE ADEQUATE PROVISIONS TO ACCOMMODATE ITEMS SCHEDULED FOR LATER INSTALLATION.
- IF COMPLIANCE WITH TWO OR MORE STANDARDS OR DIRECTIVES IS SPECIFIED AND THE STANDARDS ESTABLISH DIFFERENT OR CONFLICTING REQUIREMENTS FOR MINIMUM QUANTITIES OR QUALITY LEVELS, COMPLY WITH THE MOST STRINGENT REQUIREMENT. REFER UNCERTAINTIES AND REQUIREMENTS THAT ARE DIFFERENT, BUT APPARENTLY EQUAL, TO ARCHITECT/ENGINEER FOR A DECISION BEFORE PROCEEDING.
- THE QUANTITY OR QUALITY LEVEL SHOWN OR SPECIFIED SHALL BE THE MINIMUM PROVIDED OR PERFORMED. THE ACTUAL INSTALLATION MAY COMPLY EXACTLY WITH THE MINIMUM QUANTITY OR QUALITY SPECIFIED, OR IT MAY EXCEED THE MINIMUM WITHIN REASONABLE LIMITS. TO COMPLY WITH THESE REQUIREMENTS, INDICATED NUMERIC VALUES ARE MINIMUM OR MAXIMUM, AS APPROPRIATE, FOR THE CONTEXT OF REQUIREMENTS. REFER UNCERTAINTIES TO ENGINEER FOR A DECISION BEFORE PROCEEDING.
- DELIVER, STORE, AND HANDLE PRODUCTS USING MEANS AND METHODS THAT WILL PREVENT DAMAGE, DETERIORATION, AND LOSS, INCLUDING THEFT. COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS AND GENERALLY ACCEPTED CONSTRUCTION PRACTICE.
- WARRANTY EQUIPMENT AND INSTALLATIONS FOR A PERIOD OF ONE YEAR AFTER SUBSTANTIAL COMPLETION OF PROJECT
- EACH CONTRACTOR SHALL ASSIGN REPRESENTATIVES WITH EXPERTISE AND AUTHORITY TO ACT ON ITS BEHALF AND SHALL SCHEDULE THEM TO PARTICIPATE IN AND PERFORM COMMISSIONING PROCESS ACTIVITIES FOR ALL NEW EQUIPMENT AND SYSTEMS.
- PREPARE PROJECT SPECIFIC INFORMATION TO BE SUBMITTED AS SHOP DRAWINGS FOR PROJECT. SHOP DRAWINGS SHALL BE SUBMITTED FOR ALL EQUIPMENT AND MATERIALS TO BE USED ON PROJECT. SUBMITTALS SHALL BE DRAWN ACCURATELY AND TO SCALE. DO NOT BASE SHOP DRAWINGS ON REPRODUCTIONS OF THE CONTRACT DOCUMENTS OR STANDARD PRINTED DATA. SUBMIT SHOP DRAWINGS IN QUANTITIES AS REQUIRED BY ARCHITECT.
- THE EXISTENCE AND LOCATION OF UNDERGROUND AND OTHER UTILITIES AND CONSTRUCTION INDICATED AS EXISTING ARE NOT GUARANTEED. BEFORE BEGINNING WORK, INVESTIGATE AND VERIFY THE EXISTENCE AND LOCATION OF UTILITIES, MECHANICAL AND ELECTRICAL SYSTEMS, AND OTHER CONSTRUCTION AFFECTING THE WORK. ADVISE ARCHITECT OF CONFLICTS OR DEFICIENCIES PRIOR TO STARTING WORK.
- TAKE FIELD MEASUREMENTS AS REQUIRED TO FIT THE WORK PROPERLY. RECHECK MEASUREMENTS BEFORE INSTALLING EACH PRODUCT. WHERE PORTIONS OF THE WORK ARE INDICATED TO FIT TO OTHER CONSTRUCTION, VERIFY DIMENSIONS OF OTHER CONSTRUCTION BY FIELD MEASUREMENTS BEFORE FABRICATION. COORDINATE FABRICATION WITH CONSTRUCTION PROGRESS TO AVOID DELAYING THE WORK. VERIFY SPACE REQUIREMENTS AND DIMENSIONS OF ITEMS SHOWN DIAGRAMMATICALLY ON DRAWINGS. IMMEDIATELY ON DISCOVERY OF THE NEED FOR CLARIFICATION OF THE CONTRACT DOCUMENTS, SUBMIT A REQUEST FOR INFORMATION TO ENGINEER. INCLUDE A DETAILED DESCRIPTION OF PROBLEM ENCOUNTERED, TOGETHER WITH RECOMMENDATIONS FOR CHANGING THE CONTRACT DOCUMENTS.
- COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS AND RECOMMENDATIONS FOR INSTALLING PRODUCTS IN APPLICATIONS INDICATED.
- CONDUCT CONSTRUCTION OPERATIONS SO NO PART OF THE WORK IS SUBJECTED TO DAMAGING OPERATIONS OR LOADING IN EXCESS OF THAT EXPECTED DURING NORMAL CONDITIONS OF OCCUPANCY.
- KEEP INSTALLED WORK CLEAN. CLEAN INSTALLED SURFACES ACCORDING TO WRITTEN INSTRUCTIONS OF MANUFACTURER OR FABRICATOR OF PRODUCT INSTALLED, USING ONLY CLEANING MATERIALS SPECIFICALLY RECOMMENDED. IF SPECIFIC CLEANING MATERIALS ARE NOT RECOMMENDED, USE CLEANING MATERIALS THAT ARE NOT HAZARDOUS TO HEALTH OR PROPERTY AND THAT WILL NOT DAMAGE EXPOSED SURFACES.
- DURING HANDLING AND INSTALLATION, CLEAN AND PROTECT CONSTRUCTION IN PROGRESS AND ADJOINING MATERIALS ALREADY IN PLACE. APPLY PROTECTIVE COVERING WHERE REQUIRED TO ENSURE PROTECTION FROM DAMAGE OR DETERIORATION AT SUBSTANTIAL COMPLETION.
- CLEAN AND PROVIDE MAINTENANCE ON COMPLETED CONSTRUCTION AS FREQUENTLY AS NECESSARY THROUGH THE REMAINDER OF THE CONSTRUCTION PERIOD. ADJUST AND LUBRICATE OPERABLE COMPONENTS TO ENSURE OPERABILITY WITHOUT DAMAGING EFFECTS.
- START EQUIPMENT AND ADJUSTING COMPONENTS TO CONFIRM PROPER OPERATION. REMOVE MALFUNCTIONING UNITS. REPLACE WITH NEW UNITS, AND RETEST. ADJUST OPERATING COMPONENTS FOR PROPER OPERATION WITHOUT BINDING. ADJUST EQUIPMENT FOR PROPER OPERATION. TEST EACH PIECE OF EQUIPMENT TO VERIFY PROPER OPERATION. TEST AND ADJUST CONTROLS AND SAFETIES. REPLACE DAMAGED AND MALFUNCTIONING CONTROLS AND EQUIPMENT.
- PROVIDE FINAL PROTECTION AND MAINTAIN CONDITIONS THAT ENSURE INSTALLED WORK IS WITHOUT DAMAGE OR DETERIORATION AT TIME OF SUBSTANTIAL COMPLETION.
- THE COST OF CORRECTIVE WORK SHALL BE INCLUDED UNDER THE CONTRACT.
- SEAL CONDUIT AND CABLE PENETRATIONS WITH APPROVED FIRESTOP MATERIALS. REFER TO DIVISION 7 SECTION "THROUGH-PENETRATION FIRESTOP SYSTEMS" FOR MATERIALS.
- INSTALL EQUIPMENT TO ALLOW MAXIMUM POSSIBLE HEADROOM UNLESS SPECIFIC MOUNTING HEIGHTS ARE INDICATED. INSTALL EQUIPMENT LEVEL AND PLUMB, PARALLEL AND PERPENDICULAR TO OTHER BUILDING SYSTEMS AND COMPONENTS IN EXPOSED INTERIOR SPACES. UNLESS OTHERWISE INDICATED, INSTALL ELECTRICAL EQUIPMENT TO FACILITATE SERVICE, MAINTENANCE, AND REPAIR OR REPLACEMENT OF COMPONENTS. CONNECT EQUIPMENT FOR EASE OF DISCONNECTING, WITH MINIMUM INTERFERENCE TO OTHER INSTALLATIONS.
- ELECTRICAL AND SYSTEMS CONTRACTOR SHALL COORDINATE HIS WORK WITH GENERAL, HVAC, FIRE PROTECTION PLUMBING CONTRACTORS AND VENDORS AND SHALL MAKE NECESSARY ADJUSTMENTS OR CHANGES TO FACILITATE INSTALLATION OF EQUIPMENT IN SPACES AVAILABLE.
- ACCESS PANELS SHALL BE PROVIDED BY ELECTRICAL AND SYSTEMS CONTRACTOR FOR ALL ITEMS REQUIRING INSPECTION OR MAINTENANCE OR AS REQUIRED BY CODE. ACCESS PANELS SHALL BE OF SUFFICIENT SIZE AND LOCATED SO THAT THE CONCEALED ITEMS MAY BE SERVICED AND MAINTAINED OR COMPLETELY REMOVED AND REPLACED. MINIMUM SIZE OF PANEL SHALL BE 12" BY 12". PANELS SHALL BE COMPLETE WITH IDENTIFYING LABELS.
- ELECTRICAL CONTRACTOR SHALL KEEP AN UP TO DATE SET OF "AS-BUILT" RECORD DRAWINGS ON SITE AT ALL TIMES. AT PROJECT COMPLETION PROVIDE THE OWNER, ARCHITECT AND THE ENGINEER WITH A COMPLETE SET OF CONTRACT DRAWINGS WITH ALL FIELD CHANGES IN CAD FORMAT ALONG WITH A PDF SET AND A FULL SIZE PRINT.
- ALL ELECTRICAL EQUIPMENT, DEVICES, CONDUCTORS, CABLES AND ETC. SHALL BE U.L. LABELED AND LISTED FOR THE APPLICATION IN WHICH IT IS BEING USED.
- CONTRACTOR SHALL PREPARE OPERATION AND MAINTENANCE MANUALS FOR BUILDING OWNER. OPERATION AND MAINTENANCE MANUALS SHALL INCLUDE SHOP DRAWING SUBMITTALS AND OPERATION AND MAINTENANCE MANUALS FOR EACH PIECE OF EQUIPMENT AND SYSTEM INSTALLED FOR PROJECT. OWNER SHALL BE PROVIDED WITH 3 COPIES OF OPERATION AND MAINTENANCE MANUALS.

STANDARDS

- ALL MATERIALS, EQUIPMENT AND INSTALLATION SHALL COMPLY WITH THE FOLLOWING:
- LATEST ADOPTED MAINE UNIFIED BUILDING CODE "MUBEC"
- NATIONAL ELECTRICAL CODE, LATEST APPROVED EDITION.
- ANY AND ALL FEDERAL, STATE AND/OR LOCAL CODES, APPLICABLE ORDINANCES AND REGULATIONS.
- LATEST APPROVED STANDARDS OF IEEE, ANSI, NEMA AND NFPA.
- LOCAL UTILITY AND TELEPHONE COMPANY REGULATIONS.
- BICSI TDM-1, LATEST EDITION
- ALL EQUIPMENT SHALL BE NEW AND U.L. LISTED WHERE LISTING IS AVAILABLE.


<

SITE LIGHTING FIXTURE SCHEDULE								
TAG	DESCRIPTION	MANUFACTURER	MODEL	COLOR/TYPE	Lumens	WATTS	VOLTAGE	REMARKS
Z3	POLE MOUNTED SITE LIGHTING FIXTURE, TYPE III OPTICS, BUILT IN PHOTOEYE, UNIVERSAL SQUARE POLE MOUNT MOUNTED ON 15' POLE	BEACON	VP-ST-1-36L-39-4K7-3-UNV-ASQU-##-LS-3P R-TL	40K LED	5400 lm	39.3 W	120-277V	PROVIDE WITH 15' MOUNTING POLE
Z4F	POLE MOUNTED SITE LIGHTING FIXTURE, TYPE IV FORWARD OPTICS, BUILT IN PHOTOEYE, UNIVERSAL SQUARE POLE MOUNT MOUNTED ON 15' POLE	BEACON	VP-ST-1-36L-55-4K7-4F-UNV-ASQU-##-LS-3 PR-TL	40K LED	7500 lm	56.8 W	120-277V	PROVIDE WITH 15' MOUNTING POLE
Z4W-1	POLE MOUNTED SITE LIGHTING FIXTURE, TYPE IV WIDE OPTICS, BUILT IN PHOTOEYE, UNIVERSAL SQUARE POLE MOUNT MOUNTED ON 15' POLE	BEACON	VP-ST-1-36L-85-4K7-4W-UNV-ASQU-##-LS-3 PR-TL	40K LED	10000 lm	83.6 W	120-277V	PROVIDE WITH 20' MOUNTING POLE
Z4W-2	POLE MOUNTED SITE LIGHTING FIXTURE, TYPE IV WIDE OPTICS, BUILT IN PHOTOEYE, UNIVERSAL SQUARE POLE MOUNT MOUNTED ON 15' POLE	BEACON	VP-ST-1-36L-55-4K7-4W-UNV-ASQU-##-LS-3 PR-TL	40K LED	7500 lm	56.8 W	120-277V	PROVIDE WITH 15' MOUNTING POLE
Z4W-3	POLE MOUNTED SITE LIGHTING FIXTURE, TYPE IV WIDE OPTICS, BUILT IN PHOTOEYE, UNIVERSAL SQUARE POLE MOUNT MOUNTED ON 15' POLE	BEACON	VP-ST-1-36L-39-4K7-4W-UNV-ASQU-##-LS-3 PR-TL	40K LED	5400 lm	39.3 W	120-277V	PROVIDE WITH 15' MOUNTING POLE




NOTES:
1. CAUTION - DEEPER BURIAL DEPTHS MAY REQUIRE DERATING. SEE NEC.


3 E-101 TYPICAL SITE LIGHTING TRENCH DETAIL NTS



2 E-101 ELECTRICAL SECONDARY TRENCH DETAIL NTS



6 E-101 PEDESTAL MOUNTED CT METER AND CT CABINET DETAIL NTS



1 E-101 ELECTRICAL SITE PLAN SCALE: 1/16" = 1'-0"

SHEET E-101 GENERAL NOTES

- EXTERIOR BUILDING MOUNTED FIXTURES SHOWN FOR INDICATION OF SITE LIGHTING. FOR CIRCUITING SEE LIGHTING PLAN.

SHEET E-101 NUMBERED NOTES


- REMOVE POLE, LIGHT FIXTURE, AND OVERHEAD BRANCH CIRCUIT CONDUCTORS IN THEIR ENTIRETY.
- REMOVE LIGHT FIXTURE AND OVERHEAD BRANCH CIRCUIT CONDUCTORS.
- EXISTING 120/240V/1PH SERVICE ENTRANCE TO BE REPLACED WITH NEW 120/208V/3PH SERVICE. REMOVE EXISTING METER, RISER CONDUIT, CONDUCTORS AND UNDERGROUND CONDUIT IN THEIR ENTIRETY.

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
		HALEY WARD		
www.haleyward.com		One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824		
PROJECT				
CONNOR SCHOOL RENOVATIONS				
CONNOR, MAINE				
TITLE				
ELECTRICAL SITE PLAN				
		DATE: 2025.04.22 SCALE: As indicated DRAWN BY: TJA DESIGNED BY: TJA CHECKED BY: JMM PROJECT No.: 10377.028 DRAWING No.: REV:		
		E-101		


7 6 5 4 3 2 1

SHEET ED101 NUMBERED NOTES #

- 1 REPLACE INDICATED LIGHTING FIXTURES IN THIS ROOM. EXISTING SWITCHING AND CIRCUIT TO BE REUSED.
- 2 REMOVE LIGHT FIXTURE. LEAVE CIRCUITING IN PLACE FOR NEW/RELOCATED FIXTURE.





1 ELECTRICAL LIGHTING FIRST FLOOR DEMOLITION PLAN
ED101 / SCALE: 1/8" = 1'-0"



2 ELECTRICAL LIGHTING BASEMENT DEMOLITION PLAN
ED101 / SCALE: 3/32" = 1'-0"



REV	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE ELECTRICAL LIGHTING DEMOLITION PLAN				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY TJA	DESIGNED BY TJA	CHECKED BY JMM		
PROJECT No. 10377.028		REV		
DRAWING NO. ED101				



7 6 5 4 3 2 1

7

6

5

4

3

2


1

SHEET ED102 GENERAL NOTES


1. DEMOLISH DISCONNECTS, CONDUCTORS, AND CONDUIT ASSOCIATED WITH MECHANICAL UNITS THAT ARE TO BE REMOVED UNLESS OTHERWISE NOTED.

SHEET ED102 NUMBERED NOTES


- 1 PANEL SHALL BE REPLACED IN KIND. FEEDER CONDUIT AND CONDUCTORS SHALL REMAIN IN PLACE FOR PANEL REPLACEMENT. REMOVE ANY NECESSARY ITEMS FOR REMOVAL OF THE PANEL. REMOVE AND REPLACE TO MATCH EXISTING WALL FINISH AS REQUIRED TO COMPLETE NEW WORK.
- 2 REMOVE MDP, SERVICE ENTRANCE CONDUCTORS AND CONDUIT IN THEIR ENTIRETY.
- 3 REMOVE CONDUCTORS AND CONDUIT FROM DISCONNECT TO EXHAUST FAN. LEAVE DISCONNECT, CONDUCTORS, AND CONDUIT TO PANEL LOCATION IN PLACE FO REUSE.
- 4 REMOVE CONDUCTORS AND CONDUIT FROM DISCONNECT TO EXISTING EXHAUST FAN. LEAVE DISCONNECT, CONDUCTORS, AND CONDUIT TO PANEL LOCATION IN PLACE FOR REUSE.




1 ELECTRICAL FIRST FLOOR DEMOLITION PLAN
ED102 SCALE: 1/8" = 1'-0"



2 ELECTRICAL BASEMENT DEMOLITION PLAN
ED102 SCALE: 3/32" = 1'-0"

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
<div>HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM</div>				
PROJECT				
CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE				
ELECTRICAL POWER & SYSTEMS DEMOLITION				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY TJA	DESIGNED BY TJA	CHECKED BY JMM		
PROJECT No. 10377.028		DRAWING NO. ED102		
REV.		REV.		



LIGHTING DEVICE SCHEDULE		
TYPE MARK	VOLTAGE	FUNCTIONS
OC	LINE VOLTAGE	CEILING MOUNTED OCCUPANCY SENSOR
OC - V	LOW VOLTAGE	CEILING MOUNTED OCCUPANCY SENSOR, VACANCY OPERATION CAPABILITY
PE	LINE VOLTAGE	PHOTOEYE
S	LINE VOLTAGE	SINGLE POLE SWITCH
S - DV	LOW VOLTAGE	SINGLE POLE SWITCH, DIMMING, VACANCY OPERATION CAPABILITY



LIGHTING FIXTURE SCHEDULE							
TAG	DESCRIPTION	MANUFACTURER	MODEL	COLOR/TYPE	LUMENS	WATTS	VOLTAGE
A	2'x4' SWITCHABLE FLAT PANEL	COLUMBIA LIGHTING	CBT24 A LSCS EDD	SWITCHABLE LED	3400/4500/5800	48.0 W	120-277V
B	2'x2' FLAT PANEL	COLUMBIA LIGHTING	CBT22 A LSCS EDD	SWITCHABLE LED	2800/3300/4500	38.0 W	120-277V
BS	2'x2' FLAT PANEL, DRYWALL FLANGED RECESSED	COLUMBIA LIGHTING	CBT22 A LSCS EDD	SWITCHABLE LED	2800/3300/4500	38.0 W	120-277V
C	8" HUNG LED LINEAR	COLUMBIA LIGHTING	CSL8 A LSCS	SWITCHABLE LED	8000/8900/9600	81.0 W	120-347V
D6	6" RECESSED LED DOWNLIGHT	PRESCOLITE	LBRST 6RD M LS ML CS9 WH	SWITCHABLE LED	1100/1500/2500	30.7 W	120-277V
D8	8" SURFACE MOUNTED DOWNLIGHT	PRESCOLITE	LBRST 8RD M LS HL CS9 WH	SWITCHABLE LED	3000/4000/4600	48.7 W	120-277V
DS4	4" SURFACE MOUNTED LED DOWNLIGHT	PRESCOLITE	LBSES 4RD CS9 WH	SWITCHABLE LED	750	10.4 W	120-277V
DS6	6" SURFACE MOUNTED LED DOWNLIGHT	PRESCOLITE	LBSES 6RD CS9 WH	SWITCHABLE LED	1100	13.1 W	120-277V
DS8	8" SURFACE MOUNTED DOWNLIGHT	PRESCOLITE	LBSES 8RD CS9 WH	SWITCHABLE LED	1750	19.3 W	120-277V
DS8E	8" SURFACE MOUNTED DOWNLIGHT, EMERGENCY BATTERY BACKUP	PRESCOLITE	LBSES 8RD RM CS9 WH	SWITCHABLE LED	1750	19.3 W	120-277V
E1	UNIVERSAL MOUNTED THERMOPLASTIC LED EXIT LIGHT WITH RED LETTERING	DUAL LITE	EVEURWE	LED	N/A	3.0 W	120-277V
E2	UNIVERSAL SURFACE MOUNTED THERMOPLASTIC LED EMERGENCY BATTERY UNIT	DUAL LITE	EV2	40K LED	N/A	3.0 W	120-277V
E3	UNIVERSAL MOUNTED THERMOPLASTIC LED EXIT LIGHT WITH RED LETTERING, DUAL EMERGENCY BATTERY HEADS	DUAL LITE	EVCURW	LED	N/A	3.0 W	120-277V
G	CHAIN HUNG LOW BAY	ADVANTAGE LIGHTING SOLUTIONS	LHB 90 40 FL WH UD -PLUG	40K LED	12700	90.0 W	120-277V
H	2' CLOSET STRIP LIGHT	COLUMBIA LIGHTING	MPS 2 35 LW F W ED U	35K LED	2400	14.0 W	120-277V
J	4' SURFACE MOUNTED WRAP AROUND	COLUMBIA LIGHTING	CNW LSCS	SWITCHABLE LED	3000/3500/4000	35.0 W	120-277V
K	4' WALL MOUNTED LINEAR	COLUMBIA LIGHTING	CWM 4 35 MW SM DIS FA ED U	35K LED	4200	43.0 W	120-277V
R	24" STEM MOUNTED DRUM LIGHT	FORUM	DRM-UD 24 H (XX) HO 35 WOL UNV WH D10V	35K LED	9000	25.0 W	120-277V
V	2' WALL MOUNTED VANITY	LIGHTWAY	24-LED 02C 3 W2 WSA DIM	35K LED	2400	18.0 W	120/277V
W	4' WALL WASH LINEAR	COLUMBIA LIGHTING	W3B 4 40 LW SFA ED U	40K LED	4300	30.1 W	120-277V
X	EXTERIOR WEDGE LIGHT, EMERGENCY BATTERY BACKUP	BEACON	VPW2 48L-20 4K7 4W UNV BLT EH	40K LED	4000	20.5 W	120-277V
X2	EXTERIOR WEDGE LIGHT, EMERGENCY BATTERY BACKUP, BUILT IN PHOTOEYE	BEACON	VPW2 48L-20 4K7 4W UNV BLH PC EH	40K LED	4000	20.5 W	120-277V
Y	WALL MOUNTED STEM DISPLAY LIGHT	HYDREL	PLACERTWIN A P1 80CRI 35K 120 40DEG FLC S90 L3 BL	35K LED	2800	22.0 W	120V

SHEET EL101 GENERAL NOTES



1. ALL INTERIOR SWITCHABLE CCT LIGHTING FIXTURES SHALL BE SET TO 35K.


SHEET EL101 NUMBERED NOTES

1. RELOCATE EXISTING CLOSET LIGHT FIXTURE TO FIT LAYOUT IN ROOM. IF NOT ALREADY CONNECTED TO THE SAME CIRCUIT AS THE REMAINDER OF THE BREAK ROOMS LIGHTING, CONNECT TO THE SAME CIRCUIT AND INTEGRATE INTO THE ROOMS SWITCH LEG.
2. NORMAL LIGHTING FIXTURES SHALL REPLACE EXISTING NORMAL LIGHTING IN THIS AREA. RECONNECT TO EXISTING LOCAL LIGHTING CIRCUIT. RECONNECT NORMAL LIGHTING TO EXISTING SWITCH LEG(S). CONNECT ANY NEW EGRESS LIGHTING TO THE LOCAL LIGHTING CIRCUIT UNSWITCHED.
3. RELOCATED FIXTURE. UTILIZE EXISTING CIRCUIT AND SWITCHING FOR LIGHTING FIXTURE. EXTEND CIRCUITING AND SWITCHING WIRING AS NECESSARY FOR NEW LOCATION.
4. STEM MOUNT HALLWAY FIXTURES SO THAT EACH FIXTURE IS AT THE SAME HEIGHT.
5. ADD ROW OF NEW CLASSROOM LIGHTS IN PLACE OF REMOVED WALL WASH FIXTURE. UTILIZE EXISTING LOCAL LIGHTING CIRCUIT. EXTEND SURFACE MOUNTED CONDUIT SYSTEM ALREADY FEEDING OTHER 4 LOCATIONS TO NEW FIXTURE. EXTEND CIRCUITING AND SWITCHING WIRING AS NECESSARY FOR NEW FIXTURE LOCATION.
6. CONNECT NEW EBU TO LOCAL LIGHTING CIRCUIT UNSWITCHED. UTILIZE SURFACE MOUNTED CONDUIT FROM FLOOR BELOW TO REACH THE NEW FIXTURE.
7. LIGHTING IN NEW ROOMS SHALL BE CONNECTED TO LOCAL LIGHTING CIRCUIT IN LOBBY BEFORE ANY SWITCHES.
8. INSTALL NEW PHOTOEYE NEARBY CANOPY TO CONTROL NEW CANOPY LIGHTING. PHOTOEYE SHALL BE IN SERIES WITH NEW FIXTURES.




1 ELECTRICAL LIGHTING FIRST FLOOR PLAN
EL101 SCALE: 1/8" = 1'-0"


REV	DATE	DESCRIPTION	BY	CHK
1	2025.04.22	ISSUED FOR BID		
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 www.haleyward.com				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE ELECTRICAL LIGHTING FIRST FLOOR PLAN				
		DATE 2025.04.22 SCALE As indicated DRAWN BY TJA DESIGNED BY TJA CHECKED BY JMM PROJECT No. 10377.028 DRAWING No. EL101		




1 EQUIPMENT MOUNTING HEIGHTS
E-501 NTS




4 ELECTRICAL SERVICE GROUNDING ELECTRODE
E-501 NTS




2 TYPICAL NAMEPLATE DETAIL
E-501 NTS




3 EQUIPMENT NAMEPLATE DETAIL
E-501 NTS




7 CONDUIT STANDOFF BRACKET DETAIL
E-501 SCALE: 1/4\"/>




5 ELECTRICAL POWER DEMOLITION ONE-LINE DIAGRAM
E-501 NTS



6 ELECTRICAL POWER NEW ONE-LINE DIAGRAM
E-501 NTS

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
ISSUED FOR BID				
 HALEY WARD One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824 WWW.HALEYWARD.COM				
PROJECT CONNOR SCHOOL RENOVATIONS CONNOR, MAINE				
TITLE ELECTRICAL DETAILS				
DATE 2025.04.22		SCALE As indicated		
DRAWN BY TJA	DESIGNED BY TJA	CHECKED BY JMM		
PROJECT No. 10377.028		REV.		
DRAWING NO. E-501				



Autodesk Docs /10377/281-1623_Connor School/10377-CONNOR SCHOOL-MEP-14

Distribution Panel MDP																
Location: BASEMENT Supply From: UTILITY POLE Mounting: SURFACE Enclosure: NEMA 1				Volts: 120/208 Wye Phases: 3 Wires: 4				A.I.C. Rating: 22 kAIC Mains Type: MCB Mains Rating: 800 A MCB Rating: 800 A								
Notes: NEW PANEL REPLACING EXISTING MDP																
CKT	Circuit Description	Trip	Poles	A		B		C		Poles	Trip	Circuit Description	CKT			
1	WATER PUMP	30 A	2	0.0 W	0.0 W					2	30 A	SPARE	2			
3						0.0 W	0.0 W							4		
5								0.0 W	0.0 W					6		
7	SPARE	60 A	2	0.0 W	0.0 W					2	60 A	STOVE	8			
9						0.0 W	0.0 W							10		
11								0.0 W	0.0 W					12		
13	LPB	100 A	2	0.0 W	0.0 W					2	100 A	LPA	14			
15						0.0 W	0.0 W							16		
17													4953.... 5666....	18		
19	OU-1 FEED 1	90 A	3	4953....	5666....					3	100 A	OU-2	20			
21														22		
23						4953....	5666....						4953.... 2066....	24		
25	OU-1 FEED 2	90 A	3	4953....	2066....					3	20 A	EUH-1	26			
27						4953....	2066....							28		
29													4953.... 4953....	30		
31	OU-3 FEED 1	90 A	3	4953....	4953....					3	90 A	OU-3 FEED 2	32			
33						4953....	4953....							34		
35													0.0 W	0.0 W	36	
37	SPARE	30 A	3	0.0 W	0.0 W					3	20 A	SPARE	38			
39						0.0 W	0.0 W							40		
41													200.0.... 396.0....	42		
43	IU 14-17	15 A	2	200.0....	396.0....					2	15 A	IU 1-12	44			
45						250.0....	80.0 W							46		
47								250.0....	80.0 W					48		
49	ERV-7	15 A	2							2	15 A	BRANCH CONTROLLER BC-1	50			
51				205.6....	2704....									52		
53						205.6....	2704....						0.0 W	300.0....	54	
55	SPARE	15 A	2	0.0 W	9940....					1	15 A	ERV-2	56			
57														58		
59				SPARE	40 A	2			0.0 W				7180....			3
								0.0 W	8860....							
Total Load:				40992.3 W		37966.3 W		37632.7 W								
Total Amps:				342 A		317 A		314 A								
Legend:																
Load Classification		Connected Load		Demand Factor		Estimated Demand		Panel Totals								
HVAC		78592.0 W		100.00%		78592.0 W										
HEATING		29300.0 W		100.00%		29300.0 W						Total Conn. Load: 116591.2 W				
RECEPTACLE		2880.0 W		100.00%		2880.0 W						Total Est. Demand: 116591.2 W				
ELECTRIC WATER HEATING		5408.0 W		100.00%		5408.0 W						Total Conn.: 324 A				
LIGHTING		411.2 W		100.00%		411.2 W						Total Est. Demand: 324 A				
Notes:																

Branch Panel: P2														
Location: BASEMENT				Volts: 120/208 Wye				A.I.C. Rating: 22 kAIC						
Supply From: MDP				Phases: 3				Mains Type: MLO						
Mounting: SURFACE				Wires: 4				Mains Rating: 225 A						
Enclosure: NEMA 1														
Notes:														
CK T	Circuit Description	Trip	Poles	A		B		C		Poles	Trip	Circuit Description	CK T	
1	BREAK ROOM SINK RECEPTACLE	20 A	1	180.0...	900.0 W					1	20 A	FRONT OFFICE RECEPTACLES	2	
3	ADMIN OFFICE RECEPTACLES	20 A	1			900.0...	180.0...			1	20 A	FRONT OFFICE COPIER	4	
5	BREAK ROOM COPIER	20 A	1					180.0 W	180.0...	1	20 A	BREAK ROOM REFRIGERATOR	6	
7	EXTERIOR SERVICE RECEPTACLE	20 A	1	180.0...	180.0 W					1	20 A	ADMIN OFFICE REFRIGERATOR	8	
9	KICK HEATER	15 A	1			100.0...	0.0 W			1	20 A	SPARE	10	
11	EDC RM 122	20 A	2					1500....	1500....	2	20 A	EDC RM 121	12	
13														14
15														16
17	EDC RM 123	20 A	2			1500....	1500....			2	20 A	EDC RM 188	18	
19	EDC RM 109	20 A	2	1500....	1500....			1500....	1500....	2	20 A	EDC RM 108	20	
21						1500....	1500....						22	
23														24
25	EDC GYMNASIUM	30 A	2	2500....	0.0 W			2500....	0.0 W	1	20 A	SPARE	26	
27	SPARE	20 A	1			0.0 W	0.0 W			1	20 A	SPARE	28	
29	SPARE	20 A	1					0.0 W	0.0 W	1	20 A	SPARE	30	
31	SPARE	20 A	1	0.0 W	0.0 W					1	20 A	SPARE	32	
33	SPARE	20 A	1			0.0 W	0.0 W			1	20 A	SPARE	34	
35	SPARE	20 A	1					0.0 W	0.0 W	1	20 A	SPARE	36	
37	SPARE	20 A	1	0.0 W	0.0 W					1	20 A	SPARE	38	
39	SPARE	20 A	1			0.0 W	0.0 W			1	20 A	SPARE	40	
41	SPARE	20 A	1					0.0 W	0.0 W	1	20 A	SPARE	42	
Total Load:				9940.0 W		7180.0 W		8860.0 W						
Total Amps:				85 A		60 A		76 A						
Legend:														
Load Classification		Connected Load		Demand Factor		Estimated Demand		Panel Totals						
HEATING		23100.0 W		100.00%		23100.0 W								
RECEPTACLE		2880.0 W		100.00%		2880.0 W								
Notes:														

REV	1	DATE	DESCRIPTION	BY	CHK
DRAWING ISSUE STATUS					
ISSUED FOR BID					
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>HALEY WARD</div><div>One Merchants Plaza, Suite 701 Bangor, Maine 04401 207.989.4824</div></div></div><div><div>WWW.HALEYWARD.COM</div></div></div>					
PROJECT					
CONNOR SCHOOL RENOVATIONS					
CONNOR, MAINE					
TITLE					
ELECTRICAL SCHEDULES					
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>JARED MERRY</div><div>No. 11679</div><div>LICENSED PROFESSIONAL ENGINEER</div></div></div>		DATE	2025.04.22	SCALE	
		DRAWN BY	TJA	DESIGNED BY	TJA
		CHECKED BY	JMM	PROJECT No.	10377.028
		DRAWING NO.	E-601		