
# WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE







ISSUED FOR BID, REV.1 09-02-25
PRELIMINARY NOT FOR CONSTRUCTION



		WOODLAND - INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE		
OFDIFO	OLIFET NUMBER	DRAWING LIST	DATE	DDAMING GTATUG
SERIES  100 - GENERAL INFORMATION	SHEET NUMBER	DRAWING NAME	DATE	DRAWING STATUS
100 - GENERAL INFORMATION	100-00	DRAWING LIST	00/02/2025	ISSUED FOR BID, REV. 1
	100-01	GENERAL NOTES	09/02/2025 09/02/2025	ISSUED FOR BID, REV. 1
	100-01	GENERAL NOTES		ISSUED FOR BID, REV. 1
	100-02	GENERAL NOTES	09/02/2025	IOOOLD I OIK DID, IKE V. I
200 - EXISTING CONDITIONS				
	200-01	ORIGINAL (PRE 2022) CONDITIONS - PLAN AND SECTION	09/02/2025	ISSUED FOR BID, REV. 1
	200-02	EXISTING CONDITIONS - PLAN AND SECTION	09/02/2025	ISSUED FOR BID, REV. 1
	200-03	EXISTING CONDITIONS - SHEET WITH PHOTOS	09/02/2025	ISSUED FOR BID, REV. 1
	200-04	EXISTING CONDITIONS - DEMOLITION	09/02/2025	ISSUED FOR BID, REV. 1
			00/02/2020	
300 - NEW CONDITIONS				
	300-01	NEW INTAKE - PLAN AND SECTION	09/02/2025	ISSUED FOR BID, REV. 1
	300-02	NEW INTAKE - FRAMING SECTION BENT 0	09/02/2025	ISSUED FOR BID, REV. 1
	300-03	NEW INTAKE - FRAMING SECTION BENT 1 - 6	09/02/2025	ISSUED FOR BID, REV. 1
	300-04	NEW INTAKE - FRAMING SECTION BENT 7 CLOSURE WALL	09/02/2025	ISSUED FOR BID, REV. 1
	300-05	NEW INTAKE - FRAMING SECTION BENT 7 CLOSURE WALL DETAILS	09/02/2025	ISSUED FOR BID, REV. 1
	300-06	NEW INTAKE - FRAMING SECTION BENT 8 - 11, 12, 13 - 14, AND 15 - 21	09/02/2025	ISSUED FOR BID, REV. 1
	300-07	NEW INTAKE - FRAMING SECTION BENT 22	09/02/2025	ISSUED FOR BID, REV. 1
	300-08	NEW INTAKE - FRAMING SECTION BENT 23	09/02/2025	ISSUED FOR BID, REV. 1
	300-09	NEW INTAKE - CONCRETE SILL	09/02/2025	ISSUED FOR BID, REV. 1
	300-10	NEW INTAKE - STOPLOGS	09/02/2025	ISSUED FOR BID, REV. 1
400 - TRASHRACK AND RAKE	R SUPPORT			
	400-01	TRASH RAKER SUPPORT - PLAN VIEW	09/02/2025	ISSUED FOR BID, REV. 1
	400-02	TRASH RAKER SUPPORT SECTION AT TYPICAL BENT, CLOSURE WALL AND GATE OPERATOR	09/02/2025	ISSUED FOR BID, REV. 1
	400-03	TRASH RAKER SUPPORT - SPLICE CONNECTION AND OTHER DETAILS	09/02/2025	ISSUED FOR BID, REV. 1
500 - BYPASS ENTRANCE				
	500-01	TRASH RACKS - OVERVIEW	09/02/2025	ISSUED FOR BID, REV. 1
	500-02	TRASH RACKS - SUPPORT FRAME TYP. 10.5 FT / 9 FT BAY	09/02/2025	ISSUED FOR BID, REV. 1
	500-03	TRASH RACKS - RACK PANELS TYP. 10.5 FT / 9 FT BAY	09/02/2025	ISSUED FOR BID, REV. 1
	500-04	TRASH RACKS - BYPASS ENTRANCE	09/02/2025	ISSUED FOR BID, REV. 1
	500-05	TRASH RACKS - SUPPORT FRAME AT BYPASS ENTRANCE #1 / #2	09/02/2025	ISSUED FOR BID, REV. 1
	500-06	TRASH RACKS - BYPASS ENTRANCE REMOVABLE SECTION	09/02/2025	ISSUED FOR BID, REV. 1
	500-07	TRASH RACKS - RACK PANELS AT BYPASS ENTRANCE #1 / #2	09/02/2025	ISSUED FOR BID, REV. 1
600 - CONCRETE				
	600-01	CONCRETE DECK TOPPING - PLAN	09/02/2025	ISSUED FOR BID, REV. 1
	600-02	CONCRETE DECK TOPPING - SECTIONS	09/02/2025	ISSUED FOR BID, REV. 1
	600-03	CONCRETE DECK TOPPING - SECTIONS	09/02/2025	ISSUED FOR BID, REV. 1
700 - ELECTRICAL				
	700-01	ELECTRICAL - SINGLE LINE DIAGRAM	09/02/2025	ISSUED FOR BID, REV. 1
	700-02	ELECTRICAL - PLAN	09/02/2025	ISSUED FOR BID, REV. 1
710 - CONTROLS				
	710-01	SCHEMATIC - EEL ENTRANCE BACK-FLUSH CONTROL	09/02/2025	ISSUED FOR BID, REV. 1
	710-02	CABINET LAYOUT - EEL ENTRANCE BACK-FLUSH CONTROL PANEL	09/02/2025	ISSUED FOR BID, REV. 1

# NOT FOR CONSTRUCTION

MAINE DEPARTMENT OF MARINE RESOURCES

WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE

DRAWING LIST

С	ISSUED FOR BID, REV. 1	09-02-25	JFB	AJC	DICAVIIV		
В	ISSUED FOR BID	07-07-25	JFB	AJC	<i>V</i> //_:		
Α	ISSUED FOR VERDANTAS REVIEW	06-13-25	JFB	AJC	<i>Kleinschmid</i>		niat
No.	Revision	Date	Drawn	Checked			
THIS DOCUMENT IS A DRAFT VERSION PROVIDED FOR THE CONVENIENCE OF THE USER AND IS NOT AN INSTRUMENT OF SERVICE OF KLEINSCHMIDT GROUP UNLESS IT BEARS THE PROFESSIONAL ENGINEER'S STAMP AND ORIGINAL SIGNATURE. THIS DOCUMENT IS NOT A PRODUCT, AND TRANSFER OF A VERSION OF AN INSTRUMENT OF SERVICE BY ELECTRONIC MEDIA IS NOT DEEMED A SALE. THIS DOCUMENT MAY NOT BE ALTERED BY OTHERS OR USED FOR PROJECTS OR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE EXPRESS WRITTEN PERMISSION OF KLEINSCHMIDT GROUP.		Designed AJC	Drawn <b>JFB</b>	Checked DBN	Project No. <b>010252</b>	Date Revised 09-02-25	Drawing No.

888-224-5942
KleinschmidtGroup.com

100-00

# **GENERAL NOTES**

- ALL ELEVATIONS ARE SHOWN IN BOTH NAVD88 AND MILL DATUM. MOST OF THE ELEVATIONS ARE BASED ON HISTORICAL DRAWINGS IN MILL DATUM AND HAVE BEEN CONVERTED TO NAVD88 TO MATCH THE VERDANTAS FISH PASSAGE DRAWINGS AN APPROXIMATE CONVERSION OF 3.8 FT WAS USED (NAVD88 = MILL DATUM + 3.8 FEET), HOWEVER, NO BENCHMARK WAS FOUND TO CONFIRM THIS CONVERSION.
- 2. THESE ARE STANDARD NOTES APPLYING TO ALL WORK. SPECIFIC NOTES SHOWN ON OTHER DRAWINGS WILL TAKE PRECEDENCE.
- 3. CONTRACTOR SHALL SCHEDULE WORK IN COOPERATION WITH WOODLAND PULP.
- 4. DETERMINE LOCATIONS, EXISTING CONDITIONS AND DIMENSIONS BY VISITING THE SITE. VERIFY ALL DIMENSIONS IN THE FIELD BEFORE ORDERING OR FABRICATING MATERIAL AND BEGINNING CONSTRUCTION. ALL DISCREPANCIES SHALL BE REPORTED TO THE ENGINEER IN WRITING.
- INFORMATION SHOWN ON THESE DRAWINGS IS BASED ON LIMITED INFORMATION. VERIFY ALL DIMENSIONS AND NOTIFY THE OWNER AND ENGINEER OF DISCREPANCIES.
- WHERE DIMENSIONS ARE NOT SHOWN. CONTACT THE ENGINEER.
- CONTRACTOR SHALL DISCUSS LAYDOWN AND STAGING AREAS WITH WOODLAND PULP PRIOR TO START OF CONSTRUCTION AND BE RESPONSIBLE FOR THE DESIGN AND PLACEMENT OF THEIR EQUIPMENT OVER EXISTING INFRASTRUCTURE.
- 8. PROTECT ALL EXISTING SITE FEATURES FROM DAMAGE DURING CONSTRUCTION ACTIVITIES.
- 9. CONTRACTOR SHALL LEAVE SITE IN AS IS OR BETTER CONDITION UPON PROJECT COMPLETION. CONTRACTOR IS RESPONSIBLE FOR REPAIRS TO DAMAGED AREAS CAUSED BY CONSTRUCTION ACTIVITIES.
- 10. ALL MATERIALS STORED ON SITE SHALL BE IN A NEAR, ORDERLY MANNER IN THEIR APPROPRIATE CONTAINERS AND ALLOCATED STORAGE AREAS.
- CONTRACTOR SHALL CLEAN ANY SPILLS OR DEBRIS CAUSED BY CONSTRUCTION.
- 12. NO CONSTRUCTION OR FABRICATION SHALL BEGIN UNTIL THE CONTRACTOR THOROUGHLY REVIEWS AND UNDERSTANDS ALL PLANS AND OTHER DOCUMENTS BY ALL PERMITTING AUTHORITIES. ANY SOLID WASTE FROM THE SITE SHALL BE DISPOSED OF BY CONTRACTOR IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.
- 13. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE SOLELY REPSONSIBLE FOR THE MEANS, METHODS, TECHNIQUES AND PROCEDURES OF CONSTRUCTION INCLUDING BUT NOT LIMITED TO BRACING OF THE WORK AS REQUIRED TO PROTECT THE WORK UNTIL THE PROJECT IS COMPLETE.
- 14. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INITIATING, MAINTAINING, AND SUPERVISING ALL SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK.
- 15. THE CONTRACTOR IS RESPONSIBLE FOR SCHEDULING AND PROTECTING WORK FROM RISING WATERS IN COORDINATION WITH WOODLAND PULP. DAMAGE TO PARTIALLY COMPLETED WORK, MATERIALS, OR EQUIPMENT SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- 16. THE STRUCTURES HAVE BEEN DESIGNED TO BE SELF SUPPORTING IN THE FINAL CONDITIONS AS SHOWN IN THE CONTRACT DOCUMENTS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE CONSTRUCTION PROCEDURES AND SEQUENCES TO ENSURE STABILITY AND SAFETY DURING ALL ASPECTS OF CONSTRUCTION. THIS INCLUDES BUT NOT LIMITED TO EXCAVATION, DEMOLITION, AND ERECTION AND MAY INVOLVE THE ADDITION OF SHEETING, SHORING, TEMPORARY BRACING, GUYS, TIE DOWNS, ETC. STABILIZING STRUCTURES DURING CONSTRUCTION, BUT NOT REQUIRED IN THE FINAL CONDITIONS AND SHALL BE PROVIDED AT NO ADDITIONAL COST TO MAINE DMR.

## SUBMITTALS

- SHOP DRAWINGS THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR FABRICATION AND ERECTION OF ALL STRUCTURAL STEEL AND MISCELLANEOUS METAL FABRICATIONS INCLUDING CONCRETE REINFORCEMENT. SUBMIT ONE ELECTRONIC COPY OF SHOP DRAWINGS TO THE ENGINEER FOR REVIEW AND APPROVAL. SHOP DRAWINGS SHALL INCLUDE:
- A. PLANS, ELEVATIONS, SECTIONS, AND DETAILS OF ALL MEMBERS AND CONNECTIONS.
- B. INDICATION OF SIZES, SPACING, LOCATIONS OF STRUCTURAL MEMBERS, OPENINGS, ATTACHMENTS, AND FASTENERS.
- C. INDICATION OF WELDED CONNECTIONS WITH AWS A2.0 WELDING SYMBOLS. INDICATE NET WELD LENGTHS.
- D. DETAILS OF ANCHORAGE AND ACCESSORY ITEMS.
- E. TEMPLATES FOR ANCHOR AND BOLT INSTALLATION BY OTHERS.
- F. BAR SCHEDULES, SPACING, ARRANGEMENT, PLACEMENT, AND BENDING OF CONCRETE REINFORCEMENT.
- PRODUCT DATA THE CONTRACTOR SHALL SUBMIT DATA FOR PROPRIETARY MATERIALS AND ITEMS INCLUDING: MECHANICAL EQUIPMENT, ELECTRICAL EQUIPMENT, ELECTRICAL FIXTURES, INSTALLATION INSTRUCTIONS FOR PRODUCTS USED IN STRUCTURAL STEEL AND MISCELLANEOUS METAL FABRICATIONS, ANCHOR DETAILS, COATING PRODUCTS, GROUT, FORMING ACCESSORIES, ADMIXTURES, PATCHING COMPOUNDS, JOINT SYSTEMS, CURING COMPOUNDS, AND OTHERS IF REQUESTED BY THE ENGINEER. INCLUDE MANUFACTURER SPECIFICATIONS AND CERTIFICATIONS AS MAY BE REQUIRED TO SHOW COMPLIANCE WITH DESIGN DRAWINGS.
- EQUIPMENT LOADS AND LIFT PLANS PROVIDE DETAILED WORK PLANS AND LIFT PLANS IF EQUIPMENT OR MATERIAL WILL BE PLACED OR STORED ON THE INTAKE DECK. INCLUDE THE WEIGHT OF MATERIALS AND MEANS OF SUPPORT. FOR CRANE LOADING SHOW THE LOCATION OF OUTRIGGERS AND MAXIMUM REACTION AT EACH OUTRIGGER.
- RECORD DRAWINGS: THE CONTRACTOR SHALL MAINTAIN A SET OF DESIGN DRAWINGS ON SITE THAT IS MARKED UP THROUGHOUT THE CONSTRUCTION PROCESS TO IDENTIFY ANY AREAS WHERE ACTUAL CONSTRUCTION DEVIATED FROM WHAT IS SHOWN ON THE DESIGN DRAWINGS. THIS "RED-LINED" DRAWING SET WILL SERVE AS THE RECORD OF CONSTRUCTION AND WILL BE PROVIDED TO ENGINEER AT THE COMPLETION OF THE PROJECT TO BE USED BY THE ENGINEER IN PREPARATION OF THE RECORD DRAWINGS.

# STEEL NOTES

- 1. STRUCTURAL STEEL DESIGN STANDARD AISC SPECIFICATION FOR DESIGN AND ERECTION OF STRUCTURAL STEEL, 16TH **EDITION**
- A. FABRICATOR SHALL DESIGN NEW STEEL TO NEW STEEL CONNECTIONS FOR BEAMS USING AISC STANDARD FRAMED BEAM CONNECTIONS IF NOT SHOWN ON THE DRAWINGS. CONTACT ENGINEER FOR LOADS ON CONNECTIONS NOT DETAILED.
- B. CONNECTIONS SHALL BE SHOP WELDED AND FIELD BOLTED UNLESS NOTED OTHERWISE (U.N.O.).
- C. BOLTED CONNECTIONS SHALL HAVE A MINIMUM OF 2 BOLTS, MINIMUM BOLT SIZE 3/4" DIA. U.N.O.
- D. ALL BOLTED CONNECTIONS SHALL USE STANDARD HOLE, U.N.O.

- 2. MATERIAL PROPERTIES:
- A. STEEL BARS, PLATES, ANGLES, CHANNELS AND OTHER SHAPES UNLESS NOTES OTHERWISE ASTM A36.
- B. STRUCTURAL STEEL SHAPES, W-SHAPES ASTM A992
- C. BOLTS, ASTM F3125, GRADE A325 GALV.
- D. PIPING A53 GR. B.
- E. WELD AWS D1.1 WITH E70 ELECTRODES. NOTIFY THE ENGINEER IF BASE METALS ARE NOT COMPATIBLE.

# 

I. BETWEEN RAKER RAILS: 19-W-4 GALV. SERRATED BAR GRATING WITH 2" X 3/16" BEARING BARS. II. OTHER: 19-W-4 GALV. SERRATED BAR GRATING WITH 1 1/2" X 3/16" BEARING BARS MINIMUM.

GROUT - NON-SHRINK TYPE PRE-MIXED COMPOUND CONSISTING OF NON-METALLIC AGGREGATE, CEMENT, WATER REDUCING AND PLASTICIZING ADDITIVES, CAPABLE OF DEVELOPING A MINIMUM COMPRESSIVE STRENGTH OF 6,000 PSI AT 28 DAYS. FOR AREAS UNDERWATER USE SUBEC HYDRAULIC CEMENT OR APPROVED EQUAL

#### COATINGS:

- A. STRUCTURAL STEEL COATING
  - ALL STRUCTURAL STEEL SHALL BE SHIPPED UNCOATED.
- II. ALL STRUCTURAL STEEL ABOVE WATER SHALL BE FIELD COATED.
- III. FIELD COATING:
  - a. SURFACE PREPARATION SSPC-SP 3 POWER TOOL CLEANING
  - b. COATING: POLYSET WB HRZS SINGLE COAT SYSTEM, 6 8 MILS DFT c. COATINGS SHALL BE APPLIED PER MANUFACTURER INSTRUCTIONS.
- B. ALL TRASHRACK BAR PANELS ARE UNPAINTED.
- C. ALL BOLTS AND HARDWARE SHALL BE HOT DIPPED GALVANIZED PER ASTM A153.
- 4. CONCRETE ANCHORS:
  - A. CONCRETE ANCHOR: ADHESIVE ANCHOR BOLTS HILTI HAS-V-36 HDG (ASTM F1554 GR 36 ANCHORS), U.N.O. ANCHORS SHALL BE INSTALLED WITH HIT-RE 500 V3 INJECTABLE MORTAR, U.N.O. ANCHORS SHALL BE INSTALLED PER MANUFACTURER'S INSTRUCTIONS TO DEPTHS SHOWN.
  - B. IF EXISTING REINFORCEMENT IS ENCOUNTERED, STOP DRILLING TO PREVENT DAMAGE TO REBAR. CONTACT ENGINEER FOR GUIDANCE ON WHERE TO MOVE ANCHOR BOLT.
  - C. SEE CONCRETE INSPECTION NOTES ON 100-02. THIS INSPECTION WORK SHALL BE PERFORMED PRIOR TO INSTALLING ANY CONCRETE ANCHORS.

## HYDRAULIC INFORMATION

- 1. HEADWATER / NORMAL POND: EL. 144.6' (NAVD88) EL. 140.8' (MILL DATUM)
- 2. HIGH POND: EL. 145.4' (NAVD88)

EL. 141.6' (MILL DATUM)

3. STATION HYDRAULIC CAPACITY: 3000 CFS

# DESIGN CRITERIA FOR TRASHRACKS

- 1. SILL OF EXISTING INTAKE: EL. 122.55' (NAVD88) EL. 118.75' (MILL DATUM)
- 2. BOTTOM OF NEW RACKS: EL. 124.1' (NAVD88) EL. 120.3' (MILL DATUM)
- 3. TOP OF RACKS: EL. 146.3' (NAVD88)
  - EL. 142.5' (MILL DATUM)
- 4. DESIGNED FOR FULL BLINDING AT HIGH POND: EL. 145.4' (NAVD88) EL. 141.6' (MILL DATUM).
- 5. ICE LOAD 2 KIPS PER FT. AT NORMAL POND.
- 6. BARS 3/8" x 3" MIN. (BAR DEPTH VARIES, SEE 500-03 AND 500-06) WITH 3/4" CLEAR SPACING WITH SPACERS AT 36" OC.
- 7. MATERIAL PROPERTIES: MIN. ASTM A36 STEEL, TRASHRACK PANELS ARE UNPAINTED.

# DESIGN CRITERIA FOR INTAKE & DECK

- 1. DEAD LOADS:
  - A. CONCRETE UNIT WEIGHT = 150 PCF
- B. STEEL UNIT WEIGHT = 490 PCF
- C. WATER UNIT WEIGHT = 62.4 PCF
- D. TRASH RAKER WEIGHT = 16 TONS (32,000 LB) +/-

# 2. LIVE LOADS

- A. TRASH RAKE VERTICAL LOADS (ASSUMED FROM KUENZ, MAY CHANGE BASED ON RAKER SELECTION)
- MAX CRANE RAIL LOAD (PER WHEEL) = 110 KN = 25 KIP
- II. MIN CRANE RAIL LOAD (PER WHEEL) = -50 KN = -11.5 KIP (TENSION)
- B. TRASH RAKE HORIZONTAL LOAD
- 10% OF VERTICAL LOADS ASSUMED IN BOTH TRANSVERSE AND LONGITUDINAL DIRECTIONS.
- C. CONCRETE DECK LIVE LOAD = 250 PSF
- SEE 300-01 AND 600-01 FOR CRITERIA REGARDING ALLOWABLE CRANE LOADING ON THE NEW SLAB AND PREVIOUSLY INSTALLED SLAB.

- D. STEEL DECK (BETWEEN RAKER RAILS) = 100 PSF
- 6. HYDROSTATIC
  - A. INTAKE BENTS: MAX OPERATING POND LEVEL EL 141.6 FT WITH FULL BLINDING
- 4. SNOW LOAD = LIVE LOADING WILL CONTROL BY INSPECTION
- 5. SEISMIC LOAD (EQ) = TO BE DETERMINED IN CONSULTATION WITH RAKE VENDOR
- 6. WIND LOAD = TO BE DETERMINED IN CONSULTATION WITH RAKE VENDOR.
- 7. ICE LOAD = 2 KLF APPLIED TO TRASHRACK BARS AND HORIZONTAL SUPPORTS AT WATER LEVEL
- 8. DESIGNED FOR TEMPERATURE VARIATION OF +/- 70 DEG F FROM INSTALLATION TEMPERATURE.

TRASH RAKER NOTES

T MAX = 110 DEG F

T MIN = -30 DEG F

ASSUMING STRUCTURE IS INSTALLED AT 40 DEG F 

DEPENDING ON THE FINAL GEOMETRY OF THE MACHINE.

## THE DESIGN OF THE INTAKE FRAMING AND PROPOSED RAIL SUPPORTS HAS BEEN BASED ON CONCEPTUAL DESIGNS OF MUHR'S HYDRAULIC TRASH RACK CLEANING MACHINE - HYDRONIC M-2000 K. SOME FRAMING MAY NEED TO BE ADJUSTED

- 2. AS PART OF CONFIRMATION OF EXISTING CONDITIONS, THE CONTRACTOR SHALL PERFORM A SURVEY OF THE INTAKE TO CONFIRM THE ALIGNMENT AND CLEARANCES OF A NEW RAKER MACHINE RELATIVE TO EXISTING EQUIPMENT.
- CONTRACTOR TO COORDINATE WITH RAKE VENDOR FOR ALIGNMENT TOLERANCES.
- CONTRACTOR TO PROVIDE AND INSTALL THE RAILS AND RAIL SUPPORT STRUCTURE, INCLUDING ALL BRACKETS, PRIOR TO DELIVERY OF RAKER MACHINE. REFER TO CMAA TABLE 1.4.2-1 FOR RAIL ALIGNMENT CRITERIA. RAIL SUPPORTS HAVE BEEN INCLUDED IN THESE DESIGN DRAWINGS BASED ON THE ASSUMED LOADS LISTED IN THE INTAKE DESIGN CRITERIA.
- 5. CONTRACTOR TO PREPARE THE REQUIRED ELECTRICAL POWER CONNECTION PRIOR TO DELIVERY OF THE RAKER MACHINE.
- A. POWER SUPPLY: 480V, 3 PHASE, 60 HZ, 10.8 KW MAXIMUM DEMAND
- 6. REQUIRED RAKE LIFTING CAPACITY: 4 KIPS
- 7. TRAVEL SPEED: 1-5 METERS/MINUTE
- LOWERING SPEED OF RAKE: 0-10 METERS/MINUTE
- 9. LIFTING SPEED OF RAKE: 0-5 METERS/MINUTE
- 10. WIDTH OF GRAB RAKE: 2 METERS
- 11. ANGLE OF ROTATION: 270°

ISSUED FOR BID, REV.

ISSUED FOR BID

ISSUED FOR VERDANTAS REVIEW

- 12. SERVICES INCLUDED WITH THE PURCHASE OF THE MACHINE TO INCLUDE DELIVERY TO WOODLAND FACILITY, INSTALLATION SUPERVISION, TESTING, COMMISSIONING, AND TRAINING OF OPERATION AND MAINTENANCE PERSONNEL.
- A. PROVIDED MACHINE INSTALLATION SUPERVISION TIME: 9 DAYS
- PROVIDED MACHINE COMMISSIONING TIME: 2 DAYS
- C. PROVIDED MACHINE O&M PERSONNEL TRAINING TIME: 1 DAY.
- D. ANY ADDITIONAL DAYS BEYOND WHAT IS MENTIONED ABOVE IS SUBJECT TO ADDITIONAL COSTS AT CONTRACTORS EXPENSE.
- 13. MUHR TO PROVIDE SPRING TENSIONED CABLE REEL SYSTEM FOR BOTH POWER AND COMMUNICATION CABLES BETWEEN THE STATIONARY CONTROL CABINET AND THE RAKER MACHINE. ALL CABLING BETWEEN THE STATIONARY CONTROL CABINET AND THE RAKER MACHINE TO BE PROVIDED BY MUHR. POWER TO THE STATIONARY CONTROL CABINET FROM THE FACILITY TO BE PROVIDED BY CONTRACTOR.
- 14. MUHR TO EVALUATE AND PROVIDE ALL OVERTURNING AND STRUCTURAL LOADS UNDER ALL CONDITIONS, INCLUDING MAXIMUM WIND, SNOW, AND SEISMIC LOADS, IN ACCORDANCE WITH ASCE 7 REQUIREMENTS. APPROPRIATE FACTORS OF SAFETY SHALL BE APPLIED TO PREVENT OVERTURNING.
- 15. MUHR TO PROVIDE OPERATION AND MAINTENANCE MANUALS FOR THE MACHINE. MANUAL TO INCLUDE A COMPREHENSIVE DESCRIPTION OF MACHINE FUNCTIONS, OPERATION PROCEDURES, SAFETY RESPONSIBILITIES, TROUBLE SHOOTING GUIDELINES, AND MAINTENANCE REQUIREMENTS. MAIN ASSEMBLY DRAWINGS, ELECTRICAL WIRING DIAGRAM, AND HYDRAULIC SCHEMATIC FOR THE MACHINE ARE TO BE INCLUDED, AS WELL AS TECHNICAL BROCHURES FROM SUB-SUPPLIERS FOR KEY COMPONENTS.

16. REFER TO MUHR'S BUDGET PROPOSAL FOR ADDITIONAL DETAILS, EXCLUSIONS, AND INFORMATION.

09-02-25 JFB

07-07-25 JFB

06-13-25 JFB

DOCUMENT IS A DRAFT VERSION PROVIDED FOR THE CONVENIENCE OF THE USER AND IS NOT AN UNEXT OF SERVICE OF KLEINSCHMIDT GROUP UNLESS IT BEARS THE PROFESSIONAL ENGINEER'S STAMP AND VAL SIGNATURE. THIS DOCUMENT IS NOT A PRODUCT, AND TRANSFER OF A VERSION OF AN INSTRUMENT OF CE BY ELECTRONIC MEDIA IS NOT DEEMED A SALE. THIS DOCUMENT MAY NOT BE ALTERED BY OTHERS OR FOR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE CSS WRITTEN PERMISSION OF KLEINSCHMIDT GROUP.

Designed Drawn Checked Project No.

Date Revised Drawn Checked Dra



MAINE DEPARTMENT OF MARINE RESOURCES

WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE

**GENERAL NOTES** 

AJC AJC Date Drawn Checked

888-224-5942 KleinschmidtGroup.com

Designed Drawn Checked Project No. Date Revised Drawing

#### INSPECTION OF EXISTING STRUCTURES

- 1. THE CONDITION OF THE EXISTING CONCRETE NEAR THE WATERLINE IN THE HEADWALL (ABOVE THE HEADGATES) SHOULD BE INSPECTED AND REPAIRED PRIOR TO INSTALLING THE ANCHORAGE FOR THE TRASHRAKER.
- 2. WOODLAND PULP REPORTED SOME POSSIBLE DETERIORATION IN THE DIVIDER WALLS, DOWNSTREAM OF THE HEADWALL, BETWEEN UNIT NO. 4 AND NO. 5 AND UNIT NO. 5 AND NO. 6 THAT SHOULD BE INSPECTED BY THE CONTRACTOR PRIOR TO CONSTRUCTION.

#### DEMOLITION

- 1. SUBMIT A DETAILED DEMOLITION PLAN PRIOR TO STARTING WORK TO DISCUSS WITH WOODLAND PULP AND ENGINEER. DEMOLITION AND DEWATERING NEEDS TO BE SEQUENCED CAREFULLY TO ENSURE ADEQUATE SUPPORT IS AVAILABLE AND TO PREVENT DEBRIS OR OTHER MATERIAL FROM BYPASSING THE EXISTING / NEW TRASHRACKS.
- 2. DO NOT BEGIN DEMOLITION OR DECONSTRUCTION UNTIL AUTHORIZATION IS RECEIVED FROM WOODLAND PULP. WOODLAND PULP ASSUMES NO RESPONSIBILITY FOR ACTUAL CONDITION OF STRUCTURES TO BE DEMOLISHED.
- REMOVE EXISTING STRUCTURES INDICATED TO BE REMOVED TO ELEVATIONS AND LIMITS SHOWN IN THE DRAWINGS.
- 4. CRACKS OR SPALLING THAT PROPAGATE DEEP INTO OR THROUGH STRUCTURES ARE ONE INDICATION OF POTENTIAL STRUCTURAL DISTRESS. REPORT SUCH OBSERVATIONS TO ENGINEER BEFORE PROCEEDING WITH REPAIRS.
- 5. CONSULT WITH WOODLAND PULP AND ENGINEER TO PLAN AREAS OF CONCRETE REMOVAL AND SURFACE PREP AND OBTAIN APPROVAL OF REPAIR METHODS AND EXTENTS BEFORE PROCEEDING.
- DO NOT USE EXPLOSIVES OR CHEMICAL AGENTS FOR DEMOLITION OF STRUCTURES.
- 7. CONDUCT DEMOLITION OPERATIONS AND REMOVAL OF DEBRIS TO ENSURE MINIMUM INTERFERENCE WITH ROADS, WALKS, AND OTHER ADJACENT OCCUPIED OR USED FACILITIES. DO NOT CLOSE OR OBSTRUCT ROADWAYS AND PATHS.
- 8. ENSURE SAFE PASSAGE OF PERSONS AROUND AREA OF DEMOLITION. CONDUCT OPERATIONS TO PREVENT INJURY TO ADJACENT BUILDINGS, STRUCTURES, OTHER FACILITIES, AND PERSONS.
- 9. PREVENT THE SPREAD OF DUST AND DEBRIS AND AVOID THE CREATION OF A NUISANCE OR HAZARD IN THE SURROUNDING AREA. DO NOT USE WATER IF IT RESULTS IN HAZARDOUS OR OBJECTIONABLE CONDITIONS SUCH AS, BUT NOT LIMITED TO, ICE, FLOODING, OR POLLUTION.
- 10. PREVENT MATERIALS FROM ENTERING THE WATERWAY.

#### SURFACE PREPARATION

- 1. PREPARE CONCRETE SURFACE AND DO SELECTIVE DEMOLITION.
- 2. REMOVE DETERIORATED SURFACE MATERIAL IN DESIGNATED AREAS DOWN TO SOUND CONCRETE. SOUND CONCRETE IS DEFINED AS WHEN THE SURFACE IS STRUCK WITH A GEOLOGIST'S HAMMER. THE AGGREGATE OF THE CONCRETE FRACTURES BEFORE THE CEMENT PASTE BOND IS BROKEN.
- 3. PERFORM LOCALIZED REMOVAL WITH POINTED TOOLS THAT LIMIT IMPACT DAMAGE SUCH AS A GEOLOGIST OR LIGHT DUTY CHIP HAMMER.
- 4. AREAS GREATER THAN 6" SQUARE, PRIMARY PREPARATION METHOD SHOULD BE ABRASIVE SHOT-BLASTING. WATER-BLASTING, OR HYDRO-DEMOLITION TO MINIMIZE CONCRETE BRUISING IN ACCORDANCE WITH ACI 364.7T-02 (TECH NOTE). PREVENT MATERIALS FROM ENTERING THE WATERWAY.
- 5. IF REINFORCEMENT STEEL IS ENCOUNTERED, HAMMER CHIP TO EXPOSE CORROSION UNTIL UN-CORRODED REBAR. CLEAN REBAR OF LOOSE AND BOND-INHIBITING MATERIAL WITH HIGH-PRESSURE WATER (3,000 PSI MIN) OR ABRASIVE BLAST.
- 6. PREPARE CONCRETE SURFACE IN ACCORDANCE WITH THE INTERNATIONAL CONCRETE REPAIR INSTITUTE (ICRI) TECHNICAL GUIDELINE NO. 310.2R-2013 BUT NO LESS THAN A MINIMUM OF 1/8" AMPLITUDE. CLEAN SURFACE TO REMOVE ALL DELETERIOUS MATERIAL, INCLUDING DIRT, GREASE, ETC. WASH WITH HIGH PRESSURE WASH (AT LEAST 3,000 PSI PRESSURE).
- 7. DEMO AREAS, INITIAL CONCRETE REMOVAL MAY USE 15-LB OR 30LB JACKHAMMER. USE 15-LB JACKHAMMER FOR DENTAL CONCRETE REMOVAL AROUND REBAR. FINISH REMOVAL IN ACCORDANCE WITH NOTE 3.
- 8. ANY DETERIORATED REINFORCING STEEL ENCOUNTERED THAT IS LESS THAN 50% OF ORIGINAL CROSS-SECTION, REPLACE WITH NEW REINFORCEMENT DOWELED INTO CONCRETE.
- 9. EXISTING AND NEW REINFORCING STEEL SHALL HAVE MINIMUM 1" CLEARANCE (U.N.O.) BETWEEN REBAR AND EXISTING CONCRETE SUBSTRATE, MIN. 1/4" GREATER THAN MAXIMUM AGGREGATE SIZE FOR REPAIR MIX BEING USED.
- 10. CONCRETE SURFACES SHALL BE SATURATED SURFACE DRY IN ACCORDANCE WITH ICRI, AT TIME OF CONCRETE PLACEMENT BUT NO STANDING WATER.

#### CONCRETE

- ALL CONCRETE WORKS SHALL BE IN ACCORDANCE WITH THE LATEST ACI 318.
- 2. CONCRETE MIX

4500 PSI 28-DAY COMPRESSIVE STRENGTH.



- C. W/C RATIO, 0.42 MAXIMUM BY WEIGHT
- D. AIR ENTRAINMENT 5% TO 7%.
- E. SLUMP 3" TO 4" OR 6" TO 8" IF A HIGH-RANGE WATER REDUCER IS ADDED.
- F. THE CONTRACTOR SHALL SUBMIT THE MIX DESIGN TO THE ENGINEER FOR APPROVAL. THIS SUBMITTAL SHALL INCLUDE DOCUMENTATION OF EITHER TEST DATA OR A LETTER CERTIFYING THAT THE AGGREGATE HAS SATISFACTORY PERFORMANCE REGARDING ALKALI REACTIVITY.
- MATERIALS USED IN PRODUCING THE CONCRETE SHALL BE FROM THE SAME SOURCE FOR THE DURATION OF THE PROJECT. CHANGE OF SOURCE FOR CEMENT ADMIXTURE OR FINE AND COARSE AGGREGATE CONSTITUTES A NEW MIX DESIGN AND WILL REQUIRE RESUBMITTAL OF ALL DATA AND LABORATORY TESTS. ANY COSTS ASSOCIATED WITH RESUBMITTALS SHALL BE BORNE BY CONTRACTOR AT NO CHARGE TO MAINE DMR.
- THE TOLERANCES FOR FINISHED CAST-IN-PLACE CONCRETE SHALL CONFORM TO ACI-347.
- 5. COARSE AGGREGATE SHALL BE 3/4" PER ASTM C 33.
- 6. PROHIBITED ADMIXTURES: CALCIUM CHLORIDE THYOCYANATES OR ADMIXTURES CONTAINING MORE THAN 0.1 PERCENT CHLORIDE IONS ARE NOT PERMITTED.
- 7. CONTRACTOR TO PREPARE DESIGN MIXES FOR EACH TYPE AND STRENGTH OF CONCRETE BY EITHER LABORATORY TRIAL BATCH OR FIELD EXPERIENCE METHODS AS SPECIFIED IN ACI 301. IF TRIAL BATCH METHOD USED, USE AN INDEPENDENT TESTING FACILITY ACCEPTABLE TO THE ENGINEER FOR PREPARING AND REPORTING PROPOSED MIX DESIGNS.
- FOR PLACING CONCRETE TO COMPLY WITH ACI 304 "RECOMMENDED PRACTICE FOR MEASURING, MIXING, TRANSPORTING, AND PLACING CONCRETE", AND AS HEREIN SPECIFIED.
- COLD WEATHER PLACING: PROTECT CONCRETE WORK FROM PHYSICAL DAMAGE OR REDUCED STRENGTH WHICH COULD BE CAUSED BY FROST, FREEZING ACTIONS, OR LOW TEMPERATURES, IN COMPLIANCE WITH ACI 306 AND AS HEREIN SPECIFIED.
- 10. HOT WEATHER PLACING: WHEN HOT WEATHER CONDITIONS EXIST THAT WOULD SERIOUSLY IMPAIR QUALITY AND STRENGTH OF CONCRETE, PLACE CONCRETE IN COMPLIANCE WITH ACI 305 AND AS HEREIN SPECIFIED.
- 11. FORM SURFACES SHALL HAVE SMOOTH FINISH, FREE FROM HONEYCOMBING AND OTHER DEFECTS.
- 12. START INITIAL CURING AS SOON AS FREE WATER HAS DISAPPEARED FROM CONCRETE SURFACE AFTER PLACING AND FINISHING. KEEP CONTINUOUSLY MOIST FOR NOT LESS THAN 7 DAYS, OR USE A CURING COMPOUND INSTALLED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS, AND AS APPROVED BY THE ENGINEER.
- 13. REPAIR AND PATCH DEFECTIVE AREAS IN A MANNER ACCEPTABLE TO THE ENGINEER.
- 14. REMOVE AND REPLACE CONCRETE HAVING DEFECTIVE SURFACES IF DEFECTS CANNOT BE REPAIRED TO SATISFACTION OF ENGINEER. SURFACE DEFECTS, AS SUCH, INCLUDE COLOR AND TEXTURE IRREGULARITIES. CRACKS, SPALLS, AIR BUBBLES, HONEYCOMB, ROCK POCKETS; FINS AND OTHER PROJECTIONS ON SURFACE; AND STAINS AND OTHER DISCOLORATIONS THAT CANNOT BE REMOVED BY CLEANING.
- 15. EPOXY INJECT ALL VISIBLE SHRINKAGE CONCRETE CRACKS
- 16. COMPRESSION TEST SPECIMEN: ASTM C 31: ONE SET OF 5 STANDARD CYLINDERS FOR EACH COMPRESSIVE STRENGTH TEST, UNLESS OTHERWISE DIRECTED. MOLD AND STORE CYLINDERS FOR LABORATORY CURED TEST SPECIMENS EXCEPT WHEN FIELD-CURE TEST SPECIMENS ARE REQUIRED.
- 17. COMPRESSIVE STRENGTH TESTS: ASTM C 39; ONE SET FOR EVERY 50 CUBIC YARDS PLACED OR A MINIMUM OF ONE SET FOR EACH DAY; TWO SPECIMEN TESTED AT 7 DAYS, TWO SPECIMENS TESTED AT 28 DAYS, AND ONE SPECIMEN RETAINED IN RESERVE FOR LATER TESTING IF REQUIRED.

# FORMWORK AND CONSTRUCTION JOINTS

- CONSTRUCT FORMS TRUE TO LINE AND GRADE, ADEQUATELY BRACED TO MAINTAIN POSITION DURING PLACEMENT OF CONCRETE. WELDING OF FORM TIES TO STRUCTURAL DOWELS IS NOT PERMITTED, THOUGH ADDITIONAL DOWELS MAY BE INSTALLED FOR THAT PURPOSE.
- 2. PROVIDE 3/4" CHAMFER ON ALL EXPOSED EDGES UNLESS NOTED OTHERWISE.
- 3. REPAIR ALL AIR HOLES AND VOIDS LARGER THAN 1/4" AND FILL ALL TIE HOLES. REMOVE FINS AND PROJECTIONS.
- CONTRACTOR SHALL PROPOSE CONSTRUCTION JOINT LOCATIONS IN FOOTING FOR REVIEW BASED ON PLACEMENT PLAN.
- REINFORCEMENT SHALL BE CONTINUOUS THROUGH JOINT, UNLESS NOTED OTHERWISE AND BE FULLY DEVELOPED ON BOTH SIDES OF CONSTRUCTION JOINTS.
- 6. CLEAN ALL JOINTS OF GREEN CONCRETE WITHIN 30 HOURS TO REMOVE LAITANCE WITH MIN. 5,000 PSI WATER BLAST OR SANDBLASTING PRIOR TO NEXT CONCRETE PLACEMENT. MECHANICAL ROUGHENING IS AN ACCEPTABLE ALTERNATE FOR LAITANCE REMOVAL. ACID CLEANING/REMOVAL OF LAITANCE IS NOT ACCEPTABLE.

- 7. SATURATE JOINT IMMEDIATELY PRECEDING AND 12 HOURS PRIOR TO NEXT CONCRETE PLACEMENT REMOVE ALL STANDING WATER.
- 8. MAXIMUM VERTICAL C.J. SPACING IS 35 FEET (U.N.O.).

#### REINFORCING

- REINFORCING BARS: ASTM A 615, GRADE 60, DEFORMED, SUBMIT SHOP DRAWINGS AS OUTLINED ON 100-01.
- 2. PROVIDE DEFORMED REBAR DOWELS OF SIZE AND DIMENSION SHOWN. GROUTING OF DOWELS SHALL BE DONE EITHER WITH APPROVED CEMENTITIOUS OR PROPRIETARY EPOXY GROUT. CLEAN DRILL HOLES WITH AIR PRESSURE TO REMOVE DUST AND STANDING WATER. HOLES MAY BE DAMP. INSTALL PER MANUFACTURER'S INSTRUCTIONS.
- 3. HOOKS SHALL BE DIMENSIONED AND BENT PER ACI STANDARD HOOKS.
- 4. REBAR COVER SHALL BE 3" UNLESS NOTED OTHERWISE.
- 5. SPLICES AND DEVELOPMENT LENGTHS SHALL BE PER ACI STANDARDS PER THE FOLLOWING TABLE, UNLESS **NOTED OTHERWISE:**

CONCRETE REINFORCEMENT DEVELOPMENT SCHEDULE					
BAR SIZE	BAR DIAMETER (in)	DEVELOPMENT LENGTH (in)	CLASS B* SPLICE (in)		
4	0.500	19	25		
5	0.625	24	31		
6	0.750	28	37		
7	0.875	42	54		
8	1.000	47	62		
9	1.128	54	70		
10	1.270	60	78		
11	1.410	67	87		

#### **ELECTRICAL NOTES**

- ALL ELECTRICAL INSTALLATIONS SHALL COMPLY WITH NFPA 70 (2023), THE NATIONAL ELECTRICAL CODE (NEC).
- 2. ALL EQUIPMENT AND MATERIAL SHALL BE NEW AND SHALL CONFORM TO APPLICABLE CODES AND STANDARDS FOR THAT CLASS OF EQUIPMENT OR MATERIAL.
- 3. WHERE BRANDS, MODELS, OR PART NUMBERS ARE SPECIFIED WITHOUT QUALIFICATION, THERE SHALL BE NO SUBSTITUTIONS EXCEPT WITH WRITTEN APPROVAL OF THE ENGINEER. ALTERNATE MATERIALS MAY BE SUBMITTED WITH THE PROPOSAL AND LISTED AS AN OPTION FOR CONSIDERATION BY THE ENGINEER.
- 4. EQUIPMENT AND MATERIALS SHALL BE UTILITY OR INDUSTRIAL TYPE. COMMERCIAL OR RESIDENTIAL GRADE EQUIPMENT IS NOT ALLOWED.
- CONDUIT FOR GENERAL USE SHALL BE GALVANIZED STEEL RIGID METAL CONDUIT (RMC). COUPLINGS, CLAMPS, ELBOWS, AND OTHER FITTINGS SHALL BE OF GALVANIZED STEEL. CONDUIT PULLING BODIES SHALL BE CAST WITH SOLID GASKET AND COVERS. EMBEDDED OR BURIED CONDUIT SHALL BE SCHEDULE 40 RIGID POLYVINYL CHLORIDE (PVC). LIGHTING AND RECEPTACLE CIRCUITS MAY BE INSTALLED IN ELECTRICAL METALLIC TUBING USING COMPRESSION FITTINGS. SET SCREW FITTINGS ARE NOT ALLOWED. FOR CONNECTION TO MOTORS AND OTHER EQUIPMENT REQUIRING FLEXIBILITY, PROVIDE LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LFMC). MINIMUM CONDUIT SIZE ALLOWED IS 3/4 INCH. WHERE CONDUIT SIZES ARE NOT SHOWN, PROVIDE CONDUITS AS REQUIRED BY THE NEC. EXPOSED CONDUIT AND RACEWAYS SHALL BE RUN PARALLEL AND PERPENDICULAR TO STRUCTURAL MEMBERS AND GROUPED TOGETHER WHERE POSSIBLE. ALL CONDUIT AND WALL-MOUNTED ENCLOSURES SHALL BE MOUNTED ON STRUT.
- 6. ALL CONDUCTORS SHALL BE STRANDED COPPER. SINGLE CONDUCTOR (BUILDING WIRE) INSULATION SHALL BE 600 VOLT, TYPE XHHW-2 OR THWN-2, 90 DEGREE C. MULTI-CONDUCTOR CABLE SHALL CONSIST OF COLOR CODED, FIRE RETARDANT XLP INSULATED, 600 VOLT STRANDED CONDUCTORS IN A FLAME RESISTANT, SUNLIGHT RESISTANT, PVC JACKET. WHERE CONDUCTOR SIZES ARE NOT SHOWN, PROVIDE CABLE AS REQUIRED BY THE NEC. ALL CONDUCTOR SPLICES/TERMINATIONS SHALL BE MADE BY TINNED COPPER COMPRESSION LUGS. NYLON SLEEVED COMPRESSION TYPE RING LUGS SHALL BE USED FOR SCREW TERMINALS EXCEPT CONDUCTORS MAY BE TERMINATED DIRECTLY IN SCREW-COMPRESSION TERMINALS WIRE NUTS ARE NOT PERMITTED, BUT LEVER NUTS MAY BE USED FOR LIGHTING AND RECEPTACLE CIRCUITS.
- 7. ALL WIRES, CABLES, AND CONDUITS SHALL BE PERMANENTLY IDENTIFIED AT TERMINATION AND SPLICE POINTS, AND ALL CONDUITS SHALL BE IDENTIFIED AT ENCLOSURE AND PULL-BOX ENTRIES AS IDENTIFIED ON THE DRAWINGS AND CABLE & CONDUIT SCHEDULE. IDENTIFICATION TAGS SHALL BE TYPED AND PRINTED ON PERMANENT LABELS.
- 8. THE WORK SHALL INCLUDE TESTING OF EQUIPMENT AND WIRING AS RECOMMENDED BY THE MANUFACTURERS AS WELL AS ANY MINOR CONNECTION CHANGES OR ADJUSTMENTS NECESSARY FOR THE PROPER FUNCTIONING OF EQUIPMENT AND SYSTEMS. ALL INSULATED POWER CONDUCTORS SHALL BE INSULATION RESISTANCE TESTED AFTER PULLING IN, WITH THE APPROPRIATE VOLTAGE LEVEL. ALL 3-PHASE MOTORS SHALL BE TESTED FOR CORRECT ROTATION UNDER ENGINEER SUPERVISION. ALL SUCH TESTING SHALL BE DOCUMENTED AND TURNED OVER FOR THE RECORD.

# NOT FOR CONSTRUCTION

MAINE DEPARTMENT OF MARINE RESOURCES

WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE


**GENERAL NOTES** 


ISSUED FOR BID, REV.1 AJC 09-02-25 JFB ISSUED FOR BID 07-07-25 JFB AJC Kleinschmidt ISSUED FOR VERDANTAS REVIEW 06-13-25 JFB Date Drawn Checked

S DOCUMENT IS A DRAFT VERSION PROVIDED FOR THE CONVENIENCE OF THE USER AND IS NOT AN IRLUMENT OF SERVICE OF KLEINSCHMIDT GROUP UNLESS IT BEARS THE PROFESSIONAL ENGINEER'S STAMP AND GIVAL SIGNATURE. THIS DOCUMENT IS NOT A PRODUCT, AND TRANSFER OF A VERSION OF AN INSTRUMENT OF VICE BY ELECTRONIC MEDIA IS NOT DEEMED A SALE. THIS DOCUMENT MAY NOT BE ALTERED BY OTHERS OF DFOR PROJECTS OR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECTS OR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OF THE THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OF THE THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT FOR WHICH IT WAS PROJEC


KleinschmidtGroup.com Designed Drawn Checked Project No. Date Revised Drawing

888-224-5942















ISSUED FOR BID, REV. 1

ISSUED FOR BID

ISSUED FOR VERDANTAS REVIEW



# NOT FOR CONSTRUCTION

MAINE DEPARTMENT OF MARINE RESOURCES


WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE


**EXISTING CONDITIONS** SHEET WITH PHOTOS


Kleinschmidt


888-224-5942 KleinschmidtGroup.com


Designed Drawn Checked Project No. Date Revised Drawing No. Date Revised Drawing No. Date Revised No. Drawing No. No.




































# TYPICAL EXPANSION JOINT CONNECTION DETAIL AT UPSTREAM TRASH RAKER SUPPORT BEAM 1 1/2" = 1'-0"




# TYPICAL CONNECTION DETAIL AT UPSTREAM TRASH RAKER SUPPORT BEAM 1 1/2" = 1'-0"

USE SIMILAR BOLTING AND HOLE

PATTERN IN THE BEAMS FOR EXPANSION

AS SHOWN FOR UPSTREAM CONNECTION



TYPICAL EXPANSION JOINT CONNECTION DETAIL AT DOWNSTREAM TRASH RAKER SUPPORT BEAM

1 1/2" = 1'-0"

STD. HOLES IN 1" MAX. SHIM TO ALLOW BEAMS AND SHIM FOR FIELD LEVELING OF RAIL SUPPORT BEAM W8 OR W12 SUPPORT BEAM DEPENDING ON LOCATION

> TYPICAL CONNECTION DETAIL AT DOWNSTREAM TRASH RAKER SUPPORT BEAM

1 1/2" = 1'-0"

W12 RAIL SUPPORT BEAM -


(MAXIMUM LENGTH 2 BAYS)

1. SUPPORT BEAMS ARE CONTINUOUS FOR UP TO APPROXIMATELY 21 FEET (2 BAYS). 2. MAXIMUM CHANGE IN LENGTH OVER 140DEGF IS 1/4 INCH.

3. CONTRACTOR TO ENSURE THAT BOLTS IN SLOTTED HOLES ARE SNUG-TIGHT AND NOT OVER-TIGHTENED.

6" = 1'-0"

TYPICAL LONG SLOTTED HOLE DETAIL



TYPICAL RAKER RAIL SUPPORT COLUMNS @ BENT 23 1 1/2" = 1'-0"

## ISSUED FOR BID, REV. 09-02-25 JFB ISSUED FOR BID 07-07-25 JFB ISSUED FOR VERDANTAS REVIEW 06-13-25 JFB Date Drawn Checked Designed Drawn Checked Project No. Date Revised Drawing S DOCUMENT IS A DRAFT VERSION PROVIDED FOR THE CONVENIENCE OF THE USER AND IS NOT AN IRRUMENT OF SERVICE OF KLEINSCHMIDT GROUP UNLESS IT BEARS THE PROFESSIONAL ENGINEER'S STAMP AND GIVAL SIGNATURE. THIS DOCUMENT IS NOT A PRODUCT, AND TRANSFER OF A VERSION OF AN INSTRUMENT OF PRIVATE BY ELECTRONIC MEDIA IS NOT DEEMED A SALE. THIS DOCUMENT MAY NOT BE ALTERED BY OTHERS OR DE FOR PROJECTS OR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR FURPOSES OF THE REPORT OF THE PROJECT SOR PURPOSES OF THE THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OF THE THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT SOR PURPOSES OF THE THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE PROJECT FOR WHICH IT WAS PROJECT


NOT FOR CONSTRUCTION


MAINE DEPARTMENT OF MARINE RESOURCES


WOODLAND INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE TRASH RAKER SUPPORT


SECTIONS AND DETAILS


888-224-5942 KleinschmidtGroup.com












































ELECTRICAL ENCLOSURE - DOOR 3" = 1'-0"



**ELECTRICAL ENCLOSURE - SECTION** 3" = 1'-0"

FISH LIFT CONTROL PANEL BILL OF MATERIALS					
ITEM #	QTY	ITEM DESCRIPTION	MANUFACTURER	PART NUMBER	
1	1	PANDUCT TYPE G WIDE SLOT WIRING DUCT, DUCT NOMINAL SIZE (WXH) 2.5"X3", 6 FOOT SECTIONS	PANDUIT	G2.5X3LG6	
2	1	PANDUCT WIDE SLOT WIRING DUCT COVER FOR 2.5" DUCT, 6 FOOT SECTIONS	PANDUIT	C2.5LG6	
3	3	TYPE 4/13 METAL (800T) PILOT LIGHT, UNIVERSAL LED, 12-130V AC/DC, AMBER	ALLEN BRADLEY	800T-QH2A	
4	1	800T CUSTOM LEGEND NAMEPLATE, CUSTOM TEXT LINE 1: FLUSHING; LINE 2: PIPE 1	ALLEN BRADLEY	800T-X559E	
5	1	800T CUSTOM LEGEND NAMEPLATE, CUSTOM TEXT LINE 1: FLUSHING; LINE 2: PIPE 2	ALLEN BRADLEY	800T-X559E	
6	1	800T CUSTOM LEGEND NAMEPLATE, CUSTOM TEXT LINE 1: FLUSHING; LINE 2: PIPE 3	ALLEN BRADLEY	800T-X559E	
7	1	TYPE 4/13 METAL (800T) PUSH BUTTON, MOMENTARY, FLUSH HEAD, GREEN, 1 N.O. — 1 N.C. CONTACTS.	ALLEN BRADLEY	800T-A1A	
8	1	800T STANDARD LEGEND NAMEPLATE, "START"	ALLEN BRADLEY	800T-X547	
9	1	TYPE 4/13 METAL (800T) PUSH BUTTON, MOMENTARY, EXTENDED HEAD, RED, 1 N.O. — 1 N.C. CONTACTS.	ALLEN BRADLEY	800T-B6A	
10	1	800T STANDARD LEGEND NAMEPLATE, "STOP" (RED)	ALLEN BRADLEY	800T-X550	
11	1	ELECTRICAL ENCLOSURE. MILD STEEL, NEMA 3/4/12, HINGED DOOR W/ SLOTTED QUARTER-TURN LATCH, COLLAR STUDS FOR INNER PANEL MOUNTING. ANSI 61 GRAY. 30"x20"x6"	HAMMOND	EN4SD30206GY	
12	1	ELECTRICAL ENCLOSURE INNER PANEL	HAMMOND	EP3020	
13	7	GENERAL PURPOSE RELAY, 8 BLADE, DPDT, 120 VAC COIL, 12 AMP CONTACTS	MACROMATIC	GB120A2	
14	7	GENERAL PURPOSE RELAY SOCKET, 8 BLADE	MACROMATIC	18F-2Z-C5	
15	7	GENERAL PURPOSE RELAY RETAINER, PLASTIC	MACROMATIC	GB-PR	
16	3	RELAY, SINGLE-FUNCTION, SINGLE-RANGE, FUNCTION: ON DELAY, RANGE: 0.3 - 30 MINUTES. DPDT CONTACTS RATED 10 AMPS. 35MM DIN RAIL MOUNTING	MACROMATIC	TE5022U-15	
17	34	TERMINAL BLOCK, SCREW CONNECTION, 4 mm <sup>2</sup> , 35 A, 800 V. 2 CONNECTIONS, 1 LEVEL.	WEIDMÜLLER	WDU 4	
18	5	TERMINAL BLOCK END BRACKET FOR WDU-4	WEIDMÜLLER	WEW 35/2	
19	1	POWER DISTRIBUTION BLOCK, 2-POLE, ONE LINE-SIDE TERMINAL, 12 LOAD SIDE TERMINALS, 310 A, 100 KA SCCR. UL RECOGNIZED	EATON/BUSSMANN	16370-2	
20	1	COVER FOR POWER DISTRIBUTION TERMINAL BLOCK ITEM 32	EATON/BUSSMANN	CPDB-2	
21	4	TERMINAL BLOCK END BRACKET GROUP MARKER 33.3 x 8 mm	WEIDMÜLLER	WAD 8 MC NE WS	
22	1	TERMINAL BLOCK MARKER FOR WDU-4, 5 MM X 6 MM, (6 MM PITCH) PRE-PRINTED 1 - 50, 10 SETS.	WEIDMÜLLER	468660001 DEK 6 FW 1-50	
23		(NOT USED)			
24	7	BRANCH CIRCUIT BREAKER, SINGLE POLE, UL 489, DIN RAIL MOUNT. 13 AMP, 10 KAIC. CURVE C	EATON	FAZ-C13/1-NA-L	
25	1	BUS BAR - ONE-POLE, 12 TERMINLS	EATON	Z-SV/UL-16/1P-1TE/12	
26	2	BUS BAR SHROUD, THREE-POLE	EATON	ZV-BS-UL	
27	1	BRANCH CIRCUIT BREAKER, SINGLE POLE, UL 489, DIN RAIL MOUNT. 30 AMP, 10 KAIC. CURVE C	EATON	FAZ-C30/1-NA-L	
28	2	DIN RAIL, 35 MM X 7.5 MM X 1 M, ZINC COATED STEEL	MCMASTER-CARR	8961K15	
29	1	NAMEPLATE, ENGRAVED LAMINATED PLASTIC, WHITE TEXT ON BLACK FIELD, "EEL PASSAGE PIPE FLUSHING CONTROL". TEXT HEIGHT: 1/2". OVERALL DIMENSIONS AS REQUIRED TO FIT TEXT. FASTEN WITH STAINLESS MACHINE SCREWS	BY DESCRIPTION	BY DESCRIPTION	
30	1	NAMEPLATE, ENGRAVED LAMINATED PLASTIC, WHITE TEXT ON BLACK FIELD, "SHORT CIRCUIT CURRENT RATING: 10 KA, 120 VAC MAXIMUM". TEXT HEIGHT: 3/16". OVERALL DIMENSIONS AS REQUIRED TO FIT TEXT. FASTEN WITH STAINLESS MACHINE SCREWS	BY DESCRIPTION	BY DESCRIPTION	

## BILL OF MATERIAL ITEM NUMBER ##

ISSUED FOR BID, REV. 1

ISSUED FOR BID

ISSUED FOR VERDANTAS REVIEW

# NOT FOR CONSTRUCTION

MAINE DEPARTMENT OF MARINE RESOURCES

WOODLAND

INTAKE DESIGN FOR DOWNSTREAM FISH PASSAGE

CABINET LAYOUT EEL ENTRANCE BACKFLUSH CONTROL PANEL

**Kleinschmidt** 

888-224-5942 KleinschmidtGroup.com

RAFT VERSION PROVIDED FOR THE CONVENIENCE OF THE USER AND IS NOT AN OF KLEINSCHMIDT GROUP UNLESS IT BEARS THE PROFESSIONAL ENGINEER'S STAMP AND DOCUMENT IS NOT A PRODUCT, AND TRANSFER OF A VERSION OF AN INSTRUMENT OF REDIA IS NOT DEEMED A SALE. THIS DOCUMENT MAY NOT BE ALTERED BY OTHERS OR PURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE DURPOSES OTHER THAN THE PROJECT FOR WHICH IT WAS PREPARED, WITHOUT THE OLOR OF KLEINSCHMIDT GROUP.

07-07-25 JFB