Hydraulics/Hydrology/Scour Report


Gardiner, Maine
Bridge Street Bridge (#2101) over Cobbossee Stream WIN 018735.00
Maine Avenue Bridge (#3098) over Cobbossee Stream WIN 018736.00
Multi-use Bridge over Cobbossee Stream WIN 018736.10

Stantec

Prepared for:
MaineDOT

Prepared by:
Thomas Densford, P.E.

Reviewed by:
Tim Merritt, P.E.
Gerard Fortin, P.E.



June 6, 2018

Table of Contents

1.0 LOCATION AND PURPOSE 1.1

2.0 BRIDGE DESCRIPTIONS & FLOOD HISTORY 2.2
2.1 BRIDGE STREET BRIDGE 2.2
2.2 MAINE AVENUE BRIDGE AND MULTI-USE BRIDGE 2.2
2.3 FLOOD HISTORY 2.3

3.0 HYDRAULIC MODELING 3.4

4.0 RESULTS AND DISCUSSION 4.5

5.0 FEMA SUMMARY 5.6

LIST OF TABLES

Table 1: FEMA Cobbossee Stream Flow Data
Table 2: MaineDOT Cobbossee Stream Flow Data
Table 3: FEMA Cobbossee Stream Floodway Data
Table 4: FEMA Cobbossee Stream Flow Summary
Table 5: Scour Depth, ft
Table 6: Cobbossee Stream 100-year Flow Data

LIST OF FIGURES

Figure 1: Detail from FEMA FIRM
Figure 2: Cross Section Locations for HEC-RAS Model
Figure 3: FEMA Regulatory Floodway
Figure 4A: Proposed Bridge Street Grading
Figure 4B: Proposed Plan at Bridge Street
Figure 5: Proposed Profile at Bridge Street
Figure 6A: Proposed Maine Avenue Grading
Figure 6B: Proposed Plan at Maine Avenue
Figure 6C: Proposed Profile at Maine Avenue
Figure 7: Proposed Plan and Profile at Multi-use Bridge
Figure 8: FEMA Cobbossee Stream Profile
Figure 9: FEMA Regulatory Floodway Section
Figure 10: Cobbossee Stream Profile
Figure 11: Cobbossee Stream Profile – Existing Conditions
Figure 12: Bridge Street Bridge Elevation – Existing Conditions
Figure 13: Maine Avenue Bridge Elevation – Existing Conditions
Figure 14: Cobbossee Stream Profile – Proposed Conditions
Figure 15: Bridge Street Bridge Elevation – Proposed Conditions
Figure 16: Maine Avenue Bridge Elevation – Proposed Conditions
Figure 17: Trail Bridge Elevation – Proposed Conditions


APPENDIX

APPENDIX A: TIDAL DATA
APPENDIX B: SCOUR CALCULATIONS
APPENDIX C: BANK PROTECTION REVETMENT CALCULATIONS
APPENDIX D: HEC-RAS RESULTS FOR EXISTING CONDITIONS AT MLW
APPENDIX E: HEC-RAS RESULTS FOR EXISTING CONDITIONS AT MHW
APPENDIX F: HEC-RAS RESULTS FOR PROPOSED CONDITIONS AT MLW
APPENDIX G: HEC-RAS RESULTS FOR PROPOSED CONDITIONS AT MHW
APPENDIX H: HEC-RAS ELECTRONIC FILES

1.0 LOCATION AND PURPOSE

This report discusses two existing roadway bridge crossings, and a proposed new multi-use bridge crossing, of the Cobbosseecontee (Cobbossee) Stream, in Gardiner, Maine. The Cobbossee Stream is tributary to the Kennebec River, which lies immediately downstream of the project area.

The two existing roadway bridges are located at Bridge Street and Maine Avenue, and are scheduled for replacement. The proposed multi-use bridge is just upstream of the Maine Avenue Bridge. This report shows the study of the existing hydraulic conditions and compares the proposed conditions of the reconstructed bridges with the existing conditions. This report presents the setting and hydrologic data, as well as the hydraulic data for the existing and proposed bridges.



LOCATION MAP

2.0 BRIDGE DESCRIPTIONS & FLOOD HISTORY

2.1 BRIDGE STREET BRIDGE

The existing Bridge Street Bridge carries U.S. Route 201 over the Cobbossee Stream. The bridge consists of four 55-foot spans of concrete T-beams, with a total superstructure depth of about 6.0 feet. The superstructure is on mass piers and high cantilever abutments with shallow foundations founded on native fill material. The bridge crosses a FEMA Flood Zone and Regulatory Floodway, shown in Figure 1. The northern two bridge spans cross the Cobbossee Stream, the southern interior span crossing Arcade Street, and the southern exterior span crossing a fill slope. The vertical clearance over Arcade Street is 11.0'. The bridge supports several utilities, and overhead power exists above the bridge. An elevated concrete driveway structure abuts the bridge along its southwest edge.

An existing building, of about 23 feet in width, was on the south overbank of the Cobbossee Stream, blocking a portion of the overbank in higher flows. During the completion of this report, that building has been removed, but it remains in the existing conditions model, so the effect of its removal may be shown with other project modifications.

The existing channel upstream and downstream are lined with large stones, and appear to be stable. Small concrete walls surround each of the piers on the stream banks; these may have served as cofferdams and were left in place as scour protection. Remnants of a stacked granite block dam are just upstream of the bridge, and the bridge may have been located within the spillway area when the dam was functional. The dam remnants have been identified as a historical resource, and will remain.

The proposed Bridge Street Bridge consists of a single steel plate girder span of 135 feet, with a superstructure depth of about 5.5 feet, founded on high cantilever abutments on deep foundation piles. The proposed bank protection is riprap revetments at 1.75:1 to 2.0:1 slope.

2.2 MAINE AVENUE BRIDGE AND MULTI-USE BRIDGE

The existing Maine Avenue Bridge carries Maine Avenue over the Cobbossee Stream. The bridge consists of one concrete T-beam span of 50.0 feet, with a superstructure depth of about 4.5 feet. The superstructure is on stacked granite stone abutment walls that extend below stream grade and are founded on native fill materials. This bridge lies inundated beneath the FEMA Flood Zone water surface at the flood stage of the Kennebec River. Figure 1 shows the FEMA Flood Zone and Regulatory Floodway in the project area.

The existing channel upstream is lined with large stones and appears to be stable. The existing channel downstream has an unprotected earth slope on the south side, and a high retaining wall on the north side. While the invert of the stream is lined with large stones, the southern earth slope is prone to erosion, the northern retaining wall is prone to scour, and a known grout bag

scour repair exists at the downstream corner of the north abutment. Further downstream is a rail bridge which is founded on the retaining wall to the north and a failing stacked-stone abutment on the south. The rail bridge no longer carries rail traffic.

The proposed Maine Avenue Bridge is a single span of 78.0 feet, with a superstructure depth of about 3.7 feet, founded on integral abutments on deep foundation piles. The proposed bank protection is riprap revetments at 1.5:1 slope. Erosion and scour protection at the south earthen slope and north retaining wall should be considered for inclusion in project scoping. Similarly, the design should consider protection against high flows for the failing rail bridge south abutment.

A proposed separated Multi-use Bridge, approximately 50 feet upstream of the Maine Avenue Bridge, was modeled to determine its influence on flows. The Multi-use Bridge's proposed low chord elevation is about 8" above the proposed Maine Ave bridge's low chord elevation.

2.3 FLOOD HISTORY

According to the Kennebec County Flood Insurance Study:

> *In Kennebec County, flooding generally occurs in the winter or early spring as a result of heavy rainfall on snow covered or frozen ground. Ice jams in the rivers can compound flood problems.*
>
> *The most notable floods on the Kennebec River occurred in May 1832, December 1901, March 1936, and April 1987. The 1987 flood had a peak discharge of 232,000 cubic feet per second (cfs) at the USGS gaging station in Sidney (station No. 01049265) and a recurrence interval of over 100 years.*
>
> *Flooding in the Cities of Augusta and Gardiner occur principally in the commercial area along the banks of the Kennebec River. Gardiner has a downtown business district along Water Street, as well as a shopping center located along the bank of the Kennebec River near the mouth of Cobbosseecontee Stream, which would suffer extensive damage in a major flood.*
>
> *Three flooding events were identified within the Kennebec River Basin after 1987. The Kennebec River and Cobbosseecontee Stream flooded in March and December of 2003 as a result of ice jams. Both flooding events were estimated by the USGS to be below the 50-percent-annual-chance flood in the City of Gardiner, ME. Flooding of the Kennebec and Cobbosseecontee Rivers in April 2005 was estimated by USGS to be between the 20, and 10-percent-annual-chance flood. The April 2005 flooding event impacted the Cities of Augusta, Gardiner and Hallowell. Flooding along the Kennebec River in April 2008 (19.14 feet NAVD) reached similar gage heights in the City of Augusta as the April 2005 flooding event (19.49 feet NAVD).*

The recorded flood information indicates that FEMA FIRM flood elevations are mostly attributable to the behavior of the flows in the Kennebec River, and have less to do with the flows in the upper reaches of the Cobbossee Stream. As a result, the hydraulic openings of the bridges at Maine Avenue and Bridge Street are unlikely to affect the Kennebec-induced flooding of the greater area surrounding these bridges. However, as shown later in this Report, immediate areas

surrounding the Bridge Street Bridge and Arcade Street do experience some flooding from Cobbossee Stream flow alone. Therefore, the design of the subject bridges should only consider localized effects on the conveyance of upstream flows in the Cobbossee Stream.

3.0 HYDRAULIC MODELING

This Hydrology/Hydraulic/Scour Report, follows requirements contained in MaineDOT *Bridge Design Guide* (BDG) 2.1.9. The geometry of the Cobbossee Stream was generated from ground survey and contours provided by MaineDOT. Hydraulic modeling of the Cobbossee Stream was performed using HEC-RAS river modeling software obtained from the US Army Corps of Engineers, and follows MaineDOT and FEMA practices. Figure 1 shows the extent of flooding in the project area from the FEMA Flood Insurance Rate Map. Figure 2 shows the location of cross sections used in the HEC-RAS model. Cross sections A thru I, from Figure 1, were located in the HEC-RAS model (Figure 2) for comparison to FEMA FIS data. Figure 3 shows FEMA Floodway limits in the project area as obtained from the FEMA National Flood Hazard Layer of the Maine GIS website:

http://maine.maps.arcgis.com/apps/webappviewer/index.html?id=3c09351397764bd2aa9ba385d2e9efe7

Figures 4A, 4B, and 5 show the proposed bridge grading, plan, and profile at Bridge Street with the FEMA Floodway. The plan and profile figures for Bridge Street depict a bridge span of 135 feet. Earlier in the study process, an alternative design with a bridge span of 130 feet was modeled. Grading of the overbank near the north abutment to provide a smooth transition through the proposed bridge opening was conducted, and the bridge span set at 135 feet. Additionally, an old foundation of large granite blocks just northwest of the existing Bridge Street was modelled as remaining in place. The building just southeast of the Bridge Street bridge known as Dennis's Pizza was also removed from the proposed conditions (noted on Figure 4B).

Figures 6A, 6B, and 6C show the proposed Maine Avenue highway bridge in plan and profile views. Figure 7 depicts the proposed plan and profile views of the separated Multi-use bridge. FEMA's Regulatory Floodway is not shown on this plan, because the Floodway spills out beyond the adjacent parking areas to the north and south of the bridge project limits as can be seen in Figure 3. Table 1 shows the Hydrology flow rates as obtained from the FEMA Flood Insurance Study *Kennebec County FIS 23011CV001* (June 2011), and MaineDOT provided separate regression equation values shown in Table 2. Since the flow rates from the FEMA FIS marginally exceeded the flow rates provided by MaineDOT, the FEMA flow rates were accepted for use by MaineDOT. Manning's channel roughness "n" values were obtained from the FEMA FIS and compared to standard values. MaineDOT surveyors obtained tidal benchmarks, which Stantec compared to tidal gage data published by the US Department of Commerce. Tide data was obtained per MaineDOT BDG 2.3.6.

Figure 8 shows the FEMA FIS profile for the Cobbossee Stream, with the project area inundated by flooding of the Kennebec River. Figure 8 also shows cross section locations for the FEMA model used to set the Regulatory Floodway of the Cobbossee Stream in the vicinity of the Bridge Street Bridge. FEMA did not furnish a similar analysis for the lower reach of the Cobbossee Stream under non-flood conditions in the Kennebec River. Table 3 gives Floodway Data for the reach near the Bridge Street Bridge. Figure 9 shows the FEMA conceptual section of a Regulatory Floodway, which is the stream flow area needed to remain open to flows such that, if the floodplain were filled in to Floodway limits, the stream flow would be accommodated with no more than 1 foot of rise in water surface elevation. Floodway analyses were not conducted with this report.

Per MaineDOT BDG hydraulics section 2.3.3.2, BDG 2.3.10.2.C, and HEC-23, Stantec performed a Level 2 Basic Analysis, which is a qualitative plus steady flow analysis for bridge opening freeboard and foundation scour using tail waters for tidal mean high water and mean low water bounds. Stantec checked the backwater conditions of the bridge per BDG 2.3.10.4, using an existing conditions model (the FEMA Corrected Effective model developed for this project, further described below) for comparison with the proposed bridge layout model. Tidal information is shown in Appendix A.

Scour analysis was performed per HEC-18 as contained in HEC-RAS and as modified for current HEC-18 parameters. Slope protection scour countermeasures were evaluated per HEC-23 guidance, for the proposed bridge layouts. Scour and revetment calculations are shown in Appendix B and C.

4.0 RESULTS AND DISCUSSION

Using the HEC-RAS models described above, Stantec developed Cobbossee Stream water surface profiles for existing conditions and proposed conditions at Bridge Street and Maine Avenue for tail water conditions of Mean High Water and Mean Low Water at the confluence of Cobbossee Stream with the Kennebec River. The proposed models were also used to determine parameters for scour protection.

The hydraulic data summary Table 4 provides data typical to MaineDOT bridge plans. Figure 10 shows profile information for the FEMA FIS cross section points A thru I, as well as the remainder of the project limits downstream to the Kennebec River confluence. Representative stream profiles and sections showing bridge elevations are attached as Figures 11 thru 17.

BDG 2.3.11.1 scour requirements include evaluation of scour at the design flood (Q100) and the check flood (Q500). The procedures contained in HEC-18 have been used for scour estimation, and are contained in Appendix B. The Haley & Aldrich gradation analyses provided the soil particle sizes used for estimating scour (2.4mm Bridge St., 0.2mm Maine Ave.). Scour depths for

the unprotected channel are estimated as shown in Table 5 for Bridge Street Bridge and Maine Avenue Bridge, with the Multi-use Bridge scour similar to the nearby Maine Avenue Bridge.

	Table 5, Scour Depth, ft.			
	@ Q100		@ Q500	
	Clearwater	Live Bed	Clearwater	Live Bed
Bridge St. Bridge	13.1	11.9	15.4	14.0
Maine Ave. Bridge	49.3	13.1	50.0	7.9

A review of the stream profile at Bridge Street indicates the bridge is located at a change in stream gradient. A scour hole is indicated thru and downstream of the bridge location. Field observations confirm the flow to be turbulent upstream, and calm downstream, of this location. Hydraulic analyses indicate a hydraulic jump develops upstream of the bridge location at Section B. Revetment described below is needed to protect the abutments of the Bridge Street Bridge.

While the scour estimates for Maine Avenue Bridge are in excess of field-observed conditions, all values indicate that revetment is needed to protect the abutments and retaining wall foundations downstream of the Maine Avenue Bridge.

The HEC-23 parameters for sizing riprap were selected based on the MaineDOT BDG 2.3.11.3 slope protection criteria for the design flood (Q100). Bank protection revetment calculations are shown in Appendix C. HEC-23 recommends that riprap be a minimum of 0.8 feet D_{50} for Bridge Street, and 0.9 feet D_{50} for Maine Avenue. According to BDG 2.3.11.3, a 4-foot minimum thickness of plain riprap should be used at Bridge Street Bridge, and a 4-foot thickness of heavy riprap should be used at Maine Avenue Bridge and Multi-use Bridge. A 4-foot thickness of heavy riprap is recommended at the subject bridge locations.

The analysis and results from HEC-RAS hydraulic simulations are contained in appendices D through F, for existing and proposed conditions, with Mean Low Water (MLW) and Mean High Water (MHW) tailwater conditions at the stream confluence with the Kennebec River. Appendix H contains the HEC-RAS electronic files.

5.0 FEMA SUMMARY

The FEMA FIS indicates that the 100-year Cobbossee Stream flow from upstream sources during normal tidal water (non-flood) levels in the Kennebec River is 5,910 cubic-feet/second at about 11.2 feet/second velocity, with a water surface elevation (WSEL) of 14.7 feet (NAVD 1988) upstream and 10.9 feet downstream of the Bridge Street Bridge. Since the Flood Zone inundates the Maine Avenue Bridge, the FIS does not report similar data for this bridge. The FEMA *Flood*

FEMA SUMMARY
June 6, 2018

Insurance Rate Map 23011C0657D (FIRM, June 2011) shows that the Flood Zone elevations for both bridges are in a backwater condition from the flood levels of the Kennebec River (100-year Water Surface Elevation (WSEL) 24.0 feet) with all vertical elevation values in datum NAVD 1988.

Based on the above information, neither bridge waterway opening controls the 100-year Flood Zone elevations set by FEMA. The FEMA FIRM Flood Zone elevations solely depend on the high flow elevations of the Kennebec River rather than the upland flows in Cobbossee Stream. Upland flows in the Cobbossee Stream result in 100-year flood water surface elevations that are about 10' lower than the Kennebec River backwater flows shown on the FIRM. However, the FEMA FIS and FIRM include a Regulatory Floodway along the Cobbossee Stream to prevent further filling of the floodplain near normal stream flows when the Kennebec River is at non-flood flow levels. The calculated Floodway of the Cobbossee Stream begins at Section A on the FEMA FIRM, just downstream of the Bridge Street Bridge. However, the Floodway is delineated to the Kennebec River, and appears to be a graphic connection between the calculated Floodways of the Cobbossee Stream and the Kennebec River.

Backwater of the Kennebec River floods the project area and sets the limits of the FEMA Flood Zone at both bridges and the Regulatory Floodway at Maine Avenue. However, upstream of the Maine Avenue Bridge, FEMA has determined a separate Regulatory Floodway within the Cobbossee Stream for times when the Kennebec River is not at flood stage. Near the Bridge Street Bridge, the Regulatory Floodway is located near the defined stream channel. Near the Maine Avenue Bridge, the Regulatory Floodway is much wider than the existing bridge since the Kennebec River flooding engulfs the existing bridge.

Stantec obtained the FEMA Current Effective hydraulic model for the Cobbossee Stream from FEMA's consultant Michael Baker Jr. Inc. This model is the basis of the Cobbossee Stream Regulatory Floodway data contained in the FIS and FIRM. The model was prepared using the USGS software program E431, *Step-Backwater and Floodway Analysis*, which shows flood channel cross sections similar to the existing cross sections obtained from current ground survey. The model does not include the existing building obstructions on the south overbank downstream of the Bridge Street Bridge.

Since the FEMA Current Effective model cross sections were found to reasonably compare to the cross sections obtained from current ground survey, a Duplicate Effective (see FEMA MT-2) model was not created. Instead, a Corrected Effective model of existing conditions using current ground survey was analyzed using HEC-RAS software. This Corrected Effective model was used to establish a baseline of actual existing conditions, including the existing building obstructions at Bridge Street, and for comparing the existing condition to the hydraulic parameters of the Cobbossee Stream for proposed conditions. In the proposed conditions model, the existing building at the Bridge Street Bridge middle pier (Dennis' Pizza) has been removed since the building has been demolished prior to beginning this bridge replacement project.

FEMA SUMMARY
June 6, 2018

The proposed Bridge Street Bridge includes a 135-foot bridge span with the proposed abutments located outside the Regulatory Floodway. The work also includes removal of the existing bridge piers, and an adjacent commercial building, regrading of the channel banks, construction of bank revetment, and minor earthwork grading within the floodplain and Regulatory Floodway.

The proposed Maine Avenue Bridge and separate Multi-use Bridge construction lies completely within the Regulatory Floodway and includes construction of minor earthwork filling and bank protection. Construction of these two bridges outside of the Regulatory Floodway is not possible due to site constraints and proximity to the Kennebec River confluence. Stantec's analysis shows that the Multi-use Bridge and its access path have very little effect on stream hydraulics in the context of the modeling described above.

A summary of the existing versus proposed Cobbossee Stream 100-year flood conditions is shown in Table 6 for MaineDOT's use in making a final decision on bridge layout and potential FEMA flood insurance map impacts. The proposed modeling illustrates that there is not any increase in the water surface elevation for the 100-year event with MHW tailwater compared to the existing modeled conditions within the FEMA study reach (Sections A to I).

While the proposed Maine Avenue bridge lies within the Regulatory Floodway of the Kennebec River and Cobbossee Stream, the bridge was an existing condition when the Floodway was established. The proposed replacement bridge does not affect the flow width, and does not affect the Floodway limits. The Maine Avenue proposed bridge is slightly longer than the existing bridge, which improves the hydraulics thru the bridge opening, but since the downstream channel is unimproved, the overall hydraulics remains consistent with existing conditions. Similarly, the addition of a Multi-use Bridge which spans the channel, will also lie inside the Regulatory Floodway, but will not affect it, since the Floodway is determined by backwater flooding of the Kennebec River, not by the presence of the subject bridge.



Bridge St. Bridge over Cobbossee Stream, Gardiner ME

Maine Ave. Bridge and Multi-use Bridge over Cobbossee Stream, Gardiner ME

NFIP

NATIONAL FLOOD INSURANCE PROGRAM

PANEL 0657D

FIRM

FLOOD INSURANCE RATE MAP

KENNEBEC COUNTY, MAINE

(ALL JURISDICTIONS)

PANEL 657 OF 775

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

CONTAINS:

COMMUNITY	NUMBER	PANEL	SUFFIX
CHELSEA, TOWN OF	230234	0657	D
FARMINGDALE, TOWN OF	230164	0657	D
GARDINER, CITY OF	230068	0657	D
PITTSTON, TOWN OF	230243	0657	D
RANDOLPH, TOWN OF	230244	0657	D

Notice to User: The **Map Number** shown below should be used when placing map orders; the **Community Number** shown above should be used on insurance applications for the subject community.

MAP NUMBER
23011C0657D

EFFECTIVE DATE
JUNE 16, 2011

Federal Emergency Management Agency

LEGEND

SPECIAL FLOOD HAZARD AREAS (SFHAs) SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual chance flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

ZONE A	No Base Flood Elevations determined.
ZONE AE	Base Flood Elevations determined.
ZONE AH	Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood Elevations determined.
ZONE AO	Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average depths determined. For areas of alluvial fan flooding, velocities also determined.
ZONE AR	Special Flood Hazard Areas formerly protected from the 1% annual chance flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood.
ZONE A99	Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations determined.
ZONE V	Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.
ZONE VE	Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

OTHER FLOOD AREAS

ZONE X	Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

OTHER AREAS

ZONE X	Areas determined to be outside the 0.2% annual chance floodplain.
ZONE D	Areas in which flood hazards are undetermined, but possible.

COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.

1% Annual Chance Floodplain Boundary

0.2% Annual Chance Floodplain Boundary

Floodway boundary

Zone D boundary

CBRS and OPA boundary

Boundary dividing Special Flood Hazard Area Zones and boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths, or flood velocities.

513 — Base Flood Elevation line and value; elevation in feet*

(EL 987) — Base Flood Elevation value where uniform within zone; elevation in feet*

*Referenced to the North American Vertical Datum of 1988

A — A — Cross section line

23 — 23 — Transect line

Culvert

Bridge

45° 02' 08", 93° 02' 12" — Geographic coordinates referenced to the North American Datum of 1983 (NAD 83) Western Hemisphere

4989000 M — 1000-meter ticks: Maine State Plane West Zone (FIPS Zone 1802), Transverse Mercator projection

4989000 N — 1000-meter Universal Transverse Mercator grid values, zone 19N

DX5510 — Bench mark (see explanation in Notes to Users section of this FIRM panel)

M1.5 — River Mile

MAP REPOSITORIES
Refer to Map Repositories list on Map Index

EFFECTIVE DATE OF COUNTYWIDE FLOOD INSURANCE RATE MAP
June 16, 2011

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

Figure 1, Detail from FEMA FIRM




Figure 2, Cross Section Locations for HEC-RAS Model




Figure 3, FEMA Regulatory Floodway





Figure 4A, Proposed Bridge Street Grading

Filename: ...\BRIDGE\MSTA\ddt_grading.dgn Division: BRIDGE Username: dotaylor Date:6/1/2018



LEGEND

- - - - = Match Line with WIN 18736.10 & 22684.00

⬡ = Interpretive Panel

NOTES

1. See WIN 22684.00 Intersection Plans for Bridge Street and Water Street Intersection details. This includes removal of existing signal equipment and installation of proposed signal equipment.

2. Reference Utility Plans for proposed relocations of existing utilities (water, gas, aerial electric and cable, and underground communications) and street lighting.

3. See WIN 18736.10 plans for trail details.

PRELIMINARY
NOT FOR CONSTRUCTION

Figure 4B, Proposed Plan at Bridge Street

Stantec

STATE OF MAINE
DEPARTMENT OF TRANSPORTATION

STP-1873(500)

WIN 18735.00

BRIDGE NO. 2101

BRIDGE PLANS

PROJ. MANAGER	L. THIBEAULT
DESIGN-DETAILED	SJF
DESIGNED-DETAILED	TEK
DESIGNED-DETAILED	PLP
DESIGNED-DETAILED	TEK

BY	DATE
DOT\LSF	JAN. 2018
PLP	JAN. 2018
JTB	JAN. 2018

P.E. NUMBER

SIGNATURE

DATE

REVISIONS 1
REVISIONS 2
REVISIONS 3
REVISIONS 4
FIELD CHANGES

BRIDGE STREET BRIDGE
COBBOSSEECONTEE STREAM
KENNEBEC COUNTY
GARDINER


GENERAL PLAN

SHEET NUMBER

A2

OF A73

Filename: ...\00\BRIDGE\MSTA\0A2_Plan1.dgn Division: BRIDGE Username: kwight Date:6/2/2018



NOTE:

1. Existing substructure and foundation dimensions shown are based on a combination of existing plans and field observations. Actual conditions may differ from these Plans.

Figure 5, Proposed Profile at Bridge Street

BRIDGE STREET PROFILE

Horiz. 25 0 25 50

Vert. 5 0 5 10

Scale of Feet

PRELIMINARY
NOT FOR CONSTRUCTION

Stantec

STATE OF MAINE
DEPARTMENT OF TRANSPORTATION

STP-1873(500)

WIN 18735.00

BRIDGE NO. 2101

BRIDGE PLANS

PROJ. MANAGER	L. THIBEAULT	BY	DATE
DESIGN-DETAILED	TEK	DDT\LSF	JAN. 2018
CHECKED-DETAILED	JTB	PLP	JAN. 2018
DESIGN2-DETAILED	PLP	PLP	JAN. 2018
DESIGN3-DETAILED	TEK	JTB	
REVISIONS 1			
REVISIONS 2			
REVISIONS 3			
REVISIONS 4			
FIELD CHANGES			

SIGNATURE

P.E. NUMBER

DATE

BRIDGE STREET BRIDGE
COBBOSSEECONTEE STREAM
GARDINER KENNEBEC COUNTY

PROFILE

SHEET NUMBER

A5

OF A73

Filename: ...\BRIDGE\MSTA\ddt_grading.dgn Division: BRIDGE Username: dotaylor Date:6/2/2018




Figure 6A, Proposed Maine Avenue Grading





Figure 6B, Proposed Plan at Maine Avenue



MAINE AVENUE PROFILE

Horiz. 25 0 25 50

Vert. 5 0 5 10

Scale of Feet

PRELIMINARY
NOT FOR CONSTRUCTION

Stantec

STATE OF MAINE
DEPARTMENT OF TRANSPORTATION

STP-1873(600)

WIN 18736.00

BRIDGE NO. 3098

BRIDGE PLANS

PROJ. MANAGER	L. TIMBERLAKE	BY	DATE
DESIGN-DETAILED	LST	QA/QC	MAY 2017
QUALITY CHECKED	DDT	PM/PM	MAY 2017
DESIGN2-DETAILED2	PLP		MAY 2017
DESIGN3-DETAILED3			
REVISIONS 1			
REVISIONS 2			
REVISIONS 3			
REVISIONS 4			
FIELD CHANGES			

SIGNATURE

P.E. NUMBER

DATE

MAINE AVENUE BRIDGE
COBBOSSEECONTEE STREAM
GARDINER KENNEBEC COUNTY

PRELIMINARY PROFILE


SHEET NUMBER

3

OF 11

Filename: ...\MSTA\003_Profile.dgn Division: BRIDGE Username: dataylor Date:5/15/2017

Figure 6C, Proposed Profile at Maine Avenue



Filename: ...\006_HOPlan_BikePedBridgePlan.dgn Division: BRIDGE Username: lflanders Date:7/28/2017

Figure 7, Proposed Plan and Profile of Multi-use Bridge

Table 1, FEMA Cobbossee Stream Flow Data

FLOODING SOURCE AND LOCATION	DRAINAGE AREA (SQUARE MILES)	PEAK DISCHARGES (CUBIC FEET PER SECOND) 10-PERCENT ANNUAL CHANCE	2-PERCENT ANNUAL CHANCE	1-PERCENT ANNUAL CHANCE	0.2-PERCENT ANNUAL CHANCE		
BOND BROOK							
At Confluence with Kennebec River	21.3	1,390	2,310	2,800	4,210		
At first crossing of Bond Brook Road	17.2	1,110	1,830	2,230	3,360		
Upstream of Confluence of Stone Brook	13.7	898	1,500	1,820	2,760		
COBBOSSEECONTEE STREAM						MDOT Q1.1	MDOT Q25
At Confluence with Kennebec River	219	3,850	5,290	5,910	7,380	1,312	4,148
At inlet to Pleasant Pond near the Sagadahoc-Kennebec County limits	213	3,850	5,290	5,910	7,380		
Gardiner- West Gardiner corporate limits	212	3,850	5,290	5,910	7,380		
At Pond Road	186	3,400	4,660	5,180	6,500		
At the Litchfield-West Gardiner upstream corporate limits	140	*	*	4,140	*		
At Collins Mill Road	140	2,710	3,740	4,140	5,200		
At West Gardiner-Manchester corporate limits	139	2,710	3,740	4,140	5,200		
At Confluence with Cobbosseecontee Lake	131	2,570	3,540	3,920	4,930		

Source: FEMA Flood Insurance Study 23011CV001A, Kennebec County, ME (June 16, 2011)

Environmental Office – Hydrology Section
16 State House Station
Augusta ME 04333-0016
207.557.1052
Charles.Hebson@maine.gov

Maine Department of Transportation

Memo

To: Janet Damren, Leanne Timberlake

From: Charles Hebson

CC:

Date: 11 May 2015

Re: Gardiner - 18735 (Bridge St, 2101) & 18736 (Maine Ave, 3908) - Cobbesecontee Stream Hydrology

---

The final recommended design hydrology is summarized in Table 1 and Figure 1 below.

Table 1. Design Hydrology Summary

Return Period T (yrs)	Exceedance Prob P_{ex}	USGS gage Bull. 17B Est.
1.005	0.995	
1.01	0.990	
1.05	0.952	1122
1.1	0.900	1312
1.25	0.800	1576
1.5	0.667	1861
2	0.500	2204
2.33	0.429	2360
5	0.200	3020
10	0.100	3531
25	0.040	4148
50	0.020	4588
100	0.010	5012
200	0.005	5426
500	0.002	5959
Max of Record (1936)		5020

Note: USGS Gage 01049500 on Cobbosseecontee Stream in Gardiner, just upstream of bridges

Table 2, MaineDOT Cobbossee Stream Flow Data

Figure 8, FEMA Cobbossee Stream Profile

Source: FEMA Flood Insurance Study 23011CV001A, Kennebec County, ME (June 16, 2011)

Table 3, FEMA Cobbossee Stream Floodway Data

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER SURFACE ELEVATION (FEET NAVD)			
CROSS SECTION	DISTANCE[1]	WIDTH (FEET)	SECTION AREA (SQARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
A	1000	100	530	11.2	24.0	10.7 [2]	10.9	0.2
B	1140	80	657	9.0	24.0	14.3 [2]	14.7	0.4
C	1250	60	400	14.8	24.0	14.6 [2]	14.7	0.1
D	1370	60	449	13.2	24.0	17.1 [2]	17.1	0.0
E	1520	100	783	7.6	24.0	20.9 [2]	20.9	0.0
F	1640	90	630	9.4	24.0	21.1 [2]	21.1	0.0
G	1740	90	497	11.9	24.0	21.5 [2]	21.5	0.0
H	1820	85	464	12.8	24.0	22.3 [2]	22.3	0.0
I	1880	60	399	14.8	24.0	23.7 [2]	23.7	0.0
J	2010	85	810	7.3	27.9	27.9	27.9	0.0
K	2100	90	662	8.9	28.0	28.0	28.0	0.0
L	2180	85	664	8.9	28.5	28.5	28.5	0.0
M	2240	150	853	6.9	29.2	29.2	29.2	0.0
N	2350	120	700	8.5	29.6	29.6	29.6	0.0
O	2430	100	554	10.7	30.0	30.0	30.0	0.0
P	2540	90	546	10.8	31.1	31.1	31.1	0.0
Q	2660	80	571	10.3	33.0	33.0	33.0	0.0
R	2730	170	1320	4.5	33.9	33.9	34.2	0.3
S	2790	150	701	8.4	34.0	34.0	34.2	0.2
T	2830	140	645	9.2	34.2	34.2	34.5	0.3
U	2900	130	1150	5.1	39.2	39.2	39.5	0.3
V	3090	110	775	7.6	39.8	39.8	40.1	0.3
W	3320	130	568	10.4	43.5	43.5	43.6	0.1
X	3470	80	520	11.3	46.1	46.1	46.1	0.0
Y	3660	120	673	8.8	49.0	49.0	49.4	0.4
Z	3770	120	524	11.3	51.1	51.1	51.5	0.4
AA	3960	90	520	11.3	54.5	54.5	54.5	0.0

[1] FEET ABOVE CONFLUENCE WITH KENNEBEC RIVER

[2] ELEVATION COMPUTED WITHOUT CONSIDERATION OF BACKWATER EFFECTS FROM KENNEBEC RIVER

Source: FEMA Flood Insurance Study 23011CV001A, Kennebec County, ME (June 16, 2011)

TABLE 10

FEDERAL EMERGENCY MANAGEMENT AGENCY

KENNEBEC COUNTY, ME
(ALL JURISDICTIONS)

FLOODWAY DATA

COBBOSSEECONTEE STREAM




Figure 9, FEMA Regulatory Floodway Section

Source: FEMA Flood Insurance Study 23011CV001A, Kennebec County, ME (June 16, 2011)

Table 4, Cobbossee Stream Flow Summary

MAINEDOT GARDINER								
WIN 18735, 18736								
HYDROLOGIC AND HYDRAULIC DATA								
4/11/2018								
HYDROLOGY DATA:								
			REF:					
DRAINAGE AREA	219	sq.mi.	FEMA FIS					
ORDINARY HIGH WATER DISCHARGE (Q1.1)	1,312	cfs	MaineDOT					
DISCHARGE (Q10)	3,850	cfs	FEMA FIS					
DISCHARGE (Q25)	4,148	cfs	MaineDOT					
DESIGN DISCHARGE (Q50)	5,290	cfs	FEMA FIS					
CHECK DISCHARGE (Q100)	5,910	cfs	FEMA FIS					
SCOUR CHECK DISCHARGE (Q500)	7,380	cfs	FEMA FIS					
MEAN HIGHER HIGH WATER (MHHW) EL.	4.2	ft	MaineDOT benchmark survey					
MEAN HIGH WATER (MHW) EL.	3.8	ft	NOAA Tidal data					
MEAN TIDE LEVEL (MTL) EL.	0.9	ft	typical					
MEAN LOW WATER (MLW) EL.	-2.1	ft	NAVD Datum					
MEAN LOW LOW WATER (MLLW) EL.	-2.3	ft						
FLOOD OF RECORD EL.	24.9	ft	Onsite pole					
2018 PREDICTED HIGH TIDE EL.	5.3	ft	NOAA Tidal data					
HYDRAULIC DATA SUMMARY:								
	EXISTING MAINE AVE. BRIDGE (MLW)	EXISTING MAINE AVE. BRIDGE (MHW)	PROPOSED MAINE AVE. BRIDGE (MLW)	PROPOSED MAINE AVE. BRIDGE (MHW)	TRAIL BRIDGE (MLW)	TRAIL BRIDGE (MHW)	EXISTING BRIDGE ST. BRIDGE	PROPOSED BRIDGE ST. BRIDGE
HEC-RAS SECTION	98.5 BR U	98.5 BR U	98.5 BR U	98.5 BR U	166 BRU	166 BRU	895 BR U	895 BR U
ORDINARY HIGH WATER EL. @ Q1.1	0.9	3.8	0.6	3.8	1.9	3.9	7.1	7.0
HEADWATER EL. @ Q10	4.7	4.7	4.7	4.8	5.7	5.7	9.9	9.7
HEADWATER EL. @ Q25	5.0	5.0	5.1	5.1	6.1	6.1	10.2	10.0
HEADWATER EL. @ Q50	6.4	6.4	6.7	6.7	7.5	7.5	11.1	11.1
HEADWATER EL. @ Q100	7.2	7.2	7.6	7.6	8.2	8.2	11.7	11.6
HEADWATER EL. @ Q500	8.8	8.8	9.4	9.4	9.9	9.9	13.1	12.8
DISCHARGE VELOCITY @ Q1.1	9.0	4.6	9.8	4.5	7.0	4.5	7.1	5.7
DISCHARGE VELOCITY @ Q10	11.9	11.8	11.5	11.3	9.9	9.8	10.4	8.7
DISCHARGE VELOCITY @ Q25	12.2	12.2	11.6	11.6	10.1	10.1	10.5	8.9
DISCHARGE VELOCITY @ Q50	13.0	13.0	11.6	11.6	10.6	10.6	10.9	9.1
DISCHARGE VELOCITY @ Q100	13.3	13.3	11.6	11.6	10.8	10.8	10.8	9.3
DISCHARGE VELOCITY @ Q500	14.1	14.1	11.5	11.5	11.1	11.1	10.0	9.3
LOW CHORD EL.	10.5	10.5	11.0	11.0	11.6	11.6	21.5	22.0
VERTICAL CLEARANCE @ Q50	4.1	4.1	4.3	4.3	4.1	4.1	10.4	10.9
VERTICAL CLEARANCE @ Q100	3.4	3.4	3.5	3.5	3.4	3.4	9.8	10.4




Figure 10, Cobbossee Stream Profile

Table 6, Cobbossee Stream 100-year Flow Data

Q100 DATA, HEC-RAS MODEL AND FEMA FIS																																		
FEMA FIS SECTION --->			I	H	G	F	E	D	C	B					A		(LOWER PORTION OF COBBOSSEE STREAM NOT MODELED BY FEMA IN FIS)																	
												(Bridge St. Bridge)																		(Maine Ave Bridge)						
EXIST MHW	River Sta		1700	1635	1555	1455	1335	1185	1060	960	935	920	870	850	830	821	820	725	575	425	335	262	187	187	187	137	114.5	82.5	60	38	0	-21	-54	-88	-143
	Min Ch El	(ft)	13.8	14.0	13.3	11.8	9.5	5.5	5.0	3.5	2.0	2.0	1.0	1.0	1.0	1.0	1.0	2.5	1.5	0.0	-2.0	-3.0	-4.0	-4.0	-4.0	-4.0	-4.0	-5.0	-5.0	-4.5	-6.3	-7.0	-7.0	-6.0	-7.0
	W.S. Elev	(ft)	22.8	22.3	20.3	19.2	18.3	15.7	13.6	12.5	13.0	11.7	11.5	11.6	11.5	11.5	11.6	11.3	11.1	10.8	10.3	9.4	9.1	9.1	9.1	8.4	7.2	7.2	7.3	6.9	4.2	1.8	1.9	3.7	3.8
	Top Width	(ft)	85.0	91.6	80.1	85.0	80.4	64.2	66.8	82.8	158.2	121.5	133.3	144.2	147.3	157.7	193.2	188.2	220.8	244.7	169.0	73.2	71.1	71.1	71.1	69.0	48.5	48.5	59.0	58.5	44.3	45.7	61.4	75.5	73.6
	Vel Chnl	(ft/s)	10.6	10.5	13.0	12.4	10.8	13.2	14.2	12.2	8.3	11.3	9.6	8.8	8.2	8.1	7.5	7.4	6.2	6.2	7.8	9.9	9.7	9.7	9.7	11.1	13.3	11.8	11.0	11.6	16.5	19.8	17.7	12.7	10.6
EXIST MLW	River Sta		1700	1635	1555	1455	1335	1185	1060	960	935	920	870	850	830	821	820	725	575	425	335	262	187	187	187	137	114.5	82.5	60	38	0	-21	-54	-88	-143
	Min Ch El	(ft)	13.8	14.0	13.3	11.8	9.5	5.5	5.0	3.5	2.0	2.0	1.0	1.0	1.0	1.0	1.0	2.5	1.5	0.0	-2.0	-3.0	-4.0	-4.0	-4.0	-4.0	-4.0	-5.0	-5.0	-4.5	-6.3	-7.0	-7.0	-6.0	-7.0
	W.S. Elev	(ft)	22.8	22.3	20.3	19.2	18.3	15.7	13.6	12.5	13.0	11.7	11.5	11.6	11.5	11.5	11.6	11.3	11.1	10.8	10.3	9.4	9.1	8.4	9.1	8.4	7.2	7.2	7.3	6.9	4.2	1.8	1.9	3.2	0.9
	Top Width	(ft)	85.0	91.6	80.1	85.0	80.4	64.2	66.8	82.8	158.2	121.5	133.3	144.2	147.3	157.7	193.2	188.2	220.8	244.7	169.0	73.2	71.1	69.0	71.1	69.0	48.5	48.5	59.0	58.5	44.3	45.7	61.4	72.8	66.5
	Vel Chnl	(ft/s)	10.6	10.5	13.0	12.4	10.8	13.2	14.2	12.2	8.3	11.3	9.6	8.8	8.2	8.1	7.5	7.4	6.2	6.2	7.8	9.9	9.7	11.1	9.7	11.1	13.3	11.8	11.0	11.6	16.5	19.8	17.7	13.8	16.5
PROPOSED MHW	River Sta		1700	1635	1555	1455	1335	1185	1060	960	935	920	870	850	830	821	820	725	575	425	335	262	187	171.5	160.5	137	114.5	82.5	60	38	0	-21	-54	-88	-143
	Min Ch El	(ft)	13.8	14.0	13.3	11.8	9.5	5.5	5.0	3.5	2.0	2.0	1.0	1.0	1.0	1.0	1.0	2.5	1.5	0.0	-2.0	-3.0	-4.0	-4.0	-4.0	-4.0	-4.0	-5.0	-5.0	-4.5	-6.3	-7.0	-7.0	-6.0	-7.0
	W.S. Elev	(ft)	22.8	22.3	20.3	19.2	18.3	15.7	13.6	9.4	11.8	11.6	11.4	11.2	11.3	11.3	11.4	11.0	10.8	10.5	9.9	8.8	8.4	8.2	8.2	8.0	7.6	7.5	7.4	6.8	4.2	1.8	1.9	3.7	3.8
	Top Width	(ft)	85.0	91.6	80.1	85.0	80.4	64.1	66.9	76.5	132.9	126.6	125.6	137.1	159.1	173.1	172.4	173.8	205.8	227.4	116.9	71.1	68.8	68.1	68.3	67.7	66.3	63.1	62.8	58.8	44.3	45.7	61.4	75.5	73.6
	Vel Chnl	(ft/s)	10.6	10.5	13.0	12.4	10.8	13.2	14.2	18.6	10.4	10.7	10.4	10.8	9.2	8.3	7.7	8.2	6.5	6.5	8.1	10.6	10.5	10.8	10.7	11.0	11.6	10.8	10.9	12.0	16.5	19.8	17.7	12.7	10.6
PROPOSED MLW	River Sta		1700	1635	1555	1455	1335	1185	1060	960	935	920	870	850	830	821	820	725	575	425	335	262	187	171.5	160.5	137	114.5	82.5	60	38	0	-21	-54	-88	-143
	Min Ch El	(ft)	13.8	14.0	13.3	11.8	9.5	5.5	5.0	3.5	2.0	2.0	1.0	1.0	1.0	1.0	1.0	2.5	1.5	0.0	-2.0	-3.0	-4.0	-4.0	-4.0	-4.0	-4.0	-5.0	-5.0	-4.5	-6.3	-7.0	-7.0	-6.0	-7.0
	W.S. Elev	(ft)	22.8	22.3	20.3	19.2	18.3	15.7	13.6	9.4	11.8	11.6	11.4	11.2	11.3	11.3	11.4	11.0	10.8	10.5	9.9	8.8	8.4	8.2	8.2	8.0	7.6	7.5	7.4	6.8	4.2	1.8	1.9	3.2	0.9
	Top Width	(ft)	85.0	91.6	80.1	85.0	80.4	64.1	66.9	76.5	132.9	126.6	125.6	137.1	159.1	173.1	172.4	173.8	205.8	227.4	116.9	71.1	68.8	68.1	68.3	67.7	66.3	63.1	62.8	58.8	44.3	45.7	61.4	72.8	66.5
	Vel Chnl	(ft/s)	10.6	10.5	13.0	12.4	10.8	13.2	14.2	18.6	10.4	10.7	10.4	10.8	9.2	8.3	7.7	8.2	6.5	6.5	8.1	10.6	10.5	10.8	10.7	11.0	11.6	10.8	10.9	12.0	16.5	19.8	17.7	13.8	16.5
																								(Trail Bridge)										
FEMA FIS TABLE 10			I	H	G	F	E	D	C	B	A				A																			
	DIST		1880	1820	1740	1640	1520	1370	1250	1140	1000				1000																			
	River Sta		1700	1635	1555	1455	1335	1185	1060	960	830				830.0																			
	FEMA INVERT O4P		14.9	15.0	13.6	12.0	10.0	6.5	6.0	2.0	1.0				1.0																			
	WSEL		23.7	22.3	21.5	21.1	20.9	17.1	14.6	14.3	10.7				10.7																			
	VEL		14.8	12.8	11.9	9.4	7.6	13.2	14.8	9.0	11.2				11.2																			




Figure 11, Cobbossee Stream Profile - Existing Conditions




Figure 12, Bridge Street Bridge Elevation- Existing Conditions




Figure 13, Maine Avenue Bridge Elevation - Existing Conditions




Figure 14, Cobbossee Stream Profile - Proposed Conditions




Figure 15, Bridge Street Bridge Elevation - Proposed Conditions




Figure 16, Maine Avenue Bridge Elevation - Proposed Conditions




Figure 17, Trail Bridge Elevation - Proposed Conditions

APPENDIX A / TIDAL DATA

MEAN LOW WATER AND MEAN HIGH WATER DATA FOR KENNEBEC RIVER AT GARDINER:

from US Dept Commerce Tidal Datums

	Datum meters	Datum ft	computed NAVD ft
MHHW	1.99	6.53	4.2
MHW	1.882	6.17	3.8
MSL	1.025	3.36	1.0
MTL	0.974	3.20	0.9
MLW	0.066	0.22	-2.1
MLLW	0	0.00	-2.3

from US Dept Commerce Tidal Datums
Benchmark Elevs in Meters

7134B	7134C	7134D	benchmark
2.800	7.605	6.553	meters above MHW
4.682	9.487	8.435	meters above MLLW
1.882	1.882	1.882	difference MHW to MLLW

from US Dept Commerce Tidal Datums
Benchmark Elevs converted to feet

7134B	7134C	7134D	benchmark
9.19	24.95	21.50	feet above MHW
15.36	31.12	27.67	feet above MLLW
6.174	6.174	6.174	difference MHW to MLLW

from MaineDOT Survey

7134B	7134C	7134D	benchmark		
12.98	28.84	~~9.07~~	NAVD EL.	feet	NAVD

computed values at benchmarks, and computed average

7134B	7134C	7134D	benchmark	AVERAGE:	
3.79	3.89	~~-12.43~~	MHW	**3.8**	feet NAVD
			MLW	**-2.1**	feet NAVD
-2.38	-2.28	~~-18.60~~	MLLW	-2.3	feet NAVD

AVG, USE FOR GARDINER BRIDGE ANALYSIS

Station ID: 8417134 **PUBLICATION DATE: 02/27/2006**
Name: GARDINER, KENNEBEC RIVER MAINE
NOAA Chart: 13298 **Latitude: 44° 14.0' N**
USGS Quad: GARDINER **Longitude: 69° 46.0' W**

FROM I-295, CONTINUE NORTH ON I-295 TO EXIT 49 STATE ROUTE 201 RICHMOND, PROCEED NORTH OF STATE ROUTE 201 FOR 9.0 KM (5.6 MI) TO THE INTERSECTION OF STATE ROUTE 201 AND MARINA WAY, TURN RIGHT AND CONTINUE PAST THE CENTRAL MAINE ELECTRIC COMPANY DOWN THE PRIVATE ROAD TO THE MARINA. THE BENCH MARKS ARE LOCATED AT THE ELECTRIC COMPANY, ALONG THE WALK PATH, AND IN THE FIRE STATION WINGWALL. THE TIDE GAGE IS LOCATED ON THE FOGGY BOTTOM MARINA BULKHEAD.

T I D A L B E N C H M A R K S

PRIMARY BENCH MARK STAMPING: 7134 A 2005
DESIGNATION: 841 7134 A

MONUMENTATION: Tidal Station disk VM#: 17899
AGENCY: National Ocean Service (NOS) PID:
SETTING CLASSIFICATION: Granite foundation

The bench mark is a disk set in the granite foundation of the Maine Central Power Company located on Water Street, 44.34 m (145.5 ft) SE of the east railroad track, 15.9 m (52.2 ft) east of the fire hydrant, 1.84 m (6.04 ft) NE of the power company door, and 0.03 m (0.1 ft) above the stoop.

BENCH MARK STAMPING: 7134 B 2005
DESIGNATION: 841 7134 B

MONUMENTATION: Tidal Station disk VM#: 17900
AGENCY: National Ocean Service (NOS) PID:
SETTING CLASSIFICATION: Retaining wall

The bench mark is a disk set in a culvert located along the walk/bike path, 33.63 m (110.3 ft) south of the "5.75" mile marker, 26.00 m (85.3 ft) north of the SW corner of the home at 305 Maine Avenue, and 7.63 m (25.0 ft) west of the west railroad track.

Station ID: 8417134 **PUBLICATION DATE: 02/27/2006**
Name: GARDINER, KENNEBEC RIVER MAINE
NOAA Chart: 13298 **Latitude: 44° 14.0' N**
USGS Quad: GARDINER **Longitude: 69° 46.0' W**

T I D A L B E N C H M A R K S

BENCH MARK STAMPING: 7134 C 2005
DESIGNATION: 841 7134 C

MONUMENTATION: Tidal Station disk VM#: 17901
AGENCY: National Ocean Service (NOS) PID:
SETTING CLASSIFICATION: Concrete culvert

The bench mark is a disk set in a retaining wall located east of the Farmdale Fire Station, 10.98 m (36.0 ft) north of the NW corner of the building at 285 Maine Avenue, and 5.85 m (19.2 ft) SE of the centerline of the garage driveway.

BENCH MARK STAMPING: 7134 D 2005
DESIGNATION: 841 7134 D

MONUMENTATION: Tidal Station disk VM#: 17902
AGENCY: National Ocean Service (NOS) PID:
SETTING CLASSIFICATION: Concrete pad

The bench mark is a disk set in a concrete air conditioning unit foundation located along the east wall of the Home Care for Maine building at 357 Maine Avenue, 27.50 m (90.2 ft) north of the NE corner of the building, 7.80 m (25.6 ft) west of the fenceline, and 4.79 m (15.7 ft) south of the NE corner of the concrete pad.

Station ID: 8417134 **PUBLICATION DATE: 02/27/2006**
Name: GARDINER, KENNEBEC RIVER
MAINE
NOAA Chart: 13298 **Latitude: 44° 14.0' N**
USGS Quad: GARDINER **Longitude: 69° 46.0' W**

T I D A L D A T U M S

Tidal datums at GARDINER, KENNEBEC RIVER based on:

LENGTH OF SERIES: 1 MONTH
TIME PERIOD: September 2005
TIDAL EPOCH: 1983-2001
CONTROL TIDE STATION: 8418150 PORTLAND, CASCO BAY

Elevations of tidal datums referred to Mean Lower Low Water (MLLW), in METERS:

MEAN HIGHER HIGH WATER	MHHW	=	1.990
MEAN HIGH WATER	MHW	=	1.882
MEAN SEA LEVEL	MSL	=	1.025
MEAN TIDE LEVEL	MTL	=	0.974
MEAN LOW WATER	MLW	=	0.066
MEAN LOWER LOW WATER	MLLW	=	0.000

Bench Mark Elevation Information In METERS above:

Stamping or Designation	MLLW	MHW
7134 A 2005	8.381	6.499
7134 B 2005	4.682	2.800
7134 C 2005	9.487	7.605
7134 D 2005	8.435	6.553

Station ID: 8417134 **PUBLICATION DATE: 02/27/2006**
Name: GARDINER, KENNEBEC RIVER MAINE
NOAA Chart: 13298 **Latitude: 44° 14.0' N**
USGS Quad: GARDINER **Longitude: 69° 46.0' W**

D E F I N I T I O N S

Mean Sea Level (MSL) is a tidal datum determined over a 19-year National Tidal Datum Epoch. It pertains to local mean sea level and should not be confused with the fixed datums of North American Vertical Datum of 1988 (NAVD88).

NAVD88 is a fixed datum derived from a simultaneous, least squares, minimum constraint adjustment of Canadian/Mexican/United States leveling observations. Local mean sea level observed at Father Point/Rimouski, Canada was held fixed as the single initial constraint. NAVD88 replaces NGVD29 as the national standard geodetic reference for heights. Bench mark elevations relative to NAVD88 are available from NGS through the World Wide Web at National Geodetic Survey.

NGVD29 is a fixed datum adopted as a national standard geodetic reference for heights but is now considered superseded. NGVD29 is sometimes referred to as Sea Level Datum of 1929 or as Mean Sea Level on some early issues of Geological Survey Topographic Quads. NGVD29 was originally derived from a general adjustment of the first-order leveling networks of the U.S. and Canada after holding mean sea level observed at 26 long term tide stations as fixed. Numerous local and wide-spread adjustments have been made since establishment in 1929. Bench mark elevations relative to NGVD29 are available from the National Geodetic Survey (NGS) data base via the World Wide Web at National Geodetic Survey.

NAVD88 and NGVD29 are fixed geodetic datums whose elevation relationships to local MSL and other tidal datums may not be consistent from one location to another.

The Vertical Mark Number (VM#) and PID# shown on the bench mark sheet are unique identifiers for bench marks in the tidal and geodetic databases, respectively. Each bench mark in either database has a single, unique VM# and/or PID# assigned. Where both VM# and PID# are indicated, both tidal and geodetic elevations are available for the bench mark listed.

The NAVD88 elevation is shown on the Elevations of Tidal Datums Table Referred to MLLW only when two or more of the bench marks listed have NAVD88 elevations. The NAVD88 elevation relationship shown in the table is derived from an average of several bench mark elevations relative to tide station datum. As a result of this averaging, NAVD88 bench mark elevations computed indirectly from the tidal datums elevation table may differ slightly from NAVD88 elevations listed for each bench mark in the NGS database.

Project information		Coordinate System	
Name:	C:\pin\FARMINGDALE111111\11\SURVEY\Orig-Data\GARDINER BRIDGES 018736 018735 17 DEC 15.vce	Name:	US State Plane 1983
		Datum:	NAD 1983 (Conus)
Size:	100 KB	Zone:	Maine 2000 West
Modified:	12/17/2015 7:43:16 AM (UTC:-5)	Geoid:	GEOID12A (Conus)
Time zone:	Eastern Standard Time	Vertical datum:	
Reference number:			
Description:			


Point List


ID	Northing (US survey foot)	Easting (US survey foot)	Elevation (US survey foot)	Feature Code	Combined Scale Factor
7134B	514174.5142	1142674.4558	12.98	PTRA	1.0000120936
7134C	513649.5033	1142579.6096	28.84	PTRA	1.0000113024
7134D	515182.0207	1142678.4539	9.07	PTRA	1.0000122816
B31	515412.8733	1142704.2060	19.03	PTRA	1.0000118155
MEOW	533816.6886	1149086.1147	207.23	PCTL	1.0000051916

suspect

12/17/2015 8:05:00 AM	C:\pin\FARMINGDALE111111\11\SURVEY\Orig-Data\GARDINER BRIDGES 018736 018735 17 DEC 15.vce	Trimble Business Center

APPENDIX B / SCOUR CALCULATIONS





Hydraulic Design Data
Contraction Scour


	Left	Channel	Right
Input Data			
Average Depth (ft):	1.21	6.77	0.21
Approach Velocity (ft/s):	2.77	14.46	0.89
Br Average Depth (ft):	0.96	7.62	1.01
BR Opening Flow (cfs):	6.19	5850.29	53.52
BR Top WD (ft):	4.38	81.75	35.45
Grain Size D50 (mm):	2.4	2.4	2.4
Approach Flow (cfs):	13.51	5894.05	2.44
Approach Top WD (ft):	4.02	60.2	12.96
K1 Coefficient:	0.64	0.69	0.59
Results			
Scour Depth Ys (ft):	0	10.52	0
Critical Velocity (ft/s):			
Equation:	Clear	Clear	Clear


Abutment Scour

	Left	Right
Input Data		
Station at Toe (ft):	51.2	177.2
Toe Sta at appr (ft):	69.7	174.15
Abutment Length (ft):	4.02	12.96
Depth at Toe (ft):	-1.82	0.62
K1 Shape Coef:	1.00 - Vertical abutment	
Degree of Skew (degrees):	90	90
K2 Skew Coef:	1	1
Projected Length L' (ft):	4.02	12.96
Avg Depth Obstructed Ya (ft):	1.21	0.21
Flow Obstructed Qe (cfs):	13.51	2.44
Area Obstructed Ae (sq ft):	4.87	2.74
Results		
Scour Depth Ys (ft):	4.02	1.67
Qe/Ae = Ve:	2.77	0.89
Froude #:	0.44	0.34
Equation:	Froehlich	Froehlich

Combined Scour Depths

Left abutment scour + contraction scour (ft):	4.02
Right abutment scour + contraction scour (ft):	1.67





Hydraulic Design Data
Contraction Scour


	Left	Channel	Right
Input Data			
Average Depth (ft):	1.21	6.77	0.21
Approach Velocity (ft/s):	2.77	14.46	0.89
Br Average Depth (ft):	0.96	7.62	1.01
BR Opening Flow (cfs):	6.19	5850.29	53.52
BR Top WD (ft):	4.38	81.75	35.45
Grain Size D50 (mm):	2.4	2.4	2.4
Approach Flow (cfs):	13.51	5894.05	2.44
Approach Top WD (ft):	4.02	60.2	12.96
K1 Coefficient:	0.64	0.69	0.59
Results			
Scour Depth Ys (ft):	0	0	0.63
Critical Velocity (ft/s):			
Equation:	Live	Live	Live


Abutment Scour

	Left	Right
Input Data		
Station at Toe (ft):	51.2	177.2
Toe Sta at appr (ft):	69.7	174.15
Abutment Length (ft):	4.02	12.96
Depth at Toe (ft):	-1.82	0.62
K1 Shape Coef:	1.00 - Vertical abutment	
Degree of Skew (degrees):	90	90
K2 Skew Coef:	1	1
Projected Length L' (ft):	4.02	12.96
Avg Depth Obstructed Ya (ft):	1.21	0.21
Flow Obstructed Qe (cfs):	13.51	2.44
Area Obstructed Ae (sq ft):	4.87	2.74
Results		
Scour Depth Ys (ft):	4.02	1.67
Qe/Ae = Ve:	2.77	0.89
Froude #:	0.44	0.34
Equation:	Froehlich	Froehlich

Combined Scour Depths

Left abutment scour + contraction scour (ft):	4.02
Right abutment scour + contraction scour (ft):	2.3





Hydraulic Design Data

Contraction Scour


	Left	Channel	Right
Input Data			
Average D	1.94	8.23	0.94
Approach '	3.36	14.57	2.13
Br Average	1.52	8.74	2.13
BR Openin	20.64	7177.62	181.75
BR Top Wi	6.95	81.75	35.45
Grain Size	2	2	2
Approach	42.12	7221.43	116.44
Approach '	6.45	60.2	57.78
K1 Coeffici	0.64	0.69	0.64
Results			
Scour Dept	0	14.04	0
Critical Velocity (ft/s):			
Equation:	Clear	Clear	Clear


Abutment Scour

	Left	Right
Input Data		
Station at '	51.2	177.2
Toe Sta at	69.7	174.15
Abutment	6.45	57.78
Depth at T	-0.66	1.78
K1 Shape (	1.00 - Vertical abutment	
Degree of	90	90
K2 Skew C	1	1
Projected I	6.45	57.78
Avg Depth	1.94	0.94
Flow Obstr	42.12	116.44
Area Obstr	12.55	54.56
Results		
Scour Depth Ys (ft):		8.74
Froude #:		0.3
Equation:	Default	HIRE

Combined Scour Depths

Right abut	8.74






Hydraulic Design Data


Contraction Scour

	Left	Channel	Right
Input Data			
Average D	1.94	8.23	0.94
Approach '	3.36	14.57	2.13
Br Average	1.52	8.74	2.13
BR Openin	20.64	7177.62	181.75
BR Top WI	6.95	81.75	35.45
Grain Size	2	2	2
Approach	42.12	7221.43	116.44
Approach '	6.45	60.2	57.78
K1 Coeffici	0.64	0.69	0.64
Results			
Scour Dept	0	0	0
Critical Velocity (ft/s):			
Equation:	Live	Live	Live

Abutment Scour

	Left	Right
Input Data		
Station at '	51.2	177.2
Toe Sta at	69.7	174.15
Abutment	6.45	57.78
Depth at T	-0.66	1.78
K1 Shape C	1.00 - Vertical abutment	
Degree of	90	90
K2 Skew C	1	1
Projected I	6.45	57.78
Avg Depth	1.94	0.94
Flow Obstr	42.12	116.44
Area Obstr	12.55	54.56
Results		
Scour Depth Ys (ft):		8.74
Froude #:		0.3
Equation:	Default	HIRE





Hydraulic Design Data
Contraction Scour


	Left	Channel	Right
Input Data			
Average Depth (ft):		8.21	
Approach Velocity (ft/s):		10.46	
Br Average Depth (ft):		7.72	
BR Opening Flow (cfs):		5910	
BR Top WD (ft):		66.32	
Grain Size D50 (mm):	0.2	0.2	0.2
Approach Flow (cfs):		5910	
Approach Top WD (ft):		68.84	
K1 Coefficient:		0.69	
Results			
Scour Depth Ys (ft):		36.87	
Critical Velocity (ft/s):			
Equation:		Clear	


Abutment Scour

	Left	Right
Input Data		
Station at Toe (ft):	4.5	79.5
Toe Sta at appr (ft):	4.5	79.5
Abutment Length (ft):	0	0.48
Depth at Toe (ft):	-3.45	-0.72
K1 Shape Coef:	1.00 - Vertical abutment	
Degree of Skew (degrees):	90	90
K2 Skew Coef:	1	1
Projected Length L' (ft):	0	0.48
Avg Depth Obstructed Ya (ft):		8.21
Flow Obstructed Qe (cfs):		41.04
Area Obstructed Ae (sq ft):		3.92
Results		
Scour Depth Ys (ft):		12.41
Qe/Ae = Ve:		10.47
Froude #:		0.64
Equation:	Default	Froehlich

Combined Scour Depths

Right abutment scour + contraction scour (ft):	49.28





Hydraulic Design Data
Contraction Scour


	Left	Channel	Right
Input Data			
Average Depth (ft):		8.21	
Approach Velocity (ft/s):		10.46	
Br Average Depth (ft):		7.72	
BR Opening Flow (cfs):		5910	
BR Top WD (ft):		66.32	
Grain Size D50 (mm):	0.2	0.2	0.2
Approach Flow (cfs):		5910	
Approach Top WD (ft):		68.84	
K1 Coefficient:		0.69	
Results			
Scour Depth Ys (ft):		0.7	
Critical Velocity (ft/s):			
Equation:		Live	


Abutment Scour

	Left	Right
Input Data		
Station at Toe (ft):	4.5	79.5
Toe Sta at appr (ft):	4.5	79.5
Abutment Length (ft):	0	0.48
Depth at Toe (ft):	-3.45	-0.72
K1 Shape Coef:	1.00 - Vertical abutment	
Degree of Skew (degrees):	90	90
K2 Skew Coef:	1	1
Projected Length L' (ft):	0	0.48
Avg Depth Obstructed Ya (ft):		8.21
Flow Obstructed Qe (cfs):		41.04
Area Obstructed Ae (sq ft):		3.92
Results		
Scour Depth Ys (ft):		12.41
Qe/Ae = Ve:		10.47
Froude #:		0.64
Equation:	Default	Froehlich

Combined Scour Depths

Right abutment scour + contraction scour (ft):	13.12





Hydraulic Design Data

Contraction Scour


	Left	Channel	Right
Input Data			
Average De	0.44	9.45	0.37
Approach \	0.82	10.84	0.82
Br Average	0.55	9.19	
BR Openin	1.13	7378.87	
BR Top WE	1.94	69.5	
Grain Size	0.2	0.2	0.2
Approach I	0.52	7378.26	1.22
Approach '	1.46	72	4
K1 Coeffici	0.69	0.69	0.69
Results			
Scour Dept	0.05	42.63	
Critical Velocity (ft/s):			
Equation:	Clear	Clear	


Abutment Scour

	Left	Right
Input Data		
Station at '	4.5	79.5
Toe Sta at	4.5	79.5
Abutment	1.46	4.5
Depth at Te	-1.75	0.99
K1 Shape C	1.00 - Vertical abutment	
Degree of S	90	90
K2 Skew Co	1	1
Projected L	1.46	4.5
Avg Depth	0.44	1.38
Flow Obstr	0.52	52.46
Area Obstr	0.64	6.22
Results		
Scour Depth Ys (ft):		7.39
Qe/Ae = Ve:		8.43
Froude #:		1.27
Equation:	Default	Froehlich

Combined Scour Depths

Right abut	50.02





Hydraulic Design Data

Contraction Scour

	Left	Channel	Right
Input Data			
Average De	0.44	9.45	0.37
Approach \	0.82	10.84	0.82
Br Average	0.55	9.19	
BR Openin	1.13	7378.87	
BR Top WE	1.94	69.5	
Grain Size	0.2	0.2	0.2
Approach I	0.52	7378.26	1.22
Approach \	1.46	72	4
K1 Coeffici	0.69	0.69	0.69
Results			
Scour Dept	0.15	0.49	
Critical Velocity (ft/s):			
Equation:	Live	Live	

Abutment Scour


	Left	Right
Input Data		
Station at \	4.5	79.5
Toe Sta at	4.5	79.5
Abutment	1.46	4.5
Depth at Tc	-1.75	0.99
K1 Shape C	1.00 - Vertical abutment	
Degree of S	90	90
K2 Skew Cc	1	1
Projected L	1.46	4.5
Avg Depth	0.44	1.38
Flow Obstr	0.52	52.46
Area Obstr	0.64	6.22
Results		
Scour Depth Ys (ft):		7.39
Qe/Ae = Ve:		8.43
Froude #:		1.27
Equation:	Default	Froehlich

Combined Scour Depths

Right abut	7.89

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-104	Sample Type:	bag	Tested By:	GA
Sample ID:	2D	Test Date:	02/18/16	Checked By:	jdt
Depth :	2.0-4.0	Test Id:	365338		
Test Comment:	---				
Visual Description:	Moist, dark olive brown clayey sand				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	14.4	44.7	40.9

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
1.0 in	25.00	100		
0.75 in	19.00	94		
0.5 in	12.50	92		
0.375 in	9.50	89		
#4	4.75	86		
#10	2.00	79		
#20	0.85	70		
#40	0.42	63		
#60	0.25	56		
#100	0.15	50		
#200	0.075	41		

Coefficients

D_{85} = 4.4055 mm	D_{30} = N/A
D_{60} = 0.3440 mm	D_{15} = N/A
D_{50} = 0.1550 mm	D_{10} = N/A
C_u = N/A	C_c = N/A

Classification

ASTM N/A

AASHTO Silty Soils (A-4 (0))


Sample / Test Description

Sand/Gravel Particle Shape : ANGULAR

Sand/Gravel Hardness : HARD

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-104	Sample Type:	bag	Tested By:	GA
Sample ID:	3D	Test Date:	02/18/16	Checked By:	jdt
Depth :	4.0-6.0	Test Id:	365339		
Test Comment:	---				
Visual Description:	Moist, brown clayey sand				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	5.2	48.2	46.6

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
0.75 in	19.00	100		
0.5 in	12.50	99		
0.375 in	9.50	98		
#4	4.75	95		
#10	2.00	90		
#20	0.85	85		
#40	0.42	76		
#60	0.25	67		
#100	0.15	58		
#200	0.075	47		

Coefficients

D_{85} = 0.8564 mm D_{30} = N/A

D_{60} = 0.1688 mm D_{15} = N/A

D_{50} = 0.0921 mm D_{10} = N/A

C_u = N/A C_c = N/A

Classification

ASTM N/A

AASHTO Silty Soils (A-4 (0))


Sample / Test Description

Sand/Gravel Particle Shape : ANGULAR

Sand/Gravel Hardness : HARD

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-104	Sample Type:	bag	Tested By:	GA
Sample ID:	15D	Test Date:	02/18/16	Checked By:	jdt
Depth :	40.0-42.0	Test Id:	365340		
Test Comment:	---				
Visual Description:	Moist, dark gray silty sand				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	0.0	86.0	14.0

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
#4	4.75	100		
#10	2.00	100		
#20	0.85	100		
#40	0.42	99		
#60	0.25	75		
#100	0.15	38		
#200	0.075	14		

Coefficients

D_{85} = 0.3116 mm	D_{30} = 0.1202 mm
D_{60} = 0.2042 mm	D_{15} = 0.0773 mm
D_{50} = 0.1780 mm	D_{10} = N/A
C_u = N/A	C_c = N/A

Classification

ASTM N/A

AASHTO Silty Gravel and Sand (A-2-4 (0))

Sample / Test Description


Sand/Gravel Particle Shape : ---

Sand/Gravel Hardness : ---

printed 3/7/2016 3:23:30 PM

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-105	Sample Type:	bag	Tested By:	GA
Sample ID:	2D	Test Date:	02/18/16	Checked By:	jdt
Depth :	2.5-4.5	Test Id:	365341		
Test Comment:	---				
Visual Description:	Moist, olive brown clayey sand with gravel				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	20.7	48.1	31.2

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
0.5 in	12.50	100		
0.375 in	9.50	92		
#4	4.75	79		
#10	2.00	68		
#20	0.85	59		
#40	0.42	48		
#60	0.25	41		
#100	0.15	37		
#200	0.075	31		

Coefficients

D_{85} = 6.4389 mm D_{30} = N/A

D_{60} = 0.9551 mm D_{15} = N/A

D_{50} = 0.4719 mm D_{10} = N/A

C_u = N/A C_c = N/A

Classification

ASTM N/A

AASHTO Silty Gravel and Sand (A-2-4 (0))


Sample / Test Description

Sand/Gravel Particle Shape : ANGULAR

Sand/Gravel Hardness : HARD

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-105	Sample Type:	bag	Tested By:	GA
Sample ID:	3D	Test Date:	02/18/16	Checked By:	jdt
Depth :	4.5-6.5	Test Id:	365342		
Test Comment:	---				
Visual Description:	Moist, brown sand with silt and gravel				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	33.7	54.5	11.8

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
0.75 in	19.00	100		
0.5 in	12.50	85		
0.375 in	9.50	82		
#4	4.75	66		
#10	2.00	50		
#20	0.85	38		
#40	0.42	28		
#60	0.25	22		
#100	0.15	17		
#200	0.075	12		

Coefficients

D_{85} = 12.5175 mm D_{30} = 0.4890 mm

D_{60} = 3.3922 mm D_{15} = 0.1134 mm

D_{50} = 1.9879 mm D_{10} = N/A

C_u = N/A C_c = N/A

Classification

ASTM N/A

AASHTO Stone Fragments, Gravel and Sand (A-1-b (0))


Sample / Test Description

Sand/Gravel Particle Shape : ANGULAR

Sand/Gravel Hardness : HARD

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-105	Sample Type:	bag	Tested By:	GA
Sample ID:	14D	Test Date:	02/18/16	Checked By:	jdt
Depth :	35.5-37.5	Test Id:	365343		
Test Comment:	---				
Visual Description:	Moist, dark gray sandy clay				
Sample Comment:	---				

Particle Size Analysis - ASTM D422



% Cobble	% Gravel	% Sand	% Silt & Clay Size
—	0.0	37.5	62.5

Sieve Name	Sieve Size, mm	Percent Finer	Spec. Percent	Complies
#4	4.75	100		
#10	2.00	100		
#20	0.85	100		
#40	0.42	99		
#60	0.25	99		
#100	0.15	88		
#200	0.075	62		

Coefficients

D_{85} = 0.1396 mm D_{30} = N/A
D_{60} = N/A D_{15} = N/A
D_{50} = N/A D_{10} = N/A
C_u = N/A C_c = N/A

Classification

ASTM N/A

AASHTO Silty Soils (A-4 (0))

Sample / Test Description


Sand/Gravel Particle Shape : ---

Sand/Gravel Hardness : ---

printed 3/7/2016 3:23:32 PM

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-104	Sample Type:	bag	Tested By:	GA
Sample ID:	11D	Test Date:	02/18/16	Checked By:	jdt
Depth :	28.0-30.0	Test Id:	365355		
Test Comment:	---				
Visual Description:	Moist, dark gray clay				
Sample Comment:	---				

Atterberg Limits - ASTM D4318



Symbol	Sample ID	Boring	Depth	Natural Moisture Content, %	Liquid Limit	Plastic Limit	Plasticity Index	Liquidity Index	Soil Classification
◆	11D	B-GCS-10	28.0-30.0	33	38	18	20	0.7	

Sample Prepared using the WET method


Dry Strength: HIGH

Dilatancy: NONE

Toughness: MEDIUM

Client:	Haley & Aldrich, Inc.				
Project:	U.S. 24 over the Cobbossee Stream				
Location:	Gardiner, Maine			Project No:	GTX-304381
Boring ID:	BB-GCS-104	Sample Type:	bag	Tested By:	GA
Sample ID:	13D	Test Date:	02/18/16	Checked By:	jdt
Depth :	32.0-34.0	Test Id:	365356		
Test Comment:	---				
Visual Description:	Moist, dark gray clay				
Sample Comment:	---				

Atterberg Limits - ASTM D4318



Symbol	Sample ID	Boring	Depth	Natural Moisture Content, %	Liquid Limit	Plastic Limit	Plasticity Index	Liquidity Index	Soil Classification
◆	13D	B-GCS-10	32.0-34.0	29	36	17	19	0.6	

Sample Prepared using the WET method


Dry Strength: HIGH

Dilatancy: NONE

Toughness: MEDIUM

Client:	Haley & Aldrich, Inc.
Project Name:	U.S. 24 over the Cobbossee Stream
Project Location:	Gardiner, Maine
GTX #:	304381
Test Date:	2/15/2016
Tested By:	rlc
Checked By:	jsc
Boring ID:	BB-GCS-104
Sample ID:	R6
Depth, ft:	80.25-80.62
Sample Type:	rock core
Sample Description:	See photographs Discontinuity failure

Compressive Strength and Elastic Moduli of Rock by ASTM D7012 - Method D



Peak Compressive Stress: 4,721 psi

Both axial strain devices failed to record meaningful data. Young's Modulus and Poisson's Ratio could not be determined.

Stress Range, psi	Young's Modulus, psi	Poisson's Ratio
500-1700	---	---
1700-3000	---	---
3000-4200	---	---

Notes:
Test specimen tested at the approximate as-received moisture content and at standard laboratory temperature.
The axial load was applied continuously at a stress rate that produced failure in a test time between 2 and 15 minutes.
Young's Modulus and Poisson's Ratio calculated using the tangent to the line in the stress range listed.
Calculations assume samples are isotropic, which is not necessarily the case.

Client:	Haley & Aldrich, Inc.	Test Date:	2/12/2016
Project Name:	U.S. 24 over the Cobbossee Stream	Tested By:	daa/rlc
Project Location:	Gardiner, Maine	Checked By:	jsc
GTX #:	304381		
Boring ID:	BB-GCS-104		
Sample ID:	R6		
Depth:	80.25-80.62 ft		
Visual Description:	See photographs		

UNIT WEIGHT DETERMINATION AND DIMENSIONAL AND SHAPE TOLERANCES OF ROCK CORE SPECIMENS BY ASTM D4543

BULK DENSITY

	1	2	Average
Specimen Length, in:	4.33	4.33	4.33
Specimen Diameter, in:	1.98	1.98	1.98
Specimen Mass, g:	572.99		
Bulk Density, lb/ft^3	163	**Minimum Diameter Tolerence Met?**	YES
Length to Diameter Ratio:	2.2	**Length to Diameter Ratio Tolerance Met?**	YES

DEVIATION FROM STRAIGHTNESS (Procedure S1)

Maximum gap between side of core and reference surface plate:
Is the maximum gap ≤ 0.02 in.? YES

Maximum difference must be < 0.020 in.
Straightness Tolerance Met? YES

END FLATNESS AND PARALLELISM (Procedure FP1)


END 1	-0.875	-0.750	-0.625	-0.500	-0.375	-0.250	-0.125	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
Diameter 1, in	-0.00020	-0.00020	-0.00020	-0.00020	-0.00020	-0.00020	-0.00010	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000
Diameter 2, in (rotated 90°)	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000


Difference between max and min readings, in:
0° = 0.00020 90° = 0.00010


END 2	-0.875	-0.750	-0.625	-0.500	-0.375	-0.250	-0.125	0.000	0.125	0.250	0.375	0.500	0.625	0.750	0.875
Diameter 1, in	-0.00020	-0.00020	-0.00020	-0.00020	-0.00020	-0.00020	-0.00010	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00010	0.00010
Diameter 2, in (rotated 90°)	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	-0.00010	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000


Difference between max and min readings, in:
0° = 0.0003 90° = 0.0001

Maximum difference must be < 0.0020 in. Difference = ± 0.00015
Flatness Tolerance Met? YES









DIAMETER 1

End 1:
Slope of Best Fit Line 0.00016
Angle of Best Fit Line: 0.00917

End 2:
Slope of Best Fit Line 0.00019
Angle of Best Fit Line: 0.01089

Maximum Angular Difference: 0.00172

Parallelism Tolerance Met? YES
Spherically Seated

DIAMETER 2

End 1:
Slope of Best Fit Line 0.00008
Angle of Best Fit Line: 0.00458

End 2:
Slope of Best Fit Line 0.00008
Angle of Best Fit Line: 0.00458

Maximum Angular Difference: 0.00000

Parallelism Tolerance Met? YES
Spherically Seated

PERPENDICULARITY (Procedure P1) (Calculated from End Flatness and Parallelism measurements above)

END 1	Difference, Maximum and Minimum (in.)	Diameter (in.)	Slope	Angle°	Perpendicularity Tolerance Met?
Diameter 1, in	0.00020	1.980	0.00010	0.006	YES
Diameter 2, in (rotated 90°)	0.00010	1.980	0.00005	0.003	YES
END 2					
Diameter 1, in	0.00030	1.980	0.00015	0.009	YES
Diameter 2, in (rotated 90°)	0.00010	1.980	0.00005	0.003	YES

Maximum angle of departure must be ≤ 0.25°
Perpendicularity Tolerance Met? YES

Client:	Haley & Aldrich, Inc.
Project Name:	U.S. 24 over the Cobbossee Stream
Project Location:	Gardiner, Maine
GTX #:	304381
Test Date:	2/15/2016
Tested By:	daa/rlc
Checked By:	jsc
Boring ID:	BB-GCS-104
Sample ID:	R6
Depth, ft:	80.25-80.62



After cutting and grinding



After break

APPENDIX C / BANK PROTECTION REVETMENT CALCULATIONS

Embankment Protection Revetment Stone Sizing per HEC-23 (2009)

The EM-1601 equation can be used with uniform or gradually varying flow. Coefficients are included to account for the desired safety factor for design, specific gravity of the riprap stone, bank slope, and bendway character. The EM-1601 equation is:

$$d_{30} = y(S_f C_S C_V C_T)\left[\frac{(V_{des})}{\sqrt{K_1(S_g - 1)gy}}\right]^{2.5} \quad (4.1)$$

where:

d_{30} = Particle size for which 30% is finer by weight, ft (m)

y = Local depth of flow, ft (m)

S_f = Safety factor (must be > 1.0)

C_S = Stability coefficient (for blanket thickness = d_{100} or $1.5d_{50}$, whichever is greater, and uniformity ratio d_{85}/d_{15} = 1.7 to 5.2)
- = 0.30 for angular rock
- = 0.375 for rounded rock

C_V = Velocity distribution coefficient
- = 1.0 for straight channels or the inside of bends
- = 1.283 - 0.2log(R_c/W) for the outside of bends (1.0 for R_c/W > 26)
- = 1.25 downstream from concrete channels
- = 1.25 at the end of dikes

C_T = Blanket thickness coefficient given as a function of the uniformity ratio d_{85}/d_{15}. C_T = 1.0 is recommended because it is based on very limited data.

V_{des} = Characteristic velocity for design, defined as the depth-averaged velocity at a point 20% upslope from the toe of the revetment, ft/s (m/s)

For natural channels, $V_{des} = V_{avg}(1.74 - 0.52\log(R_c/W))$
$V_{des} = V_{avg}$ for $R_c/W > 26$

For trapezoidal channels, $V_{des} = V_{avg}(1.71 - 0.78\log(R_c/W))$
$V_{des} = V_{avg}$ for $R_c/W > 8$

V_{avg} = Channel cross-sectional average velocity, ft/s (m/s)

K_1 = Side slope correction factor

$$K_1 = \sqrt{1 - \left(\frac{\sin(\theta - 14^\circ)}{\sin(32^\circ)}\right)^{1.6}}$$

where: θ is the bank angle in degrees

R_c = Centerline radius of curvature of channel bend, ft (m)

W = Width of water surface at upstream end of channel bend, ft (m)

S_g = Specific gravity of riprap (usually taken as 2.65)


g = Acceleration due to gravity, 32.2 ft/s^2 (9.81 m/s^2)

135' span

at Q100


	Bridge St. bridge at 895 BR U	Maine Ave. bridge at 98.5 BR U
WSEL	11.6	7.56
min ch elev	2	-5
y	9.6	12.56
Sf	1.2	1.2
Cs	0.3	0.3
Cv	1	1
Ct	1	1
Vdes	10.7	11.55
Vavg	10.7	11.55
slope X:1	2	2
theta, rad	0.464	0.464
K1	0.871	0.871
Sg	2.65	2.65
g, ft/s2	32.2	32.2
d30, ft	0.63	0.72
d50=1.2*d30, ft	**0.76**	**0.86**


APPENDIX D / HEC-RAS RESULTS FOR EXISTING CONDITIONS AT MLW





EXISTING PLAN, HEC-RAS SECTIONS
MLW RUN


None of the XS's are Geo-Referenced (, Geo-Ref user entered XS , Geo-Ref interpolated XS , Non Geo-Ref user entered XS , Non Geo-Ref interpolated XS)



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
Cobosee Stream Reach 1
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
Ground
Elevation (ft)
Main Channel Distance (ft)
30
25
20
15
10
5
0
-5
-10
-500
0
500
1000
1500
2000



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1700 Upstream (I)
.07
.04
.065
Elevation (ft)
Station (ft)
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
180
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1635 H
.07
.045
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1555 G
.07
.042
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1455 F
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1335 E
.065
.045
.075
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1185 D
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1060 C
.065
.04
.07
Elevation (ft)
Station (ft)
35
30
25
20
15
10
5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 960 B
.07
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q100
WS Q50
WS Q500
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 935 JU
.065
.042
.07
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 895 BR Bridge Street
.065
.042
.07
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 895 BR Bridge Street
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 850 JD
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 830 A
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 821 AD
.065
.035
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 820 ADD
.065
.035
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 725 10
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 575 9
.065
.04
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 425 8
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 335 7
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 262 6
.04
.065
.0
6
5
Elevation (ft)
Station (ft)
14
12
10
8
6
4
2
0
-2
-4
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 187 5
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 137 4
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
15
10
5
0
-5
0
20
40
60
80
100
Station (ft)
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 60 3
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 38 2
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
10
20
30
40
50
60
70
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 0 1 (Downstream)
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -21 RR
.065
.04
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q10
WS Q100
WS Q50
WS Q25
WS Q1.1
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -54 K2
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q50
WS Q25
WS Q10
WS Q500
WS Q100
WS Q1.1
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
22 ft/s
24 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -88 K1
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -143 K0
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta

HEC-RAS Version 4.1.0 Jan 2010
U.S. Army Corps of Engineers
Hydrologic Engineering Center
609 Second Street
Davis, California

```
X     X  XXXXXX    XXXX        XXXX       XX      XXXX
X     X  X        X    X       X   X     X  X    X
X     X  X        X            X   X    X    X   X
XXXXXXX  XXXX     X       XXX  XXXX     XXXXXX    XXXX
X     X  X        X            X  X     X    X        X
X     X  X        X    X       X   X    X    X        X
X     X  XXXXXX    XXXX        X    X   X    X   XXXXX
```

PROJECT DATA
Project Title: Gardiner Existing
Project File : Existing.prj
Run Date and Time: 4/18/2018 2:02:58 PM

Project in English units

PLAN DATA

Plan Title: Plan 21
Plan File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.p21

Geometry Title: Geom 01
Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.g01

Flow Title : MLW -2.1 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.f01

Plan Summary Information:
Number of: Cross Sections = 27 Multiple Openings = 0
Culverts = 0 Inline Structures = 0
Bridges = 2 Lateral Structures = 0

Computational Information
Water surface calculation tolerance = 0.01
Critical depth calculation tolerance = 0.01

Maximum number of iterations = 20
Maximum difference tolerance = 0.3
Flow tolerance factor = 0.001

Computation Options
Critical depth computed only where necessary
Conveyance Calculation Method: At breaks in n values only
Friction Slope Method: Average Conveyance
Computational Flow Regime: Mixed Flow

FLOW DATA

Flow Title: MLW -2.1 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.f01

Flow Data (cfs)

River	Reach	RS	Q100	Q1.1	Q10	Q25	Q50	Q500
Cobosee Stream	Reach 1	1700	5910	1312	3850	4148	5290	7380
Cobosee Stream	Reach 1	-88	5910	1312	3850	4148	5290	7380

Boundary Conditions

River	Reach	Profile	Upstream	Downstream
Cobosee Stream	Reach 1	Q100	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q1.1	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q10	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q25	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q50	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q500	Critical	Known WS = -2.1

GEOMETRY DATA

Geometry Title: Geom 01
Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.g01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1700

INPUT
Description: Upstream (I)
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	40	10	39.7	20	39.2	30	37.2	40	34.5
50	29	60	23.5	70	17.5	80	15.5	90	14.5
100	13.8	110	14.2	120	14.8	130	15.7	140	19
150	25	160	31	170	33.3				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	60	.04	150	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
60	150	65	65	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	24.48	Element			
Vel Head (ft)	1.73	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.75	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	21.32	Flow Area (sq ft)		559.56	
E.G. Slope (ft/ft)	0.006899	Area (sq ft)		559.56	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	84.99	Top Width (ft)		84.99	
Vel Total (ft/s)	10.56	Avg. Vel. (ft/s)		10.56	
Max Chl Dpth (ft)	8.95	Hydr. Depth (ft)		6.58	
Conv. Total (cfs)	71152.0	Conv. (cfs)		71152.0	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		88.36	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.73	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.08	25.43	1.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.07	3.56	1.24

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	19.04	Element			
Vel Head (ft)	0.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	18.54	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	17.33	Flow Area (sq ft)		231.75	
E.G. Slope (ft/ft)	0.004837	Area (sq ft)		231.75	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	

Top Width (ft)	70.35	Top Width (ft)		70.35	
Vel Total (ft/s)	5.66	Avg. Vel. (ft/s)		5.66	
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)		3.29	
Conv. Total (cfs)	18865.3	Conv. (cfs)		18865.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		71.44	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		0.98	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.51	Cum Volume (acre-ft)	0.00	8.07	
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	2.70	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	22.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.15	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	19.81	Flow Area (sq ft)		428.08	
E.G. Slope (ft/ft)	0.006488	Area (sq ft)		428.08	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	79.67	Top Width (ft)		79.67	
Vel Total (ft/s)	8.99	Avg. Vel. (ft/s)		8.99	
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	47797.3	Conv. (cfs)		47797.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		82.15	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.11	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.01	17.91	0.02
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.29	0.04

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.73	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.33	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.40	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.05	Flow Area (sq ft)		447.72	
E.G. Slope (ft/ft)	0.006586	Area (sq ft)		447.72	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	80.49	Top Width (ft)		80.49	
Vel Total (ft/s)	9.26	Avg. Vel. (ft/s)		9.26	
Max Chl Dpth (ft)	7.60	Hydr. Depth (ft)		5.56	
Conv. Total (cfs)	51113.1	Conv. (cfs)		51113.1	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		83.10	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.01	18.98	0.03

C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.35	0.05

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.28	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.89	Flow Area (sq ft)		519.99	
E.G. Slope (ft/ft)	0.006865	Area (sq ft)		519.99	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	83.43	Top Width (ft)		83.43	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	63848.2	Conv. (cfs)		63848.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		86.53	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.04	23.27	0.33
C & E Loss (ft)	0.00	Cum SA (acres)	0.04	3.53	0.54

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.00	Wt. n-Val.	0.070	0.040	
W.S. Elev (ft)	23.79	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	22.27	Flow Area (sq ft)	0.08	649.66	
E.G. Slope (ft/ft)	0.006886	Area (sq ft)	0.08	649.66	
Q Total (cfs)	7380.00	Flow (cfs)	0.03	7379.97	
Top Width (ft)	88.50	Top Width (ft)	0.52	87.98	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	0.44	11.36	
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	0.14	7.38	
Conv. Total (cfs)	88934.8	Conv. (cfs)	0.4	88934.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)	0.60	91.84	
Min Ch El (ft)	13.80	Shear (lb/sq ft)	0.05	3.04	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.50	Cum Volume (acre-ft)	0.25	30.45	4.08
C & E Loss (ft)	0.03	Cum SA (acres)	0.14	3.60	2.01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1635

INPUT
Description: H

Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	23.5	40	17
50	14	60	14.5	70	15	80	15.2	90	15.4
100	15.6	110	15.8	115	17.9	120	20	130	26.5
140	30.1	150	30.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.045	130	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	130	80	80	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	23.95	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.69	Wt. n-Val.		0.045	
W.S. Elev (ft)	22.26	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		565.74	
E.G. Slope (ft/ft)	0.009286	Area (sq ft)		565.74	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	91.56	Top Width (ft)		91.56	
Vel Total (ft/s)	10.45	Avg. Vel. (ft/s)		10.45	
Max Chl Dpth (ft)	8.26	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	61329.1	Conv. (cfs)		61329.1	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		95.11	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.45	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.90	Cum Volume (acre-ft)	0.08	24.59	1.04
C & E Loss (ft)	0.09	Cum SA (acres)	0.07	3.42	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	18.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		181.92	
E.G. Slope (ft/ft)	0.015059	Area (sq ft)		181.92	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	75.56	Top Width (ft)		75.56	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	10691.3	Conv. (cfs)		10691.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		76.62	

Min Ch El (ft)	14.00	Shear (lb/sq ft)		2.23	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.04	Cum Volume (acre-ft)	0.00	7.77	
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	2.60	

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	21.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.47	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		407.41	
E.G. Slope (ft/ft)	0.010706	Area (sq ft)		407.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	86.07	Top Width (ft)		86.07	
Vel Total (ft/s)	9.45	Avg. Vel. (ft/s)		9.45	
Max Chl Dpth (ft)	6.47	Hydr. Depth (ft)		4.73	
Conv. Total (cfs)	37209.8	Conv. (cfs)		37209.8	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		88.57	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.07	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.01	17.29	0.02
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	3.16	0.04

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.44	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		431.49	
E.G. Slope (ft/ft)	0.010420	Area (sq ft)		431.49	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	86.93	Top Width (ft)		86.93	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	6.75	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	40635.0	Conv. (cfs)		40635.0	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		89.59	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.13	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.01	18.32	0.03
C & E Loss (ft)	0.05	Cum SA (acres)	0.01	3.23	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.36	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.045	
W.S. Elev (ft)	21.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		520.12	
E.G. Slope (ft/ft)	0.009593	Area (sq ft)		520.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	90.01	Top Width (ft)		90.01	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	7.75	Hydr. Depth (ft)		5.78	
Conv. Total (cfs)	54011.4	Conv. (cfs)		54011.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		93.26	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.91	Cum Volume (acre-ft)	0.04	22.49	0.33
C & E Loss (ft)	0.08	Cum SA (acres)	0.04	3.40	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.89	Wt. n-Val.		0.045	
W.S. Elev (ft)	23.37	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		669.19	
E.G. Slope (ft/ft)	0.008749	Area (sq ft)		669.19	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	94.97	Top Width (ft)		94.97	
Vel Total (ft/s)	11.03	Avg. Vel. (ft/s)		11.03	
Max Chl Dpth (ft)	9.37	Hydr. Depth (ft)		7.05	
Conv. Total (cfs)	78901.8	Conv. (cfs)		78901.8	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		99.18	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)	0.25	29.47	4.08
C & E Loss (ft)	0.11	Cum SA (acres)	0.14	3.46	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream

REACH: Reach 1 RS: 1555

INPUT
Description: G
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	21.5	40	15
50	13.8	60	13.6	70	13.3	80	13.5	90	13.5
100	14.5	110	19	120	26	130	29	140	29.5
150	29.9								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.042	120	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	120	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	22.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.62	Wt. n-Val.		0.042	
W.S. Elev (ft)	20.34	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	20.16	Flow Area (sq ft)		455.10	
E.G. Slope (ft/ft)	0.013988	Area (sq ft)		455.10	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	80.13	Top Width (ft)		80.13	
Vel Total (ft/s)	12.99	Avg. Vel. (ft/s)		12.99	
Max Chl Dpth (ft)	7.04	Hydr. Depth (ft)		5.68	
Conv. Total (cfs)	49970.8	Conv. (cfs)		49970.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		83.23	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.77	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.37	Cum Volume (acre-ft)	0.08	23.65	1.04
C & E Loss (ft)	0.07	Cum SA (acres)	0.07	3.27	1.24

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	17.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.042	
W.S. Elev (ft)	16.65	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)		Flow Area (sq ft)		181.93	
E.G. Slope (ft/ft)	0.011277	Area (sq ft)		181.93	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	67.33	Top Width (ft)		67.33	

Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.35	Hydr. Depth (ft)		2.70	
Conv. Total (cfs)	12355.1	Conv. (cfs)		12355.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.41	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		1.87	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.00	7.43	
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	2.46	

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	20.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.06	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.65	Flow Area (sq ft)		355.06	
E.G. Slope (ft/ft)	0.012591	Area (sq ft)		355.06	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.34	Top Width (ft)		76.34	
Vel Total (ft/s)	10.84	Avg. Vel. (ft/s)		10.84	
Max Chl Dpth (ft)	5.76	Hydr. Depth (ft)		4.65	
Conv. Total (cfs)	34310.2	Conv. (cfs)		34310.2	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		78.66	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.55	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.01	16.59	0.02
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	3.01	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	21.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.96	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.89	Flow Area (sq ft)		368.78	
E.G. Slope (ft/ft)	0.013022	Area (sq ft)		368.78	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	76.87	Top Width (ft)		76.87	
Vel Total (ft/s)	11.25	Avg. Vel. (ft/s)		11.25	
Max Chl Dpth (ft)	5.94	Hydr. Depth (ft)		4.80	
Conv. Total (cfs)	36350.1	Conv. (cfs)		36350.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		79.30	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.78	

Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.01	17.59	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.08	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	22.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.41	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.96	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	19.73	Flow Area (sq ft)		424.40	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		424.40	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	78.99	Top Width (ft)		78.99	
Vel Total (ft/s)	12.46	Avg. Vel. (ft/s)		12.46	
Max Chl Dpth (ft)	6.66	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	44978.8	Conv. (cfs)		44978.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		81.85	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.48	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.04	21.62	0.33
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	3.24	0.54

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	24.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.03	Wt. n-Val.		0.042	
W.S. Elev (ft)	21.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	21.12	Flow Area (sq ft)		528.58	
E.G. Slope (ft/ft)	0.013932	Area (sq ft)		528.58	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	82.81	Top Width (ft)		82.81	
Vel Total (ft/s)	13.96	Avg. Vel. (ft/s)		13.96	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)		6.38	
Conv. Total (cfs)	62523.5	Conv. (cfs)		62523.5	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		86.46	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		5.32	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.25	28.37	4.08
C & E Loss (ft)	0.13	Cum SA (acres)	0.14	3.30	2.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1455

INPUT
Description: F
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	45	10	38	20	31	30	24	40	16.5
50	12.5	60	11.8	70	12	80	12.3	90	12.6
100	12.8	110	14	120	18.5	130	23	140	28
150	30								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	120	120	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	21.52	Element			
Vel Head (ft)	2.37	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	19.15	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.73	Flow Area (sq ft)	4.67	476.75	0.46
E.G. Slope (ft/ft)	0.013387	Area (sq ft)	4.67	476.75	0.46
Q Total (cfs)	5910.00	Flow (cfs)	12.83	5896.66	0.51
Top Width (ft)	84.97	Top Width (ft)	3.53	80.00	1.44
Vel Total (ft/s)	12.26	Avg. Vel. (ft/s)	2.75	12.37	1.09
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)	1.32	5.96	0.32
Conv. Total (cfs)	51079.8	Conv. (cfs)	110.9	50964.5	4.4
Length Wtd. (ft)	120.00	Wetted Per. (ft)	4.41	81.85	1.58
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.88	4.87	0.25
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.08	22.58	1.04
C & E Loss (ft)	0.17	Cum SA (acres)	0.07	3.08	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	16.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.06	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	14.87	Flow Area (sq ft)		165.73	
E.G. Slope (ft/ft)	0.018077	Area (sq ft)		165.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	68.77	Top Width (ft)		68.77	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	3.26	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	9758.1	Conv. (cfs)		9758.1	
Length Wtd. (ft)	120.00	Wetted Per. (ft)		69.60	
Min Ch El (ft)	11.80	Shear (lb/sq ft)		2.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	2.24	Cum Volume (acre-ft)	0.00	7.03	
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	2.31	

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
         This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.01	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.40	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.28	Flow Area (sq ft)	0.54	338.37	
E.G. Slope (ft/ft)	0.017110	Area (sq ft)	0.54	338.37	
Q Total (cfs)	3850.00	Flow (cfs)	0.82	3849.18	
Top Width (ft)	78.76	Top Width (ft)	1.20	77.56	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	1.51	11.38	
Max Chl Dpth (ft)	5.60	Hydr. Depth (ft)	0.45	4.36	
Conv. Total (cfs)	29432.7	Conv. (cfs)	6.3	29426.5	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.50	79.17	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.38	4.57	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.01	15.79	0.02
C & E Loss (ft)	0.13	Cum SA (acres)	0.01	2.84	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
         This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	19.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.07	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.67	Reach Len. (ft)	120.00	120.00	120.00

Crit W.S. (ft)	17.49	Flow Area (sq ft)	0.91	359.10	
E.G. Slope (ft/ft)	0.016462	Area (sq ft)	0.91	359.10	
Q Total (cfs)	4148.00	Flow (cfs)	1.60	4146.40	
Top Width (ft)	79.70	Top Width (ft)	1.56	78.15	
Vel Total (ft/s)	11.52	Avg. Vel. (ft/s)	1.76	11.55	
Max Chl Dpth (ft)	5.87	Hydr. Depth (ft)	0.58	4.60	
Conv. Total (cfs)	32328.9	Conv. (cfs)	12.5	32316.5	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.94	79.81	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.48	4.62	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.53	Cum Volume (acre-ft)	0.01	16.75	0.03
C & E Loss (ft)	0.14	Cum SA (acres)	0.01	2.90	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	20.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.27	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	18.65	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.33	Flow Area (sq ft)	3.07	436.72	0.02
E.G. Slope (ft/ft)	0.014390	Area (sq ft)	3.07	436.72	0.02
Q Total (cfs)	5290.00	Flow (cfs)	7.61	5282.38	0.01
Top Width (ft)	83.19	Top Width (ft)	2.86	80.00	0.33
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	2.48	12.10	0.42
Max Chl Dpth (ft)	6.85	Hydr. Depth (ft)	1.07	5.46	0.07
Conv. Total (cfs)	44098.1	Conv. (cfs)	63.4	44034.6	0.1
Length Wtd. (ft)	120.00	Wetted Per. (ft)	3.58	81.85	0.36
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.77	4.79	0.06
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.34	Cum Volume (acre-ft)	0.04	20.64	0.33
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	3.06	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	22.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.58	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	20.29	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)		Flow Area (sq ft)	9.55	567.83	3.54
E.G. Slope (ft/ft)	0.011588	Area (sq ft)	9.55	567.83	3.54
Q Total (cfs)	7380.00	Flow (cfs)	31.00	7341.95	7.06

Top Width (ft)	89.01	Top Width (ft)	5.05	80.00	3.97
Vel Total (ft/s)	12.70	Avg. Vel. (ft/s)	3.24	12.93	1.99
Max Chl Dpth (ft)	8.49	Hydr. Depth (ft)	1.89	7.10	0.89
Conv. Total (cfs)	68558.4	Conv. (cfs)	288.0	68204.9	65.5
Length Wtd. (ft)	120.00	Wetted Per. (ft)	6.31	81.85	4.35
Min Ch El (ft)	11.80	Shear (lb/sq ft)	1.10	5.02	0.59
Alpha	1.03	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.24	27.11	4.08
C & E Loss (ft)	0.18	Cum SA (acres)	0.14	3.11	2.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1335

INPUT
Description: E
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	42.5	10	37.5	20	31	30	24	40	17
50	11	60	9.5	70	9.5	80	9.5	90	9.5
100	10.5	110	14	120	19	130	23	140	28
150	29	160	30						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.075

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	20.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.80	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	18.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.18	548.37	
E.G. Slope (ft/ft)	0.008451	Area (sq ft)	1.18	548.37	
Q Total (cfs)	5910.00	Flow (cfs)	1.62	5908.38	
Top Width (ft)	80.41	Top Width (ft)	1.84	78.57	
Vel Total (ft/s)	10.75	Avg. Vel. (ft/s)	1.37	10.77	
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	0.64	6.98	

Conv. Total (cfs)	64289.9	Conv. (cfs)	17.6	64272.3	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.24	82.00	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.28	3.53	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.56	Cum Volume (acre-ft)	0.07	21.17	1.04
C & E Loss (ft)	0.09	Cum SA (acres)	0.06	2.86	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	13.78	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.14	Wt. n-Val.		0.045	
W.S. Elev (ft)	12.63	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)		152.88	
E.G. Slope (ft/ft)	0.019322	Area (sq ft)		152.88	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	58.82	Top Width (ft)		58.82	
Vel Total (ft/s)	8.58	Avg. Vel. (ft/s)		8.58	
Max Chl Dpth (ft)	3.13	Hydr. Depth (ft)		2.60	
Conv. Total (cfs)	9438.7	Conv. (cfs)		9438.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		59.79	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.08	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.87	Cum Volume (acre-ft)	0.00	6.59	
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	2.13	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	17.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.56	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.13	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		384.19	
E.G. Slope (ft/ft)	0.010520	Area (sq ft)		384.19	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	72.81	Top Width (ft)		72.81	
Vel Total (ft/s)	10.02	Avg. Vel. (ft/s)		10.02	
Max Chl Dpth (ft)	6.63	Hydr. Depth (ft)		5.28	
Conv. Total (cfs)	37536.7	Conv. (cfs)		37536.7	

Length Wtd. (ft)	150.00	Wetted Per. (ft)		75.49	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.65	Cum Volume (acre-ft)	0.01	14.80	0.02
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	2.63	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	18.07	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.47	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		409.60	
E.G. Slope (ft/ft)	0.010117	Area (sq ft)		409.60	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	74.07	Top Width (ft)		74.07	
Vel Total (ft/s)	10.13	Avg. Vel. (ft/s)		10.13	
Max Chl Dpth (ft)	6.97	Hydr. Depth (ft)		5.53	
Conv. Total (cfs)	41238.9	Conv. (cfs)		41238.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		76.93	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.36	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.64	Cum Volume (acre-ft)	0.01	15.69	0.03
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	2.69	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.34	501.69	
E.G. Slope (ft/ft)	0.008914	Area (sq ft)	0.34	501.69	
Q Total (cfs)	5290.00	Flow (cfs)	0.31	5289.69	
Top Width (ft)	78.36	Top Width (ft)	0.98	77.37	
Vel Total (ft/s)	10.54	Avg. Vel. (ft/s)	0.93	10.54	
Max Chl Dpth (ft)	8.19	Hydr. Depth (ft)	0.34	6.48	
Conv. Total (cfs)	56029.0	Conv. (cfs)	3.3	56025.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.20	80.66	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.16	3.46	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.03	19.34	0.33
C & E Loss (ft)	0.08	Cum SA (acres)	0.03	2.84	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	21.58	Element			
Vel Head (ft)	1.97	Wt. n-Val.	0.065	0.045	0.075
W.S. Elev (ft)	19.61	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.86	653.69	0.46
E.G. Slope (ft/ft)	0.007511	Area (sq ft)	4.86	653.69	0.46
Q Total (cfs)	7380.00	Flow (cfs)	10.06	7369.59	0.34
Top Width (ft)	85.25	Top Width (ft)	3.73	80.00	1.52
Vel Total (ft/s)	11.20	Avg. Vel. (ft/s)	2.07	11.27	0.74
Max Chl Dpth (ft)	10.11	Hydr. Depth (ft)	1.30	8.17	0.30
Conv. Total (cfs)	85155.0	Conv. (cfs)	116.1	85034.9	3.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.55	83.60	1.64
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.50	3.67	0.13
Alpha	1.01	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.52	Cum Volume (acre-ft)	0.22	25.42	4.07
C & E Loss (ft)	0.14	Cum SA (acres)	0.13	2.89	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1185

INPUT
Description: D
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	41.5	4	40	10	35	20	27.5	30	20
35	16	40	12	50	7	60	5.5	70	6
80	7	90	11	100	16	110	22	120	28
130	28.2								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	35	.045	110	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
35	110	125	125	125	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	18.44	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.70	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.74	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	15.05	Flow Area (sq ft)		448.42	
E.G. Slope (ft/ft)	0.013066	Area (sq ft)		448.42	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	64.17	Top Width (ft)		64.17	
Vel Total (ft/s)	13.18	Avg. Vel. (ft/s)		13.18	
Max Chl Dpth (ft)	10.24	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	51703.8	Conv. (cfs)		51703.8	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		68.72	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		5.32	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.68	Cum Volume (acre-ft)	0.06	19.45	1.04
C & E Loss (ft)	0.05	Cum SA (acres)	0.06	2.62	1.24

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	11.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.82	Wt. n-Val.		0.045	
W.S. Elev (ft)	10.99	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)		Flow Area (sq ft)		180.57	
E.G. Slope (ft/ft)	0.008702	Area (sq ft)		180.57	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.96	Top Width (ft)		47.96	
Vel Total (ft/s)	7.27	Avg. Vel. (ft/s)		7.27	
Max Chl Dpth (ft)	5.49	Hydr. Depth (ft)		3.77	
Conv. Total (cfs)	14064.1	Conv. (cfs)		14064.1	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		49.84	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		1.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.49	Cum Volume (acre-ft)	0.00	6.02	
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	1.95	

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	16.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.08	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.16	Flow Area (sq ft)		346.47	
E.G. Slope (ft/ft)	0.011509	Area (sq ft)		346.47	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	58.78	Top Width (ft)		58.78	
Vel Total (ft/s)	11.11	Avg. Vel. (ft/s)		11.11	
Max Chl Dpth (ft)	8.58	Hydr. Depth (ft)		5.89	
Conv. Total (cfs)	35888.0	Conv. (cfs)		35888.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		62.36	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		3.99	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.62	Cum Volume (acre-ft)	0.01	13.54	0.02
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	2.40	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	16.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.04	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.34	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.46	Flow Area (sq ft)		361.81	
E.G. Slope (ft/ft)	0.011809	Area (sq ft)		361.81	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	59.62	Top Width (ft)		59.62	
Vel Total (ft/s)	11.46	Avg. Vel. (ft/s)		11.46	
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		6.07	
Conv. Total (cfs)	38171.0	Conv. (cfs)		38171.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		63.35	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.21	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.63	Cum Volume (acre-ft)	0.01	14.37	0.03
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	2.46	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.

This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	17.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.48	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.27	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	14.52	Flow Area (sq ft)		418.21	
E.G. Slope (ft/ft)	0.012741	Area (sq ft)		418.21	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	62.62	Top Width (ft)		62.62	
Vel Total (ft/s)	12.65	Avg. Vel. (ft/s)		12.65	
Max Chl Dpth (ft)	9.77	Hydr. Depth (ft)		6.68	
Conv. Total (cfs)	46865.0	Conv. (cfs)		46865.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		66.90	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.66	Cum Volume (acre-ft)	0.03	17.76	0.33
C & E Loss (ft)	0.05	Cum SA (acres)	0.03	2.60	0.54

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	19.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.33	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	16.59	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	16.20	Flow Area (sq ft)	0.22	503.78	
E.G. Slope (ft/ft)	0.014396	Area (sq ft)	0.22	503.78	
Q Total (cfs)	7380.00	Flow (cfs)	0.23	7379.77	
Top Width (ft)	66.73	Top Width (ft)	0.74	65.99	
Vel Total (ft/s)	14.64	Avg. Vel. (ft/s)	1.03	14.65	
Max Chl Dpth (ft)	11.09	Hydr. Depth (ft)	0.30	7.63	
Conv. Total (cfs)	61508.4	Conv. (cfs)	1.9	61506.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)	0.95	70.86	
Min Ch El (ft)	5.50	Shear (lb/sq ft)	0.21	6.39	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.73	Cum Volume (acre-ft)	0.21	23.43	4.07
C & E Loss (ft)	0.02	Cum SA (acres)	0.12	2.64	1.99

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1060

INPUT
Description: C
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	33	20	35	30	29	40	23
45	19.5	50	16	60	10	70	7	80	5.5
90	5	100	5	110	7	120	13	130	20
200	20.1								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	45	.04	130	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
45	130	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	16.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.15	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.57	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.57	Flow Area (sq ft)		415.00	
E.G. Slope (ft/ft)	0.013789	Area (sq ft)		415.00	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	66.76	Top Width (ft)		66.76	
Vel Total (ft/s)	14.24	Avg. Vel. (ft/s)		14.24	
Max Chl Dpth (ft)	8.57	Hydr. Depth (ft)		6.22	
Conv. Total (cfs)	50329.3	Conv. (cfs)		50329.3	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		70.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.08	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.07	Cum Volume (acre-ft)	0.06	18.21	1.04
C & E Loss (ft)	0.26	Cum SA (acres)	0.06	2.43	1.24

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.41	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.85	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	8.85	Flow Area (sq ft)		137.48	
E.G. Slope (ft/ft)	0.017292	Area (sq ft)		137.48	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	49.24	Top Width (ft)		49.24	
Vel Total (ft/s)	9.54	Avg. Vel. (ft/s)		9.54	
Max Chl Dpth (ft)	3.85	Hydr. Depth (ft)		2.79	
Conv. Total (cfs)	9977.1	Conv. (cfs)		9977.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		50.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		2.95	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.28	Cum Volume (acre-ft)	0.00	5.56	
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	1.81	

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	14.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	11.81	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	11.81	Flow Area (sq ft)		302.66	
E.G. Slope (ft/ft)	0.014662	Area (sq ft)		302.66	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.04	Top Width (ft)		61.04	
Vel Total (ft/s)	12.72	Avg. Vel. (ft/s)		12.72	
Max Chl Dpth (ft)	6.81	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	31795.8	Conv. (cfs)		31795.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		63.64	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.35	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.12	Cum Volume (acre-ft)	0.01	12.61	0.02
C & E Loss (ft)	0.26	Cum SA (acres)	0.00	2.23	0.04

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	14.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	12.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	12.10	Flow Area (sq ft)		320.59	
E.G. Slope (ft/ft)	0.014382	Area (sq ft)		320.59	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.01	Top Width (ft)		62.01	
Vel Total (ft/s)	12.94	Avg. Vel. (ft/s)		12.94	
Max Chl Dpth (ft)	7.10	Hydr. Depth (ft)		5.17	
Conv. Total (cfs)	34588.7	Conv. (cfs)		34588.7	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		64.77	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.44	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.10	Cum Volume (acre-ft)	0.01	13.39	0.03
C & E Loss (ft)	0.26	Cum SA (acres)	0.01	2.29	0.05

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	16.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.10	Flow Area (sq ft)		384.11	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		384.11	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.31	Top Width (ft)		65.31	
Vel Total (ft/s)	13.77	Avg. Vel. (ft/s)		13.77	
Max Chl Dpth (ft)	8.10	Hydr. Depth (ft)		5.88	
Conv. Total (cfs)	44979.7	Conv. (cfs)		44979.7	

Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.63	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.83	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.07	Cum Volume (acre-ft)	0.03	16.61	0.33
C & E Loss (ft)	0.25	Cum SA (acres)	0.03	2.42	0.54

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	18.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	14.68	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	14.68	Flow Area (sq ft)		490.87	
E.G. Slope (ft/ft)	0.013247	Area (sq ft)		490.87	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	70.19	Top Width (ft)		70.19	
Vel Total (ft/s)	15.03	Avg. Vel. (ft/s)		15.03	
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	64121.8	Conv. (cfs)		64121.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		74.44	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.45	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.05	Cum Volume (acre-ft)	0.21	22.00	4.07
C & E Loss (ft)	0.25	Cum SA (acres)	0.12	2.45	1.99

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 960

INPUT
Description: B
Station Elevation Data num= 21

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	32	13.6	31	22.5	30	33.1	28	54.2	20
71.6	20	72.3	15	72.9	10.091	73.4	6	79.4	5
85.5	4	100.5	3.5	114.3	4	124.5	5	135.8	10.103
140	12	202.9	14.2	203	14.5	209.1	15	224.5	20
229.5	25								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	72.9	.042	135.8	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
72.9	135.8	25	25	.3	.5

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	14.82	Element			
Vel Head (ft)	2.28	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	12.54	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	11.33	Flow Area (sq ft)	0.37	484.96	10.39
E.G. Slope (ft/ft)	0.008563	Area (sq ft)	0.37	484.96	10.39
Q Total (cfs)	5910.00	Flow (cfs)	0.20	5891.34	18.46
Top Width (ft)	82.79	Top Width (ft)	0.30	62.90	19.59
Vel Total (ft/s)	11.92	Avg. Vel. (ft/s)	0.55	12.15	1.78
Max Chl Dpth (ft)	9.04	Hydr. Depth (ft)	1.22	7.71	0.53
Conv. Total (cfs)	63865.3	Conv. (cfs)	2.2	63663.7	199.5
Length Wtd. (ft)	25.00	Wetted Per. (ft)	2.47	67.85	20.01
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.08	3.82	0.28
Alpha	1.04	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.06	17.18	1.02
C & E Loss (ft)	0.63	Cum SA (acres)	0.06	2.28	1.22

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	8.38	Element			
Vel Head (ft)	0.84	Wt. n-Val.		0.042	
W.S. Elev (ft)	7.54	Reach Len. (ft)	25.00	25.00	25.00

Crit W.S. (ft)	6.91	Flow Area (sq ft)		178.49	
E.G. Slope (ft/ft)	0.009882	Area (sq ft)		178.49	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	56.92	Top Width (ft)		56.92	
Vel Total (ft/s)	7.35	Avg. Vel. (ft/s)		7.35	
Max Chl Dpth (ft)	4.04	Hydr. Depth (ft)		3.14	
Conv. Total (cfs)	13198.2	Conv. (cfs)		13198.2	
Length Wtd. (ft)	25.00	Wetted Per. (ft)		59.07	
Min Ch El (ft)	3.50	Shear (lb/sq ft)		1.86	
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.00	5.20	
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	1.69	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	12.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.65	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	10.76	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.68	Flow Area (sq ft)	0.03	373.02	0.48
E.G. Slope (ft/ft)	0.008769	Area (sq ft)	0.03	373.02	0.48
Q Total (cfs)	3850.00	Flow (cfs)	0.01	3849.40	0.59
Top Width (ft)	64.43	Top Width (ft)	0.08	62.90	1.45
Vel Total (ft/s)	10.31	Avg. Vel. (ft/s)	0.23	10.32	1.24
Max Chl Dpth (ft)	7.26	Hydr. Depth (ft)	0.33	5.93	0.33
Conv. Total (cfs)	41114.1	Conv. (cfs)	0.1	41107.7	6.3
Length Wtd. (ft)	25.00	Wetted Per. (ft)	0.67	67.85	1.59
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.02	3.01	0.16
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	11.83	0.02
C & E Loss (ft)	0.39	Cum SA (acres)	0.00	2.09	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.75	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	11.04	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.93	Flow Area (sq ft)	0.05	390.62	0.97
E.G. Slope (ft/ft)	0.008725	Area (sq ft)	0.05	390.62	0.97
Q Total (cfs)	4148.00	Flow (cfs)	0.02	4146.46	1.52
Top Width (ft)	65.09	Top Width (ft)	0.12	62.90	2.07
Vel Total (ft/s)	10.59	Avg. Vel. (ft/s)	0.30	10.62	1.57

Max Chl Dpth (ft)	7.54	Hydr. Depth (ft)	0.47	6.21	0.47
Conv. Total (cfs)	44408.5	Conv. (cfs)	0.2	44392.0	16.3
Length Wtd. (ft)	25.00	Wetted Per. (ft)	0.95	67.85	2.27
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.03	3.14	0.23
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	12.57	0.03
C & E Loss (ft)	0.42	Cum SA (acres)	0.01	2.14	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	14.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.10	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	12.04	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.87	Flow Area (sq ft)	0.23	453.88	4.20
E.G. Slope (ft/ft)	0.008580	Area (sq ft)	0.23	453.88	4.20
Q Total (cfs)	5290.00	Flow (cfs)	0.11	5280.65	9.24
Top Width (ft)	68.60	Top Width (ft)	0.24	62.90	5.47
Vel Total (ft/s)	11.54	Avg. Vel. (ft/s)	0.47	11.63	2.20
Max Chl Dpth (ft)	8.54	Hydr. Depth (ft)	0.98	7.22	0.77
Conv. Total (cfs)	57109.9	Conv. (cfs)	1.2	57009.0	99.7
Length Wtd. (ft)	25.00	Wetted Per. (ft)	1.97	67.85	5.87
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.06	3.58	0.38
Alpha	1.01	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)	0.03	15.65	0.33
C & E Loss (ft)	0.55	Cum SA (acres)	0.03	2.27	0.53

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	16.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.93	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	11.41	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)	0.11	413.84	1.88
E.G. Slope (ft/ft)	0.022762	Area (sq ft)	0.11	413.84	1.88
Q Total (cfs)	7380.00	Flow (cfs)	0.06	7373.96	5.97
Top Width (ft)	65.95	Top Width (ft)	0.16	62.90	2.89
Vel Total (ft/s)	17.75	Avg. Vel. (ft/s)	0.59	17.82	3.17
Max Chl Dpth (ft)	7.91	Hydr. Depth (ft)	0.66	6.58	0.65

Conv. Total (cfs)	48916.0	Conv. (cfs)	0.4	48876.0	39.6
Length Wtd. (ft)	25.00	Wetted Per. (ft)	1.33	67.85	3.17
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.11	8.67	0.84
Alpha	1.01	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.71	Cum Volume (acre-ft)	0.21	20.97	4.07
C & E Loss (ft)	0.14	Cum SA (acres)	0.12	2.29	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 935

INPUT
Description: JU
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	12	30	20	28	50	10	75.8	6
82.4	4	92.4	3	105.2	2	121	3	128	5
136	10	203	12.5	203.1	13	203.2	13.1	208.7	13.4
231.8	20	232	26.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	50	.042	136	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
50	136	85	85	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	232	30	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	14.06	Element			
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	13.04	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	10.34	Flow Area (sq ft)	7.70	687.59	114.45
E.G. Slope (ft/ft)	0.003531	Area (sq ft)	7.70	687.59	120.00
Q Total (cfs)	5910.00	Flow (cfs)	12.49	5673.06	224.45
Top Width (ft)	158.21	Top Width (ft)	5.07	86.00	67.14

Vel Total (ft/s)	7.30	Avg. Vel. (ft/s)	1.62	8.25	1.96
Max Chl Dpth (ft)	11.04	Hydr. Depth (ft)	1.52	8.00	1.94
Conv. Total (cfs)	99457.7	Conv. (cfs)	210.2	95470.3	3777.2
Length Wtd. (ft)	17.00	Wetted Per. (ft)	5.91	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.29	1.71	0.43
Alpha	1.23	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.06	16.84	0.99
C & E Loss (ft)	0.29	Cum SA (acres)	0.05	2.24	1.19

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	8.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.46	Wt. n-Val.		0.042	
W.S. Elev (ft)	7.58	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	5.91	Flow Area (sq ft)		241.37	
E.G. Slope (ft/ft)	0.004364	Area (sq ft)		241.37	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	66.50	Top Width (ft)		66.50	
Vel Total (ft/s)	5.44	Avg. Vel. (ft/s)		5.44	
Max Chl Dpth (ft)	5.58	Hydr. Depth (ft)		3.63	
Conv. Total (cfs)	19859.9	Conv. (cfs)		19859.9	
Length Wtd. (ft)	17.00	Wetted Per. (ft)		68.05	
Min Ch El (ft)	2.00	Shear (lb/sq ft)		0.97	
Alpha	1.00	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.00	5.08	
C & E Loss (ft)	0.09	Cum SA (acres)	0.00	1.65	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	11.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	11.00	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	8.78	Flow Area (sq ft)	0.84	512.23	13.44
E.G. Slope (ft/ft)	0.004311	Area (sq ft)	0.84	512.23	13.44
Q Total (cfs)	3850.00	Flow (cfs)	0.71	3837.48	11.81

Top Width (ft)	114.51	Top Width (ft)	1.67	86.00	26.84
Vel Total (ft/s)	7.31	Avg. Vel. (ft/s)	0.85	7.49	0.88
Max Chl Dpth (ft)	9.00	Hydr. Depth (ft)	0.50	5.96	0.50
Conv. Total (cfs)	58637.4	Conv. (cfs)	10.9	58446.7	179.8
Length Wtd. (ft)	17.00	Wetted Per. (ft)	1.95	88.44	26.86
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.12	1.56	0.13
Alpha	1.05	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	11.58	0.01
C & E Loss (ft)	0.24	Cum SA (acres)	0.00	2.05	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.22	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	11.32	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	9.03	Flow Area (sq ft)	1.44	539.21	23.18
E.G. Slope (ft/ft)	0.004193	Area (sq ft)	1.44	539.21	23.18
Q Total (cfs)	4148.00	Flow (cfs)	1.46	4122.46	24.08
Top Width (ft)	123.44	Top Width (ft)	2.19	86.00	35.25
Vel Total (ft/s)	7.36	Avg. Vel. (ft/s)	1.01	7.65	1.04
Max Chl Dpth (ft)	9.32	Hydr. Depth (ft)	0.66	6.27	0.66
Conv. Total (cfs)	64061.1	Conv. (cfs)	22.5	63666.7	371.9
Length Wtd. (ft)	17.00	Wetted Per. (ft)	2.56	88.44	35.27
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.15	1.60	0.17
Alpha	1.07	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.01	12.30	0.02
C & E Loss (ft)	0.24	Cum SA (acres)	0.01	2.10	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	13.45	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.99	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	12.46	Reach Len. (ft)	17.00	17.00	17.00

Crit W.S. (ft)	9.93	Flow Area (sq ft)	5.05	637.91	80.37
E.G. Slope (ft/ft)	0.003743	Area (sq ft)	5.05	637.91	81.28
Q Total (cfs)	5290.00	Flow (cfs)	7.33	5154.48	128.19
Top Width (ft)	156.11	Top Width (ft)	4.10	86.00	66.01
Vel Total (ft/s)	7.31	Avg. Vel. (ft/s)	1.45	8.08	1.60
Max Chl Dpth (ft)	10.46	Hydr. Depth (ft)	1.23	7.42	1.36
Conv. Total (cfs)	86466.8	Conv. (cfs)	119.8	84251.7	2095.3
Length Wtd. (ft)	17.00	Wetted Per. (ft)	4.79	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.25	1.69	0.32
Alpha	1.19	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.03	15.33	0.30
C & E Loss (ft)	0.28	Cum SA (acres)	0.03	2.23	0.51

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	15.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.10	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	14.22	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	11.33	Flow Area (sq ft)	14.84	789.01	184.03
E.G. Slope (ft/ft)	0.003277	Area (sq ft)	14.84	789.01	205.75
Q Total (cfs)	7380.00	Flow (cfs)	28.83	6873.98	477.18
Top Width (ft)	168.60	Top Width (ft)	7.03	86.00	75.57
Vel Total (ft/s)	7.47	Avg. Vel. (ft/s)	1.94	8.71	2.59
Max Chl Dpth (ft)	12.22	Hydr. Depth (ft)	2.11	9.17	3.12
Conv. Total (cfs)	128913.2	Conv. (cfs)	503.7	120074.1	8335.4
Length Wtd. (ft)	17.00	Wetted Per. (ft)	8.20	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.37	1.83	0.64
Alpha	1.27	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.21	20.62	4.01
C & E Loss (ft)	0.23	Cum SA (acres)	0.11	2.25	1.97

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 895

INPUT
Description: Bridge Street
Distance from Upstream XS = 17
Deck/Roadway Width = 56
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	30.2	30	0
30.2	30	26	246.2	26	22
246.2	26	0	260	26	0

Upstream Bridge Cross Section Data
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	12	30	20	28	50	10	75.8	6
82.4	4	92.4	3	105.2	2	121	3	128	5
136	10	203	12.5	203.1	13	203.2	13.1	208.7	13.4
231.8	20	232	26.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	50	.042	136	.07

Bank Sta: Left Right Coeff Contr. Expan.
50 136 .3 .5
Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	232	30	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	30.2	30	0
30.2	30	26	246.2	26	22
246.2	26	0	260	26	0

Downstream Bridge Cross Section Data
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	28	26.8	20	27	14	39.8	10	75.2	5
94	1	115	1	126.8	5	131.6	5	151.3	9
174.5	10	238.1	15	238.2	25				

Manning's n Values num= 3

```
     Sta   n Val     Sta   n Val     Sta   n Val
       0    .065    39.8     .04   131.6    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
          39.8   131.6             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
       0      25      30       F
     195   238.2      30       F
Blocked Obstructions     num=       2
   Sta L   Sta R    Elev   Sta L   Sta R    Elev
   131.3   146.6      30     203     240      30

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =       2 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =      26
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Piers =  3

Pier Data
Pier Station     Upstream=    83.2    Downstream=    83.2
Upstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28
Downstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28

Pier Data
Pier Station     Upstream=   138.2    Downstream=   138.2
Upstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28
Downstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28

Pier Data
Pier Station     Upstream=   193.2    Downstream=   193.2
Upstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28
Downstream     num=       2
    Width   Elev    Width   Elev
     7.7       3       4      28
```

Number of Bridge Coefficient Sets = 1

Low Flow Methods and Data
Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
Energy Only

Additional Bridge Parameters
Add Friction component to Momentum
Do not add Weight component to Momentum
Class B flow critical depth computations use critical depth
inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Inside BR US	Inside BR DS
E.G. US. (ft)	14.06	Element		
W.S. US. (ft)	13.04	E.G. Elev (ft)	13.67	12.90
Q Total (cfs)	5910.00	W.S. Elev (ft)	11.70	11.51
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	10.78	9.93
Q Weir (cfs)		Max Chl Dpth (ft)	9.70	10.51
Weir Sta Lft (ft)		Vel Total (ft/s)	10.78	8.79
Weir Sta Rgt (ft)		Flow Area (sq ft)	548.45	672.20
Weir Submerg		Froude # Chl	0.78	0.64
Weir Max Depth (ft)		Specif Force (cu ft)	4042.63	4256.51
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.52	5.04
Min El Prs (ft)	26.00	W.P. Total (ft)	141.57	160.45
Delta EG (ft)	1.34	Conv. Total (cfs)	56292.8	71093.0
Delta WS (ft)	1.49	Top Width (ft)	121.45	133.26
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.48	0.07
BR Open Vel (ft/s)	10.78	C & E Loss (ft)	0.29	0.12
Coef of Q		Shear Total (lb/sq ft)	2.67	1.81
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

			Inside BR US	Inside BR DS
E.G. US. (ft)	8.04	Element		

W.S. US. (ft)	7.58	E.G. Elev (ft)	7.84	7.34
Q Total (cfs)	1312.00	W.S. Elev (ft)	7.07	6.86
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	6.09	5.12
Q Weir (cfs)		Max Chl Dpth (ft)	5.07	5.86
Weir Sta Lft (ft)		Vel Total (ft/s)	7.03	5.57
Weir Sta Rgt (ft)		Flow Area (sq ft)	186.55	235.64
Weir Submerg		Froude # Chl	0.68	0.50
Weir Max Depth (ft)		Specif Force (cu ft)	669.34	803.57
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	3.37	3.79
Min El Prs (ft)	26.00	W.P. Total (ft)	61.87	71.75
Delta EG (ft)	0.78	Conv. Total (cfs)	13774.8	19341.7
Delta WS (ft)	0.71	Top Width (ft)	55.33	62.17
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.35	0.05
BR Open Vel (ft/s)	7.03	C & E Loss (ft)	0.14	0.05
Coef of Q		Shear Total (lb/sq ft)	1.71	0.94
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	11.87	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.00	E.G. Elev (ft)	11.51	10.74
Q Total (cfs)	3850.00	W.S. Elev (ft)	9.84	9.44
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	9.19	8.13
Q Weir (cfs)		Max Chl Dpth (ft)	7.84	8.44
Weir Sta Lft (ft)		Vel Total (ft/s)	10.37	9.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	371.21	426.26
Weir Submerg		Froude # Chl	0.83	0.71
Weir Max Depth (ft)		Specif Force (cu ft)	2381.82	2505.53
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.81	4.46
Min El Prs (ft)	26.00	W.P. Total (ft)	90.24	114.28
Delta EG (ft)	1.34	Conv. Total (cfs)	33717.1	41227.8
Delta WS (ft)	1.52	Top Width (ft)	77.17	95.67
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.59	0.08
BR Open Vel (ft/s)	10.37	C & E Loss (ft)	0.19	0.13
Coef of Q		Shear Total (lb/sq ft)	3.35	2.03
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	12.22	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.32	E.G. Elev (ft)	11.86	11.09
Q Total (cfs)	4148.00	W.S. Elev (ft)	10.15	9.77
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	9.45	8.40
Q Weir (cfs)		Max Chl Dpth (ft)	8.15	8.77
Weir Sta Lft (ft)		Vel Total (ft/s)	10.49	9.02
Weir Sta Rgt (ft)		Flow Area (sq ft)	395.42	459.77
Weir Submerg		Froude # Chl	0.82	0.70
Weir Max Depth (ft)		Specif Force (cu ft)	2612.10	2746.19
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	5.04	4.35
Min El Prs (ft)	26.00	W.P. Total (ft)	92.49	125.72
Delta EG (ft)	1.33	Conv. Total (cfs)	36929.0	44866.2
Delta WS (ft)	1.50	Top Width (ft)	78.50	105.79
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.58	0.08
BR Open Vel (ft/s)	10.49	C & E Loss (ft)	0.19	0.13
Coef of Q		Shear Total (lb/sq ft)	3.37	1.95
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	13.45	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	12.46	E.G. Elev (ft)	13.07	12.28
Q Total (cfs)	5290.00	W.S. Elev (ft)	11.14	10.88
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	10.32	9.40
Q Weir (cfs)		Max Chl Dpth (ft)	9.14	9.88
Weir Sta Lft (ft)		Vel Total (ft/s)	10.89	8.96
Weir Sta Rgt (ft)		Flow Area (sq ft)	485.64	590.71
Weir Submerg		Froude # Chl	0.80	0.67
Weir Max Depth (ft)		Specif Force (cu ft)	3520.21	3691.43
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.60	4.65
Min El Prs (ft)	26.00	W.P. Total (ft)	123.43	151.36
Delta EG (ft)	1.37	Conv. Total (cfs)	48863.6	60747.7
Delta WS (ft)	1.53	Top Width (ft)	105.53	126.95
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.52	0.07
BR Open Vel (ft/s)	10.89	C & E Loss (ft)	0.26	0.13
Coef of Q		Shear Total (lb/sq ft)	2.88	1.85
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

			Inside BR US	Inside BR DS
E.G. US. (ft)	15.32	Element		
W.S. US. (ft)	14.22	E.G. Elev (ft)	15.01	14.35
Q Total (cfs)	7380.00	W.S. Elev (ft)	13.14	13.04
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	11.89	10.88
Q Weir (cfs)		Max Chl Dpth (ft)	11.14	12.04
Weir Sta Lft (ft)		Vel Total (ft/s)	10.02	8.39
Weir Sta Rgt (ft)		Flow Area (sq ft)	736.89	880.12
Weir Submerg		Froude # Chl	0.70	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	5392.83	5799.20
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	5.54	6.36
Min El Prs (ft)	26.00	W.P. Total (ft)	159.87	173.12
Delta EG (ft)	1.12	Conv. Total (cfs)	78846.8	99858.9
Delta WS (ft)	1.14	Top Width (ft)	140.56	145.07
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.38	0.05
BR Open Vel (ft/s)	10.02	C & E Loss (ft)	0.28	0.10
Coef of Q		Shear Total (lb/sq ft)	2.52	1.73
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 850

INPUT
Description: JD
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	28	26.8	20	27	14	39.8	10	75.2	5
94	1	115	1	126.8	5	131.6	5	151.3	9

174.5	10	238.1	15	238.2	25

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	39.8	.04	131.6	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
39.8	131.6	20	20	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	238.2	30	F

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
131.3	146.6	30	203	240	30

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.72	Element			
Vel Head (ft)	1.16	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.56	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	9.38	Flow Area (sq ft)	3.87	656.53	77.33
E.G. Slope (ft/ft)	0.004490	Area (sq ft)	3.87	656.53	77.33
Q Total (cfs)	5910.00	Flow (cfs)	4.86	5749.56	155.58
Top Width (ft)	144.16	Top Width (ft)	4.98	91.50	47.69
Vel Total (ft/s)	8.01	Avg. Vel. (ft/s)	1.26	8.76	2.01
Max Chl Dpth (ft)	10.56	Hydr. Depth (ft)	0.78	7.18	1.62
Conv. Total (cfs)	88199.3	Conv. (cfs)	72.6	85804.9	2321.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	5.21	99.49	51.37
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.21	1.85	0.42
Alpha	1.16	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.06	15.72	0.87
C & E Loss (ft)	0.07	Cum SA (acres)	0.05	2.08	1.11

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.25	Element			
Vel Head (ft)	0.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.86	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	4.89	Flow Area (sq ft)		262.03	
E.G. Slope (ft/ft)	0.003268	Area (sq ft)		262.03	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	69.29	Top Width (ft)		69.29	
Vel Total (ft/s)	5.01	Avg. Vel. (ft/s)		5.01	

Max Chl Dpth (ft)	5.86	Hydr. Depth (ft)		3.78	
Conv. Total (cfs)	22952.1	Conv. (cfs)		22952.1	
Length Wtd. (ft)	20.00	Wetted Per. (ft)		72.37	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.74	
Alpha	1.00	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.07	Cum Volume (acre-ft)	0.00	4.66	
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.53	

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.05	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.48	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.75	Flow Area (sq ft)		467.67	7.19
E.G. Slope (ft/ft)	0.005737	Area (sq ft)		467.67	7.19
Q Total (cfs)	3850.00	Flow (cfs)		3843.10	6.90
Top Width (ft)	103.69	Top Width (ft)		87.83	15.86
Vel Total (ft/s)	8.11	Avg. Vel. (ft/s)		8.22	0.96
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		5.32	0.45
Conv. Total (cfs)	50829.1	Conv. (cfs)		50738.0	91.1
Length Wtd. (ft)	20.00	Wetted Per. (ft)		93.70	17.40
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.79	0.15
Alpha	1.03	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	10.77	0.00
C & E Loss (ft)	0.09	Cum SA (acres)	0.00	1.89	0.01

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.88	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.07	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.82	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.01	Flow Area (sq ft)		497.48	13.80
E.G. Slope (ft/ft)	0.005609	Area (sq ft)		497.48	13.80
Q Total (cfs)	4148.00	Flow (cfs)		4132.32	15.68
Top Width (ft)	113.83	Top Width (ft)		90.20	23.63
Vel Total (ft/s)	8.11	Avg. Vel. (ft/s)		8.31	1.14
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)		5.52	0.58
Conv. Total (cfs)	55384.5	Conv. (cfs)		55175.1	209.4
Length Wtd. (ft)	20.00	Wetted Per. (ft)		96.43	25.51
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.81	0.19

Alpha	1.04	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	11.45	0.01
C & E Loss (ft)	0.09	Cum SA (acres)	0.01	1.94	0.01

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	12.08	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.15	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.94	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.91	Flow Area (sq ft)	1.40	599.94	50.27
E.G. Slope (ft/ft)	0.004917	Area (sq ft)	1.40	599.94	50.27
Q Total (cfs)	5290.00	Flow (cfs)	1.32	5199.07	89.61
Top Width (ft)	134.32	Top Width (ft)	3.00	91.50	39.82
Vel Total (ft/s)	8.12	Avg. Vel. (ft/s)	0.94	8.67	1.78
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	0.47	6.56	1.26
Conv. Total (cfs)	75439.9	Conv. (cfs)	18.8	74143.1	1278.0
Length Wtd. (ft)	20.00	Wetted Per. (ft)	3.14	98.87	42.86
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.14	1.86	0.36
Alpha	1.12	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.03	14.31	0.23
C & E Loss (ft)	0.07	Cum SA (acres)	0.03	2.07	0.44

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.12	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.08	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	10.40	Flow Area (sq ft)	15.20	796.26	151.22
E.G. Slope (ft/ft)	0.003513	Area (sq ft)	15.20	796.26	160.47
Q Total (cfs)	7380.00	Flow (cfs)	26.65	6944.32	409.03
Top Width (ft)	157.76	Top Width (ft)	9.86	91.50	56.40
Vel Total (ft/s)	7.67	Avg. Vel. (ft/s)	1.75	8.72	2.70
Max Chl Dpth (ft)	12.08	Hydr. Depth (ft)	1.54	8.70	3.12
Conv. Total (cfs)	124507.8	Conv. (cfs)	449.6	117157.4	6900.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	10.33	101.01	53.62
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.32	1.73	0.62
Alpha	1.22	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.18	19.26	3.74
C & E Loss (ft)	0.05	Cum SA (acres)	0.10	2.09	1.86

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 830

INPUT
Description: A

Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	23	24.1	15	34.9	10.006	41.4	7	45.2	6
58.5	6	65	5	78	4	93.5	1	108.7	1
131.1	7	155	10	167.8	10	194.1	11	251.2	15
251.3	25								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	34.9	.04	131.1	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
34.9	131.1	9	9	.3	.5

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
132	155	25	205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.57	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.54	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	2.56	712.89	53.34
E.G. Slope (ft/ft)	0.003454	Area (sq ft)	2.56	712.89	53.34
Q Total (cfs)	5910.00	Flow (cfs)	2.70	5835.78	71.52
Top Width (ft)	147.28	Top Width (ft)	3.32	96.20	47.76
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	1.06	8.19	1.34
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	0.77	7.41	1.12
Conv. Total (cfs)	100563.7	Conv. (cfs)	46.0	99300.7	1217.0
Length Wtd. (ft)	9.00	Wetted Per. (ft)	3.66	98.18	53.77
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	1.57	0.21
Alpha	1.12	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.05	15.41	0.84
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	2.03	1.08

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.17	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.37	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.80	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		267.69	
E.G. Slope (ft/ft)	0.004037	Area (sq ft)		267.69	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	88.18	Top Width (ft)		88.18	
Vel Total (ft/s)	4.90	Avg. Vel. (ft/s)		4.90	
Max Chl Dpth (ft)	5.80	Hydr. Depth (ft)		3.04	
Conv. Total (cfs)	20650.0	Conv. (cfs)		20650.0	
Length Wtd. (ft)	9.00	Wetted Per. (ft)		89.45	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.75	
Alpha	1.00	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.00	4.54	
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.50	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.34	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.47	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		513.66	2.17
E.G. Slope (ft/ft)	0.004399	Area (sq ft)		513.66	2.17
Q Total (cfs)	3850.00	Flow (cfs)		3847.49	2.51
Top Width (ft)	95.94	Top Width (ft)		95.04	0.90
Vel Total (ft/s)	7.46	Avg. Vel. (ft/s)		7.49	1.16
Max Chl Dpth (ft)	8.47	Hydr. Depth (ft)		5.40	2.41
Conv. Total (cfs)	58048.3	Conv. (cfs)		58010.5	37.8
Length Wtd. (ft)	9.00	Wetted Per. (ft)		96.90	3.26
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.46	0.18
Alpha	1.01	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	10.55	0.00
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.85	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.81	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		545.73	2.47
E.G. Slope (ft/ft)	0.004218	Area (sq ft)		545.73	2.47
Q Total (cfs)	4148.00	Flow (cfs)		4145.14	2.86

Top Width (ft)	96.67	Top Width (ft)		95.77	0.90
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)		7.60	1.16
Max Chl Dpth (ft)	8.81	Hydr. Depth (ft)		5.70	2.75
Conv. Total (cfs)	63864.6	Conv. (cfs)		63820.6	44.0
Length Wtd. (ft)	9.00	Wetted Per. (ft)		97.70	3.60
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.47	0.18
Alpha	1.01	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	11.21	0.00
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.90	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.92	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	0.91	653.30	26.53
E.G. Slope (ft/ft)	0.003757	Area (sq ft)	0.91	653.30	26.53
Q Total (cfs)	5290.00	Flow (cfs)	0.71	5262.19	27.10
Top Width (ft)	136.18	Top Width (ft)	1.98	96.20	38.00
Vel Total (ft/s)	7.77	Avg. Vel. (ft/s)	0.78	8.05	1.02
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.46	6.79	0.70
Conv. Total (cfs)	86308.4	Conv. (cfs)	11.6	85854.6	442.2
Length Wtd. (ft)	9.00	Wetted Per. (ft)	2.19	98.18	42.75
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.56	0.15
Alpha	1.07	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.03	14.02	0.21
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	2.02	0.42

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.07	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	10.15	859.71	130.67
E.G. Slope (ft/ft)	0.002737	Area (sq ft)	10.15	859.71	130.67
Q Total (cfs)	7380.00	Flow (cfs)	15.12	7098.19	266.69
Top Width (ft)	153.73	Top Width (ft)	6.63	96.20	50.90
Vel Total (ft/s)	7.38	Avg. Vel. (ft/s)	1.49	8.26	2.04
Max Chl Dpth (ft)	12.07	Hydr. Depth (ft)	1.53	8.94	2.57
Conv. Total (cfs)	141061.3	Conv. (cfs)	289.0	135674.9	5097.5
Length Wtd. (ft)	9.00	Wetted Per. (ft)	7.30	98.18	61.28
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.24	1.50	0.36
Alpha	1.21	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.18	18.88	3.68
C & E Loss (ft)	0.02	Cum SA (acres)	0.10	2.05	1.83

Warning: Divided flow computed for this cross-section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 821

INPUT
Description: AD
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12	16.5	22	12.5	27	10.25	32	8	42	6.5
52	6	62	4.5	72	3.5	82	1.5	92	1
102	1	112	4	122	7	132	9	154	10
203	11.5	235	12						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12	.065	27	.035	132	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
27	132	1	1	.3	.5

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
132	155	25	205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.53	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	1.82	729.91	36.68
E.G. Slope (ft/ft)	0.002866	Area (sq ft)	1.82	729.91	36.68
Q Total (cfs)	5910.00	Flow (cfs)	1.55	5872.59	35.86
Top Width (ft)	157.69	Top Width (ft)	2.84	105.00	49.85
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	0.85	8.05	0.98
Max Chl Dpth (ft)	10.53	Hydr. Depth (ft)	0.64	6.95	0.74
Conv. Total (cfs)	110396.7	Conv. (cfs)	29.0	109697.9	669.8
Length Wtd. (ft)	1.00	Wetted Per. (ft)	3.12	109.59	51.37
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.19	0.13
Alpha	1.09	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.05	15.26	0.83
C & E Loss (ft)	0.07	Cum SA (acres)	0.04	2.01	1.07

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.41	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.72	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		255.20	
E.G. Slope (ft/ft)	0.003214	Area (sq ft)		255.20	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.51	Top Width (ft)		80.51	
Vel Total (ft/s)	5.14	Avg. Vel. (ft/s)		5.14	
Max Chl Dpth (ft)	5.72	Hydr. Depth (ft)		3.17	
Conv. Total (cfs)	23142.0	Conv. (cfs)		23142.0	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		81.75	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.63	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.00	4.48	
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.48	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.30	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.89	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.41	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		507.74	
E.G. Slope (ft/ft)	0.003921	Area (sq ft)		507.74	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	103.12	Top Width (ft)		103.12	
Vel Total (ft/s)	7.58	Avg. Vel. (ft/s)		7.58	
Max Chl Dpth (ft)	8.41	Hydr. Depth (ft)		4.92	
Conv. Total (cfs)	61483.1	Conv. (cfs)		61483.1	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		105.41	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.18	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	10.44	0.00
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.83	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.77	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		545.09	
E.G. Slope (ft/ft)	0.003649	Area (sq ft)		545.09	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	103.92	Top Width (ft)		103.92	
Vel Total (ft/s)	7.61	Avg. Vel. (ft/s)		7.61	

Max Chl Dpth (ft)	8.77	Hydr. Depth (ft)		5.25	
Conv. Total (cfs)	68666.2	Conv. (cfs)		68666.2	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		106.65	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.16	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	11.10	0.00
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	1.88	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.88	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.98	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.90	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	0.47	664.17	12.43
E.G. Slope (ft/ft)	0.003150	Area (sq ft)	0.47	664.17	12.43
Q Total (cfs)	5290.00	Flow (cfs)	0.27	5280.75	8.98
Top Width (ft)	134.94	Top Width (ft)	1.45	105.00	28.49
Vel Total (ft/s)	7.81	Avg. Vel. (ft/s)	0.57	7.95	0.72
Max Chl Dpth (ft)	9.90	Hydr. Depth (ft)	0.33	6.33	0.44
Conv. Total (cfs)	94255.3	Conv. (cfs)	4.8	94090.4	160.0
Length Wtd. (ft)	1.00	Wetted Per. (ft)	1.59	108.96	29.38
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	1.20	0.08
Alpha	1.03	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.03	13.88	0.21
C & E Loss (ft)	0.05	Cum SA (acres)	0.02	2.00	0.42

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.98	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	13.07	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	8.87	891.56	113.66
E.G. Slope (ft/ft)	0.002233	Area (sq ft)	8.87	891.56	113.66
Q Total (cfs)	7380.00	Flow (cfs)	11.21	7168.61	200.18
Top Width (ft)	161.42	Top Width (ft)	6.42	105.00	50.00
Vel Total (ft/s)	7.28	Avg. Vel. (ft/s)	1.26	8.04	1.76
Max Chl Dpth (ft)	12.07	Hydr. Depth (ft)	1.38	8.49	2.27
Conv. Total (cfs)	156166.6	Conv. (cfs)	237.2	151693.4	4236.0
Length Wtd. (ft)	1.00	Wetted Per. (ft)	7.01	111.13	54.60
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.18	1.12	0.29
Alpha	1.19	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.18	18.70	3.65
C & E Loss (ft)	0.12	Cum SA (acres)	0.09	2.02	1.82

Warning: Divided flow computed for this cross-section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 820

INPUT
Description: ADD
Station Elevation Data num= 24

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	16.5	10	12.5	15	10.25	20	8	30	6.5
40	6	50	4.5	60	3.5	70	1.5	80	1
90	1	100	4	110	7	119.4	9	119.5	9
142.2	10	142.3	10	150	10	160	10	170	11
180	11	185.5	11.5	185.6	11.5	290	12		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	15	.035	142.3	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15	142.3	95	95	.3	.5

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.46	Element			
Vel Head (ft)	0.86	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.59	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	2.01	782.50	47.90
E.G. Slope (ft/ft)	0.002824	Area (sq ft)	2.01	782.50	47.90
Q Total (cfs)	5910.00	Flow (cfs)	1.76	5859.74	48.50
Top Width (ft)	193.15	Top Width (ft)	2.99	127.30	62.87
Vel Total (ft/s)	7.10	Avg. Vel. (ft/s)	0.88	7.49	1.01
Max Chl Dpth (ft)	10.59	Hydr. Depth (ft)	0.67	6.15	0.76
Conv. Total (cfs)	111218.0	Conv. (cfs)	33.1	110272.2	912.7
Length Wtd. (ft)	95.00	Wetted Per. (ft)	3.27	129.39	62.94
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.11	1.07	0.13
Alpha	1.10	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.31	Cum Volume (acre-ft)	0.05	15.24	0.83
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	2.01	1.07

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.12	Element			
Vel Head (ft)	0.41	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.71	Reach Len. (ft)	95.00	95.00	95.00

Crit W.S. (ft)		Flow Area (sq ft)		254.82	
E.G. Slope (ft/ft)	0.003228	Area (sq ft)		254.82	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.46	Top Width (ft)		80.46	
Vel Total (ft/s)	5.15	Avg. Vel. (ft/s)		5.15	
Max Chl Dpth (ft)	5.71	Hydr. Depth (ft)		3.17	
Conv. Total (cfs)	23093.7	Conv. (cfs)		23093.7	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		81.70	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.63	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.42	Cum Volume (acre-ft)	0.00	4.48	
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.48	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.29	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.89	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.40	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		508.45	
E.G. Slope (ft/ft)	0.004315	Area (sq ft)		508.45	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	111.75	Top Width (ft)		111.75	
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)		7.57	
Max Chl Dpth (ft)	8.40	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	58609.7	Conv. (cfs)		58609.7	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		113.65	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.21	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.48	Cum Volume (acre-ft)	0.01	10.43	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	1.82	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.65	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.88	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.77	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		551.32	
E.G. Slope (ft/ft)	0.004246	Area (sq ft)		551.32	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	120.93	Top Width (ft)		120.93	
Vel Total (ft/s)	7.52	Avg. Vel. (ft/s)		7.52	
Max Chl Dpth (ft)	8.77	Hydr. Depth (ft)		4.56	
Conv. Total (cfs)	63659.0	Conv. (cfs)		63659.0	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		122.92	

Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.19	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.47	Cum Volume (acre-ft)	0.01	11.08	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	1.88	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.83	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.95	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	0.55	700.99	21.42
E.G. Slope (ft/ft)	0.003290	Area (sq ft)	0.55	700.99	21.42
Q Total (cfs)	5290.00	Flow (cfs)	0.34	5265.76	23.91
Top Width (ft)	156.10	Top Width (ft)	1.56	127.30	27.23
Vel Total (ft/s)	7.32	Avg. Vel. (ft/s)	0.61	7.51	1.12
Max Chl Dpth (ft)	9.95	Hydr. Depth (ft)	0.35	5.51	0.79
Conv. Total (cfs)	92223.0	Conv. (cfs)	5.9	91800.4	416.8
Length Wtd. (ft)	95.00	Wetted Per. (ft)	1.71	129.39	27.28
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.07	1.11	0.16
Alpha	1.05	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.37	Cum Volume (acre-ft)	0.03	13.87	0.21
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	2.00	0.42

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.74	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	13.18	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	9.63	985.01	265.63
E.G. Slope (ft/ft)	0.001862	Area (sq ft)	9.63	985.01	265.63
Q Total (cfs)	7380.00	Flow (cfs)	11.41	6983.27	385.32
Top Width (ft)	281.71	Top Width (ft)	6.71	127.30	147.70
Vel Total (ft/s)	5.86	Avg. Vel. (ft/s)	1.18	7.09	1.45
Max Chl Dpth (ft)	12.18	Hydr. Depth (ft)	1.44	7.74	1.80
Conv. Total (cfs)	171022.7	Conv. (cfs)	264.3	161829.0	8929.4
Length Wtd. (ft)	95.00	Wetted Per. (ft)	7.33	129.39	148.96
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	0.88	0.21
Alpha	1.39	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.18	18.68	3.65
C & E Loss (ft)	0.01	Cum SA (acres)	0.09	2.02	1.82

Warning: The cross-section end points had to be extended vertically for the computed water surface.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 725

INPUT
Description: 10
10
Station Elevation Data num= 22

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	14	20	10	30	4	60	4
70	2.8	80	2.5	90	2.5	100	3	110	4.5
120	7.5	126	9	154	10	192	11	235	12
260	13	263	14	266	15	270	16	272	17
281	19	286	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	20	.04	154	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
20	154	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.30	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.12	798.33	32.38
E.G. Slope (ft/ft)	0.003724	Area (sq ft)	2.12	798.33	32.38
Q Total (cfs)	5910.00	Flow (cfs)	2.11	5874.50	33.39
Top Width (ft)	188.19	Top Width (ft)	3.25	134.00	50.94
Vel Total (ft/s)	7.10	Avg. Vel. (ft/s)	1.00	7.36	1.03
Max Chl Dpth (ft)	8.80	Hydr. Depth (ft)	0.65	5.96	0.64
Conv. Total (cfs)	96846.9	Conv. (cfs)	34.6	96265.2	547.2
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.50	136.51	50.96
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.14	1.36	0.15
Alpha	1.07	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.05	13.52	0.74
C & E Loss (ft)	0.07	Cum SA (acres)	0.04	1.73	0.95

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	6.68	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.49	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.19	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		233.27	
E.G. Slope (ft/ft)	0.006470	Area (sq ft)		233.27	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	89.27	Top Width (ft)		89.27	

Vel Total (ft/s)	5.62	Avg. Vel. (ft/s)		5.62	
Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.61	
Conv. Total (cfs)	16311.4	Conv. (cfs)		16311.4	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		90.33	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.04	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	1.33	Cum Volume (acre-ft)	0.00	3.94	
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.29	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.79	Element			
Vel Head (ft)	0.98	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.81	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		484.70	
E.G. Slope (ft/ft)	0.005976	Area (sq ft)		484.70	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	103.23	Top Width (ft)		103.23	
Vel Total (ft/s)	7.94	Avg. Vel. (ft/s)		7.94	
Max Chl Dpth (ft)	6.31	Hydr. Depth (ft)		4.70	
Conv. Total (cfs)	49802.5	Conv. (cfs)		49802.5	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		105.37	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.72	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.67	Cum Volume (acre-ft)	0.01	9.35	0.00
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.59	0.00

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	10.15	Element			
Vel Head (ft)	0.97	Wt. n-Val.		0.040	
W.S. Elev (ft)	9.18	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		523.96	
E.G. Slope (ft/ft)	0.005798	Area (sq ft)		523.96	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	109.64	Top Width (ft)		109.64	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	6.68	Hydr. Depth (ft)		4.78	
Conv. Total (cfs)	54477.2	Conv. (cfs)		54477.2	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		111.90	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.69	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00

Frctn Loss (ft)	0.63	Cum Volume (acre-ft)	0.01	9.91	0.00
C & E Loss (ft)	0.11	Cum SA (acres)	0.01	1.62	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.88	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.57	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.41	700.79	6.24
E.G. Slope (ft/ft)	0.004654	Area (sq ft)	0.41	700.79	6.24
Q Total (cfs)	5290.00	Flow (cfs)	0.26	5285.51	4.23
Top Width (ft)	157.21	Top Width (ft)	1.43	134.00	21.78
Vel Total (ft/s)	7.48	Avg. Vel. (ft/s)	0.65	7.54	0.68
Max Chl Dpth (ft)	8.07	Hydr. Depth (ft)	0.29	5.23	0.29
Conv. Total (cfs)	77538.9	Conv. (cfs)	3.9	77473.0	62.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.54	136.51	21.78
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.08	1.49	0.08
Alpha	1.02	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.47	Cum Volume (acre-ft)	0.03	12.34	0.18
C & E Loss (ft)	0.08	Cum SA (acres)	0.02	1.71	0.36

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.72	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.00	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	11.24	1025.74	171.79
E.G. Slope (ft/ft)	0.002360	Area (sq ft)	11.24	1025.74	171.79
Q Total (cfs)	7380.00	Flow (cfs)	15.55	7101.22	263.23
Top Width (ft)	247.45	Top Width (ft)	7.50	134.00	105.95
Vel Total (ft/s)	6.11	Avg. Vel. (ft/s)	1.38	6.92	1.53
Max Chl Dpth (ft)	10.50	Hydr. Depth (ft)	1.50	7.65	1.62
Conv. Total (cfs)	151921.3	Conv. (cfs)	320.2	146182.5	5418.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	8.07	136.51	106.00
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.21	1.11	0.24
Alpha	1.24	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.15	16.49	3.17
C & E Loss (ft)	0.06	Cum SA (acres)	0.08	1.74	1.54

CROSS SECTION

RIVER: Cobosee Stream

REACH: Reach 1 RS: 575

INPUT
Description: 9
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	13.5	17	8.25	20	6	30	1.5
40	1.5	50	1.5	60	2.25	70	2.8	80	3.1
110	3.1	120	4	130	7	140	9	172	10
230	11	280	12	280.1	16				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	17	.04	140	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
17	140	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.59	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.08	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	5.34	937.10	84.46
E.G. Slope (ft/ft)	0.001918	Area (sq ft)	5.34	937.10	84.46
Q Total (cfs)	5910.00	Flow (cfs)	5.81	5825.50	78.69
Top Width (ft)	220.83	Top Width (ft)	3.77	123.00	94.05
Vel Total (ft/s)	5.76	Avg. Vel. (ft/s)	1.09	6.22	0.93
Max Chl Dpth (ft)	9.58	Hydr. Depth (ft)	1.42	7.62	0.90
Conv. Total (cfs)	134958.7	Conv. (cfs)	132.7	133029.1	1796.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.72	125.44	94.08
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.14	0.89	0.11
Alpha	1.15	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.04	10.53	0.54
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	1.28	0.70

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	5.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.64	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		197.13	
E.G. Slope (ft/ft)	0.012980	Area (sq ft)		197.13	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	99.10	Top Width (ft)		99.10	
Vel Total (ft/s)	6.66	Avg. Vel. (ft/s)		6.66	
Max Chl Dpth (ft)	3.14	Hydr. Depth (ft)		1.99	
Conv. Total (cfs)	11515.9	Conv. (cfs)		11515.9	

Length Wtd. (ft)	150.00	Wetted Per. (ft)		99.96	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.60	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	1.17	Cum Volume (acre-ft)	0.00	3.20	
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.97	

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.01	Element			
Vel Head (ft)	0.63	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.39	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.01	606.57	
E.G. Slope (ft/ft)	0.003452	Area (sq ft)	0.01	606.57	
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3850.00	
Top Width (ft)	120.11	Top Width (ft)	0.18	119.93	
Vel Total (ft/s)	6.35	Avg. Vel. (ft/s)	0.19	6.35	
Max Chl Dpth (ft)	6.89	Hydr. Depth (ft)	0.07	5.06	
Conv. Total (cfs)	65528.1	Conv. (cfs)	0.0	65528.1	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.23	122.31	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.01	1.07	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.42	Cum Volume (acre-ft)	0.01	7.47	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.21	0.00

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.42	Element			
Vel Head (ft)	0.62	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.80	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.20	656.34	
E.G. Slope (ft/ft)	0.003151	Area (sq ft)	0.20	656.34	
Q Total (cfs)	4148.00	Flow (cfs)	0.09	4147.91	
Top Width (ft)	122.72	Top Width (ft)	0.73	121.99	
Vel Total (ft/s)	6.32	Avg. Vel. (ft/s)	0.47	6.32	
Max Chl Dpth (ft)	7.30	Hydr. Depth (ft)	0.27	5.38	
Conv. Total (cfs)	73891.2	Conv. (cfs)	1.7	73889.5	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.91	124.41	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.04	1.04	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.01	7.88	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.23	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.61	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.79	840.41	27.96
E.G. Slope (ft/ft)	0.002253	Area (sq ft)	2.79	840.41	27.96
Q Total (cfs)	5290.00	Flow (cfs)	2.65	5266.52	20.84
Top Width (ft)	174.83	Top Width (ft)	2.73	123.00	49.11
Vel Total (ft/s)	6.07	Avg. Vel. (ft/s)	0.95	6.27	0.75
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	1.02	6.83	0.57
Conv. Total (cfs)	111443.1	Conv. (cfs)	55.7	110948.3	439.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.41	125.44	49.13
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.12	0.94	0.08
Alpha	1.06	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.02	9.69	0.12
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.27	0.24

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.39	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.87	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	14.25	1157.61	314.35
E.G. Slope (ft/ft)	0.001335	Area (sq ft)	14.25	1157.61	314.35
Q Total (cfs)	7380.00	Flow (cfs)	17.94	6913.71	448.35
Top Width (ft)	269.19	Top Width (ft)	6.17	123.00	140.02
Vel Total (ft/s)	4.97	Avg. Vel. (ft/s)	1.26	5.97	1.43
Max Chl Dpth (ft)	11.37	Hydr. Depth (ft)	2.31	9.41	2.25
Conv. Total (cfs)	201954.9	Conv. (cfs)	491.0	189194.9	12269.1
Length Wtd. (ft)	150.00	Wetted Per. (ft)	7.71	125.44	140.91
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.15	0.77	0.19
Alpha	1.36	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.19	Cum Volume (acre-ft)	0.11	12.73	2.33
C & E Loss (ft)	0.00	Cum SA (acres)	0.06	1.29	1.12

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 425

INPUT
Description: 8
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev

0	18	10	11	12	9.8	20	5	30	0
70	0	80	.5	90	1.5	100	2	110	5.5
117.4	9	160	10	210	10	265	11	268	12
275	13	280	14						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	12	.04	117.4	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
12	117.4	90	90	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.59	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.82	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	0.86	934.95	115.56
E.G. Slope (ft/ft)	0.001604	Area (sq ft)	0.86	934.95	115.56
Q Total (cfs)	5910.00	Flow (cfs)	0.46	5815.40	94.15
Top Width (ft)	244.73	Top Width (ft)	1.70	105.40	137.64
Vel Total (ft/s)	5.62	Avg. Vel. (ft/s)	0.53	6.22	0.81
Max Chl Dpth (ft)	10.82	Hydr. Depth (ft)	0.51	8.87	0.84
Conv. Total (cfs)	147573.0	Conv. (cfs)	11.4	145210.7	2350.9
Length Wtd. (ft)	90.00	Wetted Per. (ft)	1.98	109.37	137.65
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.04	0.86	0.08
Alpha	1.21	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.03	7.31	0.20
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.89	0.30

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.46	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.63	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		240.73	
E.G. Slope (ft/ft)	0.005213	Area (sq ft)		240.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	81.90	Top Width (ft)		81.90	
Vel Total (ft/s)	5.45	Avg. Vel. (ft/s)		5.45	
Max Chl Dpth (ft)	3.63	Hydr. Depth (ft)		2.94	
Conv. Total (cfs)	18171.8	Conv. (cfs)		18171.8	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		83.10	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.94	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	2.45	
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.66	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.56	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.02	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		643.65	
E.G. Slope (ft/ft)	0.002271	Area (sq ft)		643.65	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	100.36	Top Width (ft)		100.36	
Vel Total (ft/s)	5.98	Avg. Vel. (ft/s)		5.98	
Max Chl Dpth (ft)	8.02	Hydr. Depth (ft)		6.41	
Conv. Total (cfs)	80797.5	Conv. (cfs)		80797.5	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		103.62	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.88	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.01	5.32	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.83	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	9.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.57	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.45	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		686.74	
E.G. Slope (ft/ft)	0.002174	Area (sq ft)		686.74	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	101.97	Top Width (ft)		101.97	
Vel Total (ft/s)	6.04	Avg. Vel. (ft/s)		6.04	
Max Chl Dpth (ft)	8.45	Hydr. Depth (ft)		6.73	
Conv. Total (cfs)	88971.9	Conv. (cfs)		88971.9	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		105.44	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.88	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.23	Cum Volume (acre-ft)	0.01	5.57	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.84	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.60	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.00	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	0.03	848.26	21.14
E.G. Slope (ft/ft)	0.001827	Area (sq ft)	0.03	848.26	21.14
Q Total (cfs)	5290.00	Flow (cfs)	0.01	5277.02	12.98
Top Width (ft)	148.17	Top Width (ft)	0.33	105.40	42.44
Vel Total (ft/s)	6.08	Avg. Vel. (ft/s)	0.19	6.22	0.61

Max Chl Dpth (ft)	10.00	Hydr. Depth (ft)	0.10	8.05	0.50
Conv. Total (cfs)	123773.8	Conv. (cfs)	0.1	123470.0	303.7
Length Wtd. (ft)	90.00	Wetted Per. (ft)	0.38	109.37	42.45
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.01	0.88	0.06
Alpha	1.04	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.02	6.78	0.04
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.88	0.08

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.69	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	6.62	1132.07	395.93
E.G. Slope (ft/ft)	0.001159	Area (sq ft)	6.62	1132.07	395.93
Q Total (cfs)	7380.00	Flow (cfs)	5.99	6799.86	574.15
Top Width (ft)	265.24	Top Width (ft)	4.41	105.40	155.42
Vel Total (ft/s)	4.81	Avg. Vel. (ft/s)	0.90	6.01	1.45
Max Chl Dpth (ft)	12.69	Hydr. Depth (ft)	1.50	10.74	2.55
Conv. Total (cfs)	216784.7	Conv. (cfs)	175.8	199743.3	16865.5
Length Wtd. (ft)	90.00	Wetted Per. (ft)	5.28	109.37	155.66
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.09	0.75	0.18
Alpha	1.44	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.07	8.79	1.11
C & E Loss (ft)	0.03	Cum SA (acres)	0.04	0.90	0.61

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 335

INPUT
Description: 7
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	12.5	18	8.1	20	7	30	1.5
40	-.5	50	-2	60	-2	70	-2	80	0
90	4	100	9	135	10	175	10	205	11
260	11	260.1	16						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	18	.04	100	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
18	100	73	73	73	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.93	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.27	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	4.28	756.96	38.76
E.G. Slope (ft/ft)	0.002411	Area (sq ft)	4.28	756.96	38.76
Q Total (cfs)	5910.00	Flow (cfs)	4.64	5879.19	26.17
Top Width (ft)	169.01	Top Width (ft)	3.94	82.00	83.07
Vel Total (ft/s)	7.39	Avg. Vel. (ft/s)	1.08	7.77	0.68
Max Chl Dpth (ft)	12.27	Hydr. Depth (ft)	1.08	9.23	0.47
Conv. Total (cfs)	120358.1	Conv. (cfs)	94.5	119730.7	533.0
Length Wtd. (ft)	73.00	Wetted Per. (ft)	4.50	86.15	83.09
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.14	1.32	0.07
Alpha	1.10	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.02	5.56	0.04
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	0.70	0.07

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.17	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		230.92	
E.G. Slope (ft/ft)	0.004095	Area (sq ft)		230.92	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	60.95	Top Width (ft)		60.95	
Vel Total (ft/s)	5.68	Avg. Vel. (ft/s)		5.68	
Max Chl Dpth (ft)	5.17	Hydr. Depth (ft)		3.79	
Conv. Total (cfs)	20502.4	Conv. (cfs)		20502.4	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		62.49	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		0.94	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.00	1.96	
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.51	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.31	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.50	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		532.59	
E.G. Slope (ft/ft)	0.003103	Area (sq ft)		532.59	

Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	77.91	Top Width (ft)		77.91	
Vel Total (ft/s)	7.23	Avg. Vel. (ft/s)		7.23	
Max Chl Dpth (ft)	9.50	Hydr. Depth (ft)		6.84	
Conv. Total (cfs)	69119.1	Conv. (cfs)		69119.1	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		81.56	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.26	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	4.10	0.00
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.64	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.76	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.92	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		565.64	
E.G. Slope (ft/ft)	0.003034	Area (sq ft)		565.64	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	79.52	Top Width (ft)		79.52	
Vel Total (ft/s)	7.33	Avg. Vel. (ft/s)		7.33	
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)		7.11	
Conv. Total (cfs)	75305.6	Conv. (cfs)		75305.6	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		83.37	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.29	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	4.27	0.00
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.65	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.91	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.46	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	1.68	690.54	3.69
E.G. Slope (ft/ft)	0.002648	Area (sq ft)	1.68	690.54	3.69
Q Total (cfs)	5290.00	Flow (cfs)	1.40	5286.98	1.63
Top Width (ft)	100.54	Top Width (ft)	2.47	82.00	16.06
Vel Total (ft/s)	7.60	Avg. Vel. (ft/s)	0.83	7.66	0.44
Max Chl Dpth (ft)	11.46	Hydr. Depth (ft)	0.68	8.42	0.23
Conv. Total (cfs)	102796.6	Conv. (cfs)	27.2	102737.9	31.6

Length Wtd. (ft)	73.00	Wetted Per. (ft)	2.82	86.15	16.07
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.10	1.33	0.04
Alpha	1.01	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.01	5.19	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	0.68	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.83	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.22	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	15.43	916.88	302.59
E.G. Slope (ft/ft)	0.001761	Area (sq ft)	15.43	916.88	302.59
Q Total (cfs)	7380.00	Flow (cfs)	21.94	6916.37	441.69
Top Width (ft)	249.51	Top Width (ft)	7.49	82.00	160.02
Vel Total (ft/s)	5.98	Avg. Vel. (ft/s)	1.42	7.54	1.46
Max Chl Dpth (ft)	14.22	Hydr. Depth (ft)	2.06	11.18	1.89
Conv. Total (cfs)	175839.3	Conv. (cfs)	522.7	164792.6	10524.0
Length Wtd. (ft)	73.00	Wetted Per. (ft)	8.55	86.15	161.25
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.20	1.17	0.21
Alpha	1.50	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.05	6.67	0.39
C & E Loss (ft)	0.07	Cum SA (acres)	0.03	0.71	0.29

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 262

INPUT
Description: 6
6
6
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	7	9.1	10	7	20	1	30	-2
40	-3	50	-3	60	0	70	5	80	9.5
135	11	175	12	255	13	282	14		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	7	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
7	80	75	75	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.51	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	9.39	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	0.06	599.09	
E.G. Slope (ft/ft)	0.004665	Area (sq ft)	0.06	599.09	
Q Total (cfs)	5910.00	Flow (cfs)	0.02	5909.98	
Top Width (ft)	73.18	Top Width (ft)	0.42	72.76	
Vel Total (ft/s)	9.86	Avg. Vel. (ft/s)	0.38	9.86	
Max Chl Dpth (ft)	12.39	Hydr. Depth (ft)	0.15	8.23	
Conv. Total (cfs)	86530.8	Conv. (cfs)	0.3	86530.5	
Length Wtd. (ft)	75.00	Wetted Per. (ft)	0.51	78.14	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.04	2.23	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.34	Cum Volume (acre-ft)	0.02	4.42	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	0.57	0.00

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.83	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.43	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		179.66	
E.G. Slope (ft/ft)	0.006859	Area (sq ft)		179.66	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.23	Top Width (ft)		47.23	
Vel Total (ft/s)	7.30	Avg. Vel. (ft/s)		7.30	
Max Chl Dpth (ft)	5.43	Hydr. Depth (ft)		3.80	
Conv. Total (cfs)	15841.4	Conv. (cfs)		15841.4	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		49.13	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		1.57	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.00	1.62	
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	0.42	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.95	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.56	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		406.25	
E.G. Slope (ft/ft)	0.005852	Area (sq ft)		406.25	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.72	Top Width (ft)		62.72	
Vel Total (ft/s)	9.48	Avg. Vel. (ft/s)		9.48	
Max Chl Dpth (ft)	9.56	Hydr. Depth (ft)		6.48	
Conv. Total (cfs)	50329.6	Conv. (cfs)		50329.6	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		66.70	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	3.31	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.52	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.40	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.97	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		432.83	
E.G. Slope (ft/ft)	0.005701	Area (sq ft)		432.83	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	64.35	Top Width (ft)		64.35	
Vel Total (ft/s)	9.58	Avg. Vel. (ft/s)		9.58	
Max Chl Dpth (ft)	9.97	Hydr. Depth (ft)		6.73	
Conv. Total (cfs)	54935.4	Conv. (cfs)		54935.4	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		68.54	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.25	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.40	Cum Volume (acre-ft)	0.01	3.44	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.53	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.55	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		539.04	
E.G. Slope (ft/ft)	0.005045	Area (sq ft)		539.04	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	70.12	Top Width (ft)		70.12	
Vel Total (ft/s)	9.81	Avg. Vel. (ft/s)		9.81	
Max Chl Dpth (ft)	11.55	Hydr. Depth (ft)		7.69	
Conv. Total (cfs)	74480.0	Conv. (cfs)		74480.0	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		75.15	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.26	

Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.01	4.16	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.56	0.01

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.50	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.30	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	3.47	738.55	59.83
E.G. Slope (ft/ft)	0.003559	Area (sq ft)	3.47	738.55	59.83
Q Total (cfs)	7380.00	Flow (cfs)	4.42	7300.07	75.51
Top Width (ft)	143.31	Top Width (ft)	3.15	73.00	67.17
Vel Total (ft/s)	9.20	Avg. Vel. (ft/s)	1.27	9.88	1.26
Max Chl Dpth (ft)	14.30	Hydr. Depth (ft)	1.10	10.12	0.89
Conv. Total (cfs)	123714.4	Conv. (cfs)	74.1	122374.5	1265.8
Length Wtd. (ft)	75.00	Wetted Per. (ft)	3.84	78.40	67.19
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.20	2.09	0.20
Alpha	1.14	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.03	5.28	0.08
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	0.58	0.09

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 187

INPUT
Description: 5
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	8	9.2	10	8	20	1.5	30	-2.5
40	-4	50	-4	60	-1	70	4	80	9.5
115	12	141	13	185	14				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	80	50	50	50	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.55	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.46	Wt. n-Val.		0.040	

W.S. Elev (ft)	9.10	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		610.37	
E.G. Slope (ft/ft)	0.004309	Area (sq ft)		610.37	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	71.09	Top Width (ft)		71.09	
Vel Total (ft/s)	9.68	Avg. Vel. (ft/s)		9.68	
Max Chl Dpth (ft)	13.10	Hydr. Depth (ft)		8.59	
Conv. Total (cfs)	90037.4	Conv. (cfs)		90037.4	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		77.13	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.13	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.02	3.38	0.00
C & E Loss (ft)	0.05	Cum SA (acres)	0.01	0.44	0.00

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	2.77	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.70	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.06	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		194.73	
E.G. Slope (ft/ft)	0.005256	Area (sq ft)		194.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.00	Top Width (ft)		47.00	
Vel Total (ft/s)	6.74	Avg. Vel. (ft/s)		6.74	
Max Chl Dpth (ft)	6.06	Hydr. Depth (ft)		4.14	
Conv. Total (cfs)	18097.7	Conv. (cfs)		18097.7	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		49.21	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		1.30	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.00	1.29	
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.34	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.31	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.20	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		419.08	
E.G. Slope (ft/ft)	0.005170	Area (sq ft)		419.08	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.24	Top Width (ft)		61.24	
Vel Total (ft/s)	9.19	Avg. Vel. (ft/s)		9.19	
Max Chl Dpth (ft)	10.20	Hydr. Depth (ft)		6.84	
Conv. Total (cfs)	53543.1	Conv. (cfs)		53543.1	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		65.70	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.06	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00

Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	2.60	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.42	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.97	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.35	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.63	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		445.37	
E.G. Slope (ft/ft)	0.005066	Area (sq ft)		445.37	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.67	Top Width (ft)		62.67	
Vel Total (ft/s)	9.31	Avg. Vel. (ft/s)		9.31	
Max Chl Dpth (ft)	10.63	Hydr. Depth (ft)		7.11	
Conv. Total (cfs)	58280.8	Conv. (cfs)		58280.8	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		67.36	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.09	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.01	2.68	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.42	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.24	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		550.65	
E.G. Slope (ft/ft)	0.004578	Area (sq ft)		550.65	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	68.10	Top Width (ft)		68.10	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	12.24	Hydr. Depth (ft)		8.09	
Conv. Total (cfs)	78187.3	Conv. (cfs)		78187.3	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		73.69	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.14	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.01	3.22	0.01
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	0.44	0.01

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.54	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.49	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.05	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)	2.86	751.09	16.88
E.G. Slope (ft/ft)	0.003405	Area (sq ft)	2.86	751.09	16.88

Q Total (cfs)	7380.00	Flow (cfs)	3.27	7357.75	18.98
Top Width (ft)	96.82	Top Width (ft)	3.09	72.00	21.74
Vel Total (ft/s)	9.57	Avg. Vel. (ft/s)	1.14	9.80	1.12
Max Chl Dpth (ft)	15.05	Hydr. Depth (ft)	0.93	10.43	0.78
Conv. Total (cfs)	126480.5	Conv. (cfs)	56.1	126099.1	325.3
Length Wtd. (ft)	50.00	Wetted Per. (ft)	3.60	78.17	21.79
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.17	2.04	0.16
Alpha	1.04	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.19	Cum Volume (acre-ft)	0.03	4.00	0.02
C & E Loss (ft)	0.07	Cum SA (acres)	0.01	0.45	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 137

INPUT
Description: 4
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	80	77	77	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	16	15	F
70	90	15	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.28	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.36	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.71	Flow Area (sq ft)		531.20	
E.G. Slope (ft/ft)	0.004602	Area (sq ft)	0.00	565.91	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	69.03	Top Width (ft)	0.10	68.93	
Vel Total (ft/s)	11.13	Avg. Vel. (ft/s)		11.13	

Max Chl Dpth (ft)	12.36	Hydr. Depth (ft)		9.84	
Conv. Total (cfs)	87123.8	Conv. (cfs)		87123.8	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.67	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.02	2.71	0.00
C & E Loss (ft)	0.25	Cum SA (acres)	0.00	0.36	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	2.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.62	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	0.50	Flow Area (sq ft)		178.02	
E.G. Slope (ft/ft)	0.006774	Area (sq ft)		178.02	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	45.47	Top Width (ft)		45.47	
Vel Total (ft/s)	7.37	Avg. Vel. (ft/s)		7.37	
Max Chl Dpth (ft)	5.62	Hydr. Depth (ft)		3.92	
Conv. Total (cfs)	15941.3	Conv. (cfs)		15941.3	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		47.57	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		1.58	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.00	1.08	
C & E Loss (ft)	0.13	Cum SA (acres)	0.00	0.29	

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.22	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.54	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.68	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.85	Flow Area (sq ft)		386.61	
E.G. Slope (ft/ft)	0.005631	Area (sq ft)		393.24	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	59.95	Top Width (ft)		59.95	
Vel Total (ft/s)	9.96	Avg. Vel. (ft/s)		9.96	
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)		7.16	
Conv. Total (cfs)	51305.8	Conv. (cfs)		51305.8	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	

Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.37	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	2.14	0.00
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.35	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.08	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.15	Flow Area (sq ft)		408.38	
E.G. Slope (ft/ft)	0.005446	Area (sq ft)		417.68	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	61.32	Top Width (ft)		61.32	
Vel Total (ft/s)	10.16	Avg. Vel. (ft/s)		10.16	
Max Chl Dpth (ft)	10.08	Hydr. Depth (ft)		7.56	
Conv. Total (cfs)	56209.1	Conv. (cfs)		56209.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.42	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	2.19	0.00
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.35	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.40	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.82	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.58	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.20	Flow Area (sq ft)		489.14	
E.G. Slope (ft/ft)	0.004854	Area (sq ft)		513.17	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	66.39	Top Width (ft)		66.39	
Vel Total (ft/s)	10.81	Avg. Vel. (ft/s)		10.81	
Max Chl Dpth (ft)	11.58	Hydr. Depth (ft)		9.06	
Conv. Total (cfs)	75931.7	Conv. (cfs)		75931.7	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.59	

Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	2.61	0.01
C & E Loss (ft)	0.24	Cum SA (acres)	0.00	0.36	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.28	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.15	Wt. n-Val.		0.040	
W.S. Elev (ft)	10.13	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	6.86	Flow Area (sq ft)		627.13	
E.G. Slope (ft/ft)	0.004126	Area (sq ft)	2.95	689.92	1.29
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	75.49	Top Width (ft)	3.22	70.00	2.27
Vel Total (ft/s)	11.77	Avg. Vel. (ft/s)		11.77	
Max Chl Dpth (ft)	14.13	Hydr. Depth (ft)		11.61	
Conv. Total (cfs)	114894.4	Conv. (cfs)		114894.4	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.82	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.03	3.17	0.01
C & E Loss (ft)	0.27	Cum SA (acres)	0.01	0.37	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 98.5

INPUT
Description: Maine Ave.
Distance from Upstream XS = 22
Deck/Roadway Width = 38
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta	Hi Cord	Lo Cord	Sta	Hi Cord	Lo Cord	Sta	Hi Cord	Lo Cord
1	15	-10	18.5	15	-10	18.5	15	10

67	15	10	67	15	-10	100	15	-10	

Upstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left Right Coeff Contr. Expan.
10 80 .3 .5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	16	15	F
70	90	15	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
1	15	-10	18.5	15	-10	18.5	15	10
67	15	10	67	15	-10	100	15	-10

Downstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12.7	14	15.7	-1	18.5	-2	24.4	-4	32.7	-5
42.7	-5	52.7	-3.5	62.7	1	72.7	5.5	74.7	15

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12.7	.065	15.7	.04	72.7	.065

Bank Sta: Left Right Coeff Contr. Expan.
15.7 72.7 .3 .5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
12.7	16	15	F
70	74.7	15	F

Upstream Embankment side slope = 2 horiz. to 1.0 vertical
Downstream Embankment side slope = .1 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow = .98
Elevation at which weir flow begins =
Energy head used in spillway design =
Spillway height used in design =
Weir crest shape = Broad Crested

Number of Bridge Coefficient Sets = 1

Low Flow Methods and Data
Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
Energy Only

Additional Bridge Parameters
Add Friction component to Momentum
Do not add Weight component to Momentum
Class B flow critical depth computations use critical depth
inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Inside BR US	Inside BR DS
E.G. US. (ft)	10.28	Element		
W.S. US. (ft)	8.36	E.G. Elev (ft)	9.90	9.38
Q Total (cfs)	5910.00	W.S. Elev (ft)	7.15	7.23
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	5.73	4.60
Q Weir (cfs)		Max Chl Dpth (ft)	11.15	12.23
Weir Sta Lft (ft)		Vel Total (ft/s)	13.33	11.76
Weir Sta Rgt (ft)		Flow Area (sq ft)	443.49	502.43
Weir Submerg		Froude # Chl	0.70	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	4567.03	4877.91
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	9.14	10.36
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.11	Conv. Total (cfs)	69653.8	86471.9
Delta WS (ft)	1.06	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.22	0.08
BR Open Vel (ft/s)	13.33	C & E Loss (ft)	0.30	0.14
Coef of Q		Shear Total (lb/sq ft)	3.91	2.91
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

			Inside BR US	Inside BR DS
E.G. US. (ft)	2.46	Element		
W.S. US. (ft)	1.62	E.G. Elev (ft)	2.14	1.58

Q Total (cfs)	1312.00	W.S. Elev (ft)	0.87	0.91
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.51	-0.78
Q Weir (cfs)		Max Chl Dpth (ft)	4.87	5.91
Weir Sta Lft (ft)		Vel Total (ft/s)	9.04	6.55
Weir Sta Rgt (ft)		Flow Area (sq ft)	145.15	200.43
Weir Submerg		Froude # Chl	0.86	0.54
Weir Max Depth (ft)		Specif Force (cu ft)	656.17	775.75
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	3.42	4.55
Min El Prs (ft)	10.00	W.P. Total (ft)	44.22	45.46
Delta EG (ft)	0.97	Conv. Total (cfs)	11909.0	20020.2
Delta WS (ft)	0.77	Top Width (ft)	42.48	44.01
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.26	0.07
BR Open Vel (ft/s)	9.04	C & E Loss (ft)	0.30	0.01
Coef of Q		Shear Total (lb/sq ft)	2.49	1.18
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	7.22	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	5.68	E.G. Elev (ft)	6.87	6.31
Q Total (cfs)	3850.00	W.S. Elev (ft)	4.66	4.72
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.81	2.66
Q Weir (cfs)		Max Chl Dpth (ft)	8.66	9.72
Weir Sta Lft (ft)		Vel Total (ft/s)	11.92	10.12
Weir Sta Rgt (ft)		Flow Area (sq ft)	322.86	380.62
Weir Submerg		Froude # Chl	0.71	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	2593.88	2819.42
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	6.66	7.85
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.07	Conv. Total (cfs)	41034.6	54436.6
Delta WS (ft)	0.97	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.25	0.08
BR Open Vel (ft/s)	11.92	C & E Loss (ft)	0.31	0.07
Coef of Q		Shear Total (lb/sq ft)	3.48	2.36
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.69	Element		
W.S. US. (ft)	6.08	E.G. Elev (ft)	7.33	6.77
Q Total (cfs)	4148.00	W.S. Elev (ft)	5.02	5.09
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.10	2.98
Q Weir (cfs)		Max Chl Dpth (ft)	9.02	10.09
Weir Sta Lft (ft)		Vel Total (ft/s)	12.19	10.42
Weir Sta Rgt (ft)		Flow Area (sq ft)	340.25	398.26
Weir Submerg		Froude # Chl	0.72	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	2857.45	3093.35
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	7.02	8.21
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.08	Conv. Total (cfs)	44786.0	58706.1
Delta WS (ft)	1.00	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.24	0.08
BR Open Vel (ft/s)	12.19	C & E Loss (ft)	0.31	0.08
Coef of Q		Shear Total (lb/sq ft)	3.57	2.46
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

			Inside BR US	Inside BR DS
E.G. US. (ft)	9.40	Element		
W.S. US. (ft)	7.58	E.G. Elev (ft)	9.02	8.49
Q Total (cfs)	5290.00	W.S. Elev (ft)	6.41	6.49
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.17	4.05
Q Weir (cfs)		Max Chl Dpth (ft)	10.41	11.49
Weir Sta Lft (ft)		Vel Total (ft/s)	12.97	11.34
Weir Sta Rgt (ft)		Flow Area (sq ft)	407.87	466.55
Weir Submerg		Froude # Chl	0.71	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	3939.28	4223.26
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	8.41	9.62
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.10	Conv. Total (cfs)	60582.1	76425.5
Delta WS (ft)	1.04	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.23	0.08

BR Open Vel (ft/s)	12.97	C & E Loss (ft)	0.31	0.12
Coef of Q		Shear Total (lb/sq ft)	3.81	2.77
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

E.G. US. (ft)	12.28	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	10.13	E.G. Elev (ft)	11.90	11.40
Q Total (cfs)	7380.00	W.S. Elev (ft)	8.83	8.93
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	6.97	5.83
Q Weir (cfs)		Max Chl Dpth (ft)	12.83	13.93
Weir Sta Lft (ft)		Vel Total (ft/s)	14.05	12.62
Weir Sta Rgt (ft)		Flow Area (sq ft)	525.34	584.73
Weir Submerg		Froude # Chl	0.69	0.60
Weir Max Depth (ft)		Specif Force (cu ft)	6158.37	6534.04
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	10.83	12.06
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.13	Conv. Total (cfs)	92371.1	111345.7
Delta WS (ft)	1.09	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.20	0.07
BR Open Vel (ft/s)	14.05	C & E Loss (ft)	0.30	0.18
Coef of Q		Shear Total (lb/sq ft)	4.10	3.18
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Note: Momentum answer is not valid if the water surface is above the low chord or if there is weir flow. The momentum answer has been disregarded.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 60

INPUT

Description: 3

Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12.7	14	15.7	-1	18.5	-2	24.4	-4	32.7	-5
42.7	-5	52.7	-3.5	62.7	1	72.7	5.5	74.7	15

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12.7	.065	15.7	.04	72.7	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15.7	72.7	22	22	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
12.7	16	15	F
70	74.7	15	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.17	Element			
Vel Head (ft)	1.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.30	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.52	Flow Area (sq ft)		538.71	
E.G. Slope (ft/ft)	0.004296	Area (sq ft)	6.88	547.71	0.34
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	59.04	Top Width (ft)	1.66	57.00	0.38
Vel Total (ft/s)	10.97	Avg. Vel. (ft/s)		10.97	
Max Chl Dpth (ft)	12.30	Hydr. Depth (ft)		9.98	
Conv. Total (cfs)	90166.5	Conv. (cfs)		90166.5	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.57	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	1.83	0.00
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.27	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	1.49	Element			
Vel Head (ft)	0.64	Wt. n-Val.		0.040	
W.S. Elev (ft)	0.85	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	-0.76	Flow Area (sq ft)		203.66	
E.G. Slope (ft/ft)	0.004373	Area (sq ft)	0.34	204.23	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.04	Top Width (ft)	0.37	46.67	
Vel Total (ft/s)	6.44	Avg. Vel. (ft/s)		6.44	

Max Chl Dpth (ft)	5.85	Hydr. Depth (ft)		4.39	
Conv. Total (cfs)	19840.0	Conv. (cfs)		19840.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		47.96	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		1.16	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.00	0.77	
C & E Loss (ft)	0.28	Cum SA (acres)	0.00	0.21	

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	6.16	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.45	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.71	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.53	Flow Area (sq ft)		398.91	
E.G. Slope (ft/ft)	0.004963	Area (sq ft)	3.26	400.84	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	56.38	Top Width (ft)	1.14	55.24	
Vel Total (ft/s)	9.65	Avg. Vel. (ft/s)		9.65	
Max Chl Dpth (ft)	9.71	Hydr. Depth (ft)		7.39	
Conv. Total (cfs)	54649.0	Conv. (cfs)		54649.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.19	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)	0.01	1.50	0.00
C & E Loss (ft)	0.15	Cum SA (acres)	0.00	0.26	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.60	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.52	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.08	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.84	Flow Area (sq ft)		419.17	
E.G. Slope (ft/ft)	0.004884	Area (sq ft)	3.70	421.72	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	57.29	Top Width (ft)	1.22	56.08	

Vel Total (ft/s)	9.90	Avg. Vel. (ft/s)		9.90	
Max Chl Dpth (ft)	10.08	Hydr. Depth (ft)		7.76	
Conv. Total (cfs)	59353.4	Conv. (cfs)		59353.4	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.27	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	1.51	0.00
C & E Loss (ft)	0.13	Cum SA (acres)	0.00	0.26	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.29	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.76	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.54	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.97	Flow Area (sq ft)		497.57	
E.G. Slope (ft/ft)	0.004485	Area (sq ft)	5.68	504.29	0.11
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	58.73	Top Width (ft)	1.51	57.00	0.22
Vel Total (ft/s)	10.63	Avg. Vel. (ft/s)		10.63	
Max Chl Dpth (ft)	11.54	Hydr. Depth (ft)		9.21	
Conv. Total (cfs)	78986.1	Conv. (cfs)		78986.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.47	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.01	1.81	0.01
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	0.27	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.15	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.11	Wt. n-Val.		0.040	
W.S. Elev (ft)	9.04	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.66	Flow Area (sq ft)		632.87	
E.G. Slope (ft/ft)	0.003916	Area (sq ft)	10.08	647.10	1.32
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	59.75	Top Width (ft)	2.01	57.00	0.75
Vel Total (ft/s)	11.66	Avg. Vel. (ft/s)		11.66	
Max Chl Dpth (ft)	14.04	Hydr. Depth (ft)		11.72	
Conv. Total (cfs)	117936.0	Conv. (cfs)		117936.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.75	

Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.02	2.14	0.01
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.28	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 38

INPUT
Description: 2
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	13	5	-2	15	-4	20	-4.2	30	-4.5
40	-4	50	1	60	4	62	15		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	5	.04	60	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
5	60	38	38	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.00	Element			
Vel Head (ft)	2.08	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.92	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	13.25	506.88	0.77
E.G. Slope (ft/ft)	0.005276	Area (sq ft)	13.25	506.88	0.77
Q Total (cfs)	5910.00	Flow (cfs)	27.66	5881.82	0.52
Top Width (ft)	58.50	Top Width (ft)	2.97	55.00	0.53
Vel Total (ft/s)	11.35	Avg. Vel. (ft/s)	2.09	11.60	0.68
Max Chl Dpth (ft)	11.42	Hydr. Depth (ft)	4.46	9.22	1.46
Conv. Total (cfs)	81362.3	Conv. (cfs)	380.8	80974.3	7.2
Length Wtd. (ft)	38.00	Wetted Per. (ft)	9.40	56.84	2.96
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.46	2.94	0.09
Alpha	1.04	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.31	Cum Volume (acre-ft)	0.01	1.57	0.00
C & E Loss (ft)	0.22	Cum SA (acres)	0.00	0.24	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	1.05	Element			
Vel Head (ft)	1.57	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	-0.52	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)	-0.52	Flow Area (sq ft)	0.37	130.56	
E.G. Slope (ft/ft)	0.016637	Area (sq ft)	0.37	130.56	
Q Total (cfs)	1312.00	Flow (cfs)	0.41	1311.59	
Top Width (ft)	42.46	Top Width (ft)	0.49	41.97	
Vel Total (ft/s)	10.02	Avg. Vel. (ft/s)	1.12	10.05	
Max Chl Dpth (ft)	3.98	Hydr. Depth (ft)	0.74	3.11	
Conv. Total (cfs)	10171.9	Conv. (cfs)	3.2	10168.7	
Length Wtd. (ft)	38.00	Wetted Per. (ft)	1.56	43.01	
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.24	3.15	
Alpha	1.00	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.44	Cum Volume (acre-ft)	0.00	0.69	
C & E Loss (ft)	0.15	Cum SA (acres)	0.00	0.19	

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

			Left OB	Channel	Right OB
E.G. Elev (ft)	5.86	Element			
Vel Head (ft)	1.96	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.91	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	5.81	341.34	
E.G. Slope (ft/ft)	0.008331	Area (sq ft)	5.81	341.34	
Q Total (cfs)	3850.00	Flow (cfs)	11.59	3838.41	
Top Width (ft)	56.65	Top Width (ft)	1.97	54.69	
Vel Total (ft/s)	11.09	Avg. Vel. (ft/s)	1.99	11.25	
Max Chl Dpth (ft)	8.41	Hydr. Depth (ft)	2.95	6.24	
Conv. Total (cfs)	42181.5	Conv. (cfs)	127.0	42054.5	
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.23	56.51	
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.49	3.14	
Alpha	1.03	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.42	Cum Volume (acre-ft)	0.01	1.31	0.00
C & E Loss (ft)	0.13	Cum SA (acres)	0.00	0.23	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.34	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.96	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.38	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	6.79	367.54	0.01
E.G. Slope (ft/ft)	0.007611	Area (sq ft)	6.79	367.54	0.01
Q Total (cfs)	4148.00	Flow (cfs)	13.62	4134.37	0.00
Top Width (ft)	57.20	Top Width (ft)	2.13	55.00	0.07
Vel Total (ft/s)	11.08	Avg. Vel. (ft/s)	2.01	11.25	0.21
Max Chl Dpth (ft)	8.88	Hydr. Depth (ft)	3.19	6.68	0.19
Conv. Total (cfs)	47545.4	Conv. (cfs)	156.2	47389.2	0.0
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.73	56.84	0.39
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.48	3.07	0.02
Alpha	1.03	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.00	1.31	0.00
C & E Loss (ft)	0.14	Cum SA (acres)	0.00	0.23	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.07	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	10.86	460.56	0.39
E.G. Slope (ft/ft)	0.005824	Area (sq ft)	10.86	460.56	0.39
Q Total (cfs)	5290.00	Flow (cfs)	22.31	5267.47	0.22
Top Width (ft)	58.07	Top Width (ft)	2.69	55.00	0.38
Vel Total (ft/s)	11.21	Avg. Vel. (ft/s)	2.05	11.44	0.57
Max Chl Dpth (ft)	10.57	Hydr. Depth (ft)	4.04	8.37	1.04
Conv. Total (cfs)	69315.7	Conv. (cfs)	292.3	69020.6	2.9
Length Wtd. (ft)	38.00	Wetted Per. (ft)	8.51	56.84	2.11
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.46	2.95	0.07
Alpha	1.04	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.01	1.56	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.24	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.02	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.23	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	8.79	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	19.41	610.11	2.09
E.G. Slope (ft/ft)	0.004425	Area (sq ft)	19.41	610.11	2.09
Q Total (cfs)	7380.00	Flow (cfs)	42.16	7336.04	1.81
Top Width (ft)	59.47	Top Width (ft)	3.60	55.00	0.87
Vel Total (ft/s)	11.68	Avg. Vel. (ft/s)	2.17	12.02	0.86
Max Chl Dpth (ft)	13.29	Hydr. Depth (ft)	5.40	11.09	2.40
Conv. Total (cfs)	110944.6	Conv. (cfs)	633.8	110283.7	27.1
Length Wtd. (ft)	38.00	Wetted Per. (ft)	11.38	56.84	4.87
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.47	2.97	0.12
Alpha	1.05	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.02	1.82	0.01
C & E Loss (ft)	0.26	Cum SA (acres)	0.00	0.25	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 0

INPUT
Description: 1 (Downstream)
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	19	1	19	10	2	20	-6.3	30	-6.3
40	-5	50	-2.5	52	1.8	60	19		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	52	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	52	21	21	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	8.48	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.24	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.24	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.24	Flow Area (sq ft)	1.33	357.35	1.39
E.G. Slope (ft/ft)	0.013662	Area (sq ft)	1.33	357.35	1.39

Q Total (cfs)	5910.00	Flow (cfs)	2.31	5905.31	2.38
Top Width (ft)	44.32	Top Width (ft)	1.19	42.00	1.14
Vel Total (ft/s)	16.41	Avg. Vel. (ft/s)	1.74	16.53	1.72
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	1.12	8.51	1.22
Conv. Total (cfs)	50562.8	Conv. (cfs)	19.8	50522.7	20.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	2.54	48.13	2.69
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.45	6.33	0.44
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.00	1.19	0.00
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	0.20	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	0.42	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.08	Wt. n-Val.		0.040	
W.S. Elev (ft)	-0.66	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	-1.54	Flow Area (sq ft)		157.23	
E.G. Slope (ft/ft)	0.008477	Area (sq ft)		157.23	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	37.65	Top Width (ft)		37.65	
Vel Total (ft/s)	8.34	Avg. Vel. (ft/s)		8.34	
Max Chl Dpth (ft)	5.64	Hydr. Depth (ft)		4.18	
Conv. Total (cfs)	14249.8	Conv. (cfs)		14249.8	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		41.26	
Min Ch El (ft)	-6.30	Shear (lb/sq ft)		2.02	
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.00	0.56	
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.15	

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.21	Wt. n-Val.	0.000	0.040	0.065
W.S. Elev (ft)	2.11	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.11	Flow Area (sq ft)	0.00	267.76	0.02
E.G. Slope (ft/ft)	0.015198	Area (sq ft)	0.00	267.76	0.02
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3849.99	0.01

Top Width (ft)	42.20	Top Width (ft)	0.06	42.00	0.14
Vel Total (ft/s)	14.38	Avg. Vel. (ft/s)	0.24	14.38	0.46
Max Chl Dpth (ft)	8.41	Hydr. Depth (ft)	0.05	6.38	0.15
Conv. Total (cfs)	31229.7	Conv. (cfs)	0.0	31229.6	0.1
Length Wtd. (ft)	21.00	Wetted Per. (ft)	0.12	48.13	0.34
Min Ch El (ft)	-6.30	Shear (lb/sq ft)		5.28	0.06
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.00	1.04	0.00
C & E Loss (ft)	0.33	Cum SA (acres)	0.00	0.19	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.36	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	2.45	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.45	Flow Area (sq ft)	0.05	281.94	0.10
E.G. Slope (ft/ft)	0.014853	Area (sq ft)	0.05	281.94	0.10
Q Total (cfs)	4148.00	Flow (cfs)	0.03	4147.90	0.07
Top Width (ft)	42.54	Top Width (ft)	0.24	42.00	0.30
Vel Total (ft/s)	14.70	Avg. Vel. (ft/s)	0.62	14.71	0.74
Max Chl Dpth (ft)	8.75	Hydr. Depth (ft)	0.22	6.71	0.32
Conv. Total (cfs)	34035.3	Conv. (cfs)	0.3	34034.4	0.6
Length Wtd. (ft)	21.00	Wetted Per. (ft)	0.50	48.13	0.71
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.10	5.43	0.13
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.00	1.03	0.00
C & E Loss (ft)	0.32	Cum SA (acres)	0.00	0.19	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.58	Element	Left OB	Channel	Right OB

Vel Head (ft)	3.96	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.62	Flow Area (sq ft)	0.69	331.05	0.77
E.G. Slope (ft/ft)	0.014135	Area (sq ft)	0.69	331.05	0.77
Q Total (cfs)	5290.00	Flow (cfs)	0.98	5287.92	1.10
Top Width (ft)	43.70	Top Width (ft)	0.86	42.00	0.84
Vel Total (ft/s)	15.91	Avg. Vel. (ft/s)	1.42	15.97	1.43
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.81	7.88	0.91
Conv. Total (cfs)	44494.8	Conv. (cfs)	8.3	44477.3	9.2
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.83	48.13	2.00
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.33	6.07	0.34
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.00	1.22	0.01
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.20	0.01

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	10.49	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.62	Flow Area (sq ft)	3.47	415.35	3.40
E.G. Slope (ft/ft)	0.012870	Area (sq ft)	3.47	415.35	3.40
Q Total (cfs)	7380.00	Flow (cfs)	8.07	7364.30	7.63
Top Width (ft)	45.70	Top Width (ft)	1.92	42.00	1.78
Vel Total (ft/s)	17.48	Avg. Vel. (ft/s)	2.32	17.73	2.25
Max Chl Dpth (ft)	11.92	Hydr. Depth (ft)	1.81	9.89	1.91
Conv. Total (cfs)	65054.0	Conv. (cfs)	71.1	64915.6	67.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	4.10	48.13	4.22
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.68	6.93	0.65
Alpha	1.03	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.38	0.00
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is

not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -21

INPUT
Description: RR
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	15	8	-3	25	-7	30	-7	37	-6
50	-2	59	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	59	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	59	33	33	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.91	Element			
Vel Head (ft)	6.09	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.82	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	3.29	Flow Area (sq ft)	5.17	297.09	
E.G. Slope (ft/ft)	0.024570	Area (sq ft)	5.17	297.09	
Q Total (cfs)	5910.00	Flow (cfs)	18.28	5891.73	
Top Width (ft)	45.71	Top Width (ft)	2.14	43.56	
Vel Total (ft/s)	19.55	Avg. Vel. (ft/s)	3.53	19.83	
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)	2.41	6.82	
Conv. Total (cfs)	37703.4	Conv. (cfs)	116.6	37586.8	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	5.28	47.27	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.50	9.64	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.00	1.03	0.00
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.18	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	0.18	Element			
Vel Head (ft)	0.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	-0.51	Reach Len. (ft)	33.00	33.00	33.00

Crit W.S. (ft)		Flow Area (sq ft)	1.38	196.50	
E.G. Slope (ft/ft)	0.004483	Area (sq ft)	1.38	196.50	
Q Total (cfs)	1312.00	Flow (cfs)	1.34	1310.66	
Top Width (ft)	43.72	Top Width (ft)	1.11	42.61	
Vel Total (ft/s)	6.63	Avg. Vel. (ft/s)	0.97	6.67	
Max Chl Dpth (ft)	6.49	Hydr. Depth (ft)	1.24	4.61	
Conv. Total (cfs)	19594.6	Conv. (cfs)	20.0	19574.7	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	2.72	44.75	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.14	1.23	
Alpha	1.01	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.00	0.47	
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.13	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.66	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.10	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.56	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	1.22	Flow Area (sq ft)	6.87	329.34	
E.G. Slope (ft/ft)	0.007551	Area (sq ft)	6.87	329.34	
Q Total (cfs)	3850.00	Flow (cfs)	14.81	3835.19	
Top Width (ft)	46.34	Top Width (ft)	2.47	43.87	
Vel Total (ft/s)	11.45	Avg. Vel. (ft/s)	2.15	11.64	
Max Chl Dpth (ft)	9.56	Hydr. Depth (ft)	2.78	7.51	
Conv. Total (cfs)	44306.6	Conv. (cfs)	170.4	44136.2	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.09	48.07	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.53	3.23	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.00	0.90	0.00
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.17	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.24	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.91	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	0.34	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	1.55	Flow Area (sq ft)	2.47	232.78	
E.G. Slope (ft/ft)	0.026135	Area (sq ft)	2.47	232.78	
Q Total (cfs)	4148.00	Flow (cfs)	7.06	4140.94	
Top Width (ft)	44.44	Top Width (ft)	1.48	42.96	
Vel Total (ft/s)	17.63	Avg. Vel. (ft/s)	2.85	17.79	
Max Chl Dpth (ft)	7.34	Hydr. Depth (ft)	1.67	5.42	
Conv. Total (cfs)	25658.1	Conv. (cfs)	43.7	25614.4	

Length Wtd. (ft)	33.00	Wetted Per. (ft)	3.65	45.66	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.11	8.32	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	0.91	0.00
C & E Loss (ft)	0.15	Cum SA (acres)	0.00	0.17	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	5.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.32	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	2.71	Flow Area (sq ft)	4.15	275.33	
E.G. Slope (ft/ft)	0.025006	Area (sq ft)	4.15	275.33	
Q Total (cfs)	5290.00	Flow (cfs)	13.76	5276.24	
Top Width (ft)	45.28	Top Width (ft)	1.92	43.36	
Vel Total (ft/s)	18.93	Avg. Vel. (ft/s)	3.31	19.16	
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.35	
Conv. Total (cfs)	33452.7	Conv. (cfs)	87.0	33365.6	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	4.73	46.73	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.37	9.20	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.00	1.07	0.01
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.18	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	9.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.98	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.94	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	4.65	Flow Area (sq ft)	7.84	346.01	
E.G. Slope (ft/ft)	0.023784	Area (sq ft)	7.84	346.01	
Q Total (cfs)	7380.00	Flow (cfs)	31.34	7348.67	
Top Width (ft)	46.66	Top Width (ft)	2.64	44.02	
Vel Total (ft/s)	20.86	Avg. Vel. (ft/s)	4.00	21.24	
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	2.97	7.86	
Conv. Total (cfs)	47853.6	Conv. (cfs)	203.2	47650.5	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.50	48.48	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.79	10.60	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.00	1.19	0.00
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -54

INPUT
Description: K2
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	21	5	40	-7	50	-7
60	-6	72	-2	80	0	88	2	96	4

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	88	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	88	34	34	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	6.72	Element			
Vel Head (ft)	4.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.85	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	3.09	Flow Area (sq ft)		333.87	
E.G. Slope (ft/ft)	0.025698	Area (sq ft)		333.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	61.41	Top Width (ft)		61.41	
Vel Total (ft/s)	17.70	Avg. Vel. (ft/s)		17.70	
Max Chl Dpth (ft)	8.85	Hydr. Depth (ft)		5.44	
Conv. Total (cfs)	36867.0	Conv. (cfs)		36867.0	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		65.15	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		8.22	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.83	Cum Volume (acre-ft)		0.79	0.00
C & E Loss (ft)	0.37	Cum SA (acres)		0.14	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	0.02	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	-0.67	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		196.83	
E.G. Slope (ft/ft)	0.005185	Area (sq ft)		196.83	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.34	Top Width (ft)		47.34	
Vel Total (ft/s)	6.67	Avg. Vel. (ft/s)		6.67	
Max Chl Dpth (ft)	6.33	Hydr. Depth (ft)		4.16	
Conv. Total (cfs)	18220.8	Conv. (cfs)		18220.8	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		50.04	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.27	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.29	Cum Volume (acre-ft)		0.33	
C & E Loss (ft)	0.08	Cum SA (acres)		0.10	

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.52	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.72	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		388.60	1.05
E.G. Slope (ft/ft)	0.006877	Area (sq ft)		388.60	1.05
Q Total (cfs)	3850.00	Flow (cfs)		3849.01	0.99
Top Width (ft)	66.29	Top Width (ft)		63.40	2.90
Vel Total (ft/s)	9.88	Avg. Vel. (ft/s)		9.90	0.94
Max Chl Dpth (ft)	9.72	Hydr. Depth (ft)		6.13	0.36
Conv. Total (cfs)	46426.8	Conv. (cfs)		46414.9	11.9
Length Wtd. (ft)	34.00	Wetted Per. (ft)		67.40	2.98
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.48	0.15
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.63	0.00
C & E Loss (ft)	0.09	Cum SA (acres)		0.13	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.62	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.62	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.00	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	1.58	Flow Area (sq ft)		406.25	2.01
E.G. Slope (ft/ft)	0.006950	Area (sq ft)		406.25	2.01
Q Total (cfs)	4148.00	Flow (cfs)		4145.64	2.36
Top Width (ft)	67.84	Top Width (ft)		63.84	4.01
Vel Total (ft/s)	10.16	Avg. Vel. (ft/s)		10.20	1.18
Max Chl Dpth (ft)	10.00	Hydr. Depth (ft)		6.36	0.50
Conv. Total (cfs)	49755.9	Conv. (cfs)		49727.6	28.3
Length Wtd. (ft)	34.00	Wetted Per. (ft)		67.92	4.13
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.60	0.21
Alpha	1.01	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.66	0.00
C & E Loss (ft)	0.09	Cum SA (acres)		0.13	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.98	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.93	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	2.59	Flow Area (sq ft)		466.13	7.44
E.G. Slope (ft/ft)	0.007362	Area (sq ft)		466.13	7.44
Q Total (cfs)	5290.00	Flow (cfs)		5276.04	13.96
Top Width (ft)	73.02	Top Width (ft)		65.30	7.71
Vel Total (ft/s)	11.17	Avg. Vel. (ft/s)		11.32	1.88
Max Chl Dpth (ft)	10.93	Hydr. Depth (ft)		7.14	0.96
Conv. Total (cfs)	61651.5	Conv. (cfs)		61488.8	162.7
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.66	7.95
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		3.08	0.43
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.79	0.00
C & E Loss (ft)	0.08	Cum SA (acres)		0.14	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	8.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.75	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.18	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		354.06	0.06
E.G. Slope (ft/ft)	0.033780	Area (sq ft)		354.06	0.06
Q Total (cfs)	7380.00	Flow (cfs)		7379.95	0.05
Top Width (ft)	63.23	Top Width (ft)		62.53	0.70
Vel Total (ft/s)	20.84	Avg. Vel. (ft/s)		20.84	0.81
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.66	0.09
Conv. Total (cfs)	40153.7	Conv. (cfs)		40153.5	0.3
Length Wtd. (ft)		Wetted Per. (ft)		66.37	0.72
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		11.25	0.18
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)		0.93	0.00
C & E Loss (ft)	0.07	Cum SA (acres)		0.15	0.00

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -88

INPUT
Description: K1
Station Elevation Data num= 8

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	56	-6	72	-6	80	-5
94	0	108	5	122	5				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	108	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	108	55	55	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.18	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	3.18	Flow Area (sq ft)		428.87	
E.G. Slope (ft/ft)	0.013653	Area (sq ft)		428.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	72.75	Top Width (ft)		72.75	
Vel Total (ft/s)	13.78	Avg. Vel. (ft/s)		13.78	
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.90	
Conv. Total (cfs)	50579.2	Conv. (cfs)		50579.2	

Length Wtd. (ft)	55.00	Wetted Per. (ft)		75.82	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.82	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.74	Cum Volume (acre-ft)		0.50	0.00
C & E Loss (ft)	0.02	Cum SA (acres)		0.09	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	-0.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.52	Wt. n-Val.		0.040	
W.S. Elev (ft)	-1.87	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	-1.87	Flow Area (sq ft)		132.74	
E.G. Slope (ft/ft)	0.017077	Area (sq ft)		132.74	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	44.37	Top Width (ft)		44.37	
Vel Total (ft/s)	9.88	Avg. Vel. (ft/s)		9.88	
Max Chl Dpth (ft)	4.13	Hydr. Depth (ft)		2.99	
Conv. Total (cfs)	10039.9	Conv. (cfs)		10039.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		45.68	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		3.10	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.62	Cum Volume (acre-ft)		0.20	
C & E Loss (ft)	0.20	Cum SA (acres)		0.06	

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	3.83	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.45	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.38	Reach Len. (ft)	55.00	55.00	55.00

Crit W.S. (ft)	1.38	Flow Area (sq ft)		306.55	
E.G. Slope (ft/ft)	0.014466	Area (sq ft)		306.55	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.61	Top Width (ft)		62.61	
Vel Total (ft/s)	12.56	Avg. Vel. (ft/s)		12.56	
Max Chl Dpth (ft)	7.38	Hydr. Depth (ft)		4.90	
Conv. Total (cfs)	32009.6	Conv. (cfs)		32009.6	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		65.05	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.26	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.80	Cum Volume (acre-ft)		0.36	0.00
C & E Loss (ft)	0.00	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.67	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	1.67	Flow Area (sq ft)		324.94	
E.G. Slope (ft/ft)	0.014320	Area (sq ft)		324.94	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	64.23	Top Width (ft)		64.23	
Vel Total (ft/s)	12.77	Avg. Vel. (ft/s)		12.77	
Max Chl Dpth (ft)	7.67	Hydr. Depth (ft)		5.06	
Conv. Total (cfs)	34663.2	Conv. (cfs)		34663.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		66.77	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.35	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.79	Cum Volume (acre-ft)		0.38	0.00
C & E Loss (ft)	0.00	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.68	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	2.68	Flow Area (sq ft)		393.12	
E.G. Slope (ft/ft)	0.013858	Area (sq ft)		393.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	69.94	Top Width (ft)		69.94	
Vel Total (ft/s)	13.46	Avg. Vel. (ft/s)		13.46	
Max Chl Dpth (ft)	8.68	Hydr. Depth (ft)		5.62	
Conv. Total (cfs)	44937.7	Conv. (cfs)		44937.7	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		72.83	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.67	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.75	Cum Volume (acre-ft)		0.46	0.00
C & E Loss (ft)	0.01	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	7.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.25	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	4.25	Flow Area (sq ft)		509.28	
E.G. Slope (ft/ft)	0.013360	Area (sq ft)		509.28	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	78.71	Top Width (ft)		78.71	
Vel Total (ft/s)	14.49	Avg. Vel. (ft/s)		14.49	
Max Chl Dpth (ft)	10.25	Hydr. Depth (ft)		6.47	
Conv. Total (cfs)	63848.9	Conv. (cfs)		63848.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		82.14	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		5.17	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)		0.59	0.00
C & E Loss (ft)		Cum SA (acres)		0.09	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for

additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -143

INPUT
Description: K0
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11.3	10	52.7	-7	69	-7	77.8	-6
98.2	-1	100	-1						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11.3	.04	98.2	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11.3	98.2	0	0	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	5.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.21	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	0.87	Reach Len. (ft)			
Crit W.S. (ft)	1.76	Flow Area (sq ft)		357.78	3.37
E.G. Slope (ft/ft)	0.021059	Area (sq ft)		357.78	3.37
Q Total (cfs)	5910.00	Flow (cfs)		5899.45	10.55
Top Width (ft)	66.47	Top Width (ft)		64.67	1.80
Vel Total (ft/s)	16.36	Avg. Vel. (ft/s)		16.49	3.13
Max Chl Dpth (ft)	7.87	Hydr. Depth (ft)		5.53	1.87
Conv. Total (cfs)	40725.3	Conv. (cfs)		40652.6	72.7
Length Wtd. (ft)		Wetted Per. (ft)		66.88	3.67
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		7.03	1.21
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.92	Cum Volume (acre-ft)			
C & E Loss (ft)	0.13	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.

This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	-1.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	-2.10	Reach Len. (ft)			
Crit W.S. (ft)	-2.96	Flow Area (sq ft)		178.85	
E.G. Slope (ft/ft)	0.007984	Area (sq ft)		178.85	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	52.94	Top Width (ft)		52.94	
Vel Total (ft/s)	7.34	Avg. Vel. (ft/s)		7.34	
Max Chl Dpth (ft)	4.90	Hydr. Depth (ft)		3.38	
Conv. Total (cfs)	14683.3	Conv. (cfs)		14683.3	
Length Wtd. (ft)		Wetted Per. (ft)		54.44	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.64	
Alpha	1.00	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	2.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.42	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	-0.70	Reach Len. (ft)			
Crit W.S. (ft)	0.07	Flow Area (sq ft)		259.44	0.55
E.G. Slope (ft/ft)	0.024042	Area (sq ft)		259.44	0.55
Q Total (cfs)	3850.00	Flow (cfs)		3849.21	0.79
Top Width (ft)	62.65	Top Width (ft)		60.85	1.80
Vel Total (ft/s)	14.81	Avg. Vel. (ft/s)		14.84	1.44
Max Chl Dpth (ft)	6.30	Hydr. Depth (ft)		4.26	0.30
Conv. Total (cfs)	24829.7	Conv. (cfs)		24824.6	5.1
Length Wtd. (ft)		Wetted Per. (ft)		62.76	2.10
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.21	0.39
Alpha	1.00	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	1.01	Cum Volume (acre-ft)			
C & E Loss (ft)	0.10	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	3.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.56	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	-0.46	Reach Len. (ft)			
Crit W.S. (ft)	0.32	Flow Area (sq ft)		273.91	0.97
E.G. Slope (ft/ft)	0.023585	Area (sq ft)		273.91	0.97
Q Total (cfs)	4148.00	Flow (cfs)		4146.10	1.91
Top Width (ft)	63.23	Top Width (ft)		61.43	1.80
Vel Total (ft/s)	15.09	Avg. Vel. (ft/s)		15.14	1.96
Max Chl Dpth (ft)	6.54	Hydr. Depth (ft)		4.46	0.54
Conv. Total (cfs)	27009.5	Conv. (cfs)		26997.1	12.4
Length Wtd. (ft)		Wetted Per. (ft)		63.38	2.34
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.36	0.61
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	1.00	Cum Volume (acre-ft)			
C & E Loss (ft)	0.10	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	4.43	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.02	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	0.41	Reach Len. (ft)			
Crit W.S. (ft)	1.29	Flow Area (sq ft)		328.10	2.53
E.G. Slope (ft/ft)	0.021991	Area (sq ft)		328.10	2.53
Q Total (cfs)	5290.00	Flow (cfs)		5282.66	7.34
Top Width (ft)	65.34	Top Width (ft)		63.54	1.80
Vel Total (ft/s)	16.00	Avg. Vel. (ft/s)		16.10	2.90
Max Chl Dpth (ft)	7.41	Hydr. Depth (ft)		5.16	1.41
Conv. Total (cfs)	35672.4	Conv. (cfs)		35622.9	49.5
Length Wtd. (ft)		Wetted Per. (ft)		65.66	3.21
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.86	1.08
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.95	Cum Volume (acre-ft)			
C & E Loss (ft)	0.12	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	6.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.57	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	1.94	Reach Len. (ft)			
Crit W.S. (ft)	2.81	Flow Area (sq ft)		428.54	5.30
E.G. Slope (ft/ft)	0.018989	Area (sq ft)		428.54	5.30
Q Total (cfs)	7380.00	Flow (cfs)		7362.03	17.97
Top Width (ft)	69.08	Top Width (ft)		67.28	1.80
Vel Total (ft/s)	17.01	Avg. Vel. (ft/s)		17.18	3.39
Max Chl Dpth (ft)	8.94	Hydr. Depth (ft)		6.37	2.94
Conv. Total (cfs)	53555.1	Conv. (cfs)		53424.7	130.4
Length Wtd. (ft)		Wetted Per. (ft)		69.71	4.74
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		7.29	1.32
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)			
C & E Loss (ft)	0.13	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

SUMMARY OF MANNING'S N VALUES

River:Cobosee Stream

Reach	River Sta.	n1	n2	n3
Reach 1	1700	.07	.04	.065
Reach 1	1635	.07	.045	.065
Reach 1	1555	.07	.042	.065
Reach 1	1455	.065	.045	.07
Reach 1	1335	.065	.045	.075
Reach 1	1185	.065	.045	.07
Reach 1	1060	.065	.04	.07
Reach 1	960	.07	.042	.05
Reach 1	935	.065	.042	.07
Reach 1	895	Bridge		
Reach 1	850	.065	.04	.065
Reach 1	830	.065	.04	.065
Reach 1	821	.065	.035	.065
Reach 1	820	.065	.035	.065
Reach 1	725	.065	.04	.065
Reach 1	575	.065	.04	.065
Reach 1	425	.065	.04	.065
Reach 1	335	.065	.04	.065

Reach 1	262	.065	.04	.065
Reach 1	187	.065	.04	.065
Reach 1	137	.065	.04	.065
Reach 1	98.5	Bridge		
Reach 1	60	.065	.04	.065
Reach 1	38	.065	.04	.065
Reach 1	0	.065	.04	.065
Reach 1	-21	.065	.04	.065
Reach 1	-54	.065	.04	.065
Reach 1	-88	.065	.04	.065
Reach 1	-143	.065	.04	.065

SUMMARY OF REACH LENGTHS

River: Cobosee Stream

Reach	River Sta.	Left	Channel	Right
Reach 1	1700	65	65	65
Reach 1	1635	80	80	80
Reach 1	1555	100	100	100
Reach 1	1455	120	120	120
Reach 1	1335	150	150	150
Reach 1	1185	125	125	125
Reach 1	1060	100	100	100
Reach 1	960	25	25	25
Reach 1	935	85	85	85
Reach 1	895	Bridge		
Reach 1	850	20	20	20
Reach 1	830	9	9	9
Reach 1	821	1	1	1
Reach 1	820	95	95	95
Reach 1	725	150	150	150
Reach 1	575	150	150	150
Reach 1	425	90	90	90
Reach 1	335	73	73	73
Reach 1	262	75	75	75
Reach 1	187	50	50	50
Reach 1	137	77	77	77
Reach 1	98.5	Bridge		
Reach 1	60	22	22	22
Reach 1	38	38	38	38
Reach 1	0	21	21	21
Reach 1	-21	33	33	33
Reach 1	-54	34	34	34
Reach 1	-88	55	55	55

					Existing MLW.rep
Reach 1	-143		0	0	0

SUMMARY OF CONTRACTION AND EXPANSION COEFFICIENTS
River: Cobosee Stream

Reach	River Sta.	Contr.	Expan.
Reach 1	1700	.1	.3
Reach 1	1635	.1	.3
Reach 1	1555	.1	.3
Reach 1	1455	.1	.3
Reach 1	1335	.1	.3
Reach 1	1185	.1	.3
Reach 1	1060	.1	.3
Reach 1	960	.3	.5
Reach 1	935	.3	.5
Reach 1	895	Bridge	
Reach 1	850	.3	.5
Reach 1	830	.3	.5
Reach 1	821	.3	.5
Reach 1	820	.3	.5
Reach 1	725	.1	.3
Reach 1	575	.1	.3
Reach 1	425	.1	.3
Reach 1	335	.1	.3
Reach 1	262	.1	.3
Reach 1	187	.1	.3
Reach 1	137	.3	.5
Reach 1	98.5	Bridge	
Reach 1	60	.3	.5
Reach 1	38	.1	.3
Reach 1	0	.1	.3
Reach 1	-21	.1	.3
Reach 1	-54	.1	.3
Reach 1	-88	.1	.3
Reach 1	-143	.1	.3

Profile Output Table - Standard Table 1

Reach	River Sta	Profile	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl

Reach 1	1700		Q100	5910.00	13.80	22.75	21.32	24.48	0.006899
10.56	559.56	84.99		0.73					
Reach 1	1700		Q1.1	1312.00	13.80	18.54	17.33	19.04	0.004837
5.66	231.75	70.35		0.55					
Reach 1	1700		Q10	3850.00	13.80	21.15	19.81	22.41	0.006488
8.99	428.08	79.67		0.68					
Reach 1	1700		Q25	4148.00	13.80	21.40	20.05	22.73	0.006586
9.26	447.72	80.49		0.69					
Reach 1	1700		Q50	5290.00	13.80	22.28	20.89	23.89	0.006865
10.17	519.99	83.43		0.72					
Reach 1	1700		Q500	7380.00	13.80	23.79	22.27	25.79	0.006886
11.36	649.74	88.50		0.74					
Reach 1	1635		Q100	5910.00	14.00	22.26		23.95	0.009286
10.45	565.74	91.56		0.74					
Reach 1	1635		Q1.1	1312.00	14.00	17.69		18.50	0.015059
7.21	181.92	75.56		0.82					
Reach 1	1635		Q10	3850.00	14.00	20.47		21.86	0.010706
9.45	407.41	86.07		0.77					
Reach 1	1635		Q25	4148.00	14.00	20.75		22.19	0.010420
9.61	431.49	86.93		0.76					
Reach 1	1635		Q50	5290.00	14.00	21.75		23.36	0.009593
10.17	520.12	90.01		0.75					
Reach 1	1635		Q500	7380.00	14.00	23.37		25.25	0.008749
11.03	669.19	94.97		0.73					
Reach 1	1555		Q100	5910.00	13.30	20.34	20.16	22.96	0.013988
12.99	455.10	80.13		0.96					
Reach 1	1555		Q1.1	1312.00	13.30	16.65		17.46	0.011277
7.21	181.93	67.33		0.77					
Reach 1	1555		Q10	3850.00	13.30	19.06	18.65	20.89	0.012591
10.84	355.06	76.34		0.89					
Reach 1	1555		Q25	4148.00	13.30	19.24	18.89	21.21	0.013022
11.25	368.78	76.87		0.90					
Reach 1	1555		Q50	5290.00	13.30	19.96	19.73	22.37	0.013832
12.46	424.40	78.99		0.95					
Reach 1	1555		Q500	7380.00	13.30	21.24	21.12	24.27	0.013932
13.96	528.58	82.81		0.97					
Reach 1	1455		Q100	5910.00	11.80	19.15	18.73	21.52	0.013387
12.37	481.88	84.97		0.89					
Reach 1	1455		Q1.1	1312.00	11.80	15.06	14.87	16.04	0.018077
7.92	165.73	68.77		0.90					
Reach 1	1455		Q10	3850.00	11.80	17.40	17.28	19.41	0.017110

11.38	338.91	78.76		0.96					
Reach 1	1455		Q25	4148.00	11.80	17.67	17.49	19.74	0.016462
11.55	360.01	79.70		0.95					
Reach 1	1455		Q50	5290.00	11.80	18.65	18.33	20.92	0.014390
12.10	439.82	83.19		0.91					
Reach 1	1455		Q500	7380.00	11.80	20.29		22.87	0.011588
12.93	580.92	89.01		0.86					
Reach 1	1335		Q100	5910.00	9.50	18.29		20.09	0.008451
10.77	549.55	80.41		0.72					
Reach 1	1335		Q1.1	1312.00	9.50	12.63	12.50	13.78	0.019322
8.58	152.88	58.82		0.94					
Reach 1	1335		Q10	3850.00	9.50	16.13		17.69	0.010520
10.02	384.19	72.81		0.77					
Reach 1	1335		Q25	4148.00	9.50	16.47		18.07	0.010117
10.13	409.60	74.07		0.76					
Reach 1	1335		Q50	5290.00	9.50	17.69		19.41	0.008914
10.54	502.02	78.36		0.73					
Reach 1	1335		Q500	7380.00	9.50	19.61		21.58	0.007511
11.27	659.01	85.25		0.70					
Reach 1	1185		Q100	5910.00	5.50	15.74	15.05	18.44	0.013066
13.18	448.42	64.17		0.88					
Reach 1	1185		Q1.1	1312.00	5.50	10.99		11.81	0.008702
7.27	180.57	47.96		0.66					
Reach 1	1185		Q10	3850.00	5.50	14.08	13.16	16.00	0.011509
11.11	346.47	58.78		0.81					
Reach 1	1185		Q25	4148.00	5.50	14.34	13.46	16.38	0.011809
11.46	361.81	59.62		0.82					
Reach 1	1185		Q50	5290.00	5.50	15.27	14.52	17.75	0.012741
12.65	418.21	62.62		0.86					
Reach 1	1185		Q500	7380.00	5.50	16.59	16.20	19.92	0.014396
14.65	504.00	66.73		0.93					
Reach 1	1060		Q100	5910.00	5.00	13.57	13.57	16.72	0.013789
14.24	415.00	66.76		1.01					
Reach 1	1060		Q1.1	1312.00	5.00	8.85	8.85	10.26	0.017292
9.54	137.48	49.24		1.01					
Reach 1	1060		Q10	3850.00	5.00	11.81	11.81	14.33	0.014662
12.72	302.66	61.04		1.01					
Reach 1	1060		Q25	4148.00	5.00	12.10	12.10	14.70	0.014382
12.94	320.59	62.01		1.00					
Reach 1	1060		Q50	5290.00	5.00	13.10	13.10	16.05	0.013832
13.77	384.11	65.31		1.00					
Reach 1	1060		Q500	7380.00	5.00	14.68	14.68	18.19	0.013247
15.03	490.87	70.19		1.00					

Reach 1	960		Q100	5910.00	3.50	12.54	11.33	14.82	0.008563
12.15	495.72	82.79		0.77					
Reach 1	960		Q1.1	1312.00	3.50	7.54	6.91	8.38	0.009882
7.35	178.49	56.92		0.73					
Reach 1	960		Q10	3850.00	3.50	10.76	9.68	12.41	0.008769
10.32	373.52	64.43		0.75					
Reach 1	960		Q25	4148.00	3.50	11.04	9.93	12.79	0.008725
10.62	391.65	65.09		0.75					
Reach 1	960		Q50	5290.00	3.50	12.04	10.87	14.14	0.008580
11.63	458.31	68.60		0.76					
Reach 1	960		Q500	7380.00	3.50	11.41	12.50	16.33	0.022762
17.82	415.83	65.95		1.22					
Reach 1	935		Q100	5910.00	2.00	13.04	10.34	14.06	0.003531
8.25	809.75	158.21		0.51					
Reach 1	935		Q1.1	1312.00	2.00	7.58	5.91	8.04	0.004364
5.44	241.37	66.50		0.50					
Reach 1	935		Q10	3850.00	2.00	11.00	8.78	11.87	0.004311
7.49	526.51	114.51		0.54					
Reach 1	935		Q25	4148.00	2.00	11.32	9.03	12.22	0.004193
7.65	563.83	123.44		0.54					
Reach 1	935		Q50	5290.00	2.00	12.46	9.93	13.45	0.003743
8.08	723.33	156.11		0.52					
Reach 1	935		Q500	7380.00	2.00	14.22	11.33	15.32	0.003277
8.71	987.87	168.60		0.51					
Reach 1	895		Bridge						
Reach 1	850		Q100	5910.00	1.00	11.56	9.38	12.72	0.004490
8.76	737.73	144.16		0.58					
Reach 1	850		Q1.1	1312.00	1.00	6.86	4.89	7.25	0.003268
5.01	262.03	69.29		0.45					
Reach 1	850		Q10	3850.00	1.00	9.48	7.75	10.53	0.005737
8.22	474.86	103.69		0.63					
Reach 1	850		Q25	4148.00	1.00	9.82	8.01	10.88	0.005609
8.31	511.28	113.83		0.62					
Reach 1	850		Q50	5290.00	1.00	10.94	8.91	12.08	0.004917
8.67	651.61	134.32		0.60					
Reach 1	850		Q500	7380.00	1.00	13.08	10.40	14.20	0.003513
8.72	962.68	157.76		0.52					
Reach 1	830		Q100	5910.00	1.00	11.54		12.57	0.003454

```
8.19      768.79      147.28                0.53
  Reach 1       830          Q1.1       1312.00        1.00        6.80                 7.17     0.004037
4.90      267.69       88.18                0.50
  Reach 1       830          Q10        3850.00        1.00        9.47                10.34     0.004399
7.49      515.84       95.94                0.57
  Reach 1       830          Q25        4148.00        1.00        9.81                10.70     0.004218
7.60      548.21       96.67                0.56
  Reach 1       830          Q50        5290.00        1.00       10.92                11.93     0.003757
8.05      680.74      136.18                0.54
  Reach 1       830          Q500       7380.00        1.00       13.07                14.09     0.002737
8.26     1000.53      153.73                0.49


  Reach 1       821          Q100       5910.00        1.00       11.53                12.53     0.002866
8.05      768.40      157.69                0.54
  Reach 1       821          Q1.1       1312.00        1.00        6.72                 7.13     0.003214
5.14      255.20       80.51                0.51
  Reach 1       821          Q10        3850.00        1.00        9.41                10.30     0.003921
7.58      507.74      103.12                0.60
  Reach 1       821          Q25        4148.00        1.00        9.77                10.67     0.003649
7.61      545.09      103.92                0.59
  Reach 1       821          Q50        5290.00        1.00       10.90                11.88     0.003150
7.95      677.07      134.94                0.56
  Reach 1       821          Q500       7380.00        1.00       13.07                14.04     0.002233
8.04     1014.09      161.42                0.49


  Reach 1       820          Q100       5910.00        1.00       11.59                12.46     0.002824
7.49      832.41      193.15                0.53
  Reach 1       820          Q1.1       1312.00        1.00        6.71                 7.12     0.003228
5.15      254.82       80.46                0.51
  Reach 1       820          Q10        3850.00        1.00        9.40                10.29     0.004315
7.57      508.45      111.75                0.63
  Reach 1       820          Q25        4148.00        1.00        9.77                10.65     0.004246
7.52      551.32      120.93                0.62
  Reach 1       820          Q50        5290.00        1.00       10.95                11.83     0.003290
7.51      722.96      156.10                0.56
  Reach 1       820          Q500       7380.00        1.00       13.18                13.92     0.001862
7.09     1260.27      281.71                0.45


  Reach 1       725          Q100       5910.00        2.50       11.30                12.14     0.003724
7.36      832.82      188.19                0.53
  Reach 1       725          Q1.1       1312.00        2.50        6.19                 6.68     0.006470
5.62      233.27       89.27                0.61
  Reach 1       725          Q10        3850.00        2.50        8.81                 9.79     0.005976
7.94      484.70      103.23                0.65
  Reach 1       725          Q25        4148.00        2.50        9.18                10.15     0.005798
7.92      523.96      109.64                0.64
```

Reach 1	725		Q50	5290.00	2.50	10.57	11.46	0.004654
7.54	707.44	157.21		0.58				
Reach 1	725		Q500	7380.00	2.50	13.00	13.72	0.002360
6.92	1208.76	247.45		0.44				
Reach 1	575		Q100	5910.00	1.50	11.08	11.67	0.001918
6.22	1026.90	220.83		0.40				
Reach 1	575		Q1.1	1312.00	1.50	4.64	5.33	0.012980
6.66	197.13	99.10		0.83				
Reach 1	575		Q10	3850.00	1.50	8.39	9.01	0.003452
6.35	606.59	120.11		0.50				
Reach 1	575		Q25	4148.00	1.50	8.80	9.42	0.003151
6.32	656.54	122.72		0.48				
Reach 1	575		Q50	5290.00	1.50	10.29	10.90	0.002253
6.27	871.16	174.83		0.42				
Reach 1	575		Q500	7380.00	1.50	12.87	13.39	0.001335
5.97	1486.21	269.19		0.34				
Reach 1	425		Q100	5910.00	0.00	10.82	11.41	0.001604
6.22	1051.38	244.73		0.37				
Reach 1	425		Q1.1	1312.00	0.00	3.63	4.09	0.005213
5.45	240.73	81.90		0.56				
Reach 1	425		Q10	3850.00	0.00	8.02	8.58	0.002271
5.98	643.65	100.36		0.42				
Reach 1	425		Q25	4148.00	0.00	8.45	9.01	0.002174
6.04	686.74	101.97		0.41				
Reach 1	425		Q50	5290.00	0.00	10.00	10.60	0.001827
6.22	869.43	148.17		0.39				
Reach 1	425		Q500	7380.00	0.00	12.69	13.21	0.001159
6.01	1534.62	265.24		0.32				
Reach 1	335		Q100	5910.00	-2.00	10.27	11.20	0.002411
7.77	800.00	169.01		0.45				
Reach 1	335		Q1.1	1312.00	-2.00	3.17	3.67	0.004095
5.68	230.92	60.95		0.51				
Reach 1	335		Q10	3850.00	-2.00	7.50	8.31	0.003103
7.23	532.59	77.91		0.49				
Reach 1	335		Q25	4148.00	-2.00	7.92	8.76	0.003034
7.33	565.64	79.52		0.48				
Reach 1	335		Q50	5290.00	-2.00	9.46	10.37	0.002648
7.66	695.90	100.54		0.46				
Reach 1	335		Q500	7380.00	-2.00	12.22	13.05	0.001761
7.54	1234.90	249.51		0.40				
Reach 1	262		Q100	5910.00	-3.00	9.39	10.90	0.004665

```
9.86      599.15       73.18                0.61
  Reach 1       262            Q1.1       1312.00       -3.00        2.43                    3.25     0.006859
7.30      179.66       47.23                0.66
  Reach 1       262            Q10        3850.00       -3.00        6.56                    7.95     0.005852
9.48      406.25       62.72                0.66
  Reach 1       262            Q25        4148.00       -3.00        6.97                    8.40     0.005701
9.58      432.83       64.35                0.65
  Reach 1       262            Q50        5290.00       -3.00        8.55                   10.05     0.005045
9.81      539.04       70.12                0.62
  Reach 1       262            Q500       7380.00       -3.00       11.30                   12.81     0.003559
9.88      801.85      143.31                0.55


  Reach 1       187            Q100       5910.00       -4.00        9.10                   10.55     0.004309
9.68      610.37       71.09                0.58
  Reach 1       187            Q1.1       1312.00       -4.00        2.06                    2.77     0.005256
6.74      194.73       47.00                0.58
  Reach 1       187            Q10        3850.00       -4.00        6.20                    7.51     0.005170
9.19      419.08       61.24                0.62
  Reach 1       187            Q25        4148.00       -4.00        6.63                    7.97     0.005066
9.31      445.37       62.67                0.62
  Reach 1       187            Q50        5290.00       -4.00        8.24                    9.67     0.004578
9.61      550.65       68.10                0.60
  Reach 1       187            Q500       7380.00       -4.00       11.05                   12.54     0.003405
9.80      770.83       96.82                0.53


  Reach 1       137            Q100       5910.00       -4.00        8.36        5.71        10.28     0.004602
11.13      531.20       69.03                0.63
  Reach 1       137            Q1.1       1312.00       -4.00        1.62        0.50         2.46     0.006774
7.37      178.02       45.47                0.66
  Reach 1       137            Q10        3850.00       -4.00        5.68        3.85         7.22     0.005631
9.96      386.61       59.95                0.66
  Reach 1       137            Q25        4148.00       -4.00        6.08        4.15         7.69     0.005446
10.16      408.38       61.32                0.65
  Reach 1       137            Q50        5290.00       -4.00        7.58        5.20         9.40     0.004854
10.81      489.14       66.39                0.63
  Reach 1       137            Q500       7380.00       -4.00       10.13        6.86        12.28     0.004126
11.77      627.13       75.49                0.61


  Reach 1      98.5                         Bridge


  Reach 1       60             Q100       5910.00       -5.00        7.30        4.52         9.17     0.004296
10.97      538.71       59.04                0.61
  Reach 1       60             Q1.1       1312.00       -5.00        0.85       -0.76         1.49     0.004373
6.44      203.66       47.04                0.54
```

Reach 1	60		Q10	3850.00	-5.00	4.71	2.53	6.16	0.004963
9.65	398.91	56.38		0.63					
Reach 1	60		Q25	4148.00	-5.00	5.08	2.84	6.60	0.004884
9.90	419.17	57.29		0.63					
Reach 1	60		Q50	5290.00	-5.00	6.54	3.97	8.29	0.004485
10.63	497.57	58.73		0.62					
Reach 1	60		Q500	7380.00	-5.00	9.04	5.66	11.15	0.003916
11.66	632.87	59.75		0.60					
Reach 1	38		Q100	5910.00	-4.50	6.92		9.00	0.005276
11.60	520.91	58.50		0.67					
Reach 1	38		Q1.1	1312.00	-4.50	-0.52	-0.52	1.05	0.016637
10.05	130.93	42.46		1.00					
Reach 1	38		Q10	3850.00	-4.50	3.91		5.86	0.008331
11.25	347.15	56.65		0.79					
Reach 1	38		Q25	4148.00	-4.50	4.38		6.34	0.007611
11.25	374.35	57.20		0.77					
Reach 1	38		Q50	5290.00	-4.50	6.07		8.10	0.005824
11.44	471.82	58.07		0.70					
Reach 1	38		Q500	7380.00	-4.50	8.79		11.02	0.004425
12.02	631.61	59.47		0.64					
Reach 1	0		Q100	5910.00	-6.30	4.24	4.24	8.48	0.013662
16.53	360.07	44.32		1.00					
Reach 1	0		Q1.1	1312.00	-6.30	-0.66	-1.54	0.42	0.008477
8.34	157.23	37.65		0.72					
Reach 1	0		Q10	3850.00	-6.30	2.11	2.11	5.32	0.015198
14.38	267.79	42.20		1.00					
Reach 1	0		Q25	4148.00	-6.30	2.45	2.45	5.81	0.014853
14.71	282.09	42.54		1.00					
Reach 1	0		Q50	5290.00	-6.30	3.62	3.62	7.58	0.014135
15.97	332.50	43.70		1.00					
Reach 1	0		Q500	7380.00	-6.30	5.62	5.62	10.49	0.012870
17.73	422.22	45.70		0.99					
Reach 1	-21		Q100	5910.00	-7.00	1.82	3.29	7.91	0.024570
19.83	302.26	45.71		1.34					
Reach 1	-21		Q1.1	1312.00	-7.00	-0.51		0.18	0.004483
6.67	197.87	43.72		0.55					
Reach 1	-21		Q10	3850.00	-7.00	2.56	1.22	4.66	0.007551
11.64	336.22	46.34		0.75					
Reach 1	-21		Q25	4148.00	-7.00	0.34	1.55	5.24	0.026135
17.79	235.26	44.44		1.35					
Reach 1	-21		Q50	5290.00	-7.00	1.32	2.71	7.01	0.025006
19.16	279.48	45.28		1.34					
Reach 1	-21		Q500	7380.00	-7.00	2.94	4.65	9.92	0.023784

21.24	353.85	46.66		1.34					
Reach 1	-54		Q100	5910.00	-7.00	1.85	3.09	6.72	0.025698
17.70	333.87	61.41		1.34					
Reach 1	-54		Q1.1	1312.00	-7.00	-0.67		0.02	0.005185
6.67	196.83	47.34		0.58					
Reach 1	-54		Q10	3850.00	-7.00	2.72		4.25	0.006877
9.90	389.65	66.29		0.71					
Reach 1	-54		Q25	4148.00	-7.00	3.00	1.58	4.62	0.006950
10.20	408.26	67.84		0.71					
Reach 1	-54		Q50	5290.00	-7.00	3.93	2.59	5.91	0.007362
11.32	473.56	73.02		0.75					
Reach 1	-54		Q500	7380.00	-7.00	2.18	4.20	8.92	0.033780
20.84	354.12	63.23		1.54					
Reach 1	-88		Q100	5910.00	-6.00	3.18	3.18	6.13	0.013653
13.78	428.87	72.75		1.00					
Reach 1	-88		Q1.1	1312.00	-6.00	-1.87	-1.87	-0.35	0.017077
9.88	132.74	44.37		1.01					
Reach 1	-88		Q10	3850.00	-6.00	1.38	1.38	3.83	0.014466
12.56	306.55	62.61		1.00					
Reach 1	-88		Q25	4148.00	-6.00	1.67	1.67	4.20	0.014320
12.77	324.94	64.23		1.00					
Reach 1	-88		Q50	5290.00	-6.00	2.68	2.68	5.50	0.013858
13.46	393.12	69.94		1.00					
Reach 1	-88		Q500	7380.00	-6.00	4.25	4.25	7.51	0.013360
14.49	509.28	78.71		1.00					
Reach 1	-143		Q100	5910.00	-7.00	0.87	1.76	5.09	0.021059
16.49	361.15	66.47		1.24					
Reach 1	-143		Q1.1	1312.00	-7.00	-2.10	-2.96	-1.26	0.007984
7.34	178.85	52.94		0.70					
Reach 1	-143		Q10	3850.00	-7.00	-0.70	0.07	2.72	0.024042
14.84	259.99	62.65		1.27					
Reach 1	-143		Q25	4148.00	-7.00	-0.46	0.32	3.10	0.023585
15.14	274.89	63.23		1.26					
Reach 1	-143		Q50	5290.00	-7.00	0.41	1.29	4.43	0.021991
16.10	330.63	65.34		1.25					
Reach 1	-143		Q500	7380.00	-7.00	1.94	2.81	6.52	0.018989
17.18	433.84	69.08		1.20					

Profile Output Table - Six XS Bridge


Reach	River Sta	Profile	E.G. Elev	W.S. Elev	Crit W.S.	Frctn Loss	C & E Loss	Top Width
Q Left	Q Channel	Q Right	Vel Chnl					
(cfs)	(cfs)	(cfs)	(ft/s)	(ft)	(ft)	(ft)	(ft)	(ft)
Reach 1	960		Q100	14.82	12.54	11.33	0.13	0.63	82.79
0.20	5891.34	18.46	12.15						
Reach 1	960		Q1.1	8.38	7.54	6.91	0.16	0.19	56.92
	1312.00		7.35						
Reach 1	960		Q10	12.41	10.76	9.68	0.15	0.39	64.43
0.01	3849.40	0.59	10.32						
Reach 1	960		Q25	12.79	11.04	9.93	0.15	0.42	65.09
0.02	4146.46	1.52	10.62						
Reach 1	960		Q50	14.14	12.04	10.87	0.14	0.55	68.60
0.11	5280.65	9.24	11.63						
Reach 1	960		Q500	16.33	11.41	12.50	1.71	0.14	65.95
0.06	7373.96	5.97	17.82						
Reach 1	935		Q100	14.06	13.04	10.34	0.10	0.29	158.21
12.49	5673.06	224.45	8.25						
Reach 1	935		Q1.1	8.04	7.58	5.91	0.10	0.09	66.50
	1312.00		5.44						
Reach 1	935		Q10	11.87	11.00	8.78	0.12	0.24	114.51
0.71	3837.48	11.81	7.49						
Reach 1	935		Q25	12.22	11.32	9.03	0.11	0.24	123.44
1.46	4122.46	24.08	7.65						
Reach 1	935		Q50	13.45	12.46	9.93	0.10	0.28	156.11
7.33	5154.48	128.19	8.08						
Reach 1	935		Q500	15.32	14.22	11.33	0.09	0.23	168.60
28.83	6873.98	477.18	8.71						
Reach 1	895	BR U	Q100	13.67	11.70	10.78	0.48	0.29	121.45
4.65	5851.97	53.38	11.34						
Reach 1	895	BR U	Q1.1	7.84	7.07	6.09	0.35	0.14	55.33
	1312.00		7.03						
Reach 1	895	BR U	Q10	11.51	9.84	9.19	0.59	0.19	77.17
	3850.00		10.37						
Reach 1	895	BR U	Q25	11.86	10.15	9.45	0.58	0.19	78.50
0.01	4147.99		10.49						
Reach 1	895	BR U	Q50	13.07	11.14	10.32	0.52	0.26	105.53
1.67	5272.37	15.96	11.15						
Reach 1	895	BR U	Q500	15.01	13.14	11.89	0.38	0.28	140.56
21.43	7059.92	298.66	11.21						
Reach 1	895	BR D	Q100	12.90	11.51	9.93	0.07	0.12	133.26


5.53	5712.93	191.53	9.62						
Reach 1	895	BR D	Q1.1	7.34	6.86	5.12	0.05	0.05	62.17
	1312.00		5.57						
Reach 1	895	BR D	Q10	10.74	9.44	8.13	0.08	0.13	95.67
	3842.43	7.57	9.15						
Reach 1	895	BR D	Q25	11.09	9.77	8.40	0.08	0.13	105.79
	4130.48	17.52	9.24						
Reach 1	895	BR D	Q50	12.28	10.88	9.40	0.07	0.13	126.95
1.40	5183.68	104.92	9.58						
Reach 1	895	BR D	Q500	14.35	13.04	10.88	0.05	0.10	145.07
32.16	6874.93	472.90	9.49						
Reach 1	850		Q100	12.72	11.56	9.38	0.08	0.07	144.16
4.86	5749.56	155.58	8.76						
Reach 1	850		Q1.1	7.25	6.86	4.89	0.07	0.01	69.29
	1312.00		5.01						
Reach 1	850		Q10	10.53	9.48	7.75	0.10	0.09	103.69
	3843.10	6.90	8.22						
Reach 1	850		Q25	10.88	9.82	8.01	0.10	0.09	113.83
	4132.32	15.68	8.31						
Reach 1	850		Q50	12.08	10.94	8.91	0.09	0.07	134.32
1.32	5199.07	89.61	8.67						
Reach 1	850		Q500	14.20	13.08	10.40	0.06	0.05	157.76
26.65	6944.32	409.03	8.72						
Reach 1	830		Q100	12.57	11.54		0.03	0.01	147.28
2.70	5835.78	71.52	8.19						
Reach 1	830		Q1.1	7.17	6.80		0.03	0.01	88.18
	1312.00		4.90						
Reach 1	830		Q10	10.34	9.47		0.04	0.01	95.94
	3847.49	2.51	7.49						
Reach 1	830		Q25	10.70	9.81		0.04	0.00	96.67
	4145.14	2.86	7.60						
Reach 1	830		Q50	11.93	10.92		0.03	0.01	136.18
0.71	5262.19	27.10	8.05						
Reach 1	830		Q500	14.09	13.07		0.02	0.02	153.73
15.12	7098.19	266.69	8.26						
Reach 1	187		Q100	10.55	9.10		0.22	0.05	71.09
	5910.00		9.68						
Reach 1	187		Q1.1	2.77	2.06		0.30	0.01	47.00
	1312.00		6.74						
Reach 1	187		Q10	7.51	6.20		0.27	0.02	61.24
	3850.00		9.19						


Reach 1	187		Q25	7.97	6.63		0.26	0.03	62.67
4148.00		9.31							
Reach 1	187		Q50	9.67	8.24		0.24	0.04	68.10
5290.00		9.61							
Reach 1	187		Q500	12.54	11.05		0.19	0.07	96.82
3.27	7357.75	18.98	9.80						
Reach 1	137		Q100	10.28	8.36	5.71	0.13	0.25	69.03
5910.00		11.13							
Reach 1	137		Q1.1	2.46	1.62	0.50	0.20	0.13	45.47
1312.00		7.37							
Reach 1	137		Q10	7.22	5.68	3.85	0.15	0.20	59.95
3850.00		9.96							
Reach 1	137		Q25	7.69	6.08	4.15	0.15	0.21	61.32
4148.00		10.16							
Reach 1	137		Q50	9.40	7.58	5.20	0.13	0.24	66.39
5290.00		10.81							
Reach 1	137		Q500	12.28	10.13	6.86	0.11	0.27	75.49
7380.00		11.77							
Reach 1	98.5	BR U	Q100	9.90	7.15	5.73	0.22	0.30	48.50
5910.00		13.33							
Reach 1	98.5	BR U	Q1.1	2.14	0.87	0.51	0.26	0.30	42.48
1312.00		9.04							
Reach 1	98.5	BR U	Q10	6.87	4.66	3.81	0.25	0.31	48.50
3850.00		11.92							
Reach 1	98.5	BR U	Q25	7.33	5.02	4.10	0.24	0.31	48.50
4148.00		12.19							
Reach 1	98.5	BR U	Q50	9.02	6.41	5.17	0.23	0.31	48.50
5290.00		12.97							
Reach 1	98.5	BR U	Q500	11.90	8.83	6.97	0.20	0.30	48.50
7380.00		14.05							
Reach 1	98.5	BR D	Q100	9.38	7.23	4.60	0.08	0.14	48.50
5910.00		11.76							
Reach 1	98.5	BR D	Q1.1	1.58	0.91	-0.78	0.07	0.01	44.01
1312.00		6.55							
Reach 1	98.5	BR D	Q10	6.31	4.72	2.66	0.08	0.07	48.50
3850.00		10.12							
Reach 1	98.5	BR D	Q25	6.77	5.09	2.98	0.08	0.08	48.50
4148.00		10.42							
Reach 1	98.5	BR D	Q50	8.49	6.49	4.05	0.08	0.12	48.50
5290.00		11.34							
Reach 1	98.5	BR D	Q500	11.40	8.93	5.83	0.07	0.18	48.50
7380.00		12.62							


Reach 1	60		Q100	9.17	7.30	4.52	0.10	0.06	59.04
	5910.00		10.97						
Reach 1	60		Q1.1	1.49	0.85	-0.76	0.17	0.28	47.04
	1312.00		6.44						
Reach 1	60		Q10	6.16	4.71	2.53	0.14	0.15	56.38
	3850.00		9.65						
Reach 1	60		Q25	6.60	5.08	2.84	0.13	0.13	57.29
	4148.00		9.90						
Reach 1	60		Q50	8.29	6.54	3.97	0.11	0.08	58.73
	5290.00		10.63						
Reach 1	60		Q500	11.15	9.04	5.66	0.09	0.04	59.75
	7380.00		11.66						
Reach 1	38		Q100	9.00	6.92		0.31	0.22	58.50
27.66	5881.82	0.52	11.60						
Reach 1	38		Q1.1	1.05	-0.52	-0.52	0.44	0.15	42.46
0.41	1311.59		10.05						
Reach 1	38		Q10	5.86	3.91		0.42	0.13	56.65
11.59	3838.41		11.25						
Reach 1	38		Q25	6.34	4.38		0.39	0.14	57.20
13.62	4134.37	0.00	11.25						
Reach 1	38		Q50	8.10	6.07		0.33	0.19	58.07
22.31	5267.47	0.22	11.44						
Reach 1	38		Q500	11.02	8.79		0.27	0.26	59.47
42.16	7336.04	1.81	12.02						


APPENDIX E / HEC-RAS RESULTS FOR EXISTING CONDITIONS AT MHW



1700
1635
1555
1455
1335
1185
1060
960
895
850
725
575
425
335
262
187
137
60
21
88
143
Robosee Stream
Reach 1
EXISTING PLAN, HEC-RAS SECTIONS
MHW RUN
None of the XS's are Geo-Referenced (Geo-Ref user entered XS Geo-Ref interpolated XS Non Geo-Ref user entered XS Non Geo-Ref interpolated XS)



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
Cobosee Stream Reach 1
Legend
WS Q100
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q500
Ground
Elevation (ft)
30
25
20
15
10
5
0
-5
-10
-500
0
500
1000
1500
2000
Main Channel Distance (ft)



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1700 Upstream (I)
.07
.04
.065
Elevation (ft)
Station (ft)
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
180
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1635 H
.07
.045
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1555 G
.07
.042
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1455 F
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1335 E
.065
.045
.075
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1185 D
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1060 C
.065
.04
.07
Elevation (ft)
35
30
25
20
15
10
5
0
50
100
150
200
Station (ft)
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 960 B
.07
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q100
WS Q50
WS Q500
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 935 JU
.065
.042
.07
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 895 BR Bridge Street
.065
.042
.07
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 895 BR Bridge Street
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 850 JD
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 830 A
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 821 AD
.065
.035
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 820 ADD
.065
.035
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 725 10
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 575 9
.065
.04
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 425 8
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 335 7
.065
.04
.065
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
250
300



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 262 6
.04
.065
.0
6
5
Elevation (ft)
Station (ft)
14
12
10
8
6
4
2
0
-2
-4
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 187 5
.065
.04
.065
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta
Elevation (ft)
15
10
5
0
-5
0
50
100
150
200
Station (ft)



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 137 4
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
15
10
5
0
-5
Elevation (ft)
0
20
40
60
80
100
Station (ft)
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 60 3
.065
.04
.065
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80



Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 38 2
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
10
20
30
40
50
60
70
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 0 1 (Downstream)
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q100
WS Q1.1
WS Q50
WS Q10
WS Q25
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -21 RR
.065
.04
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q1.1
WS Q10
WS Q25
WS Q500
WS Q100
WS Q50
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -54 K2
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q50
WS Q25
WS Q10
WS Q1.1
WS Q500
WS Q100
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
22 ft/s
24 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -88 K1
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q100
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta


Gardiner Existing Plan: Plan 21 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -143 K0
.065
.04
.065
Legend
WS Q100
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q500
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100

HEC-RAS Version 4.1.0 Jan 2010
U.S. Army Corps of Engineers
Hydrologic Engineering Center
609 Second Street
Davis, California

```
X     X  XXXXXX    XXXX        XXXX       XX      XXXX
X     X  X        X    X      X   X     X  X    X
X     X  X        X           X   X    X    X   X
XXXXXXX  XXXX     X       XXX  XXXX     XXXXXX    XXXX
X     X  X        X           X  X     X    X        X
X     X  X        X    X      X   X    X    X        X
X     X  XXXXXX    XXXX       X    X   X    X   XXXXX
```

PROJECT DATA
Project Title: Gardiner Existing
Project File : Existing.prj
Run Date and Time: 4/18/2018 9:40:21 AM

Project in English units

PLAN DATA

Plan Title: Plan 21
Plan File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.p21

Geometry Title: Geom 01
Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.g01

Flow Title : MHW +3.8 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.f02

Plan Summary Information:
Number of: Cross Sections = 27 Multiple Openings = 0
Culverts = 0 Inline Structures = 0
Bridges = 2 Lateral Structures = 0

Computational Information
Water surface calculation tolerance = 0.01

Critical depth calculation tolerance = 0.01
Maximum number of iterations = 20
Maximum difference tolerance = 0.3
Flow tolerance factor = 0.001

Computation Options
Critical depth computed only where necessary
Conveyance Calculation Method: At breaks in n values only
Friction Slope Method: Average Conveyance
Computational Flow Regime: Mixed Flow

FLOW DATA

Flow Title: MHW +3.8 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.f02

Flow Data (cfs)

River	Reach	RS	Q100	Q1.1	Q10	Q25	Q50	Q500
Cobosee Stream	Reach 1	1700	5910	1312	3850	4148	5290	7380
Cobosee Stream	Reach 1	-88	5910	1312	3850	4148	5290	7380

Boundary Conditions

River	Reach	Profile	Upstream	Downstream
Cobosee Stream	Reach 1	Q100	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q1.1	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q10	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q25	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q50	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q500	Critical	Known WS = 3.8

GEOMETRY DATA

Geometry Title: Geom 01

Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Existing\Existing.g01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1700

INPUT
Description: Upstream (I)
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	40	10	39.7	20	39.2	30	37.2	40	34.5
50	29	60	23.5	70	17.5	80	15.5	90	14.5
100	13.8	110	14.2	120	14.8	130	15.7	140	19
150	25	160	31	170	33.3				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	60	.04	150	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
60	150	65	65	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	24.48	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.75	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	21.32	Flow Area (sq ft)		559.56	
E.G. Slope (ft/ft)	0.006899	Area (sq ft)		559.56	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	84.99	Top Width (ft)		84.99	
Vel Total (ft/s)	10.56	Avg. Vel. (ft/s)		10.56	
Max Chl Dpth (ft)	8.95	Hydr. Depth (ft)		6.58	
Conv. Total (cfs)	71152.0	Conv. (cfs)		71152.0	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		88.36	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.73	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.08	25.59	1.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.07	3.56	1.24

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	19.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	18.54	Reach Len. (ft)	65.00	65.00	65.00

Crit W.S. (ft)	17.33	Flow Area (sq ft)		231.75	
E.G. Slope (ft/ft)	0.004837	Area (sq ft)		231.75	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	70.35	Top Width (ft)		70.35	
Vel Total (ft/s)	5.66	Avg. Vel. (ft/s)		5.66	
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)		3.29	
Conv. Total (cfs)	18865.3	Conv. (cfs)		18865.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		71.44	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		0.98	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.51	Cum Volume (acre-ft)	0.01	10.29	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	2.84	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	22.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.15	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	19.81	Flow Area (sq ft)		428.08	
E.G. Slope (ft/ft)	0.006488	Area (sq ft)		428.08	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	79.67	Top Width (ft)		79.67	
Vel Total (ft/s)	8.99	Avg. Vel. (ft/s)		8.99	
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	47797.3	Conv. (cfs)		47797.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		82.15	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.11	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.01	18.41	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.31	0.04

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.73	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.33	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.40	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.05	Flow Area (sq ft)		447.72	
E.G. Slope (ft/ft)	0.006586	Area (sq ft)		447.72	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	80.49	Top Width (ft)		80.49	
Vel Total (ft/s)	9.26	Avg. Vel. (ft/s)		9.26	
Max Chl Dpth (ft)	7.60	Hydr. Depth (ft)		5.56	
Conv. Total (cfs)	51113.1	Conv. (cfs)		51113.1	

Length Wtd. (ft)	65.00	Wetted Per. (ft)		83.10	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.02	19.46	0.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.38	0.05

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.28	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.89	Flow Area (sq ft)		519.99	
E.G. Slope (ft/ft)	0.006865	Area (sq ft)		519.99	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	83.43	Top Width (ft)		83.43	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	63848.2	Conv. (cfs)		63848.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		86.53	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.04	23.50	0.34
C & E Loss (ft)	0.00	Cum SA (acres)	0.04	3.54	0.54

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.00	Wt. n-Val.	0.070	0.040	
W.S. Elev (ft)	23.79	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	22.27	Flow Area (sq ft)	0.08	649.66	
E.G. Slope (ft/ft)	0.006886	Area (sq ft)	0.08	649.66	
Q Total (cfs)	7380.00	Flow (cfs)	0.03	7379.97	
Top Width (ft)	88.50	Top Width (ft)	0.52	87.98	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	0.44	11.36	
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	0.14	7.38	
Conv. Total (cfs)	88934.8	Conv. (cfs)	0.4	88934.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)	0.60	91.84	
Min Ch El (ft)	13.80	Shear (lb/sq ft)	0.05	3.04	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.50	Cum Volume (acre-ft)	0.25	30.53	4.08
C & E Loss (ft)	0.03	Cum SA (acres)	0.14	3.60	2.01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1635

INPUT
Description: H

Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	23.5	40	17
50	14	60	14.5	70	15	80	15.2	90	15.4
100	15.6	110	15.8	115	17.9	120	20	130	26.5
140	30.1	150	30.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.045	130	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	130	80	80	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	23.95	Element			
Vel Head (ft)	1.69	Wt. n-Val.		0.045	
W.S. Elev (ft)	22.26	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		565.74	
E.G. Slope (ft/ft)	0.009286	Area (sq ft)		565.74	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	91.56	Top Width (ft)		91.56	
Vel Total (ft/s)	10.45	Avg. Vel. (ft/s)		10.45	
Max Chl Dpth (ft)	8.26	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	61329.1	Conv. (cfs)		61329.1	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		95.11	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.45	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.90	Cum Volume (acre-ft)	0.08	24.75	1.04
C & E Loss (ft)	0.09	Cum SA (acres)	0.07	3.43	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	18.50	Element			
Vel Head (ft)	0.81	Wt. n-Val.		0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		181.92	
E.G. Slope (ft/ft)	0.015059	Area (sq ft)		181.92	

Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	75.56	Top Width (ft)		75.56	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	10691.3	Conv. (cfs)		10691.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		76.62	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		2.23	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.04	Cum Volume (acre-ft)	0.01	9.98	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	2.73	0.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	21.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.47	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		407.41	
E.G. Slope (ft/ft)	0.010706	Area (sq ft)		407.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	86.07	Top Width (ft)		86.07	
Vel Total (ft/s)	9.45	Avg. Vel. (ft/s)		9.45	
Max Chl Dpth (ft)	6.47	Hydr. Depth (ft)		4.73	
Conv. Total (cfs)	37209.8	Conv. (cfs)		37209.8	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		88.57	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.07	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.01	17.79	0.03
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	3.19	0.04

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.44	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		431.49	
E.G. Slope (ft/ft)	0.010420	Area (sq ft)		431.49	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	86.93	Top Width (ft)		86.93	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	6.75	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	40635.0	Conv. (cfs)		40635.0	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		89.59	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.13	

Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.02	18.80	0.04
C & E Loss (ft)	0.05	Cum SA (acres)	0.01	3.25	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.36	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.045	
W.S. Elev (ft)	21.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		520.12	
E.G. Slope (ft/ft)	0.009593	Area (sq ft)		520.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	90.01	Top Width (ft)		90.01	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	7.75	Hydr. Depth (ft)		5.78	
Conv. Total (cfs)	54011.4	Conv. (cfs)		54011.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		93.26	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.91	Cum Volume (acre-ft)	0.04	22.72	0.34
C & E Loss (ft)	0.08	Cum SA (acres)	0.04	3.41	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.89	Wt. n-Val.		0.045	
W.S. Elev (ft)	23.37	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		669.19	
E.G. Slope (ft/ft)	0.008749	Area (sq ft)		669.19	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	94.97	Top Width (ft)		94.97	
Vel Total (ft/s)	11.03	Avg. Vel. (ft/s)		11.03	
Max Chl Dpth (ft)	9.37	Hydr. Depth (ft)		7.05	
Conv. Total (cfs)	78901.8	Conv. (cfs)		78901.8	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		99.18	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)	0.25	29.55	4.08
C & E Loss (ft)	0.11	Cum SA (acres)	0.14	3.47	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1555

INPUT
Description: G
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	21.5	40	15
50	13.8	60	13.6	70	13.3	80	13.5	90	13.5
100	14.5	110	19	120	26	130	29	140	29.5
150	29.9								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.042	120	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	120	100	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	22.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.62	Wt. n-Val.		0.042	
W.S. Elev (ft)	20.34	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	20.16	Flow Area (sq ft)		455.10	
E.G. Slope (ft/ft)	0.013988	Area (sq ft)		455.10	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	80.13	Top Width (ft)		80.13	
Vel Total (ft/s)	12.99	Avg. Vel. (ft/s)		12.99	
Max Chl Dpth (ft)	7.04	Hydr. Depth (ft)		5.68	
Conv. Total (cfs)	49970.8	Conv. (cfs)		49970.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		83.23	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.77	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.37	Cum Volume (acre-ft)	0.08	23.81	1.04
C & E Loss (ft)	0.07	Cum SA (acres)	0.07	3.27	1.24

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	17.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.042	
W.S. Elev (ft)	16.65	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)		Flow Area (sq ft)		181.93	
E.G. Slope (ft/ft)	0.011277	Area (sq ft)		181.93	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	67.33	Top Width (ft)		67.33	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.35	Hydr. Depth (ft)		2.70	
Conv. Total (cfs)	12355.1	Conv. (cfs)		12355.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.41	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		1.87	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.01	9.65	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	2.60	0.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	20.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.06	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.65	Flow Area (sq ft)		355.06	
E.G. Slope (ft/ft)	0.012591	Area (sq ft)		355.06	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.34	Top Width (ft)		76.34	
Vel Total (ft/s)	10.84	Avg. Vel. (ft/s)		10.84	
Max Chl Dpth (ft)	5.76	Hydr. Depth (ft)		4.65	
Conv. Total (cfs)	34310.2	Conv. (cfs)		34310.2	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		78.66	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.55	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.01	17.09	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	3.04	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	21.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.96	Wt. n-Val.		0.042	

W.S. Elev (ft)	19.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.89	Flow Area (sq ft)		368.78	
E.G. Slope (ft/ft)	0.013022	Area (sq ft)		368.78	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	76.87	Top Width (ft)		76.87	
Vel Total (ft/s)	11.25	Avg. Vel. (ft/s)		11.25	
Max Chl Dpth (ft)	5.94	Hydr. Depth (ft)		4.80	
Conv. Total (cfs)	36350.1	Conv. (cfs)		36350.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		79.30	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.78	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.02	18.07	0.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	3.10	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	22.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.41	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.96	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	19.73	Flow Area (sq ft)		424.40	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		424.40	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	78.99	Top Width (ft)		78.99	
Vel Total (ft/s)	12.46	Avg. Vel. (ft/s)		12.46	
Max Chl Dpth (ft)	6.66	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	44978.8	Conv. (cfs)		44978.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		81.85	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.48	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.04	21.85	0.34
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	3.25	0.54

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	24.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.03	Wt. n-Val.		0.042	
W.S. Elev (ft)	21.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	21.12	Flow Area (sq ft)		528.58	
E.G. Slope (ft/ft)	0.013932	Area (sq ft)		528.58	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	

Top Width (ft)	82.81	Top Width (ft)	82.81	
Vel Total (ft/s)	13.96	Avg. Vel. (ft/s)	13.96	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)	6.38	
Conv. Total (cfs)	62523.5	Conv. (cfs)	62523.5	
Length Wtd. (ft)	100.00	Wetted Per. (ft)	86.46	
Min Ch El (ft)	13.30	Shear (lb/sq ft)	5.32	
Alpha	1.00	Stream Power (lb/ft s)	150.00 0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.25 28.45	4.08
C & E Loss (ft)	0.13	Cum SA (acres)	0.14 3.30	2.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1455

INPUT
Description: F
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	45	10	38	20	31	30	24	40	16.5
50	12.5	60	11.8	70	12	80	12.3	90	12.6
100	12.8	110	14	120	18.5	130	23	140	28
150	30								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	120	120	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	21.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.37	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	19.15	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.73	Flow Area (sq ft)	4.67	476.75	0.46
E.G. Slope (ft/ft)	0.013387	Area (sq ft)	4.67	476.75	0.46
Q Total (cfs)	5910.00	Flow (cfs)	12.83	5896.66	0.51
Top Width (ft)	84.97	Top Width (ft)	3.53	80.00	1.44
Vel Total (ft/s)	12.26	Avg. Vel. (ft/s)	2.75	12.37	1.09
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)	1.32	5.96	0.32
Conv. Total (cfs)	51079.8	Conv. (cfs)	110.9	50964.5	4.4

Length Wtd. (ft)	120.00	Wetted Per. (ft)	4.41	81.85	1.58
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.88	4.87	0.25
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.08	22.74	1.04
C & E Loss (ft)	0.17	Cum SA (acres)	0.07	3.09	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	16.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.06	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	14.87	Flow Area (sq ft)		165.73	
E.G. Slope (ft/ft)	0.018077	Area (sq ft)		165.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	68.77	Top Width (ft)		68.77	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	3.26	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	9758.1	Conv. (cfs)		9758.1	
Length Wtd. (ft)	120.00	Wetted Per. (ft)		69.60	
Min Ch El (ft)	11.80	Shear (lb/sq ft)		2.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	2.24	Cum Volume (acre-ft)	0.01	9.25	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	2.44	0.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.01	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.40	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.28	Flow Area (sq ft)	0.54	338.37	
E.G. Slope (ft/ft)	0.017110	Area (sq ft)	0.54	338.37	
Q Total (cfs)	3850.00	Flow (cfs)	0.82	3849.18	
Top Width (ft)	78.76	Top Width (ft)	1.20	77.56	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	1.51	11.38	
Max Chl Dpth (ft)	5.60	Hydr. Depth (ft)	0.45	4.36	
Conv. Total (cfs)	29432.7	Conv. (cfs)	6.3	29426.4	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.50	79.17	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.38	4.57	

Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.01	16.29	0.03
C & E Loss (ft)	0.13	Cum SA (acres)	0.01	2.86	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	19.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.07	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.67	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.49	Flow Area (sq ft)	0.91	359.10	
E.G. Slope (ft/ft)	0.016462	Area (sq ft)	0.91	359.10	
Q Total (cfs)	4148.00	Flow (cfs)	1.60	4146.40	
Top Width (ft)	79.70	Top Width (ft)	1.56	78.15	
Vel Total (ft/s)	11.52	Avg. Vel. (ft/s)	1.76	11.55	
Max Chl Dpth (ft)	5.87	Hydr. Depth (ft)	0.58	4.60	
Conv. Total (cfs)	32328.9	Conv. (cfs)	12.5	32316.5	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.94	79.81	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.48	4.62	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.53	Cum Volume (acre-ft)	0.02	17.23	0.04
C & E Loss (ft)	0.14	Cum SA (acres)	0.01	2.92	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	20.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.27	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	18.65	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.33	Flow Area (sq ft)	3.07	436.72	0.02
E.G. Slope (ft/ft)	0.014390	Area (sq ft)	3.07	436.72	0.02
Q Total (cfs)	5290.00	Flow (cfs)	7.61	5282.38	0.01
Top Width (ft)	83.19	Top Width (ft)	2.86	80.00	0.33
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	2.48	12.10	0.42
Max Chl Dpth (ft)	6.85	Hydr. Depth (ft)	1.07	5.46	0.07
Conv. Total (cfs)	44098.1	Conv. (cfs)	63.4	44034.6	0.1
Length Wtd. (ft)	120.00	Wetted Per. (ft)	3.58	81.85	0.36
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.77	4.79	0.06
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.34	Cum Volume (acre-ft)	0.04	20.86	0.34
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	3.07	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	22.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.58	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	20.29	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)		Flow Area (sq ft)	9.55	567.83	3.54
E.G. Slope (ft/ft)	0.011588	Area (sq ft)	9.55	567.83	3.54
Q Total (cfs)	7380.00	Flow (cfs)	31.00	7341.95	7.06
Top Width (ft)	89.01	Top Width (ft)	5.05	80.00	3.97
Vel Total (ft/s)	12.70	Avg. Vel. (ft/s)	3.24	12.93	1.99
Max Chl Dpth (ft)	8.49	Hydr. Depth (ft)	1.89	7.10	0.89
Conv. Total (cfs)	68558.4	Conv. (cfs)	288.0	68204.9	65.5
Length Wtd. (ft)	120.00	Wetted Per. (ft)	6.31	81.85	4.35
Min Ch El (ft)	11.80	Shear (lb/sq ft)	1.10	5.02	0.59
Alpha	1.03	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.24	27.19	4.08
C & E Loss (ft)	0.18	Cum SA (acres)	0.14	3.12	2.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1335

INPUT
Description: E
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	42.5	10	37.5	20	31	30	24	40	17
50	11	60	9.5	70	9.5	80	9.5	90	9.5
100	10.5	110	14	120	19	130	23	140	28
150	29	160	30						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.075

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	150	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	20.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.80	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	18.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.18	548.37	
E.G. Slope (ft/ft)	0.008451	Area (sq ft)	1.18	548.37	
Q Total (cfs)	5910.00	Flow (cfs)	1.62	5908.38	
Top Width (ft)	80.41	Top Width (ft)	1.84	78.57	
Vel Total (ft/s)	10.75	Avg. Vel. (ft/s)	1.37	10.77	
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	0.64	6.98	
Conv. Total (cfs)	64289.9	Conv. (cfs)	17.6	64272.3	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.24	82.00	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.28	3.53	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.56	Cum Volume (acre-ft)	0.07	21.33	1.04
C & E Loss (ft)	0.09	Cum SA (acres)	0.06	2.87	1.24

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	13.78	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.14	Wt. n-Val.		0.045	
W.S. Elev (ft)	12.63	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)		152.88	
E.G. Slope (ft/ft)	0.019322	Area (sq ft)		152.88	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	58.82	Top Width (ft)		58.82	
Vel Total (ft/s)	8.58	Avg. Vel. (ft/s)		8.58	
Max Chl Dpth (ft)	3.13	Hydr. Depth (ft)		2.60	
Conv. Total (cfs)	9438.7	Conv. (cfs)		9438.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		59.79	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.08	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.87	Cum Volume (acre-ft)	0.01	8.81	0.01
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	2.26	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less

than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	17.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.56	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.13	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		384.19	
E.G. Slope (ft/ft)	0.010520	Area (sq ft)		384.19	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	72.81	Top Width (ft)		72.81	
Vel Total (ft/s)	10.02	Avg. Vel. (ft/s)		10.02	
Max Chl Dpth (ft)	6.63	Hydr. Depth (ft)		5.28	
Conv. Total (cfs)	37536.7	Conv. (cfs)		37536.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		75.49	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.65	Cum Volume (acre-ft)	0.01	15.30	0.03
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	2.65	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	18.07	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.47	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		409.60	
E.G. Slope (ft/ft)	0.010117	Area (sq ft)		409.60	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	74.07	Top Width (ft)		74.07	
Vel Total (ft/s)	10.13	Avg. Vel. (ft/s)		10.13	
Max Chl Dpth (ft)	6.97	Hydr. Depth (ft)		5.53	
Conv. Total (cfs)	41238.9	Conv. (cfs)		41238.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		76.93	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.36	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.64	Cum Volume (acre-ft)	0.01	16.17	0.04
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	2.71	0.05

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.34	501.69	
E.G. Slope (ft/ft)	0.008914	Area (sq ft)	0.34	501.69	
Q Total (cfs)	5290.00	Flow (cfs)	0.31	5289.69	
Top Width (ft)	78.36	Top Width (ft)	0.98	77.37	
Vel Total (ft/s)	10.54	Avg. Vel. (ft/s)	0.93	10.54	
Max Chl Dpth (ft)	8.19	Hydr. Depth (ft)	0.34	6.48	
Conv. Total (cfs)	56029.0	Conv. (cfs)	3.3	56025.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.20	80.66	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.16	3.46	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.03	19.57	0.34
C & E Loss (ft)	0.08	Cum SA (acres)	0.03	2.85	0.54

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	21.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.97	Wt. n-Val.	0.065	0.045	0.075
W.S. Elev (ft)	19.61	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.86	653.69	0.46
E.G. Slope (ft/ft)	0.007511	Area (sq ft)	4.86	653.69	0.46
Q Total (cfs)	7380.00	Flow (cfs)	10.06	7369.59	0.34
Top Width (ft)	85.25	Top Width (ft)	3.73	80.00	1.52
Vel Total (ft/s)	11.20	Avg. Vel. (ft/s)	2.07	11.27	0.74
Max Chl Dpth (ft)	10.11	Hydr. Depth (ft)	1.30	8.17	0.30
Conv. Total (cfs)	85155.0	Conv. (cfs)	116.1	85034.9	3.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.55	83.60	1.64
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.50	3.67	0.13
Alpha	1.01	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.52	Cum Volume (acre-ft)	0.22	25.51	4.07
C & E Loss (ft)	0.14	Cum SA (acres)	0.13	2.90	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1185

INPUT
Description: D
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	41.5	4	40	10	35	20	27.5	30	20
35	16	40	12	50	7	60	5.5	70	6
80	7	90	11	100	16	110	22	120	28
130	28.2								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	35	.045	110	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
35	110	125	125	125	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	18.44	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.70	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.74	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	15.05	Flow Area (sq ft)		448.42	
E.G. Slope (ft/ft)	0.013066	Area (sq ft)		448.42	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	64.17	Top Width (ft)		64.17	
Vel Total (ft/s)	13.18	Avg. Vel. (ft/s)		13.18	
Max Chl Dpth (ft)	10.24	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	51703.8	Conv. (cfs)		51703.8	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		68.72	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		5.32	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.68	Cum Volume (acre-ft)	0.06	19.62	1.04
C & E Loss (ft)	0.05	Cum SA (acres)	0.06	2.63	1.24

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	11.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.82	Wt. n-Val.		0.045	

W.S. Elev (ft)	10.99	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)		Flow Area (sq ft)		180.57	
E.G. Slope (ft/ft)	0.008702	Area (sq ft)		180.57	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.96	Top Width (ft)		47.96	
Vel Total (ft/s)	7.27	Avg. Vel. (ft/s)		7.27	
Max Chl Dpth (ft)	5.49	Hydr. Depth (ft)		3.77	
Conv. Total (cfs)	14064.2	Conv. (cfs)		14064.2	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		49.84	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		1.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.49	Cum Volume (acre-ft)	0.01	8.24	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	2.08	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	16.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.08	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.16	Flow Area (sq ft)		346.47	
E.G. Slope (ft/ft)	0.011509	Area (sq ft)		346.47	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	58.78	Top Width (ft)		58.78	
Vel Total (ft/s)	11.11	Avg. Vel. (ft/s)		11.11	
Max Chl Dpth (ft)	8.58	Hydr. Depth (ft)		5.89	
Conv. Total (cfs)	35888.0	Conv. (cfs)		35888.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		62.36	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		3.99	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.62	Cum Volume (acre-ft)	0.01	14.04	0.03
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	2.43	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	16.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.04	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.34	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.46	Flow Area (sq ft)		361.81	
E.G. Slope (ft/ft)	0.011809	Area (sq ft)		361.81	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	59.62	Top Width (ft)		59.62	
Vel Total (ft/s)	11.46	Avg. Vel. (ft/s)		11.46	
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		6.07	
Conv. Total (cfs)	38171.0	Conv. (cfs)		38171.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		63.35	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.21	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.63	Cum Volume (acre-ft)	0.01	14.85	0.04
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	2.48	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	17.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.48	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.27	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	14.52	Flow Area (sq ft)		418.21	
E.G. Slope (ft/ft)	0.012741	Area (sq ft)		418.21	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	62.62	Top Width (ft)		62.62	
Vel Total (ft/s)	12.65	Avg. Vel. (ft/s)		12.65	
Max Chl Dpth (ft)	9.77	Hydr. Depth (ft)		6.68	
Conv. Total (cfs)	46865.0	Conv. (cfs)		46865.0	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		66.90	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.66	Cum Volume (acre-ft)	0.03	17.99	0.34
C & E Loss (ft)	0.05	Cum SA (acres)	0.03	2.61	0.54

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	19.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.33	Wt. n-Val.	0.065	0.045	

W.S. Elev (ft)	16.59	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	16.20	Flow Area (sq ft)	0.22	503.78	
E.G. Slope (ft/ft)	0.014396	Area (sq ft)	0.22	503.78	
Q Total (cfs)	7380.00	Flow (cfs)	0.23	7379.77	
Top Width (ft)	66.73	Top Width (ft)	0.74	65.99	
Vel Total (ft/s)	14.64	Avg. Vel. (ft/s)	1.03	14.65	
Max Chl Dpth (ft)	11.09	Hydr. Depth (ft)	0.30	7.63	
Conv. Total (cfs)	61508.4	Conv. (cfs)	1.9	61506.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)	0.95	70.86	
Min Ch El (ft)	5.50	Shear (lb/sq ft)	0.21	6.39	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.73	Cum Volume (acre-ft)	0.21	23.51	4.07
C & E Loss (ft)	0.02	Cum SA (acres)	0.12	2.64	1.99

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1060

INPUT
Description: C
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	33	20	35	30	29	40	23
45	19.5	50	16	60	10	70	7	80	5.5
90	5	100	5	110	7	120	13	130	20
200	20.1								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	45	.04	130	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
45	130	100	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	16.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.15	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.57	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.57	Flow Area (sq ft)		415.00	
E.G. Slope (ft/ft)	0.013789	Area (sq ft)		415.00	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	

Top Width (ft)	66.76	Top Width (ft)		66.76	
Vel Total (ft/s)	14.24	Avg. Vel. (ft/s)		14.24	
Max Chl Dpth (ft)	8.57	Hydr. Depth (ft)		6.22	
Conv. Total (cfs)	50329.3	Conv. (cfs)		50329.3	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		70.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.08	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.07	Cum Volume (acre-ft)	0.06	18.38	1.04
C & E Loss (ft)	0.26	Cum SA (acres)	0.06	2.44	1.24

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.41	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.85	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	8.85	Flow Area (sq ft)		137.48	
E.G. Slope (ft/ft)	0.017292	Area (sq ft)		137.48	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	49.24	Top Width (ft)		49.24	
Vel Total (ft/s)	9.54	Avg. Vel. (ft/s)		9.54	
Max Chl Dpth (ft)	3.85	Hydr. Depth (ft)		2.79	
Conv. Total (cfs)	9977.1	Conv. (cfs)		9977.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		50.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		2.95	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.29	Cum Volume (acre-ft)	0.01	7.78	0.01
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	1.94	0.01

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is

not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	14.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	11.81	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	11.81	Flow Area (sq ft)		302.66	
E.G. Slope (ft/ft)	0.014662	Area (sq ft)		302.66	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.04	Top Width (ft)		61.04	
Vel Total (ft/s)	12.72	Avg. Vel. (ft/s)		12.72	
Max Chl Dpth (ft)	6.81	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	31795.8	Conv. (cfs)		31795.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		63.64	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.35	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.12	Cum Volume (acre-ft)	0.01	13.11	0.03
C & E Loss (ft)	0.26	Cum SA (acres)	0.01	2.25	0.04

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	14.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	12.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	12.10	Flow Area (sq ft)		320.59	
E.G. Slope (ft/ft)	0.014382	Area (sq ft)		320.59	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.01	Top Width (ft)		62.01	
Vel Total (ft/s)	12.94	Avg. Vel. (ft/s)		12.94	
Max Chl Dpth (ft)	7.10	Hydr. Depth (ft)		5.17	
Conv. Total (cfs)	34588.7	Conv. (cfs)		34588.7	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		64.77	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.44	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.10	Cum Volume (acre-ft)	0.01	13.87	0.04
C & E Loss (ft)	0.26	Cum SA (acres)	0.01	2.31	0.05

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	16.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.10	Flow Area (sq ft)		384.11	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		384.11	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.31	Top Width (ft)		65.31	
Vel Total (ft/s)	13.77	Avg. Vel. (ft/s)		13.77	
Max Chl Dpth (ft)	8.10	Hydr. Depth (ft)		5.88	
Conv. Total (cfs)	44979.7	Conv. (cfs)		44979.7	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.63	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.83	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.07	Cum Volume (acre-ft)	0.03	16.84	0.34
C & E Loss (ft)	0.25	Cum SA (acres)	0.03	2.43	0.54

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	18.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	14.68	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	14.68	Flow Area (sq ft)		490.87	
E.G. Slope (ft/ft)	0.013247	Area (sq ft)		490.87	

Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	70.19	Top Width (ft)		70.19	
Vel Total (ft/s)	15.03	Avg. Vel. (ft/s)		15.03	
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	64121.8	Conv. (cfs)		64121.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		74.44	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.45	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.05	Cum Volume (acre-ft)	0.21	22.09	4.07
C & E Loss (ft)	0.25	Cum SA (acres)	0.12	2.45	1.99

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 960

INPUT
Description: B
Station Elevation Data num= 21

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	32	13.6	31	22.5	30	33.1	28	54.2	20
71.6	20	72.3	15	72.9	10.091	73.4	6	79.4	5
85.5	4	100.5	3.5	114.3	4	124.5	5	135.8	10.103
140	12	202.9	14.2	203	14.5	209.1	15	224.5	20
229.5	25								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	72.9	.042	135.8	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
72.9	135.8	25	25	.3	.5

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	14.82	Element	Left OB	Channel	Right OB

Vel Head (ft)	2.28	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	12.54	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	11.33	Flow Area (sq ft)	0.37	484.96	10.39
E.G. Slope (ft/ft)	0.008563	Area (sq ft)	0.37	484.96	10.39
Q Total (cfs)	5910.00	Flow (cfs)	0.20	5891.34	18.46
Top Width (ft)	82.79	Top Width (ft)	0.30	62.90	19.59
Vel Total (ft/s)	11.92	Avg. Vel. (ft/s)	0.55	12.15	1.78
Max Chl Dpth (ft)	9.04	Hydr. Depth (ft)	1.22	7.71	0.53
Conv. Total (cfs)	63865.3	Conv. (cfs)	2.2	63663.7	199.5
Length Wtd. (ft)	25.00	Wetted Per. (ft)	2.47	67.85	20.01
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.08	3.82	0.28
Alpha	1.04	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.06	17.34	1.03
C & E Loss (ft)	0.63	Cum SA (acres)	0.06	2.29	1.22

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	8.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.042	
W.S. Elev (ft)	7.53	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	6.91	Flow Area (sq ft)		177.88	
E.G. Slope (ft/ft)	0.009985	Area (sq ft)		177.88	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	56.90	Top Width (ft)		56.90	
Vel Total (ft/s)	7.38	Avg. Vel. (ft/s)		7.38	
Max Chl Dpth (ft)	4.03	Hydr. Depth (ft)		3.13	
Conv. Total (cfs)	13129.6	Conv. (cfs)		13129.6	
Length Wtd. (ft)	25.00	Wetted Per. (ft)		59.03	
Min Ch El (ft)	3.50	Shear (lb/sq ft)		1.88	
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.01	7.42	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	1.82	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	12.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.65	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	10.76	Reach Len. (ft)	25.00	25.00	25.00

Crit W.S. (ft)	9.68	Flow Area (sq ft)	0.03	373.02	0.48
E.G. Slope (ft/ft)	0.008768	Area (sq ft)	0.03	373.02	0.48
Q Total (cfs)	3850.00	Flow (cfs)	0.01	3849.40	0.59
Top Width (ft)	64.43	Top Width (ft)	0.08	62.90	1.45
Vel Total (ft/s)	10.31	Avg. Vel. (ft/s)	0.23	10.32	1.24
Max Chl Dpth (ft)	7.26	Hydr. Depth (ft)	0.33	5.93	0.33
Conv. Total (cfs)	41115.5	Conv. (cfs)	0.1	41109.1	6.3
Length Wtd. (ft)	25.00	Wetted Per. (ft)	0.67	67.85	1.59
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.02	3.01	0.16
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	12.33	0.03
C & E Loss (ft)	0.39	Cum SA (acres)	0.01	2.11	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.75	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	11.04	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.93	Flow Area (sq ft)	0.05	390.62	0.97
E.G. Slope (ft/ft)	0.008725	Area (sq ft)	0.05	390.62	0.97
Q Total (cfs)	4148.00	Flow (cfs)	0.02	4146.46	1.52
Top Width (ft)	65.09	Top Width (ft)	0.12	62.90	2.07
Vel Total (ft/s)	10.59	Avg. Vel. (ft/s)	0.30	10.62	1.57
Max Chl Dpth (ft)	7.54	Hydr. Depth (ft)	0.47	6.21	0.47
Conv. Total (cfs)	44408.0	Conv. (cfs)	0.2	44391.5	16.3
Length Wtd. (ft)	25.00	Wetted Per. (ft)	0.95	67.85	2.27
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.03	3.14	0.23
Alpha	1.00	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	13.05	0.04
C & E Loss (ft)	0.42	Cum SA (acres)	0.01	2.16	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	14.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.10	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	12.04	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.87	Flow Area (sq ft)	0.23	453.88	4.20
E.G. Slope (ft/ft)	0.008580	Area (sq ft)	0.23	453.88	4.20

Q Total (cfs)	5290.00	Flow (cfs)	0.11	5280.65	9.24
Top Width (ft)	68.60	Top Width (ft)	0.24	62.90	5.47
Vel Total (ft/s)	11.54	Avg. Vel. (ft/s)	0.47	11.63	2.20
Max Chl Dpth (ft)	8.54	Hydr. Depth (ft)	0.98	7.22	0.77
Conv. Total (cfs)	57109.9	Conv. (cfs)	1.2	57009.0	99.7
Length Wtd. (ft)	25.00	Wetted Per. (ft)	1.97	67.85	5.87
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.06	3.58	0.38
Alpha	1.01	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)	0.03	15.87	0.33
C & E Loss (ft)	0.55	Cum SA (acres)	0.03	2.28	0.53

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	16.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.93	Wt. n-Val.	0.070	0.042	0.050
W.S. Elev (ft)	11.41	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)	0.11	413.84	1.88
E.G. Slope (ft/ft)	0.022762	Area (sq ft)	0.11	413.84	1.88
Q Total (cfs)	7380.00	Flow (cfs)	0.06	7373.96	5.97
Top Width (ft)	65.95	Top Width (ft)	0.16	62.90	2.89
Vel Total (ft/s)	17.75	Avg. Vel. (ft/s)	0.59	17.82	3.17
Max Chl Dpth (ft)	7.91	Hydr. Depth (ft)	0.66	6.58	0.65
Conv. Total (cfs)	48916.0	Conv. (cfs)	0.4	48876.0	39.6
Length Wtd. (ft)	25.00	Wetted Per. (ft)	1.33	67.85	3.17
Min Ch El (ft)	3.50	Shear (lb/sq ft)	0.11	8.67	0.84
Alpha	1.01	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.71	Cum Volume (acre-ft)	0.21	21.05	4.07
C & E Loss (ft)	0.14	Cum SA (acres)	0.12	2.30	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 935

INPUT
Description: JU

Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	12	30	20	28	50	10	75.8	6
82.4	4	92.4	3	105.2	2	121	3	128	5
136	10	203	12.5	203.1	13	203.2	13.1	208.7	13.4
231.8	20	232	26.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	50	.042	136	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
50	136	85	85	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	232	30	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	14.06	Element			
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	13.04	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	10.34	Flow Area (sq ft)	7.70	687.59	114.45
E.G. Slope (ft/ft)	0.003531	Area (sq ft)	7.70	687.59	120.00
Q Total (cfs)	5910.00	Flow (cfs)	12.49	5673.06	224.45
Top Width (ft)	158.21	Top Width (ft)	5.07	86.00	67.14
Vel Total (ft/s)	7.30	Avg. Vel. (ft/s)	1.62	8.25	1.96
Max Chl Dpth (ft)	11.04	Hydr. Depth (ft)	1.52	8.00	1.94
Conv. Total (cfs)	99457.7	Conv. (cfs)	210.2	95470.3	3777.2
Length Wtd. (ft)	17.00	Wetted Per. (ft)	5.91	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.29	1.71	0.43
Alpha	1.23	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.06	17.01	0.99
C & E Loss (ft)	0.29	Cum SA (acres)	0.05	2.25	1.19

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	8.03	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.46	Wt. n-Val.		0.042	
W.S. Elev (ft)	7.57	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	5.91	Flow Area (sq ft)		240.67	
E.G. Slope (ft/ft)	0.004399	Area (sq ft)		240.67	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	66.41	Top Width (ft)		66.41	
Vel Total (ft/s)	5.45	Avg. Vel. (ft/s)		5.45	
Max Chl Dpth (ft)	5.57	Hydr. Depth (ft)		3.62	
Conv. Total (cfs)	19781.8	Conv. (cfs)		19781.8	
Length Wtd. (ft)	17.00	Wetted Per. (ft)		67.97	
Min Ch El (ft)	2.00	Shear (lb/sq ft)		0.97	
Alpha	1.00	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	7.30	0.01
C & E Loss (ft)	0.09	Cum SA (acres)	0.00	1.78	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	11.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	11.00	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	8.78	Flow Area (sq ft)	0.84	512.24	13.44
E.G. Slope (ft/ft)	0.004311	Area (sq ft)	0.84	512.24	13.44
Q Total (cfs)	3850.00	Flow (cfs)	0.71	3837.48	11.81
Top Width (ft)	114.51	Top Width (ft)	1.67	86.00	26.84
Vel Total (ft/s)	7.31	Avg. Vel. (ft/s)	0.85	7.49	0.88
Max Chl Dpth (ft)	9.00	Hydr. Depth (ft)	0.50	5.96	0.50
Conv. Total (cfs)	58639.3	Conv. (cfs)	10.9	58448.6	179.9
Length Wtd. (ft)	17.00	Wetted Per. (ft)	1.95	88.44	26.86
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.12	1.56	0.13
Alpha	1.05	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	12.08	0.02
C & E Loss (ft)	0.24	Cum SA (acres)	0.01	2.07	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.22	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	11.32	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	9.03	Flow Area (sq ft)	1.44	539.21	23.18
E.G. Slope (ft/ft)	0.004193	Area (sq ft)	1.44	539.21	23.18
Q Total (cfs)	4148.00	Flow (cfs)	1.46	4122.46	24.08
Top Width (ft)	123.44	Top Width (ft)	2.19	86.00	35.25
Vel Total (ft/s)	7.36	Avg. Vel. (ft/s)	1.01	7.65	1.04
Max Chl Dpth (ft)	9.32	Hydr. Depth (ft)	0.66	6.27	0.66
Conv. Total (cfs)	64060.3	Conv. (cfs)	22.5	63666.0	371.9
Length Wtd. (ft)	17.00	Wetted Per. (ft)	2.56	88.44	35.27
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.15	1.60	0.17
Alpha	1.07	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.01	12.78	0.03
C & E Loss (ft)	0.24	Cum SA (acres)	0.01	2.12	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	13.45	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.99	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	12.46	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	9.93	Flow Area (sq ft)	5.05	637.91	80.37
E.G. Slope (ft/ft)	0.003743	Area (sq ft)	5.05	637.91	81.28
Q Total (cfs)	5290.00	Flow (cfs)	7.33	5154.48	128.19
Top Width (ft)	156.11	Top Width (ft)	4.10	86.00	66.01
Vel Total (ft/s)	7.31	Avg. Vel. (ft/s)	1.45	8.08	1.60
Max Chl Dpth (ft)	10.46	Hydr. Depth (ft)	1.23	7.42	1.36
Conv. Total (cfs)	86466.8	Conv. (cfs)	119.8	84251.7	2095.3
Length Wtd. (ft)	17.00	Wetted Per. (ft)	4.79	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.25	1.69	0.32
Alpha	1.19	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.03	15.56	0.31
C & E Loss (ft)	0.28	Cum SA (acres)	0.03	2.24	0.51

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less

than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	15.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.10	Wt. n-Val.	0.065	0.042	0.070
W.S. Elev (ft)	14.22	Reach Len. (ft)	17.00	17.00	17.00
Crit W.S. (ft)	11.33	Flow Area (sq ft)	14.84	789.01	184.03
E.G. Slope (ft/ft)	0.003277	Area (sq ft)	14.84	789.01	205.75
Q Total (cfs)	7380.00	Flow (cfs)	28.83	6873.98	477.18
Top Width (ft)	168.60	Top Width (ft)	7.03	86.00	75.57
Vel Total (ft/s)	7.47	Avg. Vel. (ft/s)	1.94	8.71	2.59
Max Chl Dpth (ft)	12.22	Hydr. Depth (ft)	2.11	9.17	3.12
Conv. Total (cfs)	128913.2	Conv. (cfs)	503.7	120074.1	8335.4
Length Wtd. (ft)	17.00	Wetted Per. (ft)	8.20	88.44	59.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.37	1.83	0.64
Alpha	1.27	Stream Power (lb/ft s)	232.00	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.21	20.70	4.01
C & E Loss (ft)	0.23	Cum SA (acres)	0.11	2.25	1.97

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 895

INPUT
Description: Bridge Street
Distance from Upstream XS = 17
Deck/Roadway Width = 56
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta	Hi Cord	Lo Cord	Sta	Hi Cord	Lo Cord	Sta	Hi Cord	Lo Cord
0	30	0	30.2	30	0	30.2	30	26
246.2	26	22	246.2	26	0	260	26	0

Upstream Bridge Cross Section Data
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	12	30	20	28	50	10	75.8	6
82.4	4	92.4	3	105.2	2	121	3	128	5
136	10	203	12.5	203.1	13	203.2	13.1	208.7	13.4
231.8	20	232	26.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	50	.042	136	.07

Bank Sta: Left Right Coeff Contr. Expan.
50 136 .3 .5
Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	232	30	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	30.2	30	0	30.2	30	26
246.2	26	22	246.2	26	0	260	26	0

Downstream Bridge Cross Section Data
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	28	26.8	20	27	14	39.8	10	75.2	5
94	1	115	1	126.8	5	131.6	5	151.3	9
174.5	10	238.1	15	238.2	25				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	39.8	.04	131.6	.065

Bank Sta: Left Right Coeff Contr. Expan.
39.8 131.6 .3 .5
Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	25	30	F
195	238.2	30	F

Blocked Obstructions num= 2

Sta L	Sta R	Elev
131.3	146.6	30
203	240	30

Upstream Embankment side slope = 2 horiz. to 1.0 vertical
Downstream Embankment side slope = 2 horiz. to 1.0 vertical

Maximum allowable submergence for weir flow = .98
Elevation at which weir flow begins = 26
Energy head used in spillway design =
Spillway height used in design =
Weir crest shape = Broad Crested

Number of Piers = 3

Pier Data
Pier Station Upstream= 83.2 Downstream= 83.2
Upstream num= 2
Width Elev Width Elev
7.7 3 4 28
Downstream num= 2
Width Elev Width Elev
7.7 3 4 28

Pier Data
Pier Station Upstream= 138.2 Downstream= 138.2
Upstream num= 2
Width Elev Width Elev
7.7 3 4 28
Downstream num= 2
Width Elev Width Elev
7.7 3 4 28

Pier Data
Pier Station Upstream= 193.2 Downstream= 193.2
Upstream num= 2
Width Elev Width Elev
7.7 3 4 28
Downstream num= 2
Width Elev Width Elev
7.7 3 4 28

Number of Bridge Coefficient Sets = 1

Low Flow Methods and Data
Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
Energy Only

Additional Bridge Parameters
Add Friction component to Momentum
Do not add Weight component to Momentum
Class B flow critical depth computations use critical depth

inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

E.G. US. (ft)	14.06	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	13.04	E.G. Elev (ft)	13.67	12.90
Q Total (cfs)	5910.00	W.S. Elev (ft)	11.70	11.51
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	10.78	9.93
Q Weir (cfs)		Max Chl Dpth (ft)	9.70	10.51
Weir Sta Lft (ft)		Vel Total (ft/s)	10.78	8.79
Weir Sta Rgt (ft)		Flow Area (sq ft)	548.45	672.20
Weir Submerg		Froude # Chl	0.78	0.64
Weir Max Depth (ft)		Specif Force (cu ft)	4042.63	4256.51
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.52	5.04
Min El Prs (ft)	26.00	W.P. Total (ft)	141.57	160.45
Delta EG (ft)	1.34	Conv. Total (cfs)	56292.8	71093.0
Delta WS (ft)	1.49	Top Width (ft)	121.45	133.26
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.48	0.07
BR Open Vel (ft/s)	10.78	C & E Loss (ft)	0.29	0.12
Coef of Q		Shear Total (lb/sq ft)	2.67	1.81
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

E.G. US. (ft)	8.03	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	7.57	E.G. Elev (ft)	7.83	7.33
Q Total (cfs)	1312.00	W.S. Elev (ft)	7.05	6.84
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	6.09	5.12
Q Weir (cfs)		Max Chl Dpth (ft)	5.05	5.84
Weir Sta Lft (ft)		Vel Total (ft/s)	7.08	5.60
Weir Sta Rgt (ft)		Flow Area (sq ft)	185.43	234.13
Weir Submerg		Froude # Chl	0.68	0.51
Weir Max Depth (ft)		Specif Force (cu ft)	667.31	799.30
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	3.36	3.78
Min El Prs (ft)	26.00	W.P. Total (ft)	61.66	71.50
Delta EG (ft)	0.80	Conv. Total (cfs)	13668.9	19178.8
Delta WS (ft)	0.73	Top Width (ft)	55.17	61.99
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.36	0.05

BR Open Vel (ft/s)	7.08	C & E Loss (ft)	0.14	0.05
Coef of Q		Shear Total (lb/sq ft)	1.73	0.96
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	11.87	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.00	E.G. Elev (ft)	11.52	10.74
Q Total (cfs)	3850.00	W.S. Elev (ft)	9.85	9.44
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	9.19	8.13
Q Weir (cfs)		Max Chl Dpth (ft)	7.85	8.44
Weir Sta Lft (ft)		Vel Total (ft/s)	10.37	9.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	371.27	426.37
Weir Submerg		Froude # Chl	0.83	0.71
Weir Max Depth (ft)		Specif Force (cu ft)	2381.92	2505.77
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.81	4.46
Min El Prs (ft)	26.00	W.P. Total (ft)	90.24	114.33
Delta EG (ft)	1.34	Conv. Total (cfs)	33725.2	41240.5
Delta WS (ft)	1.52	Top Width (ft)	77.17	95.70
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.59	0.08
BR Open Vel (ft/s)	10.37	C & E Loss (ft)	0.19	0.13
Coef of Q		Shear Total (lb/sq ft)	3.35	2.03
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	12.22	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.32	E.G. Elev (ft)	11.86	11.09
Q Total (cfs)	4148.00	W.S. Elev (ft)	10.15	9.77
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	9.45	8.40
Q Weir (cfs)		Max Chl Dpth (ft)	8.15	8.77
Weir Sta Lft (ft)		Vel Total (ft/s)	10.49	9.02
Weir Sta Rgt (ft)		Flow Area (sq ft)	395.40	459.73
Weir Submerg		Froude # Chl	0.82	0.70
Weir Max Depth (ft)		Specif Force (cu ft)	2612.06	2746.11

Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	5.04	4.35
Min El Prs (ft)	26.00	W.P. Total (ft)	92.48	125.71
Delta EG (ft)	1.33	Conv. Total (cfs)	36925.9	44862.0
Delta WS (ft)	1.50	Top Width (ft)	78.50	105.78
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.58	0.08
BR Open Vel (ft/s)	10.49	C & E Loss (ft)	0.19	0.13
Coef of Q		Shear Total (lb/sq ft)	3.37	1.95
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	13.45	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	12.46	E.G. Elev (ft)	13.07	12.28
Q Total (cfs)	5290.00	W.S. Elev (ft)	11.14	10.88
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	10.32	9.40
Q Weir (cfs)		Max Chl Dpth (ft)	9.14	9.88
Weir Sta Lft (ft)		Vel Total (ft/s)	10.89	8.96
Weir Sta Rgt (ft)		Flow Area (sq ft)	485.64	590.71
Weir Submerg		Froude # Chl	0.80	0.67
Weir Max Depth (ft)		Specif Force (cu ft)	3520.21	3691.43
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	4.60	4.65
Min El Prs (ft)	26.00	W.P. Total (ft)	123.43	151.36
Delta EG (ft)	1.37	Conv. Total (cfs)	48863.6	60747.7
Delta WS (ft)	1.53	Top Width (ft)	105.53	126.95
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.52	0.07
BR Open Vel (ft/s)	10.89	C & E Loss (ft)	0.26	0.13
Coef of Q		Shear Total (lb/sq ft)	2.88	1.85
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

E.G. US. (ft)	15.32	Element	Inside BR US	Inside BR DS

W.S. US. (ft)	14.22	E.G. Elev (ft)	15.01	14.35
Q Total (cfs)	7380.00	W.S. Elev (ft)	13.14	13.04
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	11.89	10.88
Q Weir (cfs)		Max Chl Dpth (ft)	11.14	12.04
Weir Sta Lft (ft)		Vel Total (ft/s)	10.02	8.39
Weir Sta Rgt (ft)		Flow Area (sq ft)	736.89	880.12
Weir Submerg		Froude # Chl	0.70	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	5392.83	5799.20
Min El Weir Flow (ft)	26.96	Hydr Depth (ft)	5.54	6.36
Min El Prs (ft)	26.00	W.P. Total (ft)	159.87	173.12
Delta EG (ft)	1.12	Conv. Total (cfs)	78846.8	99858.9
Delta WS (ft)	1.14	Top Width (ft)	140.56	145.07
BR Open Area (sq ft)	2374.70	Frctn Loss (ft)	0.38	0.05
BR Open Vel (ft/s)	10.02	C & E Loss (ft)	0.28	0.10
Coef of Q		Shear Total (lb/sq ft)	2.52	1.73
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Warning: Pier drag coefficient of 2.0 assumed for Class B flow.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 850

INPUT
Description: JD
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	28	26.8	20	27	14	39.8	10	75.2	5
94	1	115	1	126.8	5	131.6	5	151.3	9
174.5	10	238.1	15	238.2	25				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	39.8	.04	131.6	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
39.8	131.6	20	20	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent

0	25	30	F
195	238.2	30	F

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
131.3	146.6	30	203	240	30

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.72	Element			
Vel Head (ft)	1.16	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.56	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	9.38	Flow Area (sq ft)	3.87	656.53	77.33
E.G. Slope (ft/ft)	0.004490	Area (sq ft)	3.87	656.53	77.33
Q Total (cfs)	5910.00	Flow (cfs)	4.86	5749.56	155.58
Top Width (ft)	144.16	Top Width (ft)	4.98	91.50	47.69
Vel Total (ft/s)	8.01	Avg. Vel. (ft/s)	1.26	8.76	2.01
Max Chl Dpth (ft)	10.56	Hydr. Depth (ft)	0.78	7.18	1.62
Conv. Total (cfs)	88199.3	Conv. (cfs)	72.6	85804.9	2321.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	5.21	99.49	51.37
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.21	1.85	0.42
Alpha	1.16	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.06	15.89	0.87
C & E Loss (ft)	0.07	Cum SA (acres)	0.05	2.08	1.11

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.23	Element			
Vel Head (ft)	0.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.84	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	4.89	Flow Area (sq ft)		260.32	
E.G. Slope (ft/ft)	0.003327	Area (sq ft)		260.32	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	69.12	Top Width (ft)		69.12	
Vel Total (ft/s)	5.04	Avg. Vel. (ft/s)		5.04	
Max Chl Dpth (ft)	5.84	Hydr. Depth (ft)		3.77	
Conv. Total (cfs)	22745.3	Conv. (cfs)		22745.3	
Length Wtd. (ft)	20.00	Wetted Per. (ft)		72.17	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.75	
Alpha	1.00	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.07	Cum Volume (acre-ft)	0.01	6.88	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.67	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.05	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.48	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.75	Flow Area (sq ft)		467.77	7.21
E.G. Slope (ft/ft)	0.005734	Area (sq ft)		467.77	7.21
Q Total (cfs)	3850.00	Flow (cfs)		3843.08	6.92
Top Width (ft)	103.72	Top Width (ft)		87.83	15.89
Vel Total (ft/s)	8.11	Avg. Vel. (ft/s)		8.22	0.96
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		5.33	0.45
Conv. Total (cfs)	50844.7	Conv. (cfs)		50753.2	91.4
Length Wtd. (ft)	20.00	Wetted Per. (ft)		93.71	17.43
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.79	0.15
Alpha	1.03	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	11.27	0.01
C & E Loss (ft)	0.09	Cum SA (acres)	0.00	1.91	0.01

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.88	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.07	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.82	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.01	Flow Area (sq ft)		497.44	13.79
E.G. Slope (ft/ft)	0.005610	Area (sq ft)		497.44	13.79
Q Total (cfs)	4148.00	Flow (cfs)		4132.33	15.67
Top Width (ft)	113.81	Top Width (ft)		90.19	23.62
Vel Total (ft/s)	8.11	Avg. Vel. (ft/s)		8.31	1.14
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)		5.52	0.58
Conv. Total (cfs)	55379.3	Conv. (cfs)		55170.1	209.3
Length Wtd. (ft)	20.00	Wetted Per. (ft)		96.43	25.50
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.81	0.19
Alpha	1.04	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	11.93	0.02
C & E Loss (ft)	0.09	Cum SA (acres)	0.01	1.96	0.01

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	12.08	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.15	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.94	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.91	Flow Area (sq ft)	1.40	599.94	50.27
E.G. Slope (ft/ft)	0.004917	Area (sq ft)	1.40	599.94	50.27
Q Total (cfs)	5290.00	Flow (cfs)	1.32	5199.07	89.61
Top Width (ft)	134.32	Top Width (ft)	3.00	91.50	39.82
Vel Total (ft/s)	8.12	Avg. Vel. (ft/s)	0.94	8.67	1.78
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	0.47	6.56	1.26
Conv. Total (cfs)	75439.9	Conv. (cfs)	18.8	74143.1	1278.0
Length Wtd. (ft)	20.00	Wetted Per. (ft)	3.14	98.87	42.86
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.14	1.86	0.36
Alpha	1.12	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.03	14.54	0.24
C & E Loss (ft)	0.07	Cum SA (acres)	0.03	2.08	0.44

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.12	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.08	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	10.40	Flow Area (sq ft)	15.20	796.26	151.22
E.G. Slope (ft/ft)	0.003513	Area (sq ft)	15.20	796.26	160.47
Q Total (cfs)	7380.00	Flow (cfs)	26.65	6944.32	409.03
Top Width (ft)	157.76	Top Width (ft)	9.86	91.50	56.40
Vel Total (ft/s)	7.67	Avg. Vel. (ft/s)	1.75	8.72	2.70
Max Chl Dpth (ft)	12.08	Hydr. Depth (ft)	1.54	8.70	3.12
Conv. Total (cfs)	124507.8	Conv. (cfs)	449.6	117157.4	6900.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	10.33	101.01	53.62
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.32	1.73	0.62
Alpha	1.22	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.18	19.35	3.75
C & E Loss (ft)	0.05	Cum SA (acres)	0.10	2.09	1.86

Warning: Divided flow computed for this cross-section.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 830

INPUT
Description: A
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	23	24.1	15	34.9	10.006	41.4	7	45.2	6
58.5	6	65	5	78	4	93.5	1	108.7	1
131.1	7	155	10	167.8	10	194.1	11	251.2	15
251.3	25								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	34.9	.04	131.1	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
34.9	131.1	9	9	.3	.5

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
132	155	25	205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.57	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.54	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	2.56	712.89	53.34
E.G. Slope (ft/ft)	0.003454	Area (sq ft)	2.56	712.89	53.34
Q Total (cfs)	5910.00	Flow (cfs)	2.70	5835.78	71.52
Top Width (ft)	147.28	Top Width (ft)	3.32	96.20	47.76
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	1.06	8.19	1.34
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	0.77	7.41	1.12
Conv. Total (cfs)	100563.7	Conv. (cfs)	46.0	99300.7	1217.0
Length Wtd. (ft)	9.00	Wetted Per. (ft)	3.66	98.18	53.77
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	1.57	0.21
Alpha	1.12	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.05	15.57	0.84
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	2.04	1.08

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.15	Element	Left OB	Channel	Right OB

Vel Head (ft)	0.38	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.77	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		265.30	
E.G. Slope (ft/ft)	0.004146	Area (sq ft)		265.30	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	87.98	Top Width (ft)		87.98	
Vel Total (ft/s)	4.95	Avg. Vel. (ft/s)		4.95	
Max Chl Dpth (ft)	5.77	Hydr. Depth (ft)		3.02	
Conv. Total (cfs)	20376.1	Conv. (cfs)		20376.1	
Length Wtd. (ft)	9.00	Wetted Per. (ft)		89.24	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.77	
Alpha	1.00	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	6.76	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.63	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.34	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.47	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		513.78	2.17
E.G. Slope (ft/ft)	0.004396	Area (sq ft)		513.78	2.17
Q Total (cfs)	3850.00	Flow (cfs)		3847.49	2.51
Top Width (ft)	95.94	Top Width (ft)		95.04	0.90
Vel Total (ft/s)	7.46	Avg. Vel. (ft/s)		7.49	1.16
Max Chl Dpth (ft)	8.47	Hydr. Depth (ft)		5.41	2.41
Conv. Total (cfs)	58068.7	Conv. (cfs)		58030.8	37.9
Length Wtd. (ft)	9.00	Wetted Per. (ft)		96.91	3.26
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.45	0.18
Alpha	1.01	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	11.05	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.87	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.80	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)		545.70	2.47
E.G. Slope (ft/ft)	0.004219	Area (sq ft)		545.70	2.47
Q Total (cfs)	4148.00	Flow (cfs)		4145.14	2.86
Top Width (ft)	96.67	Top Width (ft)		95.77	0.90
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)		7.60	1.16
Max Chl Dpth (ft)	8.80	Hydr. Depth (ft)		5.70	2.75
Conv. Total (cfs)	63858.1	Conv. (cfs)		63814.1	44.0
Length Wtd. (ft)	9.00	Wetted Per. (ft)		97.70	3.60

Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.47	0.18
Alpha	1.01	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	11.69	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.92	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.92	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	0.91	653.30	26.53
E.G. Slope (ft/ft)	0.003757	Area (sq ft)	0.91	653.30	26.53
Q Total (cfs)	5290.00	Flow (cfs)	0.71	5262.19	27.10
Top Width (ft)	136.18	Top Width (ft)	1.98	96.20	38.00
Vel Total (ft/s)	7.77	Avg. Vel. (ft/s)	0.78	8.05	1.02
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.46	6.79	0.70
Conv. Total (cfs)	86308.4	Conv. (cfs)	11.6	85854.6	442.2
Length Wtd. (ft)	9.00	Wetted Per. (ft)	2.19	98.18	42.75
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.56	0.15
Alpha	1.07	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.03	14.25	0.22
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	2.03	0.42

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.07	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	10.15	859.71	130.67
E.G. Slope (ft/ft)	0.002737	Area (sq ft)	10.15	859.71	130.67
Q Total (cfs)	7380.00	Flow (cfs)	15.12	7098.19	266.69
Top Width (ft)	153.73	Top Width (ft)	6.63	96.20	50.90
Vel Total (ft/s)	7.38	Avg. Vel. (ft/s)	1.49	8.26	2.04
Max Chl Dpth (ft)	12.07	Hydr. Depth (ft)	1.53	8.94	2.57
Conv. Total (cfs)	141061.3	Conv. (cfs)	289.0	135674.9	5097.5
Length Wtd. (ft)	9.00	Wetted Per. (ft)	7.30	98.18	61.28
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.24	1.50	0.36
Alpha	1.21	Stream Power (lb/ft s)	251.30	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.18	18.97	3.68
C & E Loss (ft)	0.02	Cum SA (acres)	0.10	2.05	1.83

Warning: Divided flow computed for this cross-section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 821

INPUT
Description: AD
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12	16.5	22	12.5	27	10.25	32	8	42	6.5
52	6	62	4.5	72	3.5	82	1.5	92	1
102	1	112	4	122	7	132	9	154	10
203	11.5	235	12						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12	.065	27	.035	132	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
27	132	1	1	.3	.5

Blocked Obstructions num= 2

Sta L	Sta R	Elev	Sta L	Sta R	Elev
132	155	25	205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.53	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	1.82	729.91	36.68
E.G. Slope (ft/ft)	0.002866	Area (sq ft)	1.82	729.91	36.68
Q Total (cfs)	5910.00	Flow (cfs)	1.55	5872.59	35.86
Top Width (ft)	157.69	Top Width (ft)	2.84	105.00	49.85
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	0.85	8.05	0.98
Max Chl Dpth (ft)	10.53	Hydr. Depth (ft)	0.64	6.95	0.74
Conv. Total (cfs)	110396.7	Conv. (cfs)	29.0	109697.9	669.8
Length Wtd. (ft)	1.00	Wetted Per. (ft)	3.12	109.59	51.37
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.19	0.13
Alpha	1.09	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.05	15.42	0.83
C & E Loss (ft)	0.07	Cum SA (acres)	0.04	2.02	1.07

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.11	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.42	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.69	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		252.86	
E.G. Slope (ft/ft)	0.003298	Area (sq ft)		252.86	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.22	Top Width (ft)		80.22	
Vel Total (ft/s)	5.19	Avg. Vel. (ft/s)		5.19	
Max Chl Dpth (ft)	5.69	Hydr. Depth (ft)		3.15	
Conv. Total (cfs)	22844.8	Conv. (cfs)		22844.8	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		81.45	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.64	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	6.70	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.61	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.30	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.89	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.41	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		507.88	
E.G. Slope (ft/ft)	0.003918	Area (sq ft)		507.88	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	103.13	Top Width (ft)		103.13	
Vel Total (ft/s)	7.58	Avg. Vel. (ft/s)		7.58	
Max Chl Dpth (ft)	8.41	Hydr. Depth (ft)		4.92	
Conv. Total (cfs)	61509.3	Conv. (cfs)		61509.3	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		105.41	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.18	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	10.94	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.85	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.90	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.77	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		545.05	
E.G. Slope (ft/ft)	0.003650	Area (sq ft)		545.05	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	103.92	Top Width (ft)		103.92	
Vel Total (ft/s)	7.61	Avg. Vel. (ft/s)		7.61	
Max Chl Dpth (ft)	8.77	Hydr. Depth (ft)		5.24	
Conv. Total (cfs)	68658.2	Conv. (cfs)		68658.2	

Length Wtd. (ft)	1.00	Wetted Per. (ft)		106.64	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.16	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	11.58	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	1.90	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.88	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.98	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.90	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	0.47	664.17	12.43
E.G. Slope (ft/ft)	0.003150	Area (sq ft)	0.47	664.17	12.43
Q Total (cfs)	5290.00	Flow (cfs)	0.27	5280.75	8.98
Top Width (ft)	134.94	Top Width (ft)	1.45	105.00	28.49
Vel Total (ft/s)	7.81	Avg. Vel. (ft/s)	0.57	7.95	0.72
Max Chl Dpth (ft)	9.90	Hydr. Depth (ft)	0.33	6.33	0.44
Conv. Total (cfs)	94255.3	Conv. (cfs)	4.8	94090.4	160.0
Length Wtd. (ft)	1.00	Wetted Per. (ft)	1.59	108.96	29.38
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	1.20	0.08
Alpha	1.03	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.03	14.11	0.22
C & E Loss (ft)	0.05	Cum SA (acres)	0.02	2.01	0.42

Warning: Divided flow computed for this cross-section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.98	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	13.07	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	8.87	891.56	113.66
E.G. Slope (ft/ft)	0.002233	Area (sq ft)	8.87	891.56	113.66
Q Total (cfs)	7380.00	Flow (cfs)	11.21	7168.61	200.18
Top Width (ft)	161.42	Top Width (ft)	6.42	105.00	50.00
Vel Total (ft/s)	7.28	Avg. Vel. (ft/s)	1.26	8.04	1.76
Max Chl Dpth (ft)	12.07	Hydr. Depth (ft)	1.38	8.49	2.27
Conv. Total (cfs)	156166.6	Conv. (cfs)	237.2	151693.4	4236.0
Length Wtd. (ft)	1.00	Wetted Per. (ft)	7.01	111.13	54.60
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.18	1.12	0.29
Alpha	1.19	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.18	18.78	3.65
C & E Loss (ft)	0.12	Cum SA (acres)	0.09	2.03	1.82

Warning: Divided flow computed for this cross-section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 820

INPUT
Description: ADD
Station Elevation Data num= 24

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	16.5	10	12.5	15	10.25	20	8	30	6.5
40	6	50	4.5	60	3.5	70	1.5	80	1
90	1	100	4	110	7	119.4	9	119.5	9
142.2	10	142.3	10	150	10	160	10	170	11
180	11	185.5	11.5	185.6	11.5	290	12		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	15	.035	142.3	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15	142.3	95	95	.3	.5

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.46	Element			
Vel Head (ft)	0.86	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.59	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	2.01	782.50	47.90
E.G. Slope (ft/ft)	0.002824	Area (sq ft)	2.01	782.50	47.90
Q Total (cfs)	5910.00	Flow (cfs)	1.76	5859.74	48.50
Top Width (ft)	193.15	Top Width (ft)	2.99	127.30	62.87
Vel Total (ft/s)	7.10	Avg. Vel. (ft/s)	0.88	7.49	1.01
Max Chl Dpth (ft)	10.59	Hydr. Depth (ft)	0.67	6.15	0.76
Conv. Total (cfs)	111218.0	Conv. (cfs)	33.1	110272.2	912.7
Length Wtd. (ft)	95.00	Wetted Per. (ft)	3.27	129.39	62.94
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.11	1.07	0.13
Alpha	1.10	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.31	Cum Volume (acre-ft)	0.05	15.41	0.83
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	2.02	1.07

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.10	Element			
Vel Head (ft)	0.42	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.68	Reach Len. (ft)	95.00	95.00	95.00

Crit W.S. (ft)		Flow Area (sq ft)		252.46	
E.G. Slope (ft/ft)	0.003313	Area (sq ft)		252.46	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.17	Top Width (ft)		80.17	
Vel Total (ft/s)	5.20	Avg. Vel. (ft/s)		5.20	
Max Chl Dpth (ft)	5.68	Hydr. Depth (ft)		3.15	
Conv. Total (cfs)	22794.7	Conv. (cfs)		22794.7	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		81.40	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.64	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.01	6.70	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	1.61	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.29	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.89	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.40	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		508.60	
E.G. Slope (ft/ft)	0.004312	Area (sq ft)		508.60	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	111.78	Top Width (ft)		111.78	
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)		7.57	
Max Chl Dpth (ft)	8.40	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	58627.2	Conv. (cfs)		58627.2	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		113.68	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.20	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.48	Cum Volume (acre-ft)	0.01	10.93	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	1.85	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.65	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.88	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.77	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		551.27	
E.G. Slope (ft/ft)	0.004247	Area (sq ft)		551.27	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	120.92	Top Width (ft)		120.92	
Vel Total (ft/s)	7.52	Avg. Vel. (ft/s)		7.52	
Max Chl Dpth (ft)	8.77	Hydr. Depth (ft)		4.56	
Conv. Total (cfs)	63653.2	Conv. (cfs)		63653.2	

Length Wtd. (ft)	95.00	Wetted Per. (ft)		122.91	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.19	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.47	Cum Volume (acre-ft)	0.01	11.56	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	1.90	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.83	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.95	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	0.55	700.99	21.42
E.G. Slope (ft/ft)	0.003290	Area (sq ft)	0.55	700.99	21.42
Q Total (cfs)	5290.00	Flow (cfs)	0.34	5265.76	23.91
Top Width (ft)	156.10	Top Width (ft)	1.56	127.30	27.23
Vel Total (ft/s)	7.32	Avg. Vel. (ft/s)	0.61	7.51	1.12
Max Chl Dpth (ft)	9.95	Hydr. Depth (ft)	0.35	5.51	0.79
Conv. Total (cfs)	92223.0	Conv. (cfs)	5.9	91800.4	416.8
Length Wtd. (ft)	95.00	Wetted Per. (ft)	1.71	129.39	27.28
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.07	1.11	0.16
Alpha	1.05	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.37	Cum Volume (acre-ft)	0.03	14.10	0.22
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	2.01	0.42

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.74	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	13.18	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	9.63	985.01	265.63
E.G. Slope (ft/ft)	0.001862	Area (sq ft)	9.63	985.01	265.63
Q Total (cfs)	7380.00	Flow (cfs)	11.41	6983.27	385.32
Top Width (ft)	281.71	Top Width (ft)	6.71	127.30	147.70
Vel Total (ft/s)	5.86	Avg. Vel. (ft/s)	1.18	7.09	1.45
Max Chl Dpth (ft)	12.18	Hydr. Depth (ft)	1.44	7.74	1.80
Conv. Total (cfs)	171022.7	Conv. (cfs)	264.3	161829.0	8929.4
Length Wtd. (ft)	95.00	Wetted Per. (ft)	7.33	129.39	148.96
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	0.88	0.21
Alpha	1.39	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.18	18.76	3.65
C & E Loss (ft)	0.01	Cum SA (acres)	0.09	2.03	1.82

Warning: The cross-section end points had to be extended vertically for the computed water surface.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 725

INPUT
Description: 10
10
Station Elevation Data num= 22

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	14	20	10	30	4	60	4
70	2.8	80	2.5	90	2.5	100	3	110	4.5
120	7.5	126	9	154	10	192	11	235	12
260	13	263	14	266	15	270	16	272	17
281	19	286	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	20	.04	154	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
20	154	150	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.14	Element			
Vel Head (ft)	0.84	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.30	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.12	798.33	32.38
E.G. Slope (ft/ft)	0.003724	Area (sq ft)	2.12	798.33	32.38
Q Total (cfs)	5910.00	Flow (cfs)	2.11	5874.50	33.39
Top Width (ft)	188.19	Top Width (ft)	3.25	134.00	50.94
Vel Total (ft/s)	7.10	Avg. Vel. (ft/s)	1.00	7.36	1.03
Max Chl Dpth (ft)	8.80	Hydr. Depth (ft)	0.65	5.96	0.64
Conv. Total (cfs)	96846.9	Conv. (cfs)	34.6	96265.2	547.2
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.50	136.51	50.96
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.14	1.36	0.15
Alpha	1.07	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.05	13.68	0.74
C & E Loss (ft)	0.07	Cum SA (acres)	0.04	1.73	0.95

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	6.62	Element			
Vel Head (ft)	0.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.09	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		224.72	

E.G. Slope (ft/ft)	0.007272	Area (sq ft)		224.72	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	88.79	Top Width (ft)		88.79	
Vel Total (ft/s)	5.84	Avg. Vel. (ft/s)		5.84	
Max Chl Dpth (ft)	3.59	Hydr. Depth (ft)		2.53	
Conv. Total (cfs)	15385.9	Conv. (cfs)		15385.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		89.81	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.14	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	1.16	Cum Volume (acre-ft)	0.01	6.18	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.43	0.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	9.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.98	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.81	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		484.97	
E.G. Slope (ft/ft)	0.005966	Area (sq ft)		484.97	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	103.25	Top Width (ft)		103.25	
Vel Total (ft/s)	7.94	Avg. Vel. (ft/s)		7.94	
Max Chl Dpth (ft)	6.31	Hydr. Depth (ft)		4.70	
Conv. Total (cfs)	49843.7	Conv. (cfs)		49843.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		105.38	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.71	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.67	Cum Volume (acre-ft)	0.01	9.85	0.01
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.61	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.15	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.		0.040	
W.S. Elev (ft)	9.18	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		523.90	
E.G. Slope (ft/ft)	0.005799	Area (sq ft)		523.90	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	109.62	Top Width (ft)		109.62	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	6.68	Hydr. Depth (ft)		4.78	
Conv. Total (cfs)	54471.4	Conv. (cfs)		54471.4	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		111.88	

Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.70	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.63	Cum Volume (acre-ft)	0.01	10.39	0.01
C & E Loss (ft)	0.11	Cum SA (acres)	0.01	1.64	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.88	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.57	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.41	700.79	6.24
E.G. Slope (ft/ft)	0.004654	Area (sq ft)	0.41	700.79	6.24
Q Total (cfs)	5290.00	Flow (cfs)	0.26	5285.51	4.23
Top Width (ft)	157.21	Top Width (ft)	1.43	134.00	21.78
Vel Total (ft/s)	7.48	Avg. Vel. (ft/s)	0.65	7.54	0.68
Max Chl Dpth (ft)	8.07	Hydr. Depth (ft)	0.29	5.23	0.29
Conv. Total (cfs)	77538.9	Conv. (cfs)	3.9	77473.0	62.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.54	136.51	21.78
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.08	1.49	0.08
Alpha	1.02	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.47	Cum Volume (acre-ft)	0.03	12.57	0.18
C & E Loss (ft)	0.08	Cum SA (acres)	0.02	1.73	0.36

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.72	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	13.00	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	11.24	1025.74	171.79
E.G. Slope (ft/ft)	0.002360	Area (sq ft)	11.24	1025.74	171.79
Q Total (cfs)	7380.00	Flow (cfs)	15.55	7101.22	263.23
Top Width (ft)	247.45	Top Width (ft)	7.50	134.00	105.95
Vel Total (ft/s)	6.11	Avg. Vel. (ft/s)	1.38	6.92	1.53
Max Chl Dpth (ft)	10.50	Hydr. Depth (ft)	1.50	7.65	1.62
Conv. Total (cfs)	151921.3	Conv. (cfs)	320.2	146182.5	5418.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	8.07	136.51	106.00
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.21	1.11	0.24
Alpha	1.24	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.15	16.57	3.17
C & E Loss (ft)	0.06	Cum SA (acres)	0.08	1.74	1.54

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 575

INPUT
Description: 9
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	13.5	17	8.25	20	6	30	1.5
40	1.5	50	1.5	60	2.25	70	2.8	80	3.1
110	3.1	120	4	130	7	140	9	172	10
230	11	280	12	280.1	16				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	17	.04	140	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
17	140	150	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.59	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.08	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	5.34	937.10	84.46
E.G. Slope (ft/ft)	0.001918	Area (sq ft)	5.34	937.10	84.46
Q Total (cfs)	5910.00	Flow (cfs)	5.81	5825.50	78.69
Top Width (ft)	220.83	Top Width (ft)	3.77	123.00	94.05
Vel Total (ft/s)	5.76	Avg. Vel. (ft/s)	1.09	6.22	0.93
Max Chl Dpth (ft)	9.58	Hydr. Depth (ft)	1.42	7.62	0.90
Conv. Total (cfs)	134958.7	Conv. (cfs)	132.7	133029.1	1796.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.72	125.44	94.08
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.14	0.89	0.11
Alpha	1.15	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.04	10.69	0.54
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	1.29	0.70

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	5.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.94	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		227.65	
E.G. Slope (ft/ft)	0.008227	Area (sq ft)		227.65	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	

Top Width (ft)	100.80	Top Width (ft)		100.80	
Vel Total (ft/s)	5.76	Avg. Vel. (ft/s)		5.76	
Max Chl Dpth (ft)	3.44	Hydr. Depth (ft)		2.26	
Conv. Total (cfs)	14464.9	Conv. (cfs)		14464.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		101.77	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.15	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.58	Cum Volume (acre-ft)	0.01	5.40	0.01
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	1.10	0.01

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	9.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.62	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.39	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.01	607.03	
E.G. Slope (ft/ft)	0.003444	Area (sq ft)	0.01	607.03	
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3850.00	
Top Width (ft)	120.14	Top Width (ft)	0.19	119.95	
Vel Total (ft/s)	6.34	Avg. Vel. (ft/s)	0.20	6.34	
Max Chl Dpth (ft)	6.89	Hydr. Depth (ft)	0.07	5.06	
Conv. Total (cfs)	65604.0	Conv. (cfs)	0.0	65603.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.23	122.33	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.01	1.07	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	7.97	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.23	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	9.42	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.62	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.80	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.20	656.25	
E.G. Slope (ft/ft)	0.003153	Area (sq ft)	0.20	656.25	
Q Total (cfs)	4148.00	Flow (cfs)	0.09	4147.91	
Top Width (ft)	122.71	Top Width (ft)	0.73	121.98	
Vel Total (ft/s)	6.32	Avg. Vel. (ft/s)	0.47	6.32	
Max Chl Dpth (ft)	7.30	Hydr. Depth (ft)	0.27	5.38	
Conv. Total (cfs)	73874.6	Conv. (cfs)	1.7	73872.9	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.91	124.41	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.04	1.04	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00

Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.01	8.36	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	1.25	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.61	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.79	840.41	27.96
E.G. Slope (ft/ft)	0.002253	Area (sq ft)	2.79	840.41	27.96
Q Total (cfs)	5290.00	Flow (cfs)	2.65	5266.52	20.84
Top Width (ft)	174.83	Top Width (ft)	2.73	123.00	49.11
Vel Total (ft/s)	6.07	Avg. Vel. (ft/s)	0.95	6.27	0.75
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	1.02	6.83	0.57
Conv. Total (cfs)	111443.1	Conv. (cfs)	55.7	110948.3	439.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.41	125.44	49.13
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.12	0.94	0.08
Alpha	1.06	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.02	9.91	0.13
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.28	0.24

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.39	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.87	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	14.25	1157.61	314.35
E.G. Slope (ft/ft)	0.001335	Area (sq ft)	14.25	1157.61	314.35
Q Total (cfs)	7380.00	Flow (cfs)	17.94	6913.71	448.35
Top Width (ft)	269.19	Top Width (ft)	6.17	123.00	140.02
Vel Total (ft/s)	4.97	Avg. Vel. (ft/s)	1.26	5.97	1.43
Max Chl Dpth (ft)	11.37	Hydr. Depth (ft)	2.31	9.41	2.25
Conv. Total (cfs)	201954.9	Conv. (cfs)	491.0	189194.9	12269.1
Length Wtd. (ft)	150.00	Wetted Per. (ft)	7.71	125.44	140.91
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.15	0.77	0.19
Alpha	1.36	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.19	Cum Volume (acre-ft)	0.11	12.81	2.33
C & E Loss (ft)	0.00	Cum SA (acres)	0.06	1.30	1.12

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 425

INPUT
Description: 8
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	11	12	9.8	20	5	30	0
70	0	80	.5	90	1.5	100	2	110	5.5
117.4	9	160	10	210	10	265	11	268	12
275	13	280	14						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	12	.04	117.4	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
12	117.4	90	90	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.41	Element			
Vel Head (ft)	0.59	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.82	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	0.86	934.95	115.56
E.G. Slope (ft/ft)	0.001604	Area (sq ft)	0.86	934.95	115.56
Q Total (cfs)	5910.00	Flow (cfs)	0.46	5815.40	94.15
Top Width (ft)	244.73	Top Width (ft)	1.70	105.40	137.64
Vel Total (ft/s)	5.62	Avg. Vel. (ft/s)	0.53	6.22	0.81
Max Chl Dpth (ft)	10.82	Hydr. Depth (ft)	0.51	8.87	0.84
Conv. Total (cfs)	147573.0	Conv. (cfs)	11.4	145210.7	2350.9
Length Wtd. (ft)	90.00	Wetted Per. (ft)	1.98	109.37	137.65
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.04	0.86	0.08
Alpha	1.21	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.03	7.47	0.20
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.90	0.30

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	4.81	Element			
Vel Head (ft)	0.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.54	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		317.80	
E.G. Slope (ft/ft)	0.002227	Area (sq ft)		317.80	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	86.35	Top Width (ft)		86.35	
Vel Total (ft/s)	4.13	Avg. Vel. (ft/s)		4.13	
Max Chl Dpth (ft)	4.54	Hydr. Depth (ft)		3.68	
Conv. Total (cfs)	27804.0	Conv. (cfs)		27804.0	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		87.93	

Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.50	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.01	4.46	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.78	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.55	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.02	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		644.11	
E.G. Slope (ft/ft)	0.002266	Area (sq ft)		644.11	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	100.38	Top Width (ft)		100.38	
Vel Total (ft/s)	5.98	Avg. Vel. (ft/s)		5.98	
Max Chl Dpth (ft)	8.02	Hydr. Depth (ft)		6.42	
Conv. Total (cfs)	80885.0	Conv. (cfs)		80885.0	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		103.64	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.88	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.01	5.81	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.85	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	9.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.57	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.45	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		686.64	
E.G. Slope (ft/ft)	0.002174	Area (sq ft)		686.64	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	101.97	Top Width (ft)		101.97	
Vel Total (ft/s)	6.04	Avg. Vel. (ft/s)		6.04	
Max Chl Dpth (ft)	8.45	Hydr. Depth (ft)		6.73	
Conv. Total (cfs)	88953.4	Conv. (cfs)		88953.4	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		105.44	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.88	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.23	Cum Volume (acre-ft)	0.01	6.05	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.86	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.60	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065

W.S. Elev (ft)	10.00	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	0.03	848.26	21.14
E.G. Slope (ft/ft)	0.001827	Area (sq ft)	0.03	848.26	21.14
Q Total (cfs)	5290.00	Flow (cfs)	0.01	5277.02	12.98
Top Width (ft)	148.17	Top Width (ft)	0.33	105.40	42.44
Vel Total (ft/s)	6.08	Avg. Vel. (ft/s)	0.19	6.22	0.61
Max Chl Dpth (ft)	10.00	Hydr. Depth (ft)	0.10	8.05	0.50
Conv. Total (cfs)	123773.8	Conv. (cfs)	0.1	123470.0	303.7
Length Wtd. (ft)	90.00	Wetted Per. (ft)	0.38	109.37	42.45
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.01	0.88	0.06
Alpha	1.04	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.02	7.01	0.04
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.89	0.08

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.69	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	6.62	1132.07	395.93
E.G. Slope (ft/ft)	0.001159	Area (sq ft)	6.62	1132.07	395.93
Q Total (cfs)	7380.00	Flow (cfs)	5.99	6799.86	574.15
Top Width (ft)	265.24	Top Width (ft)	4.41	105.40	155.42
Vel Total (ft/s)	4.81	Avg. Vel. (ft/s)	0.90	6.01	1.45
Max Chl Dpth (ft)	12.69	Hydr. Depth (ft)	1.50	10.74	2.55
Conv. Total (cfs)	216784.7	Conv. (cfs)	175.8	199743.3	16865.5
Length Wtd. (ft)	90.00	Wetted Per. (ft)	5.28	109.37	155.66
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.09	0.75	0.18
Alpha	1.44	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.07	8.87	1.11
C & E Loss (ft)	0.03	Cum SA (acres)	0.04	0.90	0.61

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 335

INPUT
Description: 7
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	12.5	18	8.1	20	7	30	1.5
40	-.5	50	-2	60	-2	70	-2	80	0
90	4	100	9	135	10	175	10	205	11
260	11	260.1	16						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	18	.04	100	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
18	100	73	73	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.93	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.27	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	4.28	756.96	38.76
E.G. Slope (ft/ft)	0.002411	Area (sq ft)	4.28	756.96	38.76
Q Total (cfs)	5910.00	Flow (cfs)	4.64	5879.19	26.17
Top Width (ft)	169.01	Top Width (ft)	3.94	82.00	83.07
Vel Total (ft/s)	7.39	Avg. Vel. (ft/s)	1.08	7.77	0.68
Max Chl Dpth (ft)	12.27	Hydr. Depth (ft)	1.08	9.23	0.47
Conv. Total (cfs)	120358.1	Conv. (cfs)	94.5	119730.7	533.0
Length Wtd. (ft)	73.00	Wetted Per. (ft)	4.50	86.15	83.09
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.14	1.32	0.07
Alpha	1.10	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.02	5.72	0.04
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	0.70	0.07

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.62	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.29	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.34	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		305.17	
E.G. Slope (ft/ft)	0.001807	Area (sq ft)		305.17	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	65.83	Top Width (ft)		65.83	
Vel Total (ft/s)	4.30	Avg. Vel. (ft/s)		4.30	
Max Chl Dpth (ft)	6.34	Hydr. Depth (ft)		4.64	
Conv. Total (cfs)	30867.5	Conv. (cfs)		30867.5	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		67.92	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		0.51	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	3.81	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.62	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.51	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		533.04	
E.G. Slope (ft/ft)	0.003095	Area (sq ft)		533.04	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	77.94	Top Width (ft)		77.94	
Vel Total (ft/s)	7.22	Avg. Vel. (ft/s)		7.22	
Max Chl Dpth (ft)	9.51	Hydr. Depth (ft)		6.84	
Conv. Total (cfs)	69203.3	Conv. (cfs)		69203.3	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		81.59	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.26	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	4.60	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.67	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.76	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.92	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		565.55	
E.G. Slope (ft/ft)	0.003035	Area (sq ft)		565.55	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	79.51	Top Width (ft)		79.51	
Vel Total (ft/s)	7.33	Avg. Vel. (ft/s)		7.33	
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)		7.11	
Conv. Total (cfs)	75287.9	Conv. (cfs)		75287.9	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		83.37	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.29	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	4.75	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.67	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.37	Element	Left OB	Channel	Right OB

Vel Head (ft)	0.91	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.46	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	1.68	690.54	3.69
E.G. Slope (ft/ft)	0.002648	Area (sq ft)	1.68	690.54	3.69
Q Total (cfs)	5290.00	Flow (cfs)	1.40	5286.98	1.63
Top Width (ft)	100.54	Top Width (ft)	2.47	82.00	16.06
Vel Total (ft/s)	7.60	Avg. Vel. (ft/s)	0.83	7.66	0.44
Max Chl Dpth (ft)	11.46	Hydr. Depth (ft)	0.68	8.42	0.23
Conv. Total (cfs)	102796.6	Conv. (cfs)	27.2	102737.9	31.6
Length Wtd. (ft)	73.00	Wetted Per. (ft)	2.82	86.15	16.07
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.10	1.33	0.04
Alpha	1.01	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.01	5.42	0.02
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	0.70	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.83	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.22	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	15.43	916.88	302.59
E.G. Slope (ft/ft)	0.001761	Area (sq ft)	15.43	916.88	302.59
Q Total (cfs)	7380.00	Flow (cfs)	21.94	6916.37	441.69
Top Width (ft)	249.51	Top Width (ft)	7.49	82.00	160.02
Vel Total (ft/s)	5.98	Avg. Vel. (ft/s)	1.42	7.54	1.46
Max Chl Dpth (ft)	14.22	Hydr. Depth (ft)	2.06	11.18	1.89
Conv. Total (cfs)	175839.3	Conv. (cfs)	522.7	164792.6	10524.0
Length Wtd. (ft)	73.00	Wetted Per. (ft)	8.55	86.15	161.25
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.20	1.17	0.21
Alpha	1.50	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.05	6.75	0.39
C & E Loss (ft)	0.07	Cum SA (acres)	0.03	0.71	0.29

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 262

INPUT
Description: 6
6
6
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	7	9.1	10	7	20	1	30	-2
40	-3	50	-3	60	0	70	5	80	9.5
135	11	175	12	255	13	282	14		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	7	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
7	80	75	75	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.51	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	9.39	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	0.06	599.09	
E.G. Slope (ft/ft)	0.004665	Area (sq ft)	0.06	599.09	
Q Total (cfs)	5910.00	Flow (cfs)	0.02	5909.98	
Top Width (ft)	73.18	Top Width (ft)	0.42	72.76	
Vel Total (ft/s)	9.86	Avg. Vel. (ft/s)	0.38	9.86	
Max Chl Dpth (ft)	12.39	Hydr. Depth (ft)	0.15	8.23	
Conv. Total (cfs)	86530.8	Conv. (cfs)	0.3	86530.5	
Length Wtd. (ft)	75.00	Wetted Per. (ft)	0.51	78.14	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.04	2.23	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.34	Cum Volume (acre-ft)	0.02	4.59	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	0.57	0.00

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.47	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.08	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		262.64	
E.G. Slope (ft/ft)	0.002305	Area (sq ft)		262.64	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.29	Top Width (ft)		53.29	
Vel Total (ft/s)	5.00	Avg. Vel. (ft/s)		5.00	
Max Chl Dpth (ft)	7.08	Hydr. Depth (ft)		4.93	

Conv. Total (cfs)	27326.8	Conv. (cfs)		27326.8	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		56.03	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		0.67	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	3.34	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.52	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.57	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		406.88	
E.G. Slope (ft/ft)	0.005827	Area (sq ft)		406.88	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.76	Top Width (ft)		62.76	
Vel Total (ft/s)	9.46	Avg. Vel. (ft/s)		9.46	
Max Chl Dpth (ft)	9.57	Hydr. Depth (ft)		6.48	
Conv. Total (cfs)	50437.4	Conv. (cfs)		50437.4	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		66.75	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	3.81	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.55	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.40	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.97	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		432.71	
E.G. Slope (ft/ft)	0.005706	Area (sq ft)		432.71	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	64.34	Top Width (ft)		64.34	
Vel Total (ft/s)	9.59	Avg. Vel. (ft/s)		9.59	
Max Chl Dpth (ft)	9.97	Hydr. Depth (ft)		6.73	
Conv. Total (cfs)	54913.1	Conv. (cfs)		54913.1	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		68.53	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.25	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.40	Cum Volume (acre-ft)	0.01	3.92	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.55	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.55	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		539.04	
E.G. Slope (ft/ft)	0.005045	Area (sq ft)		539.04	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	70.12	Top Width (ft)		70.12	
Vel Total (ft/s)	9.81	Avg. Vel. (ft/s)		9.81	
Max Chl Dpth (ft)	11.55	Hydr. Depth (ft)		7.69	
Conv. Total (cfs)	74480.0	Conv. (cfs)		74480.0	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		75.15	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.26	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.01	4.39	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.57	0.01

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.50	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.30	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	3.47	738.55	59.83
E.G. Slope (ft/ft)	0.003559	Area (sq ft)	3.47	738.55	59.83
Q Total (cfs)	7380.00	Flow (cfs)	4.42	7300.07	75.51
Top Width (ft)	143.31	Top Width (ft)	3.15	73.00	67.17
Vel Total (ft/s)	9.20	Avg. Vel. (ft/s)	1.27	9.88	1.26
Max Chl Dpth (ft)	14.30	Hydr. Depth (ft)	1.10	10.12	0.89
Conv. Total (cfs)	123714.4	Conv. (cfs)	74.1	122374.5	1265.8
Length Wtd. (ft)	75.00	Wetted Per. (ft)	3.84	78.40	67.19
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.20	2.09	0.20
Alpha	1.14	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.03	5.36	0.09
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	0.58	0.09

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 187

INPUT
Description: 5
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	8	9.2	10	8	20	1.5	30	-2.5
40	-4	50	-4	60	-1	70	4	80	9.5

115	12	141	13	185	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	80	50	50	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.55	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.46	Wt. n-Val.		0.040	
W.S. Elev (ft)	9.10	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		610.37	
E.G. Slope (ft/ft)	0.004309	Area (sq ft)		610.37	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	71.09	Top Width (ft)		71.09	
Vel Total (ft/s)	9.68	Avg. Vel. (ft/s)		9.68	
Max Chl Dpth (ft)	13.10	Hydr. Depth (ft)		8.59	
Conv. Total (cfs)	90037.4	Conv. (cfs)		90037.4	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		77.13	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.13	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.02	3.54	0.01
C & E Loss (ft)	0.05	Cum SA (acres)	0.01	0.45	0.00

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.30	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.31	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.98	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		291.39	
E.G. Slope (ft/ft)	0.001669	Area (sq ft)		291.39	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.79	Top Width (ft)		53.79	
Vel Total (ft/s)	4.50	Avg. Vel. (ft/s)		4.50	
Max Chl Dpth (ft)	7.98	Hydr. Depth (ft)		5.42	
Conv. Total (cfs)	32114.6	Conv. (cfs)		32114.6	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		57.02	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		0.53	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.01	2.86	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.43	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.31	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.22	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		419.83	
E.G. Slope (ft/ft)	0.005145	Area (sq ft)		419.83	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.28	Top Width (ft)		61.28	
Vel Total (ft/s)	9.17	Avg. Vel. (ft/s)		9.17	
Max Chl Dpth (ft)	10.22	Hydr. Depth (ft)		6.85	
Conv. Total (cfs)	53676.0	Conv. (cfs)		53676.0	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		65.75	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.05	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	3.10	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.44	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.97	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.35	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.63	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		445.22	
E.G. Slope (ft/ft)	0.005070	Area (sq ft)		445.22	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.66	Top Width (ft)		62.66	
Vel Total (ft/s)	9.32	Avg. Vel. (ft/s)		9.32	
Max Chl Dpth (ft)	10.63	Hydr. Depth (ft)		7.11	
Conv. Total (cfs)	58253.7	Conv. (cfs)		58253.7	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		67.35	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.09	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)	0.01	3.16	0.01
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.44	0.01

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.67	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.24	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)		550.65	
E.G. Slope (ft/ft)	0.004578	Area (sq ft)		550.65	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	68.10	Top Width (ft)		68.10	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	12.24	Hydr. Depth (ft)		8.09	

Conv. Total (cfs)	78187.3	Conv. (cfs)		78187.3	
Length Wtd. (ft)	50.00	Wetted Per. (ft)		73.69	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.14	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.01	3.45	0.01
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	0.45	0.01

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.54	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.49	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.05	Reach Len. (ft)	50.00	50.00	50.00
Crit W.S. (ft)		Flow Area (sq ft)	2.86	751.09	16.88
E.G. Slope (ft/ft)	0.003405	Area (sq ft)	2.86	751.09	16.88
Q Total (cfs)	7380.00	Flow (cfs)	3.27	7357.75	18.98
Top Width (ft)	96.82	Top Width (ft)	3.09	72.00	21.74
Vel Total (ft/s)	9.57	Avg. Vel. (ft/s)	1.14	9.80	1.12
Max Chl Dpth (ft)	15.05	Hydr. Depth (ft)	0.93	10.43	0.78
Conv. Total (cfs)	126480.5	Conv. (cfs)	56.1	126099.1	325.3
Length Wtd. (ft)	50.00	Wetted Per. (ft)	3.60	78.17	21.79
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.17	2.04	0.16
Alpha	1.04	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.19	Cum Volume (acre-ft)	0.03	4.08	0.02
C & E Loss (ft)	0.07	Cum SA (acres)	0.01	0.46	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 137

INPUT
Description: 4
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left Right Lengths: Left Channel Right Coeff Contr. Expan.

```
          10      80               77      77      77              .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
       0      16      15       F
      70      90      15       F
```

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.28	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.36	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.71	Flow Area (sq ft)		531.20	
E.G. Slope (ft/ft)	0.004602	Area (sq ft)	0.00	565.91	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	69.03	Top Width (ft)	0.10	68.93	
Vel Total (ft/s)	11.13	Avg. Vel. (ft/s)		11.13	
Max Chl Dpth (ft)	12.36	Hydr. Depth (ft)		9.84	
Conv. Total (cfs)	87123.8	Conv. (cfs)		87123.8	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.67	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.02	2.87	0.01
C & E Loss (ft)	0.25	Cum SA (acres)	0.00	0.37	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.22	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.32	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.90	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	0.50	Flow Area (sq ft)		291.23	
E.G. Slope (ft/ft)	0.001610	Area (sq ft)		291.91	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.92	Top Width (ft)		53.92	
Vel Total (ft/s)	4.50	Avg. Vel. (ft/s)		4.50	
Max Chl Dpth (ft)	7.90	Hydr. Depth (ft)		5.56	
Conv. Total (cfs)	32698.3	Conv. (cfs)		32698.3	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		55.43	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		0.53	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	2.53	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.37	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.23	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.70	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.85	Flow Area (sq ft)		387.51	
E.G. Slope (ft/ft)	0.005588	Area (sq ft)		394.23	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	60.01	Top Width (ft)		60.01	
Vel Total (ft/s)	9.94	Avg. Vel. (ft/s)		9.94	
Max Chl Dpth (ft)	9.70	Hydr. Depth (ft)		7.18	
Conv. Total (cfs)	51503.6	Conv. (cfs)		51503.6	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.36	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	2.63	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.37	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.68	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.08	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.15	Flow Area (sq ft)		408.21	
E.G. Slope (ft/ft)	0.005453	Area (sq ft)		417.48	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	61.31	Top Width (ft)		61.31	
Vel Total (ft/s)	10.16	Avg. Vel. (ft/s)		10.16	
Max Chl Dpth (ft)	10.08	Hydr. Depth (ft)		7.56	
Conv. Total (cfs)	56170.0	Conv. (cfs)		56170.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.43	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	2.67	0.01
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.37	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for

additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.40	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.82	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.58	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.20	Flow Area (sq ft)		489.14	
E.G. Slope (ft/ft)	0.004854	Area (sq ft)		513.17	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	66.39	Top Width (ft)		66.39	
Vel Total (ft/s)	10.81	Avg. Vel. (ft/s)		10.81	
Max Chl Dpth (ft)	11.58	Hydr. Depth (ft)		9.06	
Conv. Total (cfs)	75931.7	Conv. (cfs)		75931.7	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.59	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	2.84	0.01
C & E Loss (ft)	0.24	Cum SA (acres)	0.00	0.37	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.28	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.15	Wt. n-Val.		0.040	
W.S. Elev (ft)	10.13	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	6.86	Flow Area (sq ft)		627.13	
E.G. Slope (ft/ft)	0.004126	Area (sq ft)	2.95	689.92	1.29
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	75.49	Top Width (ft)	3.22	70.00	2.27
Vel Total (ft/s)	11.77	Avg. Vel. (ft/s)		11.77	
Max Chl Dpth (ft)	14.13	Hydr. Depth (ft)		11.61	
Conv. Total (cfs)	114894.4	Conv. (cfs)		114894.4	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.82	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.03	3.26	0.01
C & E Loss (ft)	0.27	Cum SA (acres)	0.01	0.37	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for

additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 98.5

INPUT
Description: Maine Ave.
Distance from Upstream XS = 22
Deck/Roadway Width = 38
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
1	15	-10	18.5	15	-10
67	15	10	67	15	-10
18.5	15	10	100	15	-10

Upstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left Right Coeff Contr. Expan.
10 80 .3 .5
Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	16	15	F
70	90	15	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
1	15	-10	18.5	15	-10
67	15	10	67	15	-10
18.5	15	10	100	15	-10

Downstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12.7	14	15.7	-1	18.5	-2	24.4	-4	32.7	-5

```
    42.7      -5    52.7    -3.5    62.7       1    72.7     5.5    74.7      15

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
    12.7    .065    15.7     .04    72.7    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
          15.7    72.7             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
    12.7      16      15        F
      70    74.7      15        F

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =      .1 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Bridge Coefficient Sets =  1

Low Flow Methods and Data
       Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
       Energy Only

Additional Bridge Parameters
       Add Friction component to Momentum
       Do not add Weight component to Momentum
       Class B flow critical depth computations use critical depth
           inside the bridge at the upstream end
       Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT  Profile #Q100

  E.G. US. (ft)                 10.28    Element                Inside BR US  Inside BR DS
  W.S. US. (ft)                  8.36    E.G. Elev (ft)                9.90          9.38
  Q Total (cfs)               5910.00    W.S. Elev (ft)                7.15          7.23
  Q Bridge (cfs)              5910.00    Crit W.S. (ft)                5.73          4.60
  Q Weir (cfs)                           Max Chl Dpth (ft)            11.15         12.23
  Weir Sta Lft (ft)                      Vel Total (ft/s)             13.33         11.76
  Weir Sta Rgt (ft)                      Flow Area (sq ft)           443.49        502.43
  Weir Submerg                           Froude # Chl                  0.70          0.59
  Weir Max Depth (ft)                    Specif Force (cu ft)       4567.03       4877.91
```

Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	9.14	10.36
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.11	Conv. Total (cfs)	69653.8	86471.9
Delta WS (ft)	1.06	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.22	0.08
BR Open Vel (ft/s)	13.33	C & E Loss (ft)	0.30	0.14
Coef of Q		Shear Total (lb/sq ft)	3.91	2.91
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

E.G. US. (ft)	4.22	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	3.90	E.G. Elev (ft)	4.18	4.08
Q Total (cfs)	1312.00	W.S. Elev (ft)	3.84	3.85
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.51	-0.78
Q Weir (cfs)		Max Chl Dpth (ft)	7.84	8.85
Weir Sta Lft (ft)		Vel Total (ft/s)	4.63	3.88
Weir Sta Rgt (ft)		Flow Area (sq ft)	283.19	338.24
Weir Submerg		Froude # Chl	0.29	0.23
Weir Max Depth (ft)		Specif Force (cu ft)	1109.03	1454.01
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	5.84	6.97
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	0.16	Conv. Total (cfs)	32981.4	44715.3
Delta WS (ft)	0.06	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.04	0.01
BR Open Vel (ft/s)	4.63	C & E Loss (ft)	0.05	0.01
Coef of Q		Shear Total (lb/sq ft)	0.55	0.36
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	7.23	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	5.70	E.G. Elev (ft)	6.89	6.35
Q Total (cfs)	3850.00	W.S. Elev (ft)	4.72	4.79

Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.81	2.66
Q Weir (cfs)		Max Chl Dpth (ft)	8.72	9.79
Weir Sta Lft (ft)		Vel Total (ft/s)	11.81	10.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	326.01	383.70
Weir Submerg		Froude # Chl	0.70	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	2601.18	2834.02
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	6.72	7.91
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.03	Conv. Total (cfs)	41705.0	55174.7
Delta WS (ft)	0.92	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.24	0.08
BR Open Vel (ft/s)	11.81	C & E Loss (ft)	0.30	0.07
Coef of Q		Shear Total (lb/sq ft)	3.40	2.31
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	7.68	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	6.08	E.G. Elev (ft)	7.32	6.76
Q Total (cfs)	4148.00	W.S. Elev (ft)	5.01	5.07
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.10	2.98
Q Weir (cfs)		Max Chl Dpth (ft)	9.01	10.07
Weir Sta Lft (ft)		Vel Total (ft/s)	12.21	10.43
Weir Sta Rgt (ft)		Flow Area (sq ft)	339.62	397.64
Weir Submerg		Froude # Chl	0.72	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	2855.95	3090.37
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	7.00	8.20
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.09	Conv. Total (cfs)	44647.6	58554.6
Delta WS (ft)	1.01	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.25	0.08
BR Open Vel (ft/s)	12.21	C & E Loss (ft)	0.31	0.08
Coef of Q		Shear Total (lb/sq ft)	3.59	2.47
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

			Inside BR US	Inside BR DS
E.G. US. (ft)	9.40	Element		
W.S. US. (ft)	7.58	E.G. Elev (ft)	9.02	8.49
Q Total (cfs)	5290.00	W.S. Elev (ft)	6.41	6.49
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.17	4.05
Q Weir (cfs)		Max Chl Dpth (ft)	10.41	11.49
Weir Sta Lft (ft)		Vel Total (ft/s)	12.97	11.34
Weir Sta Rgt (ft)		Flow Area (sq ft)	407.87	466.55
Weir Submerg		Froude # Chl	0.71	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	3939.28	4223.26
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	8.41	9.62
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.10	Conv. Total (cfs)	60582.1	76425.5
Delta WS (ft)	1.04	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.23	0.08
BR Open Vel (ft/s)	12.97	C & E Loss (ft)	0.31	0.12
Coef of Q		Shear Total (lb/sq ft)	3.81	2.77
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

			Inside BR US	Inside BR DS
E.G. US. (ft)	12.28	Element		
W.S. US. (ft)	10.13	E.G. Elev (ft)	11.90	11.40
Q Total (cfs)	7380.00	W.S. Elev (ft)	8.83	8.93
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	6.97	5.83
Q Weir (cfs)		Max Chl Dpth (ft)	12.83	13.93
Weir Sta Lft (ft)		Vel Total (ft/s)	14.05	12.62
Weir Sta Rgt (ft)		Flow Area (sq ft)	525.34	584.73
Weir Submerg		Froude # Chl	0.69	0.60
Weir Max Depth (ft)		Specif Force (cu ft)	6158.37	6534.04
Min El Weir Flow (ft)	15.01	Hydr Depth (ft)	10.83	12.06
Min El Prs (ft)	10.00	W.P. Total (ft)	51.01	50.38
Delta EG (ft)	1.13	Conv. Total (cfs)	92371.1	111345.7
Delta WS (ft)	1.09	Top Width (ft)	48.50	48.50
BR Open Area (sq ft)	581.85	Frctn Loss (ft)	0.20	0.07
BR Open Vel (ft/s)	14.05	C & E Loss (ft)	0.30	0.18

Coef of Q		Shear Total (lb/sq ft)	4.10	3.18
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	12.70

Note: Momentum answer is not valid if the water surface is above the low chord or if there is weir flow. The momentum answer has been disregarded.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 60

INPUT
Description: 3
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12.7	14	15.7	-1	18.5	-2	24.4	-4	32.7	-5
42.7	-5	52.7	-3.5	62.7	1	72.7	5.5	74.7	15

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12.7	.065	15.7	.04	72.7	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15.7	72.7	22	22	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
12.7	16	15	F
70	74.7	15	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	9.17	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.30	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.52	Flow Area (sq ft)		538.71	
E.G. Slope (ft/ft)	0.004296	Area (sq ft)	6.88	547.71	0.34
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	59.04	Top Width (ft)	1.66	57.00	0.38
Vel Total (ft/s)	10.97	Avg. Vel. (ft/s)		10.97	
Max Chl Dpth (ft)	12.30	Hydr. Depth (ft)		9.98	

Conv. Total (cfs)	90166.5	Conv. (cfs)		90166.5	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.57	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	2.00	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.28	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.06	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.22	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.84	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	-0.76	Flow Area (sq ft)		352.38	
E.G. Slope (ft/ft)	0.000849	Area (sq ft)	2.35	353.85	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	54.29	Top Width (ft)	0.97	53.32	
Vel Total (ft/s)	3.72	Avg. Vel. (ft/s)		3.72	
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		6.65	
Conv. Total (cfs)	45020.1	Conv. (cfs)		45020.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		55.25	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		0.34	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.01	1.98	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	6.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.42	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.77	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.53	Flow Area (sq ft)		402.48	
E.G. Slope (ft/ft)	0.004818	Area (sq ft)	3.33	404.49	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	56.54	Top Width (ft)	1.15	55.39	
Vel Total (ft/s)	9.57	Avg. Vel. (ft/s)		9.57	
Max Chl Dpth (ft)	9.77	Hydr. Depth (ft)		7.45	
Conv. Total (cfs)	55466.1	Conv. (cfs)		55466.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.15	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00

Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	1.99	0.01
C & E Loss (ft)	0.13	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.60	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.07	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.84	Flow Area (sq ft)		418.46	
E.G. Slope (ft/ft)	0.004912	Area (sq ft)	3.69	420.99	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	57.26	Top Width (ft)	1.21	56.05	
Vel Total (ft/s)	9.91	Avg. Vel. (ft/s)		9.91	
Max Chl Dpth (ft)	10.07	Hydr. Depth (ft)		7.75	
Conv. Total (cfs)	59186.1	Conv. (cfs)		59186.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.28	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	1.99	0.01
C & E Loss (ft)	0.14	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.29	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.76	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.54	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.97	Flow Area (sq ft)		497.57	
E.G. Slope (ft/ft)	0.004485	Area (sq ft)	5.68	504.29	0.11
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	58.73	Top Width (ft)	1.51	57.00	0.22
Vel Total (ft/s)	10.63	Avg. Vel. (ft/s)		10.63	
Max Chl Dpth (ft)	11.54	Hydr. Depth (ft)		9.21	
Conv. Total (cfs)	78986.1	Conv. (cfs)		78986.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.47	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.01	2.03	0.01
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.15	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.11	Wt. n-Val.		0.040	
W.S. Elev (ft)	9.04	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.66	Flow Area (sq ft)		632.87	
E.G. Slope (ft/ft)	0.003916	Area (sq ft)	10.08	647.10	1.32
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	59.75	Top Width (ft)	2.01	57.00	0.75
Vel Total (ft/s)	11.66	Avg. Vel. (ft/s)		11.66	
Max Chl Dpth (ft)	14.04	Hydr. Depth (ft)		11.72	
Conv. Total (cfs)	117936.0	Conv. (cfs)		117936.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		56.33	
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.75	
Alpha	1.00	Stream Power (lb/ft s)	74.70	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.02	2.22	0.01
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.28	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 38

INPUT
Description: 2
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	13	5	-2	15	-4	20	-4.2	30	-4.5
40	-4	50	1	60	4	62	15		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	5	.04	60	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
5	60	38	38	38	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	9.00	Element	Left OB	Channel	Right OB

Vel Head (ft)	2.08	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.92	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	13.25	506.88	0.77
E.G. Slope (ft/ft)	0.005276	Area (sq ft)	13.25	506.88	0.77
Q Total (cfs)	5910.00	Flow (cfs)	27.66	5881.82	0.52
Top Width (ft)	58.50	Top Width (ft)	2.97	55.00	0.53
Vel Total (ft/s)	11.35	Avg. Vel. (ft/s)	2.09	11.60	0.68
Max Chl Dpth (ft)	11.42	Hydr. Depth (ft)	4.46	9.22	1.46
Conv. Total (cfs)	81362.3	Conv. (cfs)	380.8	80974.3	7.2
Length Wtd. (ft)	38.00	Wetted Per. (ft)	9.40	56.84	2.96
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.46	2.94	0.09
Alpha	1.04	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.31	Cum Volume (acre-ft)	0.01	1.73	0.01
C & E Loss (ft)	0.22	Cum SA (acres)	0.00	0.25	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.03	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.24	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.80	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	5.60	335.40	
E.G. Slope (ft/ft)	0.001017	Area (sq ft)	5.60	335.40	
Q Total (cfs)	1312.00	Flow (cfs)	3.85	1308.15	
Top Width (ft)	56.26	Top Width (ft)	1.93	54.32	
Vel Total (ft/s)	3.85	Avg. Vel. (ft/s)	0.69	3.90	
Max Chl Dpth (ft)	8.30	Hydr. Depth (ft)	2.90	6.17	
Conv. Total (cfs)	41147.3	Conv. (cfs)	120.8	41026.4	
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.11	56.13	
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.06	0.38	
Alpha	1.02	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	1.80	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.25	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.94	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.84	Wt. n-Val.	0.065	0.040	0.000
W.S. Elev (ft)	4.09	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	6.19	351.69	0.00
E.G. Slope (ft/ft)	0.007597	Area (sq ft)	6.19	351.69	0.00
Q Total (cfs)	3850.00	Flow (cfs)	12.03	3837.97	0.00

Top Width (ft)	57.05	Top Width (ft)	2.03	55.00	0.02
Vel Total (ft/s)	10.76	Avg. Vel. (ft/s)	1.94	10.91	0.08
Max Chl Dpth (ft)	8.59	Hydr. Depth (ft)	3.05	6.39	0.05
Conv. Total (cfs)	44170.9	Conv. (cfs)	138.1	44032.9	0.0
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.42	56.84	0.10
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.46	2.93	
Alpha	1.03	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	1.79	0.01
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	0.25	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.98	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.35	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	6.72	365.72	0.01
E.G. Slope (ft/ft)	0.007739	Area (sq ft)	6.72	365.72	0.01
Q Total (cfs)	4148.00	Flow (cfs)	13.55	4134.45	0.00
Top Width (ft)	57.18	Top Width (ft)	2.12	55.00	0.06
Vel Total (ft/s)	11.14	Avg. Vel. (ft/s)	2.02	11.30	0.20
Max Chl Dpth (ft)	8.85	Hydr. Depth (ft)	3.17	6.65	0.17
Conv. Total (cfs)	47153.1	Conv. (cfs)	154.0	46999.1	0.0
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.69	56.84	0.36
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.49	3.11	0.02
Alpha	1.03	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.34	Cum Volume (acre-ft)	0.01	1.80	0.01
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.07	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	10.86	460.56	0.39
E.G. Slope (ft/ft)	0.005824	Area (sq ft)	10.86	460.56	0.39
Q Total (cfs)	5290.00	Flow (cfs)	22.31	5267.47	0.22
Top Width (ft)	58.07	Top Width (ft)	2.69	55.00	0.38
Vel Total (ft/s)	11.21	Avg. Vel. (ft/s)	2.05	11.44	0.57
Max Chl Dpth (ft)	10.57	Hydr. Depth (ft)	4.04	8.37	1.04
Conv. Total (cfs)	69315.7	Conv. (cfs)	292.3	69020.6	2.9
Length Wtd. (ft)	38.00	Wetted Per. (ft)	8.51	56.84	2.11
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.46	2.95	0.07
Alpha	1.04	Stream Power (lb/ft s)	62.00	0.00	0.00

Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.01	1.79	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.02	Element			
Vel Head (ft)	2.23	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	8.79	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	19.41	610.11	2.09
E.G. Slope (ft/ft)	0.004425	Area (sq ft)	19.41	610.11	2.09
Q Total (cfs)	7380.00	Flow (cfs)	42.16	7336.04	1.81
Top Width (ft)	59.47	Top Width (ft)	3.60	55.00	0.87
Vel Total (ft/s)	11.68	Avg. Vel. (ft/s)	2.17	12.02	0.86
Max Chl Dpth (ft)	13.29	Hydr. Depth (ft)	5.40	11.09	2.40
Conv. Total (cfs)	110944.6	Conv. (cfs)	633.8	110283.7	27.1
Length Wtd. (ft)	38.00	Wetted Per. (ft)	11.38	56.84	4.87
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.47	2.97	0.12
Alpha	1.05	Stream Power (lb/ft s)	62.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.02	1.91	0.01
C & E Loss (ft)	0.26	Cum SA (acres)	0.00	0.25	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 0

INPUT
Description: 1 (Downstream)
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	19	1	19	10	2	20	-6.3	30	-6.3
40	-5	50	-2.5	52	1.8	60	19		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val

0	.065	10	.04	52	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	52	21	21	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	8.48	Element			
Vel Head (ft)	4.24	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.24	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.24	Flow Area (sq ft)	1.33	357.35	1.39
E.G. Slope (ft/ft)	0.013662	Area (sq ft)	1.33	357.35	1.39
Q Total (cfs)	5910.00	Flow (cfs)	2.31	5905.31	2.38
Top Width (ft)	44.32	Top Width (ft)	1.19	42.00	1.14
Vel Total (ft/s)	16.41	Avg. Vel. (ft/s)	1.74	16.53	1.72
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	1.12	8.51	1.22
Conv. Total (cfs)	50562.8	Conv. (cfs)	19.8	50522.7	20.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	2.54	48.13	2.69
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.45	6.33	0.44
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.28	Cum Volume (acre-ft)	0.00	1.35	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	4.00	Element			
Vel Head (ft)	0.23	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.76	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)		Flow Area (sq ft)	0.82	337.25	0.90
E.G. Slope (ft/ft)	0.000817	Area (sq ft)	0.82	337.25	0.90
Q Total (cfs)	1312.00	Flow (cfs)	0.30	1311.38	0.33
Top Width (ft)	43.85	Top Width (ft)	0.93	42.00	0.91
Vel Total (ft/s)	3.87	Avg. Vel. (ft/s)	0.36	3.89	0.36
Max Chl Dpth (ft)	10.06	Hydr. Depth (ft)	0.88	8.03	0.98
Conv. Total (cfs)	45896.4	Conv. (cfs)	10.4	45874.6	11.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.99	48.13	2.16
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.02	0.36	0.02
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.01	Cum Volume (acre-ft)	0.01	1.51	0.01

C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.21	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.59	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.26	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.33	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)		Flow Area (sq ft)	0.47	318.92	0.54
E.G. Slope (ft/ft)	0.008481	Area (sq ft)	0.47	318.92	0.54
Q Total (cfs)	3850.00	Flow (cfs)	0.45	3849.01	0.54
Top Width (ft)	43.41	Top Width (ft)	0.70	42.00	0.71
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	0.97	12.07	0.99
Max Chl Dpth (ft)	9.63	Hydr. Depth (ft)	0.66	7.59	0.76
Conv. Total (cfs)	41806.1	Conv. (cfs)	4.9	41795.4	5.8
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.50	48.13	1.68
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.16	3.51	0.17
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	1.50	0.01
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.21	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.72	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.19	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.45	Flow Area (sq ft)	0.37	313.07	0.45
E.G. Slope (ft/ft)	0.010472	Area (sq ft)	0.37	313.07	0.45
Q Total (cfs)	4148.00	Flow (cfs)	0.37	4147.17	0.46
Top Width (ft)	43.27	Top Width (ft)	0.63	42.00	0.65
Vel Total (ft/s)	13.21	Avg. Vel. (ft/s)	1.00	13.25	1.03
Max Chl Dpth (ft)	9.49	Hydr. Depth (ft)	0.59	7.45	0.69
Conv. Total (cfs)	40534.4	Conv. (cfs)	3.6	40526.3	4.5
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.34	48.13	1.53
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.18	4.25	0.19
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.01	1.50	0.01
C & E Loss (ft)	0.26	Cum SA (acres)	0.00	0.21	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.96	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.62	Flow Area (sq ft)	0.69	331.05	0.77
E.G. Slope (ft/ft)	0.014135	Area (sq ft)	0.69	331.05	0.77
Q Total (cfs)	5290.00	Flow (cfs)	0.98	5287.92	1.10
Top Width (ft)	43.70	Top Width (ft)	0.86	42.00	0.84
Vel Total (ft/s)	15.91	Avg. Vel. (ft/s)	1.42	15.97	1.43
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.81	7.88	0.91
Conv. Total (cfs)	44494.8	Conv. (cfs)	8.3	44477.3	9.2
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.83	48.13	2.00
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.33	6.07	0.34
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.00	1.45	0.01
C & E Loss (ft)	0.24	Cum SA (acres)	0.00	0.21	0.01

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	10.49	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.62	Flow Area (sq ft)	3.47	415.35	3.40
E.G. Slope (ft/ft)	0.012870	Area (sq ft)	3.47	415.35	3.40
Q Total (cfs)	7380.00	Flow (cfs)	8.07	7364.30	7.63
Top Width (ft)	45.70	Top Width (ft)	1.92	42.00	1.78
Vel Total (ft/s)	17.48	Avg. Vel. (ft/s)	2.32	17.73	2.25
Max Chl Dpth (ft)	11.92	Hydr. Depth (ft)	1.81	9.89	1.91
Conv. Total (cfs)	65054.0	Conv. (cfs)	71.1	64915.6	67.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	4.10	48.13	4.22
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.68	6.93	0.65
Alpha	1.03	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.46	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.

This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -21

INPUT
Description: RR
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	15	8	-3	25	-7	30	-7	37	-6
50	-2	59	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	59	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	59	33	33	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.91	Element			
Vel Head (ft)	6.09	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.82	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	3.29	Flow Area (sq ft)	5.17	297.09	
E.G. Slope (ft/ft)	0.024570	Area (sq ft)	5.17	297.09	
Q Total (cfs)	5910.00	Flow (cfs)	18.28	5891.73	
Top Width (ft)	45.71	Top Width (ft)	2.14	43.56	
Vel Total (ft/s)	19.55	Avg. Vel. (ft/s)	3.53	19.83	
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)	2.41	6.82	
Conv. Total (cfs)	37703.4	Conv. (cfs)	116.6	37586.8	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	5.28	47.27	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.50	9.64	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.00	1.20	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.97	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.18	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.79	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	10.24	383.45	
E.G. Slope (ft/ft)	0.000546	Area (sq ft)	10.24	383.45	
Q Total (cfs)	1312.00	Flow (cfs)	6.78	1305.22	
Top Width (ft)	47.38	Top Width (ft)	3.02	44.37	
Vel Total (ft/s)	3.33	Avg. Vel. (ft/s)	0.66	3.40	
Max Chl Dpth (ft)	10.79	Hydr. Depth (ft)	3.39	8.64	
Conv. Total (cfs)	56140.0	Conv. (cfs)	289.9	55850.1	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.43	49.39	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.05	0.26	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.19	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.66	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	9.87	377.98	
E.G. Slope (ft/ft)	0.004917	Area (sq ft)	9.87	377.98	
Q Total (cfs)	3850.00	Flow (cfs)	19.36	3830.64	
Top Width (ft)	47.28	Top Width (ft)	2.96	44.32	
Vel Total (ft/s)	9.93	Avg. Vel. (ft/s)	1.96	10.13	
Max Chl Dpth (ft)	10.66	Hydr. Depth (ft)	3.33	8.53	
Conv. Total (cfs)	54902.8	Conv. (cfs)	276.1	54626.7	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.29	49.26	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.42	2.36	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.16	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.49	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.86	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.63	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	9.78	376.59	
E.G. Slope (ft/ft)	0.005774	Area (sq ft)	9.78	376.59	
Q Total (cfs)	4148.00	Flow (cfs)	20.72	4127.28	

Top Width (ft)	47.25	Top Width (ft)	2.95	44.30	
Vel Total (ft/s)	10.74	Avg. Vel. (ft/s)	2.12	10.96	
Max Chl Dpth (ft)	10.63	Hydr. Depth (ft)	3.32	8.50	
Conv. Total (cfs)	54589.5	Conv. (cfs)	272.6	54316.9	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.26	49.22	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.49	2.76	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	5.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.32	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	2.71	Flow Area (sq ft)	4.15	275.33	
E.G. Slope (ft/ft)	0.025006	Area (sq ft)	4.15	275.33	
Q Total (cfs)	5290.00	Flow (cfs)	13.76	5276.24	
Top Width (ft)	45.28	Top Width (ft)	1.92	43.36	
Vel Total (ft/s)	18.93	Avg. Vel. (ft/s)	3.31	19.16	
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.35	
Conv. Total (cfs)	33452.7	Conv. (cfs)	87.0	33365.6	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	4.73	46.73	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.37	9.20	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.00	1.30	0.01
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	9.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.98	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.94	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	4.65	Flow Area (sq ft)	7.84	346.01	
E.G. Slope (ft/ft)	0.023784	Area (sq ft)	7.84	346.01	
Q Total (cfs)	7380.00	Flow (cfs)	31.34	7348.67	
Top Width (ft)	46.66	Top Width (ft)	2.64	44.02	
Vel Total (ft/s)	20.86	Avg. Vel. (ft/s)	4.00	21.24	
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	2.97	7.86	
Conv. Total (cfs)	47853.6	Conv. (cfs)	203.2	47650.5	

Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.50	48.48	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.79	10.60	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.00	1.28	0.01
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -54

INPUT
Description: K2
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	21	5	40	-7	50	-7
60	-6	72	-2	80	0	88	2	96	4

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	88	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	88	34	34	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.85	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	3.09	Flow Area (sq ft)		333.87	
E.G. Slope (ft/ft)	0.025698	Area (sq ft)		333.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	61.41	Top Width (ft)		61.41	
Vel Total (ft/s)	17.70	Avg. Vel. (ft/s)		17.70	
Max Chl Dpth (ft)	8.85	Hydr. Depth (ft)		5.44	
Conv. Total (cfs)	36867.0	Conv. (cfs)		36867.0	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		65.15	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		8.22	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.83	Cum Volume (acre-ft)		0.96	0.01
C & E Loss (ft)	0.37	Cum SA (acres)		0.15	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.13	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.81	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		458.26	6.54
E.G. Slope (ft/ft)	0.000478	Area (sq ft)		458.26	6.54
Q Total (cfs)	1312.00	Flow (cfs)		1309.01	2.99
Top Width (ft)	72.34	Top Width (ft)		65.11	7.23
Vel Total (ft/s)	2.82	Avg. Vel. (ft/s)		2.86	0.46
Max Chl Dpth (ft)	10.81	Hydr. Depth (ft)		7.04	0.90
Conv. Total (cfs)	60036.6	Conv. (cfs)		59899.7	136.9
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.43	7.45
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		0.20	0.03
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)		1.02	0.01
C & E Loss (ft)	0.00	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.95	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.06	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.88	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		463.24	7.10
E.G. Slope (ft/ft)	0.003976	Area (sq ft)		463.24	7.10
Q Total (cfs)	3850.00	Flow (cfs)		3840.36	9.64
Top Width (ft)	72.77	Top Width (ft)		65.23	7.54
Vel Total (ft/s)	8.19	Avg. Vel. (ft/s)		8.29	1.36
Max Chl Dpth (ft)	10.88	Hydr. Depth (ft)		7.10	0.94
Conv. Total (cfs)	61057.1	Conv. (cfs)		60904.1	152.9
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.57	7.77
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.65	0.23
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.23	Wt. n-Val.		0.040	0.065

W.S. Elev (ft)	3.90	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		464.36	7.23
E.G. Slope (ft/ft)	0.004581	Area (sq ft)		464.36	7.23
Q Total (cfs)	4148.00	Flow (cfs)		4137.40	10.60
Top Width (ft)	72.87	Top Width (ft)		65.26	7.61
Vel Total (ft/s)	8.80	Avg. Vel. (ft/s)		8.91	1.47
Max Chl Dpth (ft)	10.90	Hydr. Depth (ft)		7.12	0.95
Conv. Total (cfs)	61288.0	Conv. (cfs)		61131.3	156.7
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.61	7.84
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.91	0.26
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	4.05	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	2.59	Flow Area (sq ft)		473.77	8.36
E.G. Slope (ft/ft)	0.006997	Area (sq ft)		473.77	8.36
Q Total (cfs)	5290.00	Flow (cfs)		5273.91	16.09
Top Width (ft)	73.49	Top Width (ft)		65.49	8.00
Vel Total (ft/s)	10.97	Avg. Vel. (ft/s)		11.13	1.92
Max Chl Dpth (ft)	11.05	Hydr. Depth (ft)		7.23	1.05
Conv. Total (cfs)	63239.1	Conv. (cfs)		63046.8	192.3
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.88	8.29
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.96	0.44
Alpha	1.03	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)		1.02	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	8.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.75	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.18	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		354.06	0.06
E.G. Slope (ft/ft)	0.033780	Area (sq ft)		354.06	0.06
Q Total (cfs)	7380.00	Flow (cfs)		7379.95	0.05
Top Width (ft)	63.23	Top Width (ft)		62.53	0.70
Vel Total (ft/s)	20.84	Avg. Vel. (ft/s)		20.84	0.81
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.66	0.09

Conv. Total (cfs)	40153.7	Conv. (cfs)		40153.5	0.3
Length Wtd. (ft)		Wetted Per. (ft)		66.37	0.72
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		11.25	0.18
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.07	Cum SA (acres)		0.15	0.00

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -88

INPUT
Description: K1
Station Elevation Data num= 8

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	56	-6	72	-6	80	-5
94	0	108	5	122	5				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	108	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	108	55	55	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.18	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.67	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	3.18	Flow Area (sq ft)		465.10	
E.G. Slope (ft/ft)	0.010956	Area (sq ft)		465.10	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	75.49	Top Width (ft)		75.49	
Vel Total (ft/s)	12.71	Avg. Vel. (ft/s)		12.71	
Max Chl Dpth (ft)	9.67	Hydr. Depth (ft)		6.16	
Conv. Total (cfs)	56462.2	Conv. (cfs)		56462.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		78.73	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.04	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.42	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.23	Cum SA (acres)		0.09	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for

additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.12	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.80	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		474.41	
E.G. Slope (ft/ft)	0.000512	Area (sq ft)		474.41	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	76.18	Top Width (ft)		76.18	
Vel Total (ft/s)	2.77	Avg. Vel. (ft/s)		2.77	
Max Chl Dpth (ft)	9.80	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	58000.7	Conv. (cfs)		58000.7	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.46	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		0.19	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.76	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		471.93	
E.G. Slope (ft/ft)	0.004469	Area (sq ft)		471.93	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.00	Top Width (ft)		76.00	
Vel Total (ft/s)	8.16	Avg. Vel. (ft/s)		8.16	
Max Chl Dpth (ft)	9.76	Hydr. Depth (ft)		6.21	
Conv. Total (cfs)	57589.3	Conv. (cfs)		57589.3	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.26	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		1.66	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.09	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.20	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.76	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		471.36	
E.G. Slope (ft/ft)	0.005205	Area (sq ft)		471.36	

Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	75.96	Top Width (ft)		75.96	
Vel Total (ft/s)	8.80	Avg. Vel. (ft/s)		8.80	
Max Chl Dpth (ft)	9.76	Hydr. Depth (ft)		6.21	
Conv. Total (cfs)	57495.0	Conv. (cfs)		57495.0	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.22	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		1.93	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.11	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.98	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.71	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		468.09	
E.G. Slope (ft/ft)	0.008627	Area (sq ft)		468.09	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	75.72	Top Width (ft)		75.72	
Vel Total (ft/s)	11.30	Avg. Vel. (ft/s)		11.30	
Max Chl Dpth (ft)	9.71	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	56955.1	Conv. (cfs)		56955.1	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		78.96	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		3.19	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.18	Cum SA (acres)		0.09	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	7.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.25	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	4.25	Flow Area (sq ft)		509.28	
E.G. Slope (ft/ft)	0.013360	Area (sq ft)		509.28	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	78.71	Top Width (ft)		78.71	
Vel Total (ft/s)	14.49	Avg. Vel. (ft/s)		14.49	
Max Chl Dpth (ft)	10.25	Hydr. Depth (ft)		6.47	
Conv. Total (cfs)	63848.9	Conv. (cfs)		63848.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		82.14	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		5.17	

Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)		0.67	0.01
C & E Loss (ft)		Cum SA (acres)		0.10	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -143

INPUT
Description: K0
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11.3	10	52.7	-7	69	-7	77.8	-6
98.2	-1	100	-1						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11.3	.04	98.2	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11.3	98.2	0	0	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	5.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	1.75	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.005536	Area (sq ft)		557.63	8.64
Q Total (cfs)	5910.00	Flow (cfs)		5892.41	17.59
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	10.44	Avg. Vel. (ft/s)		10.57	2.04
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.58	0.45

Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.09	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	-2.96	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.000273	Area (sq ft)		557.63	8.64
Q Total (cfs)	1312.00	Flow (cfs)		1308.10	3.90
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	2.32	Avg. Vel. (ft/s)		2.35	0.45
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		0.13	0.02
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.73	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	0.08	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.002349	Area (sq ft)		557.63	8.64
Q Total (cfs)	3850.00	Flow (cfs)		3838.54	11.46
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	6.80	Avg. Vel. (ft/s)		6.88	1.33
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.10	0.19
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.65	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.85	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			

Crit W.S. (ft)	0.32	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.002727	Area (sq ft)		557.63	8.64
Q Total (cfs)	4148.00	Flow (cfs)		4135.66	12.34
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	7.33	Avg. Vel. (ft/s)		7.42	1.43
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.27	0.22
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	1.29	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.004435	Area (sq ft)		557.63	8.64
Q Total (cfs)	5290.00	Flow (cfs)		5274.26	15.74
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	9.34	Avg. Vel. (ft/s)		9.46	1.82
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.07	0.36
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	6.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.70	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	2.81	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.008632	Area (sq ft)		557.63	8.64
Q Total (cfs)	7380.00	Flow (cfs)		7358.04	21.96
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	13.03	Avg. Vel. (ft/s)		13.20	2.54
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		4.03	0.71
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00

Frctn Loss (ft) Cum Volume (acre-ft)
C & E Loss (ft) Cum SA (acres)

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

SUMMARY OF MANNING'S N VALUES

River:Cobosee Stream

Reach	River Sta.	n1	n2	n3
Reach 1	1700	.07	.04	.065
Reach 1	1635	.07	.045	.065
Reach 1	1555	.07	.042	.065
Reach 1	1455	.065	.045	.07
Reach 1	1335	.065	.045	.075
Reach 1	1185	.065	.045	.07
Reach 1	1060	.065	.04	.07
Reach 1	960	.07	.042	.05
Reach 1	935	.065	.042	.07
Reach 1	895	Bridge		
Reach 1	850	.065	.04	.065
Reach 1	830	.065	.04	.065
Reach 1	821	.065	.035	.065
Reach 1	820	.065	.035	.065
Reach 1	725	.065	.04	.065
Reach 1	575	.065	.04	.065
Reach 1	425	.065	.04	.065
Reach 1	335	.065	.04	.065
Reach 1	262	.065	.04	.065
Reach 1	187	.065	.04	.065
Reach 1	137	.065	.04	.065
Reach 1	98.5	Bridge		
Reach 1	60	.065	.04	.065
Reach 1	38	.065	.04	.065
Reach 1	0	.065	.04	.065
Reach 1	-21	.065	.04	.065
Reach 1	-54	.065	.04	.065
Reach 1	-88	.065	.04	.065
Reach 1	-143	.065	.04	.065

SUMMARY OF REACH LENGTHS

River: Cobosee Stream

Reach	River Sta.	Left	Channel	Right
Reach 1	1700	65	65	65
Reach 1	1635	80	80	80
Reach 1	1555	100	100	100
Reach 1	1455	120	120	120
Reach 1	1335	150	150	150
Reach 1	1185	125	125	125
Reach 1	1060	100	100	100
Reach 1	960	25	25	25
Reach 1	935	85	85	85
Reach 1	895	Bridge		
Reach 1	850	20	20	20
Reach 1	830	9	9	9
Reach 1	821	1	1	1
Reach 1	820	95	95	95
Reach 1	725	150	150	150
Reach 1	575	150	150	150
Reach 1	425	90	90	90
Reach 1	335	73	73	73
Reach 1	262	75	75	75
Reach 1	187	50	50	50
Reach 1	137	77	77	77
Reach 1	98.5	Bridge		
Reach 1	60	22	22	22
Reach 1	38	38	38	38
Reach 1	0	21	21	21
Reach 1	-21	33	33	33
Reach 1	-54	34	34	34
Reach 1	-88	55	55	55
Reach 1	-143	0	0	0

SUMMARY OF CONTRACTION AND EXPANSION COEFFICIENTS
River: Cobosee Stream

Reach	River Sta.	Contr.	Expan.
Reach 1	1700	.1	.3
Reach 1	1635	.1	.3
Reach 1	1555	.1	.3
Reach 1	1455	.1	.3

Reach 1	1335		.1	.3
Reach 1	1185		.1	.3
Reach 1	1060		.1	.3
Reach 1	960		.3	.5
Reach 1	935		.3	.5
Reach 1	895	Bridge		
Reach 1	850		.3	.5
Reach 1	830		.3	.5
Reach 1	821		.3	.5
Reach 1	820		.3	.5
Reach 1	725		.1	.3
Reach 1	575		.1	.3
Reach 1	425		.1	.3
Reach 1	335		.1	.3
Reach 1	262		.1	.3
Reach 1	187		.1	.3
Reach 1	137		.3	.5
Reach 1	98.5	Bridge		
Reach 1	60		.3	.5
Reach 1	38		.1	.3
Reach 1	0		.1	.3
Reach 1	-21		.1	.3
Reach 1	-54		.1	.3
Reach 1	-88		.1	.3
Reach 1	-143		.1	.3

Profile Output Table - Standard Table 1

Reach	River Sta	Profile	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
Reach 1	1700	Q100	5910.00	13.80	22.75	21.32	24.48	0.006899	10.56	559.56	84.99	0.73
Reach 1	1700	Q1.1	1312.00	13.80	18.54	17.33	19.04	0.004837	5.66	231.75	70.35	0.55
Reach 1	1700	Q10	3850.00	13.80	21.15	19.81	22.41	0.006488	8.99	428.08	79.67	0.68
Reach 1	1700	Q25	4148.00	13.80	21.40	20.05	22.73	0.006586	9.26	447.72	80.49	0.69
Reach 1	1700	Q50	5290.00	13.80	22.28	20.89	23.89	0.006865	10.17	519.99	83.43	0.72
Reach 1	1700	Q500	7380.00	13.80	23.79	22.27	25.79	0.006886	11.36	649.74	88.50	0.74

Reach 1	1635		Q100	5910.00	14.00	22.26		23.95	0.009286
10.45	565.74	91.56		0.74					
Reach 1	1635		Q1.1	1312.00	14.00	17.69		18.50	0.015059
7.21	181.92	75.56		0.82					
Reach 1	1635		Q10	3850.00	14.00	20.47		21.86	0.010706
9.45	407.41	86.07		0.77					
Reach 1	1635		Q25	4148.00	14.00	20.75		22.19	0.010420
9.61	431.49	86.93		0.76					
Reach 1	1635		Q50	5290.00	14.00	21.75		23.36	0.009593
10.17	520.12	90.01		0.75					
Reach 1	1635		Q500	7380.00	14.00	23.37		25.25	0.008749
11.03	669.19	94.97		0.73					
Reach 1	1555		Q100	5910.00	13.30	20.34	20.16	22.96	0.013988
12.99	455.10	80.13		0.96					
Reach 1	1555		Q1.1	1312.00	13.30	16.65		17.46	0.011277
7.21	181.93	67.33		0.77					
Reach 1	1555		Q10	3850.00	13.30	19.06	18.65	20.89	0.012591
10.84	355.06	76.34		0.89					
Reach 1	1555		Q25	4148.00	13.30	19.24	18.89	21.21	0.013022
11.25	368.78	76.87		0.90					
Reach 1	1555		Q50	5290.00	13.30	19.96	19.73	22.37	0.013832
12.46	424.40	78.99		0.95					
Reach 1	1555		Q500	7380.00	13.30	21.24	21.12	24.27	0.013932
13.96	528.58	82.81		0.97					
Reach 1	1455		Q100	5910.00	11.80	19.15	18.73	21.52	0.013387
12.37	481.88	84.97		0.89					
Reach 1	1455		Q1.1	1312.00	11.80	15.06	14.87	16.04	0.018077
7.92	165.73	68.77		0.90					
Reach 1	1455		Q10	3850.00	11.80	17.40	17.28	19.41	0.017110
11.38	338.91	78.76		0.96					
Reach 1	1455		Q25	4148.00	11.80	17.67	17.49	19.74	0.016462
11.55	360.01	79.70		0.95					
Reach 1	1455		Q50	5290.00	11.80	18.65	18.33	20.92	0.014390
12.10	439.82	83.19		0.91					
Reach 1	1455		Q500	7380.00	11.80	20.29		22.87	0.011588
12.93	580.92	89.01		0.86					
Reach 1	1335		Q100	5910.00	9.50	18.29		20.09	0.008451
10.77	549.55	80.41		0.72					
Reach 1	1335		Q1.1	1312.00	9.50	12.63	12.50	13.78	0.019322
8.58	152.88	58.82		0.94					

Reach 1	1335		Q10	3850.00	9.50	16.13		17.69	0.010520
10.02	384.19	72.81		0.77					
Reach 1	1335		Q25	4148.00	9.50	16.47		18.07	0.010117
10.13	409.60	74.07		0.76					
Reach 1	1335		Q50	5290.00	9.50	17.69		19.41	0.008914
10.54	502.02	78.36		0.73					
Reach 1	1335		Q500	7380.00	9.50	19.61		21.58	0.007511
11.27	659.01	85.25		0.70					
Reach 1	1185		Q100	5910.00	5.50	15.74	15.05	18.44	0.013066
13.18	448.42	64.17		0.88					
Reach 1	1185		Q1.1	1312.00	5.50	10.99		11.81	0.008702
7.27	180.57	47.96		0.66					
Reach 1	1185		Q10	3850.00	5.50	14.08	13.16	16.00	0.011509
11.11	346.47	58.78		0.81					
Reach 1	1185		Q25	4148.00	5.50	14.34	13.46	16.38	0.011809
11.46	361.81	59.62		0.82					
Reach 1	1185		Q50	5290.00	5.50	15.27	14.52	17.75	0.012741
12.65	418.21	62.62		0.86					
Reach 1	1185		Q500	7380.00	5.50	16.59	16.20	19.92	0.014396
14.65	504.00	66.73		0.93					
Reach 1	1060		Q100	5910.00	5.00	13.57	13.57	16.72	0.013789
14.24	415.00	66.76		1.01					
Reach 1	1060		Q1.1	1312.00	5.00	8.85	8.85	10.26	0.017292
9.54	137.48	49.24		1.01					
Reach 1	1060		Q10	3850.00	5.00	11.81	11.81	14.33	0.014662
12.72	302.66	61.04		1.01					
Reach 1	1060		Q25	4148.00	5.00	12.10	12.10	14.70	0.014382
12.94	320.59	62.01		1.00					
Reach 1	1060		Q50	5290.00	5.00	13.10	13.10	16.05	0.013832
13.77	384.11	65.31		1.00					
Reach 1	1060		Q500	7380.00	5.00	14.68	14.68	18.19	0.013247
15.03	490.87	70.19		1.00					
Reach 1	960		Q100	5910.00	3.50	12.54	11.33	14.82	0.008563
12.15	495.72	82.79		0.77					
Reach 1	960		Q1.1	1312.00	3.50	7.53	6.91	8.38	0.009985
7.38	177.88	56.90		0.74					
Reach 1	960		Q10	3850.00	3.50	10.76	9.68	12.41	0.008768
10.32	373.53	64.43		0.75					
Reach 1	960		Q25	4148.00	3.50	11.04	9.93	12.79	0.008725
10.62	391.64	65.09		0.75					
Reach 1	960		Q50	5290.00	3.50	12.04	10.87	14.14	0.008580
11.63	458.31	68.60		0.76					

Reach 1	960		Q500	7380.00	3.50	11.41	12.50	16.33	0.022762
17.82	415.83	65.95		1.22					
Reach 1	935		Q100	5910.00	2.00	13.04	10.34	14.06	0.003531
8.25	809.75	158.21		0.51					
Reach 1	935		Q1.1	1312.00	2.00	7.57	5.91	8.03	0.004399
5.45	240.67	66.41		0.50					
Reach 1	935		Q10	3850.00	2.00	11.00	8.78	11.87	0.004311
7.49	526.52	114.51		0.54					
Reach 1	935		Q25	4148.00	2.00	11.32	9.03	12.22	0.004193
7.65	563.83	123.44		0.54					
Reach 1	935		Q50	5290.00	2.00	12.46	9.93	13.45	0.003743
8.08	723.33	156.11		0.52					
Reach 1	935		Q500	7380.00	2.00	14.22	11.33	15.32	0.003277
8.71	987.87	168.60		0.51					
Reach 1	895		Bridge						
Reach 1	850		Q100	5910.00	1.00	11.56	9.38	12.72	0.004490
8.76	737.73	144.16		0.58					
Reach 1	850		Q1.1	1312.00	1.00	6.84	4.89	7.23	0.003327
5.04	260.32	69.12		0.46					
Reach 1	850		Q10	3850.00	1.00	9.48	7.75	10.53	0.005734
8.22	474.98	103.72		0.63					
Reach 1	850		Q25	4148.00	1.00	9.82	8.01	10.88	0.005610
8.31	511.23	113.81		0.62					
Reach 1	850		Q50	5290.00	1.00	10.94	8.91	12.08	0.004917
8.67	651.61	134.32		0.60					
Reach 1	850		Q500	7380.00	1.00	13.08	10.40	14.20	0.003513
8.72	962.68	157.76		0.52					
Reach 1	830		Q100	5910.00	1.00	11.54		12.57	0.003454
8.19	768.79	147.28		0.53					
Reach 1	830		Q1.1	1312.00	1.00	6.77		7.15	0.004146
4.95	265.30	87.98		0.50					
Reach 1	830		Q10	3850.00	1.00	9.47		10.34	0.004396
7.49	515.95	95.94		0.57					
Reach 1	830		Q25	4148.00	1.00	9.80		10.70	0.004219
7.60	548.17	96.67		0.56					
Reach 1	830		Q50	5290.00	1.00	10.92		11.93	0.003757
8.05	680.74	136.18		0.54					
Reach 1	830		Q500	7380.00	1.00	13.07		14.09	0.002737
8.26	1000.53	153.73		0.49					

Reach 1	821		Q100	5910.00	1.00	11.53		12.53	0.002866
8.05	768.40	157.69		0.54					
Reach 1	821		Q1.1	1312.00	1.00	6.69		7.11	0.003298
5.19	252.86	80.22		0.52					
Reach 1	821		Q10	3850.00	1.00	9.41		10.30	0.003918
7.58	507.88	103.13		0.60					
Reach 1	821		Q25	4148.00	1.00	9.77		10.67	0.003650
7.61	545.05	103.92		0.59					
Reach 1	821		Q50	5290.00	1.00	10.90		11.88	0.003150
7.95	677.07	134.94		0.56					
Reach 1	821		Q500	7380.00	1.00	13.07		14.04	0.002233
8.04	1014.09	161.42		0.49					
Reach 1	820		Q100	5910.00	1.00	11.59		12.46	0.002824
7.49	832.41	193.15		0.53					
Reach 1	820		Q1.1	1312.00	1.00	6.68		7.10	0.003313
5.20	252.46	80.17		0.52					
Reach 1	820		Q10	3850.00	1.00	9.40		10.29	0.004312
7.57	508.60	111.78		0.63					
Reach 1	820		Q25	4148.00	1.00	9.77		10.65	0.004247
7.52	551.27	120.92		0.62					
Reach 1	820		Q50	5290.00	1.00	10.95		11.83	0.003290
7.51	722.96	156.10		0.56					
Reach 1	820		Q500	7380.00	1.00	13.18		13.92	0.001862
7.09	1260.27	281.71		0.45					
Reach 1	725		Q100	5910.00	2.50	11.30		12.14	0.003724
7.36	832.82	188.19		0.53					
Reach 1	725		Q1.1	1312.00	2.50	6.09		6.62	0.007272
5.84	224.72	88.79		0.65					
Reach 1	725		Q10	3850.00	2.50	8.81		9.79	0.005966
7.94	484.97	103.25		0.65					
Reach 1	725		Q25	4148.00	2.50	9.18		10.15	0.005799
7.92	523.90	109.62		0.64					
Reach 1	725		Q50	5290.00	2.50	10.57		11.46	0.004654
7.54	707.44	157.21		0.58					
Reach 1	725		Q500	7380.00	2.50	13.00		13.72	0.002360
6.92	1208.76	247.45		0.44					
Reach 1	575		Q100	5910.00	1.50	11.08		11.67	0.001918
6.22	1026.90	220.83		0.40					
Reach 1	575		Q1.1	1312.00	1.50	4.94		5.46	0.008227
5.76	227.65	100.80		0.68					

Reach 1	575		Q10	3850.00	1.50	8.39	9.01	0.003444	
6.34	607.05	120.14	0.50						
Reach 1	575		Q25	4148.00	1.50	8.80	9.42	0.003153	
6.32	656.45	122.71	0.48						
Reach 1	575		Q50	5290.00	1.50	10.29	10.90	0.002253	
6.27	871.16	174.83	0.42						
Reach 1	575		Q500	7380.00	1.50	12.87	13.39	0.001335	
5.97	1486.21	269.19	0.34						
Reach 1	425		Q100	5910.00	0.00	10.82	11.41	0.001604	
6.22	1051.38	244.73	0.37						
Reach 1	425		Q1.1	1312.00	0.00	4.54	4.81	0.002227	
4.13	317.80	86.35	0.38						
Reach 1	425		Q10	3850.00	0.00	8.02	8.58	0.002266	
5.98	644.11	100.38	0.42						
Reach 1	425		Q25	4148.00	0.00	8.45	9.01	0.002174	
6.04	686.64	101.97	0.41						
Reach 1	425		Q50	5290.00	0.00	10.00	10.60	0.001827	
6.22	869.43	148.17	0.39						
Reach 1	425		Q500	7380.00	0.00	12.69	13.21	0.001159	
6.01	1534.62	265.24	0.32						
Reach 1	335		Q100	5910.00	-2.00	10.27	11.20	0.002411	
7.77	800.00	169.01	0.45						
Reach 1	335		Q1.1	1312.00	-2.00	4.34	4.62	0.001807	
4.30	305.17	65.83	0.35						
Reach 1	335		Q10	3850.00	-2.00	7.51	8.32	0.003095	
7.22	533.04	77.94	0.49						
Reach 1	335		Q25	4148.00	-2.00	7.92	8.76	0.003035	
7.33	565.55	79.51	0.48						
Reach 1	335		Q50	5290.00	-2.00	9.46	10.37	0.002648	
7.66	695.90	100.54	0.46						
Reach 1	335		Q500	7380.00	-2.00	12.22	13.05	0.001761	
7.54	1234.90	249.51	0.40						
Reach 1	262		Q100	5910.00	-3.00	9.39	10.90	0.004665	
9.86	599.15	73.18	0.61						
Reach 1	262		Q1.1	1312.00	-3.00	4.08	4.47	0.002305	
5.00	262.64	53.29	0.40						
Reach 1	262		Q10	3850.00	-3.00	6.57	7.96	0.005827	
9.46	406.88	62.76	0.65						
Reach 1	262		Q25	4148.00	-3.00	6.97	8.40	0.005706	
9.59	432.71	64.34	0.65						
Reach 1	262		Q50	5290.00	-3.00	8.55	10.05	0.005045	
9.81	539.04	70.12	0.62						

Reach 1	262		Q500	7380.00	-3.00	11.30		12.81	0.003559
9.88	801.85	143.31		0.55					
Reach 1	187		Q100	5910.00	-4.00	9.10		10.55	0.004309
9.68	610.37	71.09		0.58					
Reach 1	187		Q1.1	1312.00	-4.00	3.98		4.30	0.001669
4.50	291.39	53.79		0.34					
Reach 1	187		Q10	3850.00	-4.00	6.22		7.52	0.005145
9.17	419.83	61.28		0.62					
Reach 1	187		Q25	4148.00	-4.00	6.63		7.97	0.005070
9.32	445.22	62.66		0.62					
Reach 1	187		Q50	5290.00	-4.00	8.24		9.67	0.004578
9.61	550.65	68.10		0.60					
Reach 1	187		Q500	7380.00	-4.00	11.05		12.54	0.003405
9.80	770.83	96.82		0.53					
Reach 1	137		Q100	5910.00	-4.00	8.36	5.71	10.28	0.004602
11.13	531.20	69.03		0.63					
Reach 1	137		Q1.1	1312.00	-4.00	3.90	0.50	4.22	0.001610
4.50	291.23	53.92		0.34					
Reach 1	137		Q10	3850.00	-4.00	5.70	3.85	7.23	0.005588
9.94	387.51	60.01		0.65					
Reach 1	137		Q25	4148.00	-4.00	6.08	4.15	7.68	0.005453
10.16	408.21	61.31		0.65					
Reach 1	137		Q50	5290.00	-4.00	7.58	5.20	9.40	0.004854
10.81	489.14	66.39		0.63					
Reach 1	137		Q500	7380.00	-4.00	10.13	6.86	12.28	0.004126
11.77	627.13	75.49		0.61					
Reach 1	98.5			Bridge					
Reach 1	60		Q100	5910.00	-5.00	7.30	4.52	9.17	0.004296
10.97	538.71	59.04		0.61					
Reach 1	60		Q1.1	1312.00	-5.00	3.84	-0.76	4.06	0.000849
3.72	352.38	54.29		0.25					
Reach 1	60		Q10	3850.00	-5.00	4.77	2.53	6.20	0.004818
9.57	402.48	56.54		0.62					
Reach 1	60		Q25	4148.00	-5.00	5.07	2.84	6.60	0.004912
9.91	418.46	57.26		0.63					
Reach 1	60		Q50	5290.00	-5.00	6.54	3.97	8.29	0.004485
10.63	497.57	58.73		0.62					
Reach 1	60		Q500	7380.00	-5.00	9.04	5.66	11.15	0.003916
11.66	632.87	59.75		0.60					

Reach 1	38		Q100	5910.00	-4.50	6.92		9.00	0.005276
11.60	520.91	58.50		0.67					
Reach 1	38		Q1.1	1312.00	-4.50	3.80		4.03	0.001017
3.90	341.00	56.26		0.28					
Reach 1	38		Q10	3850.00	-4.50	4.09		5.94	0.007597
10.91	357.89	57.05		0.76					
Reach 1	38		Q25	4148.00	-4.50	4.35		6.33	0.007739
11.30	372.45	57.18		0.77					
Reach 1	38		Q50	5290.00	-4.50	6.07		8.10	0.005824
11.44	471.82	58.07		0.70					
Reach 1	38		Q500	7380.00	-4.50	8.79		11.02	0.004425
12.02	631.61	59.47		0.64					
Reach 1	0		Q100	5910.00	-6.30	4.24	4.24	8.48	0.013662
16.53	360.07	44.32		1.00					
Reach 1	0		Q1.1	1312.00	-6.30	3.76		4.00	0.000817
3.89	338.97	43.85		0.24					
Reach 1	0		Q10	3850.00	-6.30	3.33		5.59	0.008481
12.07	319.93	43.41		0.77					
Reach 1	0		Q25	4148.00	-6.30	3.19	2.45	5.91	0.010472
13.25	313.90	43.27		0.86					
Reach 1	0		Q50	5290.00	-6.30	3.62	3.62	7.58	0.014135
15.97	332.50	43.70		1.00					
Reach 1	0		Q500	7380.00	-6.30	5.62	5.62	10.49	0.012870
17.73	422.22	45.70		0.99					
Reach 1	-21		Q100	5910.00	-7.00	1.82	3.29	7.91	0.024570
19.83	302.26	45.71		1.34					
Reach 1	-21		Q1.1	1312.00	-7.00	3.79		3.97	0.000546
3.40	393.69	47.38		0.20					
Reach 1	-21		Q10	3850.00	-7.00	3.66		5.25	0.004917
10.13	387.85	47.28		0.61					
Reach 1	-21		Q25	4148.00	-7.00	3.63		5.49	0.005774
10.96	386.37	47.25		0.66					
Reach 1	-21		Q50	5290.00	-7.00	1.32	2.71	7.01	0.025006
19.16	279.48	45.28		1.34					
Reach 1	-21		Q500	7380.00	-7.00	2.94	4.65	9.92	0.023784
21.24	353.85	46.66		1.34					
Reach 1	-54		Q100	5910.00	-7.00	1.85	3.09	6.72	0.025698
17.70	333.87	61.41		1.34					
Reach 1	-54		Q1.1	1312.00	-7.00	3.81		3.93	0.000478
2.86	464.80	72.34		0.19					

Reach 1	-54	Q10	3850.00	-7.00	3.88		4.95	0.003976	
8.29	470.34	72.77	0.55						
Reach 1	-54	Q25	4148.00	-7.00	3.90		5.13	0.004581	
8.91	471.60	72.87	0.59						
Reach 1	-54	Q50	5290.00	-7.00	4.05	2.59	5.96	0.006997	
11.13	482.13	73.49	0.73						
Reach 1	-54	Q500	7380.00	-7.00	2.18	4.20	8.92	0.033780	
20.84	354.12	63.23	1.54						
Reach 1	-88	Q100	5910.00	-6.00	3.67	3.18	6.18	0.010956	
12.71	465.10	75.49	0.90						
Reach 1	-88	Q1.1	1312.00	-6.00	3.80		3.92	0.000512	
2.77	474.41	76.18	0.20						
Reach 1	-88	Q10	3850.00	-6.00	3.76		4.80	0.004469	
8.16	471.93	76.00	0.58						
Reach 1	-88	Q25	4148.00	-6.00	3.76		4.96	0.005205	
8.80	471.36	75.96	0.62						
Reach 1	-88	Q50	5290.00	-6.00	3.71		5.70	0.008627	
11.30	468.09	75.72	0.80						
Reach 1	-88	Q500	7380.00	-6.00	4.25	4.25	7.51	0.013360	
14.49	509.28	78.71	1.00						
Reach 1	-143	Q100	5910.00	-7.00	3.80	1.75	5.53	0.005536	
10.57	566.27	73.60	0.67						
Reach 1	-143	Q1.1	1312.00	-7.00	3.80	-2.96	3.89	0.000273	
2.35	566.27	73.60	0.15						
Reach 1	-143	Q10	3850.00	-7.00	3.80	0.08	4.53	0.002349	
6.88	566.27	73.60	0.44						
Reach 1	-143	Q25	4148.00	-7.00	3.80	0.32	4.65	0.002727	
7.42	566.27	73.60	0.47						
Reach 1	-143	Q50	5290.00	-7.00	3.80	1.29	5.19	0.004435	
9.46	566.27	73.60	0.60						
Reach 1	-143	Q500	7380.00	-7.00	3.80	2.81	6.50	0.008632	
13.20	566.27	73.60	0.83						

Profile Output Table - Six XS Bridge

Reach	River Sta	Profile	E.G. Elev	W.S. Elev	Crit W.S.	Frctn Loss	C & E Loss	Top Width	Q Left	Q Channel	Q Right	Vel Chnl
			(ft)	(ft)	(ft)	(ft)	(ft)	(ft)	(cfs)	(cfs)	(cfs)	(ft/s)


Reach 1	960		Q100	14.82	12.54	11.33	0.13	0.63	82.79
0.20	5891.34	18.46	12.15						
Reach 1	960		Q1.1	8.38	7.53	6.91	0.16	0.19	56.90
	1312.00		7.38						
Reach 1	960		Q10	12.41	10.76	9.68	0.15	0.39	64.43
0.01	3849.40	0.59	10.32						
Reach 1	960		Q25	12.79	11.04	9.93	0.15	0.42	65.09
0.02	4146.46	1.52	10.62						
Reach 1	960		Q50	14.14	12.04	10.87	0.14	0.55	68.60
0.11	5280.65	9.24	11.63						
Reach 1	960		Q500	16.33	11.41	12.50	1.71	0.14	65.95
0.06	7373.96	5.97	17.82						
Reach 1	935		Q100	14.06	13.04	10.34	0.10	0.29	158.21
12.49	5673.06	224.45	8.25						
Reach 1	935		Q1.1	8.03	7.57	5.91	0.10	0.09	66.41
	1312.00		5.45						
Reach 1	935		Q10	11.87	11.00	8.78	0.12	0.24	114.51
0.71	3837.48	11.81	7.49						
Reach 1	935		Q25	12.22	11.32	9.03	0.11	0.24	123.44
1.46	4122.46	24.08	7.65						
Reach 1	935		Q50	13.45	12.46	9.93	0.10	0.28	156.11
7.33	5154.48	128.19	8.08						
Reach 1	935		Q500	15.32	14.22	11.33	0.09	0.23	168.60
28.83	6873.98	477.18	8.71						
Reach 1	895	BR U	Q100	13.67	11.70	10.78	0.48	0.29	121.45
4.65	5851.97	53.38	11.34						
Reach 1	895	BR U	Q1.1	7.83	7.05	6.09	0.36	0.14	55.17
	1312.00		7.08						
Reach 1	895	BR U	Q10	11.52	9.85	9.19	0.59	0.19	77.17
	3850.00		10.37						
Reach 1	895	BR U	Q25	11.86	10.15	9.45	0.58	0.19	78.50
0.01	4147.99		10.49						
Reach 1	895	BR U	Q50	13.07	11.14	10.32	0.52	0.26	105.53
1.67	5272.37	15.96	11.15						
Reach 1	895	BR U	Q500	15.01	13.14	11.89	0.38	0.28	140.56
21.43	7059.92	298.66	11.21						
Reach 1	895	BR D	Q100	12.90	11.51	9.93	0.07	0.12	133.26
5.53	5712.93	191.53	9.62						
Reach 1	895	BR D	Q1.1	7.33	6.84	5.12	0.05	0.05	61.99
	1312.00		5.60						
Reach 1	895	BR D	Q10	10.74	9.44	8.13	0.08	0.13	95.70
	3842.41	7.59	9.15						

Reach 1	895	BR D	Q25	11.09	9.77	8.40	0.08	0.13	105.78
	4130.49	17.51	9.24						
Reach 1	895	BR D	Q50	12.28	10.88	9.40	0.07	0.13	126.95
1.40	5183.68	104.92	9.58						
Reach 1	895	BR D	Q500	14.35	13.04	10.88	0.05	0.10	145.07
32.16	6874.93	472.90	9.49						
Reach 1	850		Q100	12.72	11.56	9.38	0.08	0.07	144.16
4.86	5749.56	155.58	8.76						
Reach 1	850		Q1.1	7.23	6.84	4.89	0.07	0.01	69.12
	1312.00		5.04						
Reach 1	850		Q10	10.53	9.48	7.75	0.10	0.09	103.72
	3843.08	6.92	8.22						
Reach 1	850		Q25	10.88	9.82	8.01	0.10	0.09	113.81
	4132.33	15.67	8.31						
Reach 1	850		Q50	12.08	10.94	8.91	0.09	0.07	134.32
1.32	5199.07	89.61	8.67						
Reach 1	850		Q500	14.20	13.08	10.40	0.06	0.05	157.76
26.65	6944.32	409.03	8.72						
Reach 1	830		Q100	12.57	11.54		0.03	0.01	147.28
2.70	5835.78	71.52	8.19						
Reach 1	830		Q1.1	7.15	6.77		0.03	0.01	87.98
	1312.00		4.95						
Reach 1	830		Q10	10.34	9.47		0.04	0.01	95.94
	3847.49	2.51	7.49						
Reach 1	830		Q25	10.70	9.80		0.04	0.00	96.67
	4145.14	2.86	7.60						
Reach 1	830		Q50	11.93	10.92		0.03	0.01	136.18
0.71	5262.19	27.10	8.05						
Reach 1	830		Q500	14.09	13.07		0.02	0.02	153.73
15.12	7098.19	266.69	8.26						
Reach 1	187		Q100	10.55	9.10		0.22	0.05	71.09
	5910.00		9.68						
Reach 1	187		Q1.1	4.30	3.98		0.08	0.00	53.79
	1312.00		4.50						
Reach 1	187		Q10	7.52	6.22		0.27	0.02	61.28
	3850.00		9.17						
Reach 1	187		Q25	7.97	6.63		0.26	0.03	62.66
	4148.00		9.32						
Reach 1	187		Q50	9.67	8.24		0.24	0.04	68.10
	5290.00		9.61						


Reach 1	187		Q500	12.54	11.05		0.19	0.07	96.82
3.27	7357.75	18.98	9.80						
Reach 1	137		Q100	10.28	8.36	5.71	0.13	0.25	69.03
	5910.00		11.13						
Reach 1	137		Q1.1	4.22	3.90	0.50	0.04	0.01	53.92
	1312.00		4.50						
Reach 1	137		Q10	7.23	5.70	3.85	0.15	0.19	60.01
	3850.00		9.94						
Reach 1	137		Q25	7.68	6.08	4.15	0.15	0.21	61.31
	4148.00		10.16						
Reach 1	137		Q50	9.40	7.58	5.20	0.13	0.24	66.39
	5290.00		10.81						
Reach 1	137		Q500	12.28	10.13	6.86	0.11	0.27	75.49
	7380.00		11.77						
Reach 1	98.5	BR U	Q100	9.90	7.15	5.73	0.22	0.30	48.50
	5910.00		13.33						
Reach 1	98.5	BR U	Q1.1	4.18	3.84	0.51	0.04	0.05	48.50
	1312.00		4.63						
Reach 1	98.5	BR U	Q10	6.89	4.72	3.81	0.24	0.30	48.50
	3850.00		11.81						
Reach 1	98.5	BR U	Q25	7.32	5.01	4.10	0.25	0.31	48.50
	4148.00		12.21						
Reach 1	98.5	BR U	Q50	9.02	6.41	5.17	0.23	0.31	48.50
	5290.00		12.97						
Reach 1	98.5	BR U	Q500	11.90	8.83	6.97	0.20	0.30	48.50
	7380.00		14.05						
Reach 1	98.5	BR D	Q100	9.38	7.23	4.60	0.08	0.14	48.50
	5910.00		11.76						
Reach 1	98.5	BR D	Q1.1	4.08	3.85	-0.78	0.01	0.01	48.50
	1312.00		3.88						
Reach 1	98.5	BR D	Q10	6.35	4.79	2.66	0.08	0.07	48.50
	3850.00		10.03						
Reach 1	98.5	BR D	Q25	6.76	5.07	2.98	0.08	0.08	48.50
	4148.00		10.43						
Reach 1	98.5	BR D	Q50	8.49	6.49	4.05	0.08	0.12	48.50
	5290.00		11.34						
Reach 1	98.5	BR D	Q500	11.40	8.93	5.83	0.07	0.18	48.50
	7380.00		12.62						
Reach 1	60		Q100	9.17	7.30	4.52	0.10	0.06	59.04
	5910.00		10.97						


Reach 1	60		Q1.1	4.06	3.84	-0.76	0.02	0.01	54.29
	1312.00		3.72						
Reach 1	60		Q10	6.20	4.77	2.53	0.13	0.13	56.54
	3850.00		9.57						
Reach 1	60		Q25	6.60	5.07	2.84	0.13	0.14	57.26
	4148.00		9.91						
Reach 1	60		Q50	8.29	6.54	3.97	0.11	0.08	58.73
	5290.00		10.63						
Reach 1	60		Q500	11.15	9.04	5.66	0.09	0.04	59.75
	7380.00		11.66						
Reach 1	38		Q100	9.00	6.92		0.31	0.22	58.50
27.66	5881.82	0.52	11.60						
Reach 1	38		Q1.1	4.03	3.80		0.03	0.00	56.26
3.85	1308.15		3.90						
Reach 1	38		Q10	5.94	4.09		0.30	0.04	57.05
12.03	3837.97	0.00	10.91						
Reach 1	38		Q25	6.33	4.35		0.34	0.07	57.18
13.55	4134.45	0.00	11.30						
Reach 1	38		Q50	8.10	6.07		0.33	0.19	58.07
22.31	5267.47	0.22	11.44						
Reach 1	38		Q500	11.02	8.79		0.27	0.26	59.47
42.16	7336.04	1.81	12.02						


APPENDIX F / HEC-RAS RESULTS FOR PROPOSED CONDITIONS AT MLW





None of the XS's are Geo-Referenced (Geo-Ref user entered XS Geo-Ref interpolated XS Non Geo-Ref user entered XS Non Geo-Ref interpolated XS)



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
Cobosee Stream Reach 1
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
Ground
Elevation (ft)
Main Channel Distance (ft)
30
25
20
15
10
5
0
-5
-10
-500
0
500
1000
1500
2000



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1700 Upstream (I)
.07
.04
.065
Elevation (ft)
Station (ft)
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
180
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1635 H
.07
.045
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1555 G
.07
.042
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1455 F
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1335 E
.065
.045
.075
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1185 D
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 1060 C
.065
.04
.07
Elevation (ft)
Station (ft)
35
30
25
20
15
10
5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 960 B
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 935 JU
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 895 BR Bridge Street
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 895 BR Bridge Street
.05
.04
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 850 JD
.05
.04
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 830 A
.05
.035
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 821 AD
.065
.035
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 820 ADD
.065
.035
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 725 10
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 575 9
.065
.04
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 425 8
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 335 7
.065
.04
.065
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
250
300



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 262 6
.04
.065
.0
6
5
Elevation (ft)
Station (ft)
14
12
10
8
6
4
2
0
-2
-4
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 187 5
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 166 BR Pedestrian Bridge
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 166 BR Pedestrian Bridge
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 137 4
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
10
20
30
40
50
60
70
80
90



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 60 3
.04
.065
.
0
6
5
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80
90
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 38 2
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = 0 1 (Downstream)
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -21 RR
.065
.04
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q10
WS Q100
WS Q50
WS Q25
WS Q1.1
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -54 K2
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q50
WS Q25
WS Q10
WS Q500
WS Q100
WS Q1.1
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
22 ft/s
24 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -88 K1
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MLW -2.1 Kennebec Tailwater
RS = -143 K0
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta

HEC-RAS Version 4.1.0 Jan 2010
U.S. Army Corps of Engineers
Hydrologic Engineering Center
609 Second Street
Davis, California

```
X     X  XXXXXX    XXXX        XXXX       XX      XXXX
X     X  X        X    X       X   X     X  X    X
X     X  X        X            X   X    X    X   X
XXXXXXX  XXXX     X       XXX  XXXX     XXXXXX    XXXX
X     X  X        X            X  X     X    X        X
X     X  X        X    X       X   X    X    X        X
X     X  XXXXXX    XXXX        X    X   X    X   XXXXX
```

PROJECT DATA
Project Title: Gardiner Proposed 135ftSpan
Project File : GardinerProposed5.prj
Run Date and Time: 4/18/2018 3:01:22 PM

Project in English units

PLAN DATA

Plan Title: Plan 02
Plan File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.p02

Geometry Title: Geom 01
Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.g01

Flow Title : MLW -2.1 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.f03

Plan Summary Information:
Number of: Cross Sections = 27 Multiple Openings = 0
Culverts = 0 Inline Structures = 0
Bridges = 3 Lateral Structures = 0

Computational Information
Water surface calculation tolerance = 0.01

Critical depth calculation tolerance = 0.01
Maximum number of iterations = 20
Maximum difference tolerance = 0.3
Flow tolerance factor = 0.001

Computation Options
Critical depth computed only where necessary
Conveyance Calculation Method: At breaks in n values only
Friction Slope Method: Average Conveyance
Computational Flow Regime: Mixed Flow

FLOW DATA

Flow Title: MLW -2.1 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.f03

Flow Data (cfs)

River	Reach	RS	Q100	Q1.1	Q10	Q25	Q50	Q500
Cobosee Stream	Reach 1	1700	5910	1312	3850	4148	5290	7380
Cobosee Stream	Reach 1	-88	5910	1312	3850	4148	5290	7380

Boundary Conditions

River	Reach	Profile	Upstream	Downstream
Cobosee Stream	Reach 1	Q100	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q1.1	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q10	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q25	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q50	Critical	Known WS = -2.1
Cobosee Stream	Reach 1	Q500	Critical	Known WS = -2.1

GEOMETRY DATA

Geometry Title: Geom 01

Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.g01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1700

INPUT
Description: Upstream (I)
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	40	10	39.7	20	39.2	30	37.2	40	34.5
50	29	60	23.5	70	17.5	80	15.5	90	14.5
100	13.8	110	14.2	120	14.8	130	15.7	140	19
150	25	160	31	170	33.3				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	60	.04	150	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
60	150	65	65	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	24.48	Element			
Vel Head (ft)	1.73	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.75	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	21.32	Flow Area (sq ft)		559.56	
E.G. Slope (ft/ft)	0.006899	Area (sq ft)		559.56	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	84.99	Top Width (ft)		84.99	
Vel Total (ft/s)	10.56	Avg. Vel. (ft/s)		10.56	
Max Chl Dpth (ft)	8.95	Hydr. Depth (ft)		6.58	
Conv. Total (cfs)	71151.3	Conv. (cfs)		71151.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		88.36	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.73	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.19	24.29	1.09
C & E Loss (ft)	0.01	Cum SA (acres)	0.10	3.40	1.11

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	19.04	Element			
Vel Head (ft)	0.50	Wt. n-Val.		0.040	

W.S. Elev (ft)	18.54	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	17.33	Flow Area (sq ft)		231.75	
E.G. Slope (ft/ft)	0.004837	Area (sq ft)		231.75	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	70.35	Top Width (ft)		70.35	
Vel Total (ft/s)	5.66	Avg. Vel. (ft/s)		5.66	
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)		3.29	
Conv. Total (cfs)	18865.3	Conv. (cfs)		18865.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		71.44	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		0.98	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.51	Cum Volume (acre-ft)	0.01	8.04	0.04
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	2.70	0.03

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	22.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.15	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	19.81	Flow Area (sq ft)		428.08	
E.G. Slope (ft/ft)	0.006488	Area (sq ft)		428.08	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	79.67	Top Width (ft)		79.67	
Vel Total (ft/s)	8.99	Avg. Vel. (ft/s)		8.99	
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	47797.5	Conv. (cfs)		47797.5	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		82.15	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.11	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.07	17.49	0.16
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	3.21	0.07

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.73	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.33	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.40	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.05	Flow Area (sq ft)		447.72	
E.G. Slope (ft/ft)	0.006586	Area (sq ft)		447.72	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	80.49	Top Width (ft)		80.49	
Vel Total (ft/s)	9.26	Avg. Vel. (ft/s)		9.26	
Max Chl Dpth (ft)	7.60	Hydr. Depth (ft)		5.56	

Conv. Total (cfs)	51113.2	Conv. (cfs)		51113.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		83.10	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.08	18.48	0.18
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	3.26	0.08

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.28	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.89	Flow Area (sq ft)		519.99	
E.G. Slope (ft/ft)	0.006865	Area (sq ft)		519.99	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	83.43	Top Width (ft)		83.43	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	63848.2	Conv. (cfs)		63848.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		86.53	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.14	22.37	0.52
C & E Loss (ft)	0.00	Cum SA (acres)	0.07	3.37	0.56

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.00	Wt. n-Val.	0.070	0.040	
W.S. Elev (ft)	23.79	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	22.27	Flow Area (sq ft)	0.08	649.67	
E.G. Slope (ft/ft)	0.006886	Area (sq ft)	0.08	649.67	
Q Total (cfs)	7380.00	Flow (cfs)	0.03	7379.97	
Top Width (ft)	88.50	Top Width (ft)	0.52	87.98	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	0.44	11.36	
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	0.14	7.38	
Conv. Total (cfs)	88935.3	Conv. (cfs)	0.4	88934.8	
Length Wtd. (ft)	65.00	Wetted Per. (ft)	0.60	91.84	
Min Ch El (ft)	13.80	Shear (lb/sq ft)	0.05	3.04	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.50	Cum Volume (acre-ft)	0.36	28.88	3.67
C & E Loss (ft)	0.03	Cum SA (acres)	0.16	3.46	2.01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1635

INPUT
Description: H
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	23.5	40	17
50	14	60	14.5	70	15	80	15.2	90	15.4
100	15.6	110	15.8	115	17.9	120	20	130	26.5
140	30.1	150	30.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.045	130	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	130	80	80	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	23.95	Element			
Vel Head (ft)	1.69	Wt. n-Val.		0.045	
W.S. Elev (ft)	22.26	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		565.73	
E.G. Slope (ft/ft)	0.009287	Area (sq ft)		565.73	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	91.56	Top Width (ft)		91.56	
Vel Total (ft/s)	10.45	Avg. Vel. (ft/s)		10.45	
Max Chl Dpth (ft)	8.26	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	61328.2	Conv. (cfs)		61328.2	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		95.11	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.45	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.90	Cum Volume (acre-ft)	0.19	23.45	1.09
C & E Loss (ft)	0.09	Cum SA (acres)	0.10	3.27	1.11

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	18.50	Element			
Vel Head (ft)	0.81	Wt. n-Val.		0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		181.92	

E.G. Slope (ft/ft)	0.015059	Area (sq ft)		181.92	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	75.56	Top Width (ft)		75.56	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	10691.3	Conv. (cfs)		10691.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		76.62	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		2.23	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.04	Cum Volume (acre-ft)	0.01	7.73	0.04
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	2.59	0.03

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	21.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.47	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		407.41	
E.G. Slope (ft/ft)	0.010705	Area (sq ft)		407.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	86.08	Top Width (ft)		86.08	
Vel Total (ft/s)	9.45	Avg. Vel. (ft/s)		9.45	
Max Chl Dpth (ft)	6.47	Hydr. Depth (ft)		4.73	
Conv. Total (cfs)	37210.3	Conv. (cfs)		37210.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		88.57	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.07	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.07	16.87	0.16
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	3.09	0.07

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		431.49	
E.G. Slope (ft/ft)	0.010420	Area (sq ft)		431.49	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	86.93	Top Width (ft)		86.93	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	6.75	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	40635.4	Conv. (cfs)		40635.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		89.59	

Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.13	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.08	17.82	0.18
C & E Loss (ft)	0.05	Cum SA (acres)	0.04	3.13	0.08

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.36	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.045	
W.S. Elev (ft)	21.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		520.12	
E.G. Slope (ft/ft)	0.009593	Area (sq ft)		520.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	90.01	Top Width (ft)		90.01	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	7.75	Hydr. Depth (ft)		5.78	
Conv. Total (cfs)	54011.4	Conv. (cfs)		54011.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		93.26	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.91	Cum Volume (acre-ft)	0.14	21.59	0.52
C & E Loss (ft)	0.08	Cum SA (acres)	0.07	3.24	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.89	Wt. n-Val.		0.045	
W.S. Elev (ft)	23.37	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		669.19	
E.G. Slope (ft/ft)	0.008748	Area (sq ft)		669.19	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	94.97	Top Width (ft)		94.97	
Vel Total (ft/s)	11.03	Avg. Vel. (ft/s)		11.03	
Max Chl Dpth (ft)	9.37	Hydr. Depth (ft)		7.05	
Conv. Total (cfs)	78902.3	Conv. (cfs)		78902.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		99.18	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)	0.36	27.90	3.67
C & E Loss (ft)	0.11	Cum SA (acres)	0.16	3.32	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1555

INPUT
Description: G
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	21.5	40	15
50	13.8	60	13.6	70	13.3	80	13.5	90	13.5
100	14.5	110	19	120	26	130	29	140	29.5
150	29.9								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.042	120	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	120	100	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	22.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.62	Wt. n-Val.		0.042	
W.S. Elev (ft)	20.34	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	20.16	Flow Area (sq ft)		455.11	
E.G. Slope (ft/ft)	0.013986	Area (sq ft)		455.11	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	80.13	Top Width (ft)		80.13	
Vel Total (ft/s)	12.99	Avg. Vel. (ft/s)		12.99	
Max Chl Dpth (ft)	7.04	Hydr. Depth (ft)		5.68	
Conv. Total (cfs)	49972.8	Conv. (cfs)		49972.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		83.24	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.77	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.37	Cum Volume (acre-ft)	0.19	22.51	1.09
C & E Loss (ft)	0.07	Cum SA (acres)	0.10	3.11	1.11

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	17.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.042	
W.S. Elev (ft)	16.65	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)		Flow Area (sq ft)		181.93	
E.G. Slope (ft/ft)	0.011277	Area (sq ft)		181.93	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	67.33	Top Width (ft)		67.33	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.35	Hydr. Depth (ft)		2.70	
Conv. Total (cfs)	12355.0	Conv. (cfs)		12355.0	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.41	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		1.87	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.01	7.39	0.04
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	2.46	0.03

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	20.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.06	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.65	Flow Area (sq ft)		355.05	
E.G. Slope (ft/ft)	0.012593	Area (sq ft)		355.05	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.34	Top Width (ft)		76.34	
Vel Total (ft/s)	10.84	Avg. Vel. (ft/s)		10.84	
Max Chl Dpth (ft)	5.76	Hydr. Depth (ft)		4.65	
Conv. Total (cfs)	34308.4	Conv. (cfs)		34308.4	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		78.66	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.55	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.07	16.17	0.16
C & E Loss (ft)	0.02	Cum SA (acres)	0.04	2.94	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	21.21	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.96	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.89	Flow Area (sq ft)		368.77	
E.G. Slope (ft/ft)	0.013023	Area (sq ft)		368.77	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	76.87	Top Width (ft)		76.87	
Vel Total (ft/s)	11.25	Avg. Vel. (ft/s)		11.25	
Max Chl Dpth (ft)	5.94	Hydr. Depth (ft)		4.80	
Conv. Total (cfs)	36348.9	Conv. (cfs)		36348.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		79.30	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.78	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.08	17.09	0.18
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	2.98	0.08

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	22.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.41	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.96	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	19.73	Flow Area (sq ft)		424.40	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		424.40	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	78.99	Top Width (ft)		78.99	
Vel Total (ft/s)	12.46	Avg. Vel. (ft/s)		12.46	
Max Chl Dpth (ft)	6.66	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	44978.9	Conv. (cfs)		44978.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		81.85	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.48	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.14	20.73	0.52
C & E Loss (ft)	0.04	Cum SA (acres)	0.07	3.09	0.56

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	24.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.03	Wt. n-Val.		0.042	
W.S. Elev (ft)	21.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	21.12	Flow Area (sq ft)		528.57	
E.G. Slope (ft/ft)	0.013933	Area (sq ft)		528.57	

Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	82.81	Top Width (ft)		82.81	
Vel Total (ft/s)	13.96	Avg. Vel. (ft/s)		13.96	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)		6.38	
Conv. Total (cfs)	62522.2	Conv. (cfs)		62522.2	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		86.46	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		5.32	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.36	26.80	3.67
C & E Loss (ft)	0.13	Cum SA (acres)	0.16	3.16	2.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1455

INPUT
Description: F
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	45	10	38	20	31	30	24	40	16.5
50	12.5	60	11.8	70	12	80	12.3	90	12.6
100	12.8	110	14	120	18.5	130	23	140	28
150	30								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	120	120	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	21.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.37	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	19.15	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.73	Flow Area (sq ft)	4.68	476.91	0.47
E.G. Slope (ft/ft)	0.013371	Area (sq ft)	4.68	476.91	0.47
Q Total (cfs)	5910.00	Flow (cfs)	12.85	5896.64	0.51
Top Width (ft)	84.97	Top Width (ft)	3.53	80.00	1.44
Vel Total (ft/s)	12.26	Avg. Vel. (ft/s)	2.75	12.36	1.09
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)	1.32	5.96	0.32

Conv. Total (cfs)	51109.1	Conv. (cfs)	111.1	50993.5	4.4
Length Wtd. (ft)	120.00	Wetted Per. (ft)	4.41	81.85	1.58
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.88	4.86	0.25
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.18	21.44	1.09
C & E Loss (ft)	0.17	Cum SA (acres)	0.09	2.93	1.10

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	16.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.06	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	14.87	Flow Area (sq ft)		165.73	
E.G. Slope (ft/ft)	0.018077	Area (sq ft)		165.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	68.77	Top Width (ft)		68.77	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	3.26	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	9758.3	Conv. (cfs)		9758.3	
Length Wtd. (ft)	120.00	Wetted Per. (ft)		69.60	
Min Ch El (ft)	11.80	Shear (lb/sq ft)		2.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	2.24	Cum Volume (acre-ft)	0.01	6.99	0.04
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	2.31	0.03

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.01	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.40	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.28	Flow Area (sq ft)	0.54	338.38	
E.G. Slope (ft/ft)	0.017108	Area (sq ft)	0.54	338.38	
Q Total (cfs)	3850.00	Flow (cfs)	0.82	3849.18	
Top Width (ft)	78.76	Top Width (ft)	1.20	77.56	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	1.51	11.38	
Max Chl Dpth (ft)	5.60	Hydr. Depth (ft)	0.45	4.36	
Conv. Total (cfs)	29434.9	Conv. (cfs)	6.3	29428.6	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.50	79.17	

Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.38	4.57	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.07	15.38	0.16
C & E Loss (ft)	0.14	Cum SA (acres)	0.04	2.76	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	19.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.07	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.67	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.49	Flow Area (sq ft)	0.91	359.11	
E.G. Slope (ft/ft)	0.016461	Area (sq ft)	0.91	359.11	
Q Total (cfs)	4148.00	Flow (cfs)	1.60	4146.40	
Top Width (ft)	79.70	Top Width (ft)	1.56	78.15	
Vel Total (ft/s)	11.52	Avg. Vel. (ft/s)	1.76	11.55	
Max Chl Dpth (ft)	5.87	Hydr. Depth (ft)	0.58	4.60	
Conv. Total (cfs)	32330.5	Conv. (cfs)	12.5	32318.0	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.94	79.81	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.48	4.62	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.53	Cum Volume (acre-ft)	0.08	16.25	0.18
C & E Loss (ft)	0.14	Cum SA (acres)	0.04	2.81	0.08

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	20.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.27	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	18.65	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.33	Flow Area (sq ft)	3.07	436.66	0.02
E.G. Slope (ft/ft)	0.014397	Area (sq ft)	3.07	436.66	0.02
Q Total (cfs)	5290.00	Flow (cfs)	7.60	5282.39	0.01
Top Width (ft)	83.19	Top Width (ft)	2.86	80.00	0.32
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	2.48	12.10	0.42
Max Chl Dpth (ft)	6.85	Hydr. Depth (ft)	1.07	5.46	0.07
Conv. Total (cfs)	44088.4	Conv. (cfs)	63.4	44024.9	0.1
Length Wtd. (ft)	120.00	Wetted Per. (ft)	3.58	81.85	0.36
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.77	4.80	0.06
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.34	Cum Volume (acre-ft)	0.14	19.74	0.52
C & E Loss (ft)	0.16	Cum SA (acres)	0.07	2.90	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	22.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.58	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	20.28	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)		Flow Area (sq ft)	9.55	567.80	3.54
E.G. Slope (ft/ft)	0.011590	Area (sq ft)	9.55	567.80	3.54
Q Total (cfs)	7380.00	Flow (cfs)	30.99	7341.96	7.05
Top Width (ft)	89.01	Top Width (ft)	5.05	80.00	3.97
Vel Total (ft/s)	12.70	Avg. Vel. (ft/s)	3.24	12.93	1.99
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)	1.89	7.10	0.89
Conv. Total (cfs)	68552.3	Conv. (cfs)	287.9	68198.9	65.5
Length Wtd. (ft)	120.00	Wetted Per. (ft)	6.31	81.85	4.35
Min Ch El (ft)	11.80	Shear (lb/sq ft)	1.10	5.02	0.59
Alpha	1.03	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.34	25.54	3.67
C & E Loss (ft)	0.18	Cum SA (acres)	0.16	2.97	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1335

INPUT
Description: E
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	42.5	10	37.5	20	31	30	24	40	17
50	11	60	9.5	70	9.5	80	9.5	90	9.5
100	10.5	110	14	120	19	130	23	140	28
150	29	160	30						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val

0	.065	40	.045	120	.075

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	20.09	Element			
Vel Head (ft)	1.80	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	18.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.19	548.74	
E.G. Slope (ft/ft)	0.008433	Area (sq ft)	1.19	548.74	
Q Total (cfs)	5910.00	Flow (cfs)	1.63	5908.37	
Top Width (ft)	80.42	Top Width (ft)	1.84	78.58	
Vel Total (ft/s)	10.75	Avg. Vel. (ft/s)	1.37	10.77	
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	0.65	6.98	
Conv. Total (cfs)	64355.9	Conv. (cfs)	17.8	64338.2	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.25	82.01	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.28	3.52	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.56	Cum Volume (acre-ft)	0.17	20.03	1.09
C & E Loss (ft)	0.09	Cum SA (acres)	0.09	2.71	1.10

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	13.78	Element			
Vel Head (ft)	1.14	Wt. n-Val.		0.045	
W.S. Elev (ft)	12.63	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)		152.87	
E.G. Slope (ft/ft)	0.019322	Area (sq ft)		152.87	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	58.82	Top Width (ft)		58.82	
Vel Total (ft/s)	8.58	Avg. Vel. (ft/s)		8.58	
Max Chl Dpth (ft)	3.13	Hydr. Depth (ft)		2.60	
Conv. Total (cfs)	9438.5	Conv. (cfs)		9438.5	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		59.79	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.08	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.87	Cum Volume (acre-ft)	0.01	6.56	0.04
C & E Loss (ft)	0.10	Cum SA (acres)	0.01	2.13	0.03

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	17.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.56	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.13	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		384.33	
E.G. Slope (ft/ft)	0.010509	Area (sq ft)		384.33	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	72.81	Top Width (ft)		72.81	
Vel Total (ft/s)	10.02	Avg. Vel. (ft/s)		10.02	
Max Chl Dpth (ft)	6.63	Hydr. Depth (ft)		5.28	
Conv. Total (cfs)	37556.8	Conv. (cfs)		37556.8	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		75.49	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.65	Cum Volume (acre-ft)	0.07	14.38	0.16
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	2.55	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	18.07	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.48	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		409.66	
E.G. Slope (ft/ft)	0.010113	Area (sq ft)		409.66	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	74.08	Top Width (ft)		74.08	
Vel Total (ft/s)	10.13	Avg. Vel. (ft/s)		10.13	
Max Chl Dpth (ft)	6.98	Hydr. Depth (ft)		5.53	
Conv. Total (cfs)	41247.6	Conv. (cfs)		41247.6	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		76.94	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.36	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.64	Cum Volume (acre-ft)	0.08	15.19	0.18
C & E Loss (ft)	0.05	Cum SA (acres)	0.04	2.60	0.08

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.68	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.34	501.53	
E.G. Slope (ft/ft)	0.008923	Area (sq ft)	0.34	501.53	
Q Total (cfs)	5290.00	Flow (cfs)	0.31	5289.69	
Top Width (ft)	78.35	Top Width (ft)	0.98	77.37	
Vel Total (ft/s)	10.54	Avg. Vel. (ft/s)	0.93	10.55	
Max Chl Dpth (ft)	8.18	Hydr. Depth (ft)	0.34	6.48	
Conv. Total (cfs)	56001.4	Conv. (cfs)	3.3	55998.1	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.19	80.66	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.16	3.46	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.58	Cum Volume (acre-ft)	0.13	18.45	0.52
C & E Loss (ft)	0.07	Cum SA (acres)	0.06	2.69	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	21.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.97	Wt. n-Val.	0.065	0.045	0.075
W.S. Elev (ft)	19.61	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.86	653.63	0.46
E.G. Slope (ft/ft)	0.007513	Area (sq ft)	4.86	653.63	0.46
Q Total (cfs)	7380.00	Flow (cfs)	10.06	7369.60	0.34
Top Width (ft)	85.25	Top Width (ft)	3.73	80.00	1.52
Vel Total (ft/s)	11.20	Avg. Vel. (ft/s)	2.07	11.27	0.74
Max Chl Dpth (ft)	10.11	Hydr. Depth (ft)	1.30	8.17	0.30
Conv. Total (cfs)	85143.6	Conv. (cfs)	116.1	85023.6	3.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.55	83.60	1.64
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.50	3.67	0.13
Alpha	1.01	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.52	Cum Volume (acre-ft)	0.33	23.85	3.66
C & E Loss (ft)	0.14	Cum SA (acres)	0.14	2.75	2.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1185

INPUT
Description: D
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	41.5	4	40	10	35	20	27.5	30	20
35	16	40	12	50	7	60	5.5	70	6
80	7	90	11	100	16	110	22	120	28
130	28.2								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	35	.045	110	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
35	110	125	125	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	18.43	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.72	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.71	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	15.05	Flow Area (sq ft)		446.60	
E.G. Slope (ft/ft)	0.013216	Area (sq ft)		446.60	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	64.07	Top Width (ft)		64.07	
Vel Total (ft/s)	13.23	Avg. Vel. (ft/s)		13.23	
Max Chl Dpth (ft)	10.21	Hydr. Depth (ft)		6.97	
Conv. Total (cfs)	51408.5	Conv. (cfs)		51408.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		68.61	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		5.37	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.68	Cum Volume (acre-ft)	0.17	18.31	1.09
C & E Loss (ft)	0.04	Cum SA (acres)	0.08	2.46	1.10

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	11.81	Element	Left OB	Channel	Right OB

Vel Head (ft)	0.82	Wt. n-Val.		0.045	
W.S. Elev (ft)	10.99	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)		Flow Area (sq ft)		180.58	
E.G. Slope (ft/ft)	0.008701	Area (sq ft)		180.58	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.96	Top Width (ft)		47.96	
Vel Total (ft/s)	7.27	Avg. Vel. (ft/s)		7.27	
Max Chl Dpth (ft)	5.49	Hydr. Depth (ft)		3.77	
Conv. Total (cfs)	14065.5	Conv. (cfs)		14065.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		49.85	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		1.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.49	Cum Volume (acre-ft)	0.01	5.98	0.04
C & E Loss (ft)	0.06	Cum SA (acres)	0.01	1.95	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	16.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.93	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.07	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.16	Flow Area (sq ft)		345.58	
E.G. Slope (ft/ft)	0.011593	Area (sq ft)		345.58	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	58.73	Top Width (ft)		58.73	
Vel Total (ft/s)	11.14	Avg. Vel. (ft/s)		11.14	
Max Chl Dpth (ft)	8.57	Hydr. Depth (ft)		5.88	
Conv. Total (cfs)	35757.5	Conv. (cfs)		35757.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		62.30	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.01	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.62	Cum Volume (acre-ft)	0.07	13.12	0.16
C & E Loss (ft)	0.06	Cum SA (acres)	0.04	2.33	0.07

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	16.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.05	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.34	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.46	Flow Area (sq ft)		361.45	
E.G. Slope (ft/ft)	0.011842	Area (sq ft)		361.45	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	59.60	Top Width (ft)		59.60	
Vel Total (ft/s)	11.48	Avg. Vel. (ft/s)		11.48	
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		6.06	
Conv. Total (cfs)	38117.1	Conv. (cfs)		38117.1	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		63.33	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.22	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.63	Cum Volume (acre-ft)	0.08	13.86	0.18
C & E Loss (ft)	0.06	Cum SA (acres)	0.04	2.37	0.08

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	17.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.47	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.28	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	14.52	Flow Area (sq ft)		419.10	
E.G. Slope (ft/ft)	0.012665	Area (sq ft)		419.10	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	62.66	Top Width (ft)		62.66	
Vel Total (ft/s)	12.62	Avg. Vel. (ft/s)		12.62	
Max Chl Dpth (ft)	9.78	Hydr. Depth (ft)		6.69	
Conv. Total (cfs)	47005.3	Conv. (cfs)		47005.3	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		66.95	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.95	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.66	Cum Volume (acre-ft)	0.13	16.86	0.52
C & E Loss (ft)	0.05	Cum SA (acres)	0.06	2.45	0.56

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	19.92	Element	Left OB	Channel	Right OB

Vel Head (ft)	3.33	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	16.59	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	16.20	Flow Area (sq ft)	0.22	503.94	
E.G. Slope (ft/ft)	0.014382	Area (sq ft)	0.22	503.94	
Q Total (cfs)	7380.00	Flow (cfs)	0.23	7379.77	
Top Width (ft)	66.73	Top Width (ft)	0.74	65.99	
Vel Total (ft/s)	14.64	Avg. Vel. (ft/s)	1.04	14.64	
Max Chl Dpth (ft)	11.09	Hydr. Depth (ft)	0.30	7.64	
Conv. Total (cfs)	61538.8	Conv. (cfs)	1.9	61536.9	
Length Wtd. (ft)	125.00	Wetted Per. (ft)	0.95	70.86	
Min Ch El (ft)	5.50	Shear (lb/sq ft)	0.21	6.39	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.73	Cum Volume (acre-ft)	0.32	21.86	3.66
C & E Loss (ft)	0.02	Cum SA (acres)	0.14	2.50	2.00

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1060

INPUT
Description: C
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	33	20	35	30	29	40	23
45	19.5	50	16	60	10	70	7	80	5.5
90	5	100	5	110	7	120	13	130	20
200	20.1								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	45	.04	130	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
45	130	100	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	16.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.12	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.60	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.60	Flow Area (sq ft)		416.89	
E.G. Slope (ft/ft)	0.013608	Area (sq ft)		416.89	

Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	66.85	Top Width (ft)		66.85	
Vel Total (ft/s)	14.18	Avg. Vel. (ft/s)		14.18	
Max Chl Dpth (ft)	8.60	Hydr. Depth (ft)		6.24	
Conv. Total (cfs)	50662.6	Conv. (cfs)		50662.6	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		70.46	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.03	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.12	Cum Volume (acre-ft)	0.17	17.07	1.09
C & E Loss (ft)	0.22	Cum SA (acres)	0.08	2.28	1.10

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.41	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.85	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	8.85	Flow Area (sq ft)		137.48	
E.G. Slope (ft/ft)	0.017292	Area (sq ft)		137.48	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	49.24	Top Width (ft)		49.24	
Vel Total (ft/s)	9.54	Avg. Vel. (ft/s)		9.54	
Max Chl Dpth (ft)	3.85	Hydr. Depth (ft)		2.79	
Conv. Total (cfs)	9977.1	Conv. (cfs)		9977.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		50.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		2.95	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.49	Cum Volume (acre-ft)	0.01	5.52	0.04
C & E Loss (ft)	0.13	Cum SA (acres)	0.01	1.81	0.03

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	14.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.49	Wt. n-Val.		0.040	
W.S. Elev (ft)	11.83	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	11.83	Flow Area (sq ft)		303.74	
E.G. Slope (ft/ft)	0.014509	Area (sq ft)		303.74	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.10	Top Width (ft)		61.10	
Vel Total (ft/s)	12.68	Avg. Vel. (ft/s)		12.68	
Max Chl Dpth (ft)	6.83	Hydr. Depth (ft)		4.97	
Conv. Total (cfs)	31962.1	Conv. (cfs)		31962.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		63.71	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.32	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.07	12.19	0.16
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	2.16	0.07

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	14.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	12.11	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	12.11	Flow Area (sq ft)		320.83	
E.G. Slope (ft/ft)	0.014350	Area (sq ft)		320.83	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.03	Top Width (ft)		62.03	
Vel Total (ft/s)	12.93	Avg. Vel. (ft/s)		12.93	
Max Chl Dpth (ft)	7.11	Hydr. Depth (ft)		5.17	
Conv. Total (cfs)	34626.6	Conv. (cfs)		34626.6	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		64.79	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.44	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.08	12.89	0.18
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	2.19	0.08

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	16.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.10	Flow Area (sq ft)		383.70	
E.G. Slope (ft/ft)	0.013874	Area (sq ft)		383.70	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.29	Top Width (ft)		65.29	
Vel Total (ft/s)	13.79	Avg. Vel. (ft/s)		13.79	
Max Chl Dpth (ft)	8.10	Hydr. Depth (ft)		5.88	
Conv. Total (cfs)	44910.9	Conv. (cfs)		44910.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.61	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.84	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.13	Cum Volume (acre-ft)	0.13	15.71	0.52
C & E Loss (ft)	0.23	Cum SA (acres)	0.06	2.26	0.56

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	18.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	14.68	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	14.68	Flow Area (sq ft)		490.72	
E.G. Slope (ft/ft)	0.013258	Area (sq ft)		490.72	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	

Top Width (ft)	70.18	Top Width (ft)		70.18	
Vel Total (ft/s)	15.04	Avg. Vel. (ft/s)		15.04	
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	64094.8	Conv. (cfs)		64094.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		74.43	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.46	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.32	20.43	3.66
C & E Loss (ft)	0.21	Cum SA (acres)	0.14	2.30	2.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 960

INPUT
Description: B
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	32	17.3	29	67	5	79.4	5	85.5	4
100.5	3.5	114.3	4	124.5	5	140	12	202.9	14.2
203	14.5	209.1	15	224.5	20	229.5	25		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	67	.042	124.5	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
67	124.5	25	25	.3	.5

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	14.55	Element	Left OB	Channel	Right OB
Vel Head (ft)	5.12	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.43	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.91	Flow Area (sq ft)	20.34	299.03	21.75

E.G. Slope (ft/ft)	0.030767	Area (sq ft)	20.34	299.03	21.75
Q Total (cfs)	5910.00	Flow (cfs)	168.11	5560.68	181.20
Top Width (ft)	76.49	Top Width (ft)	9.18	57.50	9.82
Vel Total (ft/s)	17.32	Avg. Vel. (ft/s)	8.26	18.60	8.33
Max Chl Dpth (ft)	5.93	Hydr. Depth (ft)	2.22	5.20	2.22
Conv. Total (cfs)	33693.3	Conv. (cfs)	958.4	31701.8	1033.1
Length Wtd. (ft)	25.00	Wetted Per. (ft)	10.19	57.65	10.77
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.83	9.96	3.88
Alpha	1.10	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.97	Cum Volume (acre-ft)	0.15	16.25	1.06
C & E Loss (ft)	0.20	Cum SA (acres)	0.07	2.13	1.09

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	8.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	6.44	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	6.75	Flow Area (sq ft)	2.14	126.86	2.29
E.G. Slope (ft/ft)	0.029093	Area (sq ft)	2.14	126.86	2.29
Q Total (cfs)	1312.00	Flow (cfs)	8.13	1295.11	8.76
Top Width (ft)	63.66	Top Width (ft)	2.98	57.50	3.18
Vel Total (ft/s)	9.99	Avg. Vel. (ft/s)	3.79	10.21	3.82
Max Chl Dpth (ft)	2.94	Hydr. Depth (ft)	0.72	2.21	0.72
Conv. Total (cfs)	7692.0	Conv. (cfs)	47.7	7593.0	51.4
Length Wtd. (ft)	25.00	Wetted Per. (ft)	3.31	57.65	3.49
Min Ch El (ft)	3.50	Shear (lb/sq ft)	1.18	4.00	1.19
Alpha	1.03	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.21	Cum Volume (acre-ft)	0.01	5.22	0.04
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	1.68	0.02

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	12.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.85	Wt. n-Val.	0.050	0.042	0.050

W.S. Elev (ft)	8.24	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.32	Flow Area (sq ft)	10.89	230.65	11.65
E.G. Slope (ft/ft)	0.032272	Area (sq ft)	10.89	230.65	11.65
Q Total (cfs)	3850.00	Flow (cfs)	74.85	3694.47	80.68
Top Width (ft)	71.40	Top Width (ft)	6.72	57.50	7.18
Vel Total (ft/s)	15.21	Avg. Vel. (ft/s)	6.87	16.02	6.93
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)	1.62	4.01	1.62
Conv. Total (cfs)	21431.3	Conv. (cfs)	416.7	20565.5	449.1
Length Wtd. (ft)	25.00	Wetted Per. (ft)	7.46	57.65	7.88
Min Ch El (ft)	3.50	Shear (lb/sq ft)	2.94	8.06	2.98
Alpha	1.07	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.09	Cum Volume (acre-ft)	0.06	11.58	0.14
C & E Loss (ft)	0.13	Cum SA (acres)	0.03	2.02	0.06

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.48	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.06	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	8.43	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.57	Flow Area (sq ft)	12.16	241.21	13.00
E.G. Slope (ft/ft)	0.032073	Area (sq ft)	12.16	241.21	13.00
Q Total (cfs)	4148.00	Flow (cfs)	86.43	3968.41	93.16
Top Width (ft)	72.19	Top Width (ft)	7.10	57.50	7.59
Vel Total (ft/s)	15.57	Avg. Vel. (ft/s)	7.11	16.45	7.16
Max Chl Dpth (ft)	4.93	Hydr. Depth (ft)	1.71	4.19	1.71
Conv. Total (cfs)	23161.7	Conv. (cfs)	482.6	22158.9	520.2
Length Wtd. (ft)	25.00	Wetted Per. (ft)	7.88	57.65	8.33
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.09	8.38	3.13
Alpha	1.08	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.07	Cum Volume (acre-ft)	0.07	12.24	0.16
C & E Loss (ft)	0.14	Cum SA (acres)	0.03	2.05	0.07

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q50

			Left OB	Channel	Right OB
E.G. Elev (ft)	13.86	Element			
Vel Head (ft)	4.76	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.09	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.43	Flow Area (sq ft)	17.35	279.49	18.55
E.G. Slope (ft/ft)	0.031227	Area (sq ft)	17.35	279.49	18.55
Q Total (cfs)	5290.00	Flow (cfs)	136.92	5005.50	147.58
Top Width (ft)	75.04	Top Width (ft)	8.48	57.50	9.06
Vel Total (ft/s)	16.77	Avg. Vel. (ft/s)	7.89	17.91	7.96
Max Chl Dpth (ft)	5.59	Hydr. Depth (ft)	2.05	4.86	2.05
Conv. Total (cfs)	29935.7	Conv. (cfs)	774.8	28325.7	835.2
Length Wtd. (ft)	25.00	Wetted Per. (ft)	9.41	57.65	9.94
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.59	9.45	3.64
Alpha	1.09	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.00	Cum Volume (acre-ft)	0.11	14.95	0.50
C & E Loss (ft)	0.18	Cum SA (acres)	0.05	2.12	0.55

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	16.05	Element			
Vel Head (ft)	5.85	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	10.20	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	11.80	Flow Area (sq ft)	28.01	343.23	29.95
E.G. Slope (ft/ft)	0.029537	Area (sq ft)	28.01	343.23	29.95
Q Total (cfs)	7380.00	Flow (cfs)	252.32	6855.72	271.96
Top Width (ft)	79.79	Top Width (ft)	10.77	57.50	11.52
Vel Total (ft/s)	18.40	Avg. Vel. (ft/s)	9.01	19.97	9.08
Max Chl Dpth (ft)	6.70	Hydr. Depth (ft)	2.60	5.97	2.60
Conv. Total (cfs)	42940.8	Conv. (cfs)	1468.1	39890.3	1582.4
Length Wtd. (ft)	25.00	Wetted Per. (ft)	11.96	57.65	12.64
Min Ch El (ft)	3.50	Shear (lb/sq ft)	4.32	10.98	4.37
Alpha	1.11	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.90	Cum Volume (acre-ft)	0.28	19.48	3.63
C & E Loss (ft)	0.23	Cum SA (acres)	0.12	2.15	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 935

INPUT
Description: JU
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	15.3	30	23.8	27.1	35	27	37.7	19
62	5	79	5	82.2	4	105.2	2	121.1	3
125.6	4	137.4	10	203	12.5	203.1	13	203.2	13.1
208.7	13.4	231.8	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	62	.042	125.6	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
62	125.6	85	85	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	35	28	F
188	231.8	26	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	13.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.57	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	11.75	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	9.85	Flow Area (sq ft)	39.49	523.09	95.95
E.G. Slope (ft/ft)	0.005265	Area (sq ft)	39.49	523.09	95.95
Q Total (cfs)	5910.00	Flow (cfs)	174.05	5450.01	285.95
Top Width (ft)	132.90	Top Width (ft)	11.71	63.60	57.59
Vel Total (ft/s)	8.97	Avg. Vel. (ft/s)	4.41	10.42	2.98
Max Chl Dpth (ft)	9.75	Hydr. Depth (ft)	3.37	8.22	1.67
Conv. Total (cfs)	81446.2	Conv. (cfs)	2398.5	75107.0	3940.7
Length Wtd. (ft)	11.00	Wetted Per. (ft)	13.51	63.98	59.06
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.96	2.69	0.53

Alpha	1.26	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.13	16.02	1.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.07	2.10	1.07

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.48	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	7.09	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	5.89	Flow Area (sq ft)	3.80	227.24	9.41
E.G. Slope (ft/ft)	0.004686	Area (sq ft)	3.80	227.24	9.41
Q Total (cfs)	1312.00	Flow (cfs)	7.25	1281.04	23.71
Top Width (ft)	73.32	Top Width (ft)	3.63	63.60	6.08
Vel Total (ft/s)	5.46	Avg. Vel. (ft/s)	1.91	5.64	2.52
Max Chl Dpth (ft)	5.09	Hydr. Depth (ft)	1.05	3.57	1.55
Conv. Total (cfs)	19166.7	Conv. (cfs)	105.9	18714.4	346.4
Length Wtd. (ft)	11.00	Wetted Per. (ft)	4.19	63.98	6.82
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.27	1.04	0.40
Alpha	1.05	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.05	Cum Volume (acre-ft)	0.01	5.12	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	1.65	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	11.06	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.21	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.85	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	8.32	Flow Area (sq ft)	20.41	402.56	33.65
E.G. Slope (ft/ft)	0.005604	Area (sq ft)	20.41	402.56	33.65
Q Total (cfs)	3850.00	Flow (cfs)	74.51	3633.67	141.82
Top Width (ft)	83.52	Top Width (ft)	8.42	63.60	11.51
Vel Total (ft/s)	8.43	Avg. Vel. (ft/s)	3.65	9.03	4.21
Max Chl Dpth (ft)	7.85	Hydr. Depth (ft)	2.43	6.33	2.93
Conv. Total (cfs)	51429.6	Conv. (cfs)	995.3	48539.8	1894.5
Length Wtd. (ft)	11.00	Wetted Per. (ft)	9.72	63.98	12.91
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.74	2.20	0.91
Alpha	1.09	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.05	11.40	0.13

C & E Loss (ft)	0.02	Cum SA (acres)	0.02	1.98	0.05

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.40	Element			
Vel Head (ft)	1.30	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	10.11	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	8.55	Flow Area (sq ft)	22.63	418.90	36.81
E.G. Slope (ft/ft)	0.005706	Area (sq ft)	22.63	418.90	36.81
Q Total (cfs)	4148.00	Flow (cfs)	86.27	3917.98	143.74
Top Width (ft)	87.07	Top Width (ft)	8.86	63.60	14.61
Vel Total (ft/s)	8.67	Avg. Vel. (ft/s)	3.81	9.35	3.90
Max Chl Dpth (ft)	8.11	Hydr. Depth (ft)	2.55	6.59	2.52
Conv. Total (cfs)	54913.3	Conv. (cfs)	1142.2	51868.2	1903.0
Length Wtd. (ft)	11.00	Wetted Per. (ft)	10.23	63.98	16.05
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.79	2.33	0.82
Alpha	1.11	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.06	12.05	0.15
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	2.02	0.07

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q50

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.74	Element			
Vel Head (ft)	1.47	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	11.27	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	9.42	Flow Area (sq ft)	34.13	492.93	71.59
E.G. Slope (ft/ft)	0.005275	Area (sq ft)	34.13	492.93	71.59
Q Total (cfs)	5290.00	Flow (cfs)	143.42	4940.89	205.69
Top Width (ft)	119.63	Top Width (ft)	10.88	63.60	45.15
Vel Total (ft/s)	8.84	Avg. Vel. (ft/s)	4.20	10.02	2.87
Max Chl Dpth (ft)	9.27	Hydr. Depth (ft)	3.14	7.75	1.59
Conv. Total (cfs)	72834.0	Conv. (cfs)	1974.7	68027.4	2832.0
Length Wtd. (ft)	11.00	Wetted Per. (ft)	12.56	63.98	46.61
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.89	2.54	0.51
Alpha	1.21	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.10	14.73	0.48
C & E Loss (ft)	0.02	Cum SA (acres)	0.05	2.09	0.53

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	14.57	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	12.97	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	11.03	Flow Area (sq ft)	55.13	600.98	171.93
E.G. Slope (ft/ft)	0.004645	Area (sq ft)	55.13	600.98	183.29
Q Total (cfs)	7380.00	Flow (cfs)	255.06	6451.11	673.83
Top Width (ft)	154.93	Top Width (ft)	13.83	63.60	77.49
Vel Total (ft/s)	8.91	Avg. Vel. (ft/s)	4.63	10.73	3.92
Max Chl Dpth (ft)	10.97	Hydr. Depth (ft)	3.98	9.45	2.76
Conv. Total (cfs)	108286.3	Conv. (cfs)	3742.5	94656.7	9887.1
Length Wtd. (ft)	11.00	Wetted Per. (ft)	15.97	63.98	63.87
Min Ch El (ft)	2.00	Shear (lb/sq ft)	1.00	2.72	0.78
Alpha	1.29	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.05	Cum Volume (acre-ft)	0.26	19.21	3.57
C & E Loss (ft)	0.03	Cum SA (acres)	0.12	2.12	1.96

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 895

INPUT
Description: Bridge Street
Distance from Upstream XS = 11
Deck/Roadway Width = 62
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	46.2	29.4	0
46.2	29.4	24.2	177.2	28	22.8
177.2	28	0	260	26	0

Upstream Bridge Cross Section Data
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev

```
       0      31    15.3      30    23.8    27.1      35      27    37.7      19
      62       5      79       5    82.2       4   105.2       2   121.1       3
   125.6       4   137.4      10     203    12.5   203.1      13   203.2    13.1
   208.7    13.4   231.8      20

Manning's n Values         num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
       0     .05      62    .042   125.6     .05

Bank Sta: Left   Right    Coeff Contr.   Expan.
           62   125.6             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
       0      35      28        F
     188   231.8      26        F

Downstream  Deck/Roadway Coordinates
    num=       6
     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord
       0      30       0    46.2    29.4       0    46.2    29.4    24.2
   177.2      28    22.8   177.2      28       0     260      26       0

Downstream Bridge Cross Section Data
Station Elevation Data    num=      12
     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev
       0      29      32      25    35.3      20    63.6       5    85.1       3
      94       1   114.7       1   119.9       3   139.5      10   174.5      10
   238.1      15   238.2      25

Manning's n Values         num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
       0     .05    63.6     .04   119.9     .05

Bank Sta: Left   Right    Coeff Contr.   Expan.
          63.6   119.9             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
       0      39      24        F
     184   238.2      24        F
Blocked Obstructions     num=       1
   Sta L   Sta R    Elev
     203     240      30

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =       2 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =      26
Energy head used in spillway design         =
```

Spillway height used in design =
Weir crest shape = Broad Crested

Number of Bridge Coefficient Sets = 1

Low Flow Methods and Data
Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
Energy Only

Additional Bridge Parameters
Add Friction component to Momentum
Do not add Weight component to Momentum
Class B flow critical depth computations use critical depth
inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Inside BR US	Inside BR DS
E.G. US. (ft)	13.32	Element		
W.S. US. (ft)	11.75	E.G. Elev (ft)	13.24	12.86
Q Total (cfs)	5910.00	W.S. Elev (ft)	11.59	11.35
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	9.85	9.23
Q Weir (cfs)		Max Chl Dpth (ft)	9.59	10.35
Weir Sta Lft (ft)		Vel Total (ft/s)	9.26	8.59
Weir Sta Rgt (ft)		Flow Area (sq ft)	637.90	688.22
Weir Submerg		Froude # Chl	0.59	0.54
Weir Max Depth (ft)		Specif Force (cu ft)	4208.66	4466.50
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.04	5.48
Min El Prs (ft)	24.20	W.P. Total (ft)	130.24	129.07
Delta EG (ft)	0.53	Conv. Total (cfs)	78585.2	90366.7
Delta WS (ft)	0.60	Top Width (ft)	126.63	125.59
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.30	0.05
BR Open Vel (ft/s)	9.26	C & E Loss (ft)	0.07	0.04
Coef of Q		Shear Total (lb/sq ft)	1.73	1.42
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.58	Element		

W.S. US. (ft)	7.09	E.G. Elev (ft)	7.52	7.23
Q Total (cfs)	1312.00	W.S. Elev (ft)	7.01	6.85
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	5.89	4.95
Q Weir (cfs)		Max Chl Dpth (ft)	5.01	5.85
Weir Sta Lft (ft)		Vel Total (ft/s)	5.61	4.77
Weir Sta Rgt (ft)		Flow Area (sq ft)	234.02	275.04
Weir Submerg		Froude # Chl	0.55	0.42
Weir Max Depth (ft)		Specif Force (cu ft)	666.46	843.36
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	3.21	3.90
Min El Prs (ft)	24.20	W.P. Total (ft)	74.63	72.41
Delta EG (ft)	0.37	Conv. Total (cfs)	18369.3	26058.2
Delta WS (ft)	0.28	Top Width (ft)	72.99	70.59
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.22	0.03
BR Open Vel (ft/s)	5.61	C & E Loss (ft)	0.07	0.00
Coef of Q		Shear Total (lb/sq ft)	1.00	0.60
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	11.06	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	9.85	E.G. Elev (ft)	10.97	10.60
Q Total (cfs)	3850.00	W.S. Elev (ft)	9.70	9.43
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	8.32	7.59
Q Weir (cfs)		Max Chl Dpth (ft)	7.70	8.43
Weir Sta Lft (ft)		Vel Total (ft/s)	8.67	8.15
Weir Sta Rgt (ft)		Flow Area (sq ft)	444.02	472.38
Weir Submerg		Froude # Chl	0.66	0.60
Weir Max Depth (ft)		Specif Force (cu ft)	2415.14	2625.58
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.35	5.71
Min El Prs (ft)	24.20	W.P. Total (ft)	85.97	85.56
Delta EG (ft)	0.52	Conv. Total (cfs)	49300.7	58028.0
Delta WS (ft)	0.53	Top Width (ft)	82.96	82.66
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.32	0.05
BR Open Vel (ft/s)	8.67	C & E Loss (ft)	0.05	0.01
Coef of Q		Shear Total (lb/sq ft)	1.97	1.52
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	11.40	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	10.11	E.G. Elev (ft)	11.33	10.96
Q Total (cfs)	4148.00	W.S. Elev (ft)	9.99	9.72
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	8.55	7.85
Q Weir (cfs)		Max Chl Dpth (ft)	7.99	8.72
Weir Sta Lft (ft)		Vel Total (ft/s)	8.85	8.35
Weir Sta Rgt (ft)		Flow Area (sq ft)	468.49	496.70
Weir Submerg		Froude # Chl	0.66	0.60
Weir Max Depth (ft)		Specif Force (cu ft)	2658.45	2876.22
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.57	5.91
Min El Prs (ft)	24.20	W.P. Total (ft)	87.20	87.05
Delta EG (ft)	0.51	Conv. Total (cfs)	53456.6	62394.7
Delta WS (ft)	0.50	Top Width (ft)	84.05	84.03
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.32	0.05
BR Open Vel (ft/s)	8.85	C & E Loss (ft)	0.05	0.01
Coef of Q		Shear Total (lb/sq ft)	2.02	1.57
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	12.74	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.27	E.G. Elev (ft)	12.65	12.30
Q Total (cfs)	5290.00	W.S. Elev (ft)	11.10	10.84
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	9.42	8.76
Q Weir (cfs)		Max Chl Dpth (ft)	9.10	9.84
Weir Sta Lft (ft)		Vel Total (ft/s)	9.14	8.48
Weir Sta Rgt (ft)		Flow Area (sq ft)	578.84	623.95
Weir Submerg		Froude # Chl	0.66	0.54
Weir Max Depth (ft)		Specif Force (cu ft)	3673.21	3921.31
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.04	5.01
Min El Prs (ft)	24.20	W.P. Total (ft)	118.38	127.98
Delta EG (ft)	0.55	Conv. Total (cfs)	69944.6	79903.7
Delta WS (ft)	0.71	Top Width (ft)	114.91	124.62
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.31	0.06
BR Open Vel (ft/s)	9.14	C & E Loss (ft)	0.05	0.05
Coef of Q		Shear Total (lb/sq ft)	1.75	1.33
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

			Inside BR US	Inside BR DS
E.G. US. (ft)	14.57	Element		
W.S. US. (ft)	12.97	E.G. Elev (ft)	14.49	14.15
Q Total (cfs)	7380.00	W.S. Elev (ft)	12.79	12.58
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	11.03	10.97
Q Weir (cfs)		Max Chl Dpth (ft)	10.79	11.58
Weir Sta Lft (ft)		Vel Total (ft/s)	9.33	8.75
Weir Sta Rgt (ft)		Flow Area (sq ft)	790.75	843.24
Weir Submerg		Froude # Chl	0.56	0.52
Weir Max Depth (ft)		Specif Force (cu ft)	5551.62	5877.45
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	6.14	6.59
Min El Prs (ft)	24.20	W.P. Total (ft)	132.64	131.68
Delta EG (ft)	0.46	Conv. Total (cfs)	103912.3	118131.2
Delta WS (ft)	0.44	Top Width (ft)	128.71	127.89
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.27	0.05
BR Open Vel (ft/s)	9.33	C & E Loss (ft)	0.07	0.00
Coef of Q		Shear Total (lb/sq ft)	1.88	1.56
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 850

INPUT
Description: JD
Station Elevation Data num= 12

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	29	32	25	35.3	20	63.6	5	85.1	3
94	1	114.7	1	119.9	3	139.5	10	174.5	10
238.1	15	238.2	25						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	63.6	.04	119.9	.05

Bank Sta: Left Right Lengths: Left Channel Right Coeff Contr. Expan.
63.6 119.9 20 20 20 .3 .5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	39	24	F
184	238.2	24	F

Blocked Obstructions num= 1

Sta L	Sta R	Elev
203	240	30

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.78	Element			
Vel Head (ft)	1.63	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	11.15	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	9.23	Flow Area (sq ft)	35.67	492.82	138.74
E.G. Slope (ft/ft)	0.004722	Area (sq ft)	35.67	492.82	139.77
Q Total (cfs)	5910.00	Flow (cfs)	141.84	5300.11	468.05
Top Width (ft)	137.13	Top Width (ft)	11.60	56.30	69.22
Vel Total (ft/s)	8.86	Avg. Vel. (ft/s)	3.98	10.75	3.37
Max Chl Dpth (ft)	10.15	Hydr. Depth (ft)	3.07	8.75	2.16
Conv. Total (cfs)	86009.0	Conv. (cfs)	2064.2	77133.2	6811.6
Length Wtd. (ft)	20.00	Wetted Per. (ft)	13.13	56.99	65.34
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.80	2.55	0.63
Alpha	1.34	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.06	15.02	0.80
C & E Loss (ft)	0.19	Cum SA (acres)	0.04	1.98	0.96

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.20	Element			
Vel Head (ft)	0.39	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	6.82	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	4.95	Flow Area (sq ft)	3.11	248.80	20.38
E.G. Slope (ft/ft)	0.002613	Area (sq ft)	3.11	248.80	20.38
Q Total (cfs)	1312.00	Flow (cfs)	4.08	1262.17	45.75
Top Width (ft)	70.41	Top Width (ft)	3.42	56.30	10.68
Vel Total (ft/s)	4.82	Avg. Vel. (ft/s)	1.31	5.07	2.25
Max Chl Dpth (ft)	5.82	Hydr. Depth (ft)	0.91	4.42	1.91
Conv. Total (cfs)	25664.0	Conv. (cfs)	79.7	24689.3	895.0
Length Wtd. (ft)	20.00	Wetted Per. (ft)	3.88	56.99	11.34
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.13	0.71	0.29
Alpha	1.07	Stream Power (lb/ft s)	238.20	0.00	0.00

Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.00	4.66	0.01
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.53	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.54	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.22	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	9.32	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.59	Flow Area (sq ft)	17.58	389.65	55.87
E.G. Slope (ft/ft)	0.004663	Area (sq ft)	17.58	389.65	55.87
Q Total (cfs)	3850.00	Flow (cfs)	54.87	3560.66	234.48
Top Width (ft)	82.13	Top Width (ft)	8.14	56.30	17.69
Vel Total (ft/s)	8.31	Avg. Vel. (ft/s)	3.12	9.14	4.20
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.92	3.16
Conv. Total (cfs)	56381.9	Conv. (cfs)	803.5	52144.5	3433.9
Length Wtd. (ft)	20.00	Wetted Per. (ft)	9.22	56.99	18.78
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.56	1.99	0.87
Alpha	1.13	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.01	10.63	0.04
C & E Loss (ft)	0.08	Cum SA (acres)	0.01	1.87	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.29	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	9.61	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.85	Flow Area (sq ft)	20.01	405.91	61.09
E.G. Slope (ft/ft)	0.004678	Area (sq ft)	20.01	405.91	61.09
Q Total (cfs)	4148.00	Flow (cfs)	65.32	3818.07	264.61
Top Width (ft)	83.49	Top Width (ft)	8.69	56.30	18.50
Vel Total (ft/s)	8.52	Avg. Vel. (ft/s)	3.26	9.41	4.33
Max Chl Dpth (ft)	8.61	Hydr. Depth (ft)	2.30	7.21	3.30
Conv. Total (cfs)	60646.1	Conv. (cfs)	955.0	55822.4	3868.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	9.83	56.99	19.64
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.59	2.08	0.91
Alpha	1.14	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.01	11.25	0.05
C & E Loss (ft)	0.10	Cum SA (acres)	0.01	1.90	0.04

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	12.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.63	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	10.56	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.76	Flow Area (sq ft)	29.19	459.78	101.34
E.G. Slope (ft/ft)	0.005052	Area (sq ft)	29.19	459.78	101.34
Q Total (cfs)	5290.00	Flow (cfs)	112.29	4883.80	293.91
Top Width (ft)	128.55	Top Width (ft)	10.50	56.30	61.76
Vel Total (ft/s)	8.96	Avg. Vel. (ft/s)	3.85	10.62	2.90
Max Chl Dpth (ft)	9.56	Hydr. Depth (ft)	2.78	8.17	1.64
Conv. Total (cfs)	74422.7	Conv. (cfs)	1579.8	68708.1	4134.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	11.88	56.99	62.99
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.78	2.54	0.51
Alpha	1.31	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.03	13.79	0.30
C & E Loss (ft)	0.20	Cum SA (acres)	0.03	1.97	0.44

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.57	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	12.53	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	11.04	Flow Area (sq ft)	53.50	570.57	227.26
E.G. Slope (ft/ft)	0.003944	Area (sq ft)	53.50	570.57	246.97
Q Total (cfs)	7380.00	Flow (cfs)	222.51	6183.78	973.71
Top Width (ft)	153.61	Top Width (ft)	14.21	56.30	83.10
Vel Total (ft/s)	8.67	Avg. Vel. (ft/s)	4.16	10.84	4.28
Max Chl Dpth (ft)	11.53	Hydr. Depth (ft)	3.77	10.13	3.55
Conv. Total (cfs)	117510.7	Conv. (cfs)	3543.0	98463.4	15504.2
Length Wtd. (ft)	20.00	Wetted Per. (ft)	16.08	56.99	65.34
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.82	2.47	0.86
Alpha	1.35	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.16	18.07	3.20
C & E Loss (ft)	0.18	Cum SA (acres)	0.09	2.00	1.85

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 830

INPUT
Description: A
Station Elevation Data num= 12

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	23	27.6	15	54.6	6	65	5	78	4
93.5	1	108.7	1	131.1	7	155	10	167.8	10
194.1	11	251.2	15						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	54.6	.035	131.1	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
54.6	131.1	9	9	.3	.5

Blocked Obstructions num= 1

Sta L	Sta R	Elev
205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.25	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	11.26	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	41.58	602.52	102.89
E.G. Slope (ft/ft)	0.003074	Area (sq ft)	41.58	602.52	102.89
Q Total (cfs)	5910.00	Flow (cfs)	126.11	5558.21	225.68
Top Width (ft)	159.08	Top Width (ft)	15.79	76.50	66.78
Vel Total (ft/s)	7.91	Avg. Vel. (ft/s)	3.03	9.22	2.19
Max Chl Dpth (ft)	10.26	Hydr. Depth (ft)	2.63	7.88	1.54
Conv. Total (cfs)	106589.9	Conv. (cfs)	2274.5	100245.2	4070.2
Length Wtd. (ft)	9.00	Wetted Per. (ft)	16.65	77.66	67.00
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.48	1.49	0.29
Alpha	1.28	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.04	14.77	0.74
C & E Loss (ft)	0.10	Cum SA (acres)	0.04	1.95	0.93

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.41	Wt. n-Val.	0.050	0.035	
W.S. Elev (ft)	6.74	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	0.81	256.24	

E.G. Slope (ft/ft)	0.002907	Area (sq ft)	0.81	256.24	
Q Total (cfs)	1312.00	Flow (cfs)	0.65	1311.35	
Top Width (ft)	77.73	Top Width (ft)	2.21	75.52	
Vel Total (ft/s)	5.10	Avg. Vel. (ft/s)	0.79	5.12	
Max Chl Dpth (ft)	5.74	Hydr. Depth (ft)	0.37	3.39	
Conv. Total (cfs)	24334.4	Conv. (cfs)	12.0	24322.4	
Length Wtd. (ft)	9.00	Wetted Per. (ft)	2.33	76.65	
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	0.61	
Alpha	1.00	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.00	4.54	0.00
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.50	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.05	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	9.32	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	16.52	453.66	21.42
E.G. Slope (ft/ft)	0.003638	Area (sq ft)	16.52	453.66	21.42
Q Total (cfs)	3850.00	Flow (cfs)	40.08	3767.76	42.16
Top Width (ft)	104.93	Top Width (ft)	9.96	76.50	18.47
Vel Total (ft/s)	7.83	Avg. Vel. (ft/s)	2.43	8.31	1.97
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	1.66	5.93	1.16
Conv. Total (cfs)	63831.9	Conv. (cfs)	664.6	62468.4	699.0
Length Wtd. (ft)	9.00	Wetted Per. (ft)	10.50	77.66	18.62
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.36	1.33	0.26
Alpha	1.10	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	10.43	0.02
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	1.84	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.71	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.09	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	9.62	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	19.70	477.00	27.43
E.G. Slope (ft/ft)	0.003539	Area (sq ft)	19.70	477.00	27.43
Q Total (cfs)	4148.00	Flow (cfs)	49.98	4040.20	57.82
Top Width (ft)	108.28	Top Width (ft)	10.87	76.50	20.91
Vel Total (ft/s)	7.91	Avg. Vel. (ft/s)	2.54	8.47	2.11
Max Chl Dpth (ft)	8.62	Hydr. Depth (ft)	1.81	6.24	1.31
Conv. Total (cfs)	69728.7	Conv. (cfs)	840.2	67916.6	971.9
Length Wtd. (ft)	9.00	Wetted Per. (ft)	11.46	77.66	21.07
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.38	1.36	0.29
Alpha	1.12	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.00	11.04	0.03

C & E Loss (ft)	0.07	Cum SA (acres)	0.01	1.87	0.03

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.23	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	10.68	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	32.89	557.96	67.02
E.G. Slope (ft/ft)	0.003296	Area (sq ft)	32.89	557.96	67.02
Q Total (cfs)	5290.00	Flow (cfs)	95.53	5063.76	130.71
Top Width (ft)	145.20	Top Width (ft)	14.05	76.50	54.65
Vel Total (ft/s)	8.04	Avg. Vel. (ft/s)	2.90	9.08	1.95
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)	2.34	7.29	1.23
Conv. Total (cfs)	92137.7	Conv. (cfs)	1663.9	88197.3	2276.6
Length Wtd. (ft)	9.00	Wetted Per. (ft)	14.81	77.66	54.85
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.46	1.48	0.25
Alpha	1.22	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.02	13.56	0.26
C & E Loss (ft)	0.10	Cum SA (acres)	0.02	1.94	0.41

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.21	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	12.65	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	66.36	708.58	203.58
E.G. Slope (ft/ft)	0.002508	Area (sq ft)	66.36	708.58	203.58
Q Total (cfs)	7380.00	Flow (cfs)	212.46	6578.08	589.46
Top Width (ft)	170.35	Top Width (ft)	19.95	76.50	73.90
Vel Total (ft/s)	7.54	Avg. Vel. (ft/s)	3.20	9.28	2.90
Max Chl Dpth (ft)	11.65	Hydr. Depth (ft)	3.33	9.26	2.75
Conv. Total (cfs)	147364.2	Conv. (cfs)	4242.5	131351.3	11770.4
Length Wtd. (ft)	9.00	Wetted Per. (ft)	21.03	77.66	75.02
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.49	1.43	0.42
Alpha	1.37	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.13	17.78	3.10
C & E Loss (ft)	0.08	Cum SA (acres)	0.08	1.97	1.81

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 821

INPUT

Description: AD

Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12	16.5	22	12.5	27	10.25	32	8	42	6.5
52	6	62	4.5	72	3.5	82	1.5	92	1
102	1	112	4	122	7	132	9	154	10
203	11.5	235	12						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12	.065	32	.035	132	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
32	132	1	1	.1	.3

Blocked Obstructions num= 1

Sta L	Sta R	Elev
205	235	25

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.39	Element			
Vel Head (ft)	1.05	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.34	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	12.37	698.68	69.60
E.G. Slope (ft/ft)	0.002923	Area (sq ft)	12.37	698.68	69.60
Q Total (cfs)	5910.00	Flow (cfs)	20.23	5800.40	89.38
Top Width (ft)	173.08	Top Width (ft)	7.42	100.00	65.67
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)	1.63	8.30	1.28
Max Chl Dpth (ft)	10.34	Hydr. Depth (ft)	1.67	6.99	1.06
Conv. Total (cfs)	109310.4	Conv. (cfs)	374.1	107283.2	1653.1
Length Wtd. (ft)	1.00	Wetted Per. (ft)	8.13	101.58	65.71
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.28	1.26	0.19
Alpha	1.18	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.03	14.64	0.73
C & E Loss (ft)	0.04	Cum SA (acres)	0.03	1.93	0.92

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.12	Element			
Vel Head (ft)	0.41	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.70	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)		253.80	
E.G. Slope (ft/ft)	0.003264	Area (sq ft)		253.80	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.33	Top Width (ft)		80.33	
Vel Total (ft/s)	5.17	Avg. Vel. (ft/s)		5.17	
Max Chl Dpth (ft)	5.70	Hydr. Depth (ft)		3.16	

Conv. Total (cfs)	22963.7	Conv. (cfs)		22963.7	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		81.57	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.63	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.00	4.49	0.00
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.49	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	9.35	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	2.03	500.07	1.35
E.G. Slope (ft/ft)	0.003921	Area (sq ft)	2.03	500.07	1.35
Q Total (cfs)	3850.00	Flow (cfs)	2.10	3847.29	0.61
Top Width (ft)	110.72	Top Width (ft)	3.00	100.00	7.72
Vel Total (ft/s)	7.65	Avg. Vel. (ft/s)	1.04	7.69	0.45
Max Chl Dpth (ft)	8.35	Hydr. Depth (ft)	0.68	5.00	0.18
Conv. Total (cfs)	61483.9	Conv. (cfs)	33.5	61440.7	9.7
Length Wtd. (ft)	1.00	Wetted Per. (ft)	3.29	101.58	7.72
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	1.21	0.04
Alpha	1.01	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.00	10.33	0.02
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.82	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.61	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.94	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	9.66	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	3.08	531.45	4.86
E.G. Slope (ft/ft)	0.003709	Area (sq ft)	3.08	531.45	4.86
Q Total (cfs)	4148.00	Flow (cfs)	3.57	4141.19	3.24
Top Width (ft)	118.32	Top Width (ft)	3.70	100.00	14.62
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	1.16	7.79	0.67
Max Chl Dpth (ft)	8.66	Hydr. Depth (ft)	0.83	5.31	0.33
Conv. Total (cfs)	68110.7	Conv. (cfs)	58.6	67999.0	53.2
Length Wtd. (ft)	1.00	Wetted Per. (ft)	4.06	101.58	14.63
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.18	1.21	0.08
Alpha	1.03	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.00	10.94	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.85	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.78	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.75	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	8.42	640.31	36.83
E.G. Slope (ft/ft)	0.003187	Area (sq ft)	8.42	640.31	36.83
Q Total (cfs)	5290.00	Flow (cfs)	12.65	5236.74	40.61
Top Width (ft)	152.72	Top Width (ft)	6.12	100.00	46.60
Vel Total (ft/s)	7.72	Avg. Vel. (ft/s)	1.50	8.18	1.10
Max Chl Dpth (ft)	9.75	Hydr. Depth (ft)	1.38	6.40	0.79
Conv. Total (cfs)	93710.0	Conv. (cfs)	224.0	92766.5	719.5
Length Wtd. (ft)	1.00	Wetted Per. (ft)	6.71	101.58	46.64
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.25	1.25	0.16
Alpha	1.11	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	13.44	0.25
C & E Loss (ft)	0.03	Cum SA (acres)	0.02	1.92	0.40

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.04	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	12.71	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	24.70	836.41	169.35
E.G. Slope (ft/ft)	0.002344	Area (sq ft)	24.70	836.41	169.35
Q Total (cfs)	7380.00	Flow (cfs)	45.39	7009.82	324.79
Top Width (ft)	183.54	Top Width (ft)	10.54	100.00	73.00
Vel Total (ft/s)	7.16	Avg. Vel. (ft/s)	1.84	8.38	1.92
Max Chl Dpth (ft)	11.71	Hydr. Depth (ft)	2.34	8.36	2.32
Conv. Total (cfs)	152445.9	Conv. (cfs)	937.6	144799.3	6709.1
Length Wtd. (ft)	1.00	Wetted Per. (ft)	11.54	101.58	74.23
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.31	1.20	0.33
Alpha	1.30	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.12	17.62	3.06
C & E Loss (ft)	0.06	Cum SA (acres)	0.08	1.95	1.80

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 820

INPUT
Description: ADD
Station Elevation Data num= 24

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	16.5	10	12.5	15	10.25	20	8	30	6.5
40	6	50	4.5	60	3.5	70	1.5	80	1

90	1	100	4	110	7	119.4	9	119.5	9		
142.2	10	142.3	10	150	10	160	10	170	11		
180	11	185.5	11.5	185.6	11.5	290	12				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	15	.035	142.3	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15	142.3	95	95	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.34	Element			
Vel Head (ft)	0.91	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.43	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	1.55	761.88	40.00
E.G. Slope (ft/ft)	0.003087	Area (sq ft)	1.55	761.88	40.00
Q Total (cfs)	5910.00	Flow (cfs)	1.30	5859.92	48.78
Top Width (ft)	172.37	Top Width (ft)	2.63	127.30	42.45
Vel Total (ft/s)	7.36	Avg. Vel. (ft/s)	0.84	7.69	1.22
Max Chl Dpth (ft)	10.43	Hydr. Depth (ft)	0.59	5.98	0.94
Conv. Total (cfs)	106370.9	Conv. (cfs)	23.5	105469.6	877.9
Length Wtd. (ft)	95.00	Wetted Per. (ft)	2.88	129.39	42.52
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.13	0.18
Alpha	1.08	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.03	14.62	0.73
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	1.93	0.92

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.11	Element			
Vel Head (ft)	0.42	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.70	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		253.43	
E.G. Slope (ft/ft)	0.003278	Area (sq ft)		253.43	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	80.29	Top Width (ft)		80.29	
Vel Total (ft/s)	5.18	Avg. Vel. (ft/s)		5.18	
Max Chl Dpth (ft)	5.70	Hydr. Depth (ft)		3.16	
Conv. Total (cfs)	22917.2	Conv. (cfs)		22917.2	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		81.52	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.64	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.00	4.48	0.00
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.48	0.00

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.91	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.35	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		502.71	
E.G. Slope (ft/ft)	0.004413	Area (sq ft)		502.71	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	110.46	Top Width (ft)		110.46	
Vel Total (ft/s)	7.66	Avg. Vel. (ft/s)		7.66	
Max Chl Dpth (ft)	8.35	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	57954.3	Conv. (cfs)		57954.3	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		112.35	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.23	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.49	Cum Volume (acre-ft)	0.00	10.32	0.02
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.82	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.59	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.68	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		540.00	
E.G. Slope (ft/ft)	0.004433	Area (sq ft)		540.00	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	118.58	Top Width (ft)		118.58	
Vel Total (ft/s)	7.68	Avg. Vel. (ft/s)		7.68	
Max Chl Dpth (ft)	8.68	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	62301.9	Conv. (cfs)		62301.9	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		120.54	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.24	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.48	Cum Volume (acre-ft)	0.00	10.93	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.85	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.83	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	0.37	685.12	18.10

E.G. Slope (ft/ft)	0.003558	Area (sq ft)	0.37	685.12	18.10
Q Total (cfs)	5290.00	Flow (cfs)	0.21	5270.42	19.37
Top Width (ft)	154.57	Top Width (ft)	1.29	127.30	25.99
Vel Total (ft/s)	7.52	Avg. Vel. (ft/s)	0.56	7.69	1.07
Max Chl Dpth (ft)	9.83	Hydr. Depth (ft)	0.29	5.38	0.70
Conv. Total (cfs)	88690.2	Conv. (cfs)	3.5	88361.8	324.8
Length Wtd. (ft)	95.00	Wetted Per. (ft)	1.41	129.39	26.03
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	1.18	0.15
Alpha	1.04	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.01	13.42	0.25
C & E Loss (ft)	0.01	Cum SA (acres)	0.02	1.92	0.40

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	12.85	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	7.54	942.66	216.48
E.G. Slope (ft/ft)	0.002211	Area (sq ft)	7.54	942.66	216.48
Q Total (cfs)	7380.00	Flow (cfs)	9.01	7071.98	299.01
Top Width (ft)	280.88	Top Width (ft)	5.88	127.30	147.70
Vel Total (ft/s)	6.33	Avg. Vel. (ft/s)	1.20	7.50	1.38
Max Chl Dpth (ft)	11.85	Hydr. Depth (ft)	1.28	7.41	1.47
Conv. Total (cfs)	156949.4	Conv. (cfs)	191.6	150398.7	6359.1
Length Wtd. (ft)	95.00	Wetted Per. (ft)	6.43	129.39	148.63
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.16	1.01	0.20
Alpha	1.35	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.12	17.60	3.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.08	1.95	1.79

Warning: The cross-section end points had to be extended vertically for the computed water surface.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 725

INPUT
Description: 10
10
Station Elevation Data num= 22

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	14	20	10	30	4	60	4
70	2.8	80	2.5	90	2.5	100	3	110	4.5
120	7.5	126	9	154	10	192	11	235	12

260	13	263	14	266	15	270	16	272	17
281	19	286	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	20	.04	126	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
20	126	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.98	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.20	714.06	59.80
E.G. Slope (ft/ft)	0.003914	Area (sq ft)	1.20	714.06	59.80
Q Total (cfs)	5910.00	Flow (cfs)	1.02	5828.36	80.62
Top Width (ft)	173.76	Top Width (ft)	2.45	106.00	65.31
Vel Total (ft/s)	7.63	Avg. Vel. (ft/s)	0.85	8.16	1.35
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)	0.49	6.74	0.92
Conv. Total (cfs)	94467.6	Conv. (cfs)	16.3	93162.6	1288.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.64	108.49	65.34
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.11	1.61	0.22
Alpha	1.13	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.03	13.01	0.62
C & E Loss (ft)	0.11	Cum SA (acres)	0.03	1.68	0.80

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	6.68	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.49	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.19	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		233.26	
E.G. Slope (ft/ft)	0.006471	Area (sq ft)		233.26	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	89.27	Top Width (ft)		89.27	
Vel Total (ft/s)	5.62	Avg. Vel. (ft/s)		5.62	
Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.61	
Conv. Total (cfs)	16310.2	Conv. (cfs)		16310.2	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		90.33	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.04	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	1.33	Cum Volume (acre-ft)	0.00	3.95	0.00
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.30	0.00

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	9.76	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.76	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		480.32	
E.G. Slope (ft/ft)	0.006140	Area (sq ft)		480.32	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	102.99	Top Width (ft)		102.99	
Vel Total (ft/s)	8.02	Avg. Vel. (ft/s)		8.02	
Max Chl Dpth (ft)	6.26	Hydr. Depth (ft)		4.66	
Conv. Total (cfs)	49134.6	Conv. (cfs)		49134.6	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		105.11	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.75	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.69	Cum Volume (acre-ft)	0.00	9.25	0.02
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.58	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.01	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.10	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		514.99	0.13
E.G. Slope (ft/ft)	0.005766	Area (sq ft)		514.99	0.13
Q Total (cfs)	4148.00	Flow (cfs)		4147.97	0.03
Top Width (ft)	107.22	Top Width (ft)		104.50	2.72
Vel Total (ft/s)	8.05	Avg. Vel. (ft/s)		8.05	0.23
Max Chl Dpth (ft)	6.60	Hydr. Depth (ft)		4.93	0.05
Conv. Total (cfs)	54626.0	Conv. (cfs)		54625.6	0.4
Length Wtd. (ft)	150.00	Wetted Per. (ft)		106.73	2.72
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.74	0.02
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.64	Cum Volume (acre-ft)	0.00	9.78	0.03
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.61	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.32	Reach Len. (ft)	150.00	150.00	150.00

Crit W.S. (ft)		Flow Area (sq ft)	0.13	644.27	25.04
E.G. Slope (ft/ft)	0.004495	Area (sq ft)	0.13	644.27	25.04
Q Total (cfs)	5290.00	Flow (cfs)	0.06	5262.01	27.94
Top Width (ft)	147.09	Top Width (ft)	0.81	106.00	40.28
Vel Total (ft/s)	7.90	Avg. Vel. (ft/s)	0.43	8.17	1.12
Max Chl Dpth (ft)	7.82	Hydr. Depth (ft)	0.16	6.08	0.62
Conv. Total (cfs)	78903.6	Conv. (cfs)	0.8	78486.0	416.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.87	108.49	40.31
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.04	1.67	0.17
Alpha	1.06	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.49	Cum Volume (acre-ft)	0.01	11.97	0.20
C & E Loss (ft)	0.12	Cum SA (acres)	0.02	1.66	0.33

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.44	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.95	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.49	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	7.72	873.50	204.41
E.G. Slope (ft/ft)	0.002895	Area (sq ft)	7.72	873.50	204.41
Q Total (cfs)	7380.00	Flow (cfs)	10.45	7013.32	356.23
Top Width (ft)	233.36	Top Width (ft)	6.21	106.00	121.15
Vel Total (ft/s)	6.80	Avg. Vel. (ft/s)	1.35	8.03	1.74
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	1.24	8.24	1.69
Conv. Total (cfs)	137168.8	Conv. (cfs)	194.3	130353.5	6621.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	6.69	108.49	121.20
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.21	1.46	0.30
Alpha	1.33	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.10	15.62	2.60
C & E Loss (ft)	0.10	Cum SA (acres)	0.06	1.70	1.50

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 575

INPUT
Description: 9
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	13.5	17	8.25	20	6	30	1.5
40	1.5	50	1.5	60	2.25	70	2.8	80	3.1
110	3.1	120	4	130	7	140	9	172	10
230	11	280	12	280.1	16				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	17	.04	140	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
17	140	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.82	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.39	904.54	61.45
E.G. Slope (ft/ft)	0.002176	Area (sq ft)	4.39	904.54	61.45
Q Total (cfs)	5910.00	Flow (cfs)	4.76	5849.98	55.25
Top Width (ft)	205.77	Top Width (ft)	3.42	123.00	79.35
Vel Total (ft/s)	6.09	Avg. Vel. (ft/s)	1.09	6.47	0.90
Max Chl Dpth (ft)	9.32	Hydr. Depth (ft)	1.28	7.35	0.77
Conv. Total (cfs)	126703.0	Conv. (cfs)	102.1	125416.3	1184.5
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.28	125.44	79.37
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.14	0.98	0.11
Alpha	1.12	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.02	10.23	0.41
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	1.28	0.55

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	5.33	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.64	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		197.15	
E.G. Slope (ft/ft)	0.012975	Area (sq ft)		197.15	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	99.11	Top Width (ft)		99.11	
Vel Total (ft/s)	6.65	Avg. Vel. (ft/s)		6.65	
Max Chl Dpth (ft)	3.14	Hydr. Depth (ft)		1.99	
Conv. Total (cfs)	11518.0	Conv. (cfs)		11518.0	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		99.96	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.60	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	1.16	Cum Volume (acre-ft)	0.00	3.21	0.00
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.97	0.00

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.

This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.000	0.040	
W.S. Elev (ft)	8.32	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.00	598.52	
E.G. Slope (ft/ft)	0.003596	Area (sq ft)	0.00	598.52	
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3850.00	
Top Width (ft)	119.69	Top Width (ft)	0.09	119.59	
Vel Total (ft/s)	6.43	Avg. Vel. (ft/s)	0.13	6.43	
Max Chl Dpth (ft)	6.82	Hydr. Depth (ft)	0.03	5.00	
Conv. Total (cfs)	64204.0	Conv. (cfs)	0.0	64204.0	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.11	121.97	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.10	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.00	7.39	0.02
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.20	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	9.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.71	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.14	645.69	
E.G. Slope (ft/ft)	0.003312	Area (sq ft)	0.14	645.69	
Q Total (cfs)	4148.00	Flow (cfs)	0.06	4147.94	
Top Width (ft)	122.16	Top Width (ft)	0.61	121.55	
Vel Total (ft/s)	6.42	Avg. Vel. (ft/s)	0.43	6.42	
Max Chl Dpth (ft)	7.21	Hydr. Depth (ft)	0.23	5.31	
Conv. Total (cfs)	72074.4	Conv. (cfs)	1.0	72073.3	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.77	123.96	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.04	1.08	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	7.78	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.22	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.65	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.10	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.28	816.53	19.52
E.G. Slope (ft/ft)	0.002487	Area (sq ft)	2.28	816.53	19.52
Q Total (cfs)	5290.00	Flow (cfs)	2.13	5273.56	14.31

Top Width (ft)	163.32	Top Width (ft)	2.47	123.00	37.85
Vel Total (ft/s)	6.31	Avg. Vel. (ft/s)	0.93	6.46	0.73
Max Chl Dpth (ft)	8.60	Hydr. Depth (ft)	0.93	6.64	0.52
Conv. Total (cfs)	106074.6	Conv. (cfs)	42.7	105745.0	286.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.08	125.44	37.87
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.11	1.01	0.08
Alpha	1.04	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.01	9.46	0.13
C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.27	0.19

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.41	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	11.53	1100.49	249.33
E.G. Slope (ft/ft)	0.001633	Area (sq ft)	11.53	1100.49	249.33
Q Total (cfs)	7380.00	Flow (cfs)	14.96	7027.33	337.70
Top Width (ft)	268.56	Top Width (ft)	5.55	123.00	140.01
Vel Total (ft/s)	5.42	Avg. Vel. (ft/s)	1.30	6.39	1.35
Max Chl Dpth (ft)	10.91	Hydr. Depth (ft)	2.08	8.95	1.78
Conv. Total (cfs)	182619.6	Conv. (cfs)	370.2	173892.8	8356.6
Length Wtd. (ft)	150.00	Wetted Per. (ft)	6.93	125.44	140.44
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.17	0.89	0.18
Alpha	1.32	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.23	Cum Volume (acre-ft)	0.07	12.22	1.81
C & E Loss (ft)	0.00	Cum SA (acres)	0.04	1.30	1.05

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 425

INPUT
Description: 8
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	11	12	9.8	20	5	30	0
70	0	80	.5	90	1.5	100	2	110	5.5
117.4	9	160	10	210	10	265	11	268	12
275	13	280	14						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	12	.04	117.4	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
12	117.4	90	90	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.16	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.65	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.51	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	0.42	902.74	76.06
E.G. Slope (ft/ft)	0.001827	Area (sq ft)	0.42	902.74	76.06
Q Total (cfs)	5910.00	Flow (cfs)	0.19	5855.22	54.59
Top Width (ft)	227.41	Top Width (ft)	1.19	105.40	120.82
Vel Total (ft/s)	6.04	Avg. Vel. (ft/s)	0.44	6.49	0.72
Max Chl Dpth (ft)	10.51	Hydr. Depth (ft)	0.36	8.56	0.63
Conv. Total (cfs)	138249.0	Conv. (cfs)	4.4	136967.6	1277.1
Length Wtd. (ft)	90.00	Wetted Per. (ft)	1.39	109.37	120.84
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.03	0.94	0.07
Alpha	1.14	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.01	7.11	0.17
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.89	0.21

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.46	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.64	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		241.53	
E.G. Slope (ft/ft)	0.005159	Area (sq ft)		241.53	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	81.94	Top Width (ft)		81.94	
Vel Total (ft/s)	5.43	Avg. Vel. (ft/s)		5.43	
Max Chl Dpth (ft)	3.64	Hydr. Depth (ft)		2.95	
Conv. Total (cfs)	18265.6	Conv. (cfs)		18265.6	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		83.16	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.94	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	2.46	0.00
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.66	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.57	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.94	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		635.41	

E.G. Slope (ft/ft)	0.002359	Area (sq ft)		635.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	100.05	Top Width (ft)		100.05	
Vel Total (ft/s)	6.06	Avg. Vel. (ft/s)		6.06	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)		6.35	
Conv. Total (cfs)	79260.7	Conv. (cfs)		79260.7	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		103.26	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.91	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.00	5.27	0.02
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.82	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.58	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.34	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		676.07	
E.G. Slope (ft/ft)	0.002277	Area (sq ft)		676.07	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	101.58	Top Width (ft)		101.58	
Vel Total (ft/s)	6.14	Avg. Vel. (ft/s)		6.14	
Max Chl Dpth (ft)	8.34	Hydr. Depth (ft)		6.66	
Conv. Total (cfs)	86926.8	Conv. (cfs)		86926.8	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		104.99	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.92	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.00	5.50	0.03
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.84	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.77	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		824.66	12.71
E.G. Slope (ft/ft)	0.002010	Area (sq ft)		824.66	12.71
Q Total (cfs)	5290.00	Flow (cfs)		5283.10	6.90
Top Width (ft)	138.26	Top Width (ft)		105.35	32.90
Vel Total (ft/s)	6.32	Avg. Vel. (ft/s)		6.41	0.54
Max Chl Dpth (ft)	9.77	Hydr. Depth (ft)		7.83	0.39
Conv. Total (cfs)	117990.1	Conv. (cfs)		117836.1	154.0
Length Wtd. (ft)	90.00	Wetted Per. (ft)		109.31	32.91
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.95	0.05
Alpha	1.03	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.01	6.63	0.07

C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.88	0.07

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.18	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	4.56	1078.68	318.10
E.G. Slope (ft/ft)	0.001414	Area (sq ft)	4.56	1078.68	318.10
Q Total (cfs)	7380.00	Flow (cfs)	4.02	6928.81	447.16
Top Width (ft)	260.97	Top Width (ft)	3.69	105.40	151.88
Vel Total (ft/s)	5.27	Avg. Vel. (ft/s)	0.88	6.42	1.41
Max Chl Dpth (ft)	12.18	Hydr. Depth (ft)	1.24	10.23	2.09
Conv. Total (cfs)	196291.8	Conv. (cfs)	107.0	184291.2	11893.6
Length Wtd. (ft)	90.00	Wetted Per. (ft)	4.39	109.37	152.07
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.09	0.87	0.18
Alpha	1.40	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.04	8.47	0.84
C & E Loss (ft)	0.04	Cum SA (acres)	0.03	0.91	0.55

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 335

INPUT
Description: 7
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	12.5	18	8.1	20	7	30	1.5
40	-.5	50	-2	60	-2	70	-2	80	0
90	4	100	9	135	10	175	10	205	11
260	11	260.1	16						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	18	.04	100	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
18	100	73	73	73	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065

W.S. Elev (ft)	9.90	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	2.96	726.97	14.28
E.G. Slope (ft/ft)	0.002776	Area (sq ft)	2.96	726.97	14.28
Q Total (cfs)	5910.00	Flow (cfs)	3.04	5896.84	10.12
Top Width (ft)	116.89	Top Width (ft)	3.28	82.00	31.61
Vel Total (ft/s)	7.94	Avg. Vel. (ft/s)	1.03	8.11	0.71
Max Chl Dpth (ft)	11.90	Hydr. Depth (ft)	0.90	8.87	0.45
Conv. Total (cfs)	112178.6	Conv. (cfs)	57.8	111928.8	192.1
Length Wtd. (ft)	73.00	Wetted Per. (ft)	3.74	86.15	31.63
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.14	1.46	0.08
Alpha	1.04	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.28	Cum Volume (acre-ft)	0.01	5.43	0.08
C & E Loss (ft)	0.07	Cum SA (acres)	0.01	0.70	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.68	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.18	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		231.87	
E.G. Slope (ft/ft)	0.004046	Area (sq ft)		231.87	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	61.02	Top Width (ft)		61.02	
Vel Total (ft/s)	5.66	Avg. Vel. (ft/s)		5.66	
Max Chl Dpth (ft)	5.18	Hydr. Depth (ft)		3.80	
Conv. Total (cfs)	20627.0	Conv. (cfs)		20627.0	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		62.57	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		0.94	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.37	Cum Volume (acre-ft)	0.00	1.97	0.00
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.52	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.23	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.40	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		524.52	
E.G. Slope (ft/ft)	0.003241	Area (sq ft)		524.52	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	77.52	Top Width (ft)		77.52	

Vel Total (ft/s)	7.34	Avg. Vel. (ft/s)		7.34	
Max Chl Dpth (ft)	9.40	Hydr. Depth (ft)		6.77	
Conv. Total (cfs)	67630.2	Conv. (cfs)		67630.2	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		81.11	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.31	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.00	4.07	0.02
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.64	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.66	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.79	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		555.22	
E.G. Slope (ft/ft)	0.003199	Area (sq ft)		555.22	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	79.02	Top Width (ft)		79.02	
Vel Total (ft/s)	7.47	Avg. Vel. (ft/s)		7.47	
Max Chl Dpth (ft)	9.79	Hydr. Depth (ft)		7.03	
Conv. Total (cfs)	73340.6	Conv. (cfs)		73340.6	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		82.80	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.34	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.00	4.23	0.03
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.65	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.16	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.18	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	1.07	667.92	0.59
E.G. Slope (ft/ft)	0.002961	Area (sq ft)	1.07	667.92	0.59
Q Total (cfs)	5290.00	Flow (cfs)	0.81	5289.04	0.15
Top Width (ft)	90.38	Top Width (ft)	1.97	82.00	6.41
Vel Total (ft/s)	7.90	Avg. Vel. (ft/s)	0.76	7.92	0.25
Max Chl Dpth (ft)	11.18	Hydr. Depth (ft)	0.54	8.15	0.09

Conv. Total (cfs)	97208.9	Conv. (cfs)	14.8	97191.4	2.7
Length Wtd. (ft)	73.00	Wetted Per. (ft)	2.25	86.15	6.41
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.09	1.43	0.02
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	5.09	0.06
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.68	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.59	Element			
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.57	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	10.93	863.45	198.34
E.G. Slope (ft/ft)	0.002277	Area (sq ft)	10.93	863.45	198.34
Q Total (cfs)	7380.00	Flow (cfs)	15.76	7115.18	249.06
Top Width (ft)	248.32	Top Width (ft)	6.30	82.00	160.01
Vel Total (ft/s)	6.88	Avg. Vel. (ft/s)	1.44	8.24	1.26
Max Chl Dpth (ft)	13.57	Hydr. Depth (ft)	1.73	10.53	1.24
Conv. Total (cfs)	154651.5	Conv. (cfs)	330.3	149102.0	5219.2
Length Wtd. (ft)	73.00	Wetted Per. (ft)	7.20	86.15	160.60
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.22	1.42	0.18
Alpha	1.38	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.02	6.46	0.30
C & E Loss (ft)	0.08	Cum SA (acres)	0.02	0.72	0.23

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 262

INPUT
Description: 6
6
6
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	7	9.1	10	7	20	1	30	-2
40	-3	50	-3	60	0	70	5	80	9.5
135	11	175	12	255	13	282	14		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	7	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
7	80	75	75	75	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.57	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.74	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.83	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		558.57	
E.G. Slope (ft/ft)	0.005707	Area (sq ft)		558.57	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	71.13	Top Width (ft)		71.13	
Vel Total (ft/s)	10.58	Avg. Vel. (ft/s)		10.58	
Max Chl Dpth (ft)	11.83	Hydr. Depth (ft)		7.85	
Conv. Total (cfs)	78231.2	Conv. (cfs)		78231.2	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		76.30	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.61	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	4.35	0.07
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.57	0.02

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.46	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		181.27	
E.G. Slope (ft/ft)	0.006684	Area (sq ft)		181.27	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.36	Top Width (ft)		47.36	
Vel Total (ft/s)	7.24	Avg. Vel. (ft/s)		7.24	
Max Chl Dpth (ft)	5.46	Hydr. Depth (ft)		3.83	
Conv. Total (cfs)	16047.3	Conv. (cfs)		16047.3	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		49.27	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		1.54	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.44	Cum Volume (acre-ft)	0.00	1.62	0.00
C & E Loss (ft)	0.04	Cum SA (acres)	0.00	0.42	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.85	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.48	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.37	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		394.89	
E.G. Slope (ft/ft)	0.006329	Area (sq ft)		394.89	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.01	Top Width (ft)		62.01	
Vel Total (ft/s)	9.75	Avg. Vel. (ft/s)		9.75	
Max Chl Dpth (ft)	9.37	Hydr. Depth (ft)		6.37	
Conv. Total (cfs)	48392.9	Conv. (cfs)		48392.9	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		65.91	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.37	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.00	3.30	0.02
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.52	0.01

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.74	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		418.05	
E.G. Slope (ft/ft)	0.006275	Area (sq ft)		418.05	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	63.45	Top Width (ft)		63.45	
Vel Total (ft/s)	9.92	Avg. Vel. (ft/s)		9.92	
Max Chl Dpth (ft)	9.74	Hydr. Depth (ft)		6.59	
Conv. Total (cfs)	52362.1	Conv. (cfs)		52362.1	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		67.52	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.43	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.00	3.42	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.53	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.10	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		507.69	
E.G. Slope (ft/ft)	0.005954	Area (sq ft)		507.69	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	

Top Width (ft)	68.47	Top Width (ft)		68.47	
Vel Total (ft/s)	10.42	Avg. Vel. (ft/s)		10.42	
Max Chl Dpth (ft)	11.10	Hydr. Depth (ft)		7.41	
Conv. Total (cfs)	68556.3	Conv. (cfs)		68556.3	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		73.25	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.00	4.10	0.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.56	0.02

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.85	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.41	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	1.23	673.56	15.31
E.G. Slope (ft/ft)	0.004923	Area (sq ft)	1.23	673.56	15.31
Q Total (cfs)	7380.00	Flow (cfs)	1.31	7364.13	14.57
Top Width (ft)	108.39	Top Width (ft)	1.88	73.00	33.51
Vel Total (ft/s)	10.69	Avg. Vel. (ft/s)	1.06	10.93	0.95
Max Chl Dpth (ft)	13.41	Hydr. Depth (ft)	0.66	9.23	0.46
Conv. Total (cfs)	105185.4	Conv. (cfs)	18.7	104959.1	207.6
Length Wtd. (ft)	75.00	Wetted Per. (ft)	2.29	78.40	33.52
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.17	2.64	0.14
Alpha	1.04	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.01	5.17	0.13
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	0.59	0.06

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 187

INPUT
Description: 5
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	8	9.2	10	8	20	1.5	30	-2.5
40	-4	50	-4	60	-1	70	4	80	9.5
115	13	141	13	185	14				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	80	50	50	.1	.3

Ineffective Flow num= 1

Sta L	Sta R	Elev	Permanent
84	185	14.5	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.70	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.44	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.94	Flow Area (sq ft)		564.77	
E.G. Slope (ft/ft)	0.005330	Area (sq ft)		564.77	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	68.82	Top Width (ft)		68.82	
Vel Total (ft/s)	10.46	Avg. Vel. (ft/s)		10.46	
Max Chl Dpth (ft)	12.44	Hydr. Depth (ft)		8.21	
Conv. Total (cfs)	80952.3	Conv. (cfs)		80952.3	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		74.52	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.52	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	3.39	0.07
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.45	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	2.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.11	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	0.60	Flow Area (sq ft)		197.00	
E.G. Slope (ft/ft)	0.005083	Area (sq ft)		197.00	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.17	Top Width (ft)		47.17	
Vel Total (ft/s)	6.66	Avg. Vel. (ft/s)		6.66	
Max Chl Dpth (ft)	6.11	Hydr. Depth (ft)		4.18	
Conv. Total (cfs)	18401.8	Conv. (cfs)		18401.8	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		49.41	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		1.27	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.00	1.30	0.00
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.34	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water

surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.40	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.98	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.99	Flow Area (sq ft)		405.37	
E.G. Slope (ft/ft)	0.005674	Area (sq ft)		405.37	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	60.48	Top Width (ft)		60.48	
Vel Total (ft/s)	9.50	Avg. Vel. (ft/s)		9.50	
Max Chl Dpth (ft)	9.98	Hydr. Depth (ft)		6.70	
Conv. Total (cfs)	51112.5	Conv. (cfs)		51112.5	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		64.82	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.00	2.61	0.02
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.42	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.46	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.34	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.29	Flow Area (sq ft)		427.77	
E.G. Slope (ft/ft)	0.005668	Area (sq ft)		427.77	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	61.72	Top Width (ft)		61.72	
Vel Total (ft/s)	9.70	Avg. Vel. (ft/s)		9.70	
Max Chl Dpth (ft)	10.34	Hydr. Depth (ft)		6.93	
Conv. Total (cfs)	55097.6	Conv. (cfs)		55097.6	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		66.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.28	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.00	2.69	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.42	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.64	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.71	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.39	Flow Area (sq ft)		515.03	
E.G. Slope (ft/ft)	0.005505	Area (sq ft)		515.03	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	66.29	Top Width (ft)		66.29	
Vel Total (ft/s)	10.27	Avg. Vel. (ft/s)		10.27	
Max Chl Dpth (ft)	11.71	Hydr. Depth (ft)		7.77	
Conv. Total (cfs)	71301.0	Conv. (cfs)		71301.0	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		71.59	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.47	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.00	3.22	0.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.44	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.07	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	7.13	Flow Area (sq ft)	0.63	680.26	1.48
E.G. Slope (ft/ft)	0.004763	Area (sq ft)	0.63	680.26	1.62
Q Total (cfs)	7380.00	Flow (cfs)	0.51	7378.29	1.19
Top Width (ft)	79.14	Top Width (ft)	1.45	72.00	5.69
Vel Total (ft/s)	10.82	Avg. Vel. (ft/s)	0.82	10.85	0.81
Max Chl Dpth (ft)	14.07	Hydr. Depth (ft)	0.43	9.45	0.37
Conv. Total (cfs)	106933.9	Conv. (cfs)	7.4	106909.2	17.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.69	78.17	4.02
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.11	2.59	0.11
Alpha	1.01	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	4.01	0.11
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	0.46	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 166

```
INPUT
Description: Pedestrian Bridge
Distance from Upstream XS =      21
Deck/Roadway Width        =      14
Weir Coefficient          =     2.6
Upstream  Deck/Roadway Coordinates
    num=       6
     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord
       0      16       0       6      16       0       6      16      14
      81      14      12      81      14       0     115      13       0

Upstream Bridge Cross Section Data
Station Elevation Data    num=      13
     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev
       0      14       8     9.2      10       8      20     1.5      30    -2.5
      40      -4      50      -4      60      -1      70       4      80     9.5
     115      13     141      13     185      14

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
       0    .065       8     .04      80    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
            8      80            .1       .3
Ineffective Flow     num=       1
   Sta L   Sta R    Elev  Permanent
      84     185    14.5       F

Downstream  Deck/Roadway Coordinates
    num=       6
     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord
       0      16       0       6      16       0       6      16      14
      81      14      12      81      14       0     115      13       0

Downstream Bridge Cross Section Data
Station Elevation Data    num=      10
     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev
       0      14      10     8.3      20     2.5      30    -2.5      40    -3.7
      50      -4      60      -2      70       3      80       9      90      14

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
       0    .065      10     .04      80    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
           10      80            .3       .5
Ineffective Flow     num=       1
   Sta L   Sta R    Elev  Permanent
```

84 90 14.5 F

Upstream Embankment side slope = 0 horiz. to 1.0 vertical
Downstream Embankment side slope = 0 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow = .98
Elevation at which weir flow begins =
Energy head used in spillway design =
Spillway height used in design =
Weir crest shape = Broad Crested

Number of Bridge Coefficient Sets = 1

Low Flow Methods and Data
Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
Energy Only

Additional Bridge Parameters
Add Friction component to Momentum
Do not add Weight component to Momentum
Class B flow critical depth computations use critical depth
inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Element	Inside BR US	Inside BR DS
E.G. US. (ft)	10.14		E.G. Elev (ft)	10.02	9.93
W.S. US. (ft)	8.44		W.S. Elev (ft)	8.22	8.15
Q Total (cfs)	5910.00		Crit W.S. (ft)	5.94	5.85
Q Bridge (cfs)	5910.00		Max Chl Dpth (ft)	12.22	12.15
Q Weir (cfs)			Vel Total (ft/s)	10.75	10.71
Weir Sta Lft (ft)			Flow Area (sq ft)	549.69	551.62
Weir Sta Rgt (ft)			Froude # Chl	0.67	0.66
Weir Submerg			Specif Force (cu ft)	4682.83	4678.50
Weir Max Depth (ft)			Hydr Depth (ft)	8.08	8.07
Min El Weir Flow (ft)	13.92		W.P. Total (ft)	73.63	73.91
Min El Prs (ft)	14.00		Conv. Total (cfs)	78001.3	78262.5
Delta EG (ft)	0.31		Top Width (ft)	68.05	68.32
Delta WS (ft)	0.47		Frctn Loss (ft)	0.08	0.09
BR Open Area (sq ft)	901.15		C & E Loss (ft)	0.00	0.01
BR Open Vel (ft/s)	10.75		Shear Total (lb/sq ft)	2.68	2.66
Coef of Q			Power Total (lb/ft s)	0.00	0.00
Br Sel Method	Energy only				

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water

surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

E.G. US. (ft)	2.80	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	2.11	E.G. Elev (ft)	2.68	2.60
Q Total (cfs)	1312.00	W.S. Elev (ft)	1.93	1.85
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.59	0.50
Q Weir (cfs)		Max Chl Dpth (ft)	5.93	5.85
Weir Sta Lft (ft)		Vel Total (ft/s)	6.97	6.96
Weir Sta Rgt (ft)		Flow Area (sq ft)	188.32	188.64
Weir Submerg		Froude # Chl	0.61	0.61
Weir Max Depth (ft)		Specif Force (cu ft)	740.84	734.29
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	4.05	4.07
Min El Prs (ft)	14.00	W.P. Total (ft)	48.65	48.60
Delta EG (ft)	0.30	Conv. Total (cfs)	17246.4	17307.2
Delta WS (ft)	0.42	Top Width (ft)	46.51	46.39
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.08	0.09
BR Open Vel (ft/s)	6.97	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	1.40	1.39
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	7.38	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	5.98	E.G. Elev (ft)	7.24	7.15
Q Total (cfs)	3850.00	W.S. Elev (ft)	5.73	5.65
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.98	3.90
Q Weir (cfs)		Max Chl Dpth (ft)	9.73	9.65
Weir Sta Lft (ft)		Vel Total (ft/s)	9.85	9.84
Weir Sta Rgt (ft)		Flow Area (sq ft)	390.78	391.30
Weir Submerg		Froude # Chl	0.68	0.68
Weir Max Depth (ft)		Specif Force (cu ft)	2721.40	2713.38
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	6.55	6.54
Min El Prs (ft)	14.00	W.P. Total (ft)	63.87	64.06
Delta EG (ft)	0.34	Conv. Total (cfs)	48559.3	48573.6
Delta WS (ft)	0.54	Top Width (ft)	59.67	59.84
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.09	0.10
BR Open Vel (ft/s)	9.85	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.40	2.40

Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	7.80	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	6.34	E.G. Elev (ft)	7.67	7.58
Q Total (cfs)	4148.00	W.S. Elev (ft)	6.10	6.01
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.29	4.20
Q Weir (cfs)		Max Chl Dpth (ft)	10.10	10.01
Weir Sta Lft (ft)		Vel Total (ft/s)	10.05	10.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	412.84	413.47
Weir Submerg		Froude # Chl	0.68	0.68
Weir Max Depth (ft)		Specif Force (cu ft)	2984.76	2976.88
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	6.78	6.77
Min El Prs (ft)	14.00	W.P. Total (ft)	65.30	65.50
Delta EG (ft)	0.33	Conv. Total (cfs)	52432.9	52462.7
Delta WS (ft)	0.54	Top Width (ft)	60.90	61.09
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.09	0.10
BR Open Vel (ft/s)	10.05	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.47	2.46
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	9.35	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	7.71	E.G. Elev (ft)	9.21	9.13
Q Total (cfs)	5290.00	W.S. Elev (ft)	7.47	7.40
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.40	5.30
Q Weir (cfs)		Max Chl Dpth (ft)	11.47	11.40
Weir Sta Lft (ft)		Vel Total (ft/s)	10.59	10.56
Weir Sta Rgt (ft)		Flow Area (sq ft)	499.65	501.01
Weir Submerg		Froude # Chl	0.68	0.67
Weir Max Depth (ft)		Specif Force (cu ft)	4055.74	4049.51
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	7.63	7.62
Min El Prs (ft)	14.00	W.P. Total (ft)	70.67	70.93
Delta EG (ft)	0.32	Conv. Total (cfs)	68369.7	68513.6

Delta WS (ft)	0.50	Top Width (ft)	65.51	65.77
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.08	0.09
BR Open Vel (ft/s)	10.59	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.64	2.63
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

			Inside BR US	Inside BR DS
E.G. US. (ft)	11.90	Element		
W.S. US. (ft)	10.07	E.G. Elev (ft)	11.78	11.71
Q Total (cfs)	7380.00	W.S. Elev (ft)	9.88	9.82
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	7.13	7.04
Q Weir (cfs)		Max Chl Dpth (ft)	13.88	13.82
Weir Sta Lft (ft)		Vel Total (ft/s)	11.05	11.01
Weir Sta Rgt (ft)		Flow Area (sq ft)	667.59	670.26
Weir Submerg		Froude # Chl	0.52	0.52
Weir Max Depth (ft)		Specif Force (cu ft)	6253.85	6260.42
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	9.00	9.10
Min El Prs (ft)	14.00	W.P. Total (ft)	80.51	80.04
Delta EG (ft)	0.26	Conv. Total (cfs)	103433.0	105776.4
Delta WS (ft)	0.39	Top Width (ft)	74.14	73.66
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.07	0.07
BR Open Vel (ft/s)	11.05	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.64	2.54
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 137

INPUT
Description: 4
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev

0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	80	77	77	.3	.5

Ineffective Flow num= 1

Sta L	Sta R	Elev	Permanent
84	90	14.5	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	9.84	Element			
Vel Head (ft)	1.86	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.97	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.85	Flow Area (sq ft)		539.62	
E.G. Slope (ft/ft)	0.006060	Area (sq ft)		539.62	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	67.73	Top Width (ft)		67.73	
Vel Total (ft/s)	10.95	Avg. Vel. (ft/s)		10.95	
Max Chl Dpth (ft)	11.97	Hydr. Depth (ft)		7.97	
Conv. Total (cfs)	75920.1	Conv. (cfs)		75920.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		73.21	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.79	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)	0.01	2.75	0.07
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.37	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	2.50	Element			
Vel Head (ft)	0.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.69	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	0.51	Flow Area (sq ft)		181.49	
E.G. Slope (ft/ft)	0.006412	Area (sq ft)		181.49	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	45.77	Top Width (ft)		45.77	
Vel Total (ft/s)	7.23	Avg. Vel. (ft/s)		7.23	
Max Chl Dpth (ft)	5.69	Hydr. Depth (ft)		3.97	
Conv. Total (cfs)	16384.2	Conv. (cfs)		16384.2	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		47.91	

Min Ch El (ft)	-4.00	Shear (lb/sq ft)		1.52	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.21	Cum Volume (acre-ft)	0.00	1.08	0.00
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.29	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.44	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.89	Flow Area (sq ft)		378.85	
E.G. Slope (ft/ft)	0.006877	Area (sq ft)		378.85	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	59.13	Top Width (ft)		59.13	
Vel Total (ft/s)	10.16	Avg. Vel. (ft/s)		10.16	
Max Chl Dpth (ft)	9.44	Hydr. Depth (ft)		6.41	
Conv. Total (cfs)	46424.9	Conv. (cfs)		46424.9	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		63.23	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.57	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.00	2.16	0.02
C & E Loss (ft)	0.14	Cum SA (acres)	0.00	0.35	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.47	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.66	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.81	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		400.81	
E.G. Slope (ft/ft)	0.006819	Area (sq ft)		400.81	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	60.38	Top Width (ft)		60.38	
Vel Total (ft/s)	10.35	Avg. Vel. (ft/s)		10.35	
Max Chl Dpth (ft)	9.81	Hydr. Depth (ft)		6.64	
Conv. Total (cfs)	50233.4	Conv. (cfs)		50233.4	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		64.68	

Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.64	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.00	2.21	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.35	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.02	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.82	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.20	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.30	Flow Area (sq ft)		488.44	
E.G. Slope (ft/ft)	0.006396	Area (sq ft)		488.44	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.11	Top Width (ft)		65.11	
Vel Total (ft/s)	10.83	Avg. Vel. (ft/s)		10.83	
Max Chl Dpth (ft)	11.20	Hydr. Depth (ft)		7.50	
Conv. Total (cfs)	66144.0	Conv. (cfs)		66144.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		70.18	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.78	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.00	2.65	0.06
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	0.36	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.63	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.95	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.68	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	7.04	Flow Area (sq ft)	1.67	658.13	0.46
E.G. Slope (ft/ft)	0.005108	Area (sq ft)	1.67	658.13	0.46
Q Total (cfs)	7380.00	Flow (cfs)	1.94	7377.72	0.34
Top Width (ft)	73.78	Top Width (ft)	2.42	70.00	1.36
Vel Total (ft/s)	11.18	Avg. Vel. (ft/s)	1.16	11.21	0.74
Max Chl Dpth (ft)	13.68	Hydr. Depth (ft)	0.69	9.40	0.34
Conv. Total (cfs)	103257.5	Conv. (cfs)	27.2	103225.6	4.8
Length Wtd. (ft)	22.00	Wetted Per. (ft)	2.79	75.86	1.52
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.19	2.77	0.10
Alpha	1.01	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	3.24	0.11
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.38	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 98.5

INPUT
Description: Maine Ave.
Distance from Upstream XS = 22
Deck/Roadway Width = 38
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	15.2	-10	4.5	15.2	-10
4.5	15.2	11.5	79.5	15.2	-10
100	15	-10			

Upstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left Right Coeff Contr. Expan.
10 80 .3 .5
Ineffective Flow num= 1

Sta L	Sta R	Elev	Permanent
84	90	14.5	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	15.2	-10	4.5	15.2	-10
4.5	15.2	11.5	79.5	15.2	-10
100	15	-10			

Downstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
13.5	14	15.2	3	25.3	-4	33.6	-5	48.2	-5

```
    52.6      -4    65.7       0    76.2       7    80.2     8.5    80.3      12

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
    13.5    .065    15.2     .04    65.7    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
          15.2    65.7             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
    13.5      16      15       F
      72    80.3      15       F

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =      .1 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Bridge Coefficient Sets =  1

Low Flow Methods and Data
       Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
       Energy Only

Additional Bridge Parameters
       Add Friction component to Momentum
       Do not add Weight component to Momentum
       Class B flow critical depth computations use critical depth
           inside the bridge at the upstream end
       Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT  Profile #Q100

  E.G. US. (ft)                  9.84    Element                Inside BR US  Inside BR DS
  W.S. US. (ft)                  7.97    E.G. Elev (ft)                 9.62          9.28
  Q Total (cfs)               5910.00    W.S. Elev (ft)                 7.55          7.51
  Q Bridge (cfs)              5910.00    Crit W.S. (ft)                 5.85          4.37
  Q Weir (cfs)                           Max Chl Dpth (ft)             11.55         12.51
  Weir Sta Lft (ft)                      Vel Total (ft/s)              11.57         10.35
  Weir Sta Rgt (ft)                      Flow Area (sq ft)            510.99        571.03
  Weir Submerg                           Froude # Chl                   0.73          0.58
  Weir Max Depth (ft)                    Specif Force (cu ft)        4514.16       5040.94
```

Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	7.71	10.20
Min El Prs (ft)	11.50	W.P. Total (ft)	71.53	60.06
Delta EG (ft)	0.63	Conv. Total (cfs)	70410.5	96122.0
Delta WS (ft)	0.57	Top Width (ft)	66.28	63.06
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.19	0.07
BR Open Vel (ft/s)	11.57	C & E Loss (ft)	0.16	0.01
Coef of Q		Shear Total (lb/sq ft)	3.14	2.24
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

E.G. US. (ft)	2.50	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	1.69	E.G. Elev (ft)	2.09	1.38
Q Total (cfs)	1312.00	W.S. Elev (ft)	0.60	0.72
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.50	-0.83
Q Weir (cfs)		Max Chl Dpth (ft)	4.60	5.72
Weir Sta Lft (ft)		Vel Total (ft/s)	9.80	6.50
Weir Sta Rgt (ft)		Flow Area (sq ft)	133.86	201.78
Weir Submerg		Froude # Chl	0.96	0.56
Weir Max Depth (ft)		Specif Force (cu ft)	649.68	759.81
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	3.23	4.18
Min El Prs (ft)	11.50	W.P. Total (ft)	43.02	50.74
Delta EG (ft)	1.23	Conv. Total (cfs)	10598.2	19083.1
Delta WS (ft)	1.12	Top Width (ft)	41.40	48.28
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.30	0.08
BR Open Vel (ft/s)	9.80	C & E Loss (ft)	0.42	0.01
Coef of Q		Shear Total (lb/sq ft)	2.98	1.17
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	7.04	Element	Inside BR US	Inside BR DS

W.S. US. (ft)	5.44	E.G. Elev (ft)	6.73	6.15
Q Total (cfs)	3850.00	W.S. Elev (ft)	4.66	4.76
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.90	2.44
Q Weir (cfs)		Max Chl Dpth (ft)	8.66	9.76
Weir Sta Lft (ft)		Vel Total (ft/s)	11.53	9.24
Weir Sta Rgt (ft)		Flow Area (sq ft)	333.83	416.76
Weir Submerg		Froude # Chl	0.84	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	2557.97	2861.60
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	5.91	7.44
Min El Prs (ft)	11.50	W.P. Total (ft)	60.17	60.06
Delta EG (ft)	0.99	Conv. Total (cfs)	38865.9	58200.4
Delta WS (ft)	0.83	Top Width (ft)	56.49	57.91
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.24	0.08
BR Open Vel (ft/s)	11.53	C & E Loss (ft)	0.34	0.02
Coef of Q		Shear Total (lb/sq ft)	3.40	1.90
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	7.47	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	5.81	E.G. Elev (ft)	7.17	6.63
Q Total (cfs)	4148.00	W.S. Elev (ft)	5.10	5.18
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.20	2.74
Q Weir (cfs)		Max Chl Dpth (ft)	9.10	10.18
Weir Sta Lft (ft)		Vel Total (ft/s)	11.56	9.42
Weir Sta Rgt (ft)		Flow Area (sq ft)	358.94	440.42
Weir Submerg		Froude # Chl	0.82	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	2819.66	3154.92
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	6.19	7.86
Min El Prs (ft)	11.50	W.P. Total (ft)	61.89	60.06
Delta EG (ft)	0.93	Conv. Total (cfs)	43039.6	63503.1
Delta WS (ft)	0.77	Top Width (ft)	57.98	58.61
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.23	0.07
BR Open Vel (ft/s)	11.56	C & E Loss (ft)	0.31	0.02
Coef of Q		Shear Total (lb/sq ft)	3.36	1.95
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

			Inside BR US	Inside BR DS
E.G. US. (ft)	9.02	Element		
W.S. US. (ft)	7.20	E.G. Elev (ft)	8.79	8.38
Q Total (cfs)	5290.00	W.S. Elev (ft)	6.71	6.72
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.30	3.80
Q Weir (cfs)		Max Chl Dpth (ft)	10.71	11.72
Weir Sta Lft (ft)		Vel Total (ft/s)	11.58	10.05
Weir Sta Rgt (ft)		Flow Area (sq ft)	456.68	526.54
Weir Submerg		Froude # Chl	0.76	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	3889.39	4348.86
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	7.20	9.40
Min El Prs (ft)	11.50	W.P. Total (ft)	68.23	60.06
Delta EG (ft)	0.72	Conv. Total (cfs)	60250.1	84392.2
Delta WS (ft)	0.60	Top Width (ft)	63.44	61.15
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.20	0.07
BR Open Vel (ft/s)	11.58	C & E Loss (ft)	0.21	0.01
Coef of Q		Shear Total (lb/sq ft)	3.22	2.15
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

			Inside BR US	Inside BR DS
E.G. US. (ft)	11.63	Element		
W.S. US. (ft)	9.68	E.G. Elev (ft)	11.48	11.27
Q Total (cfs)	7380.00	W.S. Elev (ft)	9.40	9.27
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	7.04	5.55
Q Weir (cfs)		Max Chl Dpth (ft)	13.40	14.27
Weir Sta Lft (ft)		Vel Total (ft/s)	11.54	11.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	639.25	669.32
Weir Submerg		Froude # Chl	0.56	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	6105.25	6773.86
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	8.95	11.95
Min El Prs (ft)	11.50	W.P. Total (ft)	77.49	60.06

Delta EG (ft)	0.43	Conv. Total (cfs)	98586.1	124198.6
Delta WS (ft)	0.52	Top Width (ft)	71.43	65.27
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.17	0.06
BR Open Vel (ft/s)	11.54	C & E Loss (ft)	0.03	0.01
Coef of Q		Shear Total (lb/sq ft)	2.89	2.46
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 60

INPUT
Description: 3
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
13.5	14	15.2	3	25.3	-4	33.6	-5	48.2	-5
52.6	-4	65.7	0	76.2	7	80.2	8.5	80.3	12

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
13.5	.065	15.2	.04	65.7	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15.2	65.7	22	22	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
13.5	16	15	F
72	80.3	15	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	9.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.80	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	7.40	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.37	Flow Area (sq ft)		531.34	33.39
E.G. Slope (ft/ft)	0.003918	Area (sq ft)	1.50	535.08	41.16
Q Total (cfs)	5910.00	Flow (cfs)		5781.54	128.46
Top Width (ft)	62.75	Top Width (ft)	0.68	50.50	11.57
Vel Total (ft/s)	10.47	Avg. Vel. (ft/s)		10.88	3.85
Max Chl Dpth (ft)	12.40	Hydr. Depth (ft)		10.69	5.30

Conv. Total (cfs)	94422.3	Conv. (cfs)		92369.9	2052.4
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.48	1.08
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.00	1.82	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.26	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	1.28	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.71	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	0.57	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	-0.83	Flow Area (sq ft)		194.61	0.25
E.G. Slope (ft/ft)	0.005264	Area (sq ft)		194.61	0.25
Q Total (cfs)	1312.00	Flow (cfs)		1311.84	0.16
Top Width (ft)	47.86	Top Width (ft)		47.00	0.86
Vel Total (ft/s)	6.73	Avg. Vel. (ft/s)		6.74	0.64
Max Chl Dpth (ft)	5.57	Hydr. Depth (ft)		4.14	0.29
Conv. Total (cfs)	18084.0	Conv. (cfs)		18081.8	2.2
Length Wtd. (ft)	22.00	Wetted Per. (ft)		49.20	1.03
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		1.30	0.08
Alpha	1.00	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.00	0.77	0.00
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.21	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	6.06	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.45	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	4.61	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.44	Flow Area (sq ft)		392.56	15.80
E.G. Slope (ft/ft)	0.004666	Area (sq ft)	0.20	394.07	15.92
Q Total (cfs)	3850.00	Flow (cfs)		3809.73	40.27
Top Width (ft)	57.66	Top Width (ft)	0.25	50.50	6.91
Vel Total (ft/s)	9.43	Avg. Vel. (ft/s)		9.70	2.55
Max Chl Dpth (ft)	9.61	Hydr. Depth (ft)		7.90	2.51

Conv. Total (cfs)	56362.0	Conv. (cfs)		55772.5	589.5
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.18	0.61
Alpha	1.05	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.00	1.50	0.01
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	0.25	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	6.54	Element			
Vel Head (ft)	1.50	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	5.04	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.74	Flow Area (sq ft)		413.84	18.49
E.G. Slope (ft/ft)	0.004524	Area (sq ft)	0.32	415.69	19.02
Q Total (cfs)	4148.00	Flow (cfs)		4096.43	51.57
Top Width (ft)	58.37	Top Width (ft)	0.31	50.50	7.55
Vel Total (ft/s)	9.59	Avg. Vel. (ft/s)		9.90	2.79
Max Chl Dpth (ft)	10.04	Hydr. Depth (ft)		8.33	2.94
Conv. Total (cfs)	61669.7	Conv. (cfs)		60902.9	766.8
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.23	0.69
Alpha	1.05	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.00	1.52	0.01
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.25	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

			Left OB	Channel	Right OB
E.G. Elev (ft)	8.30	Element			
Vel Head (ft)	1.70	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	6.60	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.80	Flow Area (sq ft)		491.54	28.34
E.G. Slope (ft/ft)	0.004093	Area (sq ft)	1.00	494.64	32.66
Q Total (cfs)	5290.00	Flow (cfs)		5190.07	99.93
Top Width (ft)	60.95	Top Width (ft)	0.56	50.50	9.90
Vel Total (ft/s)	10.18	Avg. Vel. (ft/s)		10.56	3.53
Max Chl Dpth (ft)	11.60	Hydr. Depth (ft)		9.89	4.50
Conv. Total (cfs)	82690.9	Conv. (cfs)		81128.9	1562.0
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.39	0.96
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00

Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.00	1.80	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.26	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.04	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.16	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.55	Flow Area (sq ft)		619.07	44.51
E.G. Slope (ft/ft)	0.003631	Area (sq ft)	2.94	624.23	65.15
Q Total (cfs)	7380.00	Flow (cfs)		7180.31	199.69
Top Width (ft)	65.97	Top Width (ft)	0.95	50.50	14.52
Vel Total (ft/s)	11.12	Avg. Vel. (ft/s)		11.60	4.49
Max Chl Dpth (ft)	14.16	Hydr. Depth (ft)		12.46	7.06
Conv. Total (cfs)	122479.0	Conv. (cfs)		119165.0	3314.1
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.67	1.33
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.01	2.11	0.06
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	0.27	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 38

INPUT
Description: 2
Station Elevation Data num= 11

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	13.2	13.2	13.2	13.3	0	24.2	-4	27.6	-4
43.6	-4.5	53.6	-4	61.4	0	61.5	2	83.6	12
89.9	15								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	13.3	.04	61.5	.065

Bank Sta: Left Right Lengths: Left Channel Right Coeff Contr. Expan.

13.3 61.5 38 38 38 .1 .3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	8.98	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.19	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.79	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.17	488.82	25.39
E.G. Slope (ft/ft)	0.005186	Area (sq ft)	0.17	488.82	25.39
Q Total (cfs)	5910.00	Flow (cfs)	0.03	5839.64	70.33
Top Width (ft)	58.84	Top Width (ft)	0.05	48.20	10.59
Vel Total (ft/s)	11.49	Avg. Vel. (ft/s)	0.14	11.95	2.77
Max Chl Dpth (ft)	11.29	Hydr. Depth (ft)	3.40	10.14	2.40
Conv. Total (cfs)	82068.1	Conv. (cfs)	0.3	81091.1	976.7
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.79	51.80	11.63
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	3.06	0.71
Alpha	1.07	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.00	1.56	0.01
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.24	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	0.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.33	Wt. n-Val.		0.040	
W.S. Elev (ft)	-0.42	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)	-0.59	Flow Area (sq ft)		141.70	
E.G. Slope (ft/ft)	0.014529	Area (sq ft)		141.70	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	46.14	Top Width (ft)		46.14	
Vel Total (ft/s)	9.26	Avg. Vel. (ft/s)		9.26	
Max Chl Dpth (ft)	4.08	Hydr. Depth (ft)		3.07	
Conv. Total (cfs)	10884.8	Conv. (cfs)		10884.8	
Length Wtd. (ft)	38.00	Wetted Per. (ft)		47.66	
Min Ch El (ft)	-4.50	Shear (lb/sq ft)		2.70	
Alpha	1.00	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	0.69	
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.19	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.82	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.83	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.00	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.06	353.98	4.40
E.G. Slope (ft/ft)	0.006584	Area (sq ft)	0.06	353.98	4.40
Q Total (cfs)	3850.00	Flow (cfs)	0.01	3842.33	7.66
Top Width (ft)	52.64	Top Width (ft)	0.03	48.20	4.41
Vel Total (ft/s)	10.74	Avg. Vel. (ft/s)	0.11	10.85	1.74
Max Chl Dpth (ft)	8.50	Hydr. Depth (ft)	2.00	7.34	1.00
Conv. Total (cfs)	47447.7	Conv. (cfs)	0.1	47353.2	94.4
Length Wtd. (ft)	38.00	Wetted Per. (ft)	4.00	51.80	4.84
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.81	0.37
Alpha	1.02	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.00	1.32	0.00
C & E Loss (ft)	0.14	Cum SA (acres)	0.00	0.23	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.31	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.89	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.42	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.07	374.32	6.46
E.G. Slope (ft/ft)	0.006331	Area (sq ft)	0.07	374.32	6.46
Q Total (cfs)	4148.00	Flow (cfs)	0.01	4135.47	12.53
Top Width (ft)	53.58	Top Width (ft)	0.03	48.20	5.34
Vel Total (ft/s)	10.89	Avg. Vel. (ft/s)	0.12	11.05	1.94
Max Chl Dpth (ft)	8.92	Hydr. Depth (ft)	2.21	7.77	1.21
Conv. Total (cfs)	52132.6	Conv. (cfs)	0.1	51975.0	157.4
Length Wtd. (ft)	38.00	Wetted Per. (ft)	4.42	51.80	5.86
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.86	0.44
Alpha	1.03	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.35	Cum Volume (acre-ft)	0.00	1.32	0.01
C & E Loss (ft)	0.15	Cum SA (acres)	0.00	0.23	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.08	Element	Left OB	Channel	Right OB

Vel Head (ft)	2.09	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.99	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.14	449.90	17.55
E.G. Slope (ft/ft)	0.005518	Area (sq ft)	0.14	449.90	17.55
Q Total (cfs)	5290.00	Flow (cfs)	0.02	5245.62	44.36
Top Width (ft)	57.05	Top Width (ft)	0.05	48.20	8.81
Vel Total (ft/s)	11.31	Avg. Vel. (ft/s)	0.14	11.66	2.53
Max Chl Dpth (ft)	10.49	Hydr. Depth (ft)	2.99	9.33	1.99
Conv. Total (cfs)	71215.8	Conv. (cfs)	0.2	70618.4	597.2
Length Wtd. (ft)	38.00	Wetted Per. (ft)	5.99	51.80	9.67
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.99	0.63
Alpha	1.05	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.00	1.56	0.02
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.24	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.38	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	8.63	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.28	577.30	48.55
E.G. Slope (ft/ft)	0.004557	Area (sq ft)	0.28	577.30	48.55
Q Total (cfs)	7380.00	Flow (cfs)	0.04	7223.42	156.53
Top Width (ft)	62.91	Top Width (ft)	0.07	48.20	14.65
Vel Total (ft/s)	11.79	Avg. Vel. (ft/s)	0.16	12.51	3.22
Max Chl Dpth (ft)	13.13	Hydr. Depth (ft)	4.31	11.98	3.31
Conv. Total (cfs)	109319.4	Conv. (cfs)	0.7	107000.0	2318.7
Length Wtd. (ft)	38.00	Wetted Per. (ft)	8.63	51.80	16.08
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	3.17	0.86
Alpha	1.10	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.81	0.03
C & E Loss (ft)	0.25	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 0

INPUT
Description: 1 (Downstream)
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	19	1	19	10	2	20	-6.3	30	-6.3
40	-5	50	-2.5	52	1.8	60	19		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	52	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	52	21	21	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	8.48	Element			
Vel Head (ft)	4.24	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.24	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.24	Flow Area (sq ft)	1.33	357.35	1.39
E.G. Slope (ft/ft)	0.013662	Area (sq ft)	1.33	357.35	1.39
Q Total (cfs)	5910.00	Flow (cfs)	2.31	5905.31	2.38
Top Width (ft)	44.32	Top Width (ft)	1.19	42.00	1.14
Vel Total (ft/s)	16.41	Avg. Vel. (ft/s)	1.74	16.53	1.72
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	1.12	8.51	1.22
Conv. Total (cfs)	50562.8	Conv. (cfs)	19.8	50522.7	20.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	2.54	48.13	2.69
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.45	6.33	0.44
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.00	1.19	0.00
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	0.20	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	0.42	Element			
Vel Head (ft)	1.08	Wt. n-Val.		0.040	

W.S. Elev (ft)	-0.66	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)		Flow Area (sq ft)		157.23	
E.G. Slope (ft/ft)	0.008477	Area (sq ft)		157.23	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	37.65	Top Width (ft)		37.65	
Vel Total (ft/s)	8.34	Avg. Vel. (ft/s)		8.34	
Max Chl Dpth (ft)	5.64	Hydr. Depth (ft)		4.18	
Conv. Total (cfs)	14249.8	Conv. (cfs)		14249.8	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		41.26	
Min Ch El (ft)	-6.30	Shear (lb/sq ft)		2.02	
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.00	0.56	
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.15	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.21	Wt. n-Val.	0.000	0.040	0.065
W.S. Elev (ft)	2.11	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.11	Flow Area (sq ft)	0.00	267.76	0.02
E.G. Slope (ft/ft)	0.015198	Area (sq ft)	0.00	267.76	0.02
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3849.99	0.01
Top Width (ft)	42.20	Top Width (ft)	0.06	42.00	0.14
Vel Total (ft/s)	14.38	Avg. Vel. (ft/s)	0.24	14.38	0.46
Max Chl Dpth (ft)	8.41	Hydr. Depth (ft)	0.05	6.38	0.15
Conv. Total (cfs)	31229.7	Conv. (cfs)	0.0	31229.6	0.1
Length Wtd. (ft)	21.00	Wetted Per. (ft)	0.12	48.13	0.34
Min Ch El (ft)	-6.30	Shear (lb/sq ft)		5.28	0.06
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.00	1.04	0.00
C & E Loss (ft)	0.33	Cum SA (acres)	0.00	0.19	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.81	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.36	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	2.45	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.45	Flow Area (sq ft)	0.05	281.94	0.10

E.G. Slope (ft/ft)	0.014853	Area (sq ft)	0.05	281.94	0.10
Q Total (cfs)	4148.00	Flow (cfs)	0.03	4147.90	0.07
Top Width (ft)	42.54	Top Width (ft)	0.24	42.00	0.30
Vel Total (ft/s)	14.70	Avg. Vel. (ft/s)	0.62	14.71	0.74
Max Chl Dpth (ft)	8.75	Hydr. Depth (ft)	0.22	6.71	0.32
Conv. Total (cfs)	34035.3	Conv. (cfs)	0.3	34034.4	0.6
Length Wtd. (ft)	21.00	Wetted Per. (ft)	0.50	48.13	0.71
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.10	5.43	0.13
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.00	1.03	0.00
C & E Loss (ft)	0.32	Cum SA (acres)	0.00	0.19	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.96	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.62	Flow Area (sq ft)	0.69	331.05	0.77
E.G. Slope (ft/ft)	0.014135	Area (sq ft)	0.69	331.05	0.77
Q Total (cfs)	5290.00	Flow (cfs)	0.98	5287.92	1.10
Top Width (ft)	43.70	Top Width (ft)	0.86	42.00	0.84
Vel Total (ft/s)	15.91	Avg. Vel. (ft/s)	1.42	15.97	1.43
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.81	7.88	0.91
Conv. Total (cfs)	44494.8	Conv. (cfs)	8.3	44477.3	9.2
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.83	48.13	2.00
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.33	6.07	0.34
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.00	1.22	0.01
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.20	0.01

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	10.49	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.62	Flow Area (sq ft)	3.47	415.35	3.40
E.G. Slope (ft/ft)	0.012870	Area (sq ft)	3.47	415.35	3.40
Q Total (cfs)	7380.00	Flow (cfs)	8.07	7364.30	7.63
Top Width (ft)	45.70	Top Width (ft)	1.92	42.00	1.78
Vel Total (ft/s)	17.48	Avg. Vel. (ft/s)	2.32	17.73	2.25
Max Chl Dpth (ft)	11.92	Hydr. Depth (ft)	1.81	9.89	1.91
Conv. Total (cfs)	65054.0	Conv. (cfs)	71.1	64915.6	67.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	4.10	48.13	4.22
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.68	6.93	0.65
Alpha	1.03	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.38	0.00
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -21

INPUT
Description: RR
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	15	8	-3	25	-7	30	-7	37	-6
50	-2	59	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	59	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	59	33	33	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	7.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.09	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.82	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	3.29	Flow Area (sq ft)	5.17	297.09	
E.G. Slope (ft/ft)	0.024570	Area (sq ft)	5.17	297.09	
Q Total (cfs)	5910.00	Flow (cfs)	18.28	5891.73	
Top Width (ft)	45.71	Top Width (ft)	2.14	43.56	
Vel Total (ft/s)	19.55	Avg. Vel. (ft/s)	3.53	19.83	
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)	2.41	6.82	
Conv. Total (cfs)	37703.4	Conv. (cfs)	116.6	37586.8	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	5.28	47.27	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.50	9.64	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.00	1.03	0.00
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.18	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	0.18	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	-0.51	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	1.38	196.50	
E.G. Slope (ft/ft)	0.004483	Area (sq ft)	1.38	196.50	
Q Total (cfs)	1312.00	Flow (cfs)	1.34	1310.66	
Top Width (ft)	43.72	Top Width (ft)	1.11	42.61	
Vel Total (ft/s)	6.63	Avg. Vel. (ft/s)	0.97	6.67	
Max Chl Dpth (ft)	6.49	Hydr. Depth (ft)	1.24	4.61	
Conv. Total (cfs)	19594.6	Conv. (cfs)	20.0	19574.7	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	2.72	44.75	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.14	1.23	
Alpha	1.01	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.00	0.47	
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.13	

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.66	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.10	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.56	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	1.22	Flow Area (sq ft)	6.87	329.34	
E.G. Slope (ft/ft)	0.007551	Area (sq ft)	6.87	329.34	
Q Total (cfs)	3850.00	Flow (cfs)	14.81	3835.19	

Top Width (ft)	46.34	Top Width (ft)	2.47	43.87	
Vel Total (ft/s)	11.45	Avg. Vel. (ft/s)	2.15	11.64	
Max Chl Dpth (ft)	9.56	Hydr. Depth (ft)	2.78	7.51	
Conv. Total (cfs)	44306.6	Conv. (cfs)	170.4	44136.2	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.09	48.07	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.53	3.23	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.00	0.90	0.00
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.17	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	5.24	Element			
Vel Head (ft)	4.91	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	0.34	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	1.55	Flow Area (sq ft)	2.47	232.78	
E.G. Slope (ft/ft)	0.026135	Area (sq ft)	2.47	232.78	
Q Total (cfs)	4148.00	Flow (cfs)	7.06	4140.94	
Top Width (ft)	44.44	Top Width (ft)	1.48	42.96	
Vel Total (ft/s)	17.63	Avg. Vel. (ft/s)	2.85	17.79	
Max Chl Dpth (ft)	7.34	Hydr. Depth (ft)	1.67	5.42	
Conv. Total (cfs)	25658.1	Conv. (cfs)	43.7	25614.4	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	3.65	45.66	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.11	8.32	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.00	0.91	0.00
C & E Loss (ft)	0.15	Cum SA (acres)	0.00	0.17	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.01	Element			
Vel Head (ft)	5.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.32	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	2.71	Flow Area (sq ft)	4.15	275.33	
E.G. Slope (ft/ft)	0.025006	Area (sq ft)	4.15	275.33	
Q Total (cfs)	5290.00	Flow (cfs)	13.76	5276.24	
Top Width (ft)	45.28	Top Width (ft)	1.92	43.36	
Vel Total (ft/s)	18.93	Avg. Vel. (ft/s)	3.31	19.16	
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.35	

Conv. Total (cfs)	33452.7	Conv. (cfs)	87.0	33365.6	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	4.73	46.73	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.37	9.20	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.00	1.07	0.01
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.18	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	9.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.98	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.94	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	4.65	Flow Area (sq ft)	7.84	346.01	
E.G. Slope (ft/ft)	0.023784	Area (sq ft)	7.84	346.01	
Q Total (cfs)	7380.00	Flow (cfs)	31.34	7348.67	
Top Width (ft)	46.66	Top Width (ft)	2.64	44.02	
Vel Total (ft/s)	20.86	Avg. Vel. (ft/s)	4.00	21.24	
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	2.97	7.86	
Conv. Total (cfs)	47853.6	Conv. (cfs)	203.2	47650.5	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.50	48.48	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.79	10.60	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.00	1.19	0.00
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -54

INPUT
Description: K2
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	21	5	40	-7	50	-7
60	-6	72	-2	80	0	88	2	96	4

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val

0	.065	11	.04	88	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	88	34	34	34 .1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.85	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	3.09	Flow Area (sq ft)		333.87	
E.G. Slope (ft/ft)	0.025698	Area (sq ft)		333.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	61.41	Top Width (ft)		61.41	
Vel Total (ft/s)	17.70	Avg. Vel. (ft/s)		17.70	
Max Chl Dpth (ft)	8.85	Hydr. Depth (ft)		5.44	
Conv. Total (cfs)	36867.0	Conv. (cfs)		36867.0	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		65.15	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		8.22	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.83	Cum Volume (acre-ft)		0.79	0.00
C & E Loss (ft)	0.37	Cum SA (acres)		0.14	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	0.02	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	-0.67	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		196.83	
E.G. Slope (ft/ft)	0.005185	Area (sq ft)		196.83	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.34	Top Width (ft)		47.34	
Vel Total (ft/s)	6.67	Avg. Vel. (ft/s)		6.67	
Max Chl Dpth (ft)	6.33	Hydr. Depth (ft)		4.16	
Conv. Total (cfs)	18220.8	Conv. (cfs)		18220.8	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		50.04	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.27	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.29	Cum Volume (acre-ft)		0.33	
C & E Loss (ft)	0.08	Cum SA (acres)		0.10	

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.52	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.72	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		388.60	1.05
E.G. Slope (ft/ft)	0.006877	Area (sq ft)		388.60	1.05
Q Total (cfs)	3850.00	Flow (cfs)		3849.01	0.99
Top Width (ft)	66.29	Top Width (ft)		63.40	2.90
Vel Total (ft/s)	9.88	Avg. Vel. (ft/s)		9.90	0.94
Max Chl Dpth (ft)	9.72	Hydr. Depth (ft)		6.13	0.36
Conv. Total (cfs)	46426.8	Conv. (cfs)		46414.9	11.9
Length Wtd. (ft)	34.00	Wetted Per. (ft)		67.40	2.98
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.48	0.15
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.63	0.00
C & E Loss (ft)	0.09	Cum SA (acres)		0.13	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.62	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.62	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.00	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	1.58	Flow Area (sq ft)		406.25	2.01
E.G. Slope (ft/ft)	0.006950	Area (sq ft)		406.25	2.01
Q Total (cfs)	4148.00	Flow (cfs)		4145.64	2.36
Top Width (ft)	67.84	Top Width (ft)		63.84	4.01
Vel Total (ft/s)	10.16	Avg. Vel. (ft/s)		10.20	1.18
Max Chl Dpth (ft)	10.00	Hydr. Depth (ft)		6.36	0.50
Conv. Total (cfs)	49755.9	Conv. (cfs)		49727.6	28.3
Length Wtd. (ft)	34.00	Wetted Per. (ft)		67.92	4.13
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.60	0.21
Alpha	1.01	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.66	0.00
C & E Loss (ft)	0.09	Cum SA (acres)		0.13	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.98	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.93	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	2.59	Flow Area (sq ft)		466.13	7.44
E.G. Slope (ft/ft)	0.007362	Area (sq ft)		466.13	7.44
Q Total (cfs)	5290.00	Flow (cfs)		5276.04	13.96
Top Width (ft)	73.02	Top Width (ft)		65.30	7.71
Vel Total (ft/s)	11.17	Avg. Vel. (ft/s)		11.32	1.88
Max Chl Dpth (ft)	10.93	Hydr. Depth (ft)		7.14	0.96
Conv. Total (cfs)	61651.5	Conv. (cfs)		61488.8	162.7
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.66	7.95
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		3.08	0.43
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.79	0.00
C & E Loss (ft)	0.08	Cum SA (acres)		0.14	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	8.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.75	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.18	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		354.06	0.06
E.G. Slope (ft/ft)	0.033780	Area (sq ft)		354.06	0.06
Q Total (cfs)	7380.00	Flow (cfs)		7379.95	0.05
Top Width (ft)	63.23	Top Width (ft)		62.53	0.70
Vel Total (ft/s)	20.84	Avg. Vel. (ft/s)		20.84	0.81
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.66	0.09
Conv. Total (cfs)	40153.7	Conv. (cfs)		40153.5	0.3
Length Wtd. (ft)		Wetted Per. (ft)		66.37	0.72
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		11.25	0.18
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)		0.93	0.00
C & E Loss (ft)	0.07	Cum SA (acres)		0.15	0.00

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -88

INPUT
Description: K1
Station Elevation Data num= 8

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	56	-6	72	-6	80	-5
94	0	108	5	122	5				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	108	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	108	55	55	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.18	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	3.18	Flow Area (sq ft)		428.87	
E.G. Slope (ft/ft)	0.013653	Area (sq ft)		428.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	72.75	Top Width (ft)		72.75	
Vel Total (ft/s)	13.78	Avg. Vel. (ft/s)		13.78	
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.90	
Conv. Total (cfs)	50579.2	Conv. (cfs)		50579.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		75.82	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.82	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.74	Cum Volume (acre-ft)		0.50	0.00
C & E Loss (ft)	0.02	Cum SA (acres)		0.09	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	-0.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.52	Wt. n-Val.		0.040	
W.S. Elev (ft)	-1.87	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	-1.87	Flow Area (sq ft)		132.74	
E.G. Slope (ft/ft)	0.017077	Area (sq ft)		132.74	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	44.37	Top Width (ft)		44.37	
Vel Total (ft/s)	9.88	Avg. Vel. (ft/s)		9.88	
Max Chl Dpth (ft)	4.13	Hydr. Depth (ft)		2.99	
Conv. Total (cfs)	10039.9	Conv. (cfs)		10039.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		45.68	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		3.10	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.62	Cum Volume (acre-ft)		0.20	
C & E Loss (ft)	0.20	Cum SA (acres)		0.06	

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	3.83	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.45	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.38	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	1.38	Flow Area (sq ft)		306.55	
E.G. Slope (ft/ft)	0.014466	Area (sq ft)		306.55	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.61	Top Width (ft)		62.61	
Vel Total (ft/s)	12.56	Avg. Vel. (ft/s)		12.56	
Max Chl Dpth (ft)	7.38	Hydr. Depth (ft)		4.90	
Conv. Total (cfs)	32009.6	Conv. (cfs)		32009.6	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		65.05	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.26	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.80	Cum Volume (acre-ft)		0.36	0.00
C & E Loss (ft)	0.00	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The

program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.67	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	1.67	Flow Area (sq ft)		324.94	
E.G. Slope (ft/ft)	0.014320	Area (sq ft)		324.94	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	64.23	Top Width (ft)		64.23	
Vel Total (ft/s)	12.77	Avg. Vel. (ft/s)		12.77	
Max Chl Dpth (ft)	7.67	Hydr. Depth (ft)		5.06	
Conv. Total (cfs)	34663.2	Conv. (cfs)		34663.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		66.77	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.35	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.79	Cum Volume (acre-ft)		0.38	0.00
C & E Loss (ft)	0.00	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.81	Wt. n-Val.		0.040	
W.S. Elev (ft)	2.68	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	2.68	Flow Area (sq ft)		393.12	
E.G. Slope (ft/ft)	0.013858	Area (sq ft)		393.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	69.94	Top Width (ft)		69.94	
Vel Total (ft/s)	13.46	Avg. Vel. (ft/s)		13.46	
Max Chl Dpth (ft)	8.68	Hydr. Depth (ft)		5.62	
Conv. Total (cfs)	44937.7	Conv. (cfs)		44937.7	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		72.83	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.67	

Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.75	Cum Volume (acre-ft)		0.46	0.00
C & E Loss (ft)	0.01	Cum SA (acres)		0.08	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	7.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.25	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	4.25	Flow Area (sq ft)		509.28	
E.G. Slope (ft/ft)	0.013360	Area (sq ft)		509.28	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	78.71	Top Width (ft)		78.71	
Vel Total (ft/s)	14.49	Avg. Vel. (ft/s)		14.49	
Max Chl Dpth (ft)	10.25	Hydr. Depth (ft)		6.47	
Conv. Total (cfs)	63848.9	Conv. (cfs)		63848.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		82.14	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		5.17	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)		0.59	0.00
C & E Loss (ft)		Cum SA (acres)		0.09	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -143

INPUT

Description: K0

Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11.3	10	52.7	-7	69	-7	77.8	-6
98.2	-1	100	-1						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11.3	.04	98.2	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11.3	98.2	0	0	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	5.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.21	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	0.87	Reach Len. (ft)			
Crit W.S. (ft)	1.76	Flow Area (sq ft)		357.78	3.37
E.G. Slope (ft/ft)	0.021059	Area (sq ft)		357.78	3.37
Q Total (cfs)	5910.00	Flow (cfs)		5899.45	10.55
Top Width (ft)	66.47	Top Width (ft)		64.67	1.80
Vel Total (ft/s)	16.36	Avg. Vel. (ft/s)		16.49	3.13
Max Chl Dpth (ft)	7.87	Hydr. Depth (ft)		5.53	1.87
Conv. Total (cfs)	40725.3	Conv. (cfs)		40652.6	72.7
Length Wtd. (ft)		Wetted Per. (ft)		66.88	3.67
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		7.03	1.21
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.92	Cum Volume (acre-ft)			
C & E Loss (ft)	0.13	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	-1.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	-2.10	Reach Len. (ft)			
Crit W.S. (ft)	-2.96	Flow Area (sq ft)		178.85	
E.G. Slope (ft/ft)	0.007984	Area (sq ft)		178.85	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	52.94	Top Width (ft)		52.94	
Vel Total (ft/s)	7.34	Avg. Vel. (ft/s)		7.34	

Max Chl Dpth (ft)	4.90	Hydr. Depth (ft)		3.38	
Conv. Total (cfs)	14683.3	Conv. (cfs)		14683.3	
Length Wtd. (ft)		Wetted Per. (ft)		54.44	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.64	
Alpha	1.00	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	2.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.42	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	-0.70	Reach Len. (ft)			
Crit W.S. (ft)	0.07	Flow Area (sq ft)		259.44	0.55
E.G. Slope (ft/ft)	0.024042	Area (sq ft)		259.44	0.55
Q Total (cfs)	3850.00	Flow (cfs)		3849.21	0.79
Top Width (ft)	62.65	Top Width (ft)		60.85	1.80
Vel Total (ft/s)	14.81	Avg. Vel. (ft/s)		14.84	1.44
Max Chl Dpth (ft)	6.30	Hydr. Depth (ft)		4.26	0.30
Conv. Total (cfs)	24829.7	Conv. (cfs)		24824.6	5.1
Length Wtd. (ft)		Wetted Per. (ft)		62.76	2.10
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.21	0.39
Alpha	1.00	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	1.01	Cum Volume (acre-ft)			
C & E Loss (ft)	0.10	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	3.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.56	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	-0.46	Reach Len. (ft)			
Crit W.S. (ft)	0.32	Flow Area (sq ft)		273.91	0.97
E.G. Slope (ft/ft)	0.023585	Area (sq ft)		273.91	0.97
Q Total (cfs)	4148.00	Flow (cfs)		4146.10	1.91
Top Width (ft)	63.23	Top Width (ft)		61.43	1.80
Vel Total (ft/s)	15.09	Avg. Vel. (ft/s)		15.14	1.96
Max Chl Dpth (ft)	6.54	Hydr. Depth (ft)		4.46	0.54
Conv. Total (cfs)	27009.5	Conv. (cfs)		26997.1	12.4

Length Wtd. (ft)		Wetted Per. (ft)		63.38	2.34
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.36	0.61
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	1.00	Cum Volume (acre-ft)			
C & E Loss (ft)	0.10	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	4.43	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.02	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	0.41	Reach Len. (ft)			
Crit W.S. (ft)	1.29	Flow Area (sq ft)		328.10	2.53
E.G. Slope (ft/ft)	0.021991	Area (sq ft)		328.10	2.53
Q Total (cfs)	5290.00	Flow (cfs)		5282.66	7.34
Top Width (ft)	65.34	Top Width (ft)		63.54	1.80
Vel Total (ft/s)	16.00	Avg. Vel. (ft/s)		16.10	2.90
Max Chl Dpth (ft)	7.41	Hydr. Depth (ft)		5.16	1.41
Conv. Total (cfs)	35672.4	Conv. (cfs)		35622.9	49.5
Length Wtd. (ft)		Wetted Per. (ft)		65.66	3.21
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		6.86	1.08
Alpha	1.01	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.95	Cum Volume (acre-ft)			
C & E Loss (ft)	0.12	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	6.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.57	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	1.94	Reach Len. (ft)			
Crit W.S. (ft)	2.81	Flow Area (sq ft)		428.54	5.30
E.G. Slope (ft/ft)	0.018989	Area (sq ft)		428.54	5.30
Q Total (cfs)	7380.00	Flow (cfs)		7362.03	17.97
Top Width (ft)	69.08	Top Width (ft)		67.28	1.80
Vel Total (ft/s)	17.01	Avg. Vel. (ft/s)		17.18	3.39

Max Chl Dpth (ft)	8.94	Hydr. Depth (ft)		6.37	2.94
Conv. Total (cfs)	53555.1	Conv. (cfs)		53424.7	130.4
Length Wtd. (ft)		Wetted Per. (ft)		69.71	4.74
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		7.29	1.32
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)			
C & E Loss (ft)	0.13	Cum SA (acres)			

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

SUMMARY OF MANNING'S N VALUES

River:Cobosee Stream

Reach	River Sta.	n1	n2	n3
Reach 1	1700	.07	.04	.065
Reach 1	1635	.07	.045	.065
Reach 1	1555	.07	.042	.065
Reach 1	1455	.065	.045	.07
Reach 1	1335	.065	.045	.075
Reach 1	1185	.065	.045	.07
Reach 1	1060	.065	.04	.07
Reach 1	960	.05	.042	.05
Reach 1	935	.05	.042	.05
Reach 1	895	Bridge		
Reach 1	850	.05	.04	.05
Reach 1	830	.05	.035	.05
Reach 1	821	.065	.035	.065
Reach 1	820	.065	.035	.065
Reach 1	725	.065	.04	.065
Reach 1	575	.065	.04	.065
Reach 1	425	.065	.04	.065
Reach 1	335	.065	.04	.065
Reach 1	262	.065	.04	.065
Reach 1	187	.065	.04	.065
Reach 1	166	Bridge		
Reach 1	137	.065	.04	.065
Reach 1	98.5	Bridge		
Reach 1	60	.065	.04	.065
Reach 1	38	.065	.04	.065
Reach 1	0	.065	.04	.065
Reach 1	-21	.065	.04	.065

Reach 1	-54	.065	.04	.065
Reach 1	-88	.065	.04	.065
Reach 1	-143	.065	.04	.065

SUMMARY OF REACH LENGTHS

River: Cobosee Stream

Reach	River Sta.	Left	Channel	Right
Reach 1	1700	65	65	65
Reach 1	1635	80	80	80
Reach 1	1555	100	100	100
Reach 1	1455	120	120	120
Reach 1	1335	150	150	150
Reach 1	1185	125	125	125
Reach 1	1060	100	100	100
Reach 1	960	25	25	25
Reach 1	935	85	85	85
Reach 1	895	Bridge		
Reach 1	850	20	20	20
Reach 1	830	9	9	9
Reach 1	821	1	1	1
Reach 1	820	95	95	95
Reach 1	725	150	150	150
Reach 1	575	150	150	150
Reach 1	425	90	90	90
Reach 1	335	73	73	73
Reach 1	262	75	75	75
Reach 1	187	50	50	50
Reach 1	166	Bridge		
Reach 1	137	77	77	77
Reach 1	98.5	Bridge		
Reach 1	60	22	22	22
Reach 1	38	38	38	38
Reach 1	0	21	21	21
Reach 1	-21	33	33	33
Reach 1	-54	34	34	34
Reach 1	-88	55	55	55
Reach 1	-143	0	0	0

SUMMARY OF CONTRACTION AND EXPANSION COEFFICIENTS

River: Cobosee Stream

Reach	River Sta.	Contr.	Expan.
Reach 1	1700	.1	.3
Reach 1	1635	.1	.3
Reach 1	1555	.1	.3
Reach 1	1455	.1	.3
Reach 1	1335	.1	.3
Reach 1	1185	.1	.3
Reach 1	1060	.1	.3
Reach 1	960	.3	.5
Reach 1	935	.3	.5
Reach 1	895	Bridge	
Reach 1	850	.3	.5
Reach 1	830	.3	.5
Reach 1	821	.1	.3
Reach 1	820	.1	.3
Reach 1	725	.1	.3
Reach 1	575	.1	.3
Reach 1	425	.1	.3
Reach 1	335	.1	.3
Reach 1	262	.1	.3
Reach 1	187	.1	.3
Reach 1	166	Bridge	
Reach 1	137	.3	.5
Reach 1	98.5	Bridge	
Reach 1	60	.3	.5
Reach 1	38	.1	.3
Reach 1	0	.1	.3
Reach 1	-21	.1	.3
Reach 1	-54	.1	.3
Reach 1	-88	.1	.3
Reach 1	-143	.1	.3

Profile Output Table - Standard Table 1

Reach	River Sta	Profile	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
Reach 1	1700	Q100	5910.00	13.80	22.75	21.32	24.48	0.006899	10.56	559.56	84.99	0.73

Reach 1	1700		Q1.1	1312.00	13.80	18.54	17.33	19.04	0.004837
5.66	231.75	70.35		0.55					
Reach 1	1700		Q10	3850.00	13.80	21.15	19.81	22.41	0.006488
8.99	428.08	79.67		0.68					
Reach 1	1700		Q25	4148.00	13.80	21.40	20.05	22.73	0.006586
9.26	447.72	80.49		0.69					
Reach 1	1700		Q50	5290.00	13.80	22.28	20.89	23.89	0.006865
10.17	519.99	83.43		0.72					
Reach 1	1700		Q500	7380.00	13.80	23.79	22.27	25.79	0.006886
11.36	649.74	88.50		0.74					
Reach 1	1635		Q100	5910.00	14.00	22.26		23.95	0.009287
10.45	565.73	91.56		0.74					
Reach 1	1635		Q1.1	1312.00	14.00	17.69		18.50	0.015059
7.21	181.92	75.56		0.82					
Reach 1	1635		Q10	3850.00	14.00	20.47		21.86	0.010705
9.45	407.41	86.08		0.77					
Reach 1	1635		Q25	4148.00	14.00	20.75		22.19	0.010420
9.61	431.49	86.93		0.76					
Reach 1	1635		Q50	5290.00	14.00	21.75		23.36	0.009593
10.17	520.12	90.01		0.75					
Reach 1	1635		Q500	7380.00	14.00	23.37		25.25	0.008748
11.03	669.19	94.97		0.73					
Reach 1	1555		Q100	5910.00	13.30	20.34	20.16	22.96	0.013986
12.99	455.11	80.13		0.96					
Reach 1	1555		Q1.1	1312.00	13.30	16.65		17.46	0.011277
7.21	181.93	67.33		0.77					
Reach 1	1555		Q10	3850.00	13.30	19.06	18.65	20.89	0.012593
10.84	355.05	76.34		0.89					
Reach 1	1555		Q25	4148.00	13.30	19.24	18.89	21.21	0.013023
11.25	368.77	76.87		0.91					
Reach 1	1555		Q50	5290.00	13.30	19.96	19.73	22.37	0.013832
12.46	424.40	78.99		0.95					
Reach 1	1555		Q500	7380.00	13.30	21.24	21.12	24.27	0.013933
13.96	528.57	82.81		0.97					
Reach 1	1455		Q100	5910.00	11.80	19.15	18.73	21.52	0.013371
12.36	482.06	84.97		0.89					
Reach 1	1455		Q1.1	1312.00	11.80	15.06	14.87	16.04	0.018077
7.92	165.73	68.77		0.90					
Reach 1	1455		Q10	3850.00	11.80	17.40	17.28	19.41	0.017108
11.38	338.92	78.76		0.96					
Reach 1	1455		Q25	4148.00	11.80	17.67	17.49	19.74	0.016461
11.55	360.02	79.70		0.95					

Reach 1	1455		Q50	5290.00	11.80	18.65	18.33	20.92	0.014397
12.10	439.76	83.19		0.91					
Reach 1	1455		Q500	7380.00	11.80	20.28		22.87	0.011590
12.93	580.89	89.01		0.86					
Reach 1	1335		Q100	5910.00	9.50	18.29		20.09	0.008433
10.77	549.92	80.42		0.72					
Reach 1	1335		Q1.1	1312.00	9.50	12.63	12.50	13.78	0.019322
8.58	152.87	58.82		0.94					
Reach 1	1335		Q10	3850.00	9.50	16.13		17.69	0.010509
10.02	384.33	72.81		0.77					
Reach 1	1335		Q25	4148.00	9.50	16.48		18.07	0.010113
10.13	409.66	74.08		0.76					
Reach 1	1335		Q50	5290.00	9.50	17.68		19.41	0.008923
10.55	501.86	78.35		0.73					
Reach 1	1335		Q500	7380.00	9.50	19.61		21.58	0.007513
11.27	658.95	85.25		0.70					
Reach 1	1185		Q100	5910.00	5.50	15.71	15.05	18.43	0.013216
13.23	446.60	64.07		0.88					
Reach 1	1185		Q1.1	1312.00	5.50	10.99		11.81	0.008701
7.27	180.58	47.96		0.66					
Reach 1	1185		Q10	3850.00	5.50	14.07	13.16	16.00	0.011593
11.14	345.58	58.73		0.81					
Reach 1	1185		Q25	4148.00	5.50	14.34	13.46	16.38	0.011842
11.48	361.45	59.60		0.82					
Reach 1	1185		Q50	5290.00	5.50	15.28	14.52	17.75	0.012665
12.62	419.10	62.66		0.86					
Reach 1	1185		Q500	7380.00	5.50	16.59	16.20	19.92	0.014382
14.64	504.17	66.73		0.93					
Reach 1	1060		Q100	5910.00	5.00	13.60	13.60	16.72	0.013608
14.18	416.89	66.85		1.00					
Reach 1	1060		Q1.1	1312.00	5.00	8.85	8.85	10.26	0.017292
9.54	137.48	49.24		1.01					
Reach 1	1060		Q10	3850.00	5.00	11.83	11.83	14.32	0.014509
12.68	303.74	61.10		1.00					
Reach 1	1060		Q25	4148.00	5.00	12.11	12.11	14.70	0.014350
12.93	320.83	62.03		1.00					
Reach 1	1060		Q50	5290.00	5.00	13.10	13.10	16.05	0.013874
13.79	383.70	65.29		1.00					
Reach 1	1060		Q500	7380.00	5.00	14.68	14.68	18.19	0.013258
15.04	490.72	70.18		1.00					

Reach 1	960		Q100	5910.00	3.50	9.43	10.91	14.55	0.030767
18.60	341.13	76.49		1.44					
Reach 1	960		Q1.1	1312.00	3.50	6.44	6.75	8.04	0.029093
10.21	131.29	63.66		1.21					
Reach 1	960		Q10	3850.00	3.50	8.24	9.32	12.10	0.032272
16.02	253.19	71.40		1.41					
Reach 1	960		Q25	4148.00	3.50	8.43	9.57	12.48	0.032073
16.45	266.37	72.19		1.42					
Reach 1	960		Q50	5290.00	3.50	9.09	10.43	13.86	0.031227
17.91	315.39	75.04		1.43					
Reach 1	960		Q500	7380.00	3.50	10.20	11.80	16.05	0.029537
19.97	401.20	79.79		1.44					
Reach 1	935		Q100	5910.00	2.00	11.75	9.85	13.32	0.005265
10.42	658.53	132.90		0.64					
Reach 1	935		Q1.1	1312.00	2.00	7.09	5.89	7.58	0.004686
5.64	240.45	73.32		0.53					
Reach 1	935		Q10	3850.00	2.00	9.85	8.32	11.06	0.005604
9.03	456.63	83.52		0.63					
Reach 1	935		Q25	4148.00	2.00	10.11	8.55	11.40	0.005706
9.35	478.35	87.07		0.64					
Reach 1	935		Q50	5290.00	2.00	11.27	9.42	12.74	0.005275
10.02	598.64	119.63		0.63					
Reach 1	935		Q500	7380.00	2.00	12.97	11.03	14.57	0.004645
10.73	828.04	154.93		0.62					
Reach 1	895		Bridge						
Reach 1	850		Q100	5910.00	1.00	11.15	9.23	12.78	0.004722
10.75	667.24	137.13		0.64					
Reach 1	850		Q1.1	1312.00	1.00	6.82	4.95	7.20	0.002613
5.07	272.29	70.41		0.43					
Reach 1	850		Q10	3850.00	1.00	9.32	7.59	10.54	0.004663
9.14	463.09	82.13		0.61					
Reach 1	850		Q25	4148.00	1.00	9.61	7.85	10.89	0.004678
9.41	487.02	83.49		0.62					
Reach 1	850		Q50	5290.00	1.00	10.56	8.76	12.19	0.005052
10.62	590.31	128.55		0.66					
Reach 1	850		Q500	7380.00	1.00	12.53	11.04	14.10	0.003944
10.84	851.33	153.61		0.60					
Reach 1	830		Q100	5910.00	1.00	11.26		12.51	0.003074
9.22	746.99	159.08		0.58					

Reach 1	830		Q1.1	1312.00	1.00	6.74	7.14	0.002907
5.12	257.05	77.73		0.49				
Reach 1	830		Q10	3850.00	1.00	9.32	10.37	0.003638
8.31	491.60	104.93		0.60				
Reach 1	830		Q25	4148.00	1.00	9.62	10.71	0.003539
8.47	524.13	108.28		0.60				
Reach 1	830		Q50	5290.00	1.00	10.68	11.91	0.003296
9.08	657.87	145.20		0.59				
Reach 1	830		Q500	7380.00	1.00	12.65	13.86	0.002508
9.28	978.53	170.35		0.54				
Reach 1	821		Q100	5910.00	1.00	11.34	12.39	0.002923
8.30	780.65	173.08		0.55				
Reach 1	821		Q1.1	1312.00	1.00	6.70	7.12	0.003264
5.17	253.80	80.33		0.51				
Reach 1	821		Q10	3850.00	1.00	9.35	10.27	0.003921
7.69	503.45	110.72		0.61				
Reach 1	821		Q25	4148.00	1.00	9.66	10.61	0.003709
7.79	539.38	118.32		0.60				
Reach 1	821		Q50	5290.00	1.00	10.75	11.78	0.003187
8.18	685.57	152.72		0.57				
Reach 1	821		Q500	7380.00	1.00	12.71	13.75	0.002344
8.38	1030.46	183.54		0.51				
Reach 1	820		Q100	5910.00	1.00	11.43	12.34	0.003087
7.69	803.42	172.37		0.55				
Reach 1	820		Q1.1	1312.00	1.00	6.70	7.11	0.003278
5.18	253.43	80.29		0.51				
Reach 1	820		Q10	3850.00	1.00	9.35	10.26	0.004413
7.66	502.71	110.46		0.63				
Reach 1	820		Q25	4148.00	1.00	9.68	10.59	0.004433
7.68	540.00	118.58		0.63				
Reach 1	820		Q50	5290.00	1.00	10.83	11.74	0.003558
7.69	703.59	154.57		0.58				
Reach 1	820		Q500	7380.00	1.00	12.85	13.69	0.002211
7.50	1166.68	280.88		0.49				
Reach 1	725		Q100	5910.00	2.50	10.98	12.00	0.003914
8.16	775.07	173.76		0.55				
Reach 1	725		Q1.1	1312.00	2.50	6.19	6.68	0.006471
5.62	233.26	89.27		0.61				
Reach 1	725		Q10	3850.00	2.50	8.76	9.76	0.006140
8.02	480.32	102.99		0.65				
Reach 1	725		Q25	4148.00	2.50	9.10	10.10	0.005766
8.05	515.12	107.22		0.64				

Reach 1	725		Q50	5290.00	2.50	10.32		11.35	0.004495
8.17	669.44	147.09		0.58					
Reach 1	725		Q500	7380.00	2.50	12.49		13.44	0.002895
8.03	1085.64	233.36		0.49					
Reach 1	575		Q100	5910.00	1.50	10.82		11.46	0.002176
6.47	970.39	205.77		0.42					
Reach 1	575		Q1.1	1312.00	1.50	4.64		5.33	0.012975
6.65	197.15	99.11		0.83					
Reach 1	575		Q10	3850.00	1.50	8.32		8.96	0.003596
6.43	598.52	119.69		0.51					
Reach 1	575		Q25	4148.00	1.50	8.71		9.35	0.003312
6.42	645.83	122.16		0.49					
Reach 1	575		Q50	5290.00	1.50	10.10		10.75	0.002487
6.46	838.34	163.32		0.44					
Reach 1	575		Q500	7380.00	1.50	12.41		13.01	0.001633
6.39	1361.35	268.56		0.38					
Reach 1	425		Q100	5910.00	0.00	10.51		11.16	0.001827
6.49	979.22	227.41		0.39					
Reach 1	425		Q1.1	1312.00	0.00	3.64		4.09	0.005159
5.43	241.53	81.94		0.56					
Reach 1	425		Q10	3850.00	0.00	7.94		8.51	0.002359
6.06	635.41	100.05		0.42					
Reach 1	425		Q25	4148.00	0.00	8.34		8.93	0.002277
6.14	676.07	101.58		0.42					
Reach 1	425		Q50	5290.00	0.00	9.77		10.41	0.002010
6.41	837.36	138.26		0.40					
Reach 1	425		Q500	7380.00	0.00	12.18		12.79	0.001414
6.42	1401.34	260.97		0.35					
Reach 1	335		Q100	5910.00	-2.00	9.90		10.92	0.002776
8.11	744.20	116.89		0.48					
Reach 1	335		Q1.1	1312.00	-2.00	3.18		3.68	0.004046
5.66	231.87	61.02		0.51					
Reach 1	335		Q10	3850.00	-2.00	7.40		8.23	0.003241
7.34	524.52	77.52		0.50					
Reach 1	335		Q25	4148.00	-2.00	7.79		8.66	0.003199
7.47	555.22	79.02		0.50					
Reach 1	335		Q50	5290.00	-2.00	9.18		10.16	0.002961
7.92	669.58	90.38		0.49					
Reach 1	335		Q500	7380.00	-2.00	11.57		12.59	0.002277
8.24	1072.73	248.32		0.45					

Reach 1	262		Q100	5910.00	-3.00	8.83		10.57	0.005707
10.58	558.57	71.13		0.67					
Reach 1	262		Q1.1	1312.00	-3.00	2.46		3.27	0.006684
7.24	181.27	47.36		0.65					
Reach 1	262		Q10	3850.00	-3.00	6.37		7.85	0.006329
9.75	394.89	62.01		0.68					
Reach 1	262		Q25	4148.00	-3.00	6.74		8.27	0.006275
9.92	418.05	63.45		0.68					
Reach 1	262		Q50	5290.00	-3.00	8.10		9.79	0.005954
10.42	507.69	68.47		0.67					
Reach 1	262		Q500	7380.00	-3.00	10.41		12.27	0.004923
10.93	690.11	108.39		0.63					
Reach 1	187		Q100	5910.00	-4.00	8.44	5.94	10.14	0.005330
10.46	564.77	68.82		0.64					
Reach 1	187		Q1.1	1312.00	-4.00	2.11	0.60	2.80	0.005083
6.66	197.00	47.17		0.57					
Reach 1	187		Q10	3850.00	-4.00	5.98	3.99	7.38	0.005674
9.50	405.37	60.48		0.65					
Reach 1	187		Q25	4148.00	-4.00	6.34	4.29	7.80	0.005668
9.70	427.77	61.72		0.65					
Reach 1	187		Q50	5290.00	-4.00	7.71	5.39	9.35	0.005505
10.27	515.03	66.29		0.65					
Reach 1	187		Q500	7380.00	-4.00	10.07	7.13	11.90	0.004763
10.85	682.36	79.14		0.62					
Reach 1	166			Bridge					
Reach 1	137		Q100	5910.00	-4.00	7.97	5.85	9.84	0.006060
10.95	539.62	67.73		0.68					
Reach 1	137		Q1.1	1312.00	-4.00	1.69	0.51	2.50	0.006412
7.23	181.49	45.77		0.64					
Reach 1	137		Q10	3850.00	-4.00	5.44	3.89	7.04	0.006877
10.16	378.85	59.13		0.71					
Reach 1	137		Q25	4148.00	-4.00	5.81	4.20	7.47	0.006819
10.35	400.81	60.38		0.71					
Reach 1	137		Q50	5290.00	-4.00	7.20	5.30	9.02	0.006396
10.83	488.44	65.11		0.70					
Reach 1	137		Q500	7380.00	-4.00	9.68	7.04	11.63	0.005108
11.21	660.26	73.78		0.64					
Reach 1	98.5			Bridge					

Reach 1	60		Q100	5910.00	-5.00	7.40	4.37	9.20	0.003918
10.88	564.72	62.75		0.59					
Reach 1	60		Q1.1	1312.00	-5.00	0.57	-0.83	1.28	0.005264
6.74	194.86	47.86		0.58					
Reach 1	60		Q10	3850.00	-5.00	4.61	2.44	6.06	0.004666
9.70	408.35	57.66		0.61					
Reach 1	60		Q25	4148.00	-5.00	5.04	2.74	6.54	0.004524
9.90	432.34	58.37		0.60					
Reach 1	60		Q50	5290.00	-5.00	6.60	3.80	8.30	0.004093
10.56	519.88	60.95		0.59					
Reach 1	60		Q500	7380.00	-5.00	9.16	5.55	11.21	0.003631
11.60	663.58	65.97		0.58					
Reach 1	38		Q100	5910.00	-4.50	6.79		8.98	0.005186
11.95	514.38	58.84		0.66					
Reach 1	38		Q1.1	1312.00	-4.50	-0.42	-0.59	0.91	0.014529
9.26	141.70	46.14		0.93					
Reach 1	38		Q10	3850.00	-4.50	4.00		5.82	0.006584
10.85	358.44	52.64		0.71					
Reach 1	38		Q25	4148.00	-4.50	4.42		6.31	0.006331
11.05	380.85	53.58		0.70					
Reach 1	38		Q50	5290.00	-4.50	5.99		8.08	0.005518
11.66	467.59	57.05		0.67					
Reach 1	38		Q500	7380.00	-4.50	8.63		11.01	0.004557
12.51	626.13	62.91		0.64					
Reach 1	0		Q100	5910.00	-6.30	4.24	4.24	8.48	0.013662
16.53	360.07	44.32		1.00					
Reach 1	0		Q1.1	1312.00	-6.30	-0.66		0.42	0.008477
8.34	157.23	37.65		0.72					
Reach 1	0		Q10	3850.00	-6.30	2.11	2.11	5.32	0.015198
14.38	267.79	42.20		1.00					
Reach 1	0		Q25	4148.00	-6.30	2.45	2.45	5.81	0.014853
14.71	282.09	42.54		1.00					
Reach 1	0		Q50	5290.00	-6.30	3.62	3.62	7.58	0.014135
15.97	332.50	43.70		1.00					
Reach 1	0		Q500	7380.00	-6.30	5.62	5.62	10.49	0.012870
17.73	422.22	45.70		0.99					
Reach 1	-21		Q100	5910.00	-7.00	1.82	3.29	7.91	0.024570
19.83	302.26	45.71		1.34					
Reach 1	-21		Q1.1	1312.00	-7.00	-0.51		0.18	0.004483
6.67	197.87	43.72		0.55					

Reach 1	-21		Q10	3850.00	-7.00	2.56	1.22	4.66	0.007551
11.64	336.22	46.34		0.75					
Reach 1	-21		Q25	4148.00	-7.00	0.34	1.55	5.24	0.026135
17.79	235.26	44.44		1.35					
Reach 1	-21		Q50	5290.00	-7.00	1.32	2.71	7.01	0.025006
19.16	279.48	45.28		1.34					
Reach 1	-21		Q500	7380.00	-7.00	2.94	4.65	9.92	0.023784
21.24	353.85	46.66		1.34					
Reach 1	-54		Q100	5910.00	-7.00	1.85	3.09	6.72	0.025698
17.70	333.87	61.41		1.34					
Reach 1	-54		Q1.1	1312.00	-7.00	-0.67		0.02	0.005185
6.67	196.83	47.34		0.58					
Reach 1	-54		Q10	3850.00	-7.00	2.72		4.25	0.006877
9.90	389.65	66.29		0.71					
Reach 1	-54		Q25	4148.00	-7.00	3.00	1.58	4.62	0.006950
10.20	408.26	67.84		0.71					
Reach 1	-54		Q50	5290.00	-7.00	3.93	2.59	5.91	0.007362
11.32	473.56	73.02		0.75					
Reach 1	-54		Q500	7380.00	-7.00	2.18	4.20	8.92	0.033780
20.84	354.12	63.23		1.54					
Reach 1	-88		Q100	5910.00	-6.00	3.18	3.18	6.13	0.013653
13.78	428.87	72.75		1.00					
Reach 1	-88		Q1.1	1312.00	-6.00	-1.87	-1.87	-0.35	0.017077
9.88	132.74	44.37		1.01					
Reach 1	-88		Q10	3850.00	-6.00	1.38	1.38	3.83	0.014466
12.56	306.55	62.61		1.00					
Reach 1	-88		Q25	4148.00	-6.00	1.67	1.67	4.20	0.014320
12.77	324.94	64.23		1.00					
Reach 1	-88		Q50	5290.00	-6.00	2.68	2.68	5.50	0.013858
13.46	393.12	69.94		1.00					
Reach 1	-88		Q500	7380.00	-6.00	4.25	4.25	7.51	0.013360
14.49	509.28	78.71		1.00					
Reach 1	-143		Q100	5910.00	-7.00	0.87	1.76	5.09	0.021059
16.49	361.15	66.47		1.24					
Reach 1	-143		Q1.1	1312.00	-7.00	-2.10	-2.96	-1.26	0.007984
7.34	178.85	52.94		0.70					
Reach 1	-143		Q10	3850.00	-7.00	-0.70	0.07	2.72	0.024042
14.84	259.99	62.65		1.27					
Reach 1	-143		Q25	4148.00	-7.00	-0.46	0.32	3.10	0.023585
15.14	274.89	63.23		1.26					
Reach 1	-143		Q50	5290.00	-7.00	0.41	1.29	4.43	0.021991
16.10	330.63	65.34		1.25					

Reach 1	-143		Q500	7380.00	-7.00	1.94	2.81	6.52	0.018989
17.18	433.84	69.08		1.20					

Profile Output Table - Six XS Bridge

Reach	River Sta		Profile	E.G. Elev	W.S. Elev	Crit W.S.	Frctn Loss	C & E Loss	Top Width
Q Left	Q Channel	Q Right	Vel Chnl	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)
(cfs)	(cfs)	(cfs)	(ft/s)						
Reach 1	960		Q100	14.55	9.43	10.91	1.97	0.20	76.49
168.11	5560.68	181.20	18.60						
Reach 1	960		Q1.1	8.04	6.44	6.75	2.21	0.02	63.66
8.13	1295.11	8.76	10.21						
Reach 1	960		Q10	12.10	8.24	9.32	2.09	0.13	71.40
74.85	3694.47	80.68	16.02						
Reach 1	960		Q25	12.48	8.43	9.57	2.07	0.14	72.19
86.43	3968.41	93.16	16.45						
Reach 1	960		Q50	13.86	9.09	10.43	2.00	0.18	75.04
136.92	5005.50	147.58	17.91						
Reach 1	960		Q500	16.05	10.20	11.80	1.90	0.23	79.79
252.32	6855.72	271.96	19.97						
Reach 1	935		Q100	13.32	11.75	9.85	0.06	0.02	132.90
174.05	5450.01	285.95	10.42						
Reach 1	935		Q1.1	7.58	7.09	5.89	0.05	0.01	73.32
7.25	1281.04	23.71	5.64						
Reach 1	935		Q10	11.06	9.85	8.32	0.06	0.02	83.52
74.51	3633.67	141.82	9.03						
Reach 1	935		Q25	11.40	10.11	8.55	0.06	0.01	87.07
86.27	3917.98	143.74	9.35						
Reach 1	935		Q50	12.74	11.27	9.42	0.06	0.02	119.63
143.42	4940.89	205.69	10.02						
Reach 1	935		Q500	14.57	12.97	11.03	0.05	0.03	154.93
255.06	6451.11	673.83	10.73						
Reach 1	895	BR U	Q100	13.24	11.59	9.85	0.30	0.07	126.63
169.38	5469.50	271.13	10.66						
Reach 1	895	BR U	Q1.1	7.52	7.01	5.89	0.22	0.07	72.99
6.75	1282.34	22.91	5.79						
Reach 1	895	BR U	Q10	10.97	9.70	8.32	0.32	0.05	82.96
71.42	3640.63	137.95	9.27						


Reach 1	895	BR U	Q25	11.33	9.99	8.55	0.32	0.05	84.05	
83.39	3907.93	156.69	9.50							
Reach 1	895	BR U	Q50	12.65	11.10	9.42	0.31	0.05	114.91	
138.86	4959.52	191.62	10.29							
Reach 1	895	BR U	Q500	14.49	12.79	11.03	0.27	0.07	128.71	
249.68	6504.94	625.38	11.04							
Reach 1	895	BR D	Q100	12.86	11.35	9.23	0.05	0.04	125.59	
147.25	5241.63	521.12	10.39							
Reach 1	895	BR D	Q1.1	7.23	6.85	4.95	0.03	0.00	70.59	
4.25	1261.45	46.30	5.03							
Reach 1	895	BR D	Q10	10.60	9.43	7.59	0.05	0.01	82.66	
57.10	3554.07	238.83	8.98							
Reach 1	895	BR D	Q25	10.96	9.72	7.85	0.05	0.01	84.03	
67.83	3810.80	269.38	9.24							
Reach 1	895	BR D	Q50	12.30	10.84	8.76	0.06	0.05	124.62	
119.05	4808.65	362.30	10.12							
Reach 1	895	BR D	Q500	14.15	12.58	10.97	0.05	0.00	127.89	
224.95	6197.70	957.35	10.81							
Reach 1	850		Q100	12.78	11.15	9.23	0.08	0.19	137.13	
141.84	5300.11	468.05	10.75							
Reach 1	850		Q1.1	7.20	6.82	4.95	0.06	0.01	70.41	
4.08	1262.17	45.75	5.07							
Reach 1	850		Q10	10.54	9.32	7.59	0.08	0.08	82.13	
54.87	3560.66	234.48	9.14							
Reach 1	850		Q25	10.89	9.61	7.85	0.08	0.10	83.49	
65.32	3818.07	264.61	9.41							
Reach 1	850		Q50	12.19	10.56	8.76	0.08	0.20	128.55	
112.29	4883.80	293.91	10.62							
Reach 1	850		Q500	14.10	12.53	11.04	0.06	0.18	153.61	
222.51	6183.78	973.71	10.84							
Reach 1	830		Q100	12.51	11.26		0.03	0.10	159.08	
126.11	5558.21	225.68	9.22							
Reach 1	830		Q1.1	7.14	6.74		0.03	0.00	77.73	
0.65	1311.35		5.12							
Reach 1	830		Q10	10.37	9.32		0.03	0.07	104.93	
40.08	3767.76	42.16	8.31							
Reach 1	830		Q25	10.71	9.62		0.03	0.07	108.28	
49.98	4040.20	57.82	8.47							
Reach 1	830		Q50	11.91	10.68		0.03	0.10	145.20	
95.53	5063.76	130.71	9.08							
Reach 1	830		Q500	13.86	12.65		0.02	0.08	170.35	
212.46	6578.08	589.46	9.28							

Reach 1	262		Q100	10.57	8.83		0.41	0.01	71.13
	5910.00		10.58						
Reach 1	262		Q1.1	3.27	2.46		0.44	0.04	47.36
	1312.00		7.24						
Reach 1	262		Q10	7.85	6.37		0.45	0.02	62.01
	3850.00		9.75						
Reach 1	262		Q25	8.27	6.74		0.45	0.02	63.45
	4148.00		9.92						
Reach 1	262		Q50	9.79	8.10		0.43	0.01	68.47
	5290.00		10.42						
Reach 1	262		Q500	12.27	10.41		0.36	0.01	108.39
1.31	7364.13	14.57	10.93						
Reach 1	187		Q100	10.14	8.44	5.94	0.12	0.01	68.82
	5910.00		10.46						
Reach 1	187		Q1.1	2.80	2.11	0.60	0.11	0.01	47.17
	1312.00		6.66						
Reach 1	187		Q10	7.38	5.98	3.99	0.13	0.01	60.48
	3850.00		9.50						
Reach 1	187		Q25	7.80	6.34	4.29	0.12	0.01	61.72
	4148.00		9.70						
Reach 1	187		Q50	9.35	7.71	5.39	0.12	0.01	66.29
	5290.00		10.27						
Reach 1	187		Q500	11.90	10.07	7.13	0.10	0.01	79.14
0.51	7378.29	1.19	10.85						
Reach 1	166	BR U	Q100	10.02	8.22	5.94	0.08	0.00	68.05
	5910.00		10.75						
Reach 1	166	BR U	Q1.1	2.68	1.93	0.59	0.08	0.00	46.51
	1312.00		6.97						
Reach 1	166	BR U	Q10	7.24	5.73	3.98	0.09	0.00	59.67
	3850.00		9.85						
Reach 1	166	BR U	Q25	7.67	6.10	4.29	0.09	0.00	60.90
	4148.00		10.05						
Reach 1	166	BR U	Q50	9.21	7.47	5.40	0.08	0.00	65.51
	5290.00		10.59						
Reach 1	166	BR U	Q500	11.78	9.88	7.13	0.07	0.00	74.14
0.28	7379.46	0.26	11.07						
Reach 1	166	BR D	Q100	9.93	8.15	5.85	0.09	0.01	68.32
	5910.00		10.71						


Reach 1	166	BR D	Q1.1	2.60	1.85	0.50	0.09	0.01	46.39
1312.00			6.96						
Reach 1	166	BR D	Q10	7.15	5.65	3.90	0.10	0.01	59.84
3850.00			9.84						
Reach 1	166	BR D	Q25	7.58	6.01	4.20	0.10	0.01	61.09
4148.00			10.03						
Reach 1	166	BR D	Q50	9.13	7.40	5.30	0.09	0.01	65.77
5290.00			10.56						
Reach 1	166	BR D	Q500	11.71	9.82	7.04	0.07	0.01	73.66
2.44	7376.99	0.57	11.05						
Reach 1	137		Q100	9.84	7.97	5.85	0.14	0.06	67.73
5910.00			10.95						
Reach 1	137		Q1.1	2.50	1.69	0.51	0.21	0.20	45.77
1312.00			7.23						
Reach 1	137		Q10	7.04	5.44	3.89	0.18	0.14	59.13
3850.00			10.16						
Reach 1	137		Q25	7.47	5.81	4.20	0.17	0.12	60.38
4148.00			10.35						
Reach 1	137		Q50	9.02	7.20	5.30	0.15	0.08	65.11
5290.00			10.83						
Reach 1	137		Q500	11.63	9.68	7.04	0.12	0.04	73.78
1.94	7377.72	0.34	11.21						
Reach 1	98.5	BR U	Q100	9.62	7.55	5.85	0.19	0.16	66.28
5910.00			11.57						
Reach 1	98.5	BR U	Q1.1	2.09	0.60	0.50	0.30	0.42	41.40
1312.00			9.80						
Reach 1	98.5	BR U	Q10	6.73	4.66	3.90	0.24	0.34	56.49
3850.00			11.53						
Reach 1	98.5	BR U	Q25	7.17	5.10	4.20	0.23	0.31	57.98
4148.00			11.56						
Reach 1	98.5	BR U	Q50	8.79	6.71	5.30	0.20	0.21	63.44
5290.00			11.58						
Reach 1	98.5	BR U	Q500	11.48	9.40	7.04	0.17	0.03	71.43
1.11	7378.89		11.56						
Reach 1	98.5	BR D	Q100	9.28	7.51	4.37	0.07	0.01	63.06
5779.31	130.69		10.76						
Reach 1	98.5	BR D	Q1.1	1.38	0.72	-0.83	0.08	0.01	48.28
1311.73	0.27		6.51						
Reach 1	98.5	BR D	Q10	6.15	4.76	2.44	0.08	0.02	57.91
3807.03	42.97		9.52						
Reach 1	98.5	BR D	Q25	6.63	5.18	2.74	0.07	0.02	58.61
4093.75	54.26		9.72						


Reach 1	98.5	BR D	Q50	8.38	6.72	3.80	0.07	0.01	61.15	
	5187.74	102.26	10.43							
Reach 1	98.5	BR D	Q500	11.27	9.27	5.55	0.06	0.01	65.27	
	7178.29	201.71	11.50							
Reach 1	60		Q100	9.20	7.40	4.37	0.10	0.12	62.75	
	5781.54	128.46	10.88							
Reach 1	60		Q1.1	1.28	0.57	-0.83	0.18	0.19	47.86	
	1311.84	0.16	6.74							
Reach 1	60		Q10	6.06	4.61	2.44	0.12	0.11	57.66	
	3809.73	40.27	9.70							
Reach 1	60		Q25	6.54	5.04	2.74	0.12	0.12	58.37	
	4096.43	51.57	9.90							
Reach 1	60		Q50	8.30	6.60	3.80	0.10	0.12	60.95	
	5190.07	99.93	10.56							
Reach 1	60		Q500	11.21	9.16	5.55	0.09	0.10	65.97	
	7180.31	199.69	11.60							
Reach 1	38		Q100	8.98	6.79		0.30	0.20	58.84	
0.03	5839.64	70.33	11.95							
Reach 1	38		Q1.1	0.91	-0.42	-0.59	0.41	0.07	46.14	
	1312.00		9.26							
Reach 1	38		Q10	5.82	4.00		0.36	0.14	52.64	
0.01	3842.33	7.66	10.85							
Reach 1	38		Q25	6.31	4.42		0.35	0.15	53.58	
0.01	4135.47	12.53	11.05							
Reach 1	38		Q50	8.08	5.99		0.32	0.19	57.05	
0.02	5245.62	44.36	11.66							
Reach 1	38		Q500	11.01	8.63		0.27	0.25	62.91	
0.04	7223.42	156.53	12.51							


APPENDIX G / HEC-RAS RESULTS FOR PROPOSED CONDITIONS AT MHW





None of the XS's are Geo-Referenced (, Geo-Ref user entered XS , Geo-Ref interpolated XS , Non Geo-Ref user entered XS , Non Geo-Ref interpolated XS)



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
Cobosee Stream Reach 1
Legend
WS Q100
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q500
Ground
Elevation (ft)
Main Channel Distance (ft)
30
25
20
15
10
5
0
-5
-10
-500
0
500
1000
1500
2000



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1700 Upstream (I)
.07
.04
.065
Elevation (ft)
Station (ft)
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
180
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1635 H
.07
.045
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1555 G
.07
.042
.065
Elevation (ft)
Station (ft)
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1455 F
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1335 E
.065
.045
.075
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
160
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1185 D
.065
.045
.07
Elevation (ft)
Station (ft)
45
40
35
30
25
20
15
10
5
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 1060 C
.065
.04
.07
Elevation (ft)
Station (ft)
35
30
25
20
15
10
5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 960 B
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 935 JU
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 895 BR Bridge Street
.05
.042
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
35
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 895 BR Bridge Street
.05
.04
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 850 JD
.05
.04
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
30
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 830 A
.05
.035
.05
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 821 AD
.065
.035
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
25
0
50
100
150
200
250
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 820 ADD
.065
.035
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 725 10
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 575 9
.065
.04
.065
Elevation (ft)
Station (ft)
0
2
4
6
8
10
12
14
16
18
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
1 ft/s
2 ft/s
3 ft/s
4 ft/s
5 ft/s
6 ft/s
7 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 425 8
.065
.04
.065
Elevation (ft)
Station (ft)
0
5
10
15
20
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 335 7
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 262 6
.04
.065
.0
6
5
Elevation (ft)
Station (ft)
14
12
10
8
6
4
2
0
-2
-4
0
50
100
150
200
250
300
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 187 5
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 166 BR Pedestrian Bridge
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
50
100
150
200
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 166 BR Pedestrian Bridge
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 137 4
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 98.5 BR Maine Ave.
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
10
20
30
40
50
60
70
80
90
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 60 3
.04
.065
.
0
6
5
Elevation (ft)
Station (ft)
15
10
5
0
-5
10
20
30
40
50
60
70
80
90
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Ineff
Bank Sta



Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 38 2
.065
.04
.065
Elevation (ft)
Station (ft)
15
10
5
0
-5
0
20
40
60
80
100
Legend
WS Q500
WS Q100
WS Q50
WS Q25
WS Q10
WS Q1.1
0 ft/s
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = 0 1 (Downstream)
.065
.04
.065
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60
Legend
WS Q500
WS Q100
WS Q1.1
WS Q50
WS Q10
WS Q25
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -21 RR
.065
.04
Legend
WS Q1.1
WS Q10
WS Q25
WS Q500
WS Q100
WS Q50
0 ft/s
5 ft/s
10 ft/s
15 ft/s
20 ft/s
Ground
Bank Sta
Elevation (ft)
Station (ft)
20
15
10
5
0
-5
-10
0
10
20
30
40
50
60


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -54 K2
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q50
WS Q25
WS Q10
WS Q1.1
WS Q500
WS Q100
12 ft/s
14 ft/s
16 ft/s
18 ft/s
20 ft/s
22 ft/s
24 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -88 K1
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
0
20
40
60
80
100
120
140
Legend
WS Q500
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q100
6 ft/s
8 ft/s
10 ft/s
12 ft/s
14 ft/s
16 ft/s
18 ft/s
Ground
Bank Sta


Gardiner Proposed 135ftSpan Plan: Plan 02 4/18/2018
Geom: Geom 01 Flow: MHW +3.8 Kennebec Tailwater
RS = -143 K0
.065
.04
.065
Elevation (ft)
Station (ft)
10
8
6
4
2
0
-2
-4
-6
-8
0
20
40
60
80
100
Legend
WS Q100
WS Q1.1
WS Q10
WS Q25
WS Q50
WS Q500
2 ft/s
4 ft/s
6 ft/s
8 ft/s
10 ft/s
12 ft/s
Ground
Bank Sta

HEC-RAS Version 4.1.0 Jan 2010
U.S. Army Corps of Engineers
Hydrologic Engineering Center
609 Second Street
Davis, California

```
X     X  XXXXXX    XXXX        XXXX       XX      XXXX
X     X  X        X    X       X   X     X  X    X
X     X  X        X            X   X    X    X   X
XXXXXXX  XXXX     X       XXX  XXXX     XXXXXX    XXXX
X     X  X        X            X  X     X    X        X
X     X  X        X    X       X   X    X    X        X
X     X  XXXXXX    XXXX        X    X   X    X   XXXXX
```

PROJECT DATA
Project Title: Gardiner Proposed 135ftSpan
Project File : GardinerProposed5.prj
Run Date and Time: 4/18/2018 2:52:22 PM

Project in English units

PLAN DATA

Plan Title: Plan 02
Plan File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.p02

Geometry Title: Geom 01
Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.g01

Flow Title : MHW +3.8 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.f02

Plan Summary Information:
Number of: Cross Sections = 27 Multiple Openings = 0
Culverts = 0 Inline Structures = 0
Bridges = 3 Lateral Structures = 0

Computational Information
Water surface calculation tolerance = 0.01

Critical depth calculation tolerance = 0.01
Maximum number of iterations = 20
Maximum difference tolerance = 0.3
Flow tolerance factor = 0.001

Computation Options
Critical depth computed only where necessary
Conveyance Calculation Method: At breaks in n values only
Friction Slope Method: Average Conveyance
Computational Flow Regime: Mixed Flow

FLOW DATA

Flow Title: MHW +3.8 Kennebec Tailwater
Flow File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.f02

Flow Data (cfs)

River	Reach	RS	Q100	Q1.1	Q10	Q25	Q50	Q500
Cobosee Stream	Reach 1	1700	5910	1312	3850	4148	5290	7380
Cobosee Stream	Reach 1	-88	5910	1312	3850	4148	5290	7380

Boundary Conditions

River	Reach	Profile	Upstream	Downstream
Cobosee Stream	Reach 1	Q100	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q1.1	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q10	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q25	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q50	Critical	Known WS = 3.8
Cobosee Stream	Reach 1	Q500	Critical	Known WS = 3.8

GEOMETRY DATA

Geometry Title: Geom 01

Geometry File : u:\195350266\transportation\calculations\hydraulics\Hec Ras\Final Models\Proposed\GardinerProposed5.g01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1700

INPUT
Description: Upstream (I)
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	40	10	39.7	20	39.2	30	37.2	40	34.5
50	29	60	23.5	70	17.5	80	15.5	90	14.5
100	13.8	110	14.2	120	14.8	130	15.7	140	19
150	25	160	31	170	33.3				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	60	.04	150	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
60	150	65	65	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	24.48	Element			
Vel Head (ft)	1.73	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.75	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	21.32	Flow Area (sq ft)		559.56	
E.G. Slope (ft/ft)	0.006899	Area (sq ft)		559.56	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	84.99	Top Width (ft)		84.99	
Vel Total (ft/s)	10.56	Avg. Vel. (ft/s)		10.56	
Max Chl Dpth (ft)	8.95	Hydr. Depth (ft)		6.58	
Conv. Total (cfs)	71151.3	Conv. (cfs)		71151.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		88.36	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.73	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.19	24.45	1.09
C & E Loss (ft)	0.01	Cum SA (acres)	0.10	3.41	1.11

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	19.04	Element			
Vel Head (ft)	0.50	Wt. n-Val.		0.040	
W.S. Elev (ft)	18.54	Reach Len. (ft)	65.00	65.00	65.00

Crit W.S. (ft)	17.33	Flow Area (sq ft)		231.75	
E.G. Slope (ft/ft)	0.004837	Area (sq ft)		231.75	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	70.35	Top Width (ft)		70.35	
Vel Total (ft/s)	5.66	Avg. Vel. (ft/s)		5.66	
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)		3.29	
Conv. Total (cfs)	18865.3	Conv. (cfs)		18865.3	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		71.44	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		0.98	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.51	Cum Volume (acre-ft)	0.02	10.26	0.06
C & E Loss (ft)	0.03	Cum SA (acres)	0.02	2.83	0.04

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	22.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.15	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	19.81	Flow Area (sq ft)		428.08	
E.G. Slope (ft/ft)	0.006488	Area (sq ft)		428.08	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	79.67	Top Width (ft)		79.67	
Vel Total (ft/s)	8.99	Avg. Vel. (ft/s)		8.99	
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	47797.5	Conv. (cfs)		47797.5	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		82.15	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.11	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.08	17.99	0.17
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	3.23	0.07

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.73	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.33	Wt. n-Val.		0.040	
W.S. Elev (ft)	21.40	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.05	Flow Area (sq ft)		447.72	
E.G. Slope (ft/ft)	0.006586	Area (sq ft)		447.72	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	80.49	Top Width (ft)		80.49	
Vel Total (ft/s)	9.26	Avg. Vel. (ft/s)		9.26	
Max Chl Dpth (ft)	7.60	Hydr. Depth (ft)		5.56	
Conv. Total (cfs)	51113.2	Conv. (cfs)		51113.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		83.10	

Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.22	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.53	Cum Volume (acre-ft)	0.09	18.96	0.19
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	3.28	0.09

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.040	
W.S. Elev (ft)	22.28	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	20.89	Flow Area (sq ft)		519.99	
E.G. Slope (ft/ft)	0.006865	Area (sq ft)		519.99	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	83.43	Top Width (ft)		83.43	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	63848.2	Conv. (cfs)		63848.2	
Length Wtd. (ft)	65.00	Wetted Per. (ft)		86.53	
Min Ch El (ft)	13.80	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.52	Cum Volume (acre-ft)	0.14	22.60	0.53
C & E Loss (ft)	0.00	Cum SA (acres)	0.07	3.38	0.56

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.00	Wt. n-Val.	0.070	0.040	
W.S. Elev (ft)	23.79	Reach Len. (ft)	65.00	65.00	65.00
Crit W.S. (ft)	22.27	Flow Area (sq ft)	0.08	649.67	
E.G. Slope (ft/ft)	0.006886	Area (sq ft)	0.08	649.67	
Q Total (cfs)	7380.00	Flow (cfs)	0.03	7379.97	
Top Width (ft)	88.50	Top Width (ft)	0.52	87.98	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	0.44	11.36	
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	0.14	7.38	
Conv. Total (cfs)	88935.3	Conv. (cfs)	0.4	88934.8	
Length Wtd. (ft)	65.00	Wetted Per. (ft)	0.60	91.84	
Min Ch El (ft)	13.80	Shear (lb/sq ft)	0.05	3.04	
Alpha	1.00	Stream Power (lb/ft s)	170.00	0.00	0.00
Frctn Loss (ft)	0.50	Cum Volume (acre-ft)	0.36	28.96	3.67
C & E Loss (ft)	0.03	Cum SA (acres)	0.16	3.46	2.01

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1635

INPUT
Description: H

Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	23.5	40	17
50	14	60	14.5	70	15	80	15.2	90	15.4
100	15.6	110	15.8	115	17.9	120	20	130	26.5
140	30.1	150	30.2						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.045	130	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	130	80	80	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	23.95	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.69	Wt. n-Val.		0.045	
W.S. Elev (ft)	22.26	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		565.73	
E.G. Slope (ft/ft)	0.009287	Area (sq ft)		565.73	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	91.56	Top Width (ft)		91.56	
Vel Total (ft/s)	10.45	Avg. Vel. (ft/s)		10.45	
Max Chl Dpth (ft)	8.26	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	61328.2	Conv. (cfs)		61328.2	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		95.11	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.45	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.90	Cum Volume (acre-ft)	0.19	23.61	1.09
C & E Loss (ft)	0.09	Cum SA (acres)	0.10	3.28	1.11

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	18.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.045	
W.S. Elev (ft)	17.69	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		181.92	
E.G. Slope (ft/ft)	0.015059	Area (sq ft)		181.92	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	75.56	Top Width (ft)		75.56	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	

Max Chl Dpth (ft)	3.69	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	10691.3	Conv. (cfs)		10691.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		76.62	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		2.23	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.04	Cum Volume (acre-ft)	0.02	9.95	0.06
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	2.72	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	21.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.47	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		407.41	
E.G. Slope (ft/ft)	0.010705	Area (sq ft)		407.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	86.08	Top Width (ft)		86.08	
Vel Total (ft/s)	9.45	Avg. Vel. (ft/s)		9.45	
Max Chl Dpth (ft)	6.47	Hydr. Depth (ft)		4.73	
Conv. Total (cfs)	37210.3	Conv. (cfs)		37210.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		88.57	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.07	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.08	17.37	0.17
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	3.11	0.07

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	22.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.43	Wt. n-Val.		0.045	
W.S. Elev (ft)	20.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		431.49	
E.G. Slope (ft/ft)	0.010420	Area (sq ft)		431.49	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	86.93	Top Width (ft)		86.93	
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.61	
Max Chl Dpth (ft)	6.75	Hydr. Depth (ft)		4.96	
Conv. Total (cfs)	40635.4	Conv. (cfs)		40635.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		89.59	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.13	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)	0.09	18.30	0.19
C & E Loss (ft)	0.05	Cum SA (acres)	0.04	3.15	0.09

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	23.36	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.61	Wt. n-Val.		0.045	
W.S. Elev (ft)	21.75	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		520.12	
E.G. Slope (ft/ft)	0.009593	Area (sq ft)		520.12	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	90.01	Top Width (ft)		90.01	
Vel Total (ft/s)	10.17	Avg. Vel. (ft/s)		10.17	
Max Chl Dpth (ft)	7.75	Hydr. Depth (ft)		5.78	
Conv. Total (cfs)	54011.4	Conv. (cfs)		54011.4	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		93.26	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.91	Cum Volume (acre-ft)	0.14	21.82	0.53
C & E Loss (ft)	0.08	Cum SA (acres)	0.07	3.25	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	25.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.89	Wt. n-Val.		0.045	
W.S. Elev (ft)	23.37	Reach Len. (ft)	80.00	80.00	80.00
Crit W.S. (ft)		Flow Area (sq ft)		669.19	
E.G. Slope (ft/ft)	0.008748	Area (sq ft)		669.19	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	94.97	Top Width (ft)		94.97	
Vel Total (ft/s)	11.03	Avg. Vel. (ft/s)		11.03	
Max Chl Dpth (ft)	9.37	Hydr. Depth (ft)		7.05	
Conv. Total (cfs)	78902.3	Conv. (cfs)		78902.3	
Length Wtd. (ft)	80.00	Wetted Per. (ft)		99.18	
Min Ch El (ft)	14.00	Shear (lb/sq ft)		3.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	0.87	Cum Volume (acre-ft)	0.36	27.98	3.67
C & E Loss (ft)	0.11	Cum SA (acres)	0.16	3.32	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1555

INPUT
Description: G
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	34	20	28	30	21.5	40	15
50	13.8	60	13.6	70	13.3	80	13.5	90	13.5
100	14.5	110	19	120	26	130	29	140	29.5
150	29.9								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.07	30	.042	120	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
30	120	100	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	22.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.62	Wt. n-Val.		0.042	
W.S. Elev (ft)	20.34	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	20.16	Flow Area (sq ft)		455.11	
E.G. Slope (ft/ft)	0.013986	Area (sq ft)		455.11	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	80.13	Top Width (ft)		80.13	
Vel Total (ft/s)	12.99	Avg. Vel. (ft/s)		12.99	
Max Chl Dpth (ft)	7.04	Hydr. Depth (ft)		5.68	
Conv. Total (cfs)	49972.8	Conv. (cfs)		49972.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		83.24	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.77	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.37	Cum Volume (acre-ft)	0.19	22.67	1.09
C & E Loss (ft)	0.07	Cum SA (acres)	0.10	3.12	1.11

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	17.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.81	Wt. n-Val.		0.042	
W.S. Elev (ft)	16.65	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)		Flow Area (sq ft)		181.93	

E.G. Slope (ft/ft)	0.011277	Area (sq ft)		181.93	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	67.33	Top Width (ft)		67.33	
Vel Total (ft/s)	7.21	Avg. Vel. (ft/s)		7.21	
Max Chl Dpth (ft)	3.35	Hydr. Depth (ft)		2.70	
Conv. Total (cfs)	12355.0	Conv. (cfs)		12355.0	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.41	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		1.87	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.02	9.61	0.06
C & E Loss (ft)	0.02	Cum SA (acres)	0.02	2.59	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	20.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.06	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.65	Flow Area (sq ft)		355.05	
E.G. Slope (ft/ft)	0.012593	Area (sq ft)		355.05	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.34	Top Width (ft)		76.34	
Vel Total (ft/s)	10.84	Avg. Vel. (ft/s)		10.84	
Max Chl Dpth (ft)	5.76	Hydr. Depth (ft)		4.65	
Conv. Total (cfs)	34308.4	Conv. (cfs)		34308.4	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		78.66	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.55	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.08	16.67	0.17
C & E Loss (ft)	0.02	Cum SA (acres)	0.04	2.96	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	21.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.96	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	18.89	Flow Area (sq ft)		368.77	
E.G. Slope (ft/ft)	0.013023	Area (sq ft)		368.77	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	76.87	Top Width (ft)		76.87	
Vel Total (ft/s)	11.25	Avg. Vel. (ft/s)		11.25	
Max Chl Dpth (ft)	5.94	Hydr. Depth (ft)		4.80	

Conv. Total (cfs)	36348.9	Conv. (cfs)		36348.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		79.30	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		3.78	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.46	Cum Volume (acre-ft)	0.09	17.57	0.19
C & E Loss (ft)	0.01	Cum SA (acres)	0.04	3.00	0.09

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	22.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.41	Wt. n-Val.		0.042	
W.S. Elev (ft)	19.96	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	19.73	Flow Area (sq ft)		424.40	
E.G. Slope (ft/ft)	0.013832	Area (sq ft)		424.40	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	78.99	Top Width (ft)		78.99	
Vel Total (ft/s)	12.46	Avg. Vel. (ft/s)		12.46	
Max Chl Dpth (ft)	6.66	Hydr. Depth (ft)		5.37	
Conv. Total (cfs)	44978.9	Conv. (cfs)		44978.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		81.85	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		4.48	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.41	Cum Volume (acre-ft)	0.14	20.95	0.53
C & E Loss (ft)	0.04	Cum SA (acres)	0.07	3.10	0.56

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	24.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.03	Wt. n-Val.		0.042	
W.S. Elev (ft)	21.24	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	21.12	Flow Area (sq ft)		528.57	
E.G. Slope (ft/ft)	0.013933	Area (sq ft)		528.57	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	82.81	Top Width (ft)		82.81	
Vel Total (ft/s)	13.96	Avg. Vel. (ft/s)		13.96	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)		6.38	
Conv. Total (cfs)	62522.2	Conv. (cfs)		62522.2	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		86.46	
Min Ch El (ft)	13.30	Shear (lb/sq ft)		5.32	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.36	26.88	3.67

C & E Loss (ft)	0.13	Cum SA (acres)	0.16	3.16	2.01

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1455

INPUT
Description: F
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	45	10	38	20	31	30	24	40	16.5
50	12.5	60	11.8	70	12	80	12.3	90	12.6
100	12.8	110	14	120	18.5	130	23	140	28
150	30								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	120	120	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	21.52	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.37	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	19.15	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.73	Flow Area (sq ft)	4.68	476.91	0.47
E.G. Slope (ft/ft)	0.013371	Area (sq ft)	4.68	476.91	0.47
Q Total (cfs)	5910.00	Flow (cfs)	12.85	5896.64	0.51
Top Width (ft)	84.97	Top Width (ft)	3.53	80.00	1.44
Vel Total (ft/s)	12.26	Avg. Vel. (ft/s)	2.75	12.36	1.09
Max Chl Dpth (ft)	7.35	Hydr. Depth (ft)	1.32	5.96	0.32
Conv. Total (cfs)	51109.1	Conv. (cfs)	111.1	50993.5	4.4
Length Wtd. (ft)	120.00	Wetted Per. (ft)	4.41	81.85	1.58
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.88	4.86	0.25
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.18	21.60	1.09
C & E Loss (ft)	0.17	Cum SA (acres)	0.09	2.94	1.10

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	16.04	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.06	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	14.87	Flow Area (sq ft)		165.73	
E.G. Slope (ft/ft)	0.018077	Area (sq ft)		165.73	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	68.77	Top Width (ft)		68.77	
Vel Total (ft/s)	7.92	Avg. Vel. (ft/s)		7.92	
Max Chl Dpth (ft)	3.26	Hydr. Depth (ft)		2.41	
Conv. Total (cfs)	9758.3	Conv. (cfs)		9758.3	
Length Wtd. (ft)	120.00	Wetted Per. (ft)		69.60	
Min Ch El (ft)	11.80	Shear (lb/sq ft)		2.69	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	2.24	Cum Volume (acre-ft)	0.02	9.22	0.06
C & E Loss (ft)	0.02	Cum SA (acres)	0.02	2.43	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.01	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.40	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.28	Flow Area (sq ft)	0.54	338.38	
E.G. Slope (ft/ft)	0.017108	Area (sq ft)	0.54	338.38	
Q Total (cfs)	3850.00	Flow (cfs)	0.82	3849.18	
Top Width (ft)	78.76	Top Width (ft)	1.20	77.56	
Vel Total (ft/s)	11.36	Avg. Vel. (ft/s)	1.51	11.38	
Max Chl Dpth (ft)	5.60	Hydr. Depth (ft)	0.45	4.36	
Conv. Total (cfs)	29434.8	Conv. (cfs)	6.3	29428.6	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.50	79.17	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.38	4.57	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.59	Cum Volume (acre-ft)	0.08	15.87	0.17
C & E Loss (ft)	0.14	Cum SA (acres)	0.04	2.78	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	19.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.07	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.67	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	17.49	Flow Area (sq ft)	0.91	359.11	
E.G. Slope (ft/ft)	0.016461	Area (sq ft)	0.91	359.11	
Q Total (cfs)	4148.00	Flow (cfs)	1.60	4146.40	
Top Width (ft)	79.70	Top Width (ft)	1.56	78.15	
Vel Total (ft/s)	11.52	Avg. Vel. (ft/s)	1.76	11.55	
Max Chl Dpth (ft)	5.87	Hydr. Depth (ft)	0.58	4.60	
Conv. Total (cfs)	32330.5	Conv. (cfs)	12.5	32318.0	
Length Wtd. (ft)	120.00	Wetted Per. (ft)	1.94	79.81	
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.48	4.62	
Alpha	1.00	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.53	Cum Volume (acre-ft)	0.09	16.73	0.19
C & E Loss (ft)	0.14	Cum SA (acres)	0.04	2.83	0.09

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	20.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.27	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	18.65	Reach Len. (ft)	120.00	120.00	120.00
Crit W.S. (ft)	18.33	Flow Area (sq ft)	3.07	436.66	0.02
E.G. Slope (ft/ft)	0.014397	Area (sq ft)	3.07	436.66	0.02
Q Total (cfs)	5290.00	Flow (cfs)	7.60	5282.39	0.01
Top Width (ft)	83.19	Top Width (ft)	2.86	80.00	0.32
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	2.48	12.10	0.42
Max Chl Dpth (ft)	6.85	Hydr. Depth (ft)	1.07	5.46	0.07
Conv. Total (cfs)	44088.4	Conv. (cfs)	63.4	44024.9	0.1
Length Wtd. (ft)	120.00	Wetted Per. (ft)	3.58	81.85	0.36
Min Ch El (ft)	11.80	Shear (lb/sq ft)	0.77	4.80	0.06
Alpha	1.01	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.34	Cum Volume (acre-ft)	0.14	19.97	0.53
C & E Loss (ft)	0.16	Cum SA (acres)	0.07	2.91	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	22.87	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.58	Wt. n-Val.	0.065	0.045	0.070
W.S. Elev (ft)	20.28	Reach Len. (ft)	120.00	120.00	120.00

Crit W.S. (ft)		Flow Area (sq ft)	9.55	567.80	3.54
E.G. Slope (ft/ft)	0.011590	Area (sq ft)	9.55	567.80	3.54
Q Total (cfs)	7380.00	Flow (cfs)	30.99	7341.96	7.05
Top Width (ft)	89.01	Top Width (ft)	5.05	80.00	3.97
Vel Total (ft/s)	12.70	Avg. Vel. (ft/s)	3.24	12.93	1.99
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)	1.89	7.10	0.89
Conv. Total (cfs)	68552.3	Conv. (cfs)	287.9	68198.9	65.5
Length Wtd. (ft)	120.00	Wetted Per. (ft)	6.31	81.85	4.35
Min Ch El (ft)	11.80	Shear (lb/sq ft)	1.10	5.02	0.59
Alpha	1.03	Stream Power (lb/ft s)	150.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.34	25.62	3.67
C & E Loss (ft)	0.18	Cum SA (acres)	0.16	2.97	2.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1335

INPUT
Description: E
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	42.5	10	37.5	20	31	30	24	40	17
50	11	60	9.5	70	9.5	80	9.5	90	9.5
100	10.5	110	14	120	19	130	23	140	28
150	29	160	30						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	40	.045	120	.075

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
40	120	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	20.09	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.80	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	18.29	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.19	548.74	
E.G. Slope (ft/ft)	0.008433	Area (sq ft)	1.19	548.74	
Q Total (cfs)	5910.00	Flow (cfs)	1.63	5908.37	

Top Width (ft)	80.42	Top Width (ft)	1.84	78.58	
Vel Total (ft/s)	10.75	Avg. Vel. (ft/s)	1.37	10.77	
Max Chl Dpth (ft)	8.79	Hydr. Depth (ft)	0.65	6.98	
Conv. Total (cfs)	64355.9	Conv. (cfs)	17.8	64338.2	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.25	82.01	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.28	3.52	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.56	Cum Volume (acre-ft)	0.17	20.19	1.09
C & E Loss (ft)	0.09	Cum SA (acres)	0.09	2.72	1.10

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	13.78	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.14	Wt. n-Val.		0.045	
W.S. Elev (ft)	12.63	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)	12.50	Flow Area (sq ft)		152.87	
E.G. Slope (ft/ft)	0.019322	Area (sq ft)		152.87	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	58.82	Top Width (ft)		58.82	
Vel Total (ft/s)	8.58	Avg. Vel. (ft/s)		8.58	
Max Chl Dpth (ft)	3.13	Hydr. Depth (ft)		2.60	
Conv. Total (cfs)	9438.5	Conv. (cfs)		9438.5	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		59.79	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.08	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.87	Cum Volume (acre-ft)	0.02	8.78	0.06
C & E Loss (ft)	0.10	Cum SA (acres)	0.02	2.26	0.04

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	17.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.56	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.13	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		384.33	
E.G. Slope (ft/ft)	0.010509	Area (sq ft)		384.33	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	72.81	Top Width (ft)		72.81	

Vel Total (ft/s)	10.02	Avg. Vel. (ft/s)		10.02	
Max Chl Dpth (ft)	6.63	Hydr. Depth (ft)		5.28	
Conv. Total (cfs)	37556.7	Conv. (cfs)		37556.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		75.49	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.34	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.65	Cum Volume (acre-ft)	0.07	14.88	0.17
C & E Loss (ft)	0.04	Cum SA (acres)	0.04	2.58	0.07

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	18.07	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.		0.045	
W.S. Elev (ft)	16.48	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		409.66	
E.G. Slope (ft/ft)	0.010113	Area (sq ft)		409.66	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	74.08	Top Width (ft)		74.08	
Vel Total (ft/s)	10.13	Avg. Vel. (ft/s)		10.13	
Max Chl Dpth (ft)	6.98	Hydr. Depth (ft)		5.53	
Conv. Total (cfs)	41247.6	Conv. (cfs)		41247.6	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		76.94	
Min Ch El (ft)	9.50	Shear (lb/sq ft)		3.36	
Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.64	Cum Volume (acre-ft)	0.08	15.67	0.19
C & E Loss (ft)	0.05	Cum SA (acres)	0.04	2.62	0.09

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	19.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	17.68	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.34	501.53	
E.G. Slope (ft/ft)	0.008923	Area (sq ft)	0.34	501.53	
Q Total (cfs)	5290.00	Flow (cfs)	0.31	5289.69	
Top Width (ft)	78.35	Top Width (ft)	0.98	77.37	
Vel Total (ft/s)	10.54	Avg. Vel. (ft/s)	0.93	10.55	
Max Chl Dpth (ft)	8.18	Hydr. Depth (ft)	0.34	6.48	
Conv. Total (cfs)	56001.4	Conv. (cfs)	3.3	55998.1	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	1.19	80.66	
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.16	3.46	

Alpha	1.00	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.58	Cum Volume (acre-ft)	0.13	18.67	0.53
C & E Loss (ft)	0.07	Cum SA (acres)	0.06	2.70	0.56

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	21.58	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.97	Wt. n-Val.	0.065	0.045	0.075
W.S. Elev (ft)	19.61	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.86	653.63	0.46
E.G. Slope (ft/ft)	0.007513	Area (sq ft)	4.86	653.63	0.46
Q Total (cfs)	7380.00	Flow (cfs)	10.06	7369.60	0.34
Top Width (ft)	85.25	Top Width (ft)	3.73	80.00	1.52
Vel Total (ft/s)	11.20	Avg. Vel. (ft/s)	2.07	11.27	0.74
Max Chl Dpth (ft)	10.11	Hydr. Depth (ft)	1.30	8.17	0.30
Conv. Total (cfs)	85143.6	Conv. (cfs)	116.1	85023.6	3.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.55	83.60	1.64
Min Ch El (ft)	9.50	Shear (lb/sq ft)	0.50	3.67	0.13
Alpha	1.01	Stream Power (lb/ft s)	160.00	0.00	0.00
Frctn Loss (ft)	1.52	Cum Volume (acre-ft)	0.33	23.94	3.67
C & E Loss (ft)	0.14	Cum SA (acres)	0.14	2.75	2.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1185

INPUT
Description: D
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	41.5	4	40	10	35	20	27.5	30	20
35	16	40	12	50	7	60	5.5	70	6
80	7	90	11	100	16	110	22	120	28
130	28.2								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	35	.045	110	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
35	110	125	125	.1	.3

CROSS SECTION OUTPUT Profile #Q100

		Element	Left OB	Channel	Right OB
E.G. Elev (ft)	18.43				
Vel Head (ft)	2.72	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.71	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	15.05	Flow Area (sq ft)		446.60	
E.G. Slope (ft/ft)	0.013216	Area (sq ft)		446.60	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	64.07	Top Width (ft)		64.07	
Vel Total (ft/s)	13.23	Avg. Vel. (ft/s)		13.23	
Max Chl Dpth (ft)	10.21	Hydr. Depth (ft)		6.97	
Conv. Total (cfs)	51408.5	Conv. (cfs)		51408.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		68.61	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		5.37	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.68	Cum Volume (acre-ft)	0.17	18.48	1.09
C & E Loss (ft)	0.04	Cum SA (acres)	0.08	2.47	1.10

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

		Element	Left OB	Channel	Right OB
E.G. Elev (ft)	11.81				
Vel Head (ft)	0.82	Wt. n-Val.		0.045	
W.S. Elev (ft)	10.99	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)		Flow Area (sq ft)		180.58	
E.G. Slope (ft/ft)	0.008701	Area (sq ft)		180.58	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	47.96	Top Width (ft)		47.96	
Vel Total (ft/s)	7.27	Avg. Vel. (ft/s)		7.27	
Max Chl Dpth (ft)	5.49	Hydr. Depth (ft)		3.77	
Conv. Total (cfs)	14065.5	Conv. (cfs)		14065.5	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		49.85	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		1.97	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.49	Cum Volume (acre-ft)	0.02	8.20	0.06
C & E Loss (ft)	0.06	Cum SA (acres)	0.02	2.07	0.04

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for

additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	16.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.93	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.07	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.16	Flow Area (sq ft)		345.59	
E.G. Slope (ft/ft)	0.011592	Area (sq ft)		345.59	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	58.73	Top Width (ft)		58.73	
Vel Total (ft/s)	11.14	Avg. Vel. (ft/s)		11.14	
Max Chl Dpth (ft)	8.57	Hydr. Depth (ft)		5.88	
Conv. Total (cfs)	35758.2	Conv. (cfs)		35758.2	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		62.30	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.01	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.62	Cum Volume (acre-ft)	0.07	13.62	0.17
C & E Loss (ft)	0.06	Cum SA (acres)	0.04	2.35	0.07

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	16.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.05	Wt. n-Val.		0.045	
W.S. Elev (ft)	14.34	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	13.46	Flow Area (sq ft)		361.45	
E.G. Slope (ft/ft)	0.011842	Area (sq ft)		361.45	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	59.60	Top Width (ft)		59.60	
Vel Total (ft/s)	11.48	Avg. Vel. (ft/s)		11.48	
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		6.06	
Conv. Total (cfs)	38117.1	Conv. (cfs)		38117.1	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		63.33	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.22	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.63	Cum Volume (acre-ft)	0.08	14.35	0.19
C & E Loss (ft)	0.06	Cum SA (acres)	0.04	2.39	0.09

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	17.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.47	Wt. n-Val.		0.045	
W.S. Elev (ft)	15.28	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	14.52	Flow Area (sq ft)		419.10	
E.G. Slope (ft/ft)	0.012665	Area (sq ft)		419.10	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	62.66	Top Width (ft)		62.66	
Vel Total (ft/s)	12.62	Avg. Vel. (ft/s)		12.62	
Max Chl Dpth (ft)	9.78	Hydr. Depth (ft)		6.69	
Conv. Total (cfs)	47005.3	Conv. (cfs)		47005.3	
Length Wtd. (ft)	125.00	Wetted Per. (ft)		66.95	
Min Ch El (ft)	5.50	Shear (lb/sq ft)		4.95	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.66	Cum Volume (acre-ft)	0.13	17.09	0.53
C & E Loss (ft)	0.05	Cum SA (acres)	0.06	2.46	0.56

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	19.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.33	Wt. n-Val.	0.065	0.045	
W.S. Elev (ft)	16.59	Reach Len. (ft)	125.00	125.00	125.00
Crit W.S. (ft)	16.20	Flow Area (sq ft)	0.22	503.94	
E.G. Slope (ft/ft)	0.014382	Area (sq ft)	0.22	503.94	
Q Total (cfs)	7380.00	Flow (cfs)	0.23	7379.77	
Top Width (ft)	66.73	Top Width (ft)	0.74	65.99	
Vel Total (ft/s)	14.64	Avg. Vel. (ft/s)	1.04	14.64	
Max Chl Dpth (ft)	11.09	Hydr. Depth (ft)	0.30	7.64	
Conv. Total (cfs)	61538.8	Conv. (cfs)	1.9	61536.9	
Length Wtd. (ft)	125.00	Wetted Per. (ft)	0.95	70.86	
Min Ch El (ft)	5.50	Shear (lb/sq ft)	0.21	6.39	
Alpha	1.00	Stream Power (lb/ft s)	130.00	0.00	0.00
Frctn Loss (ft)	1.73	Cum Volume (acre-ft)	0.32	21.94	3.66
C & E Loss (ft)	0.02	Cum SA (acres)	0.14	2.50	2.00

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 1060

INPUT
Description: C
Station Elevation Data num= 16

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	35	10	33	20	35	30	29	40	23
45	19.5	50	16	60	10	70	7	80	5.5
90	5	100	5	110	7	120	13	130	20
200	20.1								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	45	.04	130	.07

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
45	130	100	100	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	16.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.12	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.60	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.60	Flow Area (sq ft)		416.89	
E.G. Slope (ft/ft)	0.013608	Area (sq ft)		416.89	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	66.85	Top Width (ft)		66.85	
Vel Total (ft/s)	14.18	Avg. Vel. (ft/s)		14.18	
Max Chl Dpth (ft)	8.60	Hydr. Depth (ft)		6.24	
Conv. Total (cfs)	50662.6	Conv. (cfs)		50662.6	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		70.46	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.03	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.12	Cum Volume (acre-ft)	0.17	17.24	1.09
C & E Loss (ft)	0.22	Cum SA (acres)	0.08	2.28	1.10

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is

not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.41	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.85	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	8.85	Flow Area (sq ft)		137.48	
E.G. Slope (ft/ft)	0.017292	Area (sq ft)		137.48	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	49.24	Top Width (ft)		49.24	
Vel Total (ft/s)	9.54	Avg. Vel. (ft/s)		9.54	
Max Chl Dpth (ft)	3.85	Hydr. Depth (ft)		2.79	
Conv. Total (cfs)	9977.1	Conv. (cfs)		9977.1	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		50.35	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		2.95	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.51	Cum Volume (acre-ft)	0.02	7.75	0.06
C & E Loss (ft)	0.13	Cum SA (acres)	0.02	1.93	0.04

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	14.32	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.49	Wt. n-Val.		0.040	
W.S. Elev (ft)	11.83	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	11.83	Flow Area (sq ft)		303.73	
E.G. Slope (ft/ft)	0.014510	Area (sq ft)		303.73	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	61.10	Top Width (ft)		61.10	
Vel Total (ft/s)	12.68	Avg. Vel. (ft/s)		12.68	
Max Chl Dpth (ft)	6.83	Hydr. Depth (ft)		4.97	
Conv. Total (cfs)	31961.2	Conv. (cfs)		31961.2	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		63.71	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.32	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.27	Cum Volume (acre-ft)	0.07	12.69	0.17
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	2.18	0.07

Warning: The energy equation could not be balanced within the specified number of iterations. The

program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	14.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	12.11	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	12.11	Flow Area (sq ft)		320.83	
E.G. Slope (ft/ft)	0.014350	Area (sq ft)		320.83	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	62.03	Top Width (ft)		62.03	
Vel Total (ft/s)	12.93	Avg. Vel. (ft/s)		12.93	
Max Chl Dpth (ft)	7.11	Hydr. Depth (ft)		5.17	
Conv. Total (cfs)	34626.6	Conv. (cfs)		34626.6	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		64.79	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.44	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.26	Cum Volume (acre-ft)	0.08	13.37	0.19
C & E Loss (ft)	0.16	Cum SA (acres)	0.04	2.21	0.09

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	16.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.95	Wt. n-Val.		0.040	
W.S. Elev (ft)	13.10	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	13.10	Flow Area (sq ft)		383.70	
E.G. Slope (ft/ft)	0.013874	Area (sq ft)		383.70	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.29	Top Width (ft)		65.29	
Vel Total (ft/s)	13.79	Avg. Vel. (ft/s)		13.79	
Max Chl Dpth (ft)	8.10	Hydr. Depth (ft)		5.88	

Conv. Total (cfs)	44910.9	Conv. (cfs)		44910.9	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		68.61	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		4.84	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.13	Cum Volume (acre-ft)	0.13	15.94	0.53
C & E Loss (ft)	0.23	Cum SA (acres)	0.06	2.27	0.56

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	18.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	14.68	Reach Len. (ft)	100.00	100.00	100.00
Crit W.S. (ft)	14.68	Flow Area (sq ft)		490.72	
E.G. Slope (ft/ft)	0.013258	Area (sq ft)		490.72	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	70.18	Top Width (ft)		70.18	
Vel Total (ft/s)	15.04	Avg. Vel. (ft/s)		15.04	
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)		6.99	
Conv. Total (cfs)	64094.8	Conv. (cfs)		64094.8	
Length Wtd. (ft)	100.00	Wetted Per. (ft)		74.43	
Min Ch El (ft)	5.00	Shear (lb/sq ft)		5.46	
Alpha	1.00	Stream Power (lb/ft s)	200.00	0.00	0.00
Frctn Loss (ft)	1.11	Cum Volume (acre-ft)	0.32	20.52	3.66
C & E Loss (ft)	0.21	Cum SA (acres)	0.14	2.30	2.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 960

INPUT
Description: B
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	32	17.3	29	67	5	79.4	5	85.5	4
100.5	3.5	114.3	4	124.5	5	140	12	202.9	14.2
203	14.5	209.1	15	224.5	20	229.5	25		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	67	.042	124.5	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
67	124.5	25	25	.3	.5

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	14.55	Element	Left OB	Channel	Right OB
Vel Head (ft)	5.12	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.43	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.91	Flow Area (sq ft)	20.34	299.03	21.75
E.G. Slope (ft/ft)	0.030767	Area (sq ft)	20.34	299.03	21.75
Q Total (cfs)	5910.00	Flow (cfs)	168.11	5560.68	181.20
Top Width (ft)	76.49	Top Width (ft)	9.18	57.50	9.82
Vel Total (ft/s)	17.32	Avg. Vel. (ft/s)	8.26	18.60	8.33
Max Chl Dpth (ft)	5.93	Hydr. Depth (ft)	2.22	5.20	2.22
Conv. Total (cfs)	33693.3	Conv. (cfs)	958.4	31701.8	1033.1
Length Wtd. (ft)	25.00	Wetted Per. (ft)	10.19	57.65	10.77
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.83	9.96	3.88
Alpha	1.10	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.97	Cum Volume (acre-ft)	0.15	16.42	1.07
C & E Loss (ft)	0.20	Cum SA (acres)	0.07	2.14	1.09

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	8.04	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.60	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	6.44	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	6.75	Flow Area (sq ft)	2.14	126.86	2.29
E.G. Slope (ft/ft)	0.029093	Area (sq ft)	2.14	126.86	2.29
Q Total (cfs)	1312.00	Flow (cfs)	8.13	1295.11	8.76
Top Width (ft)	63.66	Top Width (ft)	2.98	57.50	3.18
Vel Total (ft/s)	9.99	Avg. Vel. (ft/s)	3.79	10.21	3.82
Max Chl Dpth (ft)	2.94	Hydr. Depth (ft)	0.72	2.21	0.72
Conv. Total (cfs)	7692.0	Conv. (cfs)	47.7	7593.0	51.4
Length Wtd. (ft)	25.00	Wetted Per. (ft)	3.31	57.65	3.49
Min Ch El (ft)	3.50	Shear (lb/sq ft)	1.18	4.00	1.19
Alpha	1.03	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.21	Cum Volume (acre-ft)	0.02	7.44	0.06
C & E Loss (ft)	0.02	Cum SA (acres)	0.01	1.81	0.04

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	12.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.85	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	8.24	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.32	Flow Area (sq ft)	10.89	230.65	11.65
E.G. Slope (ft/ft)	0.032272	Area (sq ft)	10.89	230.65	11.65
Q Total (cfs)	3850.00	Flow (cfs)	74.85	3694.47	80.68
Top Width (ft)	71.40	Top Width (ft)	6.72	57.50	7.18
Vel Total (ft/s)	15.21	Avg. Vel. (ft/s)	6.87	16.02	6.93
Max Chl Dpth (ft)	4.74	Hydr. Depth (ft)	1.62	4.01	1.62
Conv. Total (cfs)	21431.3	Conv. (cfs)	416.7	20565.5	449.1
Length Wtd. (ft)	25.00	Wetted Per. (ft)	7.46	57.65	7.88
Min Ch El (ft)	3.50	Shear (lb/sq ft)	2.94	8.06	2.98
Alpha	1.07	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.09	Cum Volume (acre-ft)	0.06	12.08	0.15
C & E Loss (ft)	0.13	Cum SA (acres)	0.03	2.04	0.06

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	12.48	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.06	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	8.43	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	9.57	Flow Area (sq ft)	12.16	241.21	13.00
E.G. Slope (ft/ft)	0.032073	Area (sq ft)	12.16	241.21	13.00
Q Total (cfs)	4148.00	Flow (cfs)	86.43	3968.41	93.16
Top Width (ft)	72.19	Top Width (ft)	7.10	57.50	7.59
Vel Total (ft/s)	15.57	Avg. Vel. (ft/s)	7.11	16.45	7.16
Max Chl Dpth (ft)	4.93	Hydr. Depth (ft)	1.71	4.19	1.71
Conv. Total (cfs)	23161.7	Conv. (cfs)	482.6	22158.9	520.2
Length Wtd. (ft)	25.00	Wetted Per. (ft)	7.88	57.65	8.33
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.09	8.38	3.13
Alpha	1.08	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.07	Cum Volume (acre-ft)	0.07	12.72	0.17
C & E Loss (ft)	0.14	Cum SA (acres)	0.03	2.08	0.08

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	13.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.76	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.09	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	10.43	Flow Area (sq ft)	17.35	279.49	18.55
E.G. Slope (ft/ft)	0.031227	Area (sq ft)	17.35	279.49	18.55
Q Total (cfs)	5290.00	Flow (cfs)	136.92	5005.50	147.58
Top Width (ft)	75.04	Top Width (ft)	8.48	57.50	9.06
Vel Total (ft/s)	16.77	Avg. Vel. (ft/s)	7.89	17.91	7.96
Max Chl Dpth (ft)	5.59	Hydr. Depth (ft)	2.05	4.86	2.05
Conv. Total (cfs)	29935.7	Conv. (cfs)	774.8	28325.7	835.2
Length Wtd. (ft)	25.00	Wetted Per. (ft)	9.41	57.65	9.94
Min Ch El (ft)	3.50	Shear (lb/sq ft)	3.59	9.45	3.64
Alpha	1.09	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	2.00	Cum Volume (acre-ft)	0.11	15.18	0.51
C & E Loss (ft)	0.18	Cum SA (acres)	0.05	2.13	0.55

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.

This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	16.05	Element			
Vel Head (ft)	5.85	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	10.20	Reach Len. (ft)	25.00	25.00	25.00
Crit W.S. (ft)	11.80	Flow Area (sq ft)	28.01	343.23	29.95
E.G. Slope (ft/ft)	0.029537	Area (sq ft)	28.01	343.23	29.95
Q Total (cfs)	7380.00	Flow (cfs)	252.32	6855.72	271.96
Top Width (ft)	79.79	Top Width (ft)	10.77	57.50	11.52
Vel Total (ft/s)	18.40	Avg. Vel. (ft/s)	9.01	19.97	9.08
Max Chl Dpth (ft)	6.70	Hydr. Depth (ft)	2.60	5.97	2.60
Conv. Total (cfs)	42940.8	Conv. (cfs)	1468.1	39890.3	1582.4
Length Wtd. (ft)	25.00	Wetted Per. (ft)	11.96	57.65	12.64
Min Ch El (ft)	3.50	Shear (lb/sq ft)	4.32	10.98	4.37
Alpha	1.11	Stream Power (lb/ft s)	229.50	0.00	0.00
Frctn Loss (ft)	1.90	Cum Volume (acre-ft)	0.28	19.56	3.63
C & E Loss (ft)	0.23	Cum SA (acres)	0.12	2.16	1.99

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Note: Program found supercritical flow starting at this cross section.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 935

INPUT
Description: JU
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	15.3	30	23.8	27.1	35	27	37.7	19
62	5	79	5	82.2	4	105.2	2	121.1	3
125.6	4	137.4	10	203	12.5	203.1	13	203.2	13.1
208.7	13.4	231.8	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	62	.042	125.6	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
62	125.6	85	85	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	35	28	F
188	231.8	26	F

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	13.32	Element			
Vel Head (ft)	1.57	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	11.75	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	9.85	Flow Area (sq ft)	39.49	523.09	95.95
E.G. Slope (ft/ft)	0.005265	Area (sq ft)	39.49	523.09	95.95
Q Total (cfs)	5910.00	Flow (cfs)	174.05	5450.01	285.95
Top Width (ft)	132.90	Top Width (ft)	11.71	63.60	57.59
Vel Total (ft/s)	8.97	Avg. Vel. (ft/s)	4.41	10.42	2.98
Max Chl Dpth (ft)	9.75	Hydr. Depth (ft)	3.37	8.22	1.67
Conv. Total (cfs)	81446.2	Conv. (cfs)	2398.5	75107.0	3940.7
Length Wtd. (ft)	11.00	Wetted Per. (ft)	13.51	63.98	59.06
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.96	2.69	0.53
Alpha	1.26	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.13	16.18	1.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.07	2.11	1.07

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.56	Element			
Vel Head (ft)	0.49	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	7.07	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	5.89	Flow Area (sq ft)	3.73	225.92	9.28
E.G. Slope (ft/ft)	0.004779	Area (sq ft)	3.73	225.92	9.28
Q Total (cfs)	1312.00	Flow (cfs)	7.13	1281.35	23.52
Top Width (ft)	73.24	Top Width (ft)	3.60	63.60	6.04
Vel Total (ft/s)	5.49	Avg. Vel. (ft/s)	1.91	5.67	2.53
Max Chl Dpth (ft)	5.07	Hydr. Depth (ft)	1.04	3.55	1.54
Conv. Total (cfs)	18978.0	Conv. (cfs)	103.1	18534.7	340.3
Length Wtd. (ft)	11.00	Wetted Per. (ft)	4.15	63.98	6.78
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.27	1.05	0.41
Alpha	1.05	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.05	Cum Volume (acre-ft)	0.01	7.34	0.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	1.78	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q10

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.06	Element			
Vel Head (ft)	1.21	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	9.85	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	8.32	Flow Area (sq ft)	20.42	402.58	33.66
E.G. Slope (ft/ft)	0.005603	Area (sq ft)	20.42	402.58	33.66
Q Total (cfs)	3850.00	Flow (cfs)	74.51	3633.66	141.83
Top Width (ft)	83.52	Top Width (ft)	8.42	63.60	11.51
Vel Total (ft/s)	8.43	Avg. Vel. (ft/s)	3.65	9.03	4.21
Max Chl Dpth (ft)	7.85	Hydr. Depth (ft)	2.43	6.33	2.93
Conv. Total (cfs)	51434.1	Conv. (cfs)	995.4	48543.9	1894.8
Length Wtd. (ft)	11.00	Wetted Per. (ft)	9.72	63.98	12.91
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.74	2.20	0.91
Alpha	1.09	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.05	11.89	0.14
C & E Loss (ft)	0.02	Cum SA (acres)	0.02	2.01	0.06

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q25

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.40	Element			
Vel Head (ft)	1.30	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	10.11	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	8.55	Flow Area (sq ft)	22.63	418.90	36.81
E.G. Slope (ft/ft)	0.005706	Area (sq ft)	22.63	418.90	36.81
Q Total (cfs)	4148.00	Flow (cfs)	86.27	3917.98	143.75
Top Width (ft)	87.07	Top Width (ft)	8.86	63.60	14.60
Vel Total (ft/s)	8.67	Avg. Vel. (ft/s)	3.81	9.35	3.91
Max Chl Dpth (ft)	8.11	Hydr. Depth (ft)	2.55	6.59	2.52
Conv. Total (cfs)	54912.3	Conv. (cfs)	1142.1	51867.2	1903.0
Length Wtd. (ft)	11.00	Wetted Per. (ft)	10.23	63.98	16.04
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.79	2.33	0.82
Alpha	1.11	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.06	12.53	0.16
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	2.04	0.07

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	12.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.47	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	11.27	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	9.42	Flow Area (sq ft)	34.13	492.93	71.59
E.G. Slope (ft/ft)	0.005275	Area (sq ft)	34.13	492.93	71.59
Q Total (cfs)	5290.00	Flow (cfs)	143.42	4940.89	205.69
Top Width (ft)	119.63	Top Width (ft)	10.88	63.60	45.15
Vel Total (ft/s)	8.84	Avg. Vel. (ft/s)	4.20	10.02	2.87
Max Chl Dpth (ft)	9.27	Hydr. Depth (ft)	3.14	7.75	1.59
Conv. Total (cfs)	72834.0	Conv. (cfs)	1974.7	68027.4	2832.0
Length Wtd. (ft)	11.00	Wetted Per. (ft)	12.56	63.98	46.61
Min Ch El (ft)	2.00	Shear (lb/sq ft)	0.89	2.54	0.51
Alpha	1.21	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.10	14.95	0.48
C & E Loss (ft)	0.02	Cum SA (acres)	0.05	2.10	0.53

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.57	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.	0.050	0.042	0.050
W.S. Elev (ft)	12.97	Reach Len. (ft)	11.00	11.00	11.00
Crit W.S. (ft)	11.03	Flow Area (sq ft)	55.13	600.98	171.93
E.G. Slope (ft/ft)	0.004645	Area (sq ft)	55.13	600.98	183.29
Q Total (cfs)	7380.00	Flow (cfs)	255.06	6451.11	673.83
Top Width (ft)	154.93	Top Width (ft)	13.83	63.60	77.49
Vel Total (ft/s)	8.91	Avg. Vel. (ft/s)	4.63	10.73	3.92
Max Chl Dpth (ft)	10.97	Hydr. Depth (ft)	3.98	9.45	2.76
Conv. Total (cfs)	108286.3	Conv. (cfs)	3742.5	94656.7	9887.1
Length Wtd. (ft)	11.00	Wetted Per. (ft)	15.97	63.98	63.87
Min Ch El (ft)	2.00	Shear (lb/sq ft)	1.00	2.72	0.78
Alpha	1.29	Stream Power (lb/ft s)	231.80	0.00	0.00
Frctn Loss (ft)	0.05	Cum Volume (acre-ft)	0.26	19.29	3.57
C & E Loss (ft)	0.03	Cum SA (acres)	0.12	2.12	1.96

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 895

INPUT
Description: Bridge Street
Distance from Upstream XS = 11
Deck/Roadway Width = 62
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	46.2	29.4	0
46.2	29.4	24.2	177.2	28	22.8
177.2	28	0	260	26	0

Upstream Bridge Cross Section Data
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	31	15.3	30	23.8	27.1	35	27	37.7	19
62	5	79	5	82.2	4	105.2	2	121.1	3
125.6	4	137.4	10	203	12.5	203.1	13	203.2	13.1
208.7	13.4	231.8	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	62	.042	125.6	.05

Bank Sta: Left Right Coeff Contr. Expan.
62 125.6 .3 .5
Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	35	28	F
188	231.8	26	F

Downstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	30	0	46.2	29.4	0
46.2	29.4	24.2	177.2	28	22.8
177.2	28	0	260	26	0

Downstream Bridge Cross Section Data
Station Elevation Data num= 12

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	29	32	25	35.3	20	63.6	5	85.1	3
94	1	114.7	1	119.9	3	139.5	10	174.5	10
238.1	15	238.2	25						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val

```
       0     .05    63.6     .04   119.9     .05

Bank Sta: Left   Right    Coeff Contr.   Expan.
          63.6   119.9            .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
       0      39      24       F
     184   238.2      24       F
Blocked Obstructions     num=       1
   Sta L   Sta R    Elev
     203     240      30

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =       2 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =      26
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Bridge Coefficient Sets =  1

Low Flow Methods and Data
       Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
       Energy Only

Additional Bridge Parameters
       Add Friction component to Momentum
       Do not add Weight component to Momentum
       Class B flow critical depth computations use critical depth
           inside the bridge at the upstream end
       Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT  Profile #Q100

  E.G. US. (ft)                 13.32    Element                Inside BR US  Inside BR DS
  W.S. US. (ft)                 11.75    E.G. Elev (ft)               13.24         12.86
  Q Total (cfs)               5910.00    W.S. Elev (ft)               11.59         11.35
  Q Bridge (cfs)              5910.00    Crit W.S. (ft)                9.85          9.23
  Q Weir (cfs)                           Max Chl Dpth (ft)             9.59         10.35
  Weir Sta Lft (ft)                      Vel Total (ft/s)              9.26          8.59
  Weir Sta Rgt (ft)                      Flow Area (sq ft)           637.90        688.22
  Weir Submerg                           Froude # Chl                  0.59          0.54
  Weir Max Depth (ft)                    Specif Force (cu ft)        4208.66       4466.50
  Min El Weir Flow (ft)         27.39    Hydr Depth (ft)               5.04          5.48
  Min El Prs (ft)               24.20    W.P. Total (ft)             130.24        129.07
```

Delta EG (ft)	0.53	Conv. Total (cfs)	78585.2	90366.7
Delta WS (ft)	0.60	Top Width (ft)	126.63	125.59
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.30	0.05
BR Open Vel (ft/s)	9.26	C & E Loss (ft)	0.07	0.04
Coef of Q		Shear Total (lb/sq ft)	1.73	1.42
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

E.G. US. (ft)	7.56	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	7.07	E.G. Elev (ft)	7.50	7.21
Q Total (cfs)	1312.00	W.S. Elev (ft)	6.98	6.83
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	5.89	4.95
Q Weir (cfs)		Max Chl Dpth (ft)	4.98	5.83
Weir Sta Lft (ft)		Vel Total (ft/s)	5.65	4.80
Weir Sta Rgt (ft)		Flow Area (sq ft)	232.30	273.11
Weir Submerg		Froude # Chl	0.55	0.42
Weir Max Depth (ft)		Specif Force (cu ft)	662.63	837.22
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	3.19	3.88
Min El Prs (ft)	24.20	W.P. Total (ft)	74.53	72.27
Delta EG (ft)	0.38	Conv. Total (cfs)	18157.0	25781.8
Delta WS (ft)	0.29	Top Width (ft)	72.90	70.46
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.22	0.03
BR Open Vel (ft/s)	5.65	C & E Loss (ft)	0.07	0.00
Coef of Q		Shear Total (lb/sq ft)	1.02	0.61
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

E.G. US. (ft)	11.06	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	9.85	E.G. Elev (ft)	10.97	10.60
Q Total (cfs)	3850.00	W.S. Elev (ft)	9.70	9.43
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	8.32	7.59
Q Weir (cfs)		Max Chl Dpth (ft)	7.70	8.43
Weir Sta Lft (ft)		Vel Total (ft/s)	8.67	8.15
Weir Sta Rgt (ft)		Flow Area (sq ft)	444.05	472.42
Weir Submerg		Froude # Chl	0.66	0.60

Weir Max Depth (ft)		Specif Force (cu ft)	2415.24	2625.71
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.35	5.72
Min El Prs (ft)	24.20	W.P. Total (ft)	85.97	85.56
Delta EG (ft)	0.52	Conv. Total (cfs)	49306.0	58034.6
Delta WS (ft)	0.53	Top Width (ft)	82.96	82.66
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.32	0.05
BR Open Vel (ft/s)	8.67	C & E Loss (ft)	0.05	0.01
Coef of Q		Shear Total (lb/sq ft)	1.97	1.52
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

E.G. US. (ft)	11.40	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	10.11	E.G. Elev (ft)	11.33	10.96
Q Total (cfs)	4148.00	W.S. Elev (ft)	9.99	9.72
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	8.55	7.85
Q Weir (cfs)		Max Chl Dpth (ft)	7.99	8.72
Weir Sta Lft (ft)		Vel Total (ft/s)	8.85	8.35
Weir Sta Rgt (ft)		Flow Area (sq ft)	468.48	496.69
Weir Submerg		Froude # Chl	0.66	0.60
Weir Max Depth (ft)		Specif Force (cu ft)	2658.42	2876.18
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.57	5.91
Min El Prs (ft)	24.20	W.P. Total (ft)	87.20	87.05
Delta EG (ft)	0.51	Conv. Total (cfs)	53455.0	62392.7
Delta WS (ft)	0.50	Top Width (ft)	84.05	84.03
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.32	0.05
BR Open Vel (ft/s)	8.85	C & E Loss (ft)	0.05	0.01
Coef of Q		Shear Total (lb/sq ft)	2.02	1.57
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	12.74	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	11.27	E.G. Elev (ft)	12.65	12.30
Q Total (cfs)	5290.00	W.S. Elev (ft)	11.10	10.84
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	9.42	8.76
Q Weir (cfs)		Max Chl Dpth (ft)	9.10	9.84

Weir Sta Lft (ft)		Vel Total (ft/s)	9.14	8.48
Weir Sta Rgt (ft)		Flow Area (sq ft)	578.84	623.95
Weir Submerg		Froude # Chl	0.66	0.54
Weir Max Depth (ft)		Specif Force (cu ft)	3673.21	3921.31
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	5.04	5.01
Min El Prs (ft)	24.20	W.P. Total (ft)	118.38	127.98
Delta EG (ft)	0.55	Conv. Total (cfs)	69944.6	79903.7
Delta WS (ft)	0.71	Top Width (ft)	114.91	124.62
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.31	0.06
BR Open Vel (ft/s)	9.14	C & E Loss (ft)	0.05	0.05
Coef of Q		Shear Total (lb/sq ft)	1.75	1.33
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

E.G. US. (ft)	14.57	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	12.97	E.G. Elev (ft)	14.49	14.15
Q Total (cfs)	7380.00	W.S. Elev (ft)	12.79	12.58
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	11.03	10.97
Q Weir (cfs)		Max Chl Dpth (ft)	10.79	11.58
Weir Sta Lft (ft)		Vel Total (ft/s)	9.33	8.75
Weir Sta Rgt (ft)		Flow Area (sq ft)	790.75	843.24
Weir Submerg		Froude # Chl	0.56	0.52
Weir Max Depth (ft)		Specif Force (cu ft)	5551.62	5877.45
Min El Weir Flow (ft)	27.39	Hydr Depth (ft)	6.14	6.59
Min El Prs (ft)	24.20	W.P. Total (ft)	132.64	131.68
Delta EG (ft)	0.46	Conv. Total (cfs)	103912.3	118131.2
Delta WS (ft)	0.44	Top Width (ft)	128.71	127.89
BR Open Area (sq ft)	2192.90	Frctn Loss (ft)	0.27	0.05
BR Open Vel (ft/s)	9.33	C & E Loss (ft)	0.07	0.00
Coef of Q		Shear Total (lb/sq ft)	1.88	1.56
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream

REACH: Reach 1 RS: 850

INPUT
Description: JD
Station Elevation Data num= 12

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	29	32	25	35.3	20	63.6	5	85.1	3
94	1	114.7	1	119.9	3	139.5	10	174.5	10
238.1	15	238.2	25						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	63.6	.04	119.9	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
63.6	119.9	20	20	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
0	39	24	F
184	238.2	24	F

Blocked Obstructions num= 1

Sta L	Sta R	Elev
203	240	30

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.78	Element			
Vel Head (ft)	1.63	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	11.15	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	9.23	Flow Area (sq ft)	35.67	492.82	138.74
E.G. Slope (ft/ft)	0.004722	Area (sq ft)	35.67	492.82	139.77
Q Total (cfs)	5910.00	Flow (cfs)	141.84	5300.11	468.05
Top Width (ft)	137.13	Top Width (ft)	11.60	56.30	69.22
Vel Total (ft/s)	8.86	Avg. Vel. (ft/s)	3.98	10.75	3.37
Max Chl Dpth (ft)	10.15	Hydr. Depth (ft)	3.07	8.75	2.16
Conv. Total (cfs)	86009.0	Conv. (cfs)	2064.2	77133.2	6811.6
Length Wtd. (ft)	20.00	Wetted Per. (ft)	13.13	56.99	65.34
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.80	2.55	0.63
Alpha	1.34	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.06	15.19	0.80
C & E Loss (ft)	0.19	Cum SA (acres)	0.04	1.99	0.96

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.18	Element			

Vel Head (ft)	0.39	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	6.79	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	4.95	Flow Area (sq ft)	3.01	247.20	20.08
E.G. Slope (ft/ft)	0.002673	Area (sq ft)	3.01	247.20	20.08
Q Total (cfs)	1312.00	Flow (cfs)	3.95	1262.69	45.35
Top Width (ft)	70.27	Top Width (ft)	3.37	56.30	10.60
Vel Total (ft/s)	4.85	Avg. Vel. (ft/s)	1.31	5.11	2.26
Max Chl Dpth (ft)	5.79	Hydr. Depth (ft)	0.89	4.39	1.89
Conv. Total (cfs)	25378.8	Conv. (cfs)	76.5	24425.0	877.3
Length Wtd. (ft)	20.00	Wetted Per. (ft)	3.82	56.99	11.26
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.13	0.72	0.30
Alpha	1.07	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.01	6.88	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.66	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.54	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.22	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	9.32	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.59	Flow Area (sq ft)	17.58	389.68	55.88
E.G. Slope (ft/ft)	0.004662	Area (sq ft)	17.58	389.68	55.88
Q Total (cfs)	3850.00	Flow (cfs)	54.88	3560.63	234.50
Top Width (ft)	82.13	Top Width (ft)	8.15	56.30	17.69
Vel Total (ft/s)	8.31	Avg. Vel. (ft/s)	3.12	9.14	4.20
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.92	3.16
Conv. Total (cfs)	56389.2	Conv. (cfs)	803.7	52150.8	3434.6
Length Wtd. (ft)	20.00	Wetted Per. (ft)	9.22	56.99	18.78
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.56	1.99	0.87
Alpha	1.13	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.02	11.12	0.05
C & E Loss (ft)	0.08	Cum SA (acres)	0.01	1.89	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.29	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	9.61	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	7.85	Flow Area (sq ft)	20.01	405.90	61.09
E.G. Slope (ft/ft)	0.004678	Area (sq ft)	20.01	405.90	61.09
Q Total (cfs)	4148.00	Flow (cfs)	65.31	3818.08	264.60

Top Width (ft)	83.49	Top Width (ft)	8.69	56.30	18.50
Vel Total (ft/s)	8.52	Avg. Vel. (ft/s)	3.26	9.41	4.33
Max Chl Dpth (ft)	8.61	Hydr. Depth (ft)	2.30	7.21	3.30
Conv. Total (cfs)	60644.0	Conv. (cfs)	954.9	55820.5	3868.5
Length Wtd. (ft)	20.00	Wetted Per. (ft)	9.83	56.99	19.64
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.59	2.08	0.91
Alpha	1.14	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.02	11.73	0.06
C & E Loss (ft)	0.10	Cum SA (acres)	0.01	1.92	0.04

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	12.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.63	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	10.56	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	8.76	Flow Area (sq ft)	29.19	459.78	101.34
E.G. Slope (ft/ft)	0.005052	Area (sq ft)	29.19	459.78	101.34
Q Total (cfs)	5290.00	Flow (cfs)	112.29	4883.80	293.91
Top Width (ft)	128.55	Top Width (ft)	10.50	56.30	61.76
Vel Total (ft/s)	8.96	Avg. Vel. (ft/s)	3.85	10.62	2.90
Max Chl Dpth (ft)	9.56	Hydr. Depth (ft)	2.78	8.17	1.64
Conv. Total (cfs)	74422.7	Conv. (cfs)	1579.8	68708.1	4134.8
Length Wtd. (ft)	20.00	Wetted Per. (ft)	11.88	56.99	62.99
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.78	2.54	0.51
Alpha	1.31	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.08	Cum Volume (acre-ft)	0.03	14.02	0.30
C & E Loss (ft)	0.20	Cum SA (acres)	0.03	1.98	0.44

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	14.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.57	Wt. n-Val.	0.050	0.040	0.050
W.S. Elev (ft)	12.53	Reach Len. (ft)	20.00	20.00	20.00
Crit W.S. (ft)	11.04	Flow Area (sq ft)	53.50	570.57	227.26
E.G. Slope (ft/ft)	0.003944	Area (sq ft)	53.50	570.57	246.97
Q Total (cfs)	7380.00	Flow (cfs)	222.51	6183.78	973.71
Top Width (ft)	153.61	Top Width (ft)	14.21	56.30	83.10
Vel Total (ft/s)	8.67	Avg. Vel. (ft/s)	4.16	10.84	4.28
Max Chl Dpth (ft)	11.53	Hydr. Depth (ft)	3.77	10.13	3.55
Conv. Total (cfs)	117510.7	Conv. (cfs)	3543.0	98463.4	15504.2
Length Wtd. (ft)	20.00	Wetted Per. (ft)	16.08	56.99	65.34

Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.82	2.47	0.86
Alpha	1.35	Stream Power (lb/ft s)	238.20	0.00	0.00
Frctn Loss (ft)	0.06	Cum Volume (acre-ft)	0.16	18.15	3.20
C & E Loss (ft)	0.18	Cum SA (acres)	0.09	2.01	1.85

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 830

INPUT
Description: A
Station Elevation Data num= 12

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	23	27.6	15	54.6	6	65	5	78	4
93.5	1	108.7	1	131.1	7	155	10	167.8	10
194.1	11	251.2	15						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.05	54.6	.035	131.1	.05

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
54.6	131.1	9	9	.3	.5

Blocked Obstructions num= 1

Sta L	Sta R	Elev
205	235	25

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.25	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	11.26	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	41.58	602.52	102.89
E.G. Slope (ft/ft)	0.003074	Area (sq ft)	41.58	602.52	102.89
Q Total (cfs)	5910.00	Flow (cfs)	126.11	5558.21	225.68
Top Width (ft)	159.08	Top Width (ft)	15.79	76.50	66.78
Vel Total (ft/s)	7.91	Avg. Vel. (ft/s)	3.03	9.22	2.19
Max Chl Dpth (ft)	10.26	Hydr. Depth (ft)	2.63	7.88	1.54
Conv. Total (cfs)	106589.9	Conv. (cfs)	2274.5	100245.2	4070.2
Length Wtd. (ft)	9.00	Wetted Per. (ft)	16.65	77.66	67.00
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.48	1.49	0.29
Alpha	1.28	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.04	14.94	0.75

C & E Loss (ft)	0.10	Cum SA (acres)	0.04	1.96	0.93

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	7.12	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.41	Wt. n-Val.	0.050	0.035	
W.S. Elev (ft)	6.70	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	0.74	253.75	
E.G. Slope (ft/ft)	0.002997	Area (sq ft)	0.74	253.75	
Q Total (cfs)	1312.00	Flow (cfs)	0.58	1311.42	
Top Width (ft)	77.51	Top Width (ft)	2.11	75.39	
Vel Total (ft/s)	5.16	Avg. Vel. (ft/s)	0.78	5.17	
Max Chl Dpth (ft)	5.70	Hydr. Depth (ft)	0.35	3.37	
Conv. Total (cfs)	23967.0	Conv. (cfs)	10.6	23956.4	
Length Wtd. (ft)	9.00	Wetted Per. (ft)	2.23	76.52	
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	0.62	
Alpha	1.00	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	6.77	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.63	0.02

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.37	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.05	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	9.32	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	16.53	453.70	21.43
E.G. Slope (ft/ft)	0.003637	Area (sq ft)	16.53	453.70	21.43
Q Total (cfs)	3850.00	Flow (cfs)	40.09	3767.73	42.18
Top Width (ft)	104.94	Top Width (ft)	9.96	76.50	18.48
Vel Total (ft/s)	7.83	Avg. Vel. (ft/s)	2.43	8.30	1.97
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	1.66	5.93	1.16
Conv. Total (cfs)	63842.0	Conv. (cfs)	664.9	62477.7	699.4
Length Wtd. (ft)	9.00	Wetted Per. (ft)	10.50	77.66	18.62
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.36	1.33	0.26
Alpha	1.10	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	10.93	0.04
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	1.86	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.71	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.09	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	9.62	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	19.70	476.99	27.43
E.G. Slope (ft/ft)	0.003539	Area (sq ft)	19.70	476.99	27.43
Q Total (cfs)	4148.00	Flow (cfs)	49.98	4040.21	57.81

Top Width (ft)	108.28	Top Width (ft)	10.87	76.50	20.90
Vel Total (ft/s)	7.91	Avg. Vel. (ft/s)	2.54	8.47	2.11
Max Chl Dpth (ft)	8.62	Hydr. Depth (ft)	1.81	6.24	1.31
Conv. Total (cfs)	69725.7	Conv. (cfs)	840.1	67913.8	971.8
Length Wtd. (ft)	9.00	Wetted Per. (ft)	11.46	77.66	21.07
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.38	1.36	0.29
Alpha	1.12	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	11.53	0.04
C & E Loss (ft)	0.07	Cum SA (acres)	0.01	1.89	0.03

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.23	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	10.68	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	32.89	557.96	67.02
E.G. Slope (ft/ft)	0.003296	Area (sq ft)	32.89	557.96	67.02
Q Total (cfs)	5290.00	Flow (cfs)	95.53	5063.76	130.71
Top Width (ft)	145.20	Top Width (ft)	14.05	76.50	54.65
Vel Total (ft/s)	8.04	Avg. Vel. (ft/s)	2.90	9.08	1.95
Max Chl Dpth (ft)	9.68	Hydr. Depth (ft)	2.34	7.29	1.23
Conv. Total (cfs)	92137.7	Conv. (cfs)	1663.9	88197.3	2276.6
Length Wtd. (ft)	9.00	Wetted Per. (ft)	14.81	77.66	54.85
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.46	1.48	0.25
Alpha	1.22	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.02	13.79	0.27
C & E Loss (ft)	0.10	Cum SA (acres)	0.02	1.95	0.41

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.86	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.21	Wt. n-Val.	0.050	0.035	0.050
W.S. Elev (ft)	12.65	Reach Len. (ft)	9.00	9.00	9.00
Crit W.S. (ft)		Flow Area (sq ft)	66.36	708.58	203.58
E.G. Slope (ft/ft)	0.002508	Area (sq ft)	66.36	708.58	203.58
Q Total (cfs)	7380.00	Flow (cfs)	212.46	6578.08	589.46
Top Width (ft)	170.35	Top Width (ft)	19.95	76.50	73.90
Vel Total (ft/s)	7.54	Avg. Vel. (ft/s)	3.20	9.28	2.90
Max Chl Dpth (ft)	11.65	Hydr. Depth (ft)	3.33	9.26	2.75
Conv. Total (cfs)	147364.2	Conv. (cfs)	4242.5	131351.3	11770.4
Length Wtd. (ft)	9.00	Wetted Per. (ft)	21.03	77.66	75.02
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.49	1.43	0.42
Alpha	1.37	Stream Power (lb/ft s)	251.20	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.13	17.86	3.10
C & E Loss (ft)	0.08	Cum SA (acres)	0.08	1.98	1.81

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 821

INPUT
Description: AD
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
12	16.5	22	12.5	27	10.25	32	8	42	6.5
52	6	62	4.5	72	3.5	82	1.5	92	1
102	1	112	4	122	7	132	9	154	10
203	11.5	235	12						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
12	.065	32	.035	132	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
32	132	1	1	.1	.3

Blocked Obstructions num= 1

Sta L	Sta R	Elev
205	235	25

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.39	Element			
Vel Head (ft)	1.05	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.34	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	12.37	698.68	69.60
E.G. Slope (ft/ft)	0.002923	Area (sq ft)	12.37	698.68	69.60
Q Total (cfs)	5910.00	Flow (cfs)	20.23	5800.40	89.38
Top Width (ft)	173.08	Top Width (ft)	7.42	100.00	65.67
Vel Total (ft/s)	7.57	Avg. Vel. (ft/s)	1.63	8.30	1.28
Max Chl Dpth (ft)	10.34	Hydr. Depth (ft)	1.67	6.99	1.06
Conv. Total (cfs)	109310.4	Conv. (cfs)	374.1	107283.2	1653.1
Length Wtd. (ft)	1.00	Wetted Per. (ft)	8.13	101.58	65.71
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.28	1.26	0.19
Alpha	1.18	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.03	14.80	0.73
C & E Loss (ft)	0.04	Cum SA (acres)	0.03	1.94	0.92

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.09	Element			
Vel Head (ft)	0.42	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.67	Reach Len. (ft)	1.00	1.00	1.00

Crit W.S. (ft)		Flow Area (sq ft)		250.98	
E.G. Slope (ft/ft)	0.003368	Area (sq ft)		250.98	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	79.98	Top Width (ft)		79.98	
Vel Total (ft/s)	5.23	Avg. Vel. (ft/s)		5.23	
Max Chl Dpth (ft)	5.67	Hydr. Depth (ft)		3.14	
Conv. Total (cfs)	22607.3	Conv. (cfs)		22607.3	
Length Wtd. (ft)	1.00	Wetted Per. (ft)		81.21	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.65	
Alpha	1.00	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	6.72	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.61	0.02

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	9.35	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	2.03	500.13	1.36
E.G. Slope (ft/ft)	0.003920	Area (sq ft)	2.03	500.13	1.36
Q Total (cfs)	3850.00	Flow (cfs)	2.10	3847.29	0.61
Top Width (ft)	110.73	Top Width (ft)	3.00	100.00	7.73
Vel Total (ft/s)	7.65	Avg. Vel. (ft/s)	1.04	7.69	0.45
Max Chl Dpth (ft)	8.35	Hydr. Depth (ft)	0.68	5.00	0.18
Conv. Total (cfs)	61495.0	Conv. (cfs)	33.6	61451.7	9.7
Length Wtd. (ft)	1.00	Wetted Per. (ft)	3.29	101.58	7.74
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.15	1.20	0.04
Alpha	1.01	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	10.83	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.84	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.61	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.94	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	9.66	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	3.08	531.43	4.85
E.G. Slope (ft/ft)	0.003709	Area (sq ft)	3.08	531.43	4.85
Q Total (cfs)	4148.00	Flow (cfs)	3.57	4141.20	3.24
Top Width (ft)	118.31	Top Width (ft)	3.70	100.00	14.62
Vel Total (ft/s)	7.69	Avg. Vel. (ft/s)	1.16	7.79	0.67
Max Chl Dpth (ft)	8.66	Hydr. Depth (ft)	0.83	5.31	0.33
Conv. Total (cfs)	68107.5	Conv. (cfs)	58.5	67995.8	53.2
Length Wtd. (ft)	1.00	Wetted Per. (ft)	4.06	101.58	14.63
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.18	1.21	0.08
Alpha	1.03	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	11.42	0.04

C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.87	0.03

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.78	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	10.75	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	8.42	640.31	36.83
E.G. Slope (ft/ft)	0.003187	Area (sq ft)	8.42	640.31	36.83
Q Total (cfs)	5290.00	Flow (cfs)	12.65	5236.74	40.61
Top Width (ft)	152.72	Top Width (ft)	6.12	100.00	46.60
Vel Total (ft/s)	7.72	Avg. Vel. (ft/s)	1.50	8.18	1.10
Max Chl Dpth (ft)	9.75	Hydr. Depth (ft)	1.38	6.40	0.79
Conv. Total (cfs)	93710.0	Conv. (cfs)	224.0	92766.5	719.5
Length Wtd. (ft)	1.00	Wetted Per. (ft)	6.71	101.58	46.64
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.25	1.25	0.16
Alpha	1.11	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.01	13.66	0.25
C & E Loss (ft)	0.03	Cum SA (acres)	0.02	1.93	0.40

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.04	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	12.71	Reach Len. (ft)	1.00	1.00	1.00
Crit W.S. (ft)		Flow Area (sq ft)	24.70	836.41	169.35
E.G. Slope (ft/ft)	0.002344	Area (sq ft)	24.70	836.41	169.35
Q Total (cfs)	7380.00	Flow (cfs)	45.39	7009.82	324.79
Top Width (ft)	183.54	Top Width (ft)	10.54	100.00	73.00
Vel Total (ft/s)	7.16	Avg. Vel. (ft/s)	1.84	8.38	1.92
Max Chl Dpth (ft)	11.71	Hydr. Depth (ft)	2.34	8.36	2.32
Conv. Total (cfs)	152445.9	Conv. (cfs)	937.6	144799.3	6709.1
Length Wtd. (ft)	1.00	Wetted Per. (ft)	11.54	101.58	74.23
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.31	1.20	0.33
Alpha	1.30	Stream Power (lb/ft s)	235.00	0.00	0.00
Frctn Loss (ft)	0.00	Cum Volume (acre-ft)	0.12	17.70	3.06
C & E Loss (ft)	0.06	Cum SA (acres)	0.08	1.96	1.80

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 820

INPUT
Description: ADD

Station Elevation Data num= 24

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	16.5	10	12.5	15	10.25	20	8	30	6.5
40	6	50	4.5	60	3.5	70	1.5	80	1
90	1	100	4	110	7	119.4	9	119.5	9
142.2	10	142.3	10	150	10	160	10	170	11
180	11	185.5	11.5	185.6	11.5	290	12		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	15	.035	142.3	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15	142.3	95	95	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	12.34	Element			
Vel Head (ft)	0.91	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	11.43	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	1.55	761.88	40.00
E.G. Slope (ft/ft)	0.003087	Area (sq ft)	1.55	761.88	40.00
Q Total (cfs)	5910.00	Flow (cfs)	1.30	5859.92	48.78
Top Width (ft)	172.37	Top Width (ft)	2.63	127.30	42.45
Vel Total (ft/s)	7.36	Avg. Vel. (ft/s)	0.84	7.69	1.22
Max Chl Dpth (ft)	10.43	Hydr. Depth (ft)	0.59	5.98	0.94
Conv. Total (cfs)	106370.9	Conv. (cfs)	23.5	105469.6	877.9
Length Wtd. (ft)	95.00	Wetted Per. (ft)	2.88	129.39	42.52
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.10	1.13	0.18
Alpha	1.08	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.03	14.79	0.73
C & E Loss (ft)	0.01	Cum SA (acres)	0.03	1.94	0.92

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.09	Element			
Vel Head (ft)	0.43	Wt. n-Val.		0.035	
W.S. Elev (ft)	6.66	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		250.60	
E.G. Slope (ft/ft)	0.003382	Area (sq ft)		250.60	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	79.94	Top Width (ft)		79.94	
Vel Total (ft/s)	5.24	Avg. Vel. (ft/s)		5.24	
Max Chl Dpth (ft)	5.66	Hydr. Depth (ft)		3.13	
Conv. Total (cfs)	22558.8	Conv. (cfs)		22558.8	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		81.16	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		0.65	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00

Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.01	6.71	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.61	0.02

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	10.26	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.91	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.35	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		502.77	
E.G. Slope (ft/ft)	0.004412	Area (sq ft)		502.77	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	110.47	Top Width (ft)		110.47	
Vel Total (ft/s)	7.66	Avg. Vel. (ft/s)		7.66	
Max Chl Dpth (ft)	8.35	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	57961.2	Conv. (cfs)		57961.2	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		112.36	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.23	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.49	Cum Volume (acre-ft)	0.01	10.82	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.84	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.59	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.		0.035	
W.S. Elev (ft)	9.68	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)		539.98	
E.G. Slope (ft/ft)	0.004433	Area (sq ft)		539.98	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	118.57	Top Width (ft)		118.57	
Vel Total (ft/s)	7.68	Avg. Vel. (ft/s)		7.68	
Max Chl Dpth (ft)	8.68	Hydr. Depth (ft)		4.55	
Conv. Total (cfs)	62299.7	Conv. (cfs)		62299.7	
Length Wtd. (ft)	95.00	Wetted Per. (ft)		120.53	
Min Ch El (ft)	1.00	Shear (lb/sq ft)		1.24	
Alpha	1.00	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.48	Cum Volume (acre-ft)	0.01	11.41	0.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	1.87	0.03

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.74	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.92	Wt. n-Val.	0.065	0.035	0.065

W.S. Elev (ft)	10.83	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	0.37	685.12	18.10
E.G. Slope (ft/ft)	0.003558	Area (sq ft)	0.37	685.12	18.10
Q Total (cfs)	5290.00	Flow (cfs)	0.21	5270.42	19.37
Top Width (ft)	154.57	Top Width (ft)	1.29	127.30	25.99
Vel Total (ft/s)	7.52	Avg. Vel. (ft/s)	0.56	7.69	1.07
Max Chl Dpth (ft)	9.83	Hydr. Depth (ft)	0.29	5.38	0.70
Conv. Total (cfs)	88690.2	Conv. (cfs)	3.5	88361.8	324.8
Length Wtd. (ft)	95.00	Wetted Per. (ft)	1.41	129.39	26.03
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.06	1.18	0.15
Alpha	1.04	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.01	13.65	0.25
C & E Loss (ft)	0.01	Cum SA (acres)	0.02	1.93	0.40

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.69	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.	0.065	0.035	0.065
W.S. Elev (ft)	12.85	Reach Len. (ft)	95.00	95.00	95.00
Crit W.S. (ft)		Flow Area (sq ft)	7.54	942.66	216.48
E.G. Slope (ft/ft)	0.002211	Area (sq ft)	7.54	942.66	216.48
Q Total (cfs)	7380.00	Flow (cfs)	9.01	7071.98	299.01
Top Width (ft)	280.88	Top Width (ft)	5.88	127.30	147.70
Vel Total (ft/s)	6.33	Avg. Vel. (ft/s)	1.20	7.50	1.38
Max Chl Dpth (ft)	11.85	Hydr. Depth (ft)	1.28	7.41	1.47
Conv. Total (cfs)	156949.4	Conv. (cfs)	191.6	150398.7	6359.1
Length Wtd. (ft)	95.00	Wetted Per. (ft)	6.43	129.39	148.63
Min Ch El (ft)	1.00	Shear (lb/sq ft)	0.16	1.01	0.20
Alpha	1.35	Stream Power (lb/ft s)	290.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.12	17.68	3.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.08	1.95	1.79

Warning: The cross-section end points had to be extended vertically for the computed water surface.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 725

INPUT
Description: 10
10
Station Elevation Data num= 22

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	14	20	10	30	4	60	4
70	2.8	80	2.5	90	2.5	100	3	110	4.5

120	7.5	126	9	154	10	192	11	235	12
260	13	263	14	266	15	270	16	272	17
281	19	286	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	20	.04	126	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
20	126	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	12.00	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.98	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	1.20	714.06	59.80
E.G. Slope (ft/ft)	0.003914	Area (sq ft)	1.20	714.06	59.80
Q Total (cfs)	5910.00	Flow (cfs)	1.02	5828.36	80.62
Top Width (ft)	173.76	Top Width (ft)	2.45	106.00	65.31
Vel Total (ft/s)	7.63	Avg. Vel. (ft/s)	0.85	8.16	1.35
Max Chl Dpth (ft)	8.48	Hydr. Depth (ft)	0.49	6.74	0.92
Conv. Total (cfs)	94467.6	Conv. (cfs)	16.3	93162.6	1288.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	2.64	108.49	65.34
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.11	1.61	0.22
Alpha	1.13	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.03	13.18	0.62
C & E Loss (ft)	0.11	Cum SA (acres)	0.03	1.68	0.80

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	6.62	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.09	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		224.72	
E.G. Slope (ft/ft)	0.007271	Area (sq ft)		224.72	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	88.79	Top Width (ft)		88.79	
Vel Total (ft/s)	5.84	Avg. Vel. (ft/s)		5.84	
Max Chl Dpth (ft)	3.59	Hydr. Depth (ft)		2.53	
Conv. Total (cfs)	15386.6	Conv. (cfs)		15386.6	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		89.81	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.14	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	1.16	Cum Volume (acre-ft)	0.01	6.19	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	1.43	0.02

Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section.
This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	9.76	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.00	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.76	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		480.41	
E.G. Slope (ft/ft)	0.006136	Area (sq ft)		480.41	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	103.00	Top Width (ft)		103.00	
Vel Total (ft/s)	8.01	Avg. Vel. (ft/s)		8.01	
Max Chl Dpth (ft)	6.26	Hydr. Depth (ft)		4.66	
Conv. Total (cfs)	49149.6	Conv. (cfs)		49149.6	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		105.11	
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.75	
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.69	Cum Volume (acre-ft)	0.01	9.75	0.03
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.61	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	10.10	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.01	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.10	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		514.96	0.13
E.G. Slope (ft/ft)	0.005767	Area (sq ft)		514.96	0.13
Q Total (cfs)	4148.00	Flow (cfs)		4147.97	0.03
Top Width (ft)	107.21	Top Width (ft)		104.50	2.72
Vel Total (ft/s)	8.05	Avg. Vel. (ft/s)		8.05	0.23
Max Chl Dpth (ft)	6.60	Hydr. Depth (ft)		4.93	0.05
Conv. Total (cfs)	54621.3	Conv. (cfs)		54620.9	0.4
Length Wtd. (ft)	150.00	Wetted Per. (ft)		106.73	2.72
Min Ch El (ft)	2.50	Shear (lb/sq ft)		1.74	0.02
Alpha	1.00	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.64	Cum Volume (acre-ft)	0.01	10.26	0.04
C & E Loss (ft)	0.11	Cum SA (acres)	0.00	1.63	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	11.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.32	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.13	644.27	25.04
E.G. Slope (ft/ft)	0.004495	Area (sq ft)	0.13	644.27	25.04
Q Total (cfs)	5290.00	Flow (cfs)	0.06	5262.01	27.94

Top Width (ft)	147.09	Top Width (ft)	0.81	106.00	40.28
Vel Total (ft/s)	7.90	Avg. Vel. (ft/s)	0.43	8.17	1.12
Max Chl Dpth (ft)	7.82	Hydr. Depth (ft)	0.16	6.08	0.62
Conv. Total (cfs)	78903.6	Conv. (cfs)	0.8	78486.0	416.7
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.87	108.49	40.31
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.04	1.67	0.17
Alpha	1.06	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.49	Cum Volume (acre-ft)	0.01	12.20	0.21
C & E Loss (ft)	0.12	Cum SA (acres)	0.02	1.67	0.33

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.44	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.95	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.49	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	7.72	873.50	204.41
E.G. Slope (ft/ft)	0.002895	Area (sq ft)	7.72	873.50	204.41
Q Total (cfs)	7380.00	Flow (cfs)	10.45	7013.32	356.23
Top Width (ft)	233.36	Top Width (ft)	6.21	106.00	121.15
Vel Total (ft/s)	6.80	Avg. Vel. (ft/s)	1.35	8.03	1.74
Max Chl Dpth (ft)	9.99	Hydr. Depth (ft)	1.24	8.24	1.69
Conv. Total (cfs)	137168.8	Conv. (cfs)	194.3	130353.5	6621.0
Length Wtd. (ft)	150.00	Wetted Per. (ft)	6.69	108.49	121.20
Min Ch El (ft)	2.50	Shear (lb/sq ft)	0.21	1.46	0.30
Alpha	1.33	Stream Power (lb/ft s)	286.00	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.10	15.70	2.60
C & E Loss (ft)	0.10	Cum SA (acres)	0.06	1.70	1.50

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 575

INPUT
Description: 9
Station Elevation Data num= 18

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	13.5	17	8.25	20	6	30	1.5
40	1.5	50	1.5	60	2.25	70	2.8	80	3.1
110	3.1	120	4	130	7	140	9	172	10
230	11	280	12	280.1	16				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	17	.04	140	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
17	140	150	150	150	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.82	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	4.39	904.54	61.45
E.G. Slope (ft/ft)	0.002176	Area (sq ft)	4.39	904.54	61.45
Q Total (cfs)	5910.00	Flow (cfs)	4.76	5849.98	55.25
Top Width (ft)	205.77	Top Width (ft)	3.42	123.00	79.35
Vel Total (ft/s)	6.09	Avg. Vel. (ft/s)	1.09	6.47	0.90
Max Chl Dpth (ft)	9.32	Hydr. Depth (ft)	1.28	7.35	0.77
Conv. Total (cfs)	126703.0	Conv. (cfs)	102.1	125416.3	1184.5
Length Wtd. (ft)	150.00	Wetted Per. (ft)	4.28	125.44	79.37
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.14	0.98	0.11
Alpha	1.12	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.02	10.39	0.41
C & E Loss (ft)	0.00	Cum SA (acres)	0.02	1.29	0.55

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	5.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.52	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.94	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)		227.22	
E.G. Slope (ft/ft)	0.008276	Area (sq ft)		227.22	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	100.78	Top Width (ft)		100.78	
Vel Total (ft/s)	5.77	Avg. Vel. (ft/s)		5.77	
Max Chl Dpth (ft)	3.44	Hydr. Depth (ft)		2.25	
Conv. Total (cfs)	14421.7	Conv. (cfs)		14421.7	
Length Wtd. (ft)	150.00	Wetted Per. (ft)		101.74	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.15	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.58	Cum Volume (acre-ft)	0.01	5.41	0.03
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	1.10	0.02

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.000	0.040	
W.S. Elev (ft)	8.32	Reach Len. (ft)	150.00	150.00	150.00

Crit W.S. (ft)		Flow Area (sq ft)	0.00	598.69	
E.G. Slope (ft/ft)	0.003593	Area (sq ft)	0.00	598.69	
Q Total (cfs)	3850.00	Flow (cfs)	0.00	3850.00	
Top Width (ft)	119.70	Top Width (ft)	0.09	119.60	
Vel Total (ft/s)	6.43	Avg. Vel. (ft/s)	0.13	6.43	
Max Chl Dpth (ft)	6.82	Hydr. Depth (ft)	0.04	5.01	
Conv. Total (cfs)	64232.8	Conv. (cfs)	0.0	64232.8	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.12	121.98	
Min Ch El (ft)	1.50	Shear (lb/sq ft)		1.10	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.01	7.89	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.22	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	9.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	8.71	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	0.14	645.64	
E.G. Slope (ft/ft)	0.003313	Area (sq ft)	0.14	645.64	
Q Total (cfs)	4148.00	Flow (cfs)	0.06	4147.94	
Top Width (ft)	122.16	Top Width (ft)	0.61	121.55	
Vel Total (ft/s)	6.42	Avg. Vel. (ft/s)	0.43	6.42	
Max Chl Dpth (ft)	7.21	Hydr. Depth (ft)	0.23	5.31	
Conv. Total (cfs)	72066.6	Conv. (cfs)	1.0	72065.5	
Length Wtd. (ft)	150.00	Wetted Per. (ft)	0.77	123.96	
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.04	1.08	
Alpha	1.00	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	8.26	0.04
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	1.24	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.75	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.65	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.10	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	2.28	816.53	19.52
E.G. Slope (ft/ft)	0.002487	Area (sq ft)	2.28	816.53	19.52
Q Total (cfs)	5290.00	Flow (cfs)	2.13	5273.56	14.31
Top Width (ft)	163.32	Top Width (ft)	2.47	123.00	37.85
Vel Total (ft/s)	6.31	Avg. Vel. (ft/s)	0.93	6.46	0.73
Max Chl Dpth (ft)	8.60	Hydr. Depth (ft)	0.93	6.64	0.52
Conv. Total (cfs)	106074.6	Conv. (cfs)	42.7	105745.0	286.9
Length Wtd. (ft)	150.00	Wetted Per. (ft)	3.08	125.44	37.87
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.11	1.01	0.08
Alpha	1.04	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)	0.01	9.68	0.13

C & E Loss (ft)	0.00	Cum SA (acres)	0.01	1.28	0.19

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	13.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.41	Reach Len. (ft)	150.00	150.00	150.00
Crit W.S. (ft)		Flow Area (sq ft)	11.53	1100.49	249.33
E.G. Slope (ft/ft)	0.001633	Area (sq ft)	11.53	1100.49	249.33
Q Total (cfs)	7380.00	Flow (cfs)	14.96	7027.33	337.70
Top Width (ft)	268.56	Top Width (ft)	5.55	123.00	140.01
Vel Total (ft/s)	5.42	Avg. Vel. (ft/s)	1.30	6.39	1.35
Max Chl Dpth (ft)	10.91	Hydr. Depth (ft)	2.08	8.95	1.78
Conv. Total (cfs)	182619.6	Conv. (cfs)	370.2	173892.8	8356.6
Length Wtd. (ft)	150.00	Wetted Per. (ft)	6.93	125.44	140.44
Min Ch El (ft)	1.50	Shear (lb/sq ft)	0.17	0.89	0.18
Alpha	1.32	Stream Power (lb/ft s)	280.10	0.00	0.00
Frctn Loss (ft)	0.23	Cum Volume (acre-ft)	0.07	12.30	1.82
C & E Loss (ft)	0.00	Cum SA (acres)	0.04	1.31	1.05

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 425

INPUT
Description: 8
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	11	12	9.8	20	5	30	0
70	0	80	.5	90	1.5	100	2	110	5.5
117.4	9	160	10	210	10	265	11	268	12
275	13	280	14						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	12	.04	117.4	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
12	117.4	90	90	90	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	11.16	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.65	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.51	Reach Len. (ft)	90.00	90.00	90.00

Crit W.S. (ft)		Flow Area (sq ft)	0.42	902.74	76.06
E.G. Slope (ft/ft)	0.001827	Area (sq ft)	0.42	902.74	76.06
Q Total (cfs)	5910.00	Flow (cfs)	0.19	5855.22	54.59
Top Width (ft)	227.41	Top Width (ft)	1.19	105.40	120.82
Vel Total (ft/s)	6.04	Avg. Vel. (ft/s)	0.44	6.49	0.72
Max Chl Dpth (ft)	10.51	Hydr. Depth (ft)	0.36	8.56	0.63
Conv. Total (cfs)	138249.0	Conv. (cfs)	4.4	136967.6	1277.1
Length Wtd. (ft)	90.00	Wetted Per. (ft)	1.39	109.37	120.84
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.03	0.94	0.07
Alpha	1.14	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)	0.01	7.28	0.17
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.90	0.21

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.27	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.53	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		317.19	
E.G. Slope (ft/ft)	0.002240	Area (sq ft)		317.19	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	86.31	Top Width (ft)		86.31	
Vel Total (ft/s)	4.14	Avg. Vel. (ft/s)		4.14	
Max Chl Dpth (ft)	4.53	Hydr. Depth (ft)		3.67	
Conv. Total (cfs)	27723.5	Conv. (cfs)		27723.5	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		87.89	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.50	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.18	Cum Volume (acre-ft)	0.01	4.48	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.78	0.02

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.57	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.94	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		635.59	
E.G. Slope (ft/ft)	0.002357	Area (sq ft)		635.59	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	100.06	Top Width (ft)		100.06	
Vel Total (ft/s)	6.06	Avg. Vel. (ft/s)		6.06	
Max Chl Dpth (ft)	7.94	Hydr. Depth (ft)		6.35	
Conv. Total (cfs)	79294.3	Conv. (cfs)		79294.3	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		103.27	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.91	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.01	5.77	0.03

C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.85	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.58	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.34	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		676.02	
E.G. Slope (ft/ft)	0.002277	Area (sq ft)		676.02	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	101.58	Top Width (ft)		101.58	
Vel Total (ft/s)	6.14	Avg. Vel. (ft/s)		6.14	
Max Chl Dpth (ft)	8.34	Hydr. Depth (ft)		6.66	
Conv. Total (cfs)	86918.0	Conv. (cfs)		86918.0	
Length Wtd. (ft)	90.00	Wetted Per. (ft)		104.99	
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.92	
Alpha	1.00	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.01	5.99	0.04
C & E Loss (ft)	0.03	Cum SA (acres)	0.00	0.86	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.41	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.64	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.77	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)		824.66	12.71
E.G. Slope (ft/ft)	0.002010	Area (sq ft)		824.66	12.71
Q Total (cfs)	5290.00	Flow (cfs)		5283.10	6.90
Top Width (ft)	138.26	Top Width (ft)		105.35	32.90
Vel Total (ft/s)	6.32	Avg. Vel. (ft/s)		6.41	0.54
Max Chl Dpth (ft)	9.77	Hydr. Depth (ft)		7.83	0.39
Conv. Total (cfs)	117990.1	Conv. (cfs)		117836.1	154.0
Length Wtd. (ft)	90.00	Wetted Per. (ft)		109.31	32.91
Min Ch El (ft)	0.00	Shear (lb/sq ft)		0.95	0.05
Alpha	1.03	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.22	Cum Volume (acre-ft)	0.01	6.86	0.07
C & E Loss (ft)	0.03	Cum SA (acres)	0.01	0.89	0.07

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.60	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	12.18	Reach Len. (ft)	90.00	90.00	90.00
Crit W.S. (ft)		Flow Area (sq ft)	4.56	1078.68	318.10
E.G. Slope (ft/ft)	0.001414	Area (sq ft)	4.56	1078.68	318.10
Q Total (cfs)	7380.00	Flow (cfs)	4.02	6928.81	447.16

Top Width (ft)	260.97	Top Width (ft)	3.69	105.40	151.88
Vel Total (ft/s)	5.27	Avg. Vel. (ft/s)	0.88	6.42	1.41
Max Chl Dpth (ft)	12.18	Hydr. Depth (ft)	1.24	10.23	2.09
Conv. Total (cfs)	196291.8	Conv. (cfs)	107.0	184291.2	11893.6
Length Wtd. (ft)	90.00	Wetted Per. (ft)	4.39	109.37	152.07
Min Ch El (ft)	0.00	Shear (lb/sq ft)	0.09	0.87	0.18
Alpha	1.40	Stream Power (lb/ft s)	280.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.04	8.55	0.84
C & E Loss (ft)	0.04	Cum SA (acres)	0.03	0.91	0.55

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 335

INPUT
Description: 7
Station Elevation Data num= 17

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	18	10	12.5	18	8.1	20	7	30	1.5
40	-.5	50	-2	60	-2	70	-2	80	0
90	4	100	9	135	10	175	10	205	11
260	11	260.1	16						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	18	.04	100	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
18	100	73	73	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.90	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	2.96	726.97	14.28
E.G. Slope (ft/ft)	0.002776	Area (sq ft)	2.96	726.97	14.28
Q Total (cfs)	5910.00	Flow (cfs)	3.04	5896.84	10.12
Top Width (ft)	116.89	Top Width (ft)	3.28	82.00	31.61
Vel Total (ft/s)	7.94	Avg. Vel. (ft/s)	1.03	8.11	0.71
Max Chl Dpth (ft)	11.90	Hydr. Depth (ft)	0.90	8.87	0.45
Conv. Total (cfs)	112178.6	Conv. (cfs)	57.8	111928.8	192.1
Length Wtd. (ft)	73.00	Wetted Per. (ft)	3.74	86.15	31.63
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.14	1.46	0.08
Alpha	1.04	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.28	Cum Volume (acre-ft)	0.01	5.59	0.08

C & E Loss (ft)	0.07	Cum SA (acres)	0.01	0.70	0.05

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.62	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.29	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.33	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		304.64	
E.G. Slope (ft/ft)	0.001816	Area (sq ft)		304.64	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	65.80	Top Width (ft)		65.80	
Vel Total (ft/s)	4.31	Avg. Vel. (ft/s)		4.31	
Max Chl Dpth (ft)	6.33	Hydr. Depth (ft)		4.63	
Conv. Total (cfs)	30789.6	Conv. (cfs)		30789.6	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		67.89	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		0.51	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	3.83	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.62	0.02

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	8.24	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.84	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.40	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		524.70	
E.G. Slope (ft/ft)	0.003238	Area (sq ft)		524.70	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	77.53	Top Width (ft)		77.53	
Vel Total (ft/s)	7.34	Avg. Vel. (ft/s)		7.34	
Max Chl Dpth (ft)	9.40	Hydr. Depth (ft)		6.77	
Conv. Total (cfs)	67662.9	Conv. (cfs)		67662.9	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		81.12	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.31	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.01	4.57	0.03
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.66	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.66	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.79	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)		555.18	
E.G. Slope (ft/ft)	0.003200	Area (sq ft)		555.18	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	79.01	Top Width (ft)		79.01	
Vel Total (ft/s)	7.47	Avg. Vel. (ft/s)		7.47	
Max Chl Dpth (ft)	9.79	Hydr. Depth (ft)		7.03	
Conv. Total (cfs)	73332.1	Conv. (cfs)		73332.1	
Length Wtd. (ft)	73.00	Wetted Per. (ft)		82.80	
Min Ch El (ft)	-2.00	Shear (lb/sq ft)		1.34	
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.01	4.71	0.04
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.67	0.02

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	10.16	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.97	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.18	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	1.07	667.92	0.59
E.G. Slope (ft/ft)	0.002961	Area (sq ft)	1.07	667.92	0.59
Q Total (cfs)	5290.00	Flow (cfs)	0.81	5289.04	0.15
Top Width (ft)	90.38	Top Width (ft)	1.97	82.00	6.41
Vel Total (ft/s)	7.90	Avg. Vel. (ft/s)	0.76	7.92	0.25
Max Chl Dpth (ft)	11.18	Hydr. Depth (ft)	0.54	8.15	0.09
Conv. Total (cfs)	97208.9	Conv. (cfs)	14.8	97191.4	2.7
Length Wtd. (ft)	73.00	Wetted Per. (ft)	2.25	86.15	6.41
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.09	1.43	0.02
Alpha	1.00	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.01	5.32	0.06
C & E Loss (ft)	0.07	Cum SA (acres)	0.00	0.69	0.03

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.59	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.02	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	11.57	Reach Len. (ft)	73.00	73.00	73.00
Crit W.S. (ft)		Flow Area (sq ft)	10.93	863.45	198.34
E.G. Slope (ft/ft)	0.002277	Area (sq ft)	10.93	863.45	198.34
Q Total (cfs)	7380.00	Flow (cfs)	15.76	7115.18	249.06
Top Width (ft)	248.32	Top Width (ft)	6.30	82.00	160.01
Vel Total (ft/s)	6.88	Avg. Vel. (ft/s)	1.44	8.24	1.26
Max Chl Dpth (ft)	13.57	Hydr. Depth (ft)	1.73	10.53	1.24
Conv. Total (cfs)	154651.5	Conv. (cfs)	330.3	149102.0	5219.2
Length Wtd. (ft)	73.00	Wetted Per. (ft)	7.20	86.15	160.60
Min Ch El (ft)	-2.00	Shear (lb/sq ft)	0.22	1.42	0.18
Alpha	1.38	Stream Power (lb/ft s)	260.10	0.00	0.00
Frctn Loss (ft)	0.24	Cum Volume (acre-ft)	0.02	6.54	0.31
C & E Loss (ft)	0.08	Cum SA (acres)	0.02	0.72	0.23

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 262

INPUT
Description: 6
6
6
Station Elevation Data num= 14

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	7	9.1	10	7	20	1	30	-2
40	-3	50	-3	60	0	70	5	80	9.5
135	11	175	12	255	13	282	14		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	7	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
7	80	75	75	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.57	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.74	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.83	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		558.57	
E.G. Slope (ft/ft)	0.005707	Area (sq ft)		558.57	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	71.13	Top Width (ft)		71.13	
Vel Total (ft/s)	10.58	Avg. Vel. (ft/s)		10.58	
Max Chl Dpth (ft)	11.83	Hydr. Depth (ft)		7.85	
Conv. Total (cfs)	78231.2	Conv. (cfs)		78231.2	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		76.30	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.61	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.41	Cum Volume (acre-ft)	0.01	4.52	0.07
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.57	0.02

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.46	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.39	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.07	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		262.15	
E.G. Slope (ft/ft)	0.002317	Area (sq ft)		262.15	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.25	Top Width (ft)		53.25	
Vel Total (ft/s)	5.00	Avg. Vel. (ft/s)		5.00	
Max Chl Dpth (ft)	7.07	Hydr. Depth (ft)		4.92	
Conv. Total (cfs)	27253.9	Conv. (cfs)		27253.9	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		55.99	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		0.68	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.01	3.36	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.52	0.02

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.85	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.47	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.38	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		395.14	
E.G. Slope (ft/ft)	0.006318	Area (sq ft)		395.14	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	62.03	Top Width (ft)		62.03	
Vel Total (ft/s)	9.74	Avg. Vel. (ft/s)		9.74	
Max Chl Dpth (ft)	9.38	Hydr. Depth (ft)		6.37	
Conv. Total (cfs)	48434.8	Conv. (cfs)		48434.8	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		65.92	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.36	

Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.01	3.80	0.03
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.54	0.02

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	8.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.53	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.74	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		417.99	
E.G. Slope (ft/ft)	0.006278	Area (sq ft)		417.99	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	63.44	Top Width (ft)		63.44	
Vel Total (ft/s)	9.92	Avg. Vel. (ft/s)		9.92	
Max Chl Dpth (ft)	9.74	Hydr. Depth (ft)		6.59	
Conv. Total (cfs)	52350.5	Conv. (cfs)		52350.5	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		67.52	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.43	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.45	Cum Volume (acre-ft)	0.01	3.90	0.04
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.55	0.02

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.79	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.69	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.10	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)		507.69	
E.G. Slope (ft/ft)	0.005954	Area (sq ft)		507.69	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	68.47	Top Width (ft)		68.47	
Vel Total (ft/s)	10.42	Avg. Vel. (ft/s)		10.42	
Max Chl Dpth (ft)	11.10	Hydr. Depth (ft)		7.41	
Conv. Total (cfs)	68556.3	Conv. (cfs)		68556.3	
Length Wtd. (ft)	75.00	Wetted Per. (ft)		73.25	
Min Ch El (ft)	-3.00	Shear (lb/sq ft)		2.58	
Alpha	1.00	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.43	Cum Volume (acre-ft)	0.00	4.33	0.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.57	0.02

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	12.27	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.85	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.41	Reach Len. (ft)	75.00	75.00	75.00
Crit W.S. (ft)		Flow Area (sq ft)	1.23	673.56	15.31

E.G. Slope (ft/ft)	0.004923	Area (sq ft)	1.23	673.56	15.31
Q Total (cfs)	7380.00	Flow (cfs)	1.31	7364.13	14.57
Top Width (ft)	108.39	Top Width (ft)	1.88	73.00	33.51
Vel Total (ft/s)	10.69	Avg. Vel. (ft/s)	1.06	10.93	0.95
Max Chl Dpth (ft)	13.41	Hydr. Depth (ft)	0.66	9.23	0.46
Conv. Total (cfs)	105185.4	Conv. (cfs)	18.7	104959.1	207.6
Length Wtd. (ft)	75.00	Wetted Per. (ft)	2.29	78.40	33.52
Min Ch El (ft)	-3.00	Shear (lb/sq ft)	0.17	2.64	0.14
Alpha	1.04	Stream Power (lb/ft s)	282.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.01	5.25	0.13
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	0.59	0.06

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 187

INPUT
Description: 5
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	8	9.2	10	8	20	1.5	30	-2.5
40	-4	50	-4	60	-1	70	4	80	9.5
115	13	141	13	185	14				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	80	50	50	.1	.3

Ineffective Flow num= 1

Sta L	Sta R	Elev	Permanent
84	185	14.5	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	10.14	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.70	Wt. n-Val.		0.040	
W.S. Elev (ft)	8.44	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.94	Flow Area (sq ft)		564.77	
E.G. Slope (ft/ft)	0.005330	Area (sq ft)		564.77	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	68.82	Top Width (ft)		68.82	
Vel Total (ft/s)	10.46	Avg. Vel. (ft/s)		10.46	
Max Chl Dpth (ft)	12.44	Hydr. Depth (ft)		8.21	
Conv. Total (cfs)	80952.3	Conv. (cfs)		80952.3	

Length Wtd. (ft)	21.00	Wetted Per. (ft)		74.52	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.52	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	3.55	0.07
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.45	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.29	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.32	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.97	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	0.60	Flow Area (sq ft)		290.86	
E.G. Slope (ft/ft)	0.001678	Area (sq ft)		290.86	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.75	Top Width (ft)		53.75	
Vel Total (ft/s)	4.51	Avg. Vel. (ft/s)		4.51	
Max Chl Dpth (ft)	7.97	Hydr. Depth (ft)		5.41	
Conv. Total (cfs)	32032.8	Conv. (cfs)		32032.8	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		56.98	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		0.53	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	2.88	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.43	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.38	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.40	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.98	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.99	Flow Area (sq ft)		405.67	
E.G. Slope (ft/ft)	0.005662	Area (sq ft)		405.67	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	60.50	Top Width (ft)		60.50	
Vel Total (ft/s)	9.49	Avg. Vel. (ft/s)		9.49	
Max Chl Dpth (ft)	9.98	Hydr. Depth (ft)		6.71	
Conv. Total (cfs)	51166.1	Conv. (cfs)		51166.1	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		64.84	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.21	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	3.11	0.03
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.44	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.46	Wt. n-Val.		0.040	
W.S. Elev (ft)	6.34	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.29	Flow Area (sq ft)		427.69	
E.G. Slope (ft/ft)	0.005671	Area (sq ft)		427.69	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	61.71	Top Width (ft)		61.71	
Vel Total (ft/s)	9.70	Avg. Vel. (ft/s)		9.70	
Max Chl Dpth (ft)	10.34	Hydr. Depth (ft)		6.93	
Conv. Total (cfs)	55082.9	Conv. (cfs)		55082.9	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		66.25	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.29	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	3.17	0.04
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.44	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.35	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.64	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.71	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.39	Flow Area (sq ft)		515.03	
E.G. Slope (ft/ft)	0.005505	Area (sq ft)		515.03	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	66.29	Top Width (ft)		66.29	
Vel Total (ft/s)	10.27	Avg. Vel. (ft/s)		10.27	
Max Chl Dpth (ft)	11.71	Hydr. Depth (ft)		7.77	
Conv. Total (cfs)	71301.0	Conv. (cfs)		71301.0	
Length Wtd. (ft)	21.00	Wetted Per. (ft)		71.59	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.47	
Alpha	1.00	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.00	3.45	0.06
C & E Loss (ft)	0.01	Cum SA (acres)	0.00	0.45	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	11.90	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.83	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	10.07	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	7.13	Flow Area (sq ft)	0.63	680.26	1.48
E.G. Slope (ft/ft)	0.004763	Area (sq ft)	0.63	680.26	1.62
Q Total (cfs)	7380.00	Flow (cfs)	0.51	7378.29	1.19
Top Width (ft)	79.14	Top Width (ft)	1.45	72.00	5.69
Vel Total (ft/s)	10.82	Avg. Vel. (ft/s)	0.82	10.85	0.81
Max Chl Dpth (ft)	14.07	Hydr. Depth (ft)	0.43	9.45	0.37
Conv. Total (cfs)	106933.9	Conv. (cfs)	7.4	106909.2	17.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.69	78.17	4.02
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.11	2.59	0.11
Alpha	1.01	Stream Power (lb/ft s)	185.00	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.01	4.09	0.11
C & E Loss (ft)	0.01	Cum SA (acres)	0.01	0.46	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 166

INPUT
Description: Pedestrian Bridge
Distance from Upstream XS = 21
Deck/Roadway Width = 14
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	16	0	6	16	0
6	16	14	81	14	12
81	14	0	115	13	0

Upstream Bridge Cross Section Data
Station Elevation Data num= 13

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	8	9.2	10	8	20	1.5	30	-2.5
40	-4	50	-4	60	-1	70	4	80	9.5
115	13	141	13	185	14				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	80	.065

```
Bank Sta: Left   Right    Coeff Contr.   Expan.
            8      80            .1       .3
Ineffective Flow     num=       1
   Sta L   Sta R    Elev  Permanent
      84     185    14.5       F

Downstream  Deck/Roadway Coordinates
    num=       6
     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord
       0      16       0       6      16       0       6      16      14
      81      14      12      81      14       0     115      13       0

Downstream Bridge Cross Section Data
Station Elevation Data    num=      10
     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev
       0      14      10     8.3      20     2.5      30    -2.5      40    -3.7
      50      -4      60      -2      70       3      80       9      90      14

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
       0    .065      10     .04      80    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
           10      80            .3       .5
Ineffective Flow     num=       1
   Sta L   Sta R    Elev  Permanent
      84      90    14.5       F

Upstream Embankment side slope              =       0 horiz. to 1.0 vertical
Downstream Embankment side slope            =       0 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Bridge Coefficient Sets =  1

Low Flow Methods and Data
       Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
       Energy Only

Additional Bridge Parameters
       Add Friction component to Momentum
       Do not add Weight component to Momentum
```

Class B flow critical depth computations use critical depth
inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Inside BR US	Inside BR DS
E.G. US. (ft)	10.14	Element		
W.S. US. (ft)	8.44	E.G. Elev (ft)	10.02	9.93
Q Total (cfs)	5910.00	W.S. Elev (ft)	8.22	8.15
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	5.94	5.85
Q Weir (cfs)		Max Chl Dpth (ft)	12.22	12.15
Weir Sta Lft (ft)		Vel Total (ft/s)	10.75	10.71
Weir Sta Rgt (ft)		Flow Area (sq ft)	549.69	551.62
Weir Submerg		Froude # Chl	0.67	0.66
Weir Max Depth (ft)		Specif Force (cu ft)	4682.83	4678.50
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	8.08	8.07
Min El Prs (ft)	14.00	W.P. Total (ft)	73.63	73.91
Delta EG (ft)	0.31	Conv. Total (cfs)	78001.3	78262.5
Delta WS (ft)	0.47	Top Width (ft)	68.05	68.32
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.08	0.09
BR Open Vel (ft/s)	10.75	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.68	2.66
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

			Inside BR US	Inside BR DS
E.G. US. (ft)	4.29	Element		
W.S. US. (ft)	3.97	E.G. Elev (ft)	4.25	4.23
Q Total (cfs)	1312.00	W.S. Elev (ft)	3.93	3.91
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.59	0.50
Q Weir (cfs)		Max Chl Dpth (ft)	7.93	7.91
Weir Sta Lft (ft)		Vel Total (ft/s)	4.54	4.48
Weir Sta Rgt (ft)		Flow Area (sq ft)	288.70	292.67
Weir Submerg		Froude # Chl	0.35	0.34
Weir Max Depth (ft)		Specif Force (cu ft)	1118.01	1128.37
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	5.39	5.42
Min El Prs (ft)	14.00	W.P. Total (ft)	56.82	57.23
Delta EG (ft)	0.09	Conv. Total (cfs)	31698.2	32270.4
Delta WS (ft)	0.09	Top Width (ft)	53.61	53.96
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.02	0.02
BR Open Vel (ft/s)	4.54	C & E Loss (ft)	0.00	0.00
Coef of Q		Shear Total (lb/sq ft)	0.54	0.53
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.38	Element		
W.S. US. (ft)	5.98	E.G. Elev (ft)	7.25	7.15
Q Total (cfs)	3850.00	W.S. Elev (ft)	5.74	5.65
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.98	3.90
Q Weir (cfs)		Max Chl Dpth (ft)	9.74	9.65
Weir Sta Lft (ft)		Vel Total (ft/s)	9.84	9.83
Weir Sta Rgt (ft)		Flow Area (sq ft)	391.14	391.68
Weir Submerg		Froude # Chl	0.68	0.68
Weir Max Depth (ft)		Specif Force (cu ft)	2722.69	2714.74
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	6.55	6.54
Min El Prs (ft)	14.00	W.P. Total (ft)	63.90	64.08
Delta EG (ft)	0.33	Conv. Total (cfs)	48622.6	48640.4
Delta WS (ft)	0.54	Top Width (ft)	59.69	59.86
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.09	0.10
BR Open Vel (ft/s)	9.84	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.40	2.39
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.80	Element		
W.S. US. (ft)	6.34	E.G. Elev (ft)	7.67	7.58
Q Total (cfs)	4148.00	W.S. Elev (ft)	6.10	6.01
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.29	4.20
Q Weir (cfs)		Max Chl Dpth (ft)	10.10	10.01
Weir Sta Lft (ft)		Vel Total (ft/s)	10.05	10.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	412.74	413.37
Weir Submerg		Froude # Chl	0.68	0.68
Weir Max Depth (ft)		Specif Force (cu ft)	2984.41	2976.50
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	6.78	6.77
Min El Prs (ft)	14.00	W.P. Total (ft)	65.30	65.49
Delta EG (ft)	0.34	Conv. Total (cfs)	52415.6	52444.4
Delta WS (ft)	0.54	Top Width (ft)	60.89	61.08
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.09	0.10

BR Open Vel (ft/s)	10.05	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.47	2.46
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	9.35	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	7.71	E.G. Elev (ft)	9.21	9.13
Q Total (cfs)	5290.00	W.S. Elev (ft)	7.47	7.40
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.40	5.30
Q Weir (cfs)		Max Chl Dpth (ft)	11.47	11.40
Weir Sta Lft (ft)		Vel Total (ft/s)	10.59	10.56
Weir Sta Rgt (ft)		Flow Area (sq ft)	499.65	501.01
Weir Submerg		Froude # Chl	0.68	0.67
Weir Max Depth (ft)		Specif Force (cu ft)	4055.74	4049.51
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	7.63	7.62
Min El Prs (ft)	14.00	W.P. Total (ft)	70.67	70.93
Delta EG (ft)	0.32	Conv. Total (cfs)	68369.7	68513.6
Delta WS (ft)	0.50	Top Width (ft)	65.51	65.77
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.08	0.09
BR Open Vel (ft/s)	10.59	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.64	2.63
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

E.G. US. (ft)	11.90	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	10.07	E.G. Elev (ft)	11.78	11.71
Q Total (cfs)	7380.00	W.S. Elev (ft)	9.88	9.82
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	7.13	7.04
Q Weir (cfs)		Max Chl Dpth (ft)	13.88	13.82
Weir Sta Lft (ft)		Vel Total (ft/s)	11.05	11.01
Weir Sta Rgt (ft)		Flow Area (sq ft)	667.59	670.26
Weir Submerg		Froude # Chl	0.52	0.52
Weir Max Depth (ft)		Specif Force (cu ft)	6253.85	6260.42
Min El Weir Flow (ft)	13.92	Hydr Depth (ft)	9.00	9.10
Min El Prs (ft)	14.00	W.P. Total (ft)	80.51	80.04

Delta EG (ft)	0.26	Conv. Total (cfs)	103433.0	105776.4
Delta WS (ft)	0.39	Top Width (ft)	74.14	73.66
BR Open Area (sq ft)	901.15	Frctn Loss (ft)	0.07	0.07
BR Open Vel (ft/s)	11.05	C & E Loss (ft)	0.00	0.01
Coef of Q		Shear Total (lb/sq ft)	2.64	2.54
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	0.00

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 137

INPUT
Description: 4
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	80	77	77	.3	.5

Ineffective Flow num= 1

Sta L	Sta R	Elev	Permanent
84	90	14.5	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	9.84	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.86	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.97	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.85	Flow Area (sq ft)		539.62	
E.G. Slope (ft/ft)	0.006060	Area (sq ft)		539.62	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	67.73	Top Width (ft)		67.73	
Vel Total (ft/s)	10.95	Avg. Vel. (ft/s)		10.95	
Max Chl Dpth (ft)	11.97	Hydr. Depth (ft)		7.97	
Conv. Total (cfs)	75920.1	Conv. (cfs)		75920.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		73.21	

Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.79	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)	0.01	2.92	0.07
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.38	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.20	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.32	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.89	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	0.51	Flow Area (sq ft)		291.15	
E.G. Slope (ft/ft)	0.001678	Area (sq ft)		291.15	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	53.87	Top Width (ft)		53.87	
Vel Total (ft/s)	4.51	Avg. Vel. (ft/s)		4.51	
Max Chl Dpth (ft)	7.89	Hydr. Depth (ft)		5.40	
Conv. Total (cfs)	32032.5	Conv. (cfs)		32032.5	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		57.12	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		0.53	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.04	Cum Volume (acre-ft)	0.01	2.55	0.03
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.37	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	7.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.60	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.45	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.89	Flow Area (sq ft)		379.31	
E.G. Slope (ft/ft)	0.006854	Area (sq ft)		379.31	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	59.16	Top Width (ft)		59.16	
Vel Total (ft/s)	10.15	Avg. Vel. (ft/s)		10.15	
Max Chl Dpth (ft)	9.45	Hydr. Depth (ft)		6.41	
Conv. Total (cfs)	46503.2	Conv. (cfs)		46503.2	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		63.26	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.57	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.01	2.66	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.37	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	7.47	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.66	Wt. n-Val.		0.040	
W.S. Elev (ft)	5.80	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		400.69	
E.G. Slope (ft/ft)	0.006824	Area (sq ft)		400.69	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	60.37	Top Width (ft)		60.37	
Vel Total (ft/s)	10.35	Avg. Vel. (ft/s)		10.35	
Max Chl Dpth (ft)	9.80	Hydr. Depth (ft)		6.64	
Conv. Total (cfs)	50212.1	Conv. (cfs)		50212.1	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		64.67	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.64	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.01	2.69	0.04
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.37	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	9.02	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.82	Wt. n-Val.		0.040	
W.S. Elev (ft)	7.20	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.30	Flow Area (sq ft)		488.44	
E.G. Slope (ft/ft)	0.006396	Area (sq ft)		488.44	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	65.11	Top Width (ft)		65.11	
Vel Total (ft/s)	10.83	Avg. Vel. (ft/s)		10.83	
Max Chl Dpth (ft)	11.20	Hydr. Depth (ft)		7.50	
Conv. Total (cfs)	66144.0	Conv. (cfs)		66144.0	
Length Wtd. (ft)	22.00	Wetted Per. (ft)		70.18	
Min Ch El (ft)	-4.00	Shear (lb/sq ft)		2.78	
Alpha	1.00	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.00	2.87	0.06
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	0.38	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.63	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.95	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	9.68	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	7.04	Flow Area (sq ft)	1.67	658.13	0.46
E.G. Slope (ft/ft)	0.005108	Area (sq ft)	1.67	658.13	0.46
Q Total (cfs)	7380.00	Flow (cfs)	1.94	7377.72	0.34
Top Width (ft)	73.78	Top Width (ft)	2.42	70.00	1.36
Vel Total (ft/s)	11.18	Avg. Vel. (ft/s)	1.16	11.21	0.74
Max Chl Dpth (ft)	13.68	Hydr. Depth (ft)	0.69	9.40	0.34
Conv. Total (cfs)	103257.5	Conv. (cfs)	27.2	103225.6	4.8
Length Wtd. (ft)	22.00	Wetted Per. (ft)	2.79	75.86	1.52
Min Ch El (ft)	-4.00	Shear (lb/sq ft)	0.19	2.77	0.10
Alpha	1.01	Stream Power (lb/ft s)	90.00	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	3.32	0.11
C & E Loss (ft)	0.04	Cum SA (acres)	0.01	0.38	0.03

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE

RIVER: Cobosee Stream
REACH: Reach 1 RS: 98.5

INPUT
Description: Maine Ave.
Distance from Upstream XS = 22
Deck/Roadway Width = 38
Weir Coefficient = 2.6
Upstream Deck/Roadway Coordinates
num= 6

Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord	Sta Hi Cord	Lo Cord
0	15.2	-10	4.5	15.2	-10
4.5	15.2	11.5	79.5	15.2	-10
100	15	-10			

Upstream Bridge Cross Section Data
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	14	10	8.3	20	2.5	30	-2.5	40	-3.7
50	-4	60	-2	70	3	80	9	90	14

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	80	.065

Bank Sta: Left Right Coeff Contr. Expan.

```
           10      80              .3       .5
Ineffective Flow     num=       1
   Sta L   Sta R    Elev  Permanent
      84      90    14.5       F

Downstream  Deck/Roadway Coordinates
    num=       6
     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord     Sta Hi Cord Lo Cord
       0    15.2     -10     4.5    15.2     -10     4.5    15.2    11.5
    79.5    15.2    11.5    79.5    15.2     -10     100      15     -10

Downstream Bridge Cross Section Data
Station Elevation Data    num=      10
     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev     Sta    Elev
    13.5      14    15.2       3    25.3      -4    33.6      -5    48.2      -5
    52.6      -4    65.7       0    76.2       7    80.2     8.5    80.3      12

Manning's n Values        num=       3
     Sta   n Val     Sta   n Val     Sta   n Val
    13.5    .065    15.2     .04    65.7    .065

Bank Sta: Left   Right    Coeff Contr.   Expan.
          15.2    65.7             .3       .5
Ineffective Flow     num=       2
   Sta L   Sta R    Elev  Permanent
    13.5      16      15       F
      72    80.3      15       F

Upstream Embankment side slope              =       2 horiz. to 1.0 vertical
Downstream Embankment side slope            =      .1 horiz. to 1.0 vertical
Maximum allowable submergence for weir flow =     .98
Elevation at which weir flow begins         =
Energy head used in spillway design         =
Spillway height used in design              =
Weir crest shape                            = Broad Crested

Number of Bridge Coefficient Sets =  1

Low Flow Methods and Data
       Energy
Selected Low Flow Methods = Highest Energy Answer

High Flow Method
       Energy Only

Additional Bridge Parameters
       Add Friction component to Momentum
       Do not add Weight component to Momentum
       Class B flow critical depth computations use critical depth
```

inside the bridge at the upstream end
Criteria to check for pressure flow = Upstream energy grade line

BRIDGE OUTPUT Profile #Q100

			Inside BR US	Inside BR DS
E.G. US. (ft)	9.84	Element		
W.S. US. (ft)	7.97	E.G. Elev (ft)	9.62	9.28
Q Total (cfs)	5910.00	W.S. Elev (ft)	7.55	7.51
Q Bridge (cfs)	5910.00	Crit W.S. (ft)	5.85	4.37
Q Weir (cfs)		Max Chl Dpth (ft)	11.55	12.51
Weir Sta Lft (ft)		Vel Total (ft/s)	11.57	10.35
Weir Sta Rgt (ft)		Flow Area (sq ft)	510.99	571.03
Weir Submerg		Froude # Chl	0.73	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	4514.16	5040.94
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	7.71	10.20
Min El Prs (ft)	11.50	W.P. Total (ft)	71.53	60.06
Delta EG (ft)	0.63	Conv. Total (cfs)	70410.5	96122.0
Delta WS (ft)	0.57	Top Width (ft)	66.28	63.06
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.19	0.07
BR Open Vel (ft/s)	11.57	C & E Loss (ft)	0.16	0.01
Coef of Q		Shear Total (lb/sq ft)	3.14	2.24
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q1.1

			Inside BR US	Inside BR DS
E.G. US. (ft)	4.20	Element		
W.S. US. (ft)	3.89	E.G. Elev (ft)	4.16	4.07
Q Total (cfs)	1312.00	W.S. Elev (ft)	3.84	3.86
Q Bridge (cfs)	1312.00	Crit W.S. (ft)	0.50	-0.83
Q Weir (cfs)		Max Chl Dpth (ft)	7.84	8.86
Weir Sta Lft (ft)		Vel Total (ft/s)	4.54	3.58
Weir Sta Rgt (ft)		Flow Area (sq ft)	288.84	366.52
Weir Submerg		Froude # Chl	0.35	0.24
Weir Max Depth (ft)		Specif Force (cu ft)	1110.10	1529.48
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	5.38	6.61
Min El Prs (ft)	11.50	W.P. Total (ft)	56.95	59.44
Delta EG (ft)	0.15	Conv. Total (cfs)	31672.6	47593.6
Delta WS (ft)	0.04	Top Width (ft)	53.72	56.42
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.04	0.01
BR Open Vel (ft/s)	4.54	C & E Loss (ft)	0.06	0.00
Coef of Q		Shear Total (lb/sq ft)	0.54	0.29
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q10

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.05	Element		
W.S. US. (ft)	5.45	E.G. Elev (ft)	6.76	6.21
Q Total (cfs)	3850.00	W.S. Elev (ft)	4.77	4.86
Q Bridge (cfs)	3850.00	Crit W.S. (ft)	3.90	2.44
Q Weir (cfs)		Max Chl Dpth (ft)	8.77	9.86
Weir Sta Lft (ft)		Vel Total (ft/s)	11.32	9.11
Weir Sta Rgt (ft)		Flow Area (sq ft)	339.99	422.38
Weir Submerg		Froude # Chl	0.82	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	2569.60	2888.97
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	5.98	7.54
Min El Prs (ft)	11.50	W.P. Total (ft)	60.60	60.06
Delta EG (ft)	0.92	Conv. Total (cfs)	39879.5	59442.7
Delta WS (ft)	0.73	Top Width (ft)	56.86	58.07
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.23	0.07
BR Open Vel (ft/s)	11.32	C & E Loss (ft)	0.32	0.01
Coef of Q		Shear Total (lb/sq ft)	3.26	1.84
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q25

			Inside BR US	Inside BR DS
E.G. US. (ft)	7.47	Element		
W.S. US. (ft)	5.80	E.G. Elev (ft)	7.17	6.63
Q Total (cfs)	4148.00	W.S. Elev (ft)	5.09	5.17
Q Bridge (cfs)	4148.00	Crit W.S. (ft)	4.20	2.74
Q Weir (cfs)		Max Chl Dpth (ft)	9.09	10.17
Weir Sta Lft (ft)		Vel Total (ft/s)	11.57	9.43
Weir Sta Rgt (ft)		Flow Area (sq ft)	358.46	439.99
Weir Submerg		Froude # Chl	0.82	0.59
Weir Max Depth (ft)		Specif Force (cu ft)	2818.68	3152.73

Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	6.19	7.86
Min El Prs (ft)	11.50	W.P. Total (ft)	61.86	60.06
Delta EG (ft)	0.93	Conv. Total (cfs)	42958.7	63405.0
Delta WS (ft)	0.78	Top Width (ft)	57.95	58.59
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.23	0.07
BR Open Vel (ft/s)	11.57	C & E Loss (ft)	0.31	0.02
Coef of Q		Shear Total (lb/sq ft)	3.37	1.96
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q50

E.G. US. (ft)	9.02	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	7.20	E.G. Elev (ft)	8.79	8.38
Q Total (cfs)	5290.00	W.S. Elev (ft)	6.71	6.72
Q Bridge (cfs)	5290.00	Crit W.S. (ft)	5.30	3.80
Q Weir (cfs)		Max Chl Dpth (ft)	10.71	11.72
Weir Sta Lft (ft)		Vel Total (ft/s)	11.58	10.05
Weir Sta Rgt (ft)		Flow Area (sq ft)	456.68	526.54
Weir Submerg		Froude # Chl	0.76	0.58
Weir Max Depth (ft)		Specif Force (cu ft)	3889.39	4348.86
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	7.20	9.40
Min El Prs (ft)	11.50	W.P. Total (ft)	68.23	60.06
Delta EG (ft)	0.72	Conv. Total (cfs)	60250.1	84392.2
Delta WS (ft)	0.60	Top Width (ft)	63.44	61.15
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.20	0.07
BR Open Vel (ft/s)	11.58	C & E Loss (ft)	0.21	0.01
Coef of Q		Shear Total (lb/sq ft)	3.22	2.15
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.
Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

BRIDGE OUTPUT Profile #Q500

E.G. US. (ft)	11.63	Element	Inside BR US	Inside BR DS
W.S. US. (ft)	9.68	E.G. Elev (ft)	11.48	11.27

Q Total (cfs)	7380.00	W.S. Elev (ft)	9.40	9.27
Q Bridge (cfs)	7380.00	Crit W.S. (ft)	7.04	5.55
Q Weir (cfs)		Max Chl Dpth (ft)	13.40	14.27
Weir Sta Lft (ft)		Vel Total (ft/s)	11.54	11.03
Weir Sta Rgt (ft)		Flow Area (sq ft)	639.25	669.32
Weir Submerg		Froude # Chl	0.56	0.57
Weir Max Depth (ft)		Specif Force (cu ft)	6105.25	6773.86
Min El Weir Flow (ft)	15.20	Hydr Depth (ft)	8.95	11.95
Min El Prs (ft)	11.50	W.P. Total (ft)	77.49	60.06
Delta EG (ft)	0.43	Conv. Total (cfs)	98586.1	124198.6
Delta WS (ft)	0.52	Top Width (ft)	71.43	65.27
BR Open Area (sq ft)	793.15	Frctn Loss (ft)	0.17	0.06
BR Open Vel (ft/s)	11.54	C & E Loss (ft)	0.03	0.01
Coef of Q		Shear Total (lb/sq ft)	2.89	2.46
Br Sel Method	Energy only	Power Total (lb/ft s)	0.00	13.50

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 60

INPUT
Description: 3
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
13.5	14	15.2	3	25.3	-4	33.6	-5	48.2	-5
52.6	-4	65.7	0	76.2	7	80.2	8.5	80.3	12

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
13.5	.065	15.2	.04	65.7	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
15.2	65.7	22	22	.3	.5

Ineffective Flow num= 2

Sta L	Sta R	Elev	Permanent
13.5	16	15	F
72	80.3	15	F

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	9.20	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.80	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	7.40	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	4.37	Flow Area (sq ft)		531.34	33.39
E.G. Slope (ft/ft)	0.003918	Area (sq ft)	1.50	535.08	41.16
Q Total (cfs)	5910.00	Flow (cfs)		5781.54	128.46
Top Width (ft)	62.75	Top Width (ft)	0.68	50.50	11.57
Vel Total (ft/s)	10.47	Avg. Vel. (ft/s)		10.88	3.85
Max Chl Dpth (ft)	12.40	Hydr. Depth (ft)		10.69	5.30
Conv. Total (cfs)	94422.3	Conv. (cfs)		92369.9	2052.4
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.48	1.08
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.00	1.98	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.27	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.05	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.21	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.84	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	-0.83	Flow Area (sq ft)		354.65	11.09
E.G. Slope (ft/ft)	0.000765	Area (sq ft)	0.06	355.55	11.09
Q Total (cfs)	1312.00	Flow (cfs)		1302.41	9.59
Top Width (ft)	56.40	Top Width (ft)	0.13	50.50	5.77
Vel Total (ft/s)	3.59	Avg. Vel. (ft/s)		3.67	0.86
Max Chl Dpth (ft)	8.84	Hydr. Depth (ft)		7.14	1.92
Conv. Total (cfs)	47435.9	Conv. (cfs)		47089.3	346.6
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	6.93
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		0.32	0.08
Alpha	1.04	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.01	1.98	0.02
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	6.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.41	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	4.72	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.44	Flow Area (sq ft)		398.14	16.50
E.G. Slope (ft/ft)	0.004447	Area (sq ft)	0.23	399.74	16.71
Q Total (cfs)	3850.00	Flow (cfs)		3807.71	42.29

Top Width (ft)	57.85	Top Width (ft)	0.27	50.50	7.08
Vel Total (ft/s)	9.29	Avg. Vel. (ft/s)		9.56	2.56
Max Chl Dpth (ft)	9.72	Hydr. Depth (ft)		8.01	2.62
Conv. Total (cfs)	57734.9	Conv. (cfs)		57100.6	634.2
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.11	0.61
Alpha	1.05	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.11	Cum Volume (acre-ft)	0.01	1.99	0.02
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	0.28	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.51	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	5.03	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	2.74	Flow Area (sq ft)		413.42	18.44
E.G. Slope (ft/ft)	0.004540	Area (sq ft)	0.32	415.26	18.95
Q Total (cfs)	4148.00	Flow (cfs)		4096.59	51.41
Top Width (ft)	58.35	Top Width (ft)	0.31	50.50	7.54
Vel Total (ft/s)	9.61	Avg. Vel. (ft/s)		9.91	2.79
Max Chl Dpth (ft)	10.03	Hydr. Depth (ft)		8.32	2.93
Conv. Total (cfs)	61561.6	Conv. (cfs)		60798.6	763.0
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.23	0.69
Alpha	1.05	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.12	Cum Volume (acre-ft)	0.01	2.00	0.02
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.27	0.01

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.30	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.70	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	6.60	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	3.80	Flow Area (sq ft)		491.54	28.34
E.G. Slope (ft/ft)	0.004093	Area (sq ft)	1.00	494.64	32.66
Q Total (cfs)	5290.00	Flow (cfs)		5190.07	99.93
Top Width (ft)	60.95	Top Width (ft)	0.56	50.50	9.90
Vel Total (ft/s)	10.18	Avg. Vel. (ft/s)		10.56	3.53
Max Chl Dpth (ft)	11.60	Hydr. Depth (ft)		9.89	4.50
Conv. Total (cfs)	82690.9	Conv. (cfs)		81128.9	1562.0
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57

Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.39	0.96
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.10	Cum Volume (acre-ft)	0.00	2.02	0.03
C & E Loss (ft)	0.12	Cum SA (acres)	0.00	0.27	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.21	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.04	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	9.16	Reach Len. (ft)	22.00	22.00	22.00
Crit W.S. (ft)	5.55	Flow Area (sq ft)		619.07	44.51
E.G. Slope (ft/ft)	0.003631	Area (sq ft)	2.94	624.23	65.15
Q Total (cfs)	7380.00	Flow (cfs)		7180.31	199.69
Top Width (ft)	65.97	Top Width (ft)	0.95	50.50	14.52
Vel Total (ft/s)	11.12	Avg. Vel. (ft/s)		11.60	4.49
Max Chl Dpth (ft)	14.16	Hydr. Depth (ft)		12.46	7.06
Conv. Total (cfs)	122479.0	Conv. (cfs)		119165.0	3314.1
Length Wtd. (ft)	22.00	Wetted Per. (ft)		52.48	7.57
Min Ch El (ft)	-5.00	Shear (lb/sq ft)		2.67	1.33
Alpha	1.06	Stream Power (lb/ft s)	80.30	0.00	0.00
Frctn Loss (ft)	0.09	Cum Volume (acre-ft)	0.01	2.20	0.06
C & E Loss (ft)	0.10	Cum SA (acres)	0.00	0.28	0.02

Note: Multiple critical depths were found at this location. The critical depth with the lowest, valid, water surface was used.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 38

INPUT
Description: 2
Station Elevation Data num= 11

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	13.2	13.2	13.2	13.3	0	24.2	-4	27.6	-4
43.6	-4.5	53.6	-4	61.4	0	61.5	2	83.6	12
89.9	15								

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	13.3	.04	61.5	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
13.3	61.5	38	38	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	8.98	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.19	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	6.79	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.17	488.82	25.39
E.G. Slope (ft/ft)	0.005186	Area (sq ft)	0.17	488.82	25.39
Q Total (cfs)	5910.00	Flow (cfs)	0.03	5839.64	70.33
Top Width (ft)	58.84	Top Width (ft)	0.05	48.20	10.59
Vel Total (ft/s)	11.49	Avg. Vel. (ft/s)	0.14	11.95	2.77
Max Chl Dpth (ft)	11.29	Hydr. Depth (ft)	3.40	10.14	2.40
Conv. Total (cfs)	82068.1	Conv. (cfs)	0.3	81091.1	976.7
Length Wtd. (ft)	38.00	Wetted Per. (ft)	6.79	51.80	11.63
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	3.06	0.71
Alpha	1.07	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.30	Cum Volume (acre-ft)	0.00	1.72	0.02
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	4.03	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.22	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.81	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.05	344.90	3.61
E.G. Slope (ft/ft)	0.000834	Area (sq ft)	0.05	344.90	3.61
Q Total (cfs)	1312.00	Flow (cfs)	0.00	1309.91	2.09
Top Width (ft)	52.22	Top Width (ft)	0.03	48.20	3.99
Vel Total (ft/s)	3.76	Avg. Vel. (ft/s)	0.04	3.80	0.58
Max Chl Dpth (ft)	8.31	Hydr. Depth (ft)	1.90	7.16	0.90
Conv. Total (cfs)	45419.6	Conv. (cfs)	0.1	45347.0	72.5
Length Wtd. (ft)	38.00	Wetted Per. (ft)	3.81	51.80	4.38
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.00	0.35	0.04
Alpha	1.02	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.03	Cum Volume (acre-ft)	0.01	1.81	0.01
C & E Loss (ft)	0.00	Cum SA (acres)	0.00	0.25	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.91	Element	Left OB	Channel	Right OB

Vel Head (ft)	1.74	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.17	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.07	362.58	5.22
E.G. Slope (ft/ft)	0.006073	Area (sq ft)	0.07	362.58	5.22
Q Total (cfs)	3850.00	Flow (cfs)	0.01	3840.75	9.24
Top Width (ft)	53.04	Top Width (ft)	0.03	48.20	4.80
Vel Total (ft/s)	10.47	Avg. Vel. (ft/s)	0.11	10.59	1.77
Max Chl Dpth (ft)	8.67	Hydr. Depth (ft)	2.09	7.52	1.09
Conv. Total (cfs)	49405.7	Conv. (cfs)	0.1	49287.0	118.6
Length Wtd. (ft)	38.00	Wetted Per. (ft)	4.17	51.80	5.27
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.65	0.38
Alpha	1.02	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.80	0.01
C & E Loss (ft)	0.05	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	6.30	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.90	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.40	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.07	373.66	6.38
E.G. Slope (ft/ft)	0.006369	Area (sq ft)	0.07	373.66	6.38
Q Total (cfs)	4148.00	Flow (cfs)	0.01	4135.62	12.37
Top Width (ft)	53.55	Top Width (ft)	0.03	48.20	5.31
Vel Total (ft/s)	10.91	Avg. Vel. (ft/s)	0.12	11.07	1.94
Max Chl Dpth (ft)	8.90	Hydr. Depth (ft)	2.20	7.75	1.20
Conv. Total (cfs)	51976.8	Conv. (cfs)	0.1	51821.7	155.1
Length Wtd. (ft)	38.00	Wetted Per. (ft)	4.40	51.80	5.83
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.87	0.44
Alpha	1.03	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.31	Cum Volume (acre-ft)	0.01	1.80	0.01
C & E Loss (ft)	0.08	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	8.08	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.09	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.99	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.14	449.90	17.55
E.G. Slope (ft/ft)	0.005518	Area (sq ft)	0.14	449.90	17.55
Q Total (cfs)	5290.00	Flow (cfs)	0.02	5245.62	44.36

Top Width (ft)	57.05	Top Width (ft)	0.05	48.20	8.81
Vel Total (ft/s)	11.31	Avg. Vel. (ft/s)	0.14	11.66	2.53
Max Chl Dpth (ft)	10.49	Hydr. Depth (ft)	2.99	9.33	1.99
Conv. Total (cfs)	71215.8	Conv. (cfs)	0.2	70618.4	597.2
Length Wtd. (ft)	38.00	Wetted Per. (ft)	5.99	51.80	9.67
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	2.99	0.63
Alpha	1.05	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.32	Cum Volume (acre-ft)	0.00	1.79	0.02
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	11.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.38	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	8.63	Reach Len. (ft)	38.00	38.00	38.00
Crit W.S. (ft)		Flow Area (sq ft)	0.28	577.30	48.55
E.G. Slope (ft/ft)	0.004557	Area (sq ft)	0.28	577.30	48.55
Q Total (cfs)	7380.00	Flow (cfs)	0.04	7223.42	156.53
Top Width (ft)	62.91	Top Width (ft)	0.07	48.20	14.65
Vel Total (ft/s)	11.79	Avg. Vel. (ft/s)	0.16	12.51	3.22
Max Chl Dpth (ft)	13.13	Hydr. Depth (ft)	4.31	11.98	3.31
Conv. Total (cfs)	109319.4	Conv. (cfs)	0.7	107000.0	2318.7
Length Wtd. (ft)	38.00	Wetted Per. (ft)	8.63	51.80	16.08
Min Ch El (ft)	-4.50	Shear (lb/sq ft)	0.01	3.17	0.86
Alpha	1.10	Stream Power (lb/ft s)	89.90	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.89	0.03
C & E Loss (ft)	0.25	Cum SA (acres)	0.00	0.25	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: 0

INPUT
Description: 1 (Downstream)
Station Elevation Data num= 9

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	19	1	19	10	2	20	-6.3	30	-6.3
40	-5	50	-2.5	52	1.8	60	19		

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	10	.04	52	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
10	52	21	21	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	8.48	Element			
Vel Head (ft)	4.24	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	4.24	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	4.24	Flow Area (sq ft)	1.33	357.35	1.39
E.G. Slope (ft/ft)	0.013662	Area (sq ft)	1.33	357.35	1.39
Q Total (cfs)	5910.00	Flow (cfs)	2.31	5905.31	2.38
Top Width (ft)	44.32	Top Width (ft)	1.19	42.00	1.14
Vel Total (ft/s)	16.41	Avg. Vel. (ft/s)	1.74	16.53	1.72
Max Chl Dpth (ft)	10.54	Hydr. Depth (ft)	1.12	8.51	1.22
Conv. Total (cfs)	50562.8	Conv. (cfs)	19.8	50522.7	20.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	2.54	48.13	2.69
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.45	6.33	0.44
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.28	Cum Volume (acre-ft)	0.00	1.35	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q1.1

			Left OB	Channel	Right OB
E.G. Elev (ft)	4.00	Element			
Vel Head (ft)	0.23	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.76	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)		Flow Area (sq ft)	0.82	337.25	0.90
E.G. Slope (ft/ft)	0.000817	Area (sq ft)	0.82	337.25	0.90
Q Total (cfs)	1312.00	Flow (cfs)	0.30	1311.38	0.33
Top Width (ft)	43.85	Top Width (ft)	0.93	42.00	0.91
Vel Total (ft/s)	3.87	Avg. Vel. (ft/s)	0.36	3.89	0.36
Max Chl Dpth (ft)	10.06	Hydr. Depth (ft)	0.88	8.03	0.98

Conv. Total (cfs)	45896.4	Conv. (cfs)	10.4	45874.6	11.4
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.99	48.13	2.16
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.02	0.36	0.02
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.01	Cum Volume (acre-ft)	0.01	1.51	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.21	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.59	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.26	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.33	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)		Flow Area (sq ft)	0.47	318.94	0.54
E.G. Slope (ft/ft)	0.008479	Area (sq ft)	0.47	318.94	0.54
Q Total (cfs)	3850.00	Flow (cfs)	0.45	3849.01	0.54
Top Width (ft)	43.41	Top Width (ft)	0.70	42.00	0.71
Vel Total (ft/s)	12.03	Avg. Vel. (ft/s)	0.97	12.07	0.99
Max Chl Dpth (ft)	9.63	Hydr. Depth (ft)	0.66	7.59	0.76
Conv. Total (cfs)	41810.6	Conv. (cfs)	4.9	41799.9	5.8
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.50	48.13	1.68
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.16	3.51	0.17
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.13	Cum Volume (acre-ft)	0.01	1.50	0.01
C & E Loss (ft)	0.20	Cum SA (acres)	0.00	0.21	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.91	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.72	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.19	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	2.45	Flow Area (sq ft)	0.37	313.06	0.45
E.G. Slope (ft/ft)	0.010473	Area (sq ft)	0.37	313.06	0.45
Q Total (cfs)	4148.00	Flow (cfs)	0.37	4147.17	0.46
Top Width (ft)	43.27	Top Width (ft)	0.63	42.00	0.65
Vel Total (ft/s)	13.22	Avg. Vel. (ft/s)	1.00	13.25	1.03
Max Chl Dpth (ft)	9.49	Hydr. Depth (ft)	0.59	7.45	0.69
Conv. Total (cfs)	40532.0	Conv. (cfs)	3.6	40523.9	4.5
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.34	48.13	1.53
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.18	4.25	0.19
Alpha	1.00	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.16	Cum Volume (acre-ft)	0.01	1.50	0.01
C & E Loss (ft)	0.26	Cum SA (acres)	0.00	0.21	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.58	Element			
Vel Head (ft)	3.96	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	3.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	3.62	Flow Area (sq ft)	0.69	331.05	0.77
E.G. Slope (ft/ft)	0.014135	Area (sq ft)	0.69	331.05	0.77
Q Total (cfs)	5290.00	Flow (cfs)	0.98	5287.92	1.10
Top Width (ft)	43.70	Top Width (ft)	0.86	42.00	0.84
Vel Total (ft/s)	15.91	Avg. Vel. (ft/s)	1.42	15.97	1.43
Max Chl Dpth (ft)	9.92	Hydr. Depth (ft)	0.81	7.88	0.91
Conv. Total (cfs)	44494.8	Conv. (cfs)	8.3	44477.3	9.2
Length Wtd. (ft)	21.00	Wetted Per. (ft)	1.83	48.13	2.00
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.33	6.07	0.34
Alpha	1.01	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.25	Cum Volume (acre-ft)	0.00	1.44	0.01
C & E Loss (ft)	0.24	Cum SA (acres)	0.00	0.21	0.01

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION OUTPUT Profile #Q500

			Left OB	Channel	Right OB
E.G. Elev (ft)	10.49	Element			
Vel Head (ft)	4.87	Wt. n-Val.	0.065	0.040	0.065
W.S. Elev (ft)	5.62	Reach Len. (ft)	21.00	21.00	21.00
Crit W.S. (ft)	5.62	Flow Area (sq ft)	3.47	415.35	3.40
E.G. Slope (ft/ft)	0.012870	Area (sq ft)	3.47	415.35	3.40
Q Total (cfs)	7380.00	Flow (cfs)	8.07	7364.30	7.63
Top Width (ft)	45.70	Top Width (ft)	1.92	42.00	1.78
Vel Total (ft/s)	17.48	Avg. Vel. (ft/s)	2.32	17.73	2.25
Max Chl Dpth (ft)	11.92	Hydr. Depth (ft)	1.81	9.89	1.91
Conv. Total (cfs)	65054.0	Conv. (cfs)	71.1	64915.6	67.3
Length Wtd. (ft)	21.00	Wetted Per. (ft)	4.10	48.13	4.22
Min Ch El (ft)	-6.30	Shear (lb/sq ft)	0.68	6.93	0.65
Alpha	1.03	Stream Power (lb/ft s)	60.00	0.00	0.00
Frctn Loss (ft)	0.27	Cum Volume (acre-ft)	0.01	1.46	0.01
C & E Loss (ft)	0.06	Cum SA (acres)	0.00	0.21	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The program used critical depth for the water surface and continued on with the calculations.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.
Warning: During the standard step iterations, when the assumed water surface was set equal to critical depth, the calculated water surface came back below critical depth. This indicates that there is not a valid subcritical answer. The program defaulted to critical depth.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -21

INPUT
Description: RR
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	15	8	-3	25	-7	30	-7	37	-6
50	-2	59	20						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	8	.04	59	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
8	59	33	33	.1	.3

CROSS SECTION OUTPUT Profile #Q100

			Left OB	Channel	Right OB
E.G. Elev (ft)	7.91	Element			
Vel Head (ft)	6.09	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.82	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	3.29	Flow Area (sq ft)	5.17	297.09	
E.G. Slope (ft/ft)	0.024570	Area (sq ft)	5.17	297.09	
Q Total (cfs)	5910.00	Flow (cfs)	18.28	5891.73	
Top Width (ft)	45.71	Top Width (ft)	2.14	43.56	
Vel Total (ft/s)	19.55	Avg. Vel. (ft/s)	3.53	19.83	
Max Chl Dpth (ft)	8.82	Hydr. Depth (ft)	2.41	6.82	
Conv. Total (cfs)	37703.4	Conv. (cfs)	116.6	37586.8	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	5.28	47.27	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.50	9.64	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.38	Cum Volume (acre-ft)	0.00	1.20	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.97	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.18	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.79	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	10.24	383.45	
E.G. Slope (ft/ft)	0.000546	Area (sq ft)	10.24	383.45	
Q Total (cfs)	1312.00	Flow (cfs)	6.78	1305.22	
Top Width (ft)	47.38	Top Width (ft)	3.02	44.37	
Vel Total (ft/s)	3.33	Avg. Vel. (ft/s)	0.66	3.40	
Max Chl Dpth (ft)	10.79	Hydr. Depth (ft)	3.39	8.64	
Conv. Total (cfs)	56140.0	Conv. (cfs)	289.9	55850.1	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.43	49.39	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.05	0.26	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.02	Cum SA (acres)	0.00	0.19	0.01

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	5.25	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.59	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.67	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	9.87	378.00	
E.G. Slope (ft/ft)	0.004917	Area (sq ft)	9.87	378.00	
Q Total (cfs)	3850.00	Flow (cfs)	19.36	3830.64	
Top Width (ft)	47.28	Top Width (ft)	2.96	44.32	
Vel Total (ft/s)	9.93	Avg. Vel. (ft/s)	1.96	10.13	
Max Chl Dpth (ft)	10.67	Hydr. Depth (ft)	3.33	8.53	
Conv. Total (cfs)	54907.0	Conv. (cfs)	276.1	54630.9	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.29	49.26	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.42	2.36	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.15	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.16	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.49	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.86	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	3.63	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)		Flow Area (sq ft)	9.78	376.58	
E.G. Slope (ft/ft)	0.005774	Area (sq ft)	9.78	376.58	

Q Total (cfs)	4148.00	Flow (cfs)	20.72	4127.29	
Top Width (ft)	47.25	Top Width (ft)	2.95	44.30	
Vel Total (ft/s)	10.74	Avg. Vel. (ft/s)	2.12	10.96	
Max Chl Dpth (ft)	10.63	Hydr. Depth (ft)	3.32	8.50	
Conv. Total (cfs)	54587.4	Conv. (cfs)	272.6	54314.8	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	7.26	49.22	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	0.49	2.76	
Alpha	1.04	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)	0.00	1.33	0.01
C & E Loss (ft)	0.19	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	7.01	Element	Left OB	Channel	Right OB
Vel Head (ft)	5.69	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	1.32	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	2.71	Flow Area (sq ft)	4.15	275.33	
E.G. Slope (ft/ft)	0.025006	Area (sq ft)	4.15	275.33	
Q Total (cfs)	5290.00	Flow (cfs)	13.76	5276.24	
Top Width (ft)	45.28	Top Width (ft)	1.92	43.36	
Vel Total (ft/s)	18.93	Avg. Vel. (ft/s)	3.31	19.16	
Max Chl Dpth (ft)	8.32	Hydr. Depth (ft)	2.16	6.35	
Conv. Total (cfs)	33452.7	Conv. (cfs)	87.0	33365.6	
Length Wtd. (ft)	33.00	Wetted Per. (ft)	4.73	46.73	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.37	9.20	
Alpha	1.02	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.39	Cum Volume (acre-ft)	0.00	1.30	0.01
C & E Loss (ft)	0.17	Cum SA (acres)	0.00	0.19	0.01

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	9.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.98	Wt. n-Val.	0.065	0.040	
W.S. Elev (ft)	2.94	Reach Len. (ft)	33.00	33.00	33.00
Crit W.S. (ft)	4.65	Flow Area (sq ft)	7.84	346.01	
E.G. Slope (ft/ft)	0.023784	Area (sq ft)	7.84	346.01	
Q Total (cfs)	7380.00	Flow (cfs)	31.34	7348.67	
Top Width (ft)	46.66	Top Width (ft)	2.64	44.02	
Vel Total (ft/s)	20.86	Avg. Vel. (ft/s)	4.00	21.24	
Max Chl Dpth (ft)	9.94	Hydr. Depth (ft)	2.97	7.86	
Conv. Total (cfs)	47853.6	Conv. (cfs)	203.2	47650.5	

Length Wtd. (ft)	33.00	Wetted Per. (ft)	6.50	48.48	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)	1.79	10.60	
Alpha	1.03	Stream Power (lb/ft s)	59.00	0.00	0.00
Frctn Loss (ft)	0.36	Cum Volume (acre-ft)	0.00	1.28	0.01
C & E Loss (ft)	0.21	Cum SA (acres)	0.00	0.19	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -54

INPUT
Description: K2
Station Elevation Data num= 10

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	21	5	40	-7	50	-7
60	-6	72	-2	80	0	88	2	96	4

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	88	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	88	34	34	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.72	Element	Left OB	Channel	Right OB
Vel Head (ft)	4.87	Wt. n-Val.		0.040	
W.S. Elev (ft)	1.85	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	3.09	Flow Area (sq ft)		333.87	
E.G. Slope (ft/ft)	0.025698	Area (sq ft)		333.87	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	61.41	Top Width (ft)		61.41	
Vel Total (ft/s)	17.70	Avg. Vel. (ft/s)		17.70	
Max Chl Dpth (ft)	8.85	Hydr. Depth (ft)		5.44	
Conv. Total (cfs)	36867.0	Conv. (cfs)		36867.0	
Length Wtd. (ft)	34.00	Wetted Per. (ft)		65.15	
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		8.22	
Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.83	Cum Volume (acre-ft)		0.96	0.01
C & E Loss (ft)	0.37	Cum SA (acres)		0.15	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.93	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.13	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.81	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		458.26	6.54
E.G. Slope (ft/ft)	0.000478	Area (sq ft)		458.26	6.54
Q Total (cfs)	1312.00	Flow (cfs)		1309.01	2.99
Top Width (ft)	72.34	Top Width (ft)		65.11	7.23
Vel Total (ft/s)	2.82	Avg. Vel. (ft/s)		2.86	0.46
Max Chl Dpth (ft)	10.81	Hydr. Depth (ft)		7.04	0.90
Conv. Total (cfs)	60036.6	Conv. (cfs)		59899.7	136.9
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.43	7.45
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		0.20	0.03
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)		1.02	0.01
C & E Loss (ft)	0.00	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.95	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.06	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.88	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		463.27	7.11
E.G. Slope (ft/ft)	0.003975	Area (sq ft)		463.27	7.11
Q Total (cfs)	3850.00	Flow (cfs)		3840.35	9.65
Top Width (ft)	72.77	Top Width (ft)		65.23	7.54
Vel Total (ft/s)	8.18	Avg. Vel. (ft/s)		8.29	1.36
Max Chl Dpth (ft)	10.88	Hydr. Depth (ft)		7.10	0.94
Conv. Total (cfs)	61062.8	Conv. (cfs)		60909.8	153.0
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.58	7.77
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.65	0.23
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.14	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	5.13	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.23	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.90	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)		Flow Area (sq ft)		464.35	7.23

E.G. Slope (ft/ft)	0.004581	Area (sq ft)		464.35	7.23
Q Total (cfs)	4148.00	Flow (cfs)		4137.40	10.60
Top Width (ft)	72.87	Top Width (ft)		65.26	7.61
Vel Total (ft/s)	8.80	Avg. Vel. (ft/s)		8.91	1.47
Max Chl Dpth (ft)	10.90	Hydr. Depth (ft)		7.12	0.95
Conv. Total (cfs)	61285.1	Conv. (cfs)		61128.5	156.6
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.61	7.84
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.91	0.26
Alpha	1.02	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.92	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	4.04	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	2.59	Flow Area (sq ft)		473.69	8.35
E.G. Slope (ft/ft)	0.007001	Area (sq ft)		473.69	8.35
Q Total (cfs)	5290.00	Flow (cfs)		5273.94	16.06
Top Width (ft)	73.49	Top Width (ft)		65.49	8.00
Vel Total (ft/s)	10.97	Avg. Vel. (ft/s)		11.13	1.92
Max Chl Dpth (ft)	11.04	Hydr. Depth (ft)		7.23	1.04
Conv. Total (cfs)	63222.0	Conv. (cfs)		63030.0	192.0
Length Wtd. (ft)	34.00	Wetted Per. (ft)		69.87	8.29
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.96	0.44
Alpha	1.03	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.26	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.15	0.00

Warning: The cross-section end points had to be extended vertically for the computed water surface.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	8.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	6.75	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	2.18	Reach Len. (ft)	34.00	34.00	34.00
Crit W.S. (ft)	4.20	Flow Area (sq ft)		354.06	0.06
E.G. Slope (ft/ft)	0.033780	Area (sq ft)		354.06	0.06
Q Total (cfs)	7380.00	Flow (cfs)		7379.95	0.05
Top Width (ft)	63.23	Top Width (ft)		62.53	0.70
Vel Total (ft/s)	20.84	Avg. Vel. (ft/s)		20.84	0.81
Max Chl Dpth (ft)	9.18	Hydr. Depth (ft)		5.66	0.09
Conv. Total (cfs)	40153.7	Conv. (cfs)		40153.5	0.3
Length Wtd. (ft)		Wetted Per. (ft)		66.37	0.72
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		11.25	0.18

Alpha	1.00	Stream Power (lb/ft s)	96.00	0.00	0.00
Frctn Loss (ft)	0.93	Cum Volume (acre-ft)		1.01	0.01
C & E Loss (ft)	0.07	Cum SA (acres)		0.15	0.00

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -88

INPUT
Description: K1
Station Elevation Data num= 8

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11	10	56	-6	72	-6	80	-5
94	0	108	5	122	5				

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11	.04	108	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11	108	55	55	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	6.18	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.51	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.67	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	3.18	Flow Area (sq ft)		465.10	
E.G. Slope (ft/ft)	0.010956	Area (sq ft)		465.10	
Q Total (cfs)	5910.00	Flow (cfs)		5910.00	
Top Width (ft)	75.49	Top Width (ft)		75.49	
Vel Total (ft/s)	12.71	Avg. Vel. (ft/s)		12.71	
Max Chl Dpth (ft)	9.67	Hydr. Depth (ft)		6.16	
Conv. Total (cfs)	56462.2	Conv. (cfs)		56462.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		78.73	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		4.04	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.42	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.23	Cum SA (acres)		0.09	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.92	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.12	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.80	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		474.41	
E.G. Slope (ft/ft)	0.000512	Area (sq ft)		474.41	
Q Total (cfs)	1312.00	Flow (cfs)		1312.00	
Top Width (ft)	76.18	Top Width (ft)		76.18	
Vel Total (ft/s)	2.77	Avg. Vel. (ft/s)		2.77	
Max Chl Dpth (ft)	9.80	Hydr. Depth (ft)		6.23	
Conv. Total (cfs)	58000.7	Conv. (cfs)		58000.7	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.46	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		0.19	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.02	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.01	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.80	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.03	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.76	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		471.96	
E.G. Slope (ft/ft)	0.004468	Area (sq ft)		471.96	
Q Total (cfs)	3850.00	Flow (cfs)		3850.00	
Top Width (ft)	76.00	Top Width (ft)		76.00	
Vel Total (ft/s)	8.16	Avg. Vel. (ft/s)		8.16	
Max Chl Dpth (ft)	9.76	Hydr. Depth (ft)		6.21	
Conv. Total (cfs)	57595.2	Conv. (cfs)		57595.2	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.27	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		1.66	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.17	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.09	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.96	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.20	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.76	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		471.34	
E.G. Slope (ft/ft)	0.005206	Area (sq ft)		471.34	
Q Total (cfs)	4148.00	Flow (cfs)		4148.00	
Top Width (ft)	75.96	Top Width (ft)		75.96	
Vel Total (ft/s)	8.80	Avg. Vel. (ft/s)		8.80	
Max Chl Dpth (ft)	9.76	Hydr. Depth (ft)		6.21	
Conv. Total (cfs)	57491.9	Conv. (cfs)		57491.9	

Length Wtd. (ft)	55.00	Wetted Per. (ft)		79.22	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		1.93	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.20	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.11	Cum SA (acres)		0.09	0.00

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.70	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.98	Wt. n-Val.		0.040	
W.S. Elev (ft)	3.71	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)		Flow Area (sq ft)		467.88	
E.G. Slope (ft/ft)	0.008637	Area (sq ft)		467.88	
Q Total (cfs)	5290.00	Flow (cfs)		5290.00	
Top Width (ft)	75.70	Top Width (ft)		75.70	
Vel Total (ft/s)	11.31	Avg. Vel. (ft/s)		11.31	
Max Chl Dpth (ft)	9.71	Hydr. Depth (ft)		6.18	
Conv. Total (cfs)	56921.1	Conv. (cfs)		56921.1	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		78.95	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		3.20	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)	0.33	Cum Volume (acre-ft)		0.65	0.01
C & E Loss (ft)	0.18	Cum SA (acres)		0.09	0.00

Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	7.51	Element	Left OB	Channel	Right OB
Vel Head (ft)	3.26	Wt. n-Val.		0.040	
W.S. Elev (ft)	4.25	Reach Len. (ft)	55.00	55.00	55.00
Crit W.S. (ft)	4.25	Flow Area (sq ft)		509.28	
E.G. Slope (ft/ft)	0.013360	Area (sq ft)		509.28	
Q Total (cfs)	7380.00	Flow (cfs)		7380.00	
Top Width (ft)	78.71	Top Width (ft)		78.71	
Vel Total (ft/s)	14.49	Avg. Vel. (ft/s)		14.49	
Max Chl Dpth (ft)	10.25	Hydr. Depth (ft)		6.47	
Conv. Total (cfs)	63848.9	Conv. (cfs)		63848.9	
Length Wtd. (ft)	55.00	Wetted Per. (ft)		82.14	
Min Ch El (ft)	-6.00	Shear (lb/sq ft)		5.17	
Alpha	1.00	Stream Power (lb/ft s)	122.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)		0.67	0.01
C & E Loss (ft)		Cum SA (acres)		0.10	0.00

Warning: The energy equation could not be balanced within the specified number of iterations. The

program used critical depth for the water surface and continued on with the calculations.
Warning: The velocity head has changed by more than 0.5 ft (0.15 m). This may indicate the need for additional cross sections.
Warning: The conveyance ratio (upstream conveyance divided by downstream conveyance) is less than 0.7 or greater than 1.4. This may indicate the need for additional cross sections.
Warning: The energy loss was greater than 1.0 ft (0.3 m). between the current and previous cross section. This may indicate the need for additional cross sections.

CROSS SECTION

RIVER: Cobosee Stream
REACH: Reach 1 RS: -143

INPUT
Description: K0
Station Elevation Data num= 7

Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev	Sta	Elev
0	10	11.3	10	52.7	-7	69	-7	77.8	-6
98.2	-1	100	-1						

Manning's n Values num= 3

Sta	n Val	Sta	n Val	Sta	n Val
0	.065	11.3	.04	98.2	.065

Bank Sta: Left	Right	Lengths: Left Channel	Right	Coeff Contr.	Expan.
11.3	98.2	0	0	.1	.3

CROSS SECTION OUTPUT Profile #Q100

E.G. Elev (ft)	5.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.73	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	1.75	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.005536	Area (sq ft)		557.63	8.64
Q Total (cfs)	5910.00	Flow (cfs)		5892.41	17.59
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	10.44	Avg. Vel. (ft/s)		10.57	2.04
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.58	0.45
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q1.1

E.G. Elev (ft)	3.89	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.09	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	-2.96	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.000273	Area (sq ft)		557.63	8.64
Q Total (cfs)	1312.00	Flow (cfs)		1308.10	3.90
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	2.32	Avg. Vel. (ft/s)		2.35	0.45
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		0.13	0.02
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q10

E.G. Elev (ft)	4.53	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.73	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	0.05	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.002349	Area (sq ft)		557.63	8.64
Q Total (cfs)	3850.00	Flow (cfs)		3838.54	11.46
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	6.80	Avg. Vel. (ft/s)		6.88	1.33
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.10	0.19
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q25

E.G. Elev (ft)	4.65	Element	Left OB	Channel	Right OB
Vel Head (ft)	0.85	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	0.32	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.002727	Area (sq ft)		557.63	8.64
Q Total (cfs)	4148.00	Flow (cfs)		4135.66	12.34
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	7.33	Avg. Vel. (ft/s)		7.42	1.43
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60

Min Ch El (ft)	-7.00	Shear (lb/sq ft)		1.27	0.22
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q50

E.G. Elev (ft)	5.19	Element	Left OB	Channel	Right OB
Vel Head (ft)	1.39	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	1.29	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.004435	Area (sq ft)		557.63	8.64
Q Total (cfs)	5290.00	Flow (cfs)		5274.26	15.74
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	9.34	Avg. Vel. (ft/s)		9.46	1.82
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		2.07	0.36
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

CROSS SECTION OUTPUT Profile #Q500

E.G. Elev (ft)	6.50	Element	Left OB	Channel	Right OB
Vel Head (ft)	2.70	Wt. n-Val.		0.040	0.065
W.S. Elev (ft)	3.80	Reach Len. (ft)			
Crit W.S. (ft)	2.81	Flow Area (sq ft)		557.63	8.64
E.G. Slope (ft/ft)	0.008632	Area (sq ft)		557.63	8.64
Q Total (cfs)	7380.00	Flow (cfs)		7358.04	21.96
Top Width (ft)	73.60	Top Width (ft)		71.80	1.80
Vel Total (ft/s)	13.03	Avg. Vel. (ft/s)		13.20	2.54
Max Chl Dpth (ft)	10.80	Hydr. Depth (ft)		7.77	4.80
Conv. Total (cfs)	79433.6	Conv. (cfs)		79197.2	236.4
Length Wtd. (ft)		Wetted Per. (ft)		74.59	6.60
Min Ch El (ft)	-7.00	Shear (lb/sq ft)		4.03	0.71
Alpha	1.02	Stream Power (lb/ft s)	100.00	0.00	0.00
Frctn Loss (ft)		Cum Volume (acre-ft)			
C & E Loss (ft)		Cum SA (acres)			

Note: Hydraulic jump has occurred between this cross section and the previous upstream section.

SUMMARY OF MANNING'S N VALUES

River:Cobosee Stream

Reach	River Sta.	n1	n2	n3
Reach 1	1700	.07	.04	.065
Reach 1	1635	.07	.045	.065
Reach 1	1555	.07	.042	.065
Reach 1	1455	.065	.045	.07
Reach 1	1335	.065	.045	.075
Reach 1	1185	.065	.045	.07
Reach 1	1060	.065	.04	.07
Reach 1	960	.05	.042	.05
Reach 1	935	.05	.042	.05
Reach 1	895	Bridge		
Reach 1	850	.05	.04	.05
Reach 1	830	.05	.035	.05
Reach 1	821	.065	.035	.065
Reach 1	820	.065	.035	.065
Reach 1	725	.065	.04	.065
Reach 1	575	.065	.04	.065
Reach 1	425	.065	.04	.065
Reach 1	335	.065	.04	.065
Reach 1	262	.065	.04	.065
Reach 1	187	.065	.04	.065
Reach 1	166	Bridge		
Reach 1	137	.065	.04	.065
Reach 1	98.5	Bridge		
Reach 1	60	.065	.04	.065
Reach 1	38	.065	.04	.065
Reach 1	0	.065	.04	.065
Reach 1	-21	.065	.04	.065
Reach 1	-54	.065	.04	.065
Reach 1	-88	.065	.04	.065
Reach 1	-143	.065	.04	.065

SUMMARY OF REACH LENGTHS

River: Cobosee Stream

Reach	River Sta.	Left	Channel	Right
Reach 1	1700	65	65	65
Reach 1	1635	80	80	80
Reach 1	1555	100	100	100
Reach 1	1455	120	120	120

Reach 1	1335	150	150	150
Reach 1	1185	125	125	125
Reach 1	1060	100	100	100
Reach 1	960	25	25	25
Reach 1	935	85	85	85
Reach 1	895	Bridge		
Reach 1	850	20	20	20
Reach 1	830	9	9	9
Reach 1	821	1	1	1
Reach 1	820	95	95	95
Reach 1	725	150	150	150
Reach 1	575	150	150	150
Reach 1	425	90	90	90
Reach 1	335	73	73	73
Reach 1	262	75	75	75
Reach 1	187	50	50	50
Reach 1	166	Bridge		
Reach 1	137	77	77	77
Reach 1	98.5	Bridge		
Reach 1	60	22	22	22
Reach 1	38	38	38	38
Reach 1	0	21	21	21
Reach 1	-21	33	33	33
Reach 1	-54	34	34	34
Reach 1	-88	55	55	55
Reach 1	-143	0	0	0

SUMMARY OF CONTRACTION AND EXPANSION COEFFICIENTS
River: Cobosee Stream

Reach	River Sta.	Contr.	Expan.
Reach 1	1700	.1	.3
Reach 1	1635	.1	.3
Reach 1	1555	.1	.3
Reach 1	1455	.1	.3
Reach 1	1335	.1	.3
Reach 1	1185	.1	.3
Reach 1	1060	.1	.3
Reach 1	960	.3	.5
Reach 1	935	.3	.5
Reach 1	895	Bridge	
Reach 1	850	.3	.5
Reach 1	830	.3	.5
Reach 1	821	.1	.3

Reach 1	820		.1	.3
Reach 1	725		.1	.3
Reach 1	575		.1	.3
Reach 1	425		.1	.3
Reach 1	335		.1	.3
Reach 1	262		.1	.3
Reach 1	187		.1	.3
Reach 1	166	Bridge		
Reach 1	137		.3	.5
Reach 1	98.5	Bridge		
Reach 1	60		.3	.5
Reach 1	38		.1	.3
Reach 1	0		.1	.3
Reach 1	-21		.1	.3
Reach 1	-54		.1	.3
Reach 1	-88		.1	.3
Reach 1	-143		.1	.3

Profile Output Table - Standard Table 1

Reach	River Sta	Profile	Q Total (cfs)	Min Ch El (ft)	W.S. Elev (ft)	Crit W.S. (ft)	E.G. Elev (ft)	E.G. Slope (ft/ft)	Vel Chnl (ft/s)	Flow Area (sq ft)	Top Width (ft)	Froude # Chl
Reach 1	1700	Q100	5910.00	13.80	22.75	21.32	24.48	0.006899	10.56	559.56	84.99	0.73
Reach 1	1700	Q1.1	1312.00	13.80	18.54	17.33	19.04	0.004837	5.66	231.75	70.35	0.55
Reach 1	1700	Q10	3850.00	13.80	21.15	19.81	22.41	0.006488	8.99	428.08	79.67	0.68
Reach 1	1700	Q25	4148.00	13.80	21.40	20.05	22.73	0.006586	9.26	447.72	80.49	0.69
Reach 1	1700	Q50	5290.00	13.80	22.28	20.89	23.89	0.006865	10.17	519.99	83.43	0.72
Reach 1	1700	Q500	7380.00	13.80	23.79	22.27	25.79	0.006886	11.36	649.74	88.50	0.74
Reach 1	1635	Q100	5910.00	14.00	22.26		23.95	0.009287	10.45	565.73	91.56	0.74
Reach 1	1635	Q1.1	1312.00	14.00	17.69		18.50	0.015059	7.21	181.92	75.56	0.82
Reach 1	1635	Q10	3850.00	14.00	20.47		21.86	0.010705	9.45	407.41	86.08	0.77
Reach 1	1635	Q25	4148.00	14.00	20.75		22.19	0.010420				

9.61	431.49	86.93		0.76					
Reach 1	1635		Q50	5290.00	14.00	21.75		23.36	0.009593
10.17	520.12	90.01		0.75					
Reach 1	1635		Q500	7380.00	14.00	23.37		25.25	0.008748
11.03	669.19	94.97		0.73					
Reach 1	1555		Q100	5910.00	13.30	20.34	20.16	22.96	0.013986
12.99	455.11	80.13		0.96					
Reach 1	1555		Q1.1	1312.00	13.30	16.65		17.46	0.011277
7.21	181.93	67.33		0.77					
Reach 1	1555		Q10	3850.00	13.30	19.06	18.65	20.89	0.012593
10.84	355.05	76.34		0.89					
Reach 1	1555		Q25	4148.00	13.30	19.24	18.89	21.21	0.013023
11.25	368.77	76.87		0.91					
Reach 1	1555		Q50	5290.00	13.30	19.96	19.73	22.37	0.013832
12.46	424.40	78.99		0.95					
Reach 1	1555		Q500	7380.00	13.30	21.24	21.12	24.27	0.013933
13.96	528.57	82.81		0.97					
Reach 1	1455		Q100	5910.00	11.80	19.15	18.73	21.52	0.013371
12.36	482.06	84.97		0.89					
Reach 1	1455		Q1.1	1312.00	11.80	15.06	14.87	16.04	0.018077
7.92	165.73	68.77		0.90					
Reach 1	1455		Q10	3850.00	11.80	17.40	17.28	19.41	0.017108
11.38	338.92	78.76		0.96					
Reach 1	1455		Q25	4148.00	11.80	17.67	17.49	19.74	0.016461
11.55	360.02	79.70		0.95					
Reach 1	1455		Q50	5290.00	11.80	18.65	18.33	20.92	0.014397
12.10	439.76	83.19		0.91					
Reach 1	1455		Q500	7380.00	11.80	20.28		22.87	0.011590
12.93	580.89	89.01		0.86					
Reach 1	1335		Q100	5910.00	9.50	18.29		20.09	0.008433
10.77	549.92	80.42		0.72					
Reach 1	1335		Q1.1	1312.00	9.50	12.63	12.50	13.78	0.019322
8.58	152.87	58.82		0.94					
Reach 1	1335		Q10	3850.00	9.50	16.13		17.69	0.010509
10.02	384.33	72.81		0.77					
Reach 1	1335		Q25	4148.00	9.50	16.48		18.07	0.010113
10.13	409.66	74.08		0.76					
Reach 1	1335		Q50	5290.00	9.50	17.68		19.41	0.008923
10.55	501.86	78.35		0.73					
Reach 1	1335		Q500	7380.00	9.50	19.61		21.58	0.007513
11.27	658.95	85.25		0.70					

Reach 1	1185		Q100	5910.00	5.50	15.71	15.05	18.43	0.013216
13.23	446.60	64.07		0.88					
Reach 1	1185		Q1.1	1312.00	5.50	10.99		11.81	0.008701
7.27	180.58	47.96		0.66					
Reach 1	1185		Q10	3850.00	5.50	14.07	13.16	16.00	0.011592
11.14	345.59	58.73		0.81					
Reach 1	1185		Q25	4148.00	5.50	14.34	13.46	16.38	0.011842
11.48	361.45	59.60		0.82					
Reach 1	1185		Q50	5290.00	5.50	15.28	14.52	17.75	0.012665
12.62	419.10	62.66		0.86					
Reach 1	1185		Q500	7380.00	5.50	16.59	16.20	19.92	0.014382
14.64	504.17	66.73		0.93					
Reach 1	1060		Q100	5910.00	5.00	13.60	13.60	16.72	0.013608
14.18	416.89	66.85		1.00					
Reach 1	1060		Q1.1	1312.00	5.00	8.85	8.85	10.26	0.017292
9.54	137.48	49.24		1.01					
Reach 1	1060		Q10	3850.00	5.00	11.83	11.83	14.32	0.014510
12.68	303.73	61.10		1.00					
Reach 1	1060		Q25	4148.00	5.00	12.11	12.11	14.70	0.014350
12.93	320.83	62.03		1.00					
Reach 1	1060		Q50	5290.00	5.00	13.10	13.10	16.05	0.013874
13.79	383.70	65.29		1.00					
Reach 1	1060		Q500	7380.00	5.00	14.68	14.68	18.19	0.013258
15.04	490.72	70.18		1.00					
Reach 1	960		Q100	5910.00	3.50	9.43	10.91	14.55	0.030767
18.60	341.13	76.49		1.44					
Reach 1	960		Q1.1	1312.00	3.50	6.44	6.75	8.04	0.029093
10.21	131.29	63.66		1.21					
Reach 1	960		Q10	3850.00	3.50	8.24	9.32	12.10	0.032272
16.02	253.19	71.40		1.41					
Reach 1	960		Q25	4148.00	3.50	8.43	9.57	12.48	0.032073
16.45	266.37	72.19		1.42					
Reach 1	960		Q50	5290.00	3.50	9.09	10.43	13.86	0.031227
17.91	315.39	75.04		1.43					
Reach 1	960		Q500	7380.00	3.50	10.20	11.80	16.05	0.029537
19.97	401.20	79.79		1.44					
Reach 1	935		Q100	5910.00	2.00	11.75	9.85	13.32	0.005265
10.42	658.53	132.90		0.64					
Reach 1	935		Q1.1	1312.00	2.00	7.07	5.89	7.56	0.004779
5.67	238.94	73.24		0.53					
Reach 1	935		Q10	3850.00	2.00	9.85	8.32	11.06	0.005603
9.03	456.65	83.52		0.63					
Reach 1	935		Q25	4148.00	2.00	10.11	8.55	11.40	0.005706

```
9.35      478.34       87.07                0.64
  Reach 1       935          Q50         5290.00        2.00       11.27        9.42       12.74      0.005275
10.02      598.64      119.63                0.63
  Reach 1       935          Q500        7380.00        2.00       12.97       11.03       14.57      0.004645
10.73      828.04      154.93                0.62


  Reach 1       895                      Bridge



  Reach 1       850          Q100        5910.00        1.00       11.15        9.23       12.78      0.004722
10.75      667.24      137.13                0.64
  Reach 1       850          Q1.1        1312.00        1.00        6.79        4.95        7.18      0.002673
5.11       270.29       70.27                0.43
  Reach 1       850          Q10         3850.00        1.00        9.32        7.59       10.54      0.004662
9.14       463.14       82.13                0.61
  Reach 1       850          Q25         4148.00        1.00        9.61        7.85       10.89      0.004678
9.41       487.00       83.49                0.62
  Reach 1       850          Q50         5290.00        1.00       10.56        8.76       12.19      0.005052
10.62      590.31      128.55                0.66
  Reach 1       850          Q500        7380.00        1.00       12.53       11.04       14.10      0.003944
10.84      851.33      153.61                0.60


  Reach 1       830          Q100        5910.00        1.00       11.26                   12.51      0.003074
9.22       746.99      159.08                0.58
  Reach 1       830          Q1.1        1312.00        1.00        6.70                    7.12      0.002997
5.17       254.49       77.51                0.50
  Reach 1       830          Q10         3850.00        1.00        9.32                   10.37      0.003637
8.30       491.66      104.94                0.60
  Reach 1       830          Q25         4148.00        1.00        9.62                   10.71      0.003539
8.47       524.11      108.28                0.60
  Reach 1       830          Q50         5290.00        1.00       10.68                   11.91      0.003296
9.08       657.87      145.20                0.59
  Reach 1       830          Q500        7380.00        1.00       12.65                   13.86      0.002508
9.28       978.53      170.35                0.54


  Reach 1       821          Q100        5910.00        1.00       11.34                   12.39      0.002923
8.30       780.65      173.08                0.55
  Reach 1       821          Q1.1        1312.00        1.00        6.67                    7.09      0.003368
5.23       250.98       79.98                0.52
  Reach 1       821          Q10         3850.00        1.00        9.35                   10.27      0.003920
7.69       503.51      110.73                0.61
  Reach 1       821          Q25         4148.00        1.00        9.66                   10.61      0.003709
7.79       539.36      118.31                0.60
  Reach 1       821          Q50         5290.00        1.00       10.75                   11.78      0.003187
8.18       685.57      152.72                0.57
```

Reach 1	821		Q500	7380.00	1.00	12.71		13.75	0.002344
8.38	1030.46	183.54		0.51					
Reach 1	820		Q100	5910.00	1.00	11.43		12.34	0.003087
7.69	803.42	172.37		0.55					
Reach 1	820		Q1.1	1312.00	1.00	6.66		7.09	0.003382
5.24	250.60	79.94		0.52					
Reach 1	820		Q10	3850.00	1.00	9.35		10.26	0.004412
7.66	502.77	110.47		0.63					
Reach 1	820		Q25	4148.00	1.00	9.68		10.59	0.004433
7.68	539.98	118.57		0.63					
Reach 1	820		Q50	5290.00	1.00	10.83		11.74	0.003558
7.69	703.59	154.57		0.58					
Reach 1	820		Q500	7380.00	1.00	12.85		13.69	0.002211
7.50	1166.68	280.88		0.49					
Reach 1	725		Q100	5910.00	2.50	10.98		12.00	0.003914
8.16	775.07	173.76		0.55					
Reach 1	725		Q1.1	1312.00	2.50	6.09		6.62	0.007271
5.84	224.72	88.79		0.65					
Reach 1	725		Q10	3850.00	2.50	8.76		9.76	0.006136
8.01	480.41	103.00		0.65					
Reach 1	725		Q25	4148.00	2.50	9.10		10.10	0.005767
8.05	515.09	107.21		0.64					
Reach 1	725		Q50	5290.00	2.50	10.32		11.35	0.004495
8.17	669.44	147.09		0.58					
Reach 1	725		Q500	7380.00	2.50	12.49		13.44	0.002895
8.03	1085.64	233.36		0.49					
Reach 1	575		Q100	5910.00	1.50	10.82		11.46	0.002176
6.47	970.39	205.77		0.42					
Reach 1	575		Q1.1	1312.00	1.50	4.94		5.46	0.008276
5.77	227.22	100.78		0.68					
Reach 1	575		Q10	3850.00	1.50	8.32		8.96	0.003593
6.43	598.70	119.70		0.51					
Reach 1	575		Q25	4148.00	1.50	8.71		9.35	0.003313
6.42	645.78	122.16		0.49					
Reach 1	575		Q50	5290.00	1.50	10.10		10.75	0.002487
6.46	838.34	163.32		0.44					
Reach 1	575		Q500	7380.00	1.50	12.41		13.01	0.001633
6.39	1361.35	268.56		0.38					
Reach 1	425		Q100	5910.00	0.00	10.51		11.16	0.001827
6.49	979.22	227.41		0.39					
Reach 1	425		Q1.1	1312.00	0.00	4.53		4.80	0.002240

4.14	317.19	86.31		0.38					
Reach 1	425		Q10	3850.00	0.00	7.94		8.51	0.002357
6.06	635.59	100.06		0.42					
Reach 1	425		Q25	4148.00	0.00	8.34		8.93	0.002277
6.14	676.02	101.58		0.42					
Reach 1	425		Q50	5290.00	0.00	9.77		10.41	0.002010
6.41	837.36	138.26		0.40					
Reach 1	425		Q500	7380.00	0.00	12.18		12.79	0.001414
6.42	1401.34	260.97		0.35					
Reach 1	335		Q100	5910.00	-2.00	9.90		10.92	0.002776
8.11	744.20	116.89		0.48					
Reach 1	335		Q1.1	1312.00	-2.00	4.33		4.62	0.001816
4.31	304.64	65.80		0.35					
Reach 1	335		Q10	3850.00	-2.00	7.40		8.24	0.003238
7.34	524.70	77.53		0.50					
Reach 1	335		Q25	4148.00	-2.00	7.79		8.66	0.003200
7.47	555.18	79.01		0.50					
Reach 1	335		Q50	5290.00	-2.00	9.18		10.16	0.002961
7.92	669.58	90.38		0.49					
Reach 1	335		Q500	7380.00	-2.00	11.57		12.59	0.002277
8.24	1072.73	248.32		0.45					
Reach 1	262		Q100	5910.00	-3.00	8.83		10.57	0.005707
10.58	558.57	71.13		0.67					
Reach 1	262		Q1.1	1312.00	-3.00	4.07		4.46	0.002317
5.00	262.15	53.25		0.40					
Reach 1	262		Q10	3850.00	-3.00	6.38		7.85	0.006318
9.74	395.14	62.03		0.68					
Reach 1	262		Q25	4148.00	-3.00	6.74		8.27	0.006278
9.92	417.99	63.44		0.68					
Reach 1	262		Q50	5290.00	-3.00	8.10		9.79	0.005954
10.42	507.69	68.47		0.67					
Reach 1	262		Q500	7380.00	-3.00	10.41		12.27	0.004923
10.93	690.11	108.39		0.63					
Reach 1	187		Q100	5910.00	-4.00	8.44	5.94	10.14	0.005330
10.46	564.77	68.82		0.64					
Reach 1	187		Q1.1	1312.00	-4.00	3.97	0.60	4.29	0.001678
4.51	290.86	53.75		0.34					
Reach 1	187		Q10	3850.00	-4.00	5.98	3.99	7.38	0.005662
9.49	405.67	60.50		0.65					
Reach 1	187		Q25	4148.00	-4.00	6.34	4.29	7.80	0.005671
9.70	427.69	61.71		0.65					
Reach 1	187		Q50	5290.00	-4.00	7.71	5.39	9.35	0.005505
10.27	515.03	66.29		0.65					

Reach 1	187		Q500	7380.00	-4.00	10.07	7.13	11.90	0.004763
10.85	682.36	79.14		0.62					
Reach 1	166		Bridge						
Reach 1	137		Q100	5910.00	-4.00	7.97	5.85	9.84	0.006060
10.95	539.62	67.73		0.68					
Reach 1	137		Q1.1	1312.00	-4.00	3.89	0.51	4.20	0.001678
4.51	291.15	53.87		0.34					
Reach 1	137		Q10	3850.00	-4.00	5.45	3.89	7.05	0.006854
10.15	379.31	59.16		0.71					
Reach 1	137		Q25	4148.00	-4.00	5.80	4.20	7.47	0.006824
10.35	400.69	60.37		0.71					
Reach 1	137		Q50	5290.00	-4.00	7.20	5.30	9.02	0.006396
10.83	488.44	65.11		0.70					
Reach 1	137		Q500	7380.00	-4.00	9.68	7.04	11.63	0.005108
11.21	660.26	73.78		0.64					
Reach 1	98.5		Bridge						
Reach 1	60		Q100	5910.00	-5.00	7.40	4.37	9.20	0.003918
10.88	564.72	62.75		0.59					
Reach 1	60		Q1.1	1312.00	-5.00	3.84	-0.83	4.05	0.000765
3.67	365.74	56.40		0.24					
Reach 1	60		Q10	3850.00	-5.00	4.72	2.44	6.13	0.004447
9.56	414.64	57.85		0.60					
Reach 1	60		Q25	4148.00	-5.00	5.03	2.74	6.53	0.004540
9.91	431.86	58.35		0.61					
Reach 1	60		Q50	5290.00	-5.00	6.60	3.80	8.30	0.004093
10.56	519.88	60.95		0.59					
Reach 1	60		Q500	7380.00	-5.00	9.16	5.55	11.21	0.003631
11.60	663.58	65.97		0.58					
Reach 1	38		Q100	5910.00	-4.50	6.79		8.98	0.005186
11.95	514.38	58.84		0.66					
Reach 1	38		Q1.1	1312.00	-4.50	3.81		4.03	0.000834
3.80	348.57	52.22		0.25					
Reach 1	38		Q10	3850.00	-4.50	4.17		5.91	0.006073
10.59	367.87	53.04		0.68					
Reach 1	38		Q25	4148.00	-4.50	4.40		6.30	0.006369
11.07	380.12	53.55		0.70					
Reach 1	38		Q50	5290.00	-4.50	5.99		8.08	0.005518

11.66	467.59	57.05		0.67					
Reach 1	38		Q500	7380.00	-4.50	8.63		11.01	0.004557
12.51	626.13	62.91		0.64					
Reach 1	0		Q100	5910.00	-6.30	4.24	4.24	8.48	0.013662
16.53	360.07	44.32		1.00					
Reach 1	0		Q1.1	1312.00	-6.30	3.76		4.00	0.000817
3.89	338.97	43.85		0.24					
Reach 1	0		Q10	3850.00	-6.30	3.33		5.59	0.008479
12.07	319.95	43.41		0.77					
Reach 1	0		Q25	4148.00	-6.30	3.19	2.45	5.91	0.010473
13.25	313.88	43.27		0.86					
Reach 1	0		Q50	5290.00	-6.30	3.62	3.62	7.58	0.014135
15.97	332.50	43.70		1.00					
Reach 1	0		Q500	7380.00	-6.30	5.62	5.62	10.49	0.012870
17.73	422.22	45.70		0.99					
Reach 1	-21		Q100	5910.00	-7.00	1.82	3.29	7.91	0.024570
19.83	302.26	45.71		1.34					
Reach 1	-21		Q1.1	1312.00	-7.00	3.79		3.97	0.000546
3.40	393.69	47.38		0.20					
Reach 1	-21		Q10	3850.00	-7.00	3.67		5.25	0.004917
10.13	387.87	47.28		0.61					
Reach 1	-21		Q25	4148.00	-7.00	3.63		5.49	0.005774
10.96	386.36	47.25		0.66					
Reach 1	-21		Q50	5290.00	-7.00	1.32	2.71	7.01	0.025006
19.16	279.48	45.28		1.34					
Reach 1	-21		Q500	7380.00	-7.00	2.94	4.65	9.92	0.023784
21.24	353.85	46.66		1.34					
Reach 1	-54		Q100	5910.00	-7.00	1.85	3.09	6.72	0.025698
17.70	333.87	61.41		1.34					
Reach 1	-54		Q1.1	1312.00	-7.00	3.81		3.93	0.000478
2.86	464.80	72.34		0.19					
Reach 1	-54		Q10	3850.00	-7.00	3.88		4.95	0.003975
8.29	470.37	72.77		0.55					
Reach 1	-54		Q25	4148.00	-7.00	3.90		5.13	0.004581
8.91	471.58	72.87		0.59					
Reach 1	-54		Q50	5290.00	-7.00	4.04	2.59	5.96	0.007001
11.13	482.04	73.49		0.73					
Reach 1	-54		Q500	7380.00	-7.00	2.18	4.20	8.92	0.033780
20.84	354.12	63.23		1.54					
Reach 1	-88		Q100	5910.00	-6.00	3.67	3.18	6.18	0.010956
12.71	465.10	75.49		0.90					

Reach 1	-88		Q1.1	1312.00	-6.00	3.80		3.92	0.000512
2.77	474.41	76.18		0.20					
Reach 1	-88		Q10	3850.00	-6.00	3.76		4.80	0.004468
8.16	471.96	76.00		0.58					
Reach 1	-88		Q25	4148.00	-6.00	3.76		4.96	0.005206
8.80	471.34	75.96		0.62					
Reach 1	-88		Q50	5290.00	-6.00	3.71		5.70	0.008637
11.31	467.88	75.70		0.80					
Reach 1	-88		Q500	7380.00	-6.00	4.25	4.25	7.51	0.013360
14.49	509.28	78.71		1.00					
Reach 1	-143		Q100	5910.00	-7.00	3.80	1.75	5.53	0.005536
10.57	566.27	73.60		0.67					
Reach 1	-143		Q1.1	1312.00	-7.00	3.80	-2.96	3.89	0.000273
2.35	566.27	73.60		0.15					
Reach 1	-143		Q10	3850.00	-7.00	3.80	0.05	4.53	0.002349
6.88	566.27	73.60		0.44					
Reach 1	-143		Q25	4148.00	-7.00	3.80	0.32	4.65	0.002727
7.42	566.27	73.60		0.47					
Reach 1	-143		Q50	5290.00	-7.00	3.80	1.29	5.19	0.004435
9.46	566.27	73.60		0.60					
Reach 1	-143		Q500	7380.00	-7.00	3.80	2.81	6.50	0.008632
13.20	566.27	73.60		0.83					

Profile Output Table - Six XS Bridge

Reach	River Sta	Profile	E.G. Elev	W.S. Elev	Crit W.S.	Frctn Loss	C & E Loss	Top Width
Q Left	Q Channel Q Right	Vel Chnl	(ft)	(ft)	(ft)	(ft)	(ft)	(ft)
(cfs)	(cfs) (cfs)	(ft/s)						
Reach 1	960	Q100	14.55	9.43	10.91	1.97	0.20	76.49
168.11	5560.68 181.20	18.60						
Reach 1	960	Q1.1	8.04	6.44	6.75	2.21	0.02	63.66
8.13	1295.11 8.76	10.21						
Reach 1	960	Q10	12.10	8.24	9.32	2.09	0.13	71.40
74.85	3694.47 80.68	16.02						
Reach 1	960	Q25	12.48	8.43	9.57	2.07	0.14	72.19
86.43	3968.41 93.16	16.45						
Reach 1	960	Q50	13.86	9.09	10.43	2.00	0.18	75.04
136.92	5005.50 147.58	17.91						
Reach 1	960	Q500	16.05	10.20	11.80	1.90	0.23	79.79
252.32	6855.72 271.96	19.97						

Reach 1	935		Q100	13.32	11.75	9.85	0.06	0.02	132.90
174.05	5450.01	285.95	10.42						
Reach 1	935		Q1.1	7.56	7.07	5.89	0.05	0.01	73.24
7.13	1281.35	23.52	5.67						
Reach 1	935		Q10	11.06	9.85	8.32	0.06	0.02	83.52
74.51	3633.66	141.83	9.03						
Reach 1	935		Q25	11.40	10.11	8.55	0.06	0.01	87.07
86.27	3917.98	143.75	9.35						
Reach 1	935		Q50	12.74	11.27	9.42	0.06	0.02	119.63
143.42	4940.89	205.69	10.02						
Reach 1	935		Q500	14.57	12.97	11.03	0.05	0.03	154.93
255.06	6451.11	673.83	10.73						
Reach 1	895	BR U	Q100	13.24	11.59	9.85	0.30	0.07	126.63
169.38	5469.50	271.13	10.66						
Reach 1	895	BR U	Q1.1	7.50	6.98	5.89	0.22	0.07	72.90
6.61	1282.69	22.70	5.83						
Reach 1	895	BR U	Q10	10.97	9.70	8.32	0.32	0.05	82.96
71.43	3640.61	137.96	9.26						
Reach 1	895	BR U	Q25	11.33	9.99	8.55	0.32	0.05	84.05
83.38	3907.93	156.68	9.50						
Reach 1	895	BR U	Q50	12.65	11.10	9.42	0.31	0.05	114.91
138.86	4959.52	191.62	10.29						
Reach 1	895	BR U	Q500	14.49	12.79	11.03	0.27	0.07	128.71
249.68	6504.94	625.38	11.04						
Reach 1	895	BR D	Q100	12.86	11.35	9.23	0.05	0.04	125.59
147.25	5241.63	521.12	10.39						
Reach 1	895	BR D	Q1.1	7.21	6.83	4.95	0.03	0.00	70.46
4.13	1261.95	45.92	5.06						
Reach 1	895	BR D	Q10	10.60	9.43	7.59	0.05	0.01	82.66
57.11	3554.04	238.85	8.97						
Reach 1	895	BR D	Q25	10.96	9.72	7.85	0.05	0.01	84.03
67.82	3810.81	269.37	9.24						
Reach 1	895	BR D	Q50	12.30	10.84	8.76	0.06	0.05	124.62
119.05	4808.65	362.30	10.12						
Reach 1	895	BR D	Q500	14.15	12.58	10.97	0.05	0.00	127.89
224.95	6197.70	957.35	10.81						
Reach 1	850		Q100	12.78	11.15	9.23	0.08	0.19	137.13
141.84	5300.11	468.05	10.75						
Reach 1	850		Q1.1	7.18	6.79	4.95	0.06	0.01	70.27
3.95	1262.69	45.35	5.11						
Reach 1	850		Q10	10.54	9.32	7.59	0.08	0.08	82.13
54.88	3560.63	234.50	9.14						

Reach 1	850		Q25	10.89	9.61	7.85	0.08	0.10	83.49
65.31	3818.08	264.60	9.41						
Reach 1	850		Q50	12.19	10.56	8.76	0.08	0.20	128.55
112.29	4883.80	293.91	10.62						
Reach 1	850		Q500	14.10	12.53	11.04	0.06	0.18	153.61
222.51	6183.78	973.71	10.84						
Reach 1	830		Q100	12.51	11.26		0.03	0.10	159.08
126.11	5558.21	225.68	9.22						
Reach 1	830		Q1.1	7.12	6.70		0.03	0.00	77.51
0.58	1311.42		5.17						
Reach 1	830		Q10	10.37	9.32		0.03	0.07	104.94
40.09	3767.73	42.18	8.30						
Reach 1	830		Q25	10.71	9.62		0.03	0.07	108.28
49.98	4040.21	57.81	8.47						
Reach 1	830		Q50	11.91	10.68		0.03	0.10	145.20
95.53	5063.76	130.71	9.08						
Reach 1	830		Q500	13.86	12.65		0.02	0.08	170.35
212.46	6578.08	589.46	9.28						
Reach 1	262		Q100	10.57	8.83		0.41	0.01	71.13
	5910.00		10.58						
Reach 1	262		Q1.1	4.46	4.07		0.15	0.02	53.25
	1312.00		5.00						
Reach 1	262		Q10	7.85	6.38		0.45	0.02	62.03
	3850.00		9.74						
Reach 1	262		Q25	8.27	6.74		0.45	0.02	63.44
	4148.00		9.92						
Reach 1	262		Q50	9.79	8.10		0.43	0.01	68.47
	5290.00		10.42						
Reach 1	262		Q500	12.27	10.41		0.36	0.01	108.39
1.31	7364.13	14.57	10.93						
Reach 1	187		Q100	10.14	8.44	5.94	0.12	0.01	68.82
	5910.00		10.46						
Reach 1	187		Q1.1	4.29	3.97	0.60	0.04	0.00	53.75
	1312.00		4.51						
Reach 1	187		Q10	7.38	5.98	3.99	0.13	0.01	60.50
	3850.00		9.49						
Reach 1	187		Q25	7.80	6.34	4.29	0.13	0.01	61.71
	4148.00		9.70						
Reach 1	187		Q50	9.35	7.71	5.39	0.12	0.01	66.29
	5290.00		10.27						
Reach 1	187		Q500	11.90	10.07	7.13	0.10	0.01	79.14

0.51	7378.29	1.19	10.85						
Reach 1	166	BR U	Q100	10.02	8.22	5.94	0.08	0.00	68.05
	5910.00		10.75						
Reach 1	166	BR U	Q1.1	4.25	3.93	0.59	0.02	0.00	53.61
	1312.00		4.54						
Reach 1	166	BR U	Q10	7.25	5.74	3.98	0.09	0.00	59.69
	3850.00		9.84						
Reach 1	166	BR U	Q25	7.67	6.10	4.29	0.09	0.00	60.89
	4148.00		10.05						
Reach 1	166	BR U	Q50	9.21	7.47	5.40	0.08	0.00	65.51
	5290.00		10.59						
Reach 1	166	BR U	Q500	11.78	9.88	7.13	0.07	0.00	74.14
0.28	7379.46	0.26	11.07						
Reach 1	166	BR D	Q100	9.93	8.15	5.85	0.09	0.01	68.32
	5910.00		10.71						
Reach 1	166	BR D	Q1.1	4.23	3.91	0.50	0.02	0.00	53.96
	1312.00		4.48						
Reach 1	166	BR D	Q10	7.15	5.65	3.90	0.10	0.01	59.86
	3850.00		9.83						
Reach 1	166	BR D	Q25	7.58	6.01	4.20	0.10	0.01	61.08
	4148.00		10.03						
Reach 1	166	BR D	Q50	9.13	7.40	5.30	0.09	0.01	65.77
	5290.00		10.56						
Reach 1	166	BR D	Q500	11.71	9.82	7.04	0.07	0.01	73.66
2.44	7376.99	0.57	11.05						
Reach 1	137		Q100	9.84	7.97	5.85	0.14	0.06	67.73
	5910.00		10.95						
Reach 1	137		Q1.1	4.20	3.89	0.51	0.04	0.00	53.87
	1312.00		4.51						
Reach 1	137		Q10	7.05	5.45	3.89	0.17	0.12	59.16
	3850.00		10.15						
Reach 1	137		Q25	7.47	5.80	4.20	0.17	0.12	60.37
	4148.00		10.35						
Reach 1	137		Q50	9.02	7.20	5.30	0.15	0.08	65.11
	5290.00		10.83						
Reach 1	137		Q500	11.63	9.68	7.04	0.12	0.04	73.78
1.94	7377.72	0.34	11.21						
Reach 1	98.5	BR U	Q100	9.62	7.55	5.85	0.19	0.16	66.28
	5910.00		11.57						
Reach 1	98.5	BR U	Q1.1	4.16	3.84	0.50	0.04	0.06	53.72
	1312.00		4.54						

Reach 1	98.5	BR U	Q10	6.76	4.77	3.90	0.23	0.32	56.86
	3850.00		11.32						
Reach 1	98.5	BR U	Q25	7.17	5.09	4.20	0.23	0.31	57.95
	4148.00		11.57						
Reach 1	98.5	BR U	Q50	8.79	6.71	5.30	0.20	0.21	63.44
	5290.00		11.58						
Reach 1	98.5	BR U	Q500	11.48	9.40	7.04	0.17	0.03	71.43
1.11	7378.89		11.56						
Reach 1	98.5	BR D	Q100	9.28	7.51	4.37	0.07	0.01	63.06
	5779.31	130.69	10.76						
Reach 1	98.5	BR D	Q1.1	4.07	3.86	-0.83	0.01	0.00	56.42
	1302.35	9.65	3.66						
Reach 1	98.5	BR D	Q10	6.21	4.86	2.44	0.07	0.01	58.07
	3805.25	44.75	9.40						
Reach 1	98.5	BR D	Q25	6.63	5.17	2.74	0.07	0.02	58.59
	4093.89	54.11	9.73						
Reach 1	98.5	BR D	Q50	8.38	6.72	3.80	0.07	0.01	61.15
	5187.74	102.26	10.43						
Reach 1	98.5	BR D	Q500	11.27	9.27	5.55	0.06	0.01	65.27
	7178.29	201.71	11.50						
Reach 1	60		Q100	9.20	7.40	4.37	0.10	0.12	62.75
	5781.54	128.46	10.88						
Reach 1	60		Q1.1	4.05	3.84	-0.83	0.02	0.00	56.40
	1302.41	9.59	3.67						
Reach 1	60		Q10	6.13	4.72	2.44	0.11	0.10	57.85
	3807.71	42.29	9.56						
Reach 1	60		Q25	6.53	5.03	2.74	0.12	0.12	58.35
	4096.59	51.41	9.91						
Reach 1	60		Q50	8.30	6.60	3.80	0.10	0.12	60.95
	5190.07	99.93	10.56						
Reach 1	60		Q500	11.21	9.16	5.55	0.09	0.10	65.97
	7180.31	199.69	11.60						
Reach 1	38		Q100	8.98	6.79		0.30	0.20	58.84
0.03	5839.64	70.33	11.95						
Reach 1	38		Q1.1	4.03	3.81		0.03	0.00	52.22
0.00	1309.91	2.09	3.80						
Reach 1	38		Q10	5.91	4.17		0.27	0.05	53.04
0.01	3840.75	9.24	10.59						
Reach 1	38		Q25	6.30	4.40		0.31	0.08	53.55
0.01	4135.62	12.37	11.07						
Reach 1	38		Q50	8.08	5.99		0.32	0.19	57.05
0.02	5245.62	44.36	11.66						
Reach 1	38		Q500	11.01	8.63		0.27	0.25	62.91

0.04	7223.42	156.53	12.51