# CHILD SAFETY SEAT

BUCKLE

AM PRECIOUS CARGO





- Belt path for base installation
- Refer to owner's manual



 Rear-facing infant car seats and convertible car seats used as rear-facing offer the same protection





• Tightly rolled blankets can give more support



#### **Rear Facing Convertible Install**

- Belt path
- Harness clip
- Harness height: at or below the child's shoulders



- Recline adjustment
- Adjuster foot











## Multiple harness loops for rethreading



- Attach the harness back to the splitter plate
- Use infant position; until harness needs to be lengthened to allow for growing children needing a longer harness







• Position on the vehicle seat for proper recline angle







• Push top of car seat into the back of the vehicle seat while pulling up on the shoulder portion of the belt



• Apply pressure where the child's bottom would be



• Changing to forward-facing moving the recline stand



 When forward-facing, adjust harness at or above child's shoulders















• Press the adjuster's release button to lengthen the tether strap and route the tether hook according to manufacturer's instructions



- Once the tether strap length is adjusted, attach to tether anchor point
- Pull the end of the strap to tighten and to remove any slack



### Loosen harness



- Place the child into restraint
- Adjust harness strap over shoulders
- Insert buckle tongues into crotch buckle









• Connect the chest clip at armpit level, then check for harness fit and tighten to remove slack



• Once the child's shoulders are above the top harness slots, they have outgrown the harness



## • Fitting the booster seat properly







• Press tab to release back of booster to use just the backless booster seat portion



• Use the shoulder belt guide for proper seat belt fit







#### For more information:

Please contact the Maine Bureau of Highway Safety 207-626-3840. www.maine.gov/dps/bhs/