



Client:	Haley & Aldrich, Inc.
Project Name:	Souadabscook East; Bridge Nos. 1431 and 5949
Project Location:	Hampden, Maine
GTX #:	309948
Test Date:	06/21/19
Tested By:	PK
Checked By:	emm

pH by AASHTO T 289

Boring ID	Sample ID	Depth, ft	Description	pH
BB-HSS-113/214	7D/4D	12.5-14.5 & 10-12	Moist, olive gray silt	6.39



Client:	Haley & Aldrich, Inc.
Project Name:	Souadabscook East; Bridge Nos. 1431 and 5949
Project Location:	Hampden, Maine
GTX #:	309948
Test Date:	06/24/19
Tested By:	PK
Checked By:	emm

<h2>Minimum Laboratory Soil Resistivity by AASHTO T 288</h2>
--

Boring ID	Sample ID	Depth, ft	Sample Description	Minimum Soil Resistivity, ohm-cm
BB-HSS-113/214	7D/4D	12.5-14.5 & 10-12 ft	Moist, olive gray silt	1,240

Comments: Test Equipment: Nilsson Model 400 Soil Resistance Meter, MC Miller Soil Box
Test conducted in standard laboratory atmosphere: 68-73 F



|||||
GEOTESTING EXPRESS INCORPORATED
125 NAGOG PARK
ACTON MA 01720-3451
USA

Analysis No. TS-A1908034
Report Date 26 June 2019
Date Sampled 19 June 2019
Date Received 24 June 2019
Where Sampled Acton, MA USA
Sampled By Client

This is to attest that we have examined: Soil for Project Name: Souadabscook East Bridge Nos. 1431 & 5949; Site Location: Hampden, ME; Job Number: GTX-309948

When examined to the applicable requirements of:

- AASHTO T-291-13 "Standard Method of Test for Determining Water-Soluble Chloride Ion Content in Soil" Method B
- AASHTO T-290-16 "Standard Method of Test for Determining Water-Soluble Sulfate Ion Content in Soil"

Results:

AASHTO T-291 – Chloride Method B

Sample		Results		Detection Limit
		ppm (mg/kg)	% ¹	
BB-HSS-113/214		42.	0.0042	10.
7D/4D	12.5-14.5' & 10-12'			

NOTE: ¹Percent by weight after drying.

AASHTO T-290 - Sulfate (soluble)

Sample		Results		Detection Limit
		ppm (mg/kg)	% ¹	
BB-HSS-113/214		14.	0.0014	10.
7D/4D	12.5-14.5' & 10-12'			

NOTE: ¹Percent by weight after drying.

END OF ANALYSIS

USEPA Laboratory ID UT00930

Merrill Gee P.E. – Engineer in Charge

© 2019 by Testing Engineers International, Inc. This certificate may not be reproduced except in full, without the expressed written consent of TEI-Testing Services, LLC. Note: The values in this certificate are the values obtained under standard test conditions as reported in the appropriate Report of Test and thus may be used for purposes of demonstrating compliance or for comparison with other units tested under the same standard. The results do not indicate the function of the sample(s) under nonstandard or field conditions. This certificate gives the characteristics of the sample(s) submitted for testing only. It does not and may not be used to certify the characteristics of the product, nor to imply that the product in general meets the requirements of any standard, nor its acceptability in the marketplace. TEI-Testing Services is a wholly owned LLC of Testing Engineers International, Inc.



Client:	Haley & Aldrich, Inc.
Project Name:	Souadabscook West; Bridge Nos.1433 and 5951
Project Location:	Hampden, Maine
GTX #:	309948
Test Date:	06/21/19
Tested By:	PK
Checked By:	emm

pH by AASHTO T 289

Boring ID	Sample ID	Depth, ft	Description	pH
201/203/204	3D/4D/4DA	4-7.5-7.8	Moist, dark gray silt	5.58



Client:	Haley & Aldrich, Inc.
Project Name:	Souadabscook West; Bridge Nos.1433 and 5951
Project Location:	Hampden, Maine
GTX #:	309946
Test Date:	06/24/19
Tested By:	PK
Checked By:	emm

**Minimum Laboratory Soil Resistivity
by AASHTO T 288**

Boring ID	Sample ID	Depth, ft	Sample Description	Minimum Soil Resistivity, ohm-cm
201/203/204	3D/4D/4DA	4-7.5 & 7.8-8	Moist, dark gray silt	1,240

Comments: Test Equipment: Nilsson Model 400 Soil Resistance Meter, MC Miller Soil Box
Test conducted in standard laboratory atmosphere: 68-73 F

